SPANDEK®

Minimum recommended roof pitch = 3° (1 in 20)

FINISH
ZINCALUME® steel
COLORBOND® steel
COLORBOND® Ultra steel
COLORBOND® steel Matt
COLORBOND® Metallic steel Corstrip
COLORBOND® steel Hi Gloss 80%
COLORBOND® steel Double Sided Hi Gloss
COLORBOND® steel Double Sided
COLORBOND® COOLMAX® steel
ZINCALUME® steel
COLORBOND® steel
COLORBOND® Ultra steel
COLORBOND® steel Matt
COLORBOND® COOLMAX® steel

To convert price to **lineal metres multiply** by 0.700

Maximum length = 27,900mm, Minimum Rollformed length = 500mm

SPANDEK® FASTENERS

	APPLICATION
	Steel battens up to 1.0mm BMT
	Steel purlins 1.2mm up to 1.9mm BMT
	Timber – Softwood
	Timber – Hardwood

SPANDEK® ROOF INFILL STRIPS

	PRODUCT
	SPANDEK® top
	SPANDEK® bottom

SPANDEK® TRANSLUCENT SHEETING (FIBREGLASS)

	PRODUCT
	Fibreglass

Maximum length = 12,200mm, Minimum length = 900mm

TRANSLUCENT SHEETING ACCESSORIES

	PRODUCT
	Roofing Wire (2 x 300 x 150mm)
	Lapseal
	Weatherlok Washer (Fibreglass only)

SPANDEK® STANDARD FLASHINGS

	PRODUCT
	Ridge Capping
	Tile Flashing
	Apron Flashing
	Barge Capping
	Valley Gutter

Maximum length = 8000mm, Minimum length = 1000mm