TRIMDEK®

Minimum recommended roof pitch = 2° (1 in 30)

FINISH
ZINCALUME® steel
Galvanised Z450
COLORBOND® steel
COLORBOND® Metallic steel Corstrip
COLORBOND® steel Hi Gloss 80%
COLORBOND® Ultra steel
COLORBOND® steel Matt
COLORBOND® steel Double Sided Hi Gloss
COLORBOND® steel Double Sided
COLORBOND® COOLMAX® steel
ZINCALUME® steel
COLORBOND® steel
COLORBOND® Ultra steel
COLORBOND® steel Matt
COLORBOND® COOLMAX® steel

To convert price to **lineal metres multiply** by 0.762

Maximum length* = 30,000mm, Minimum Rollformed length* = 305mm

TRIMDEK® FASTENERS

	APPLICATION
	Steel battens up to 1.0mm BMT
	Steel purlins 1.2mm up to 1.9mm BMT
	Timber – Softwood
	Timber – Hardwood

TRIMDEK® ROOF INFILL STRIPS

	PRODUCT
(Bottom profile shown)	TRIMDEK® top
	TRIMDEK® bottom

TRIMDEK® TRANSLUCENT SHEETING

	PRODUCT
	Fibreglass

Maximum length = 12,200mm, Minimum length = 900mm - Notes: ,

TRIMDEK® POLYCARBONATE SHEETING

	DESCRIPTION
	TRIMDEK®

TRIMDEK® STANDARD FLASHINGS

	PRODUCT
	Ridge Capping
	Tile Flashing
	Apron Flashing
	Barge Capping
	Valley Gutter

Maximum length = 8000mm, Minimum length = 1000mm

TRANSLUCENT SHEETING ACCESSORIES

	PRODUCT	PROD. CODE
	Roofing Wire (2 x 300 x 150mm)	RW20300150
	Lapseal	TSLS25514W
	Weatherlok Washer (Fibreglass only)	TSWW32

TRIM-KLIP®

	FINISH
	TRIM-KLIP® Bracket
	TRIM-KLIP® Weather Strip 963mm
	End-Lap Packer 40mm x 10mm x 1470mm