QUAD GUTTER

Quad gutter is so adaptable because of its classic form. It can blend perfectly with older style colonial and cottage homes and is also used extensively in new home construction. It is available in a wide choice of sizes and can be optioned with slots to prevent overflow.



DIMENSIONS

Size (mm)	A	B	C
115^	61	115	90
115 Low Front*	49	113	72
125†	61	127	90
125*	64	125	70
125**	60	127	84
150†	79	138	76
175†	103	175	95

PRODUCT SPECIFICATIONS

Size (mm)	Tensile (MPa)	BMT (mm)	Type	Capacity (mm²)	Total Cross Sect. Area (mm²)
115^	G550	0.42	Standard	5621	6760
			Slotted	5057	6192
115 Low Front*	G550	0.42	Standard	4307	5429
125	G550	0.42	Standard*	6488	7833
			Slotted†	5592	6842
125**	G550	0.42	Standard	6697	7958
150†	G300	0.55	Standard	8685	10088
175†	G550	0.42	Standard	12213	13767

* Available in NSW. ** Available in SA, NT
† Available in QLD. ^ Available in NSW, VIC, SA, WA, NT.

NOTE: Calculation of effective cross sectional area 'Capacity' for each nominal size of eaves gutter is based on requirements of section 3.8 AS/NZS 2179.1:1994

ACCESSORIES

NOTE: Component availability is State specific, please check prior to ordering.

90˚ External and Internal Cast Angle

90˚ 2-Pce Ext. and Int. Cast Angle

135˚ 2-Pce Ext. and Int. Cast Angle

Manufactured Int. or Ext. Mitre

Int. Str-8-line Strap

External Bracket

GP Bracket

Full Return Stop End


Return Stop End

Concealed Bracket

Timber Fix Clip

Stop End

Spike Bracket

Overstrap

Overstrap Bracket