

# Spring Mini Project

## Spring Mini Project[A Glory]

아파트 관리 사무소 웹사이트

1. 정해진 회원만 접근 가능(요청, 접수, 처리 홈페이지)
2. 테이블(공지사항, 요청접수, 회원관리)

Free Bootstrap Admin Template - AdminLTE.IO

<https://adminlte.io/>

### ▼ DB 생성 & 환경설정

#### DB 생성

기본

옵션

인덱스 (1)

외래 키 (0)

제약 조건 확인 (0)

분할

CREATE 코드

ALTER 코드

이름:

glorynotice

코멘트:

열:

+

추가

×

제거

▲

위로

▼

아래로

#	이름	데이터 유형	길이/설정	부호 없...	NULL 허...	0으로...	기본값	코멘트	조합	표현식	가상
<div></div> 1	nid	INT	10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AUTO_INCRE...				
2	ntitle	VARCHAR	50	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	'0'		utf8mb4_0900_ai_ci		
3	ncontent	LONGTEXT		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	기본값 없음		utf8mb4_0900_ai_ci		
4	ncate	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	'0'		utf8mb4_0900_ai_ci		
5	nwriter	VARCHAR	50	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	'admin'		utf8mb4_0900_ai_ci		
6	ndate	TIMESTAMP		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	CURRENT_TIMEST...				

기본 옵션 인덱스 (1) 외래 키 (0) 제약 조건 확인 (0) 분할 CREATE 코드 ALTER 코드

이름: gloryboard

코멘트:

---

열: + 추가 ✖ 제거 ▲ 위로 ▼ 아래로

#	이름	데이터 유형	길이/설정	부호 없...	NULL 허...	0으로...	기본값	코멘트	조합	표현식	가상
1	bid	INT	10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AUTO_INCREMENT...				
2	bpid	VARCHAR	50	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0		utf8mb4_0900_ai_ci		
3	btitle	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
4	bcontent	LONGTEXT		<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
5	bcate	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
6	bstatus	INT	10	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1				
7	bwriter	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
8	bdate	TIMESTAMP		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	CURRENT_TIMESTAMP...				

기본 옵션 인덱스 (1) 외래 키 (0) 제약 조건 확인 (0) 분할 CREATE 코드 ALTER 코드

이름: glorymember

코멘트:

---

열: + 추가 ✖ 제거 ▲ 위로 ▼ 아래로

#	이름	데이터 유형	길이/설정	부호 없...	NULL 허...	0으로...	기본값	코멘트	조합	표현식	가상
1	mid	INT	10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AUTO_INCREMENT...				
2	enabled	TINYINT	3	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1				
3	username	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>			utf8mb4_0900_ai_ci		
4	password	VARCHAR	200	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
5	authority	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	ROLE_USER		utf8mb4_0900_ai_ci		
6	mname	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
7	memail	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
8	mtel	VARCHAR	50	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	NULL		utf8mb4_0900_ai_ci		
9	mdate	TIMESTAMP		<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	CURRENT_TIMESTAMP...				

```
CREATE TABLE `glorynotice` (
  `nid` INT(10) NOT NULL AUTO_INCREMENT,
  `ntitle` VARCHAR(50) NOT NULL DEFAULT '0' COLLATE 'utf8mb4_0900_ai_ci',
  `ncontent` LONGTEXT NOT NULL COLLATE 'utf8mb4_0900_ai_ci',
  `ncate` VARCHAR(50) NULL DEFAULT '0' COLLATE 'utf8mb4_0900_ai_ci',
  `nwriter` VARCHAR(50) NOT NULL DEFAULT 'admin' COLLATE 'utf8mb4_0900_ai_ci',
  `ndate` TIMESTAMP NOT NULL DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY (`nid`) USING BTREE
)
COLLATE='utf8mb4_0900_ai_ci'
ENGINE=InnoDB
AUTO_INCREMENT=3
;

CREATE TABLE `gloryboard` (
  `bid` INT(10) NOT NULL AUTO_INCREMENT,
  `bpid` VARCHAR(50) NOT NULL DEFAULT '0' COLLATE 'utf8mb4_0900_ai_ci',
  `btitle` VARCHAR(50) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
  `bcontent` LONGTEXT NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
  `bcate` VARCHAR(50) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
  `bstatus` INT(10) NULL DEFAULT '1',
  `bwriter` VARCHAR(50) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
  `bdate` TIMESTAMP NOT NULL DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY (`bid`) USING BTREE
)
COLLATE='utf8mb4_0900_ai_ci'
ENGINE=InnoDB
;


CREATE TABLE `glorymember` (
  `mid` INT(10) NOT NULL AUTO_INCREMENT,
  `enabled` TINYINT(3) NULL DEFAULT '1',
  `username` VARCHAR(50) NULL DEFAULT '' COLLATE 'utf8mb4_0900_ai_ci',
  `password` VARCHAR(200) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
```

```

`authority` VARCHAR(50) NULL DEFAULT 'ROLE_USER' COLLATE 'utf8mb4_0900_ai_ci',
`mname` VARCHAR(50) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
`memail` VARCHAR(50) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
`mtel` VARCHAR(50) NULL DEFAULT NULL COLLATE 'utf8mb4_0900_ai_ci',
`mdate` TIMESTAMP NULL DEFAULT CURRENT_TIMESTAMP,
PRIMARY KEY (`mid`) USING BTREE
)
COLLATE='utf8mb4_0900_ai_ci'
ENGINE=InnoDB
;

```

## 패키지 설정



## pom.xml 설정



```

        <groupId>org.springframework</groupId>
        <artifactId>spring-jdbc</artifactId>
        <version>5.3.19</version>
    </dependency>
    <!-- https://mvnrepository.com/artifact/org.apache.commons/commons-dbcp2 -->
    <dependency>
        <groupId>org.apache.commons</groupId>
        <artifactId>commons-dbcp2</artifactId>
        <version>2.7.0</version>
    </dependency>
    <!-- https://mvnrepository.com/artifact/org.bgee.log4jdbc-log4j2/log4jdbc-log4j2-jdbc4 -->
    <dependency>
        <groupId>org.bgee.log4jdbc-log4j2</groupId>
        <artifactId>log4jdbc-log4j2-jdbc4</artifactId>
        <version>1.16</version>
    </dependency>
    <!-- https://mvnrepository.com/artifact/mysql/mysql-connector-java -->
    <dependency>
        <groupId>mysql</groupId>
        <artifactId>mysql-connector-java</artifactId>
        <version>8.0.28</version>
    </dependency>

```

## servlet-context.xml 설정

```

<?xml version="1.0" encoding="UTF-8"?>
<beans:beans xmlns="http://www.springframework.org/schema/mvc"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:beans="http://www.springframework.org/schema/beans"
    xmlns:context="http://www.springframework.org/schema/context"
    xsi:schemaLocation="http://www.springframework.org/schema/mvc https://www.springframework.org/schema/mvc/spring-mvc.xsd
        http://www.springframework.org/schema/beans https://www.springframework.org/schema/beans/spring-beans.xsd
        http://www.springframework.org/schema/context https://www.springframework.org/schema/context/spring-context.xsd">

    <!-- DispatcherServlet Context: defines this servlet's request-processing infrastructure -->

    <!-- Enables the Spring MVC @Controller programming model -->
    <annotation-driven />

    <!-- Handles HTTP GET requests for /resources/** by efficiently serving up static resources in the ${webappRoot}/resources directory -->
    <resources mapping="/resources/**" location="/resources/" />

    <!-- Resolves views selected for rendering by @Controllers to .jsp resources in the /WEB-INF/views directory -->
    <beans:bean class="org.springframework.web.servlet.view.InternalResourceViewResolver">
        <beans:property name="prefix" value="/WEB-INF/views/" />
        <beans:property name="suffix" value=".jsp" />
    </beans:bean>

    <!-- 업로드 패스 설정 -->
    <beans:bean class="java.lang.String" id="uploadPath">
        <beans:constructor-arg
            value="C:\\develop\\JSP\\Glory\\src\\main\\webapp\\resources" /> <!-- 로컬에서 작업할 때 -->
    </beans:bean>

    <context:component-scan base-package="com.glory.*" />

</beans:beans>

```

## root-context.xml 설정

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.springframework.org/schema/beans https://www.springframework.org/schema/beans/spring-beans.xsd">

    <!-- Root Context: defines shared resources visible to all other web components -->

    <!-- mysql 연결 설정 -->
    <bean id="dataSource" class="org.apache.commons.dbcp2.BasicDataSource" destroy-method="close">
        <property name="driverClassName" value="com.mysql.cj.jdbc.Driver"/>
        <property name="url" value="jdbc:mysql://localhost:3306/difbfl4751?serverTimezone=UTC"/>
    </bean>

```

```

<property name="username" value="difbfl4751"/>
<property name="password" value="비밀번호"/>
</bean>

<bean id="sqlSessionFactory"
      class="org.mybatis.spring.SqlSessionFactoryBean">
  <property name="dataSource" ref="dataSource" />
  <property name="mapperLocations"
            value="classpath:/sqlmap/**/*.SQL.xml" />
</bean>
<bean id="sqlSessionTemplate"
      class="org.mybatis.spring.SqlSessionTemplate">
  <constructor-arg index="0" ref="sqlSessionFactory" />
</bean>

</beans>

```

## web.xml 설정

```

<?xml version="1.0" encoding="UTF-8"?>
<web-app version="2.5" xmlns="http://java.sun.com/xml/ns/javaee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">

  <!-- The definition of the Root Spring Container shared by all Servlets and Filters -->
  <context-param>
    <param-name>contextConfigLocation</param-name>
    <param-value>/WEB-INF/spring/root-context.xml</param-value>
  </context-param>

  <!-- Creates the Spring Container shared by all Servlets and Filters -->
  <listener>
    <listener-class>org.springframework.web.context.ContextLoaderListener</listener-class>
  </listener>

  <!-- Processes application requests -->
  <servlet>
    <servlet-name>appServlet</servlet-name>
    <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-class>
    <init-param>
      <param-name>contextConfigLocation</param-name>
      <param-value>/WEB-INF/spring/appServlet/servlet-context.xml</param-value>
    </init-param>
    <load-on-startup>1</load-on-startup>
  </servlet>

  <servlet-mapping>
    <servlet-name>appServlet</servlet-name>
    <url-pattern>/</url-pattern>
  </servlet-mapping>

  <filter>
    <filter-name>encodingFilter</filter-name>
    <filter-class>org.springframework.web.filter.CharacterEncodingFilter
  </filter-class>
    <init-param>
      <param-name>encoding</param-name>
      <param-value>UTF-8</param-value>
    </init-param>
  </filter>
  <filter-mapping>
    <filter-name>encodingFilter</filter-name>
    <url-pattern>/*</url-pattern>
  </filter-mapping>

  <filter>
    <filter-name>springSecurityFilterChain</filter-name>
    <filter-class>org.springframework.web.filter.DelegatingFilterProxy</filter-class>
  </filter>
  <filter-mapping>
    <filter-name>springSecurityFilterChain</filter-name>
    <url-pattern>/*</url-pattern>
  </filter-mapping>

  <filter>
    <filter-name>httpMethodFilter</filter-name>
    <filter-class>org.springframework.web.filter.HiddenHttpMethodFilter</filter-class>
  </filter>
  <filter-mapping>

```

```

        <filter-name>httpMethodFilter</filter-name>
        <servlet-name>appServlet</servlet-name>
    </filter-mapping>

    <error-page>
        <error-code>404</error-code>
        <location>/WEB-INF/views/error.jsp</location>
    </error-page>

</web-app>

```

## ▼ Board

### Board.java

```

package com.glory.board;

public class Board {

    private int bid, bstatus;

    private String bpid, btitle, bcontent, bcate, bwriter, bdate;

    public int getBid() {
        return bid;
    }

    public void setBid(int bid) {
        this.bid = bid;
    }

    public int getBstatus() {
        return bstatus;
    }

    public void setBstatus(int bstatus) {
        this.bstatus = bstatus;
    }

    public String getBpid() {
        return bpid;
    }

    public void setBpid(String bpid) {
        this.bpid = bpid;
    }

    public String getBtitle() {
        return btitle;
    }

    public void setBtitle(String btitle) {
        this.btitle = btitle;
    }

    public String getBcontent() {
        return bcontent;
    }

    public void setBcontent(String bcontent) {
        this.bcontent = bcontent;
    }

    public String getBcate() {
        return bcate;
    }

    public void setBcate(String bcate) {
        this.bcate = bcate;
    }

    public String getBwriter() {
        return bwriter;
    }

    public void setBwriter(String bwriter) {

```

```

        this.bwriter = bwriter;
    }

    public String getBdate() {
        return bdate;
    }

    public void setBdate(String bdate) {
        this.bdate = bdate;
    }

    public Board() {
    }

    public Board(int bid, int bstatus, String bpid, String btitle, String bcontent, String bcate, String bwriter,
        String bdate) {
        this.bid = bid;
        this.bstatus = bstatus;
        this.bpid = bpid;
        this.btitle = btitle;
        this.bcontent = bcontent;
        this.bcate = bcate;
        this.bwriter = bwriter;
        this.bdate = bdate;
    }
}
}

```

## board\_SQL.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org/DTD Mapper 3.0//EN" "http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="board">

    <insert id="insert"
        parameterType="com.glory.board.Board" useGeneratedKeys="true" keyProperty="bid">
        <![CDATA[
            INSERT INTO gloryboard
            (btitle, bcontent, bcate, bstatus, bwriter) VALUES (#{btitle}, #{bcontent}, #{bcate}, #{bstatus}, #{bwriter})
        ]]>
    </insert>

    <insert id="insert_reply"
        parameterType="hashMap" useGeneratedKeys="true" keyProperty="bid">
        <![CDATA[
            INSERT INTO gloryboard
            (bpid, bcontent, bwriter) VALUES (#{bid}, #{bcontent}, #{bwriter})
        ]]>
    </insert>

    <select id="select_detail" parameterType="String" resultType="com.glory.board.Board">
        <![CDATA[
            SELECT * FROM gloryboard WHERE bid = #{bid}
        ]]>
    </select>

    <select id="select_list" resultType="com.glory.board.Board">
        <![CDATA[
            SELECT * FROM gloryboard WHERE bpid IS NULL ORDER BY bid DESC
        ]]>
    </select>

    <select id="select_reply" resultType="com.glory.board.Board">
        <![CDATA[
            SELECT * FROM gloryboard WHERE bpid=#{bid} ORDER BY bid DESC
        ]]>
    </select>

    <!-- <update id="update_view" parameterType="hashMap"> -->
    <!-- <![CDATA[ -->
    <!-- UPDATE board SET bview = bview + 1 WHERE bid = #{bid} -->
    <!-- ]]> -->
    <!-- </update> -->

    <!-- <update id="update_like" parameterType="hashMap"> -->
    <!-- <![CDATA[ -->
    <!-- UPDATE board SET blike = blike + 1 WHERE bid = #{bid} -->
    <!-- ]]> -->

```

```

<!-- </update> -->

<!-- <update id="update_hate" parameterType="hashMap"> -->
<!-- <![CDATA[ -->
<!-- UPDATE board SET bhate = bhate + 1 WHERE bid = #{bid} -->
<!-- ]]> -->
<!-- </update> -->

</mapper>

```

## BoardRepository.java

```

package com.glory.board;

import java.util.List;
import java.util.Map;

public interface BoardRepository {

    void setNewBoard(Board board);

    List<Board> getAllBoardList();

    Board getBoardById(String bId);

    void replyNewBoard(Map<String, Object> map);

    List<Board> getReplyById(String bid);

}

```

## BoardRepositoryImpl.java

```

package com.glory.board;

import java.util.List;
import java.util.Map;

import org.mybatis.spring.SqlSessionTemplate;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Repository;

@Repository
public class BoardRepositoryImpl implements BoardRepository {

    @Autowired
    SqlSessionTemplate sqlSessionTemplate;

    @Override
    public List<Board> getAllBoardList() {
        return this.sqlSessionTemplate.selectList("board.select_list");
    }

    @Override
    public Board getBoardById(String bId) {
        return this.sqlSessionTemplate.selectOne("board.select_detail", bId);
    }

    @Override
    public void setNewBoard(Board board) {
        this.sqlSessionTemplate.insert("board.insert", board);
    }

    @Override
    public void replyNewBoard(Map<String, Object> map) {
        this.sqlSessionTemplate.insert("board.insert_reply", map);
    }

    @Override
    public List<Board> getReplyById(String bid) {
        return this.sqlSessionTemplate.selectList("board.select_reply", bid);
    }

}

```



```
}
```

### BoardService.java

```
package com.glory.board;

import java.util.List;
import java.util.Map;

public interface BoardService {

    void setNewBoard(Board board);

    List<Board> getAllBoardList();

    Board getBoardById(String bid);

    void replyNewBoard(Map<String, Object> map);

    List<Board> getReplyById(String bid);

}
```

### BoardServiceImpl.java

```
package com.glory.board;

import java.util.List;
import java.util.Map;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class BoardServiceImpl implements BoardService{

    @Autowired // DI 의존성 주입 IoC 제어의 역전
    private BoardRepository boardRepository;

    @Override
    public List<Board> getAllBoardList() {
        return boardRepository.getAllBoardList();
    }

    @Override
    public Board getBoardById(String bid) {

        Board boardById = boardRepository.getBoardById(bid);

        return boardById;
    }

    @Override
    public void setNewBoard(Board board) {
        boardRepository.setNewBoard(board);
    }

    @Override
    public void replyNewBoard(Map<String, Object> map) {
        boardRepository.replyNewBoard(map);
    }

    @Override
    public List<Board> getReplyById(String bid) {
        return boardRepository.getReplyById(bid);
    }

}
```

```

import java.util.Map;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class BoardServiceImpl implements BoardService{

    @Autowired    // DI 의존성 주입 IoC 제어의 역전
    private BoardRepository boardRepository;

    @Override
    public List<Board> getAllBoardList() {
        return boardRepository.getAllBoardList();
    }

    @Override
    public Board getBoardById(String bid) {

        Board boardById = boardRepository.getBoardById(bid);

        return boardById;
    }

    @Override
    public void setNewBoard(Board board) {
        boardRepository.setNewBoard(board);
    }

    @Override
    public void replyNewBoard(Map<String, Object> map) {
        boardRepository.replyNewBoard(map);
    }

    @Override
    public List<Board> getReplyById(String bid) {
        return boardRepository.getReplyById(bid);
    }

}

```

## BoardController.java

```

package com.glory.board;

import java.util.HashMap;
import java.util.List;
import java.util.Map;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestParam;
import org.springframework.web.bind.annotation.ResponseBody;

@Controller
@RequestMapping("/boards")
public class BoardController {

    // @Autowired
    // private MailService mailService;

    @Autowired    // DI
    private BoardService boardService;

    // @Autowired
    // private UserService userService;

    @GetMapping("/addBoard")
    public String requestAddBoardForm(@ModelAttribute("NewBoard") Board board) {
        return "boards/addBoard";
    }

    @PostMapping("/addBoard")

```

```

public String submitAddBoardForm(@ModelAttribute("NewBoard") Board board) {

    boardService.setNewBoard(board);

    //    User user = userService.existUsername(board.getBwriter());

    //    String to = user.getUemail();
    //    String subject = board.getBwriter() + "님의 게시물이 등록되었습니다.";
    //    String body = board.getBcontent();

    //    mailService.sendMail(to, subject, body);

    return "redirect:/boards/list";
}

@RequestMapping("/list")
public String BoardList(Model model) {
    List<Board> list = boardService.getAllBoardList();
    model.addAttribute("boardList", list);
    return "boards/list";
}

@GetMapping("/detail")
public String requestCarById(@RequestParam("id") String bid, Model model) {

    //view 데이터를 불러오기 전에 조회수 증가
    Map<String, Object> map = new HashMap<String, Object>();
    map.put("bid", bid);
    map.put("check", "bview");

    //주 게시물
    Board boardById = boardService.getBoardById(bid);
    model.addAttribute("board", boardById);

    //답변 게시물
    List<Board> list = boardService.getReplyById(bid);
    int cnt = list.size();
    model.addAttribute("replyList", list);
    model.addAttribute("cnt", cnt);

    return "boards/board";
}

@ResponseBody
@RequestMapping("/replyNew")
public void replyNew(@RequestParam Map<String, Object> map) {

    boardService.replyNewBoard(map);

    //    String boardWriter = (String) map.get("boardWriter");

    //    User user = userService.existUsername(boardWriter);

    //    String to = user.getUemail();
    //    String subject = (String) map.get("bwriter") + "님이 댓글을 등록하였습니다.";
    //    String body = (String) map.get("bcontent");

    //    mailService.sendMail(to, subject, body);

}
}

```

## addBoard.jsp

```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib uri="http://www.springframework.org/tags/form" prefix="form" %>
<!-- <%@ taglib uri="http://www.springframework.org/security/tags" prefix="sec" %> --%>

<head>
<title>게시판 등록</title>
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<meta charset="utf-8">

</head>

<!-- Google Font: Source Sans Pro -->
<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">

```

```

<!-- Font Awesome -->
<link rel="stylesheet" href="/resources/admin/plugins/fontawesome-free/css/all.min.css">
<!-- Theme style -->
<link rel="stylesheet" href="/resources/admin/dist/css/adminlte.min.css">
<body class="text-center">
<div class="container"><h1>게시판 등록</h1>

<fieldset>
  <form:form modelAttribute="NewBoard" action="/.addBoard?${_csrf.parameterName}=${_csrf.token}" class="form-horizontal" method="post">
    <!-- Main content -->
    <section class="content">
      <div class="row">
        <div class="col-md-6">
          <div class="card card-primary">
            <div class="card-header">
              <h3 class="card-title">General</h3>

            <form:input path="bwriter" type="hidden" value="admin" class="form-control" />

            <div class="card-tools">
              <button type="button" class="btn btn-tool" data-card-widget="collapse" title="Collapse">
                <i class="fas fa-minus"></i>
              </button>
            </div>
            <div class="card-body">
              <div class="form-group">
                <label for="inputName">제목</label>
                <form:input path="bttitle" class="form-control" />
              </div>
              <div class="form-group">
                <label for="inputDescription">내용</label>
                <form:textarea path="bcontent" class="form-control" rows="10"/>
              </div>
              <div class="form-group">
                <label for="inputStatus">유형</label>
                <form:select path="bcate" class="form-control custom-select">
                  <option selected disabled>선택하세요</option>
                  <option>버그처리</option>
                  <option>신규기능</option>
                  <option>기타</option>
                </form:select>
              </div>
            </div>
          </div>

          <div class="row">
            <div class="col-6">
              <a href="#" class="btn btn-secondary">취소</a>
              <input type="submit" value="등록" class="btn btn-success float-right">
            </div>
          </div>
        </div>

        <!-- /.card-body -->
      </div>
    <!-- /.card -->
  </div>
</div>
</section>
</form:form>
</fieldset>
</div>

<!-- jQuery -->
<script src="/resources/admin/plugins/jquery/jquery.min.js"></script>
<!-- Bootstrap 4 -->
<script src="/resources/admin/plugins/bootstrap/js/bootstrap.bundle.min.js"></script>
<!-- AdminLTE App -->
<script src="/resources/admin/dist/js/adminlte.min.js"></script>
<!-- AdminLTE for demo purposes -->
<!-- <script src="/resources/admin/dist/js/demo.js"></script> -->

</body>
</html>

```

list.jsp

```

<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Insert title here</title>

<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">

<link rel="stylesheet" href="/resources/admin/plugins/fontawesome-free/css/all.min.css">

<link rel="stylesheet" href="/resources/admin/plugins/datatables-bs4/css/dataTables.bootstrap4.min.css">
<link rel="stylesheet" href="/resources/admin/plugins/datatables-responsive/css/responsive.bootstrap4.min.css">
<link rel="stylesheet" href="/resources/admin/plugins/datatables-buttons/css/buttons.bootstrap4.min.css">

<link rel="stylesheet" href="/resources/admin/dist/css/adminlte.min.css?v=3.2.0">
<script nonce="ee5d093f-ace6-44b5-bf0b-1e27a02cb5bb">(function(w,d){!function(a,b,c,d){a[c]=a[c]||{};a[c].executed=[];a.zaraz={def

</head>
<body>

<div class="card">
<div class="card-header">
<h3 class="card-title">DataTable with default features</h3>
</div>

<div class="card-body">
<table id="example1" class="table table-bordered table-striped">
<thead>
<tr>
<th>Rendering engine</th>
<th>Browser</th>
<th>Platform(s)</th>
<th>Engine version</th>
<th>CSS grade</th>
</tr>
</thead>
<tbody>
<tr>
<td>Trident</td>
<td>Internet
Explorer 4.0
</td>
<td>Win 95+</td>
<td> 4</td>
<td>X</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 5.0
</td>
<td>Win 95+</td>
<td>5</td>
<td>C</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 5.5
</td>
<td>Win 95+</td>
<td>5.5</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 6
</td>
<td>Win 98+</td>
<td>6</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet Explorer 7</td>
<td>Win XP SP2+</td>
<td>7</td>
<td>A</td>
</tr>
<tr>

```

```

<td>Trident</td>
<td>AOL browser (AOL desktop)</td>
<td>Win XP</td>
<td>6</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 1.0</td>
<td>Win 98+ / OSX.2+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 1.5</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 2.0</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 3.0</td>
<td>Win 2k+ / OSX.3+</td>
<td>1.9</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Camino 1.0</td>
<td>OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Camino 1.5</td>
<td>OSX.3+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape 7.2</td>
<td>Win 95+ / Mac OS 8.6-9.2</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape Browser 8</td>
<td>Win 98SE+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape Navigator 9</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.0</td>
<td>Win 95+ / OSX.1+</td>
<td>1</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.1</td>
<td>Win 95+ / OSX.1+</td>
<td>1.1</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.2</td>
<td>Win 95+ / OSX.1+</td>

```

```

<td>1.2</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.3</td>
<td>Win 95+ / OSX.1+</td>
<td>1.3</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.4</td>
<td>Win 95+ / OSX.1+</td>
<td>1.4</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.5</td>
<td>Win 95+ / OSX.1+</td>
<td>1.5</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.6</td>
<td>Win 95+ / OSX.1+</td>
<td>1.6</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.7</td>
<td>Win 98+ / OSX.1+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.8</td>
<td>Win 98+ / OSX.1+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Seamonkey 1.1</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Epiphany 2.20</td>
<td>Gnome</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 1.2</td>
<td>OSX.3</td>
<td>125.5</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 1.3</td>
<td>OSX.3</td>
<td>312.8</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 2.0</td>
<td>OSX.4+</td>
<td>419.3</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 3.0</td>
<td>OSX.4+</td>
<td>522.1</td>
<td>A</td>
</tr>

```

```

<tr>
<td>Webkit</td>
<td>OmniWeb 5.5</td>
<td>OSX.4+</td>
<td>420</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>iPod Touch / iPhone</td>
<td>iPod</td>
<td>420.1</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>S60</td>
<td>S60</td>
<td>413</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 7.0</td>
<td>Win 95+ / OSX.1+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 7.5</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 8.0</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 8.5</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.0</td>
<td>Win 95+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.2</td>
<td>Win 88+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.5</td>
<td>Win 88+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera for Wii</td>
<td>Wii</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Nokia N800</td>
<td>N800</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Nintendo DS browser</td>

```



```

<td>Nintendo DS</td>
<td>8.5</td>
<td>C/A<sup>1</sup></td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.1</td>
<td>KDE 3.1</td>
<td>3.1</td>
<td>C</td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.3</td>
<td>KDE 3.3</td>
<td>3.3</td>
<td>A</td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.5</td>
<td>KDE 3.5</td>
<td>3.5</td>
<td>A</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 4.5</td>
<td>Mac OS 8-9</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 5.1</td>
<td>Mac OS 7.6-9</td>
<td>1</td>
<td>C</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 5.2</td>
<td>Mac OS 8-X</td>
<td>1</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>NetFront 3.1</td>
<td>Embedded devices</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>NetFront 3.4</td>
<td>Embedded devices</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Misc</td>
<td>Dillo 0.8</td>
<td>Embedded devices</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>Links</td>
<td>Text only</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>Lynx</td>
<td>Text only</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>IE Mobile</td>
<td>Windows Mobile 6</td>
<td>-</td>
<td>C</td>

```

```

</tr>
<tr>
<td>Misc</td>
<td>PSP browser</td>
<td>PSP</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Other browsers</td>
<td>All others</td>
<td>-</td>
<td>-</td>
<td>U</td>
</tr>
</tbody>
<tfoot>
<tr>
<th>Rendering engine</th>
<th>Browser</th>
<th>Platform(s)</th>
<th>Engine version</th>
<th>CSS grade</th>
</tr>
</tfoot>
</table>
</div>

</div>

<footer class="main-footer">
<div class="float-right d-none d-sm-block">
<b>Version</b> 3.2.0
</div>
<strong>Copyright &copy; 2014-2021 <a href="https://adminlte.io">AdminLTE.io</a>.</strong> All rights reserved.
</footer>

<aside class="control-sidebar control-sidebar-dark">

</aside>

</body>

<script src="/resources/admin/plugins/jquery/jquery.min.js"></script>

<script src="/resources/admin/plugins/bootstrap/js/bootstrap.bundle.min.js"></script>

<script src="/resources/admin/plugins/datatables/jquery.dataTables.min.js"></script>
<script src="/resources/admin/plugins/datatables-bs4/js/dataTables.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/datatables-responsive/js/dataTables.responsive.min.js"></script>
<script src="/resources/admin/plugins/datatables-responsive/js/responsive.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/dataTables.buttons.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/jszip/jszip.min.js"></script>
<script src="/resources/admin/plugins/pdfmake/pdfmake.min.js"></script>
<script src="/resources/admin/plugins/pdfmake/vfs_fonts.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.html5.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.print.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.colVis.min.js"></script>

<script src="/resources/admin/dist/js/adminlte.min.js?v=3.2.0"></script>

<!-- <script src="/resources/admin/dist/js/demo.js"></script> -->

<script>
$(function () {
  $("#example1").DataTable({
    "responsive": true, "lengthChange": false, "autoWidth": false,
    "buttons": ["copy", "csv", "excel", "pdf", "print", "colvis"]
  }).buttons().container().appendTo('#example1_wrapper .col-md-6:eq(0)');
  $('#example2').DataTable({
    "paging": true,
    "lengthChange": false,
    "searching": false,
    "ordering": true,
    "info": true,
    "autoWidth": false,
    "responsive": true,
  });
});
</script>

</html>

```

## ▼ Notice

### Notice.java

```
package com.glory.notice;

public class Notice {

    private int nid;

    private String ntitle, ncontent, ncate, nwriter, ndate;

    public int getNid() {
        return nid;
    }

    public void setNid(int nid) {
        this.nid = nid;
    }

    public String getNtitle() {
        return ntitle;
    }

    public void setNtitle(String ntitle) {
        this.ntitle = ntitle;
    }

    public String getNcontent() {
        return ncontent;
    }

    public void setNcontent(String ncontent) {
        this.ncontent = ncontent;
    }

    public String getNcate() {
        return ncate;
    }

    public void setNcate(String ncate) {
        this.ncate = ncate;
    }

    public String getNwriter() {
        return nwriter;
    }

    public void setNwriter(String nwriter) {
        this.nwriter = nwriter;
    }

    public String getNdate() {
        return ndate;
    }

    public void setNdate(String ndate) {
        this.ndate = ndate;
    }

    public Notice() {
    }

    public Notice(int nid, String ntitle, String ncontent, String ncate, String nwriter, String ndate) {
        this.nid = nid;
        this.ntitle = ntitle;
        this.ncontent = ncontent;
        this.ncate = ncate;
        this.nwriter = nwriter;
        this.ndate = ndate;
    }

}
```

## notice\_SQL.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org/DTD Mapper 3.0//EN" "http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="notice">

    <insert id="insert"
        parameterType="com.glory.notice.Notice" useGeneratedKeys="true" keyProperty="nid">
        <![CDATA[
            INSERT INTO glorynotice
            (ntitle, ncontent, ncate, nwriter) VALUES (#{ntitle}, #{ncontent}, #{ncate}, #{nwriter})
        ]]>
    </insert>

    <select id="select_detail" parameterType="String" resultType="com.glory.notice.Notice">
    <![CDATA[
        SELECT * FROM glorynotice WHERE nid = #{nid}
    ]]>
    </select>

    <select id="select_list" resultType="com.glory.notice.Notice">
    <![CDATA[
        SELECT * FROM glorynotice ORDER BY nid DESC
    ]]>
    </select>

</mapper>
```

## NoticeRepository.java

```
package com.glory.notice;

import java.util.List;

public interface NoticeRepository {

    void setNewNotice(Notice notice);

    List<Notice> getAllNoticeList();

    Notice getNoticeById(String nId);

}
```

## NoticeRepositoryImpl.java

```
package com.glory.notice;

import java.util.List;

import org.mybatis.spring.SqlSessionTemplate;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Repository;

@Repository
public class NoticeRepositoryImpl implements NoticeRepository {

    @Autowired
    SqlSessionTemplate sqlSessionTemplate;

    @Override
    public void setNewNotice(Notice notice) {
        this.sqlSessionTemplate.insert("notice.insert", notice);
    }

    @Override
    public List<Notice> getAllNoticeList() {
        return this.sqlSessionTemplate.selectList("notice.select_list");
    }

}
```

```

@Override
public Notice getNoticeById(String nId) {
    return this.sqlSessionTemplate.selectOne("notice.select_detail", nId);
}

}

```

### NoticeService.java

```

package com.glory.notice;

import java.util.List;

public interface NoticeService {

    void setNewNotice(Notice notice);

    List<Notice> getAllNoticeList();

    Notice getNoticeById(String nid);

}

```

### NoticeServiceImpl.java

```

package com.glory.notice;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class NoticeServiceImpl implements NoticeService {

    @Autowired
    private NoticeRepository noticeRepository;

    @Override
    public void setNewNotice(Notice notice) {
        noticeRepository.setNewNotice(notice);
    }

    @Override
    public List<Notice> getAllNoticeList() {
        return noticeRepository.getAllNoticeList();
    }

    @Override
    public Notice getNoticeById(String nid) {

        Notice noticeById = noticeRepository.getNoticeById(nid);

        return noticeById;
    }

}

```

### NoticeController.java

```

package com.glory.notice;

import java.util.HashMap;
import java.util.List;
import java.util.Map;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;

```

```

import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestParam;

@Controller
@RequestMapping("/notice")
public class NoticeController {

    // @Autowired
    // private MailService mailService;

    @Autowired
    private NoticeService noticeService;

    // @Autowired
    // private UserService userService;

    @GetMapping("/addNotice")
    public String requestAddNoticeForm(@ModelAttribute("NewNotice") Notice notice) {
        return "notices/addNotice";
    }

    @PostMapping("/addNotice")
    public String submitAddNoticeForm(@ModelAttribute("NewNotice") Notice notice) {

        noticeService.setNewNotice(notice);

        // User user = userService.existUsername(board.getBwriter());

        // String to = user.getUemail();
        // String subject = board.getBwriter() + "님의 게시물이 등록되었습니다.";
        // String body = board.getBcontent();

        // mailService.sendMail(to, subject, body);

        return "redirect:/notices/list";
    }

    @RequestMapping("/list")
    public String NoticeList(Model model) {
        List<Notice> list = noticeService.getAllNoticeList();
        model.addAttribute("noticeList", list);
        return "notices/list";
    }

    @GetMapping("/detail")
    public String requestNoticeById(@RequestParam("id") String nid, Model model) {

        //view 데이터를 불러오기 전에 조회수 증가
        Map<String, Object> map = new HashMap<String, Object>();
        map.put("nid", nid);
        map.put("check", "nview");

        //주 게시물
        Notice noticeById = noticeService.getNoticeById(nid);
        model.addAttribute("notice", noticeById);

        return "notices/notice";
    }
}

```

## addNotice.jsp

```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib uri="http://www.springframework.org/tags/form" prefix="form" %>
<%- -> <%@ taglib uri="http://www.springframework.org/security/tags" prefix="sec" %> - -%>

<head>
<title>공지사항 등록</title>
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<meta charset="utf-8">

</head>

```

```

<!-- Google Font: Source Sans Pro -->
<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">
<!-- Font Awesome -->
<link rel="stylesheet" href="/resources/admin/plugins/fontawesome-free/css/all.min.css">
<!-- Theme style -->
<link rel="stylesheet" href="/resources/admin/dist/css/adminlte.min.css">
<body class="text-center">

<%@ include file="../header.jsp" %>

<div class="container"><h1>공지사항 등록</h1>

<fieldset>
  <form:form modelAttribute="NewNotice" action="/addNotice?${_csrf.parameterName}=${_csrf.token}" class="form-horizontal" method="post">
    <!-- Main content -->
    <section class="content">
      <div class="row">
        <div class="col-md-6">
          <div class="card card-primary">
            <div class="card-header">
              <h3 class="card-title">General</h3>

            <form:input path="nwriter" type="hidden" value="admin" class="form-control" />

            <div class="card-tools">
              <button type="button" class="btn btn-tool" data-card-widget="collapse" title="Collapse">
                <i class="fas fa-minus"></i>
              </button>
            </div>
            <div class="card-body">
              <div class="form-group">
                <label for="inputName">제목</label>
                <form:input path="ntitle" class="form-control" />
              </div>
              <div class="form-group">
                <label for="inputDescription">내용</label>
                <form:textarea path="ncontent" class="form-control" rows="10"/>
              </div>
              <div class="form-group">
                <label for="inputStatus">유형</label>
                <form:select path="ncate" class="form-control custom-select">
                  <option selected disabled>선택하세요</option>
                  <option>일반</option>
                  <option>행사</option>
                  <option>기타</option>
                </form:select>
              </div>
            </div>
            <div class="row">
              <div class="col-6">
                <a href="#" class="btn btn-secondary">취소</a>
                <input type="submit" value="등록" class="btn btn-success float-right">
              </div>
            </div>
          </div>
        </div>
        <div class="col-md-6">
          <div class="card card-primary">
            <div class="card-header">
              <h3 class="card-title">General</h3>
            </div>
            <div class="card-body">
              <div class="form-group">
                <label for="inputName">제목</label>
                <form:input path="ntitle" class="form-control" />
              </div>
              <div class="form-group">
                <label for="inputDescription">내용</label>
                <form:textarea path="ncontent" class="form-control" rows="10"/>
              </div>
              <div class="form-group">
                <label for="inputStatus">유형</label>
                <form:select path="ncate" class="form-control custom-select">
                  <option selected disabled>선택하세요</option>
                  <option>일반</option>
                  <option>행사</option>
                  <option>기타</option>
                </form:select>
              </div>
            </div>
            <div class="row">
              <div class="col-6">
                <a href="#" class="btn btn-secondary">취소</a>
                <input type="submit" value="등록" class="btn btn-success float-right">
              </div>
            </div>
          </div>
        </div>
      </div>
    </section>
  </form:form>
</fieldset>
</div>

<!-- jQuery -->
<script src="/resources/admin/plugins/jquery/jquery.min.js"></script>
<!-- Bootstrap 4 -->
<script src="/resources/admin/plugins/bootstrap/js/bootstrap.bundle.min.js"></script>
<!-- AdminLTE App -->
<script src="/resources/admin/dist/js/adminlte.min.js"></script>
<!-- AdminLTE for demo purposes -->
<!-- <script src="/resources/admin/dist/js/demo.js"></script> -->
<%@ include file="../footer.jsp" %>

</body>
</html>

```

## list.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Insert title here</title>

<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">

<link rel="stylesheet" href="/resources/admin/plugins/fontawesome-free/css/all.min.css">

<link rel="stylesheet" href="/resources/admin/plugins/datatables-bs4/css/dataTables.bootstrap4.min.css">
<link rel="stylesheet" href="/resources/admin/plugins/datatables-responsive/css/responsive.bootstrap4.min.css">
<link rel="stylesheet" href="/resources/admin/plugins/datatables-buttons/css/buttons.bootstrap4.min.css">

<link rel="stylesheet" href="/resources/admin/dist/css/adminlte.min.css?v=3.2.0">
<script nonce="ee5d093f-ace6-44b5-bf0b-1e27a02cb5bb">(function(w,d){!function(a,b,c,d){a[c]=a[c]||{};a[c].executed=[];a.zaraz={defi

</head>
<body>

<div class="card">
<div class="card-header">
<h3 class="card-title">DataTable with default features</h3>
</div>

<div class="card-body">
<table id="example1" class="table table-bordered table-striped">
<thead>
<tr>
<th>Rendering engine</th>
<th>Browser</th>
<th>Platform(s)</th>
<th>Engine version</th>
<th>CSS grade</th>
</tr>
</thead>
<tbody>
<tr>
<td>Trident</td>
<td>Internet
Explorer 4.0
</td>
<td>Win 95+</td>
<td>4</td>
<td>X</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 5.0
</td>
<td>Win 95+</td>
<td>5</td>
<td>C</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 5.5
</td>
<td>Win 95+</td>
<td>5.5</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 6
</td>
<td>Win 98+</td>
<td>6</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet Explorer 7</td>
<td>Win XP SP2+</td>
```



```

<td>7</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>AOL browser (AOL desktop)</td>
<td>Win XP</td>
<td>6</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 1.0</td>
<td>Win 98+ / OSX.2+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 1.5</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 2.0</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 3.0</td>
<td>Win 2k+ / OSX.3+</td>
<td>1.9</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Camino 1.0</td>
<td>OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Camino 1.5</td>
<td>OSX.3+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape 7.2</td>
<td>Win 95+ / Mac OS 8.6-9.2</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape Browser 8</td>
<td>Win 98SE+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape Navigator 9</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.0</td>
<td>Win 95+ / OSX.1+</td>
<td>1</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.1</td>
<td>Win 95+ / OSX.1+</td>
<td>1.1</td>
<td>A</td>
</tr>

```

```

<tr>
<td>Gecko</td>
<td>Mozilla 1.2</td>
<td>Win 95+ / OSX.1+</td>
<td>1.2</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.3</td>
<td>Win 95+ / OSX.1+</td>
<td>1.3</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.4</td>
<td>Win 95+ / OSX.1+</td>
<td>1.4</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.5</td>
<td>Win 95+ / OSX.1+</td>
<td>1.5</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.6</td>
<td>Win 95+ / OSX.1+</td>
<td>1.6</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.7</td>
<td>Win 98+ / OSX.1+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.8</td>
<td>Win 98+ / OSX.1+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Seamonkey 1.1</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Epiphany 2.20</td>
<td>Gnome</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 1.2</td>
<td>OSX.3</td>
<td>125.5</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 1.3</td>
<td>OSX.3</td>
<td>312.8</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 2.0</td>
<td>OSX.4+</td>
<td>419.3</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 3.0</td>

```

```

<td>OSX.4+</td>
<td>522.1</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>OmniWeb 5.5</td>
<td>OSX.4+</td>
<td>420</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>iPod Touch / iPhone</td>
<td>iPod</td>
<td>420.1</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>S60</td>
<td>S60</td>
<td>413</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 7.0</td>
<td>Win 95+ / OSX.1+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 7.5</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 8.0</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 8.5</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.0</td>
<td>Win 95+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.2</td>
<td>Win 88+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.5</td>
<td>Win 88+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera for Wii</td>
<td>Wii</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Nokia N800</td>
<td>N800</td>
<td>-</td>
<td>A</td>

```

```

</tr>
<tr>
<td>Presto</td>
<td>Nintendo DS browser</td>
<td>Nintendo DS</td>
<td>8.5</td>
<td>C/A<sup>1</sup></td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.1</td>
<td>KDE 3.1</td>
<td>3.1</td>
<td>C</td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.3</td>
<td>KDE 3.3</td>
<td>3.3</td>
<td>A</td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.5</td>
<td>KDE 3.5</td>
<td>3.5</td>
<td>A</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 4.5</td>
<td>Mac OS 8-9</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 5.1</td>
<td>Mac OS 7.6-9</td>
<td>1</td>
<td>C</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 5.2</td>
<td>Mac OS 8-X</td>
<td>1</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>NetFront 3.1</td>
<td>Embedded devices</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>NetFront 3.4</td>
<td>Embedded devices</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Misc</td>
<td>Dillo 0.8</td>
<td>Embedded devices</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>Links</td>
<td>Text only</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>Lynx</td>
<td>Text only</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>

```

```

<td>IE Mobile</td>
<td>Windows Mobile 6</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>PSP browser</td>
<td>PSP</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Other browsers</td>
<td>All others</td>
<td>-</td>
<td>-</td>
<td>U</td>
</tr>
</tbody>
<tfoot>
<tr>
<th>Rendering engine</th>
<th>Browser</th>
<th>Platform(s)</th>
<th>Engine version</th>
<th>CSS grade</th>
</tr>
</tfoot>
</table>
</div>

</div>

<footer class="main-footer">
<div class="float-right d-none d-sm-block">
<b>Version</b> 3.2.0
</div>
<strong>Copyright &copy; 2014-2021 <a href="https://adminlte.io">AdminLTE.io</a>.</strong> All rights reserved.
</footer>

<aside class="control-sidebar control-sidebar-dark">

</aside>

</body>

<script src="/resources/admin/plugins/jquery/jquery.min.js"></script>

<script src="/resources/admin/plugins/bootstrap/js/bootstrap.bundle.min.js"></script>

<script src="/resources/admin/plugins/datatables/jquery.dataTables.min.js"></script>
<script src="/resources/admin/plugins/datatables-bs4/js/dataTables.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/datatables-responsive/js/dataTables.responsive.min.js"></script>
<script src="/resources/admin/plugins/datatables-responsive/js/responsive.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/dataTables.buttons.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/jszip/jszip.min.js"></script>
<script src="/resources/admin/plugins/pdfmake/pdfmake.min.js"></script>
<script src="/resources/admin/plugins/pdfmake/vfs_fonts.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.html5.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.print.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.colVis.min.js"></script>

<script src="/resources/admin/dist/js/adminlte.min.js?v=3.2.0"></script>

<!-- <script src="/resources/admin/dist/js/demo.js"></script> -->

<script>
$(function () {
  $('#example1').DataTable({
    "responsive": true, "lengthChange": false, "autoWidth": false,
    "buttons": ["copy", "csv", "excel", "pdf", "print", "colvis"]
  }).buttons().container().appendTo('#example1_wrapper .col-md-6:eq(0)');
  $('#example2').DataTable({
    "paging": true,
    "lengthChange": false,
    "searching": false,
    "ordering": true,
    "info": true,
    "autoWidth": false,
    "responsive": true,
  });
});
</script>

```

```
</html>
```

## ▼ Member

### Member.java

```
package com.glory.member;

public class Member {

    private int mid, enabled;

    private String username, password, authority, mname, memail, mtel, mdate;

    public int getMid() {
        return mid;
    }

    public void setMid(int mid) {
        this.mid = mid;
    }

    public int getEnabled() {
        return enabled;
    }

    public void setEnabled(int enabled) {
        this.enabled = enabled;
    }

    public String getUsername() {
        return username;
    }

    public void setUsername(String username) {
        this.username = username;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }

    public String getAuthority() {
        return authority;
    }

    public void setAuthority(String authority) {
        this.authority = authority;
    }

    public String getMname() {
        return mname;
    }

    public void setMname(String mname) {
        this.mname = mname;
    }

    public String getMemail() {
        return memail;
    }

    public void setMemail(String memail) {
        this.memail = memail;
    }

    public String getMtel() {
        return mtel;
    }
}
```

```

    public void setMtel(String mtel) {
        this.mtel = mtel;
    }

    public String getMdate() {
        return mdate;
    }

    public void setMdate(String mdate) {
        this.mdate = mdate;
    }

    public Member() {
    }

    public Member(int mid, int enabled, String username, String password, String authority, String mname, String memail,
        String mtel, String mdate) {
        this.mid = mid;
        this.enabled = enabled;
        this.username = username;
        this.password = password;
        this.authority = authority;
        this.mname = mname;
        this.memail = memail;
        this.mtel = mtel;
        this.mdate = mdate;
    }

}

```

## member\_SQL.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org/DTD Mapper 3.0//EN" "http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="member">

    <insert id="insert"
        parameterType="com.glory.member.Member" useGeneratedKeys="true" keyProperty="mid">
        <![CDATA[
            INSERT INTO glorymember
            (username, password, mname, memail, mtel) VALUES ({username}, #{password}, #{mname}, #{memail}, #{mtel})
        ]]>
    </insert>

    <select id="select_detail" parameterType="String" resultType="com.glory.member.Member">
    <![CDATA[
        SELECT * FROM glorymember WHERE mid = #{mid}
    ]]>
    </select>

    <select id="select_list" resultType="com.glory.member.Member">
    <![CDATA[
        SELECT * FROM glorymember ORDER BY mid DESC
    ]]>
    </select>

</mapper>

```

## MemberRepository.java

```

package com.glory.member;

import java.util.List;

public interface MemberRepository {

    void setNewMember(Member member);

    List<Member> getAllMemberList();

    Member getMemberById(String mId);

}

```

### MemberRepositoryImpl.java

```
package com.glory.member;

import java.util.List;

import org.mybatis.spring.SqlSessionTemplate;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Repository;

@Repository
public class MemberRepositoryImpl implements MemberRepository {

    @Autowired
    SqlSessionTemplate sqlSessionTemplate;

    @Override
    public void setNewMember(Member member) {
        this.sqlSessionTemplate.insert("member.insert", member);
    }

    @Override
    public List<Member> getAllMemberList() {
        return this.sqlSessionTemplate.selectList("member.select_list");
    }

    @Override
    public Member getMemberById(String mId) {
        return this.sqlSessionTemplate.selectOne("member.select_detail", mId);
    }
}
```

### MemberService.java

```
package com.glory.member;

import java.util.List;

public interface MemberService {

    void setNewMember(Member member);

    List<Member> getAllMemberList();

    Member getMemberById(String mid);
}
```

### MemberServiceImpl.java

```
package com.glory.member;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class MemberServiceImpl implements MemberService {

    @Autowired
    private MemberRepository memberRepository;

    @Override
    public void setNewMember(Member member) {
        memberRepository.setNewMember(member);
    }

    @Override
```



```

    public List<Member> getAllMemberList() {
        return memberRepository.getAllMemberList();
    }

    @Override
    public Member getMemberById(String mid) {

        Member memberById = memberRepository.getMemberById(mid);

        return memberById;
    }
}

```

## MemberController.java

```

package com.glory.member;

import java.util.HashMap;
import java.util.List;
import java.util.Map;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestParam;

@Controller
@RequestMapping("/member")
public class MemberController {

    // @Autowired
    // private MailService mailService;

    @Autowired
    private MemberService memberService;

    // @Autowired
    // private UserService userService;

    @GetMapping("/addMember")
    public String requestAddMemberForm(@ModelAttribute("NewMember") Member member) {
        return "members/addMember";
    }

    @PostMapping("/addMember")
    public String submitAddMemberForm(@ModelAttribute("NewMember") Member member) {

        memberService.setNewMember(member);

        // User user = userService.existUsername(board.getBwriter());

        // String to = user.getUemail();
        // String subject = board.getBwriter() + "님의 게시물이 등록되었습니다.";
        // String body = board.getBcontent();

        // mailService.sendMail(to, subject, body);

        return "redirect:/member/list";
    }

    @RequestMapping("/list")
    public String MemberList(Model model) {
        List<Member> list = memberService.getAllMemberList();
        model.addAttribute("memberList", list);
        return "members/list";
    }

    @GetMapping("/detail")
    public String requestMemberById(@RequestParam("id") String mid, Model model) {

        //view 데이터를 불러오기 전에 조회수 증가
        Map<String, Object> map = new HashMap<String, Object>();
        map.put("mid", mid);
        map.put("check", "mview");
    }
}

```

```

//주 게시물
Member memberById = memberService.getMemberById(mid);
model.addAttribute("member", memberById);

return "members/member";
}

}

```

## addMember.jsp

```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib uri="http://www.springframework.org/tags/form" prefix="form" %>
<!-- <%@ taglib uri="http://www.springframework.org/security/tags" prefix="sec" %> --%>

<head>
<title>회원가입</title>
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<meta charset="utf-8">

</head>
<!-- Google Font: Source Sans Pro -->
<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">
<!-- Font Awesome -->
<link rel="stylesheet" href="/resources/admin/plugins/fontawesome-free/css/all.min.css">
<!-- Theme style -->
<link rel="stylesheet" href="/resources/admin/dist/css/adminlte.min.css">
<body class="text-center">
<div class="container"><h1>회원가입</h1>

<fieldset>
<form:form modelAttribute="NewMember" action="./addMember?${_csrf.parameterName}=${_csrf.token}" class="form-horizontal" met
<!-- Main content -->
<section class="content">
<div class="row">
<div class="col-md-6">
<div class="card card-primary">
<div class="card-header">
<h3 class="card-title">General</h3>

<div class="card-tools">
<button type="button" class="btn btn-tool" data-card-widget="collapse" title="Collapse">
<i class="fas fa-minus"></i>
</button>
</div>
</div>
<div class="card-body">
<div class="form-group">
<label for="inputName">아이디</label>
<form:input path="username" class="form-control" />
</div>

<div class="form-group">
<label for="inputName">비밀번호</label>
<form:input path="password" type="password" class="form-control" />
</div>

<div class="form-group">
<label for="inputName">이름</label>
<form:input path="mname" class="form-control" />
</div>

<div class="form-group">
<label for="inputName">이메일</label>
<form:input path="memail" class="form-control" />
</div>

<div class="form-group">
<label for="inputName">전화번호</label>
<form:input path="mtel" class="form-control" />
</div>
</div>

<div class="row">
<div class="col-6">
<a href="#" class="btn btn-secondary">취소</a>
<input type="submit" value="등록" class="btn btn-success float-right">
</div>
</div>
</div>

```

```

        <!-- /.card-body -->
    </div>
    <!-- /.card -->
</div>
</section>
    </form:form>
    </fieldset>
</div>

<!-- jQuery -->
<script src="/resources/admin/plugins/jquery/jquery.min.js"></script>
<!-- Bootstrap 4 -->
<script src="/resources/admin/plugins/bootstrap/js/bootstrap.bundle.min.js"></script>
<!-- AdminLTE App -->
<script src="/resources/admin/dist/js/adminlte.min.js"></script>
<!-- AdminLTE for demo purposes -->
<!-- <script src="/resources/admin/dist/js/demo.js"></script> -->

</body>
</html>

```

## list.jsp

```

<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Insert title here</title>

<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">

<link rel="stylesheet" href="/resources/admin/plugins/fontawesome-free/css/all.min.css">

<link rel="stylesheet" href="/resources/admin/plugins/datatables-bs4/css/dataTables.bootstrap4.min.css">
<link rel="stylesheet" href="/resources/admin/plugins/datatables-responsive/css/responsive.bootstrap4.min.css">
<link rel="stylesheet" href="/resources/admin/plugins/datatables-buttons/css/buttons.bootstrap4.min.css">

<link rel="stylesheet" href="/resources/admin/dist/css/adminlte.min.css?v=3.2.0">
<script nonce="ee5d093f-ace6-44b5-bf0b-1e27a02cb5bb">(function(w,d){!function(a,b,c,d){a[c]=a[c]||{};a[c].executed=[];a.zaraz={defi

</head>
<body>

<div class="card">
<div class="card-header">
<h3 class="card-title">DataTable with default features</h3>
</div>

<div class="card-body">
<table id="example1" class="table table-bordered table-striped">
<thead>
<tr>
<th>Rendering engine</th>
<th>Browser</th>
<th>Platform(s)</th>
<th>Engine version</th>
<th>CSS grade</th>
</tr>
</thead>
<tbody>
<tr>
<td>Trident</td>
<td>Internet
Explorer 4.0
</td>
<td>Win 95+</td>
<td> 4</td>
<td>X</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 5.0
</td>

```

```

<td>Win 95+</td>
<td>5</td>
<td>C</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 5.5
</td>
<td>Win 95+</td>
<td>5.5</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet
Explorer 6
</td>
<td>Win 98+</td>
<td>6</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>Internet Explorer 7</td>
<td>Win XP SP2+</td>
<td>7</td>
<td>A</td>
</tr>
<tr>
<td>Trident</td>
<td>AOL browser (AOL desktop)</td>
<td>Win XP</td>
<td>6</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 1.0</td>
<td>Win 98+ / OSX.2+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 1.5</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 2.0</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Firefox 3.0</td>
<td>Win 2k+ / OSX.3+</td>
<td>1.9</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Camino 1.0</td>
<td>OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Camino 1.5</td>
<td>OSX.3+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape 7.2</td>
<td>Win 95+ / Mac OS 8.6-9.2</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>

```

```

<td>Netscape Browser 8</td>
<td>Win 98SE+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Netscape Navigator 9</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.0</td>
<td>Win 95+ / OSX.1+</td>
<td>1</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.1</td>
<td>Win 95+ / OSX.1+</td>
<td>1.1</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.2</td>
<td>Win 95+ / OSX.1+</td>
<td>1.2</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.3</td>
<td>Win 95+ / OSX.1+</td>
<td>1.3</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.4</td>
<td>Win 95+ / OSX.1+</td>
<td>1.4</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.5</td>
<td>Win 95+ / OSX.1+</td>
<td>1.5</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.6</td>
<td>Win 95+ / OSX.1+</td>
<td>1.6</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.7</td>
<td>Win 98+ / OSX.1+</td>
<td>1.7</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Mozilla 1.8</td>
<td>Win 98+ / OSX.1+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Seamonkey 1.1</td>
<td>Win 98+ / OSX.2+</td>
<td>1.8</td>
<td>A</td>
</tr>
<tr>
<td>Gecko</td>
<td>Epiphany 2.20</td>
<td>Gnome</td>
<td>1.8</td>

```

```

<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 1.2</td>
<td>OSX.3</td>
<td>125.5</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 1.3</td>
<td>OSX.3</td>
<td>312.8</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 2.0</td>
<td>OSX.4+</td>
<td>419.3</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>Safari 3.0</td>
<td>OSX.4+</td>
<td>522.1</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>OmniWeb 5.5</td>
<td>OSX.4+</td>
<td>420</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>iPod Touch / iPhone</td>
<td>iPod</td>
<td>420.1</td>
<td>A</td>
</tr>
<tr>
<td>Webkit</td>
<td>S60</td>
<td>S60</td>
<td>413</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 7.0</td>
<td>Win 95+ / OSX.1+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 7.5</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 8.0</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 8.5</td>
<td>Win 95+ / OSX.2+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.0</td>
<td>Win 95+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>

```

```

<td>Presto</td>
<td>Opera 9.2</td>
<td>Win 88+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera 9.5</td>
<td>Win 88+ / OSX.3+</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Opera for Wii</td>
<td>Wii</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Nokia N800</td>
<td>N800</td>
<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Presto</td>
<td>Nintendo DS browser</td>
<td>Nintendo DS</td>
<td>8.5</td>
<td>C/A<sup>1</sup></td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.1</td>
<td>KDE 3.1</td>
<td>3.1</td>
<td>C</td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.3</td>
<td>KDE 3.3</td>
<td>3.3</td>
<td>A</td>
</tr>
<tr>
<td>KHTML</td>
<td>Konqueror 3.5</td>
<td>KDE 3.5</td>
<td>3.5</td>
<td>A</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 4.5</td>
<td>Mac OS 8-9</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 5.1</td>
<td>Mac OS 7.6-9</td>
<td>1</td>
<td>C</td>
</tr>
<tr>
<td>Tasman</td>
<td>Internet Explorer 5.2</td>
<td>Mac OS 8-X</td>
<td>1</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>NetFront 3.1</td>
<td>Embedded devices</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>NetFront 3.4</td>
<td>Embedded devices</td>

```

```

<td>-</td>
<td>A</td>
</tr>
<tr>
<td>Misc</td>
<td>Dillo 0.8</td>
<td>Embedded devices</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>Links</td>
<td>Text only</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>Lynx</td>
<td>Text only</td>
<td>-</td>
<td>X</td>
</tr>
<tr>
<td>Misc</td>
<td>IE Mobile</td>
<td>Windows Mobile 6</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Misc</td>
<td>PSP browser</td>
<td>PSP</td>
<td>-</td>
<td>C</td>
</tr>
<tr>
<td>Other browsers</td>
<td>All others</td>
<td>-</td>
<td>-</td>
<td>U</td>
</tr>
</tbody>
<tfoot>
<tr>
<th>Rendering engine</th>
<th>Browser</th>
<th>Platform(s)</th>
<th>Engine version</th>
<th>CSS grade</th>
</tr>
</tfoot>
</table>
</div>

</div>

<footer class="main-footer">
<div class="float-right d-none d-sm-block">
<b>Version</b> 3.2.0
</div>
<strong>Copyright &copy; 2014-2021 <a href="https://adminlte.io">AdminLTE.io</a>.</strong> All rights reserved.
</footer>

<aside class="control-sidebar control-sidebar-dark">

</aside>

</body>

<script src="/resources/admin/plugins/jquery/jquery.min.js"></script>

<script src="/resources/admin/plugins/bootstrap/js/bootstrap.bundle.min.js"></script>

<script src="/resources/admin/plugins/datatables/jquery.dataTables.min.js"></script>
<script src="/resources/admin/plugins/datatables-bs4/js/dataTables.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/datatables-responsive/js/dataTables.responsive.min.js"></script>
<script src="/resources/admin/plugins/datatables-responsive/js/responsive.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/dataTables.buttons.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.bootstrap4.min.js"></script>
<script src="/resources/admin/plugins/jszip/jszip.min.js"></script>
<script src="/resources/admin/plugins/pdfmake/pdfmake.min.js"></script>

```



```

<script src="/resources/admin/plugins/pdfmake/vfs_fonts.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.html5.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.print.min.js"></script>
<script src="/resources/admin/plugins/datatables-buttons/js/buttons.colVis.min.js"></script>

<script src="/resources/admin/dist/js/adminlte.min.js?v=3.2.0"></script>

<!-- <script src="/resources/admin/dist/js/demo.js"></script> -->

<script>
$(function () {
  $('#example1').DataTable({
    "responsive": true, "lengthChange": false, "autoWidth": false,
    "buttons": ["copy", "csv", "excel", "pdf", "print", "colvis"]
  }).container().appendTo('#example1_wrapper .col-md-6:eq(0)');
  $('#example2').DataTable({
    "paging": true,
    "lengthChange": false,
    "searching": false,
    "ordering": true,
    "info": true,
    "autoWidth": false,
    "responsive": true,
  });
});
</script>

</html>

```

## header.jsp

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="utf-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
<title>AdminLTE 3 | DataTables</title>

<link rel="stylesheet" href="https://fonts.googleapis.com/css?family=Source+Sans+Pro:300,400,400i,700&display=fallback">

<link rel="stylesheet" href="../../plugins/fontawesome-free/css/all.min.css">

<link rel="stylesheet" href="../../plugins/datatables-bs4/css/dataTables.bootstrap4.min.css">
<link rel="stylesheet" href="../../plugins/datatables-responsive/css/responsive.bootstrap4.min.css">
<link rel="stylesheet" href="../../plugins/datatables-buttons/css/buttons.bootstrap4.min.css">

<link rel="stylesheet" href="../../dist/css/adminlte.min.css?v=3.2.0">
<script nonce="ee5d093f-ace6-44b5-bf0b-1e27a02cb5bb">(function(w,d){!function(a,b,c,d){a[c]=a[c]||{};a[c].executed=[];a.zaraz={deferre
<body class="hold-transition sidebar-mini">
<div class="wrapper">

<nav class="main-header navbar navbar-expand navbar-white navbar-light">

<ul class="navbar-nav">
<li class="nav-item">
<a class="nav-link" data-widget="pushmenu" href="#" role="button"><i class="fas fa-bars"></i></a>
</li>
<li class="nav-item d-none d-sm-inline-block">
<a href="../../index3.html" class="nav-link">Home</a>
</li>
<li class="nav-item d-none d-sm-inline-block">
<a href="#" class="nav-link">Contact</a>
</li>
</ul>

<ul class="navbar-nav ml-auto">

<li class="nav-item">
<a class="nav-link" data-widget="navbar-search" href="#" role="button">
<i class="fas fa-search"></i>
</a>
<div class="navbar-search-block">
<form class="form-inline">
<div class="input-group input-group-sm">
<input class="form-control form-control-navbar" type="search" placeholder="Search" aria-label="Search">
<div class="input-group-append">

```

```

<button class="btn btn-navbar" type="submit">
<i class="fas fa-search"></i>
</button>
<button class="btn btn-navbar" type="button" data-widget="navbar-search">
<i class="fas fa-times"></i>
</button>
</div>
</div>
</form>
</div>
</li>

<li class="nav-item dropdown">
<a class="nav-link" data-toggle="dropdown" href="#">
<i class="far fa-comments"></i>
<span class="badge badge-danger navbar-badge">3</span>
</a>
<div class="dropdown-menu dropdown-menu-lg dropdown-menu-right">
<a href="#" class="dropdown-item">

<div class="media">

<div class="media-body">
<h3 class="dropdown-item-title">
Brad Diesel
<span class="float-right text-sm text-danger"><i class="fas fa-star"></i></span>
</h3>
<p class="text-sm">Call me whenever you can...</p>
<p class="text-sm text-muted"><i class="far fa-clock mr-1"></i> 4 Hours Ago</p>
</div>
</div>

</a>
<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item">

<div class="media">

<div class="media-body">
<h3 class="dropdown-item-title">
John Pierce
<span class="float-right text-sm text-muted"><i class="fas fa-star"></i></span>
</h3>
<p class="text-sm">I got your message bro</p>
<p class="text-sm text-muted"><i class="far fa-clock mr-1"></i> 4 Hours Ago</p>
</div>
</div>

</a>
<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item">

<div class="media">

<div class="media-body">
<h3 class="dropdown-item-title">
Nora Silvester
<span class="float-right text-sm text-warning"><i class="fas fa-star"></i></span>
</h3>
<p class="text-sm">The subject goes here</p>
<p class="text-sm text-muted"><i class="far fa-clock mr-1"></i> 4 Hours Ago</p>
</div>
</div>

</a>
<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item dropdown-footer">See All Messages</a>
</div>
</li>

<li class="nav-item dropdown">
<a class="nav-link" data-toggle="dropdown" href="#">
<i class="far fa-bell"></i>
<span class="badge badge-warning navbar-badge">15</span>
</a>
<div class="dropdown-menu dropdown-menu-lg dropdown-menu-right">
<span class="dropdown-item dropdown-header">15 Notifications</span>
<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item">
<i class="fas fa-envelope mr-2"></i> 4 new messages
<span class="float-right text-muted text-sm">3 mins</span>
</a>
<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item">
<i class="fas fa-users mr-2"></i> 8 friend requests
<span class="float-right text-muted text-sm">12 hours</span>
</a>

```

```

<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item">
<i class="fas fa-file mr-2"></i> 3 new reports
<span class="float-right text-muted text-sm">2 days</span>
</a>
<div class="dropdown-divider"></div>
<a href="#" class="dropdown-item dropdown-footer">See All Notifications</a>
</div>
</li>
<li class="nav-item">
<a class="nav-link" data-widget="fullscreen" href="#" role="button">
<i class="fas fa-expand-arrows-alt"></i>
</a>
</li>
<li class="nav-item">
<a class="nav-link" data-widget="control-sidebar" data-slide="true" href="#" role="button">
<i class="fas fa-th-large"></i>
</a>
</li>
</ul>
</nav>

<aside class="main-sidebar sidebar-dark-primary elevation-4">

<a href="../../../index3.html" class="brand-link">

<span class="brand-text font-weight-light">AdminLTE 3</span>
</a>

<div class="sidebar">

<div class="user-panel mt-3 pb-3 mb-3 d-flex">
<div class="image">

</div>
<div class="info">
<a href="#" class="d-block">Alexander Pierce</a>
</div>
</div>

<div class="form-inline">
<div class="input-group" data-widget="sidebar-search">
<input class="form-control form-control-sidebar" type="search" placeholder="Search" aria-label="Search">
<div class="input-group-append">
<button class="btn btn-sidebar">
<i class="fas fa-search fa-fw"></i>
</button>
</div>
</div>
</div>

<nav class="mt-2">
<ul class="nav nav-pills nav-sidebar flex-column" data-widget="treeview" role="menu" data-accordion="false">

<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-tachometer-alt"></i>
<p>
Dashboard
<i class="right fas fa-angle-left"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../../../index.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Dashboard v1</p>
</a>
</li>
<li class="nav-item">
<a href="../../../index2.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Dashboard v2</p>
</a>
</li>
<li class="nav-item">
<a href="../../../index3.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Dashboard v3</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="../../../widgets.html" class="nav-link">
<i class="nav-icon fas fa-th"></i>

```

```

<p>
Widgets
<span class="right badge badge-danger">New</span>
</p>
</a>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-copy"></i>
<p>
Layout Options
<i class="fas fa-angle-left"></i>
<span class="badge badge-info right">6</span>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../layout/top-nav.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Top Navigation</p>
</a>
</li>
<li class="nav-item">
<a href="../layout/top-nav-sidebar.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Top Navigation + Sidebar</p>
</a>
</li>
<li class="nav-item">
<a href="../layout/boxed.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Boxed</p>
</a>
</li>
<li class="nav-item">
<a href="../layout/fixed-sidebar.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Fixed Sidebar</p>
</a>
</li>
<li class="nav-item">
<a href="../layout/fixed-sidebar-custom.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Fixed Sidebar <small>+ Custom Area</small></p>
</a>
</li>
<li class="nav-item">
<a href="../layout/fixed-topnav.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Fixed Navbar</p>
</a>
</li>
<li class="nav-item">
<a href="../layout/fixed-footer.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Fixed Footer</p>
</a>
</li>
<li class="nav-item">
<a href="../layout/collapsed-sidebar.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Collapsed Sidebar</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-chart-pie"></i>
<p>
Charts
<i class="right fas fa-angle-left"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../charts/chartjs.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>ChartJS</p>
</a>
</li>
<li class="nav-item">
<a href="../charts/flot.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Flot</p>
</a>
</li>

```

```

<li class="nav-item">
<a href="../charts/inline.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Inline</p>
</a>
</li>
<li class="nav-item">
<a href="../charts/uplot.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>uPlot</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-tree"></i>
<p>
UI Elements
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../UI/general.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>General</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/icons.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Icons</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/buttons.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Buttons</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/sliders.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Sliders</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/modals.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Modals & Alerts</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/navbar.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Navbar & Tabs</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/timeline.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Timeline</p>
</a>
</li>
<li class="nav-item">
<a href="../UI/ribbons.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Ribbons</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-edit"></i>
<p>
Forms
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../forms/general.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>General Elements</p>
</a>

```

```

</li>
<li class="nav-item">
<a href="../forms/advanced.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Advanced Elements</p>
</a>
</li>
<li class="nav-item">
<a href="../forms/editors.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Editors</p>
</a>
</li>
<li class="nav-item">
<a href="../forms/validation.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Validation</p>
</a>
</li>
</ul>
</li>
<li class="nav-item menu-open">
<a href="#" class="nav-link active">
<i class="nav-icon fas fa-table"></i>
<p>
Tables
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../tables/simple.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Simple Tables</p>
</a>
</li>
<li class="nav-item">
<a href="../tables/data.html" class="nav-link active">
<i class="far fa-circle nav-icon"></i>
<p>DataTables</p>
</a>
</li>
<li class="nav-item">
<a href="../tables/jsgrid.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>jsGrid</p>
</a>
</li>
</ul>
</li>
<li class="nav-header">EXAMPLES</li>
<li class="nav-item">
<a href="../calendar.html" class="nav-link">
<i class="nav-icon far fa-calendar-alt"></i>
<p>
Calendar
<span class="badge badge-info right">2</span>
</p>
</a>
</li>
<li class="nav-item">
<a href="../gallery.html" class="nav-link">
<i class="nav-icon far fa-image"></i>
<p>
Gallery
</p>
</a>
</li>
<li class="nav-item">
<a href="../kanban.html" class="nav-link">
<i class="nav-icon fas fa-columns"></i>
<p>
Kanban Board
</p>
</a>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon far fa-envelope"></i>
<p>
Mailbox
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../mailbox/mailbox.html" class="nav-link">

```

```

<i class="far fa-circle nav-icon"></i>
<p>Inbox</p>
</a>
</li>
<li class="nav-item">
<a href="../mailbox/compose.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Compose</p>
</a>
</li>
<li class="nav-item">
<a href="../mailbox/read-mail.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Read</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-book"></i>
<p>
Pages
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../examples/invoice.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Invoice</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/profile.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Profile</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/e-commerce.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>E-commerce</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/projects.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Projects</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/project-add.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Project Add</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/project-edit.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Project Edit</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/project-detail.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Project Detail</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/contacts.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Contacts</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/faq.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>FAQ</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/contact-us.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Contact us</p>
</a>
</li>

```

```

</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon far fa-plus-square"></i>
<p>
Extras
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="#" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>
Login & Register v1
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../examples/login.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Login v1</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/register.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Register v1</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/forgot-password.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Forgot Password v1</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/recover-password.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Recover Password v1</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>
Login & Register v2
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../examples/login-v2.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Login v2</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/register-v2.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Register v2</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/forgot-password-v2.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Forgot Password v2</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/recover-password-v2.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Recover Password v2</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="../examples/lockscreen.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Lockscreen</p>
</a>
</li>

```



```

<li class="nav-item">
<a href="../examples/legacy-user-menu.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Legacy User Menu</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/language-menu.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Language Menu</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/404.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Error 404</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/500.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Error 500</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/pace.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Pace</p>
</a>
</li>
<li class="nav-item">
<a href="../examples/blank.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Blank Page</p>
</a>
</li>
<li class="nav-item">
<a href="../../starter.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Starter Page</p>
</a>
</li>
</ul>
</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="nav-icon fas fa-search"></i>
<p>
Search
<i class="fas fa-angle-left right"></i>
</p>
</a>
<ul class="nav nav-treeview">
<li class="nav-item">
<a href="../search/simple.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Simple Search</p>
</a>
</li>
<li class="nav-item">
<a href="../search/enhanced.html" class="nav-link">
<i class="far fa-circle nav-icon"></i>
<p>Enhanced</p>
</a>
</li>
</ul>
</li>
<li class="nav-header">MISCELLANEOUS</li>
<li class="nav-item">
<a href="../../iframe.html" class="nav-link">
<i class="nav-icon fas fa-ellipsis-h"></i>
<p>Tabbed IFrame Plugin</p>
</a>
</li>
<li class="nav-item">
<a href="https://adminlte.io/docs/3.1/" class="nav-link">
<i class="nav-icon fas fa-file"></i>
<p>Documentation</p>
</a>
</li>
<li class="nav-header">MULTI LEVEL EXAMPLE</li>
<li class="nav-item">
<a href="#" class="nav-link">
<i class="fas fa-circle nav-icon"></i>
<p>Level 1</p>
</a>
</li>

```

```

<li class="nav-item">
  <a href="#" class="nav-link">
    <i class="nav-icon fas fa-circle"></i>
    <p>
      Level 1
    <i class="right fas fa-angle-left"></i>
    </p>
    </a>
    <ul class="nav nav-treeview">
      <li class="nav-item">
        <a href="#" class="nav-link">
          <i class="far fa-circle nav-icon"></i>
          <p>Level 2</p>
        </a>
        </li>
        <li class="nav-item">
          <a href="#" class="nav-link">
            <i class="far fa-circle nav-icon"></i>
            <p>
              Level 2
            <i class="right fas fa-angle-left"></i>
            </p>
            </a>
            <ul class="nav nav-treeview">
              <li class="nav-item">
                <a href="#" class="nav-link">
                  <i class="far fa-dot-circle nav-icon"></i>
                  <p>Level 3</p>
                </a>
                </li>
                <li class="nav-item">
                  <a href="#" class="nav-link">
                    <i class="far fa-dot-circle nav-icon"></i>
                    <p>Level 3</p>
                  </a>
                  </li>
                <li class="nav-item">
                  <a href="#" class="nav-link">
                    <i class="far fa-dot-circle nav-icon"></i>
                    <p>Level 3</p>
                  </a>
                  </li>
                </ul>
              </li>
              <li class="nav-item">
                <a href="#" class="nav-link">
                  <i class="far fa-circle nav-icon"></i>
                  <p>Level 2</p>
                </a>
                </li>
              </ul>
            </li>
            <li class="nav-item">
              <a href="#" class="nav-link">
                <i class="fas fa-circle nav-icon"></i>
                <p>Level 1</p>
              </a>
              </li>
            </ul>
          </li>
          <li class="nav-item">
            <a href="#" class="nav-link">
              <i class="nav-icon far fa-circle text-danger"></i>
              <p class="text">Important</p>
            </a>
            </li>
            <li class="nav-item">
              <a href="#" class="nav-link">
                <i class="nav-icon far fa-circle text-warning"></i>
                <p>Warning</p>
              </a>
              </li>
            <li class="nav-item">
              <a href="#" class="nav-link">
                <i class="nav-icon far fa-circle text-info"></i>
                <p>Informational</p>
              </a>
              </li>
            </ul>
          </nav>
        </div>
      </aside>

```

## footer.jsp

```
<footer class="main-footer">
<div class="float-right d-none d-sm-block">
<b>Version</b> 3.2.0
</div>
<strong>Copyright &copy; 2014-2021 <a href="https://adminlte.io">AdminLTE.io</a>.</strong> All rights reserved.
</footer>
```