

SDK development manual for scanner module

Overview:

Customer can get scanning results in their own app, and Simulate scan button to trigger scanning. The following is a brief description. See the sdk code for details.

Version information		
version	date	editor
V1.0	2022/06/24	LiXin

1. Development Instructions

1.1 Trigger scan broadcast

Open the file /vendor/etc/scanner_config.xml in the device to check the configuration of buttons.

```
<buttons>
  <button id="L/R key">
    <!--松开触发的是关闭广播，摁下去触发的是打开广播-->
    <closeBroadcast>com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_L_UP</closeBroadcast>
    <openBroadcast>com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_L_DOWN</openBroadcast>
    <value>true</value><!--广播的默认值，开和关==true or false-->
  </button>
  <!--button id="R key"-->
  <!--closeBroadcast>com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_R_UP</closeBroadcast>-->
  <!--openBroadcast>com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_R_DOWN</openBroadcast>-->
  <!--value>true</value>-->
  <!--/button-->
  <!--button id="F key"-->
  <!--closeBroadcast>com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_F_UP</closeBroadcast>-->
  <!--openBroadcast>com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_F_DOWN</openBroadcast>-->
  <!--value>true</value>-->
  <!--/button-->
</buttons>
```

Down: trigger scan

```
sendBroadcast(Intent("com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_L_DOWN"))
```

Up: disables code scanning

```
sendBroadcast(Intent("com.android.action.keyevent.KEYCODE_KEYCODE_SCAN_L_UP"))
```

Notes: L,R,F are corresponding to different buttons on the device respectively

1.2 get data broadcast

Obtain scan code data by listening to the broadcast. If you modify it to a custom broadcast in [Scanning Tool], you need to modify it to the corresponding broadcast action and data.

```
val intentFilter = IntentFilter()

val action = "com.android.serial.BARCODEPORT_RECEIVEDDATA_ACTION"

val data = "DATA"

intentFilter.addAction(action)

registerReceiver(object : BroadcastReceiver() {

    override fun onReceive(context: Context, intent: Intent) {

        if (action == intent.action) {

            var data = intent.getStringExtra(data)

            Log.d("scan", "scanQrCode = [${data}]")

        }

    }

}, intentFilter)
```