

# Boost.Graph tutorial

Richel Bilderbeek

December 7, 2015

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Coding style used . . . . .	3
1.2	Pitfalls . . . . .	3
<b>2</b>	<b>Building graphs</b>	<b>3</b>
2.1	Creating an empty (directed) graph . . . . .	3
2.2	Creating an empty undirected graph . . . . .	4
2.3	Add a vertex . . . . .	4
2.4	Add an edge . . . . .	5
2.5	Creating $K_2$ , a fully connected graph with two vertices . . . . .	6
2.6	Creating an empty graph with named vertices . . . . .	7
2.7	Add a vertex with a name . . . . .	8
2.8	Creating $K_2$ with named vertices . . . . .	8
2.9	Creating an empty graph with named edges and vertices . . . . .	9
2.10	Add an edge with a name . . . . .	11
2.11	Creating $K_3$ with named edges and vertices . . . . .	11
2.12	Create an empty graph with custom vertices . . . . .	14
2.12.1	Creating the custom vertex class . . . . .	14
2.12.2	Installing the new property . . . . .	15
2.12.3	Create the empty graph with custom vertices . . . . .	16
2.13	Add a custom vertex . . . . .	17
2.14	Creating $K_2$ with custom vertices . . . . .	17
2.15	Create an empty graph with custom edges and vertices . . . . .	19
2.16	Add a custom edge . . . . .	19
2.17	Creating $K_2$ with custom edges and vertices . . . . .	19
<b>3</b>	<b>Measuring simple graphs traits</b>	<b>19</b>
3.1	Getting the vertices . . . . .	19
3.2	Getting the edges . . . . .	19
3.3	Counting the number of vertices . . . . .	19
3.4	Counting the number of edges . . . . .	19
3.5	Getting the vertices' names . . . . .	20
3.6	Getting the edges' names . . . . .	21

3.7	Getting the vertices' my_vertexes . . . . .	21
3.8	Count vertex name . . . . .	22
3.9	Find a vertex by its name . . . . .	22
3.10	Get a named vertex its in-degree . . . . .	22
3.11	Get a named vertex its out-degree . . . . .	23
3.12	Count vertex my_vertex . . . . .	23
3.13	Find a my_vertex . . . . .	23
3.14	Find the vertices connected to a certain my_vertex . . . . .	23
<b>4</b>	<b>Modifying simple graphs traits</b>	<b>23</b>
4.1	Setting all vertices' names . . . . .	23
4.2	Setting all vertices' my_vertex objects . . . . .	24
4.3	Replace a vertex its name . . . . .	25
4.4	Replace an edge its name . . . . .	25
4.5	Replace a my_vertex . . . . .	26
4.6	Clear a named vertex . . . . .	26
4.7	Remove a named vertex . . . . .	26
4.8	Remove a named edge . . . . .	26
4.9	Remove a my_vertex . . . . .	26
<b>5</b>	<b>Visualizing graphs</b>	<b>26</b>
5.1	Storing a graph as a .dot . . . . .	27
5.2	Storing a graph with named vertices as a .dot . . . . .	28
5.3	Storing a graph with named vertices and edges as a .dot . . . . .	30
5.4	Storing a graph with custom vertices as a .dot . . . . .	32
<b>6</b>	<b>Measuring more complex graphs traits</b>	<b>34</b>
6.1	Count the number of self-loops . . . . .	34

# 1 Introduction

I needed this tutorial in 2006, when I started experimenting with Boost.Graph. More specifically, I needed a tutorial that:

- Orders concepts chronologically
- Increases complexity gradually
- Shows complete pieces of code

What I had were the book [1] and the Boost.Graph website, both did not satisfy these requirements.

## 1.1 Coding style used

I use the coding style from the Core C++ Guidelines.

I prefer to use the keyword `auto` over doubling the lines of code for using statements. There are plenty of algorithms that return an explicit data type, which can be used for reference.

All coding snippets are taken from compiled C++ code.

vd: vertex\_descriptor

## 1.2 Pitfalls

The choice between `'boost::get'`, `'std::get'` and `'get'`. AFAIKS, when in doubt, use `'get'`.

# 2 Building graphs

Boost.Graph is about creating graphs. In this chapter we create graphs, starting from simple to more complex.

## 2.1 Creating an empty (directed) graph

Let's create a trivial empty graph:

---

**Algorithm 1** Creating an empty graph

---

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<>
create_empty_directed_graph() noexcept
{
    return boost::adjacency_list<>();
}
```

---

Congratulations, you've just created a `boost::adjacency_list` in which:

- The out edges are stored in a `std::vector`
- The vertices are stored in a `std::vector`
- The graph is directed
- Vertices, edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` is the most commonly used graph type, the other is the `boost::adjacency_matrix`.

## 2.2 Creating an empty undirected graph

Let's create a trivial empty graph:

---

**Algorithm 2** Creating an empty graph

---

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_empty_undirected_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS
    >();
}
```

---

Congratulations, you've just created a `boost::adjacency_list` in which:

- The out edges are stored in a `std::vector`
- The vertices are stored in a `std::vector`
- The graph is undirected
- Vertices, edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` is the most commonly used graph type, the other is the `boost::adjacency_matrix`.

## 2.3 Add a vertex

To add a vertex to a graph, the `boost::add_vertex` function is used as such:

---

**Algorithm 3** Adding a vertex to a graph

---

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_vertex(graph& g)
{
    boost::add_vertex(g);
}
```

---

Note that `boost::add_vertex` returns a vertex descriptor, which is ignored for now. A vertex descriptor can be used to, for example, connect two vertices by an edge

## 2.4 Add an edge

To add an edge to a graph, two vertex descriptors are needed. A vertex descriptor is a handle to the vertex within graph. Algorithm 4 adds two vertices to a graph, and connects these two using `boost::add_edge`:

---

**Algorithm 4** Adding (two vertices and) an edge to a graph

---

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_edge(graph& g)
{
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto vertex_descriptor_b = boost::add_vertex(g);
    const auto edge_insertion_result = boost::add_edge(
        vertex_descriptor_a,
        vertex_descriptor_b,
        g
    );

    assert(edge_insertion_result.second);
}
```

---

This algorithm only shows how to add an isolated edge to a graph, instead of allowing for graphs with higher connectivities. The function `boost::add_vertex` returns a vertex descriptor, which I prefix with 'vd'. The function `boost::add_edge` returns a `std::pair`, consisting of an edge descriptor and a boolean success indi-

cator. In algorithm 4 we assert that this insertion was successful. Insertion can fail if an edge is already present and duplicates are not allowed.

## 2.5 Creating $K_2$ , a fully connected graph with two vertices

To create a fully connected graph with two vertices (also called  $K_2$ ), one needs two vertices and one (undirected) edge, as depicted in figure 1.



Figure 1:  $K_2$ : a fully connected graph with two vertices named  $a$  and  $b$

To create  $K_2$ , the following code can be used:

---

**Algorithm 5** Creating  $K_2$  as depicted in figure 1

---

```
#include "create_k2_graph.h"
#include "create_empty_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_k2_graph() noexcept
{
    auto g = create_empty_undirected_graph();
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto vertex_descriptor_b = boost::add_vertex(g);
    const auto edge_insertion_result
        = boost::add_edge(vertex_descriptor_a,
                          vertex_descriptor_b, g);
    assert(edge_insertion_result.second);
    return g;
}
```

---

Note that this code has more lines of using statements than actual code! In this code, the third template argument of `boost::adjacency_list` is `boost::undirectedS`, to select (that is what the `S` means) for an undirected graph. Adding a vertex with `boost::add_vertex` results in a vertex descriptor, which is a handle to the vertex added to the graph. Two vertex descriptors are then used to add an edge to the graph. Adding an edge using `boost::add_edge` returns two things:

an edge descriptor and a boolean indicating success. In the code example, we assume insertion is successful.

Note that the graph lacks all properties: nodes do not have names, nor do edges.

## 2.6 Creating an empty graph with named vertices

Let's create a trivial empty graph, in which the vertices can have a name:

---

**Algorithm 6** Creating an empty graph with named vertices

---

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
create_empty_named_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    > ();
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- Edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property<boost::vertex_name_t,std::string>`'. This can be read as: “vertices have the property '`boost::vertex_name_t`', that is of data type '`std::string`”. Or simply: “vertices have a name that is stored as a `std::string`”.

## 2.7 Add a vertex with a name

Adding a vertex without a name was trivially easy (see chapter 3). Adding a vertex with a name is less easy:

---

**Algorithm 7** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_named_vertex(graph& g, const std::string& name)
{
    const auto vertex_descriptor_a = boost::add_vertex(g);
    auto vertex_name_map = boost::get(boost::vertex_name,g)
    ;
    vertex_name_map[vertex_descriptor_a] = name;
}
```

---

Instead of calling '`boost::add_vertex`' with an additional argument containing the name of the vertex, multiple things need to be done. When adding a new vertex to the graph, the vertex descriptor is stored. After obtaining the name map from the graph (using '`boost::get(boost::vertex_name,g)`'), the name of the vertex is set using that vertex descriptor.

## 2.8 Creating $K_2$ with named vertices

We extend  $K_2$  of chapter 2.5 by naming the vertices 'from' and 'to', as depicted in figure 2:




Figure 2:  $K_2$ : a fully connected graph with two vertices with the text 'from' and 'to'

To create  $K_2$ , the following code can be used:



---

**Algorithm 8** Creating  $K_2$  as depicted in figure 2

---

```
#include "create_named_vertices_k2_graph.h"
#include "create_empty_named_vertices_graph.h"
boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>
>
create_named_vertices_k2_graph() noexcept
{
    auto g = create_empty_named_vertices_graph();
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto vertex_descriptor_b = boost::add_vertex(g);
    const auto edge_insertion_result
        = boost::add_edge(
            vertex_descriptor_a,
            vertex_descriptor_b,
            g
        );
    assert(edge_insertion_result.second);

    auto name_map = boost::get(boost::vertex_name, g);
    name_map[vertex_descriptor_a] = "from";
    name_map[vertex_descriptor_b] = "to";

    return g;
}
```

---

Most of the code is a repeat of algorithm 5. In the end, the names are obtained as a `boost::property_map` and set.

## 2.9 Creating an empty graph with named edges and vertices

Let's create a trivial empty graph, in which the both the edges and vertices can have a name:

---

**Algorithm 9** Creating an empty graph with named edges and vertices

---

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_empty_named_edges_and_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    > ();
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- The edges have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::edge_name_t, std::string>`)
- The graph has no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fifth template argument '`boost::property< boost::edge_name_t, std::string>`'. This can be read as: "edges have the property '`boost::edge_name_t`', that is of data type '`std::string`'". Or simply: "edges have a name that is stored as a `std::string`".

## 2.10 Add an edge with a name

Adding an edge with a name:

---

**Algorithm 10** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_named_edge(graph& g, const std::string&
    edge_name)
{
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto vertex_descriptor_b = boost::add_vertex(g);
    const auto edge_insertion_result
        = boost::add_edge(vertex_descriptor_a,
            vertex_descriptor_b, g);

    assert(edge_insertion_result.second);

    auto edge_name_map = boost::get(boost::edge_name, g);
    edge_name_map[edge_insertion_result.first] = edge_name;
}
```

---

In this code snippet, the edge descriptor when using 'boost::add\_edge' is used as a key to change the edge name map.

## 2.11 Creating $K_3$ with named edges and vertices

We extend the graph  $K_2$  with named vertices of chapter 2.8 by adding names to the edges, as depicted in figure 3:




Figure 3:  $K_3$ : a fully connected graph with three named edges and vertices

To create  $K_3$ , the following code can be used:

---

**Algorithm 11** Creating  $K_3$  as depicted in figure 3

---

```
#include "create_named_edges_and_vertices_k3_graph.h"

#include "create_empty_named_edges_and_vertices_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_named_edges_and_vertices_k3_graph() noexcept
{
    auto g = create_empty_named_edges_and_vertices_graph();
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto vertex_descriptor_b = boost::add_vertex(g);
    const auto vertex_descriptor_c = boost::add_vertex(g);
    const auto edge_insertion_result_ab
        = boost::add_edge(vertex_descriptor_a,
            vertex_descriptor_b, g);
    assert(edge_insertion_result_ab.second);
    const auto edge_insertion_result_bc
        = boost::add_edge(vertex_descriptor_b,
            vertex_descriptor_c, g);
    assert(edge_insertion_result_bc.second);
    const auto edge_insertion_result_ca
        = boost::add_edge(vertex_descriptor_c,
            vertex_descriptor_a, g);
    assert(edge_insertion_result_ca.second);

    //Add vertex names
    auto vertex_name_map = boost::get(boost::vertex_name, g);
    ;
    vertex_name_map[vertex_descriptor_a] = "top";
    vertex_name_map[vertex_descriptor_b] = "right";
    vertex_name_map[vertex_descriptor_c] = "left";

    //Add edge names
    auto edge_name_map = boost::get(boost::edge_name, g);
    edge_name_map[edge_insertion_result_ab.first] = "AB";
    edge_name_map[edge_insertion_result_bc.first] = "BC";
    edge_name_map[edge_insertion_result_ca.first] = "CA";

    return g;
}
```

Most of the code is a repeat of algorithm 8. In the end, the edge names are obtained as a `boost::property_map` and set.

## 2.12 Create an empty graph with custom vertices

Say we want to use our own vertex class as graph nodes. This is done in multiple steps:

1. Create a custom vertex class, called 'my\_vertex'
2. Install a new property, called 'vertex\_custom\_type'
3. Use the new property in creating a `boost::adjacency_list`

### 2.12.1 Creating the custom vertex class

In this example, I create a custom vertex class. Here I will show the header file of it, as the implementation of it is not important yet.

---

**Algorithm 12** Declaration of `my_vertex`

---

```
#ifndef MY_VERTEX_H
#define MY_VERTEX_H

#include <string>

class my_vertex
{
public:
    my_vertex(
        const std::string& name = "",
        const std::string& description = "",
        const double x = 0.0,
        const double y = 0.0
    );
    std::string m_name;
    std::string m_description;
    double m_x;
    double m_y;
};

bool operator==(const my_vertex& lhs, const my_vertex&
    rhs) noexcept;

#endif // MY_VERTEX_H
```

---

my\_vertex is a class that has multiple properties: two doubles 'm\_x' ('m\_' stands for member) and 'm\_y', and two std::strings m\_name and m\_description. my\_vertex is copyable, but cannot trivially be converted to a std::string.

### 2.12.2 Installing the new property

Installing a new property would have been easier, if 'more C++ compilers were standards conformant' ([1], chapter 3.6, footnote at page 52). Boost.Graph uses the BOOST\_INSTALL\_PROPERTY macro to allow using a custom property:

---

**Algorithm 13** Installing the vertex\_custom\_type property

---

```
#include <boost/graph/properties.hpp>

namespace boost {
    enum vertex_custom_type_t { vertex_custom_type = 314 };
    BOOST_INSTALL_PROPERTY(vertex, custom_type);
}
```

---

The enum value 314 must be unique.

### 2.12.3 Create the empty graph with custom vertices

---

**Algorithm 14** Creating an empty graph with custom vertices

---

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_vertex
    >
>
>
create_empty_custom_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_custom_type_t, my_vertex
        >
    >();
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a custom type, that is of data type `my_vertex` (due to the `boost::property< boost::vertex_custom_type_t, my_vertex>`)
- The edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property< boost::vertex_custom_type_t, my_vertex>`'. This can be read as: "vertices have the property '`boost::vertex_custom_type_t`', which is of data type '`my_vertex`'". Or simply: "vertices have a custom type called `my_vertex`".



## 2.13 Add a custom vertex

Adding a custom vertex is very similar to adding a named vertex (chapter 7).

---

**Algorithm 15** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_vertex.h"

template <typename graph>
void add_custom_vertex(graph& g, const my_vertex& v)
{
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto my_vertex_map = boost::get(boost::
        vertex_custom_type, g);
    my_vertex_map[vertex_descriptor_a] = v;
}
```

---

When having added a new (abstract) vertex to the graph, the vertex descriptor is used to set the my\_vertex in the graph its my\_vertex map (using 'boost::get(boost::vertex\_custom\_type,g)').

## 2.14 Creating $K_2$ with custom vertices

We reproduce the  $K_2$  with named vertices of chapter 2.8 , but with our custom vertices instead:

---

**Algorithm 16** Creating  $K_2$  as depicted in figure 2

---

```
#include "install_vertex_custom_type.h"
#include "my_vertex.h"
#include "create_empty_custom_vertices_graph.h"

#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_vertex
    >
>
>
create_custom_vertices_k2_graph() noexcept
{
    auto g = create_empty_custom_vertices_graph();
    const auto vertex_descriptor_a = boost::add_vertex(g);
    const auto vertex_descriptor_b = boost::add_vertex(g);
    const auto edge_insertion_result
        = boost::add_edge(vertex_descriptor_a,
            vertex_descriptor_b, g);
    assert(edge_insertion_result.second);

    //Add names
    auto my_vertex_name_map = boost::get(boost::
        vertex_custom_type, g);
    my_vertex_name_map[vertex_descriptor_a]
        = my_vertex("from", "source", 0.0, 0.0);
    my_vertex_name_map[vertex_descriptor_b]
        = my_vertex("to", "target", 3.14, 3.14);

    return g;
}
```

---

Most of the code is a slight modification of algorithm 8. In the end, the `my_vertices` are obtained as a `boost::property_map` and set with two custom `my_vertex` objects.

### 2.15 Create an empty graph with custom edges and vertices

### 2.16 Add a custom edge

### 2.17 Creating $K_2$ with custom edges and vertices

Instead of using edges with a name, or other properties, here we use a custom edge class called 'my\_edge'.

## 3 Measuring simple graphs traits

Measuring simple traits of the graphs created allows you to debug your code.

### 3.1 Getting the vertices

You can use `boost::vertices` to obtain an iterator pair. The first iterator points to the first vertex, the second points to beyond the last vertex.

### 3.2 Getting the edges

You can use `boost::edges` to obtain an iterator pair. The first iterator points to the first edge, the second points to beyond the last edge.

### 3.3 Counting the number of vertices

Use `boost::num_vertices`, as shown here:

---

**Algorithm 17** Count the number of vertices

---

```
#include <boost/graph/adjacency_list.hpp>

//Get the number of vertices a graph has
template <class graph>
int get_n_vertices(const graph& g)
{
    return static_cast<int>(boost::num_vertices(g));
}
```

---

### 3.4 Counting the number of edges

Use `boost::num_edges`, as shown here:

---

**Algorithm 18** Count the number of edges

---

```
#include <boost/graph/adjacency_list.hpp>

//Get the number of edges a graph has
template <class graph>
int get_n_edges(const graph& g)
{
    return static_cast<int>(boost::num_edges(g));
}
```

---

### 3.5 Getting the vertices' names

When the vertices of a graph have named vertices, one can extract them as such:

---

**Algorithm 19** Get the vertices' names

---

```
#include <string>
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_vertex_names(const graph& g)
{
    std::vector<std::string> v;

    const auto vertex_name_map = get(boost::vertex_name, g);

    for (auto p = vertices(g);
         p.first != p.second;
         ++p.first) {
        v.emplace_back(get(vertex_name_map, *p.first));
    }
    return v;
}
```

---

The names of the vertices are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the vertices' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

### 3.6 Getting the edges' names

When the edges of a graph have named vertices, one can extract them as such:

---

**Algorithm 20** Get the edges' names

---

```
#include <string>
#include <vector>
#include <boost/graph/adjacency_list.hpp>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_edge_names(const graph& g)
{
    std::vector<std::string> v;

    const auto edge_name_map = get(boost::edge_name, g);

    for (auto p = boost::edges(g);
         p.first != p.second;
         ++p.first) {
        v.emplace_back(get(edge_name_map, *p.first));
    }
    return v;
}
```

---

The names of the edges are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the edges' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

### 3.7 Getting the vertices' my\_vertexes<sup>1</sup>

When the vertices of a graph have any associated `my_vertex`, one can extract these as such:

---

<sup>1</sup>the name 'my\_vertexes' is chosen to indicate this function returns a container of `my_vertex`

---

**Algorithm 21** Get the vertices' my\_vertexes

---

```
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "install_vertex_custom_type.h"
#include "my_vertex.h"

//TODO: generalize to return any type
template <typename graph>
std::vector<my_vertex> get_vertex_my_vertexes(const graph
& g)
{
    std::vector<my_vertex> v;

    const auto my_vertexes_map = get(boost::
vertex_custom_type, g);

    for (auto p = vertices(g);
        p.first != p.second;
        ++p.first) {
        v.emplace_back(get(my_vertexes_map, *p.first));
    }
    return v;
}
```

---

The my\_vertex object associated with the vertices are obtained from a boost::property\_map and then put into a std::vector.

When trying to get the vertices' my\_vertex from a graph without my\_vertex objects associated, you will get the error 'formed reference to void' (for example, with the code 'get\_vertex\_my\_vertexes(create\_k2\_graph());').

### 3.8 Count vertex name

count\_vertices\_with\_name

### 3.9 Find a vertex by its name

find\_vertex\_with\_name

### 3.10 Get a named vertex its in-degree

get\_named\_vertex\_in\_degree

- degree\_size\_type in\_degree(vertex\_descriptor u, const adjacency\_list& g) . Returns the in-degree of a vertex

### 3.11 Get a named vertex its out-degree

`get_named_vertex_out_degree`

- `degree_size_type in_degree(vertex_descriptor u, const adjacency_list& g)` . Returns the in-degree of a vertex

### 3.12 Count vertex `my_vertex`

`count_vertex_my_vertex`

### 3.13 Find a `my_vertex`

`find_my_vertex`

### 3.14 Find the vertices connected to a certain `my_vertex`

`find_vertices_connected_to_my_vertex`

## 4 Modifying simple graphs traits

It is useful to be able to modify every aspect of a graph. Adding nodes and edges are found in earlier chapters.

### 4.1 Setting all vertices' names

When the vertices of a graph have named vertices, one set their names as such:

---

**Algorithm 22** Setting the vertices' names

---

```
#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize 'names'
template <typename graph>
void set_vertex_names(
    graph& g,
    const std::vector<std::string>& names
)
{
    const auto vertex_name_map = get(boost::vertex_name, g);

    auto names_begin = std::begin(names);
    const auto names_end = std::end(names);
    for (auto vi = vertices(g);
        vi.first != vi.second;
        ++vi.first, ++names_begin)
    {
        assert(names_begin != names_end);
        put(vertex_name_map, *vi.first, *names_begin);
    }
}
```

---

An impressive feature is that getting the property map holding the graph its names is not a copy, but a reference. Otherwise, modifying 'name\_map' (obtained by non-reference) would only modify a copy.

## 4.2 Setting all vertices' my\_vertex objects

When the vertices of a graph are associated with my\_vertex objects, one can set these my\_vertexes as such:



---

**Algorithm 23** Setting the vertices' `my_vertexes`

---

```
#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

#include "install_vertex_custom_type.h"
#include "my_vertex.h"

//TODO: generalize 'my_vertexes'
template <typename graph>
void set_vertex_my_vertexes(
    graph& g,
    const std::vector<my_vertex>& my_vertexes
)
{
    const auto my_vertex_map = get(boost::
        vertex_custom_type, g);

    auto my_vertexes_begin = std::begin(my_vertexes);
    const auto my_vertexes_end = std::end(my_vertexes);
    for (auto vi = vertices(g);
        vi.first != vi.second;
        ++vi.first, ++my_vertexes_begin)
    {
        assert(my_vertexes_begin != my_vertexes_end);
        put(my_vertex_map, *vi.first, *my_vertexes_begin);
    }
}
```

---

An impressive feature is that getting the property map holding the graph its names is not a copy, but a reference. Otherwise, modifying 'my\_vertexes\_map' (obtained by non-reference) would only modify a copy.

### 4.3 Replace a vertex its name

rename\_vertex

### 4.4 Replace an edge its name

rename\_edge

## 4.5 Replace a my\_vertex

replace\_my\_vertex

## 4.6 Clear a named vertex

clear\_named\_vertex

- void clear\_vertex(vertex\_descriptor u, adjacency\_list& g) . Removes all edges to and from u
- void clear\_out\_edges(vertex\_descriptor u, adjacency\_list& g) . Removes all outgoing edges from vertex u in the directed graph g (not applicable for undirected graphs)
- void clear\_in\_edges(vertex\_descriptor u, adjacency\_list& g) . Removes all incoming edges from vertex u in the directed graph g (not applicable for undirected graphs)

## 4.7 Remove a named vertex

remove\_named\_vertex

## 4.8 Remove a named edge

remove\_named\_vertex

- void remove\_edge(vertex\_descriptor u, vertex\_descriptor v, adjacency\_list& g) . Removes an edge from g
- void remove\_edge(edge\_descriptor e, adjacency\_list& g) . Removes an edge from g

## 4.9 Remove a my\_vertex

remove\_my\_vertex

- void remove\_vertex(vertex\_descriptor u, adjacency\_list& g) . Removes a vertex from graph g (It is expected that all edges associated with this vertex have already been removed using clear\_vertex or another appropriate function.)

# 5 Visualizing graphs

Before graphs are visualized, they are stored as a file first. Here, I use the .dot file format.

## 5.1 Storing a graph as a .dot

Graph are easily saved to a .dot file:

---

**Algorithm 24** Storing a graph as a .dot file

---

```
#include <fstream>
#include <boost/graph/graphviz.hpp>

///Save a graph to a .dot file
template <typename graph>
void save_graph_to_dot(const graph& g, const std::string&
    filename)
{
    std::ofstream f(filename);
    boost::write_graphviz(f,g);
}
```

---

Using the `create_k2_graph` function (algorithm 5) to create a  $K_2$  graph, the .dot file created is displayed in algorithm 25:

---

**Algorithm 25** .dot file created from the `create_k2_graph` function (algorithm 5)

---

```
digraph G {
0;
1;
0->1 ;
}
```

---

This .dot file corresponds to figure 4:




Figure 4: .svg file created from the `create_k2_graph` function (algorithm 5)

If you used the `create_named_vertices_k2_graph` function (algorithm 8) to produce a  $K_2$  graph with named vertices, you see that the `.dot` file does not have stored the vertex names:

---

**Algorithm 26** `.dot` file created from the `create_named_vertices_k2_graph` function (algorithm 8)

---

```
graph G {
0;
1;
0--1 ;
}
```

---

So, the `'save_graph_to_dot'` function (algorithm 24) saves the structure of the graph.

## 5.2 Storing a graph with named vertices as a `.dot`

If you used the `create_named_vertices_k2_graph` function (algorithm 8) to produce a  $K_2$  graph with named vertices, you can store these names additionally with algorithm 27:

---

**Algorithm 27** Storing a graph with named vertices as a `.dot` file

---

```
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_vertices_graph_to_dot(const graph& g,
    const std::string& filename)
{
    std::ofstream f(filename);
    const auto names = get_vertex_names(g);
    boost::write_graphviz(f,g,boost::make_label_writer(&
        names[0]));
}
```

---

The `.dot` file created is displayed in algorithm 28:

---

**Algorithm 28** .dot file created from the create\_named\_vertices\_k2\_graph function (algorithm 8)

---

```
graph G {
0[label=from];
1[label=to];
0--1 ;
}
```

---

This .dot file corresponds to figure 5:




Figure 5: .svg file created from the create\_k2\_graph function (algorithm 8)

If you used the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 11) to produce a  $K_3$  graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

---

**Algorithm 29** .dot file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 11)

---

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 ;
1--2 ;
2--0 ;
}
```

---

So, the 'save\_named\_vertices\_graph\_to\_dot' function (algorithm 24) saves only the structure of the graph and its vertex names.

### 5.3 Storing a graph with named vertices and edges as a .dot

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 11) to produce a  $K_3$  graph with named edges and vertices, you can store these names additionally with algorithm 30:

---

**Algorithm 30** Storing a graph with named edges and vertices as a .dot file

---

```
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_edge_names.h"
#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_edges_and_vertices_graph_to_dot(const
    graph& g, const std::string& filename)
{
    std::ofstream f(filename);
    const auto vertex_names = get_vertex_names(g);
    const auto edge_name_map = boost::get(boost::edge_name,
        g);
    boost::write_graphviz(
        f,
        g,
        boost::make_label_writer(&vertex_names[0]),
        [edge_name_map](std::ostream& out, const auto& e) {
            out << "[label=\"" << edge_name_map[e] << "\"]";
        }
    );
}
```

---

Note that this algorithm uses C++17.

The .dot file created is displayed in algorithm 31:

---

**Algorithm 31** .dot file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 8)

---

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}
```

---

This .dot file corresponds to figure 6:




Figure 6: .svg file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 8)

If you used the MORE\_COMPLEX\_create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 11) to produce a  $K_3$  graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

---

**Algorithm 32** .dot file created from the MORE\_COMPLEX\_create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 11)

---

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}
```

---

So, the 'save\_named\_edges\_and\_vertices\_graph\_to\_dot' function (algorithm 24) saves only the structure of the graph and its edge and vertex names.

## 5.4 Storing a graph with custom vertices as a .dot

If you used the create\_custom\_vertices\_k2\_graph function (algorithm 16) to produce a  $K_2$  graph with vertices associated with my\_vertex objects, you can store these my\_vertexes additionally with algorithm 33:



---

**Algorithm 33** Storing a graph with custom vertices as a .dot file

---

```
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_my_vertexes.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_custom_vertices_graph_to_dot(const graph& g,
    const std::string& filename)
{
    std::ofstream f(filename);
    const auto my_vertexes = get_vertex_my_vertexes(g);
    boost::write_graphviz(
        f,
        g,
        [my_vertexes](std::ostream& out, const auto& v) {
            const my_vertex m{my_vertexes[v]};
            out << "[label=\""
                << m.m_name
                << ", "
                << m.m_description
                << ", "
                << m.m_x
                << ", "
                << m.m_y
                << "\"\"]";
        })
    );
}
```

---

Note that this algorithm uses C++17.

The .dot file created is displayed in algorithm 34:

---

**Algorithm 34** .dot file created from the create\_custom\_vertices\_k2\_graph function (algorithm 8)

---

```
graph G {
0[label="from,source,0,0"];
1[label="to,target,3.14,3.14"];
0--1 ;
}
```

---

This .dot file corresponds to figure 34:




Figure 7: .svg file created from the `create_custom_vertices_k2_graph` function (algorithm 16)

## 6 Measuring more complex graphs traits

### 6.1 Count the number of self-loops

#### References

- [1] Jeremy G Siek, Lie-Quan Lee, and Andrew Lumsdaine. *Boost Graph Library: User Guide and Reference Manual, The*. Pearson Education, 2001.

## Index

- $K_2$  with named vertices, create, 8
- $K_2$ , create, 6
- $K_3$  with named edges and vertices, create, 11
- Add a vertex, 4
- Add an edge, 5
- Add named edge, 11
- Add named vertex, 8
- add\_edge, 5
- add\_named\_edge, 11
- add\_named\_vertex, 8, 17
- add\_vertex, 5
- assert, 6
- boost::add\_edge, 5, 6, 11
- boost::add\_vertex, 4, 6
- boost::adjacency\_list, 3, 4, 6, 8, 10, 16
- boost::adjacency\_matrix, 3, 4
- boost::edge\_name\_t, 10
- boost::get, 8, 17
- boost::num\_edges, 19
- boost::num\_vertices, 19
- boost::property, 7, 8, 10, 16
- boost::undirectedS, 6, 7, 10, 16
- boost::vecS, 7, 10, 16
- boost::vertex\_custom\_type, 17
- boost::vertex\_custom\_type\_t, 16
- boost::vertex\_name, 8
- boost::vertex\_name\_t, 7, 8, 10
- BOOST\_INSTALL\_PROPERTY, 15
- C++17, 30, 33
- Counting the number of edges, 19
- Counting the number of vertices, 19
- Create  $K_2$ , 6
- Create  $K_2$  with named vertices, 8
- Create  $K_3$  with named edges and vertices, 11
- Create .dot from graph, 27
- Create .dot from graph with custom vertices, 32
- Create .dot from graph with named edges and vertices, 30
- Create .dot from graph with named vertices, 28
- Create an empty directed graph, 3
- Create an empty graph, 4
- Create an empty graph with named edges and vertices, 9
- Create an empty graph with named vertices, 7
- create\_custom\_vertices\_k2\_graph, 18
- create\_empty\_custom\_vertices\_graph, 16
- create\_empty\_directed\_graph, 3
- create\_empty\_named\_edges\_and\_vertices\_graph, 10
- create\_empty\_named\_vertices\_graph, 7
- create\_empty\_undirected\_graph, 4
- create\_k2\_graph, 6
- create\_named\_edges\_and\_vertices\_k3, 13
- create\_named\_vertices\_k2\_graph, 9
- Declaration, my\_vertex, 14
- edge descriptor, 11
- Edge, add, 5
- Edges, counting, 19
- Empty directed graph, create, 3
- Empty graph with named edges and vertices, create, 9
- Empty graph with named vertices, create, 7
- Empty graph, create, 4
- formed reference to void, 20, 22
- get\_edge\_names, 21
- get\_n\_edges, 20
- get\_n\_vertices, 19
- get\_vertex\_my\_vertexes, 22
- get\_vertex\_names, 20
- install\_vertex\_custom\_type, 15

- m\_, 15
- macro, 15
- member, 15
- my\_vertex, 14, 16
- my\_vertex declaration, 14
- my\_vertex.h, 14
  
- Named edge, add, 11
- Named edges and vertices, create empty graph, 9
- Named vertex, add, 8
- Named vertices, create empty graph, 7
  
- pi, 15, 34
  
- Save graph as .dot, 27
- Save graph with custom vertices as .dot, 32
- Save graph with name edges and vertices as .dot, 30
- Save graph with name vertices as .dot, 28
- save\_custom\_vertices\_graph\_to\_dot, 33
- save\_graph\_to\_dot, 27
- save\_named\_edges\_and\_vertices\_graph\_to\_dot, 30
- save\_named\_vertices\_graph\_to\_dot, 28
- Set vertices my\_vertexes, 24
- Set vertices names, 23
- set\_vertex\_my\_vertexes, 25
- set\_vertex\_names, 24
- std::pair, 5
  
- vd, 5
- Vertex descriptor, 5, 6
- Vertex, add, 4
- Vertex, add named, 8
- vertex\_custom\_type, 14
- Vertices, counting, 19
- Vertices, set my\_vertexes, 24
- Vertices, set names, 23