

Boost.Graph tutorial

Richel Bilderbeek

December 6, 2015

Contents

1	Introduction	2
1.1	Coding style used	2
1.2	Pitfalls	2
2	Building graphs	2
2.1	Creating an empty graph	3
2.2	Add a vertex	3
2.3	Add an edge	4
2.4	Creating K_2 , a fully connected graph with two vertices	4
2.5	Creating an empty graph with named vertices	6
2.6	Add a vertex with a name	7
2.7	Creating K_2 with named vertices	8
2.8	Creating an empty graph with named edges and vertices	10
2.9	Add an edge with a name	11
2.10	Creating K_3 with named edges and vertices	12
2.11	Create an empty graph with custom vertices	15
2.12	Add a custom vertex	15
2.13	Creating K_2 with custom vertices	15
2.14	Add a custom edge	15
2.15	Creating K_2 with custom edges and vertices	15
3	Measuring simple graphs traits	15
3.1	Getting the vertices	15
3.2	Getting the edges	15
3.3	Counting the number of vertices	15
3.4	Counting the number of edges	16
3.5	Getting the vertices' names	17
3.6	Getting the edges' names	19
3.7	Find a vertex by its name	21
3.8	Replace a vertex its name	21
4	Modifying simple graphs traits	21
4.1	Setting all vertices' names	21

5	Visualizing graphs	23
5.1	Storing a graph as a .dot	23
5.2	Storing a graph with named vertices as a .dot	24
5.3	Storing a graph with named vertices and edges as a .dot	26
6	TODO's in general	29
6.1	Personal experiences with Boost.Graph	29
6.2	To add	30
7	Graph of this tutorial	30

1 Introduction

I needed this tutorial in 2006, when I started experimenting with Boost.Graph. More specifically, I needed a tutorial that:

- Orders concepts chronologically
- Increases complexity gradually
- Shows complete pieces of code

What I had were the book [1] and the Boost.Graph website, both did not satisfy these requirements.

1.1 Coding style used

I use the coding style from the Core C++ Guidelines.

I prefer not to use the keyword `auto`, but to explicitly mention the type instead. I think this is beneficial to beginners. When using Boost.Graph in production code, I do prefer to use `auto`.

OTOH, while writing this tutorial, I use `auto` when I loose too much time figuring out the type

All coding snippets are taken from compiled C++ code.

1.2 Pitfalls

The choice between `'boost::get'`, `'std::get'` and `'get'`. AFAIKS, when in doubt, use `'get'`.

2 Building graphs

Boost.Graph is about creating graphs. In this chapter we create graphs, starting from simple to more complex.

2.1 Creating an empty graph

Let's create a trivial empty graph:

Algorithm 1 Creating an empty graph

```
#include "create_empty_graph.h"

boost::adjacency_list<
create_empty_graph() noexcept
{
    return boost::adjacency_list<>();
}
```

Congratulations, you've just created a `boost::adjacency_list` in which:

- The out edges are stored in a `std::vector`
- The vertices are stored in a `std::vector`
- The graph is directed
- Vertices, edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` is the most commonly used graph type, the other is the `boost::adjacency_matrix`.

2.2 Add a vertex

To add a vertex to a graph, the `boost::add_vertex` function is used as such:

Algorithm 2 Adding a vertex to a graph

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_vertex(graph& g)
{
    boost::add_vertex(g);
}
```

Note that `boost::add_vertex` returns a vertex descriptor, which is ignored for now. A vertex descriptor can be used to, for example, connect two vertices by an edge

2.3 Add an edge

To add an edge to a graph, two vertex descriptors are needed. A vertex descriptor is a handle to the vertex with in graph. Algorithm 3 adds two vertices to a graph, and connects these two using `boost::add_edge`:

Algorithm 3 Adding (two vertices and) an edge to a graph

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_edge(graph& g)
{
    using boost::graph_traits;
    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;

    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);

    assert(ea.second);
}
```

Note that half of the code consists out of using statements. This algorithm only shows how to add an isolated edge to a graph, instead of allowing for graphs with higher connectivities. The function `boost::add_edge` returns a `std::pair`, consisting of an edge descriptor and a boolean success indicator. In algorithm 3 we assert that this insertion was successful. Insertion can fail if an edge is already present and duplicates are not allowed.

2.4 Creating K_2 , a fully connected graph with two vertices

To create a fully connected graph with two vertices (also called K_2), one needs two vertices and one (undirected) edge, as depicted in figure 1.




Figure 1: K_2 : a fully connected graph with two vertices named a and b

To create K_2 , the following code can be used:

Algorithm 4 Creating K_2 as depicted in figure 1

```
#include "create_k2_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_k2_graph() noexcept
{
    using boost::graph_traits;

    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS
    >;

    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);
    return g;
}
```

Note that this code has more lines of using statements than actual code! In

this code, the third template argument of `boost::adjacency_list` is `boost::undirectedS`, to select (that is what the `S` means) for an undirected graph. Adding a vertex with `boost::add_vertex` results in a vertex descriptor, which is a handle to the vertex added to the graph. Two vertex descriptors are then used to add an edge to the graph. Adding an edge using `boost::add_edge` returns two things: an edge descriptor and a boolean indicating success. In the code example, we assume insertion is successful.

Note that the graph lacks all properties: nodes do not have names, nor do edges.

2.5 Creating an empty graph with named vertices

Let's create a trivial empty graph, in which the vertices can have a name:

Algorithm 5 Creating an empty graph with named vertices

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
create_empty_named_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    >
    >;

    graph g;
    return g;
}
```

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)

- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- Edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property< boost::vertex_name_t, std::string>`'. This can be read as: “vertices have the property '`boost::vertex_name_t`', that is of data type '`std::string`’”. Or simply: “vertices have a name that is stored as a `std::string`”.

2.6 Add a vertex with a name

Adding a vertex without a name was trivially easy (see chapter 2). Adding a vertex with a name is less easy:

Algorithm 6 Add a vertex with a name

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_named_vertex(graph& g, const std::string& name)
{
    using boost::graph_traits;
    using boost::property_map;
    using boost::vertex_name_t;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using name_map_t
        = typename property_map<graph, vertex_name_t>::type;

    const vertex_descriptor vd{
        boost::add_vertex(g)
    };

    name_map_t name_map{boost::get(boost::vertex_name, g)};
    name_map[vd] = name;
}
```

Instead of calling '`boost::add_vertex`' with an additional argument containing the name of the vertex, multiple things need to be done. When adding a new vertex to the graph, the vertex descriptor is stored. After obtaining the

name map from the graph (using `'boost::get(boost::vertex_name,g)'`), the name of the vertex is set using that vertex descriptor.

2.7 Creating K_2 with named vertices

We extend K_2 of chapter 2.4 by naming the vertices 'from' and 'to', as depicted in figure 2:




Figure 2: K_2 : a fully connected graph with two vertices with the text 'from' and 'to'

To create K_2 , the following code can be used:

Algorithm 7 Creating K_2 as depicted in figure 2

```
#include "create_named_vertices_k2_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>
>
create_named_vertices_k2_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using name_map_t
        = boost::property_map<graph, boost::vertex_name_t>::
            type;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);

    //Add names
    name_map_t name_map{boost::get(boost::vertex_name, g)};
    name_map[va] = "from";
    name_map[vb] = "to";

    return g;
}
```

Most of the code is a repeat of algorithm 4. In the end, the names are obtained as a `boost::property_map` and `set`.

2.8 Creating an empty graph with named edges and vertices

Let's create a trivial empty graph, in which the both the edges and vertices can have a name:

Algorithm 8 Creating an empty graph with named edges and vertices

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_empty_named_edges_and_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    >;

    graph g;
    return g;
}
```

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)

- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- The edges have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::edge_name_t, std::string>`)
- The graph has no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fifth template argument '`boost::property< boost::edge_name_t, std::string>`'. This can be read as: “edges have the property '`boost::edge_name_t`', that is of data type '`std::string`'”. Or simply: “edges have a name that is stored as a `std::string`”.

2.9 Add an edge with a name

Adding an edge with a name:

Algorithm 9 Add a vertex with a name

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_named_edge(graph& g, const std::string&
    edge_name)
{
    using boost::edge_name_t;
    using boost::graph_traits;
    using boost::property_map;
    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using name_map_t
        = typename property_map<graph, edge_name_t>::type;

    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);

    assert(ea.second);

    name_map_t name_map{
        boost::get(boost::edge_name, g)
    };
    name_map[ea.first] = edge_name;
}
```

In this code snippet, the edge descriptor when using 'boost::add_edge' is used as a key to change the edge name map.

2.10 Creating K_3 with named edges and vertices

We extend the graph K_2 with named vertices of chapter 2.7 by adding names to the edges, as depicted in figure 3:




Figure 3: K_3 : a fully connected graph with three named edges and vertices

To create K_3 , the following code can be used:

Algorithm 10 Creating K_3 as depicted in figure 3

```
#include "create_named_edges_and_vertices_k3_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_named_edges_and_vertices_k3_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using vertex_name_map_t
        = boost::property_map<graph, boost::vertex_name_t>::
            type;
    using edge_name_map_t
        = boost::property_map<graph, boost::edge_name_t>::type
        ;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const vertex_descriptor vc = boost::add_vertex(g);
    const edge_insertion_result eab
        = boost::add_edge(va, vb, g);
    assert(eab.second);
    const edge_insertion_result ebc
        = boost::add_edge(vb, vc, g);
    assert(ebc.second);
    const edge_insertion_result eca
        = boost::add_edge(vc, va, g);
    assert(eca.second);

    //Add vertex names
    vertex_name_map_t vertex_name_map{boost::get(boost::
        vertex_name, g)};
```

Most of the code is a repeat of algorithm 7. In the end, the edge names are obtained as a `boost::property_map` and set.

2.11 Create an empty graph with custom vertices

2.12 Add a custom vertex

2.13 Creating K_2 with custom vertices

Instead of using vertices with a name, or other properties, here we use a custom vertex class called `'my_vertex'`. A `'my_vertex'` has an x coordinat, y coordinat, a name and a description.

2.14 Add a custom edge

2.15 Creating K_2 with custom edges and vertices

Instead of using edges with a name, or other properties, here we use a custom edge class called `'my_edge'`.

3 Measuring simple graphs traits

Measuring simple traits of the graphs created allows you to debug your code.

3.1 Getting the vertices

You can use `boost::vertices` to obtain an iterator pair. The first iterator points to the first vertex, the second points to beyond the last vertex.

3.2 Getting the edges

You can use `boost::edges` to obtain an iterator pair. The first iterator points to the first edge, the second points to beyond the last edge.

3.3 Counting the number of vertices

Use `boost::num_vertices`, as shown here:

Algorithm 11 Count the numbe of vertices

```
#ifndef GET_N_VERTICES_H
#define GET_N_VERTICES_H

#include <utility>
#include <boost/graph/adjacency_list.hpp>

///Get the number of vertices a graph has
template <class graph>
int get_n_vertices(const graph& g)
{
    return static_cast<int>(boost::num_vertices(g));
}

void get_n_vertices_test() noexcept;

#endif // GET_N_VERTICES_H
```

3.4 Counting the number of edges

Use boost::num_edges, as show here:

Algorithm 12 Count the number of edges

```
#ifndef GET_N_EDGES_H
#define GET_N_EDGES_H

#include <utility>
#include <boost/graph/adjacency_list.hpp>

///Get the number of edges a graph has
template <class graph>
int get_n_edges(const graph& g)
{
    return static_cast<int>(boost::num_edges(g));
}

void get_n_edges_test() noexcept;

#endif // GET_N_EDGES_H
```

3.5 Getting the vertices' names

When the vertices of a graph have named vertices, one can extract them as such:

Algorithm 13 Get the vertices' names

```
#ifndef GET_VERTEX_NAMES_H
#define GET_VERTEX_NAMES_H

#include <string>
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_vertex_names(const graph& g)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    std::vector<std::string> v;

    //TODO: remove auto
    const auto name_map = get(boost::vertex_name, g);

    for (vertex_iterators p = vertices(g);
        p.first != p.second;
        ++p.first)
    {
        v.emplace_back(get(name_map, *p.first));
    }
    return v;
}

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_vertex_names_DOESNOTWORK(
    const graph& g)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;
    using name_map_t
        = typename boost::property_map<graph, boost::
            vertex_name_t>::type;

    std::vector<std::string> v;18

    const name_map_t name_map = get(boost::vertex_name, g);

    for (vertex_iterators p = vertices(g);
        p.first != p.second;
        ++p.first)
    {
```

The names of the vertices are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the vertices' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

3.6 Getting the edges' names

When the edges of a graph have named vertices, one can extract them as such:

Algorithm 14 Get the edges' names

```
#ifndef GET_EDGE_NAMES_H
#define GET_EDGE_NAMES_H

#include <string>
#include <vector>
#include <boost/graph/adjacency_list.hpp>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_edge_names(const graph& g)
{
    using boost::graph_traits;
    using edge_iterator
        = typename graph_traits<graph>::edge_iterator;
    using edge_iterators
        = std::pair<edge_iterator, edge_iterator>;

    std::vector<std::string> v;

    //TODO: remove auto
    const auto name_map = get(boost::edge_name, g);

    for (edge_iterators p = boost::edges(g);
         p.first != p.second;
         ++p.first)
    {
        v.emplace_back(get(name_map, *p.first));
    }
    return v;
}

void get_edge_names_test() noexcept;

#endif // GET_EDGE_NAMES_H
```

The names of the edges are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the edges' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

3.7 Find a vertex by its name

3.8 Replace a vertex its name

4 Modifying simple graphs traits

It is useful to be able to modify every aspect of a graph. Adding nodes and edges are found in earlier chapters.

4.1 Setting all vertices' names

When the vertices of a graph have named vertices, one set their names as such:

Algorithm 15 Setting the vertices' names

```
#ifndef SET_VERTEX_NAMES_H
#define SET_VERTEX_NAMES_H

#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize 'names'
template <typename graph>
void set_vertex_names(
    graph& g,
    const std::vector<std::string>& names
)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    const auto name_map = get(boost::vertex_name, g);

    auto names_begin = std::begin(names);
    const auto names_end = std::end(names);
    for (vertex_iterators vi = vertices(g);
        vi.first != vi.second;
        ++vi.first, ++names_begin)
    {
        assert(names_begin != names_end);
        put(name_map, *vi.first, *names_begin);
    }
}

void set_vertex_names_test() noexcept;

#endif // SET_VERTEX_NAMES_H
```

An impressive feature is that getting the property map holding the graph its names is not a copy, but a reference. Otherwise, modifying 'name_map'

(obtained by non-reference) would only modify a copy.

5 Visualizing graphs

Before graphs are visualized, they are stored as a file first. Here, I use the .dot file format.

5.1 Storing a graph as a .dot

Graph are easily saved to a .dot file:

Algorithm 16 Storing a graph as a .dot file

```
#ifndef SAVE_GRAPH_TO_DOT_H
#define SAVE_GRAPH_TO_DOT_H

#include <fstream>
#include <boost/graph/graphviz.hpp>

///Save a graph to a .dot file
template <typename graph>
void save_graph_to_dot(const graph& g, const std::string&
    filename)
{
    std::ofstream f(filename);
    boost::write_graphviz(f,g);
}

void save_graph_to_dot_test() noexcept;

#endif // SAVE_GRAPH_TO_DOT_H
```

Using the `create_k2_graph` function (algorithm 4) to create a K_2 graph, the .dot file created is displayed in algorithm 17:

Algorithm 17 .dot file created from the `create_k2_graph` function (algorithm 4)

```
graph G {
0;
1;
0--1 ;
}
```

This .dot file corresponds to figure 4:




Figure 4: .svg file created from the `create_k2_graph` function (algorithm 4)

If you used the `create_named_vertices_k2_graph` function (algorithm 7) to produce a K_2 graph with named vertices, you see that the .dot file does not have stored the vertex names:

Algorithm 18 .dot file created from the `create_named_vertices_k2_graph` function (algorithm 7)

```

graph G {
0;
1;
0--1 ;
}

```

So, the 'save_graph_to_dot' function (algorithm 16) saves the structure of the graph.

5.2 Storing a graph with named vertices as a .dot

If you used the `create_named_vertices_k2_graph` function (algorithm 7) to produce a K_2 graph with named vertices, you can store these names additionally with algorithm 19:

Algorithm 19 Storing a graph with named vertices as a .dot file

```
#ifndef SAVE_NAMED_VERTICES_GRAPH_TO_DOT_H
#define SAVE_NAMED_VERTICES_GRAPH_TO_DOT_H

#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_vertices_graph_to_dot(const graph& g,
    const std::string& filename)
{
    std::ofstream f(filename);
    const auto names = get_vertex_names(g);
    boost::write_graphviz(f, g, boost::make_label_writer(&
        names[0]));
}

void save_named_vertices_graph_to_dot_test() noexcept;

#endif // SAVE_NAMED_VERTICES_GRAPH_TO_DOT_H
```

The .dot file created is displayed in algorithm 20:

Algorithm 20 .dot file created from the create_named_vertices_k2_graph function (algorithm 7)

```
graph G {
0[label=from];
1[label=to];
0--1 ;
}
```

This .dot file corresponds to figure 5:




Figure 5: .svg file created from the `create_k2_graph` function (algorithm 7)

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 10) to produce a K_3 graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

Algorithm 21 .dot file created from the `create_named_edges_and_vertices_k3_graph` function (algorithm 10)

```

graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 ;
1--2 ;
2--0 ;
}

```

So, the 'save_named_vertices_graph_to_dot' function (algorithm 16) saves only the structure of the graph and its vertex names.

5.3 Storing a graph with named vertices and edges as a .dot

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 10) to produce a K_3 graph with named edges and vertices, you can store these names additionally with algorithm 22:

Algorithm 22 Storing a graph with named edges and vertices as a .dot file

```
#ifndef SAVE_NAMED_EDGES_AND_VERTICES_GRAPH_TO_DOT
#define SAVE_NAMED_EDGES_AND_VERTICES_GRAPH_TO_DOT

#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_edge_names.h"
#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_edges_and_vertices_graph_to_dot(const
    graph& g, const std::string& filename)
{
    std::ofstream f(filename);
    const auto vertex_names = get_vertex_names(g);
    const auto edge_name_map = boost::get(boost::edge_name,
        g);
    boost::write_graphviz(
        f,
        g,
        boost::make_label_writer(&vertex_names[0]),
        [edge_name_map](std::ostream& out, const auto& e) {
            out << "[label=\"" << edge_name_map[e] << "\"]";
        }
    );
}

void save_named_edges_and_vertices_graph_to_dot_test()
    noexcept;

#endif // SAVE_NAMED_EDGES_AND_VERTICES_GRAPH_TO_DOT
```

The .dot file created is displayed in algorithm 23:

Algorithm 23 .dot file created from the create_named_edges_and_vertices_k3_graph function (algorithm 7)

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}
```

This .dot file corresponds to figure 6:




Figure 6: .svg file created from the create_named_edges_and_vertices_k3_graph function (algorithm 7)

If you used the MORE_COMPLEX_create_named_edges_and_vertices_k3_graph function (algorithm 10) to produce a K_3 graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

Algorithm 24 .dot file created from the
MORE_COMPLEX_create_named_edges_and_vertices_k3_graph func-
tion (algorithm 10)

```
graph G {  
0[label=top];  
1[label=right];  
2[label=left];  
0--1 [label="AB"];  
1--2 [label="BC"];  
2--0 [label="CA"];  
}
```

So, the 'save_named_edges_and_vertices_graph_to_dot' function (algorithm 16) saves only the structure of the graph and its edge and vertex names.

6 TODO's in general

6.1 Personal experiences with Boost.Graph

I have been experimenting with Boost.Graph since 2006 and I both use the documentation on the Boost website [1] and the book [1].

- Boost.Graph seems like the most type-safe extendable graph library around: learning it will pay off!
- Boost.Graph requires a good compiler, like GCC
- The book [2] will not help a beginner: all code snippets are written 'too smart', where a beginner might prefer four easy-to-understand lines, instead of one using magic. Most code snippets are scattered as part of a complete project, where a beginner might prefer simple short projects
- The website [1] will not help a beginner, for the same reasons as above
- I have never found Boost.Graph documentation or code snippets a beginner would understand (except for (hopefully) at my website), as if nobody understands Boost.Graph and/or everybody that understands Boost.Graph cannot explain simply anymore
- I learned most of Boost.Graph from my IDE (the helpful Qt Creator): by viewing the code that failed, I could understand what was expected for me. I would never have understood Boost.Graph if I would have used a text editor for programming

6.2 To add

Code snippets show include guards , use header_impl instead.

- `std::pair<edge_iterator, edge_iterator> edges(const adjacency_list& g)`
. Returns an iterator pair corresponding to the edges in graph g
- `vertex_descriptor source(edge_descriptor e, const adjacency_list& g)` .
Returns the source vertex of an edge
- `vertex_descriptor target(edge_descriptor e, const adjacency_list& g)` .
Returns the target vertex of an edge
- `degree_size_type in_degree(vertex_descriptor u, const adjacency_list& g)` .
Returns the in-degree of a vertex
- `degree_size_type out_degree(vertex_descriptor u, const adjacency_list& g)` .
Returns the out-degree of a vertex
- `void remove_edge(vertex_descriptor u, vertex_descriptor v, adjacency_list& g)` .
Removes an edge from g
- `void remove_edge(edge_descriptor e, adjacency_list& g)` .
Removes an edge from g
- `void clear_vertex(vertex_descriptor u, adjacency_list& g)` .
Removes all edges to and from u
- `void clear_out_edges(vertex_descriptor u, adjacency_list& g)` .
Removes all outgoing edges from vertex u in the directed graph g (not applicable for undirected graphs)
- `void clear_in_edges(vertex_descriptor u, adjacency_list& g)` .
Removes all incoming edges from vertex u in the directed graph g (not applicable for undirected graphs)
- `void remove_vertex(vertex_descriptor u, adjacency_list& g)` .
Removes a vertex from graph g (It is expected that all edges associated with this vertex have already been removed using `clear_vertex` or another appropriate function.)

7 Graph of this tutorial

This tutorial would not be complete with a graph that connects all chapter chronologically:




Figure 7: .svg file created from the create_tutorial_chapters_graph function

References

- [1] Jeremy G Siek, Lie-Quan Lee, and Andrew Lumsdaine. *Boost Graph Library: User Guide and Reference Manual, The*. Pearson Education, 2001.

Index

- K_2 with named vertices, create, 8
- K_2 , create, 4
- K_3 with named edges and vertices, create, 12
- Add a vertex, 3
- Add an edge, 4
- Add named edge, 11
- Add named vertex, 7
- add_edge, 4
- add_named_edge, 12
- add_named_vertex, 7
- add_vertex, 3
- assert, 4
- boost::add_edge, 4, 6, 12
- boost::add_vertex, 3, 6
- boost::adjacency_list, 3, 6, 7, 11
- boost::adjacency_matrix, 3
- boost::edge_name_t, 11
- boost::get(boost::vertex_name,g), 8
- boost::property, 7, 11
- boost::property<boost::edge_name_t, std::string>, 11
- boost::property<boost::vertex_name_t, std::string>, 7, 11
- boost::undirectedS, 6, 7, 10
- boost::vecS, 6, 10
- boost::vertex_name, 8
- boost::vertex_name_t, 7, 11
- Create K_2 , 4
- Create K_2 with named vertices, 8
- Create K_3 with named edges and vertices, 12
- Create an empty graph, 3
- Create an empty graph with named edges and vertices, 10
- Create an empty graph with named vertices, 6
- create_empty_graph, 3
- create_empty_named_edges_and_vertices_graph, 10
- create_empty_named_vertices_graph, 6
- create_k2_graph, 5
- create_named_edges_and_vertices_k3, 14
- create_named_vertices_k2_graph, 9
- create_tutorial_chapters_graph, 31
- edge descriptor, 12
- Edge, add, 4
- Empty graph with named edges and vertices, create, 10
- Empty graph with named vertices, create, 6
- Empty graph, create, 3
- Named edge, add, 11
- Named edges and vertices, create empty graph, 10
- Named vertex, add, 7
- Named vertices, create empty graph, 6
- std::pair, 4
- vertex_descriptor, 3, 4, 6
- Vertex, add, 3
- Vertex, add named, 7