

# Boost.Graph tutorial

Richel Bilderbeek

December 6, 2015

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Coding style used . . . . .	2
1.2	Pitfalls . . . . .	2
<b>2</b>	<b>Building graphs</b>	<b>2</b>
2.1	Creating an empty graph . . . . .	3
2.2	Add a vertex . . . . .	3
2.3	Add an edge . . . . .	4
2.4	Creating $K_2$ , a fully connected graph with two vertices . . . . .	4
2.5	Creating an empty graph with named vertices . . . . .	6
2.6	Add a vertex with a name . . . . .	7
2.7	Creating $K_2$ with named vertices . . . . .	8
2.8	Creating an empty graph with named edges and vertices . . . . .	10
2.9	Add an edge with a name . . . . .	11
2.10	Creating $K_3$ with named edges and vertices . . . . .	12
2.11	Create an empty graph with custom vertices . . . . .	15
2.12	Add a custom vertex . . . . .	15
2.13	Creating $K_2$ with custom vertices . . . . .	15
2.14	Add a custom edge . . . . .	15
2.15	Creating $K_2$ with custom edges and vertices . . . . .	15
<b>3</b>	<b>Measuring simple graphs traits</b>	<b>15</b>
3.1	Getting the vertices . . . . .	15
3.2	Getting the edges . . . . .	15
3.3	Counting the number of vertices . . . . .	15
3.4	Counting the number of edges . . . . .	16
3.5	Getting the vertices' names . . . . .	17
3.6	Getting the edges' names . . . . .	19
3.7	Find a vertex by its name . . . . .	21
3.8	Replace a vertex its name . . . . .	21
<b>4</b>	<b>Modifying simple graphs traits</b>	<b>21</b>
4.1	Setting all vertices' names . . . . .	21

<b>5</b>	<b>Visualizing graphs</b>	<b>23</b>
5.1	Storing a graph as a .dot . . . . .	23
5.2	Storing a graph with named vertices as a .dot . . . . .	24
5.3	Storing a graph with named vertices and edges as a .dot . . . . .	26
<b>6</b>	<b>TODO's in general</b>	<b>29</b>
6.1	Personal experiences with Boost.Graph . . . . .	29
6.2	To add . . . . .	30
<b>7</b>	<b>Graph of this tutorial</b>	<b>30</b>

## 1 Introduction

I needed this tutorial in 2006, when I started experimenting with Boost.Graph. More specifically, I needed a tutorial that:

- Orders concepts chronologically
- Increases complexity gradually
- Shows complete pieces of code

What I had were the book [1] and the Boost.Graph website, both did not satisfy these requirements.

### 1.1 Coding style used

I use the coding style from the Core C++ Guidelines.

I prefer not to use the keyword `auto`, but to explicitly mention the type instead. I think this is beneficial to beginners. When using Boost.Graph in production code, I do prefer to use `auto`.

OTOH, while writing this tutorial, I use `auto` when I loose too much time figuring out the type

All coding snippets are taken from compiled C++ code.

### 1.2 Pitfalls

The choice between `'boost::get'`, `'std::get'` and `'get'`. AFAIKS, when in doubt, use `'get'`.

## 2 Building graphs

Boost.Graph is about creating graphs. In this chapter we create graphs, starting from simple to more complex.

## 2.1 Creating an empty graph

Let's create a trivial empty graph:

---

**Algorithm 1** Creating an empty graph

---

```
#include "create_empty_graph.h"

boost::adjacency_list<>
create_empty_graph() noexcept
{
    return boost::adjacency_list<>();
}
```

---

Congratulations, you've just created a `boost::adjacency_list` in which:

- The out edges are stored in a `std::vector`
- The vertices are stored in a `std::vector`
- The graph is directed
- Vertices, edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` is the most commonly used graph type, the other is the `boost::adjacency_matrix`.

## 2.2 Add a vertex

To add a vertex to a graph, the `boost::add_vertex` function is used as such:

---

**Algorithm 2** Adding a vertex to a graph

---

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_vertex(graph& g)
{
    boost::add_vertex(g);
}
```

---

Note that `boost::add_vertex` returns a vertex descriptor, which is ignored for now. A vertex descriptor can be used to, for example, connect two vertices by an edge

## 2.3 Add an edge

To add an edge to a graph, two vertex descriptors are needed. A vertex descriptor is a handle to the vertex with in graph. Algorithm 3 adds two vertices to a graph, and connects these two using `boost::add_edge`:

---

**Algorithm 3** Adding (two vertices and) an edge to a graph

---

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_edge(graph& g)
{
    using boost::graph_traits;
    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;

    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);

    assert(ea.second);
}
```

---

Note that half of the code consists out of using statements. This algorithm only shows how to add an isolated edge to a graph, instead of allowing for graphs with higher connectivities. The function `boost::add_edge` returns a `std::pair`, consisting of an edge descriptor and a boolean success indicator. In algorithm 3 we assert that this insertion was successful. Insertion can fail if an edge is already present and duplicates are not allowed.

## 2.4 Creating $K_2$ , a fully connected graph with two vertices

To create a fully connected graph with two vertices (also called  $K_2$ ), one needs two vertices and one (undirected) edge, as depicted in figure 1.




Figure 1:  $K_2$ : a fully connected graph with two vertices named  $a$  and  $b$

To create  $K_2$ , the following code can be used:

---

**Algorithm 4** Creating  $K_2$  as depicted in figure 1

---

```
#include "create_k2_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_k2_graph() noexcept
{
    using boost::graph_traits;

    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS
    >;

    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);
    return g;
}
```

---

Note that this code has more lines of using statements than actual code! In

this code, the third template argument of `boost::adjacency_list` is `boost::undirectedS`, to select (that is what the S means) for an undirected graph. Adding a vertex with `boost::add_vertex` results in a vertex descriptor, which is a handle to the vertex added to the graph. Two vertex descriptors are then used to add an edge to the graph. Adding an edge using `boost::add_edge` returns two things: an edge descriptor and a boolean indicating success. In the code example, we assume insertion is successful.

Note that the graph lacks all properties: nodes do not have names, nor do edges.

## 2.5 Creating an empty graph with named vertices

Let's create a trivial empty graph, in which the vertices can have a name:

---

**Algorithm 5** Creating an empty graph with named vertices

---

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
create_empty_named_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    >
    >;

    graph g;
    return g;
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)

- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- Edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property< boost::vertex_name_t, std::string>`'. This can be read as: “vertices have the property '`boost::vertex_name_t`', that is of data type '`std::string`’”. Or simply: “vertices have a name that is stored as a `std::string`”.

## 2.6 Add a vertex with a name

Adding a vertex without a name was trivially easy (see chapter 2). Adding a vertex with a name is less easy:

---

**Algorithm 6** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_named_vertex(graph& g, const std::string& name)
{
    using boost::graph_traits;
    using boost::property_map;
    using boost::vertex_name_t;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using name_map_t
        = typename property_map<graph, vertex_name_t>::type;

    const vertex_descriptor vd{
        boost::add_vertex(g)
    };

    name_map_t name_map{ boost::get( boost::vertex_name, g) };
    name_map[vd] = name;
}
```

---

Instead of calling '`boost::add_vertex`' with an additional argument containing the name of the vertex, multiple things need to be done. When adding a new vertex to the graph, the vertex descriptor is stored. After obtaining the

name map from the graph (using `'boost::get(boost::vertex_name,g)'`), the name of the vertex is set using that vertex descriptor.

## 2.7 Creating $K_2$ with named vertices

We extend  $K_2$  of chapter 2.4 by naming the vertices 'from' and 'to', as depicted in figure 2:




Figure 2:  $K_2$ : a fully connected graph with two vertices with the text 'from' and 'to'

To create  $K_2$ , the following code can be used:



---

**Algorithm 7** Creating  $K_2$  as depicted in figure 2

---

```
#include "create_named_vertices_k2_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>
>
create_named_vertices_k2_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using name_map_t
        = boost::property_map<graph, boost::vertex_name_t>::
            type;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);

    //Add names
    name_map_t name_map{boost::get(boost::vertex_name, g)};
    name_map[va] = "from";
    name_map[vb] = "to";

    return g;
}
```

---

Most of the code is a repeat of algorithm 4. In the end, the names are obtained as a `boost::property_map` and `set`.

## 2.8 Creating an empty graph with named edges and vertices

Let's create a trivial empty graph, in which the both the edges and vertices can have a name:

---

**Algorithm 8** Creating an empty graph with named edges and vertices

---

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_empty_named_edges_and_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    >;

    graph g;
    return g;
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)

- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- The edges have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::edge_name_t, std::string>`)
- The graph has no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fifth template argument '`boost::property< boost::edge_name_t, std::string>`'. This can be read as: “edges have the property '`boost::edge_name_t`', that is of data type '`std::string`'”. Or simply: “edges have a name that is stored as a `std::string`”.

## 2.9 Add an edge with a name

Adding an edge with a name:

---

**Algorithm 9** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_named_edge(graph& g, const std::string&
    edge_name)
{
    using boost::edge_name_t;
    using boost::graph_traits;
    using boost::property_map;
    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using name_map_t
        = typename property_map<graph, edge_name_t>::type;

    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);

    assert(ea.second);

    name_map_t name_map{
        boost::get(boost::edge_name, g)
    };
    name_map[ea.first] = edge_name;
}
```

---

In this code snippet, the edge descriptor when using 'boost::add\_edge' is used as a key to change the edge name map.

## 2.10 Creating $K_3$ with named edges and vertices

We extend the graph  $K_2$  with named vertices of chapter 2.7 by adding names to the edges, as depicted in figure 3:




Figure 3:  $K_3$ : a fully connected graph with three named edges and vertices

To create  $K_3$ , the following code can be used:

---

**Algorithm 10** Creating  $K_3$  as depicted in figure 3

---

```
#include "create_named_edges_and_vertices_k3_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_named_edges_and_vertices_k3_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using vertex_name_map_t
        = boost::property_map<graph, boost::vertex_name_t>::
            type;
    using edge_name_map_t
        = boost::property_map<graph, boost::edge_name_t>::type
        ;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const vertex_descriptor vc = boost::add_vertex(g);
    const edge_insertion_result eab
        = boost::add_edge(va, vb, g);
    assert(eab.second);
    const edge_insertion_result ebc
        = boost::add_edge(vb, vc, g);
    assert(ebc.second);
    const edge_insertion_result eca
        = boost::add_edge(vc, va, g);
    assert(eca.second);

    //Add vertex names
    vertex_name_map_t vertex_name_map{boost::get(boost::
        vertex_name, g)};
```

Most of the code is a repeat of algorithm 7. In the end, the edge names are obtained as a `boost::property_map` and set.

### **2.11 Create an empty graph with custom vertices**

### **2.12 Add a custom vertex**

### **2.13 Creating $K_2$ with custom vertices**

Instead of using vertices with a name, or other properties, here we use a custom vertex class called 'my\_vertex'. A 'my\_vertex' has an x coordinat, y coordinat, a name and a description.

### **2.14 Add a custom edge**

### **2.15 Creating $K_2$ with custom edges and vertices**

Instead of using edges with a name, or other properties, here we use a custom edge class called 'my\_edge'.

## **3 Measuring simple graphs traits**

Measuring simple traits of the graphs created allows you to debug your code.

### **3.1 Getting the vertices**

You can use `boost::vertices` to obtain an iterator pair. The first iterator points to the first vertex, the second points to beyond the last vertex.

### **3.2 Getting the edges**

You can use `boost::edges` to obtain an iterator pair. The first iterator points to the first edge, the second points to beyond the last edge.

### **3.3 Counting the number of vertices**

Use `boost::num_vertices`, as shown here:

---

**Algorithm 11** Count the numbe of vertices

---

```
#ifndef GET_N_VERTICES_H
#define GET_N_VERTICES_H

#include <utility>
#include <boost/graph/adjacency_list.hpp>

///Get the number of vertices a graph has
template <class graph>
int get_n_vertices(const graph& g)
{
    return static_cast<int>(boost::num_vertices(g));
    /*
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    const vertex_iterators vertex_iters
        = boost::vertices(g);
    return std::distance(
        vertex_iters.first,
        vertex_iters.second
    );
    */
}

void get_n_vertices_test() noexcept;

#endif // GET_N_VERTICES_H
```

---

### 3.4 Counting the number of edges

Use boost::num\_edges, as show here:



---

**Algorithm 12** Count the number of edges

---

```
#ifndef GET_N_EDGES_H
#define GET_N_EDGES_H

#include <utility>
#include <boost/graph/adjacency_list.hpp>

///Get the number of edges a graph has
template <class graph>
int get_n_edges(const graph& g)
{
    return static_cast<int>(boost::num_edges(g));
    /*
    const auto edge_iters = boost::edges(g);
    return std::distance(edge_iters.first, edge_iters.second
    );
    */
}

void get_n_edges_test() noexcept;

#endif // GET_N_EDGES_H
```

---

### 3.5 Getting the vertices' names

When the vertices of a graph have named vertices, one can extract them as such:

---

**Algorithm 13** Get the vertices' names

---

```
#ifndef GET_VERTEX_NAMES_H
#define GET_VERTEX_NAMES_H

#include <string>
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_vertex_names(const graph& g)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    std::vector<std::string> v;

    //TODO: remove auto
    const auto name_map = get(boost::vertex_name, g);

    for (vertex_iterators p = vertices(g);
        p.first != p.second;
        ++p.first)
    {
        v.emplace_back(get(name_map, *p.first));
    }
    return v;
}

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_vertex_names_DOESNOTWORK(
    const graph& g)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;
    using name_map_t
        = typename boost::property_map<graph, boost::
            vertex_name_t>::type;

    std::vector<std::string> v;18

    const name_map_t name_map = get(boost::vertex_name, g);

    for (vertex_iterators p = vertices(g);
        p.first != p.second;
        ++p.first)
    {
```

The names of the vertices are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the vertices' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

### **3.6 Getting the edges' names**

When the edges of a graph have named vertices, one can extract them as such:

---

**Algorithm 14** Get the edges' names

---

```
#ifndef GET_EDGE_NAMES_H
#define GET_EDGE_NAMES_H

#include <string>
#include <vector>
#include <boost/graph/adjacency_list.hpp>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_edge_names(const graph& g)
{
    using boost::graph_traits;
    using edge_iterator
        = typename graph_traits<graph>::edge_iterator;
    using edge_iterators
        = std::pair<edge_iterator, edge_iterator>;

    std::vector<std::string> v;

    //TODO: remove auto
    const auto name_map = get(boost::edge_name, g);

    for (edge_iterators p = boost::edges(g);
         p.first != p.second;
         ++p.first)
    {
        v.emplace_back(get(name_map, *p.first));
    }
    return v;
}

void get_edge_names_test() noexcept;

#endif // GET_EDGE_NAMES_H
```

---

The names of the edges are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the edges' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

### **3.7 Find a vertex by its name**

### **3.8 Replace a vertex its name**

## **4 Modifying simple graphs traits**

It is useful to be able to modify every aspect of a graph. Adding nodes and edges are found in earlier chapters.

### **4.1 Setting all vertices' names**

When the vertices of a graph have named vertices, one set their names as such:

---

**Algorithm 15** Setting the vertices' names

---

```
#ifndef SET_VERTEX_NAMES_H
#define SET_VERTEX_NAMES_H

#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize 'names'
template <typename graph>
void set_vertex_names(
    graph& g,
    const std::vector<std::string>& names
)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    const auto name_map = get(boost::vertex_name, g);

    auto names_begin = std::begin(names);
    const auto names_end = std::end(names);
    for (vertex_iterators vi = vertices(g);
        vi.first != vi.second;
        ++vi.first, ++names_begin)
    {
        assert(names_begin != names_end);
        put(name_map, *vi.first, *names_begin);
    }
}

void set_vertex_names_test() noexcept;

#endif // SET_VERTEX_NAMES_H
```

---

An impressive feature is that getting the property map holding the graph its names is not a copy, but a reference. Otherwise, modifying 'name\_map'

(obtained by non-reference) would only modify a copy.

## 5 Visualizing graphs

Before graphs are visualized, they are stored as a file first. Here, I use the .dot file format.

### 5.1 Storing a graph as a .dot

Graph are easily saved to a .dot file:

---

**Algorithm 16** Storing a graph as a .dot file

---

```
#ifndef SAVE_GRAPH_TO_DOT_H
#define SAVE_GRAPH_TO_DOT_H

#include <fstream>
#include <boost/graph/graphviz.hpp>

///Save a graph to a .dot file
template <typename graph>
void save_graph_to_dot(const graph& g, const std::string&
    filename)
{
    std::ofstream f(filename);
    boost::write_graphviz(f,g);
}

void save_graph_to_dot_test() noexcept;

#endif // SAVE_GRAPH_TO_DOT_H
```

---

Using the `create_k2_graph` function (algorithm 4) to create a  $K_2$  graph, the .dot file created is displayed in algorithm 17:

---

**Algorithm 17** .dot file created from the `create_k2_graph` function (algorithm 4)

---

```
graph G {
0;
1;
0--1 ;
}
```

---

This .dot file corresponds to figure 4:




Figure 4: .svg file created from the `create_k2_graph` function (algorithm 4)

If you used the `create_named_vertices_k2_graph` function (algorithm 7) to produce a  $K_2$  graph with named vertices, you see that the .dot file does not have stored the vertex names:

---

**Algorithm 18** .dot file created from the `create_named_vertices_k2_graph` function (algorithm 7)

---

```

graph G {
0;
1;
0--1 ;
}

```

---

So, the 'save\_graph\_to\_dot' function (algorithm 16) saves the structure of the graph.

## 5.2 Storing a graph with named vertices as a .dot

If you used the `create_named_vertices_k2_graph` function (algorithm 7) to produce a  $K_2$  graph with named vertices, you can store these names additionally with algorithm 19:



---

**Algorithm 19** Storing a graph with named vertices as a .dot file

---

```
#ifndef SAVE_NAMED_VERTICES_GRAPH_TO_DOT_H
#define SAVE_NAMED_VERTICES_GRAPH_TO_DOT_H

#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_vertices_graph_to_dot(const graph& g,
    const std::string& filename)
{
    std::ofstream f(filename);
    const auto names = get_vertex_names(g);
    boost::write_graphviz(f, g, boost::make_label_writer(&
        names[0]));
}

void save_named_vertices_graph_to_dot_test() noexcept;

#endif // SAVE_NAMED_VERTICES_GRAPH_TO_DOT_H
```

---

The .dot file created is displayed in algorithm 20:

---

**Algorithm 20** .dot file created from the create\_named\_vertices\_k2\_graph function (algorithm 7)

---

```
graph G {
0[label=from];
1[label=to];
0--1 ;
}
```

---

This .dot file corresponds to figure 5:




Figure 5: .svg file created from the `create_k2_graph` function (algorithm 7)

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 10) to produce a  $K_3$  graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

---

**Algorithm 21** .dot file created from the `create_named_edges_and_vertices_k3_graph` function (algorithm 10)

---

```

graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 ;
1--2 ;
2--0 ;
}

```

---

So, the 'save\_named\_vertices\_graph\_to\_dot' function (algorithm 16) saves only the structure of the graph and its vertex names.

### 5.3 Storing a graph with named vertices and edges as a .dot

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 10) to produce a  $K_3$  graph with named edges and vertices, you can store these names additionally with algorithm 22:

---

**Algorithm 22** Storing a graph with named edges and vertices as a .dot file

---

```
#ifndef SAVE_NAMED_EDGES_AND_VERTICES_GRAPH_TO_DOT
#define SAVE_NAMED_EDGES_AND_VERTICES_GRAPH_TO_DOT

#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_edge_names.h"
#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_edges_and_vertices_graph_to_dot(const
    graph& g, const std::string& filename)
{
    std::ofstream f(filename);
    const auto vertex_names = get_vertex_names(g);
    const auto edge_name_map = boost::get(boost::edge_name,
        g);
    boost::write_graphviz(
        f,
        g,
        boost::make_label_writer(&vertex_names[0]),
        [edge_name_map](std::ostream& out, const auto& e) {
            out << "[label=\"" << edge_name_map[e] << "\"]";
        }
    );
}

void save_named_edges_and_vertices_graph_to_dot_test()
    noexcept;

#endif // SAVE_NAMED_EDGES_AND_VERTICES_GRAPH_TO_DOT
```

---

The .dot file created is displayed in algorithm 23:

---

**Algorithm 23** .dot file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 7)

---

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}
```

---

This .dot file corresponds to figure 6:




Figure 6: .svg file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 7)

If you used the MORE\_COMPLEX\_create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 10) to produce a  $K_3$  graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

---

**Algorithm 24** .dot file created from the  
MORE\_COMPLEX\_create\_named\_edges\_and\_vertices\_k3\_graph func-  
tion (algorithm 10)

---

```
graph G {  
0[label=top];  
1[label=right];  
2[label=left];  
0--1 [label="AB"];  
1--2 [label="BC"];  
2--0 [label="CA"];  
}
```

---

So, the 'save\_named\_edges\_and\_vertices\_graph\_to\_dot' function (algorithm 16) saves only the structure of the graph and its edge and vertex names.

## 6 TODO's in general

### 6.1 Personal experiences with Boost.Graph

I have been experimenting with Boost.Graph since 2006 and I both use the documentation on the Boost website [1] and the book [1].

- Boost.Graph seems like the most type-safe extendable graph library around: learning it will pay off!
- Boost.Graph requires a good compiler, like GCC
- The book [2] will not help a beginner: all code snippets are written 'too smart', where a beginner might prefer four easy-to-understand lines, instead of one using magic. Most code snippets are scattered as part of a complete project, where a beginner might prefer simple short projects
- The website [1] will not help a beginner, for the same reasons as above
- I have never found Boost.Graph documentation or code snippets a beginner would understand (except for (hopefully) at my website), as if nobody understands Boost.Graph and/or everybody that understands Boost.Graph cannot explain simply anymore
- I learned most of Boost.Graph from my IDE ( the helpful Qt Creator): by viewing the code that failed, I could understand what was expected for me. I would never have understood Boost.Graph if I would have used a text editor for programming

## 6.2 To add

Code snippets show include guards , use header\_impl instead.

- `std::pair<edge_iterator, edge_iterator> edges(const adjacency_list& g)`  
. Returns an iterator pair corresponding to the edges in graph g
- `vertex_descriptor source(edge_descriptor e, const adjacency_list& g)` .  
Returns the source vertex of an edge
- `vertex_descriptor target(edge_descriptor e, const adjacency_list& g)` .  
Returns the target vertex of an edge
- `degree_size_type in_degree(vertex_descriptor u, const adjacency_list& g)` .  
Returns the in-degree of a vertex
- `degree_size_type out_degree(vertex_descriptor u, const adjacency_list& g)` .  
Returns the out-degree of a vertex
- `void remove_edge(vertex_descriptor u, vertex_descriptor v, adjacency_list& g)` .  
Removes an edge from g
- `void remove_edge(edge_descriptor e, adjacency_list& g)` .  
Removes an edge from g
- `void clear_vertex(vertex_descriptor u, adjacency_list& g)` .  
Removes all edges to and from u
- `void clear_out_edges(vertex_descriptor u, adjacency_list& g)` .  
Removes all outgoing edges from vertex u in the directed graph g (not applicable for undirected graphs)
- `void clear_in_edges(vertex_descriptor u, adjacency_list& g)` .  
Removes all incoming edges from vertex u in the directed graph g (not applicable for undirected graphs)
- `void remove_vertex(vertex_descriptor u, adjacency_list& g)` .  
Removes a vertex from graph g (It is expected that all edges associated with this vertex have already been removed using `clear_vertex` or another appropriate function.)

## 7 Graph of this tutorial

This tutorial would not be complete with a graph that connects all chapter chronologically:




Figure 7: .svg file created from the `create_tutorial_chapters_graph` function

## References

- [1] Jeremy G Siek, Lie-Quan Lee, and Andrew Lumsdaine. *Boost Graph Library: User Guide and Reference Manual, The*. Pearson Education, 2001.

## Index

$K_2$  with named vertices, create, 8  
 $K_2$ , create, 4  
 $K_3$  with named edges and vertices, create, 12  
  
Add a vertex, 3  
Add an edge, 4  
Add named edge, 11  
Add named vertex, 7  
add\_edge, 4  
add\_named\_edge, 12  
add\_named\_vertex, 7  
add\_vertex, 3  
assert, 4  
  
boost::add\_edge, 4, 6, 12  
boost::add\_vertex, 3, 6  
boost::adjacency\_list, 3, 6, 7, 11  
boost::adjacency\_matrix, 3  
boost::edge\_name\_t, 11  
boost::get(boost::vertex\_name,g), 8  
boost::property, 7, 11  
boost::property<boost::edge\_name\_t, std::string>, 11  
boost::property<boost::vertex\_name\_t, std::string>, 7, 11  
boost::undirectedS, 6, 7, 10  
boost::vecS, 6, 10  
boost::vertex\_name, 8  
boost::vertex\_name\_t, 7, 11  
  
Create  $K_2$ , 4  
Create  $K_2$  with named vertices, 8  
Create  $K_3$  with named edges and vertices, 12  
Create an empty graph, 3  
Create an empty graph with named edges and vertices, 10  
Create an empty graph with named vertices, 6  
create\_empty\_graph, 3  
create\_empty\_named\_edges\_and\_vertices\_graph, 10  
create\_empty\_named\_vertices\_graph, 6  
create\_k2\_graph, 5  
create\_named\_edges\_and\_vertices\_k3, 14  
create\_named\_vertices\_k2\_graph, 9  
create\_tutorial\_chapters\_graph, 31  
  
edge descriptor, 12  
Edge, add, 4  
Empty graph with named edges and vertices, create, 10  
Empty graph with named vertices, create, 6  
Empty graph, create, 3  
  
Named edge, add, 11  
Named edges and vertices, create empty graph, 10  
Named vertex, add, 7  
Named vertices, create empty graph, 6  
  
std::pair, 4  
vertex\_descriptor, 3, 4, 6  
Vertex, add, 3  
Vertex, add named, 7