


A well-connected C++11 Boost.Graph tutorial

Richèl Bilderbeek

December 26, 2015



Contents

1	Introduction	8
1.1	Why this tutorial	8
1.2	Code snippets	8
1.3	Coding style	9
1.4	Tutorial style	9
1.5	License	10
1.6	Feedback	10
1.7	Help	10
1.8	Acknowledgements	10
1.9	Outline	10
2	Building graphs without properties	11
2.1	Creating an empty (directed) graph	15
2.2	Creating an empty undirected graph	17
2.3	Counting the number of vertices	18
2.4	Counting the number of edges	19

2.5	Adding a vertex	20
2.6	Vertex descriptors	22
2.7	Get the vertex iterators	22
2.8	Get all vertex descriptors	23
2.9	Add an edge	25
2.10	boost::add_edge result	27
2.11	Getting the edge iterators	27
2.12	Edge descriptors	28
2.13	Get all edge descriptors	29
2.14	Creating a directed graph	30
2.14.1	Graph	30
2.14.2	Function to create such a graph	31
2.14.3	Creating such a graph	31
2.14.4	The .dot file produced	32
2.14.5	The .svg file produced	32
2.15	Creating K_2 , a fully connected undirected graph with two vertices	33
2.15.1	Graph	33
2.15.2	Function to create such a graph	33
2.15.3	Creating such a graph	34
2.15.4	The .dot file produced	35
2.15.5	The .svg file produced	35
3	Working on graphs without properties	36
3.1	Getting the vertices' out degree	36
3.2	Saving a graph to a .dot file	38
3.3	Loading a directed graph from a .dot	39
3.4	Loading an undirected graph from a .dot file	41
4	Building graphs with named vertices	43
4.1	Creating an empty directed graph with named vertices	44
4.2	Creating an empty undirected graph with named vertices	45
4.3	Add a vertex with a name	47
4.4	Getting the vertices' names	48
4.5	Creating a Markov chain with named vertices	50
4.5.1	Graph	50
4.5.2	Function to create such a graph	51
4.5.3	Creating such a graph	52
4.5.4	The .dot file produced	52
4.5.5	The .svg file produced	53
4.6	Creating K_2 with named vertices	53
4.6.1	Graph	53
4.6.2	Function to create such a graph	53
4.6.3	Creating such a graph	54
4.6.4	The .dot file produced	55
4.6.5	The .svg file produced	55

5	Working on graphs with named vertices	56
5.1	Check if there exists a vertex with a certain name	57
5.2	Find a vertex by its name	58
5.3	Get a (named) vertex its degree, in degree and out degree	60
5.4	Get a vertex its name from its vertex descriptor	62
5.5	Set a (named) vertex its name from its vertex descriptor	64
5.6	Setting all vertices' names	65
5.7	Clear the edges of a named vertex	66
5.8	Remove a named vertex	68
5.9	Removing the edge between two named vertices	69
5.10	Saving an directed/undirected graph with named vertices to a .dot file	71
5.10.1	Using boost::make_label_writer	71
5.10.2	Using a C++11 lambda function	72
5.10.3	Demonstration	74
5.11	Loading a directed graph with named vertices from a .dot	74
5.12	Loading an undirected graph with named vertices from a .dot . .	76
6	Building graphs with named edges and vertices	78
6.1	Creating an empty directed graph with named edges and vertices	79
6.2	Creating an empty undirected graph with named edges and vertices	81
6.3	Adding a named edge	83
6.4	Getting the edges' names	85
6.5	Creating Markov chain with named edges and vertices	87
6.5.1	Graph	87
6.5.2	Function to create such a graph	88
6.5.3	Creating such a graph	90
6.5.4	The .dot file produced	91
6.5.5	The .svg file produced	91
6.6	Creating K_3 with named edges and vertices	91
6.6.1	Graph	91
6.6.2	Function to create such a graph	92
6.6.3	Creating such a graph	94
6.6.4	The .dot file produced	95
6.6.5	The .svg file produced	95
7	Working on graphs with named edges and vertices	96
7.1	Check if there exists an edge with a certain name	96
7.2	Find an edge by its name	98
7.3	Get a (named) edge its name from its edge descriptor	100
7.4	Set a (named) edge its name from its edge descriptor	101
7.5	Removing the first edge with a certain name	103
7.6	Saving an undirected graph with named edges and vertices as a .dot	105
7.7	Loading a directed graph with named edges and vertices from a .dot	106

7.8	Loading an undirected graph with named edges and vertices from a .dot	109
8	Building graphs with bundled vertices	111
8.1	Creating the bundled vertex class	111
8.2	Create the empty directed graph with bundled vertices	113
8.3	Create the empty undirected graph with bundled vertices	114
8.4	Add a bundled vertex	114
8.5	Getting the bundled vertices' my_vertexes	115
8.6	Creating a two-state Markov chain with bundled vertices	116
8.6.1	Graph	116
8.6.2	Function to create such a graph	117
8.6.3	Creating such a graph	118
8.6.4	The .dot file produced	119
8.6.5	The .svg file produced	120
8.7	Creating K_2 with bundled vertices	120
8.7.1	Graph	120
8.7.2	Function to create such a graph	121
8.7.3	Creating such a graph	121
8.7.4	The .dot file produced	122
8.7.5	The .svg file produced	122
9	Working on graphs with bundled vertices	122
9.1	Has a bundled vertex with a my_bundled_vertex	123
9.2	Find a bundled vertex with a certain my_bundled_vertex	124
9.3	Get a bundled vertex its 'my_bundled_vertex'	126
9.4	Set a bundled vertex its my_vertex	127
9.5	Setting all bundled vertices' my_vertex objects	128
9.6	Storing a graph with bundled vertices as a .dot	129
9.7	Loading a directed graph with bundled vertices from a .dot	133
9.8	Loading an undirected graph with bundled vertices from a .dot	135
10	Building graphs with bundled edges and vertices	137
10.1	Creating the bundled edge class	138
10.2	Create an empty directed graph with bundled edges and vertices	139
10.3	Create an empty undirected graph with bundled edges and vertices	141
10.4	Add a bundled edge	142
10.5	Getting the bundled edges my_edges	144
10.6	Creating a Markov-chain with bundled edges and vertices	145
10.6.1	Graph	145
10.6.2	Function to create such a graph	146
10.6.3	Creating such a graph	148
10.6.4	The .dot file produced	149
10.6.5	The .svg file produced	149
10.7	Creating K_3 with bundled edges and vertices	149
10.7.1	Graph	149

10.7.2	Function to create such a graph	150
10.7.3	Creating such a graph	151
10.7.4	The .dot file produced	151
10.7.5	The .svg file produced	151
11	Working on graphs with bundled edges and vertices	152
11.1	Has a my_bundled_edge	152
11.2	Find a my_bundled_edge	153
11.3	Get an edge its my_bundled_edge	155
11.4	Set an edge its my_bundled_edge	157
11.5	Storing a graph with bundled edges and vertices as a .dot	159
11.6	Load a directed graph with bundled edges and vertices from a .dot file	161
11.7	Load an undirected graph with bundled edges and vertices from a .dot file	164
12	Building graphs with custom vertices	167
12.1	Creating the vertex class	167
12.2	Installing the new vertex property	169
12.3	Create the empty directed graph with custom vertices	170
12.4	Create the empty undirected graph with custom vertices	172
12.5	Add a custom vertex	173
12.6	Getting the vertices' my_vertexes	174
12.7	Creating a two-state Markov chain with custom vertices	176
12.7.1	Graph	176
12.7.2	Function to create such a graph	176
12.7.3	Creating such a graph	177
12.7.4	The .dot file produced	178
12.7.5	The .svg file produced	179
12.8	Creating K_2 with custom vertices	179
12.8.1	Graph	179
12.8.2	Function to create such a graph	180
12.8.3	Creating such a graph	180
12.8.4	The .dot file produced	181
12.8.5	The .svg file produced	182
13	Working on graphs with custom vertices (as a custom property)	182
13.1	Has a custom vertex with a my_vertex	182
13.2	Find a custom vertex with a certain my_vertex	184
13.3	Get a custom vertex its my_vertex	186
13.4	Set a custom vertex its my_vertex	188
13.5	Setting all custom vertices' my_vertex objects	190
13.6	Storing a graph with custom vertices as a .dot	192
13.7	Loading a directed graph with custom vertices from a .dot	193
13.8	Loading an undirected graph with custom vertices from a .dot . .	194

14 Building graphs with custom and selectable vertices	196
14.1 Installing the new <code>is_selected</code> property	197
14.2 Create an empty directed graph with custom and selectable vertices	198
14.3 Create an empty undirected graph with custom and selectable vertices	200
14.4 Add a custom and selectable vertex	201
14.5 Creating a Markov-chain with custom and selectable vertices . .	204
14.5.1 Graph	204
14.5.2 Function to create such a graph	204
14.5.3 Creating such a graph	206
14.5.4 The <code>.dot</code> file produced	207
14.5.5 The <code>.svg</code> file produced	208
14.6 Creating K_2 with custom and selectable vertices	209
14.6.1 Graph	209
14.6.2 Function to create such a graph	210
14.6.3 Creating such a graph	211
14.6.4 The <code>.dot</code> file produced	211
14.6.5 The <code>.svg</code> file produced	212
15 Working on graphs with custom and selectable vertices	212
15.1 Storing a graph with custom and selectable vertices as a <code>.dot</code> . .	213
15.2 Loading a directed graph with custom and selectable vertices from a <code>.dot</code>	215
15.3 Loading an undirected graph with custom and selectable vertices from a <code>.dot</code>	217
16 Building graphs with custom edges and vertices	219
16.1 Creating the custom edge class	220
16.2 Installing the new edge property	222
16.3 Create an empty directed graph with custom edges and vertices .	223
16.4 Create an empty undirected graph with custom edges and vertices	225
16.5 Add a custom edge	226
16.6 Getting the custom edges <code>my_edges</code>	228
16.7 Creating a Markov-chain with custom edges and vertices	229
16.7.1 Graph	229
16.7.2 Function to create such a graph	230
16.7.3 Creating such a graph	232
16.7.4 The <code>.dot</code> file produced	233
16.7.5 The <code>.svg</code> file produced	233
16.8 Creating K_3 with custom edges and vertices	233
16.8.1 Graph	233
16.8.2 Function to create such a graph	234
16.8.3 Creating such a graph	235
16.8.4 The <code>.dot</code> file produced	235
16.8.5 The <code>.svg</code> file produced	236

17 Working on graphs with custom edges and vertices	236
17.1 Has a my_custom_edge	236
17.2 Find a my_custom_edge	238
17.3 Get an edge its my_custom_edge	240
17.4 Set an edge its my_custom_edge	242
17.5 Storing a graph with custom edges and vertices as a .dot	244
17.6 Load a directed graph with custom edges and vertices from a .dot file	246
17.7 Load an undirected graph with custom edges and vertices from a .dot file	249
18 Building graphs with a graph name	251
18.1 Create an empty directed graph with a graph name property . .	252
18.2 Create an empty undirected graph with a graph name property .	253
18.3 Get a graph its name property	255
18.4 Set a graph its name property	256
18.5 Create a directed graph with a graph name property	257
18.5.1 Graph	257
18.5.2 Function to create such a graph	257
18.5.3 Creating such a graph	258
18.5.4 The .dot file produced	259
18.5.5 The .svg file produced	260
18.6 Create an undirected graph with a graph name property	260
18.6.1 Graph	260
18.6.2 Function to create such a graph	260
18.6.3 Creating such a graph	261
18.6.4 The .dot file produced	262
18.6.5 The .svg file produced	262
19 Working on graphs with a graph name	263
19.1 Storing a graph with a graph name property as a .dot file	263
19.2 Loading a directed graph with a graph name property from a .dot file	263
19.3 Loading an undirected graph with a graph name property from a .dot file	265
20 Building graphs with custom graph properties	267
21 Working on graphs with custom graph properties	267
22 Other graph functions	267
22.1 Encode a std::string to a Graphviz-friendly format	267
22.2 Decode a std::string from a Graphviz-friendly format	267

23 Misc functions	268
23.1 Getting a data type as a <code>std::string</code>	268
23.2 Convert a <code>.dot</code> to <code>.svg</code>	269
23.3 Check if a file exists	270
24 Errors	271
24.1 Formed reference to void	271
24.2 No matching function for call to <code>'clear_out_edges'</code>	271
24.3 No matching function for call to <code>'clear_in_edges'</code>	272
24.4 Undefined reference to <code>boost::detail::graph::read_graphviz_new</code> .	272
24.5 Property not found: <code>node_id</code>	272
25 Appendix	273
25.1 List of all edge, graph and vertex properties	273
25.2 Graphviz attributes	274

1 Introduction

This is 'A well-connected C++11 Boost.Graph tutorial', version 1.5.

1.1 Why this tutorial

I needed this tutorial already in 2006, when I started experimenting with Boost.Graph. More specifically, I needed a tutorial that:

- Orders concepts chronologically
- Increases complexity gradually
- Shows complete pieces of code

What I had were the book [8] and the Boost.Graph website, both did not satisfy these requirements.

This tutorial is intended to take the reader to the level of understanding the book [8] and the Boost.Graph website require. It is about basic graph manipulation, not the more advanced graph algorithms. An analogy with `std::vector`: it teaches the `std::vector` member functions, but not the algorithms that work on.

1.2 Code snippets

For every concept, I will show

- the 'do' function: a function that achieves a goal, for example `'create_empty_undirected_graph'`
- the 'demo' function: a function that demonstrates how to call the first, for example `'create_empty_undirected_graph_demo'`

I enjoy to show concepts by putting those in (long-named) functions. These functions sometimes border the trivial, by, for example, only calling a single `Boost.Graph` function. On the other hand, these functions have more English-sounding names, resulting in demonstration code that is readable. Additionally, they explicitly mention their return type (in a simpler way), which may be considered informative.

All coding snippets are taken from compiled C++11 code. I chose to use C++11 because (1) C++14 was not installable on all my computers (2) the step to C++14 is small. All code is tested to compile cleanly under GCC at the highest warning level. The code, as well as this tutorial, can be downloaded from the GitHub at www.github.com/richebilderbeek/BoostGraphTutorial.

1.3 Coding style

I use the coding style from the Core C++ Guidelines. At the time of this writing, the Core C++ Guidelines were still in early development, so I can only hope the conventions I then chose to follow are still Good Ideas.

It is important to add comments to code. In this tutorial, however, I have chosen not to put comments in code, as I already describe the function in the tutorial its text. This way, it prevents me from saying the same things twice.

It is good to write generic code. In this tutorial, however, I have chosen my functions to have no templated arguments for conciseness and readability. For example, a vertex name is `std::string`, the type for if a vertex is selected is a boolean, and the custom vertex type is of type `'my_custom_vertex'`. I think these choices are reasonable and that the resulting increase in readability is worth it.

Due to my long function names and the limitation of ≈ 50 characters per line, sometimes the code does get to look a bit awkward. I am sorry for this.

I prefer to use the keyword `auto` over doubling the lines of code for using statements. Because the `'do'` functions return an explicit data type, these can be used for reference (until `'decltype(auto)'` gets into fashion as a return type). If you really want to know a type, you can use the `'get_type_name'` function (chapter 23.1).

On the other hand, I am explicit in the namespaces of functions and classes I use, so to distinguish between types like `'std::array'` and `'boost::array'`. Some functions (for example, `'get'`) reside in the namespace of the graph to work on. In this tutorial, this is in the global namespace. Thus, I will write `'get'`, instead of `'boost::get'`, as the latter does not compile.

1.4 Tutorial style

In the index, I did first put all my long-named functions there literally, but this resulted in a very sloppy layout. Instead, the function `'do_something'` can be found as `'Do something'` in the index. On the other hand, STL and Boost functions like `'std::do_something'` and `'boost::do_something'` can be found as such in the index.

1.5 License

This tutorial is licensed under Creative Commons license 4.0. All C++ code is licensed under GPL 3.0.



Figure 1: Creative Commons license 4.0

1.6 Feedback

This tutorial is not intended to be perfect yet. For that, I need help and feedback from the community. All referenced feedback is welcome, as well as any constructive feedback.

I have tried hard to strictly follow the style as described above. If you find I deviated from these decisions somewhere, I would be grateful if you'd let know. Next to this, there are some sections that need to be coded or have its code improved.

1.7 Help

There are some pieces of code I could use help with:

- Issue #12: Loading a directed graph with a name, function 'load_directed_graph_with_graph_name_fn' as shown in chapters 19.2. Perhaps the function 'save_graph_with_graph_name_to_dot' (chapter 19.1) needs to be rewritten as well

I have already put the tests in place, so you/I can easily check if your solution works. If the program crashes with the message 'assertion failed: !"Fixed #"', a problem has been solved.

1.8 Acknowledgements

These are users that improved this tutorial and/or the code behind this tutorial, in chronological order:

- E. Kawashima

1.9 Outline

The chapters of this tutorial are also like a well-connected graph (as shown in figure 2). To allow for quicker learners to skim chapters, or for beginners looking to find the patterns, some chapters are repetitions of each other (for example, getting an edge its name is very similar to getting a vertex its name)¹. This

¹There was even copy-pasting involved!

tutorial is not about being short, but being complete, at the risk of being called bloated.

The distinction between the chapter is in the type of edges and vertices. They can have:

- no properties: see chapter 2
- have a name: see chapter 4
- have a bundled property: see chapter 8
- have a custom property: see chapter 12

The differences between graphs with bundled and custom prorties are shown in table 1:

	Bundled	Custom
Meaning	Edges/vertices are of your type	Edges/vertices have an additional custom property
Interface	Directly	Via property map
Class members	Must be public	Can be private
File I/O mechanism	Via public class members	Via stream operators
File I/O success	Fails, please help!	Works, with encoding/decoding

Table 1: Difference between bundled and custom properties

Pivotal chapters are chapters like 'Finding the first vertex with ...', as this opens up the door to finding a vertex and manipulating it.

All chapters have a rather similar structure in themselves, as depicted in figure 3.

2 Building graphs without properties

Boost.Graph is about creating graphs. In this chapter we create the simplest of graphs, in which edges and nodes have no properties (e.g. having a name).

Still, there are two types of graphs that can be constructed: undirected and directed graphs. The difference between directed and undirected graphs is in the edges: in an undirected graph, an edge connects two vertices without any directionality, as displayed in figure 4. In a directed graph, an edge goes from a certain vertex, its source, to another (which may actually be the same), its target. A directed graph is shown in figure 5.




Figure 2: The relations between chapters




Figure 3: The relations between sub-chapters




Figure 4: Example of an undirected graph




Figure 5: Example of a directed graph

In this chapter, we will build two directed and two undirected graphs:

- An empty (directed) graph, which is the default type: see chapter 2.1
- An empty (undirected) graph: see chapter 2.2
- A two-state Markov chain, a directed graph with two vertices and four edges, chapter 2.14
- K_2 , an undirected graph with two vertices and one edge, chapter 2.15

Creating an empty graph may sound trivial, it is not, thanks to the versatility of the Boost.Graph library.

In the process of creating graphs, some basic (sometimes bordering trivial) functions are encountered:

- Counting the number of vertices: see chapter 2.3
- Counting the number of edges: see chapter 2.4
- Adding a vertex: see chapter 2.5
- Getting all vertices: see chapter 2.7

- Getting all vertex descriptors: see chapter 2.8
- Adding an edge: see chapter 2.9
- Getting all edges: see chapter 2.11
- Getting all edge descriptors: see chapter 2.13

These functions are mostly there for completion and showing which data types are used.

The chapter also introduces some important concepts:

- Vertex descriptors: see chapter 2.6
- Edge insertion result: see chapter 2.10
- Edge descriptors: see chapter 2.12

After this chapter you may want to:

- Building graphs with named vertices: see chapter 4
- Building graphs with bundled vertices: see chapter 8
- Building graphs with custom vertices: see chapter 12
- Building graphs with a graph name: see chapter 18

2.1 Creating an empty (directed) graph

Let's create an empty graph!

Algorithm 1 shows the function to create an empty graph.

Algorithm 1 Creating an empty (directed) graph

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<>
create_empty_directed_graph() noexcept
{
    return boost::adjacency_list<>();
}
```

The code consists out of an `#include` and a function definition. The `#include` tells the compiler to read the header file `'adjacency_list.hpp'`. A header file (often with a `'.h'` or `'.hpp'` extension) contains class and functions declarations and/or definitions. The header file `'adjacency_list.hpp'` contains the `boost::adjacency_list` class definition. Without including this file, you will get compile errors like `'definition of boost::adjacency_list unknown'`². The function `'create_empty_directed_graph'` has:

²In practice, these compiler error messages will be longer, bordering the unreadable

- a return type: The return type is 'boost::adjacency_list<>', that is a 'boost::adjacency_list with all template arguments set at their defaults
- a noexcept specification: the function should not throw³, so it is preferred to mark it noexcept ([10] chapter 13.7).
- a function body: all the function body does is create a 'boost::adjacency_list<>', by calling its constructor, by using the round brackets

Algorithm 2 demonstrates the 'create_empty_directed_graph' function. Note that it includes a header file with the same name as the function⁴ first, to be able to use it. 'auto' is used, as this is preferred over explicit type declarations ([10] chapter 31.6). The keyword 'auto' lets the compiler figure out the type itself.

Algorithm 2 Demonstration of 'create_empty_directed_graph'

```
#include "create_empty_directed_graph.h"

void create_empty_directed_graph_demo() noexcept
{
    const auto g = create_empty_directed_graph();
}
```

Congratulations, you've just created a boost::adjacency_list with its default template arguments. The boost::adjacency_list is the most commonly used graph type, the other is the boost::adjacency_matrix. We do not do anything with it yet, but still, you've just created a graph, in which:

- The out edges and vertices are stored in a std::vector
- The edges have a direction
- The vertices, edges and graph have no properties
- The edges are stored in a std::list

It stores its edges, out edges and vertices in a two different STL⁵ containers. std::vector is the container you should use by default ([10] chapter 31.6, [11] chapter 76), as it has constant time look-up and back insertion. The std::list is used for storing the edges, as it is better suited at inserting elements at any position.

I use const to store the empty graph as we do not modify it. Correct use of const is called const-correct. Prefer to be const-correct ([9] chapter 7.9.3, [10] chapter 12.7, [7] item 3, [3] chapter 3, [11] item 15, [2] FAQ 14.05, [1] item 8, [4] 9.1.6).

³if the function would throw because it cannot allocate this little piece of memory, you are already in big trouble

⁴I do not think it is important to have creative names

⁵Standard Template Library, the standard library

2.2 Creating an empty undirected graph

Let's create another empty graph! This time, we even make it undirected!

Algorithm 3 shows how to create an undirected graph.

Algorithm 3 Creating an empty undirected graph

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_empty_undirected_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS
    >();
}
```

This algorithm differs from the 'create_empty_directed_graph' function (algorithm 1) in that there are three template arguments that need to be specified in the creation of the `boost::adjacency_list`:

- the first '`boost::vecS`': select (that is what the 'S' means) that out edges are stored in a `std::vector`. This is the default way.
- the second '`boost::vecS`': select that the graph vertices are stored in a `std::vector`. This is the default way.
- '`boost::undirectedS`': select that the graph is undirected. This is all we needed to change. By default, this argument is `boost::directed`

Algorithm 4 demonstrates the 'create_empty_undirected_graph' function.

Algorithm 4 Demonstration of 'create_empty_undirected_graph'

```
#include "create_empty_undirected_graph.h"

void create_empty_undirected_graph_demo() noexcept
{
    const auto g = create_empty_undirected_graph();
}
```

Congratulations, with algorithm 4, you’ve just created an undirected graph in which:

- The out edges and vertices are stored in a `std::vector`
- The graph is undirected
- Vertices, edges and graph have no properties
- Edges are stored in a `std::list`

2.3 Counting the number of vertices

Let’s count all zero vertices of an empty graph!

Algorithm 5 Count the number of vertices

```
#include <cassert>
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
int get_n_vertices(const graph& g) noexcept
{
    const int n{
        static_cast<int>(boost::num_vertices(g))
    };
    assert(static_cast<unsigned long>(n)
        == boost::num_vertices(g)
    );
    return n;
}
```

The function ‘`get_n_vertices`’ takes the result of `boost::num_vertices`, converts it to `int` and checks if there was conversion error. We do so, as one should prefer using signed data types over unsigned ones in an interface ([4] chapter 9.2.2). To do so, in the function body its first statement, the unsigned long produced by `boost::num_vertices` get converted to an `int` using a `static_cast`. Using an unsigned integer over a (signed) integer for the sake of gaining that one more bit ([9] chapter 4.4) should be avoided. The integer ‘`n`’ is initialized using list-initialization, which is preferred over the other initialization syntaxes ([10] chapter 17.7.6).

The `assert` checks if the conversion back to unsigned long re-creates the original value, to check if no information has been lost. If information is lost, the program crashes. Use `assert` extensively ([9] chapter 24.5.18, [10] chapter 30.5, [11] chapter 68, [6] chapter 8.2, [5] hour 24, [4] chapter 2.6).

The function 'get_n_vertices' is demonstrated in algorithm 6, to measure the number of vertices of both the directed and undirected graph we are already able to create.

Algorithm 6 Demonstration of the 'get_n_vertices' function

```
#include <cassert>

#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"
#include "get_n_vertices.h"

void get_n_vertices_demo() noexcept
{
    const auto g = create_empty_directed_graph();
    assert(get_n_vertices(g) == 0);

    const auto h = create_empty_undirected_graph();
    assert(get_n_vertices(h) == 0);
}
```

Note that the type of graph does not matter here. One can count the number of vertices of every graph, as all graphs have vertices. Boost.Graph is very good at detecting operations that are not allowed, during compile time.

2.4 Counting the number of edges

Let's count all zero edges of an empty graph!

This is very similar to the previous chapter, only it uses `boost::num_edges` instead:

Algorithm 7 Count the number of edges

```
#include <cassert>
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
int get_n_edges(const graph& g) noexcept
{
    const int n{
        static_cast<int>(boost::num_edges(g))
    };
    assert(static_cast<unsigned long>(n)
        == boost::num_edges(g)
    );
    return n;
}
```

This code is similar to the 'get_n_vertices' function (algorithm 5, see rationale there) except 'boost::num_edges' is used, instead of 'boost::num_vertices', which also returns an unsigned long.

The function 'get_n_edges' is demonstrated in algorithm 8, to measure the number of edges of an empty directed and undirected graph.

Algorithm 8 Demonstration of the 'get_n_edges' function

```
#include <cassert>

#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"
#include "get_n_edges.h"

void get_n_edges_demo() noexcept
{
    const auto g = create_empty_directed_graph();
    assert(get_n_edges(g) == 0);

    const auto h = create_empty_undirected_graph();
    assert(get_n_edges(h) == 0);
}
```

2.5 Adding a vertex

Empty graphs are nice, now its time to add a vertex!

To add a vertex to a graph, the `boost::add_vertex` function is used as shows in algorithm 9:

Algorithm 9 Adding a vertex to a graph

```
#include <type_traits>
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_vertex(graph& g) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    boost::add_vertex(g);
}
```

The `static_assert` at the top of the function checks during compiling if the function is called with a non-const graph. One can freely omit this `static_assert`: you will get a compiler error anyways, be it a less helpful one.

Note that `boost::add_vertex` (in the 'add_vertex' function) returns a vertex descriptor, which is ignored for now. Vertex descriptors are looked at in more details at the chapter 2.6, as we need these to add an edge. Algorithm 10 shows how to add a vertex to a directed and undirected graph.

Algorithm 10 Demonstration of the 'add_vertex' function

```
#include "add_vertex.h"
#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"

void add_vertex_demo() noexcept
{
    auto g = create_empty_undirected_graph();
    add_vertex(g);
    assert(boost::num_vertices(g) == 1);

    auto h = create_empty_directed_graph();
    add_vertex(h);
    assert(boost::num_vertices(h) == 1);
}
```

This demonstration code creates two empty graphs, adds one vertex to each and then asserts that the number of vertices in each graph is one. This works for both types of graphs, as all graphs have vertices.

2.6 Vertex descriptors

A vertex descriptor is a handle to a vertex within a graph.

Vertex descriptors can be obtained by dereferencing a vertex iterator (see chapter 2.8). To do so, we first obtain some vertex iterators in chapter 2.7).

Vertex descriptors are used to:

- add an edge between two vertices, see chapter 2.9
- obtain properties of a vertex, for example the vertex's out-degrees (chapter 3.1), the vertex's name (chapter 4.4), or a custom vertex property (chapter 12.6)

In this tutorial, vertex descriptors have names prefixed with 'vd_', for example 'vd_1'.

2.7 Get the vertex iterators

You cannot get the vertices. This may sound unexpected, as it must be possible to work on the vertices of a graph. Working on the vertices of a graph is done through these steps:

- Obtain a vertex iterator pair from the graph
- Dereferencing a vertex iterator to obtain a vertex descriptor

'vertices' (not 'boost::vertices') is used to obtain a vertex iterator pair, as shown in algorithm 11. The first vertex iterator points to the first vertex (its descriptor, to be precise), the second points to beyond the last vertex (its descriptor, to be precise). In this tutorial, vertex iterator pairs have names prefixed with 'vip_', for example 'vip_1'.

Algorithm 11 Get the vertex iterators of a graph

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
std::pair<
    typename graph::vertex_iterator,
    typename graph::vertex_iterator
>
get_vertex_iterators(const graph& g) noexcept
{
    return vertices(g); //not boost::vertices
}
```

This is a somewhat trivial function, as it forwards the function call to 'vertices' (not 'boost::vertices').

These vertex iterators can be dereferenced to obtain the vertex descriptors. Note that 'get_vertex_iterators' will not be used often in isolation: usually one obtains the vertex descriptors immediately. Just for your reference, algorithm 12 demonstrates the 'get_vertices' function, by showing that the vertex iterators of an empty graph point to the same location.

Algorithm 12 Demonstration of 'get_vertex_iterators'

```
#include <cassert>
#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"
#include "get_vertex_iterators.h"

void get_vertex_iterators_demo() noexcept
{
    const auto g = create_empty_undirected_graph();
    const auto vip_g = get_vertex_iterators(g);
    assert(vip_g.first == vip_g.second);

    const auto h = create_empty_directed_graph();
    const auto vip_h = get_vertex_iterators(h);
    assert(vip_h.first == vip_h.second);
}
```

2.8 Get all vertex descriptors

Vertex descriptors are the way to manipulate those vertices. Let's go get the all!

Vertex descriptors are obtained from dereferencing vertex iterators. Algorithm 13 shows how to obtain all vertex descriptors from a graph.

Algorithm 13 Get all vertex descriptors of a graph

```
#include <vector>
#include "boost/graph/graph_traits.hpp"

template <typename graph>
std::vector<
    typename boost::graph_traits<graph>::vertex_descriptor
>
get_vertex_descriptors(const graph& g) noexcept
{
    using boost::graph_traits;
    using vd
        = typename graph_traits<graph>::vertex_descriptor;

    std::vector<vd> vds;
    const auto vis = vertices(g); //not boost::vertices
    const auto j = vis.second;
    for (auto i = vis.first; i!=j; ++i) {
        vds.emplace_back(*i);
    }
    return vds;
}
```

This is the first more complex piece of code. In the first lines, some 'using' statements allow for shorter type names⁶. The function 'vertices' (not `boost::vertices`!) returns a vertex iterator pair. The two iterators are extracted, of which the first iterator, 'i', points to the first vertex, and the second, 'j', points to beyond the last vertex. In the for-loop, 'i' loops from begin to end. Dereferencing it produces a vertex descriptor, which is stored in the `std::vector` using `emplace_back`. Prefer using `emplace_back` ([10] chapter 31.6, items 25 and 27).

Algorithm 14 demonstrates that an empty graph has no vertex descriptors:

⁶which may be necessary just to create a tutorial with code snippets that are readable

Algorithm 14 Demonstration of 'get_vertex_descriptors'

```
#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"
#include "get_vertex_descriptors.h"

void get_vertex_descriptors_demo() noexcept
{
    const auto g = create_empty_undirected_graph();
    const auto vds_g = get_vertex_descriptors(g);
    assert(vds_g.empty());

    const auto h = create_empty_directed_graph();
    const auto vds_h = get_vertex_descriptors(h);
    assert(vds_h.empty());
}
```

Because all graphs have vertices and thus vertex descriptors, the type of graph is unimportant for this code to compile.

2.9 Add an edge

To add an edge to a graph, two vertex descriptors are needed. A vertex descriptor is a handle to the vertex within a graph (vertex descriptors are looked at in more details in chapter 2.6). Algorithm 15 adds two vertices to a graph, and connects these two using `boost::add_edge`:

Algorithm 15 Adding (two vertices and) an edge to a graph

```
#include <cassert>
#include <type_traits>
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_edge(graph& g) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(
        vd_a, // Source/from
        vd_b, // Target/to
        g
    );

    assert(aer.second);
}
```

Algorithm 15 shows how to add an isolated edge to a graph (instead of allowing for graphs with higher connectivities). First, two vertices are created, using the function 'boost::add_vertex'. 'boost::add_vertex' returns a vertex descriptor (which I prefix with 'vd'), both of which are stored. The vertex descriptors are used to add an edge to the graph, using 'boost::add_edge'. 'boost::add_edge' returns a std::pair, consisting of an edge descriptor and a boolean success indicator. The success of adding the edge is checked by an assert statement. Here we assert that this insertion was successful. Insertion can fail if an edge is already present and duplicates are not allowed.

A demonstration of add_edge is shown in algorithm 16, in which an edge is added to both a directed and undirected graph, after which the number of edges and vertices is checked.

Algorithm 16 Demonstration of 'add_edge'

```
#include "add_edge.h"
#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"

void add_edge_demo() noexcept
{
    auto g = create_empty_undirected_graph();
    add_edge(g);
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 1);

    auto h = create_empty_directed_graph();
    add_edge(h);
    assert(boost::num_vertices(h) == 2);
    assert(boost::num_edges(h) == 1);
}
```

The graph type is unimportant: as all graph types have vertices and edges, edges can be added without possible compile problems.

2.10 boost::add_edge result

When using the function 'boost::add_edge', a 'std::pair<edge_descriptor, bool>' is returned. It contains both the edge descriptor (see chapter 2.12) and a boolean, which indicates insertion success.

In this tutorial, boost::add_edge results have named prefixed with 'aer_', for example 'aer_1'.

2.11 Getting the edge iterators

You cannot get the edges directly. Instead, working on the edges of a graph is done through these steps:

- Obtain an edge iterator pair from the graph
- Dereference an edge iterator to obtain an edge descriptor

'edges' (not boost::edges!) is used to obtain an edge iterator pair. The first edge iterator points to the first edge (its descriptor, to be precise), the second points to beyond the last edge (its descriptor, to be precise). In this tutorial, edge iterator pairs have named prefixed with 'eip_', for example 'eip_1'. Algorithm 17 shows how to obtain these:

Algorithm 17 Get the edge iterators of a graph

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
std::pair<
    typename graph::edge_iterator,
    typename graph::edge_iterator
>
get_edge_iterators(const graph& g) noexcept
{
    return edges(g); //not boost::edges
}
```

This is a somewhat trivial function, as all it does is forward to function call to 'edges' (not boost::edges!) These edge iterators can be dereferenced to obtain the edge descriptors. Note that this function will not be used often in isolation: usually one obtains the edge descriptors immediatly.

Algorithm 18 demonstrates 'get_edge_iterators' by showing that both iterators of the edge iterator pair point to the same location, when the graph is empty.

Algorithm 18 Demonstration of 'get_edge_iterators'

```
#include <cassert>
#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"
#include "get_edge_iterators.h"

void get_edge_iterators_demo() noexcept
{
    const auto g = create_empty_undirected_graph();
    const auto eip_g = get_edge_iterators(g);
    assert(eip_g.first == eip_g.second);

    auto h = create_empty_directed_graph();
    const auto eip_h = get_edge_iterators(h);
    assert(eip_h.first == eip_h.second);
}
```

2.12 Edge descriptors

An edge descriptor is a handle to an edge within a graph. They are similar to vertex descriptors (chapter 2.6).

Edge descriptors are used to obtain the name, or other properties, of an edge. In this tutorial, edge descriptors have names prefixed with 'ed_', for example 'ed_1'.

2.13 Get all edge descriptors

Obtaining all edge descriptors is similar to obtaining all vertex descriptors (algorithm 13), as shown in algorithm 19:

Algorithm 19 Get all edge descriptors of a graph

```
#include <vector>
#include "boost/graph/graph_traits.hpp"

template <typename graph>
std::vector<
    typename boost::graph_traits<graph>::edge_descriptor
> get_edge_descriptors(const graph& g) noexcept
{
    using boost::graph_traits;
    using ed = typename graph_traits<graph>::
        edge_descriptor;

    std::vector<ed> eds;

    const auto ei = edges(g); //not boost::edges
    const auto j = ei.second;

    for (auto i = ei.first; i!=j; ++i) {
        eds.emplace_back(*i);
    }
    return eds;
}
```

The only difference is that instead of the function 'vertices' (not `boost::vertices`!), 'edges' (not `boost::edges`!) is used.

Algorithm 20 demonstrates the 'get_edge_descriptor', by showing that empty graphs do not have any edge descriptors.

Algorithm 20 Demonstration of `get_edge_descriptors`

```
#include <cassert>
#include "create_empty_directed_graph.h"
#include "create_empty_undirected_graph.h"
#include "get_edge_descriptors.h"

void get_edge_descriptors_demo() noexcept
{
    const auto g = create_empty_directed_graph();
    const auto eds_g = get_edge_descriptors(g);
    assert(eds_g.empty());

    const auto h = create_empty_undirected_graph();
    const auto eds_h = get_edge_descriptors(h);
    assert(eds_h.empty());
}
```

2.14 Creating a directed graph

Finally, we are going to create a directed non-empty graph!

2.14.1 Graph

This directed graph is a two-state Markov chain, with two vertices and four edges, as depicted in figure 6:




Figure 6: The two-state Markov chain

Note that directed graphs can have edges that start and end in the same vertex. These are called self-loops.

2.14.2 Function to create such a graph

To create this two-state Markov chain, the following code can be used:

Algorithm 21 Creating the two-state Markov chain as depicted in figure 6

```
#include <cassert>
#include "create_empty_directed_graph.h"

boost::adjacency_list<>
create_markov_chain() noexcept
{
    auto g = create_empty_directed_graph();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);
    return g;
}
```

Instead of typing the complete type, we call the 'create_empty_directed_graph' function, and let auto figure out the type. The vertex descriptors (see chapter 2.6) created by two boost::add_vertex calls are stored to add an edge to the graph. Then boost::add_edge is called four times. Every time, its return type (see chapter 2.10) is checked for a successful insertion.

Note that the graph lacks all properties: nodes do not have names, nor do edges.

2.14.3 Creating such a graph

Algorithm 22 demonstrates the 'create_markov_chain_graph' function and checks if it has the correct amount of edges and vertices:

Algorithm 22 Demonstration of the 'create_markov_chain'

```
#include <cassert>
#include "create_markov_chain.h"

void create_markov_chain_demo() noexcept
{
    const auto g = create_markov_chain();
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 4);
}
```

2.14.4 The .dot file produced

Running a bit ahead, this graph can be converted to a .dot file using the 'save_graph_to_dot' function (algorithm 29). The .dot file created is displayed in algorithm 23:

Algorithm 23 .dot file created from the 'create_markov_chain_graph' function (algorithm 21), converted from graph to .dot file using algorithm 29

```
digraph G {
0;
1;
0->0 ;
0->1 ;
1->0 ;
1->1 ;
}
```

From the .dot file one can already see that the graph is directed, because:

- The first word, 'digraph', denotes a directed graph (where 'graph' would have indicated an undirectional graph)
- The edges are written as '->' (where undirected connections would be written as '-')

2.14.5 The .svg file produced

The .svg file of this graph is shown in figure 7:




Figure 7: .svg file created from the 'create_markov_chain' function (algorithm 21) its .dot file and converted from .dot file to .svg using algorithm 254

This figure shows that the graph is directed, as the edges have arrow heads. The vertices display the node index, which is the default behavior.

2.15 Creating K_2 , a fully connected undirected graph with two vertices

Finally, we are going to create an undirected non-empty graph!

2.15.1 Graph

To create a fully connected undirected graph with two vertices (also called K_2), one needs two vertices and one (undirected) edge, as depicted in figure 8.



Figure 8: K_2 : a fully connected undirected graph with two vertices

2.15.2 Function to create such a graph

To create K_2 , the following code can be used:

Algorithm 24 Creating K_2 as depicted in figure 8

```
#include "create_empty_undirected_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_k2_graph() noexcept
{
    auto g = create_empty_undirected_graph();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);
    return g;
}
```

This code is very similar to the 'add_edge' function (algorithm 15). Instead of typing the graph its type, we call the 'create_empty_undirected_graph' function and let auto figure it out. The vertex descriptors (see chapter 2.6) created by two boost::add_vertex calls are stored to add an edge to the graph. From boost::add_edge its return type (see chapter 2.10), it is only checked that insertion has been successful.

Note that the graph lacks all properties: nodes do not have names, nor do edges.

2.15.3 Creating such a graph

Algorithm 25 demonstrates how to 'create_k2_graph' and checks if it has the correct amount of edges and vertices:

Algorithm 25 Demonstration of 'create_k2_graph'

```
#include <cassert>

#include "create_k2_graph.h"

void create_k2_graph_demo() noexcept
{
    const auto g = create_k2_graph();
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 1);
}
```

2.15.4 The .dot file produced

Running a bit ahead, this graph can be converted to the .dot file as shown in algorithm 26:

Algorithm 26 .dot file created from the 'create_k2_graph' function (algorithm 24), converted from graph to .dot file using algorithm 29

```
graph G {  
0;  
1;  
0--1 ;  
}
```

From the .dot file one can already see that the graph is undirected, because:

- The first word, 'graph', denotes an undirected graph (where 'digraph' would have indicated a directional graph)
- The edge between 0 and 1 is written as '-' (where directed connections would be written as '->', '<-' or '<>')

2.15.5 The .svg file produced

Continuing to running a bit ahead, this .dot file can be converted to the .svg as shown in figure 9:




Figure 9: .svg file created from the 'create_k2_graph' function (algorithm 24) its .dot file, converted from .dot file to .svg using algorithm 254

Also this figure shows that the graph is undirected, otherwise the edge would have one or two arrow heads. The vertices display the node index, which is the default behavior.

3 Working on graphs without properties

Now that we can build a graph, there are some things we can do:

- Getting the vertices' out degrees: see chapter 3.1
- Saving a graph without properties to .dot file: see chapter 3.2
- Loading an undirected graph without properties from .dot file: see chapter 3.4
- Loading a directed graph without properties from .dot file: see chapter 3.3

3.1 Getting the vertices' out degree

Let's measure the out degree of all vertices in a graph!

The out degree of a vertex is the number of edges that originate at it.

The number of connections is called the 'degree' of the vertex. There are three types of degrees:

- in degree: the number of incoming connections, using 'in_degree' (not 'boost::in_edgree')
- out degree: the number of outgoing connections, using 'out_degree' (not 'boost::out_edgree')
- degree: sum of the in degree and out degree, using 'degree' (not 'boost::edgree')

Algorithm 27 shows how to obtain these:

Algorithm 27 Get the vertices' out degrees

```
#include <vector>

template <typename graph>
std::vector<int> get_vertex_out_degrees(
    const graph& g
) noexcept
{
    std::vector<int> v;
    const auto vis
        = vertices(g); //not boost::vertices
    const auto j = vis.second;
    for (auto i = vis.first; i!=j; ++i) {
        v.emplace_back(
            out_degree(*i,g) //not boost::out_degree
        );
    }
    return v;
}
```

The structure of this algorithm is similar to `get_vertex_descriptors` (algorithm 13), except that the out degrees from the vertex descriptors are stored. The out degree of a vertex iterator is obtained from the function '`out_degree`' (not `boost::out_degree`!).

Albeit that the K_2 graph and the two-state Markov chain are rather simple, we can use it to demonstrate '`get_vertex_out_degrees`' on, as shown in algorithm 28.

Algorithm 28 Demonstration of the 'get_vertex_out_degrees' function

```
#include <cassert>

#include "create_k2_graph.h"
#include "create_markov_chain.h"
#include "get_vertex_out_degrees.h"

void get_vertex_out_degrees_demo() noexcept
{
    const auto g = create_k2_graph();
    const std::vector<int> expected_out_degrees_g{1,1};
    const std::vector<int> vertex_out_degrees_g{
        get_vertex_out_degrees(g)
    };
    assert(expected_out_degrees_g
        == vertex_out_degrees_g
    );

    const auto h = create_markov_chain();
    const std::vector<int> expected_out_degrees_h{2,2};
    const std::vector<int> vertex_out_degrees_h{
        get_vertex_out_degrees(h)
    };
    assert(expected_out_degrees_h
        == vertex_out_degrees_h
    );
}
```

It is expected that K_2 has one out-degree for every vertex, where the two-state Markov chain is expected to have two out-degrees per vertex.

3.2 Saving a graph to a .dot file

Graphs are easily saved to a file, thanks to Graphviz. Graphviz (short for Graph Visualization Software) is a package of open-source tools for drawing graphs. It uses the DOT language for describing graphs, and these are commonly stored in (plain-text) .dot files (I show .dot file of every non-empty graph created, e.g. chapters 2.14.4 and 2.15.4)

Algorithm 29 Saving a graph to a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>

template <typename graph>
void save_graph_to_dot(
    const graph& g,
    const std::string& filename
) noexcept
{
    std::ofstream f(filename);
    boost::write_graphviz(f,g);
}
```

All the code does is create an `std::ofstream` (an output-to-file stream) and use `boost::write_graphviz` to write the DOT description of our graph to that stream. Instead of `'std::ofstream'`, one could use `std::cout` (a related output stream) to display the DOT language on screen directly.

Algorithm 30 shows how to use the `'save_graph_to_dot'` function:

Algorithm 30 Demonstration of the `'save_graph_to_dot'` function

```
#include "create_k2_graph.h"
#include "create_markov_chain.h"
#include "save_graph_to_dot.h"

void save_graph_to_dot_demo() noexcept
{
    const auto g = create_k2_graph();
    save_graph_to_dot(g, "create_k2_graph.dot");

    const auto h = create_markov_chain();
    save_graph_to_dot(h, "create_markov_chain.dot");
}
```

When using the `'save_graph_to_dot'` function (algorithm 29), only the structure of the graph is saved: all other properties like names are not stored. Algorithm 66 shows how to do so.

3.3 Loading a directed graph from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph is loaded, as shown in algorithm 31:

Algorithm 31 Loading a directed graph from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_directed_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
load_directed_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_directed_graph();
    boost::dynamic_properties p(
        boost::ignore_other_properties
    );
    boost::read_graphviz(f, g, p);
    return g;
}
```

In this algorithm, first it is checked if the file to load exists, using the 'is_regular_file' function (algorithm 255), after which an std::ifstream is opened. Then an empty directed graph is created, which saves us writing down the template arguments explicitly. Then, a boost::dynamic_properties is created with the 'boost::ignore_other_properties' in its constructor (using a default constructor here results in the run-time error 'property not found: node_id', see chapter 24.5). From this and the empty graph, 'boost::read_graphviz' is called to build up the graph.

Algorithm 32 shows how to use the 'load_directed_graph_from_dot' function:

Algorithm 32 Demonstration of the 'load_directed_graph_from_dot' function

```
#include <cassert>
#include "create_markov_chain.h"
#include "load_directed_graph_from_dot.h"
#include "save_graph_to_dot.h"

void load_directed_graph_from_dot_demo() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g = create_markov_chain();
    const std::string filename{
        "create_markov_chain.dot"
    };
    save_graph_to_dot(g, filename);
    const auto h = load_directed_graph_from_dot(filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
}
```

This demonstration shows how the Markov chain is created using the 'create_markov_chain_graph' function (algorithm 21), saved and then loaded. The loaded graph is then checked to be a two-state Markov chain.

3.4 Loading an undirected graph from a .dot file

Loading an undirected graph from a .dot file is very similar to loading a directed graph from a .dot file, as shown in chapter 3.3. Algorithm 33 show how to do so:

Algorithm 33 Loading an undirected graph from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_undirected_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
load_undirected_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_undirected_graph();
    boost::dynamic_properties p(
        boost::ignore_other_properties
    );
    boost::read_graphviz(f, g, p);
    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 3.3 describes the rationale of this function.

Algorithm 34 shows how to use the 'load_undirected_graph_from_dot' function:

Algorithm 34 Demonstration of the 'load_undirected_graph_from_dot' function

```
#include <cassert>
#include "create_k2_graph.h"
#include "load_undirected_graph_from_dot.h"
#include "save_graph_to_dot.h"

void load_undirected_graph_from_dot_demo() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g = create_k2_graph();
    const std::string filename{"create_k2_graph.dot"};
    save_graph_to_dot(g, filename);
    const auto h
        = load_undirected_graph_from_dot(filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
}
```

This demonstration shows how the K_2 graph is created using the 'create_k2_graph' function (algorithm 24), saved and then loaded. The loaded graph is checked to be a K_2 graph.

4 Building graphs with named vertices

Up until now, the graphs created have had edges and vertices without any property. In this chapter, graphs will be created, in which the vertices can have a name. This name will be of the `std::string` data type, but other types are possible as well. There are many more built-in properties edges and nodes can have (see chapter 25.1 for a list).

In this chapter, we will build the following graphs:

- An empty directed graph that allows for vertices with names: see chapter 4.1
- An empty undirected graph that allows for vertices with names: see chapter 4.2
- Two-state Markov chain with named vertices: see chapter 4.5
- K_2 with named vertices: see chapter 4.6

In the process, some basic (sometimes bordering trivial) functions are shown:

- Adding a named vertex: see chapter 4.3
- Getting the vertices' names: see chapter 4.4

After this chapter you may want to:

- Building graphs with named edges and vertices: see chapter 6
- Building graphs with bundled vertices: see chapter 8
- Building graphs with custom vertices: see chapter 12
- Building graphs with a graph name: see chapter 18

4.1 Creating an empty directed graph with named vertices

Let's create a trivial empty directed graph, in which the vertices can have a name:

Algorithm 35 Creating an empty directed graph with named vertices

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
create_empty_directed_named_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
        >
    > ();
}
```

Instead of using a `boost::adjacency_list` with default template argument, we will now have to specify four template arguments, where we only set the fourth to a non-default value.

Note there is some flexibility in this function: the data type of the vertex names is set to `std::string` by default, but can be of any other type if desired.

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is directed (due to the `boost::directedS`)
- The vertices have one property: they have a name, which is of data type `std::string` (due to the `boost::property<boost::vertex_name_t, std::string>`)
- Edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property<boost::vertex_name_t, std::string>`'. This can be read as: “vertices have the property '`boost::vertex_name_t`', that is of data type `std::string`”. Or simply: “vertices have a name that is stored as a `std::string`”.

Algorithm 36 shows how to create such a graph:

Algorithm	36	Demonstration	of	the	'create_empty_directed_named_vertices_graph' function
------------------	-----------	---------------	----	-----	---

```
#include <cassert>
#include <boost/graph/adjacency_list.hpp>
#include "create_empty_directed_named_vertices_graph.h"

void create_empty_named_directed_vertices_graph_demo()
    noexcept
{
    const auto g
        = create_empty_directed_named_vertices_graph();
    assert(boost::num_vertices(g) == 0);
    assert(boost::num_edges(g) == 0);
}
```

4.2 Creating an empty undirected graph with named vertices

Let's create a trivial empty undirected graph, in which the vertices can have a name:

Algorithm 37 Creating an empty undirected graph with named vertices

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
create_empty_undirected_named_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    > ();
}
```

This code is very similar to the code described in chapter 4.1, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`). See chapter 4.1 for most of the explanation.

Algorithm 38 shows how to create such a graph:

Algorithm 38 Demonstration of the 'create_empty_undirected_named_vertices_graph' function

```
#include <cassert>
#include <boost/graph/adjacency_list.hpp>
#include "create_empty_undirected_named_vertices_graph.h"

void create_empty_undirected_named_vertices_graph_demo()
    noexcept
{
    const auto g
        = create_empty_undirected_named_vertices_graph();
    assert(boost::num_vertices(g) == 0);
    assert(boost::num_edges(g) == 0);
}
```

4.3 Add a vertex with a name

Adding a vertex without a name was trivially easy (see chapter 2.5). Adding a vertex with a name takes slightly more work, as shown by algorithm 39:

Algorithm 39 Adding a vertex with a name

```
#include <string>
#include <type_traits>
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_named_vertex(
    const std::string& vertex_name,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");

    const auto vd_a = boost::add_vertex(g);
    auto vertex_name_map
        = get( //not boost::get
            boost::vertex_name, g
        );
    vertex_name_map[vd_a] = vertex_name;
}
```

Instead of calling 'boost::add_vertex' with an additional argument containing the name of the vertex⁷, multiple things need to be done:

First, the static_assert at the top of the function checks during compiling if the function is called with a non-const graph. One can freely omit this static_assert: you will get a compiler error anyways, be it a less helpful one.

When adding a new vertex to the graph, the vertex descriptor (as described in chapter 2.6) is stored. After obtaining the name map from the graph (using 'get(boost::vertex_name,g)'), the name of the vertex is set using that vertex descriptor. Note that 'get' has no 'boost::' prepending it, as it lives in the same (global) namespace the function is in. Using 'boost::get' will not compile.

Using 'add_named_vertex' is straightforward, as demonstrated by algorithm 40.

Algorithm 40 Demonstration of 'add_named_vertex'

```
#include <cassert>
#include "add_named_vertex.h"
#include "create_empty_undirected_named_vertices_graph.h"

void add_named_vertex_demo() noexcept
{
    auto g
        = create_empty_undirected_named_vertices_graph();
    add_named_vertex("Lex", g);
    assert(boost::num_vertices(g) == 1);
}
```

4.4 Getting the vertices' names

When the vertices of a graph have named vertices, one can extract them as such:

⁷I am unsure if this would have been a good interface. I am sure I expected this interface myself. I do see a problem with multiple properties and the order of initialization, but initialization could simply follow the same order as the the property list.

Algorithm 41 Get the vertices' names

```
#include <string>
#include <vector>
#include <boost/graph/properties.hpp>
#include <boost/graph/graph_traits.hpp>

template <typename graph>
std::vector<std::string> get_vertex_names(
    const graph& g
) noexcept
{
    std::vector<std::string> v;

    const auto vertex_name_map = get(
        boost::vertex_name, g
    );
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        v.emplace_back(
            get( //not boost::get
                vertex_name_map,
                *i
            )
        );
    }
    return v;
}
```

This code is very similar to 'get_vertex_out_degrees' (algorithm 27), as also there we iterated through all vertices, accessing all vertex descriptors sequentially.

The names of the vertices are obtained from a `boost::property_map` and then put into a `std::vector`.

The order of the vertex names may be different after saving and loading.

When trying to get the vertices' names from a graph without vertices with names, you will get the error 'formed reference to void' (see chapter 24.1).

Algorithm 42 shows how to add two named vertices, and check if the added names are retrieved as expected.

Algorithm 42 Demonstration of 'get_vertex_names'

```
#include <cassert>

#include "add_named_vertex.h"
#include "create_empty_undirected_named_vertices_graph.h"
#include "get_vertex_names.h"

void get_vertex_names_demo() noexcept
{
    auto g
        = create_empty_undirected_named_vertices_graph();
    const std::string vertex_name_1{"Chip"};
    const std::string vertex_name_2{"Chap"};
    add_named_vertex(vertex_name_1, g);
    add_named_vertex(vertex_name_2, g);
    const std::vector<std::string> expected_names{
        vertex_name_1, vertex_name_2
    };
    const std::vector<std::string> vertex_names{
        get_vertex_names(g)
    };
    assert(expected_names == vertex_names);
}
```

4.5 Creating a Markov chain with named vertices

Let's create a directed non-empty graph with named vertices!

4.5.1 Graph

We extend the Markov chain of chapter 2.14 by naming the vertices 'Good' and 'Not bad', as depicted in figure 10:




Figure 10: A two-state Markov chain where the vertices have texts

The vertex names are nonsensical, but I choose these for a reason: one name is only one word, the other has two words (as it contains a space). This will have implications for file I/O.

4.5.2 Function to create such a graph

To create this Markov chain, the following code can be used:

Algorithm 43 Creating a Markov chain with named vertices as depicted in figure 10

```
#include <cassert>
#include "create_empty_directed_named_vertices_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<boost::vertex_name_t, std::string>
>
create_named_vertices_markov_chain() noexcept
{
    auto g
        = create_empty_directed_named_vertices_graph();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    auto name_map = get( //not boost::get
        boost::vertex_name, g
    );
    name_map[vd_a] = "Good";
    name_map[vd_b] = "Not_bad";

    return g;
}
```

Most of the code is a repeat of algorithm 21, 'create_markov_chain_graph'. In the end of the function body, the names are obtained as a `boost::property_map` and set to the desired values.

4.5.3 Creating such a graph

Also the demonstration code (algorithm 44) is very similar to the demonstration code of the 'create_markov_chain_graph' function (algorithm 22).

Algorithm 44 Demonstrating the 'create_named_vertices_markov_chain' function

```
#include <cassert>

#include "create_named_vertices_markov_chain.h"
#include "get_vertex_names.h"

void create_named_vertices_markov_chain_demo() noexcept
{
    const auto g
        = create_named_vertices_markov_chain();
    const std::vector<std::string> expected_names{
        "Good", "Not_bad"
    };
    const std::vector<std::string> vertex_names{
        get_vertex_names(g)
    };
    assert(expected_names == vertex_names);
}
```

4.5.4 The .dot file produced

Because the vertices now have a name, this should be visible in the .dot file:

Algorithm 45 .dot file created from the 'create_named_vertices_markov_chain' function (algorithm 43), converted from graph to .dot file using algorithm 29

```
digraph G {
0[label=Good];
1[label="Not bad"];
0->0 ;
0->1 ;
1->0 ;
1->1 ;
}
```

As one can see, the names are stored as a label. Note that if a vertex name contains a space, the name will be surrounded by quotes, for example '1[label="Not bad"]';.

4.5.5 The .svg file produced

Now that the vertices have names, this should be reflected in the .svg:




Figure 11: .svg file created from the 'create_named_vertices_markov_chain' function (algorithm 43) its .dot file, converted from .dot file to .svg using algorithm 254

The .svg now shows the vertex names, instead of the vertex indices.

4.6 Creating K_2 with named vertices

Let's create an undirected non-empty graph with named vertices!

4.6.1 Graph

We extend K_2 of chapter 2.15 by naming the vertices 'Me' and 'My computer', as depicted in figure 12:




Figure 12: K_2 : a fully connected graph with two named vertices

4.6.2 Function to create such a graph

To create K_2 , the following code can be used:

Algorithm 46 Creating K_2 with named vertices as depicted in figure 12

```
#include <cassert>
#include "create_empty_undirected_named_vertices_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>
>
create_named_vertices_k2_graph() noexcept
{
    auto g
        = create_empty_undirected_named_vertices_graph();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);

    auto name_map = get( //not boost::get
        boost::vertex_name, g
    );
    name_map[vd_a] = "Me";
    name_map[vd_b] = "My_computer";

    return g;
}
```

Most of the code is a repeat of algorithm 24. In the end, the names are obtained as a `boost::property_map` and set to the desired names.

4.6.3 Creating such a graph

Also the demonstration code (algorithm 47) is very similar to the demonstration code of the 'create_k2_graph function' (algorithm 24).

Algorithm 47 Demonstrating the 'create_k2_graph' function

```
#include <cassert>

#include "create_named_vertices_k2_graph.h"
#include "get_vertex_names.h"

void create_named_vertices_k2_graph_demo() noexcept
{
    const auto g = create_named_vertices_k2_graph();
    const std::vector<std::string> expected_names{"Me", "My
        _computer"};
    const std::vector<std::string> vertex_names =
        get_vertex_names(g);
    assert(expected_names == vertex_names);
}
```

4.6.4 The .dot file produced

Because the vertices now have a name, this should be visible in the .dot file:

Algorithm 48 .dot file created from the 'create_named_vertices_k2' function (algorithm 46), converted from graph to .dot file using algorithm 66

```
graph G {
0[label=Me];
1[label="My computer"];
0--1 ;
}
```

As one can see, the names are stored as a label. Note that if a vertex name contains a space, the name will be surrounded by quotes, for example '1[label="My computer"]';.

4.6.5 The .svg file produced

Now that the vertices have names, this should be reflected in the .svg:




Figure 13: .svg file created from the 'create_named_vertices_k2_graph' function (algorithm 43) its .dot file, converted from .dot file to .svg using algorithm 66

The .svg now shows the vertex names, instead of the vertex indices.

5 Working on graphs with named vertices

When vertices have names, this name gives a way to find a vertex and working with it. This chapter shows some basic operations on graphs with named vertices.

- Check if there exists a vertex with a certain name: chapter 5.1
- Find a vertex by its name: chapter 5.2
- Get a named vertex its degree, in degree and out degree: chapter: 5.3
- Get a vertex its name from its vertex descriptor: chapter 5.4
- Set a vertex its name using its vertex descriptor: chapter 5.5
- Setting all vertices' names: chapter 5.6
- Clear a named vertex its edges: chapter 5.7
- Remove a named vertex: chapter 5.8
- Removing an edge between two named vertices: chapter 5.9
- Saving an directed/undirected graph with named vertices to a .dot file: chapter 5.10
- Loading a directed graph with named vertices from a .dot file: chapter 5.11
- Loading an undirected graph with named vertices from a .dot file: chapter 5.12

Especially the 'find_first_vertex_by_name' function (chapter 5.2) is important, as it shows how to obtain a vertex descriptor, which is used in later algorithms.

5.1 Check if there exists a vertex with a certain name

Before modifying our vertices, let's first determine if we can find a vertex by its name in a graph. After obtaining a name map, we obtain the vertex iterators, dereference these to obtain the vertex descriptors and then compare each vertex its name with the one desired.

Algorithm 49 Find if there is vertex with a certain name

```
#include <boost/graph/properties.hpp>

template <typename graph>
bool has_vertex_with_name(
    const std::string& vertex_name,
    const graph& g
) noexcept
{
    const auto vertex_name_map
        = get( //not boost::get
              boost::vertex_name,
              g
            );
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;
    for (auto i = vip.first; i!=j; ++i) {
        if (
            get( //not boost::get
                vertex_name_map,
                *i
            ) == vertex_name
        ) {
            return true;
        }
    }
    return false;
}
```

This function can be demonstrated as in algorithm 50, where a certain name cannot be found in an empty graph. After adding the desired name, it is found.

Algorithm 50 Demonstration of the 'has_vertex_with_name' function

```
#include <cassert>

#include "add_named_vertex.h"
#include "create_empty_undirected_named_vertices_graph.h"
#include "has_vertex_with_name.h"

void has_vertex_with_name_demo() noexcept
{
    auto g
        = create_empty_undirected_named_vertices_graph();
    assert(!has_vertex_with_name("Felix",g));
    add_named_vertex("Felix",g);
    assert(has_vertex_with_name("Felix",g));
}
```

Note that this function only finds if there is at least one vertex with that name: it does not tell how many vertices with that name exist in the graph.

5.2 Find a vertex by its name

Where STL functions work with iterators, here we obtain a vertex descriptor (see chapter 2.6) to obtain a handle to the desired vertex. Algorithm 51 shows how to obtain a vertex descriptor to the first (name) vertex found with a specific name.

Algorithm 51 Find the first vertex by its name

```
#include <cassert>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "has_vertex_with_name.h"

template <typename graph>
typename boost::graph_traits<graph>::vertex_descriptor
find_first_vertex_with_name(
    const std::string& name,
    const graph& g
) noexcept
{
    assert(has_vertex_with_name(name, g));
    const auto vertex_name_map
        = get(boost::vertex_name, g);
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        const std::string s{
            get( //not boost::get
                vertex_name_map,
                *i
            )
        };
        if (s == name) { return *i; }
    }
    assert(!"Should_not_get_here");
    throw; //Will crash the program
}
```

With the vertex descriptor obtained, one can read and modify the vertex and the edges surrounding it. Algorithm 52 shows some examples of how to do so.

Algorithm 52 Demonstration of the 'find_first_vertex_with_name' function

```
#include <cassert>

#include "create_named_vertices_k2_graph.h"
#include "find_first_vertex_with_name.h"

void find_first_vertex_with_name_demo() noexcept
{
    const auto g
        = create_named_vertices_k2_graph();
    const auto vd
        = find_first_vertex_with_name(
            "My_computer", g
        );
    assert(
        out_degree(vd, g) == 1 //not boost::out_degree
    );
    assert(in_degree(vd, g) == 1); //not boost::in_degree
}
```

5.3 Get a (named) vertex its degree, in degree and out degree

We already obtained all out degrees of all vertices in chapter 3.1 by just collecting all vertex descriptors. Here, we will search for a vertex with a certain name, obtain its vertex descriptor and find the number of connections it has.

With a vertex descriptor, we can read a vertex its types of degrees. Algorithm 51 shows how to find a vertex, obtain its vertex descriptor and then obtain the out degree from it.

Algorithm 53 Get the first vertex with a certain name its out degree from its vertex descriptor

```
#include <cassert>
#include "find_first_vertex_with_name.h"
#include "has_vertex_with_name.h"

template <typename graph>
int get_first_vertex_with_name_out_degree(
    const std::string& name,
    const graph& g) noexcept
{
    assert(has_vertex_with_name(name, g));
    const auto vd
        = find_first_vertex_with_name(name, g);
    const int od {
        static_cast<int>(
            out_degree(vd, g) //not boost::out_degree
        )
    };
    assert(static_cast<unsigned long>(od)
        == out_degree(vd, g)
    );

    return od;
}
```

Algorithm 54 shows how to use this function.

Algorithm 54 Demonstration of the 'get_first_vertex_with_name_out_degree' function

```
#include <cassert>
#include "create_named_vertices_k2_graph.h"
#include "get_first_vertex_with_name_out_degree.h"

void get_first_vertex_with_name_out_degree_demo()
    noexcept
{
    const auto g = create_named_vertices_k2_graph();
    assert(
        get_first_vertex_with_name_out_degree(
            "Me", g
        ) == 1
    );
    assert(
        get_first_vertex_with_name_out_degree(
            "My_computer", g
        ) == 1
    );
}
```

5.4 Get a vertex its name from its vertex descriptor

This may seem a trivial paragraph, as chapter 4.4 describes the 'get_vertex_names' algorithm, in which we get all vertices' names. But it does not allow to first find a vertex of interest and subsequently getting only that one its name.

To obtain the name from a vertex descriptor, one needs to pull out the name map and then look up the vertex of interest.

Algorithm 55 Get a vertex its name from its vertex descriptor

```
#include <string>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

template <typename graph>
std::string get_vertex_name(
    const typename boost::graph_traits<graph>::
        vertex_descriptor& vd,
    const graph& g
) noexcept
{
    const auto vertex_name_map
        = get( //not boost::get
              boost::vertex_name,
              g
            );
    return vertex_name_map[ vd ];
}
```

To use 'get_vertex_name', one first needs to obtain a vertex descriptor. Algorithm 56 shows a simple example:

Algorithm 56 Demonstration if the 'get_vertex_name' function

```
#include <cassert>

#include "add_named_vertex.h"
#include "create_empty_undirected_named_vertices_graph.h"
#include "find_first_vertex_with_name.h"
#include "get_vertex_name.h"

void get_vertex_name_demo() noexcept
{
    auto g
        = create_empty_undirected_named_vertices_graph();
    const std::string name{"Dex"};
    add_named_vertex(name, g);
    const auto vd
        = find_first_vertex_with_name(name, g);
    assert(get_vertex_name(vd, g) == name);
}
```

5.5 Set a (named) vertex its name from its vertex descriptor

If you know how to get the name from a vertex descriptor, setting it is just as easy, as shown in algorithm 57.

Algorithm 57 Set a vertex its name from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

template <typename graph>
void set_vertex_name(
    const std::string& any_vertex_name,
    const typename boost::graph_traits<graph>::
        vertex_descriptor& vd,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");

    auto vertex_name_map
        = get( //not boost::get
            boost::vertex_name,
            g
        );
    vertex_name_map[vd]
        = any_vertex_name;
}
```

To use 'set_vertex_name', one first needs to obtain a vertex descriptor. Algorithm 58 shows a simple example.

Algorithm 58 Demonstration if the 'set_vertex_name' function

```
#include <cassert>

#include "add_named_vertex.h"
#include "create_empty_undirected_named_vertices_graph.h"
#include "find_first_vertex_with_name.h"
#include "get_vertex_name.h"
#include "set_vertex_name.h"

void set_vertex_name_demo() noexcept
{
    auto g
        = create_empty_undirected_named_vertices_graph();
    const std::string old_name{"Dex"};
    add_named_vertex(old_name, g);
    const auto vd
        = find_first_vertex_with_name(old_name, g);
    assert(get_vertex_name(vd, g) == old_name);
    const std::string new_name{"Diggy"};
    set_vertex_name(new_name, vd, g);
    assert(get_vertex_name(vd, g) == new_name);
}
```

5.6 Setting all vertices' names

When the vertices of a graph have named vertices and you want to set all their names at once:

Algorithm 59 Setting the vertices' names

```
#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

template <typename graph>
void set_vertex_names(
    graph& g,
    const std::vector<std::string>& names
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    const auto vertex_name_map
        = get(boost::vertex_name, g);
    auto ni = std::begin(names);
    const auto names_end = std::end(names);
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;
    for (auto i = vip.first; i!=j; ++i, ++ni)
    {
        assert(ni != names_end);
        put(vertex_name_map, *i, *ni);
    }
}
```

A new function makes its appearance here: 'put' (not 'boost::put'), which is the opposite of 'get' (not 'boost::get')

This is not a very usefull function if the graph is complex. But for just creating graphs for debugging, it may come in handy.

5.7 Clear the edges of a named vertex

A vertex descriptor can be used to clear all in/out/both edges connected to a vertex. It is necessary to remove these connections before the vertex itself can be removed. There are three functions to remove the edges connected to a vertex:

- `boost::clear_vertex`: removes all edges to and from the vertex
- `boost::clear_out_edges`: removes all outgoing edges from the vertex (in

directed graphs only, else you will get a 'error: no matching function for call to clear_out_edges', as described in chapter 24.2)

- `boost::clear_in_edges`: removes all incoming edges from the vertex (in directed graphs only, else you will get a 'error: no matching function for call to clear_in_edges', as described in chapter 24.3)

In the algorithm 'clear_first_vertex_with_name' the 'boost::clear_vertex' algorithm is used, as the graph used is undirectional:

Algorithm 60 Clear the first vertex with a certain name

```
#include <boost/graph/adjacency_list.hpp>
#include "find_first_vertex_with_name.h"
#include "has_vertex_with_name.h"

template <typename graph>
void clear_first_vertex_with_name(
    const std::string& name,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");

    assert(has_vertex_with_name(name, g));
    const auto vd
        = find_first_vertex_with_name(name, g);
    boost::clear_vertex(vd, g);
}
```

Algorithm 61 shows the clearing of the first named vertex found.

Algorithm 61 Demonstration of the 'clear_first_vertex_with_name' function

```
#include <cassert>
#include "clear_first_vertex_with_name.h"
#include "create_named_vertices_k2_graph.h"

void clear_first_vertex_with_name_demo() noexcept
{
    auto g = create_named_vertices_k2_graph();
    assert(boost::num_edges(g) == 1);
    clear_first_vertex_with_name("My_computer", g);
    assert(boost::num_edges(g) == 0);
}
```

5.8 Remove a named vertex

A vertex descriptor can be used to remove a vertex from a graph. It is necessary to remove these connections (e.g. using `clear_first_vertex_with_name`, algorithm 60) before the vertex itself can be removed.

Removing a named vertex goes as follows: use the name of the vertex to get a first vertex descriptor, then call 'boost::remove_vertex', shown in algorithm 5.8:

Algorithm 62 Remove the first vertex with a certain name

```
#include <boost/graph/adjacency_list.hpp>
#include "find_first_vertex_with_name.h"
#include "has_vertex_with_name.h"

template <typename graph>
void remove_first_vertex_with_name(
    const std::string& name,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const"
    );

    assert(has_vertex_with_name(name, g));
    const auto vd
        = find_first_vertex_with_name(name, g);
    assert(degree(vd, g) == 0); //not degree
    boost::remove_vertex(vd, g);
}
```

Algorithm 63 shows the removal of the first named vertex found.

Algorithm 63 Demonstration of the 'remove_first_vertex_with_name' function

```
#include <cassert>

#include "clear_first_vertex_with_name.h"
#include "create_named_vertices_k2_graph.h"
#include "remove_first_vertex_with_name.h"

void remove_first_vertex_with_name_demo() noexcept
{
    auto g = create_named_vertices_k2_graph();
    clear_first_vertex_with_name(
        "My_computer", g
    );
    remove_first_vertex_with_name(
        "My_computer", g
    );
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 1);
}
```

Again, be sure that the vertex removed does not have any connections!

5.9 Removing the edge between two named vertices

Instead of looking for an edge descriptor, one can also remove an edge from two vertex descriptors (which is: the edge between the two vertices). Removing an edge between two named vertices named edge goes as follows: use the names of the vertices to get both vertex descriptors, then call 'boost::remove_edge' on those two, as shown in algorithm 64.

Algorithm 64 Remove the first edge with a certain name

```
#include "find_first_vertex_with_name.h"
#include "has_vertex_with_name.h"
#include "has_edge_between_vertices.h"

template <typename graph>
void remove_edge_between_vertices_with_names(
    const std::string& name_1,
    const std::string& name_2,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
    ;

    assert(has_vertex_with_name(name_1, g));
    assert(has_vertex_with_name(name_2, g));
    const auto vd_1
        = find_first_vertex_with_name(name_1, g);
    const auto vd_2
        = find_first_vertex_with_name(name_2, g);
    assert(has_edge_between_vertices(vd_1, vd_2, g));
    boost::remove_edge(vd_1, vd_2, g);
}
```

Algorithm 65 shows the removal of the first named edge found.

Algorithm 65 Demonstration of the 'remove_edge_between_vertices_with_names' function

```
#include <cassert>

#include "create_named_edges_and_vertices_k3_graph.h"
#include "remove_edge_between_vertices_with_names.h"

void remove_edge_between_vertices_with_names_demo()
    noexcept
{
    auto g = create_named_edges_and_vertices_k3_graph();
    assert(boost::num_edges(g) == 3);
    remove_edge_between_vertices_with_names("top", "right", g);
    assert(boost::num_edges(g) == 2);
}
```

5.10 Saving an directed/undirected graph with named vertices to a .dot file

If you used the 'create_named_vertices_k2_graph' function (algorithm 46) to produce a K_2 graph with named vertices, you can store these names in multiple ways:

- Using `boost::make_label_writer`
- Using a C++11 lambda function

I show both ways, because you may need all of them.

The created .dot file is shown at algorithm 48.

You can use all characters in the vertex without problems (for example: comma's, quotes, whitespace). This will not hold anymore for bundled and custom vertices in later chapters.

The 'save_named_vertices_graph_to_dot' functions below only save the structure of the graph and its vertex names. It ignores other edge and vertex properties.

5.10.1 Using `boost::make_label_writer`

The first implementation uses `boost::make_label_writer`, as shown in algorithm 66:

Algorithm 66 Saving a graph with named vertices to a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_names.h"

template <typename graph>
void save_named_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
) noexcept
{
    std::ofstream f(filename);
    const auto names = get_vertex_names(g);
    boost::write_graphviz(
        f,
        g,
        boost::make_label_writer(&names[0])
    );
}
```

Here, the function `boost::write_graphviz` is called with a new, third argument. After collecting all names, these are used by `boost::make_label_writer` to write the names as labels.

5.10.2 Using a C++11 lambda function

An equivalent algorithm is algorithm 67:

Algorithm 67 Saving a graph with named vertices to a .dot file using a lambda expression

```
#include <string>
#include <ostream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_names.h"

template <typename graph>
void save_named_vertices_graph_to_dot_using_lambda(
    const graph& g,
    const std::string& filename
) noexcept
{
    using vd_t = typename graph::vertex_descriptor;
    std::ofstream f(filename);
    const auto name_map = get(boost::vertex_name, g);
    boost::write_graphviz(
        f,
        g,
        [name_map](std::ostream& os, const vd_t& vd) {
            const std::string s{name_map[vd]};
            if (s.find('_') == std::string::npos) {
                //No space, no quotes around string
                os << "[label=" << s << " ]";
            }
            else {
                //Has space, put quotes around string
                os << "[label=\"" << s << "\" ]";
            }
        }
    );
}
```

In this code, a lambda function is used as a third argument.

A lambda function is an on-the-fly function that has these parts:

- the capture brackets '[]', to take variables within the lambda function
- the function argument parentheses '()', to put the function arguments in
- the function body '{}', where to write what it does

First we create a shorthand for the vertex descriptor type, that we'll need to use a lambda function argument (in C++14 you can use auto).

We then create a vertex name map at function scope (in C++17 this can be at lambda function scope) and pass it to the lambda function using its capture section.

The lambda function arguments need to be two: a `std::ostream&` (a reference to a general out-stream) and a vertex descriptor. In the function body, we get the name of the vertex the same as the `'get_vertex_name'` function (algorithm 55) and stream it to the out stream.

5.10.3 Demonstration

Algorithm 68 shows how to use (one of) the `'save_named_vertices_graph_to_dot'` function(s):

Algorithm 68 Demonstration of the `'save_named_vertices_graph_to_dot'` function

```
#include "create_named_vertices_k2_graph.h"
#include "create_named_vertices_markov_chain.h"
#include "save_named_vertices_graph_to_dot.h"

void save_named_vertices_graph_to_dot_demo() noexcept
{
    const auto g = create_named_vertices_k2_graph();
    save_named_vertices_graph_to_dot(
        g, "create_named_vertices_k2_graph.dot"
    );

    const auto h = create_named_vertices_markov_chain();
    save_named_vertices_graph_to_dot(
        h, "create_named_vertices_markov_chain.dot"
    );
}
```

When using the `'save_named_vertices_graph_to_dot'` function (algorithm 66), only the structure of the graph and the vertex names are saved: all other properties like edge name are not stored. Algorithm 97 shows how to do so.

5.11 Loading a directed graph with named vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with named vertices is loaded, as shown in algorithm 69:

Algorithm 69 Loading a directed graph with named vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_directed_named_vertices_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
load_directed_named_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_directed_named_vertices_graph();
    boost::dynamic_properties p; //_do_default_construct
    p.property("node_id", get(boost::vertex_name, g));
    p.property("label", get(boost::vertex_name, g));
    boost::read_graphviz(f, g, p);
    return g;
}
```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created. Next to this, a `boost::dynamic_properties` is created with its default constructor, after which we direct the `boost::dynamic_properties` to find a 'node_id' and 'label' in the vertex name map. From this and the empty graph, 'boost::read_graphviz' is called to build up the graph.

Algorithm 70 shows how to use the 'load_directed_graph_from_dot' function:

Algorithm 70 Demonstration of the 'load_directed_named_vertices_graph_from_dot' function

```
#include "create_named_vertices_markov_chain.h"
#include "load_directed_named_vertices_graph_from_dot.h"
#include "save_named_vertices_graph_to_dot.h"
#include "get_vertex_names.h"

void load_directed_named_vertices_graph_from_dot_demo()
    noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_named_vertices_markov_chain();
    const std::string filename{
        "create_named_vertices_markov_chain.dot"
    };
    save_named_vertices_graph_to_dot(g, filename);
    const auto h
        = load_directed_named_vertices_graph_from_dot(
            filename
        );
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_vertex_names(g) == get_vertex_names(h));
}
```

This demonstration shows how the Markov chain is created using the 'create_named_vertices_markov_chain' function (algorithm 21), saved and then loaded. The loaded graph is checked to be a directed graph similar to the Markov chain with the same vertex names (using the 'get_vertex_names' function, algorithm 41).

5.12 Loading an undirected graph with named vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with named vertices is loaded, as shown in algorithm 71:

Algorithm 71 Loading an undirected graph with named vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_undirected_named_vertices_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
load_undirected_named_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_undirected_named_vertices_graph();
    ;
    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id", get(boost::vertex_name, g));
    p.property("label", get(boost::vertex_name, g));
    boost::read_graphviz(f, g, p);
    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 5.11 describes the rationale of this function.

Algorithm 72 shows how to use the 'load_undirected_graph_from_dot' function:

Algorithm 72 Demonstration of the 'load_undirected_graph_from_dot' function

```
#include "create_named_vertices_k2_graph.h"
#include "load_undirected_named_vertices_graph_from_dot.h"
"

#include "save_named_vertices_graph_to_dot.h"
#include "get_vertex_names.h"

void load_undirected_named_vertices_graph_from_dot_demo()
    noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_named_vertices_k2_graph();
    const std::string filename{
        "create_named_vertices_k2_graph.dot"
    };
    save_named_vertices_graph_to_dot(g, filename);
    const auto h
        = load_undirected_named_vertices_graph_from_dot(
            filename
        );
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_vertex_names(g) == get_vertex_names(h));
}
```

This demonstration shows how K_2 with named vertices is created using the 'create_named_vertices_k2_graph' function (algorithm 46), saved and then loaded. The loaded graph is checked to be an undirected graph similar to K_2 , with the same vertex names (using the 'get_vertex_names' function, algorithm 41).

6 Building graphs with named edges and vertices

Up until now, the graphs created have had edges and vertices without any property. In this chapter, graphs will be created, in which edges vertices can have a name. This name will be of the `std::string` data type, but other types are possible as well. There are many more built-in properties edges and nodes can have (see the `boost/graph/properties.hpp` file for these).

In this chapter, we will build the following graphs:

- An empty directed graph that allows for edges and vertices with names: see chapter 6.1
- An empty undirected graph that allows for edges and vertices with names: see chapter 6.2
- Markov chain with named edges and vertices: see chapter 6.5
- K_3 with named edges and vertices: see chapter 6.6

In the process, some basic (sometimes bordering trivial) functions are shown:

- Adding an named edge: see chapter 6.3
- Getting the edges' names: see chapter 6.4

These functions are mostly there for completion and showing which data types are used.

6.1 Creating an empty directed graph with named edges and vertices

Let's create a trivial empty directed graph, in which the both the edges and vertices can have a name:

Algorithm 73 Creating an empty directed graph with named edges and vertices

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_empty_directed_named_edges_and_vertices_graph()
    noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    > ();
}
```

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is directed (due to the `boost::directedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- The edges have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::edge_name_t, std::string>`)
- The graph has no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fifth template argument '`boost::property<boost::edge_name_t, std::string>`'. This can be read as: “edges have the property '`boost::edge_name_t`', that is of data type '`std::string`'”. Or simply: “edges have a name that is stored as a `std::string`”.

Algorithm 74 shows how to create this graph. Note that all the earlier functions defined in this tutorial keep working as expected.

Algorithm	74	Demonstration	if	the	'cre-
		ate_empty_directed_named_edges_and_vertices_graph'	function		

```
#include <cassert>
#include "add_named_edge.h"
#include "
    create_empty_directed_named_edges_and_vertices_graph.h"
#include "get_edge_names.h"
#include "get_vertex_names.h"

void
    create_empty_directed_named_edges_and_vertices_graph_demo
    () noexcept
{
    using strings = std::vector<std::string>;
    auto g
        =
            create_empty_directed_named_edges_and_vertices_graph
            ();
    add_named_edge("Reed", g);
    const strings expected_vertex_names{"", ""};
    const strings vertex_names = get_vertex_names(g);
    assert(expected_vertex_names == vertex_names);
    const strings expected_edge_names{"Reed"};
    const strings edge_names = get_edge_names(g);
    assert(expected_edge_names == edge_names);
}
```

6.2 Creating an empty undirected graph with named edges and vertices

Let's create a trivial empty undirected graph, in which the both the edges and vertices can have a name:

Algorithm 75 Creating an empty undirected graph with named edges and vertices

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_empty_undirected_named_edges_and_vertices_graph()
    noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    > ();
}
```

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- The edges have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::edge_name_t, std::string>`)
- The graph has no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fifth template argument `'boost::property<boost::edge_name_t,std::string>'`. This can be read as: “edges have the property `'boost::edge_name_t'`, that is of data type `'std::string'`”. Or simply: “edges have a name that is stored as a `std::string`”.

Algorithm 76 shows how to create this graph. Note that all the earlier functions defined in this tutorial keep working as expected.

Algorithm	76	Demonstration	if	the	'cre-
		ate_empty_undirected_named_edges_and_vertices_graph'			function

```
#include <cassert>

#include "add_named_edge.h"
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"
#include "get_edge_names.h"
#include "get_vertex_names.h"

void
    create_empty_undirected_named_edges_and_vertices_graph_demo
    () noexcept
{
    using strings = std::vector<std::string>;
    auto g
        =
        create_empty_undirected_named_edges_and_vertices_graph
        ();
    add_named_edge("Reed", g);
    const strings expected_vertex_names{"", ""};
    const strings vertex_names = get_vertex_names(g);
    assert(expected_vertex_names == vertex_names);
    const strings expected_edge_names{"Reed"};
    const strings edge_names = get_edge_names(g);
    assert(expected_edge_names == edge_names);
}
```

6.3 Adding a named edge

Adding an edge with a name:

Algorithm 77 Add a vertex with a name

```
#include <cassert>
#include <string>
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_named_edge(
    const std::string& edge_name,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);

    auto edge_name_map
        = get( //not boost::get
              boost::edge_name, g
            );
    edge_name_map[aer.first] = edge_name;
}
```

In this code snippet, the edge descriptor (see chapter 2.12 if you need to refresh your memory) when using 'boost::add_edge' is used as a key to change the edge its name map.

The algorithm 78 shows how to add a named edge to an empty graph. When trying to add named vertices to graph without this property, you will get the error 'formed reference to void' (see chapter 24.1).

Algorithm 78 Demonstration of the 'add_named_edge' function

```
#include <cassert>
#include "add_named_edge.h"
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"

void add_named_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_named_edges_and_vertices_graph
            ();
    add_named_edge("Richards", g);
    assert(boost::num_edges(g) == 1);
}
```

6.4 Getting the edges' names

When the edges of a graph have named vertices, one can extract them as such:

Algorithm 79 Get the edges' names

```
#include <string>
#include <vector>
#include <boost/graph/properties.hpp>

template <typename graph>
std::vector<std::string> get_edge_names(const graph& g)
    noexcept
{
    std::vector<std::string> v;

    const auto edge_name_map = get(boost::edge_name, g);
    const auto eip = edges(g); //not boost::edges
    const auto j = eip.second;

    for (auto i = eip.first; i!=j; ++i) {
        v.emplace_back(
            get( //not boost::get
                edge_name_map,
                *i
            )
        );
    }
    return v;
}
```

The names of the edges are obtained from a `boost::property_map` and then put into a `std::vector`. The algorithm 80 shows how to apply this function.

The order of the edge names may be different after saving and loading.

Would you dare to try to get the edges' names from a graph without vertices with names, you will get the error 'formed reference to void' (see chapter 24.1).

Algorithm 80 Demonstration of the 'get_edge_names' function

```
#include <cassert>

#include "add_named_edge.h"
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"
#include "get_edge_names.h"

void get_edge_names_demo() noexcept
{
    auto g
        =
            create_empty_undirected_named_edges_and_vertices_graph
            ();
    const std::string edge_name_1{"Eugene"};
    const std::string edge_name_2{"Another_Eugene"};
    add_named_edge(edge_name_1, g);
    add_named_edge(edge_name_2, g);
    const std::vector<std::string> expected_names{
        edge_name_1, edge_name_2
    };
    const std::vector<std::string> edge_names{
        get_edge_names(g)
    };
    assert(expected_names == edge_names);
}
```

6.5 Creating Markov chain with named edges and vertices

6.5.1 Graph

We build this graph:




Figure 14: A two-state Markov chain where the vertices have texts *Sunny* and *Rainy*, and the edges have texts *Sometimes*, *Often*, *Rarely* and *Mostly*

6.5.2 Function to create such a graph

Here is the code:

Algorithm 81 Creating the two-state Markov chain as depicted in figure 14

```
#include <string>
#include "
    create_empty_directed_named_edges_and_vertices_graph.h
"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_named_edges_and_vertices_markov_chain() noexcept
{
    auto g
        =
            create_empty_directed_named_edges_and_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    auto vertex_name_map = get( //not boost::get
        boost::vertex_name, g
    );
    vertex_name_map[vd_a] = "Sunny";
    vertex_name_map[vd_b] = "Rainy";

    auto edge_name_map = get( //not boost::get
        boost::edge_name, g
    );
    edge_name_map[aer_aa.first] = "Sometimes";
    edge_name_map[aer_ab.first] = "Often";
    edge_name_map[aer_ba.first] = "Rarely";
    edge_name_map[aer_bb.first] = "Mostly";

    return g;
}
```

6.5.3 Creating such a graph

Here is the demo:

Algorithm 82 Demo of the 'create_named_edges_and_vertices_markov_chain' function (algorithm 81)

```
#include <cassert>
#include <iostream>
#include "create_named_edges_and_vertices_markov_chain.h"
#include "get_edge_names.h"
#include "get_vertex_names.h"

void create_named_edges_and_vertices_markov_chain_demo()
    noexcept
{
    using strings = std::vector<std::string>;

    const auto g
        = create_named_edges_and_vertices_markov_chain();

    const strings expected_vertex_names{
        "Sunny", "Rainy"
    };
    const strings vertex_names{
        get_vertex_names(g)
    };
    assert(expected_vertex_names == vertex_names);

    const strings expected_edge_names{
        "Sometimes", "Often", "Rarely", "Mostly"
    };

    const strings edge_names{get_edge_names(g)};
    assert(expected_edge_names == edge_names);
}
```

6.5.4 The .dot file produced

Algorithm 83 .dot file created from the 'create_named_edges_and_vertices_markov_chain' function (algorithm 81), converted from graph to .dot file using algorithm 29

```

digraph G {
0[label=Sunny];
1[label=Rainy];
0->0 [label="Sometimes"];
0->1 [label="Often"];
1->0 [label="Rarely"];
1->1 [label="Mostly"];
}

```

6.5.5 The .svg file produced




Figure 15: .svg file created from the 'create_named_edges_and_vertices_markov_chain' function (algorithm 81) its .dot file, converted from .dot file to .svg using algorithm 254

6.6 Creating K_3 with named edges and vertices

6.6.1 Graph

We extend the graph K_2 with named vertices of chapter 4.6 by adding names to the edges, as depicted in figure 16:




Figure 16: K_3 : a fully connected graph with three named edges and vertices

6.6.2 Function to create such a graph

To create K_3 , the following code can be used:

Algorithm 84 Creating K_3 as depicted in figure 16

```
#include <string>
#include <boost/graph/adjacency_list.hpp>
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_named_edges_and_vertices_k3_graph() noexcept
{
    auto g
        =
            create_empty_undirected_named_edges_and_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto vd_c = boost::add_vertex(g);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_bc = boost::add_edge(vd_b, vd_c, g);
    assert(aer_bc.second);
    const auto aer_ca = boost::add_edge(vd_c, vd_a, g);
    assert(aer_ca.second);

    auto vertex_name_map = get(boost::vertex_name, g);
    vertex_name_map[vd_a] = "top";
    vertex_name_map[vd_b] = "right";
    vertex_name_map[vd_c] = "left";

    auto edge_name_map = get(boost::edge_name, g);
    edge_name_map[aer_ab.first] = "AB";
    edge_name_map[aer_bc.first] = "BC";
    edge_name_map[aer_ca.first] = "CA";

    return g;
}
```

Most of the code is a repeat of algorithm 46. In the end, the edge names are

obtained as a `boost::property_map` and `set`.

6.6.3 Creating such a graph

Algorithm 85 shows how to create the graph and measure its edge and vertex names.

Algorithm 85 Demonstration of the 'create_named_edges_and_vertices_k3' function

```
#include <cassert>
#include <iostream>
#include "create_named_edges_and_vertices_k3_graph.h"
#include "get_edge_names.h"
#include "get_vertex_names.h"

void create_named_edges_and_vertices_k3_graph_demo()
    noexcept
{
    using strings = std::vector<std::string>;

    const auto g
        = create_named_edges_and_vertices_k3_graph();

    const strings expected_vertex_names{
        "top", "right", "left"
    };
    const strings vertex_names{
        get_vertex_names(g)
    };
    assert(expected_vertex_names == vertex_names);

    const strings expected_edge_names{
        "AB", "BC", "CA"
    };
    const strings edge_names{get_edge_names(g)};
    assert(expected_edge_names == edge_names);
}
```

6.6.4 The .dot file produced

Algorithm 86 .dot file created from the 'create_named_edges_and_vertices_k3_graph' function (algorithm 84), converted from graph to .dot file using algorithm 29

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}
```

6.6.5 The .svg file produced




Figure 17: .svg file created from the 'create_named_edges_and_vertices_k3_graph' function (algorithm 84) its .dot file, converted from .dot file to .svg using algorithm 254

7 Working on graphs with named edges and vertices

Working with named edges...

- Check if there exists an edge with a certain name: chapter 7.1
- Find a (named) edge by its name: chapter 7.2
- Get a (named) edge its name from its edge descriptor: chapter 7.3
- Set a (named) edge its name using its edge descriptor: chapter 7.4
- Remove a named edge: chapter 7.5
- Saving a graph with named edges and vertices to a .dot file: chapter 7.6
- Loading a directed graph with named edges and vertices from a .dot file: chapter 7.7
- Loading an undirected graph with named edges and vertices from a .dot file: chapter 7.8

Especially chapter 7.2 with the 'find_first_edge_by_name' algorithm shows how to obtain an edge descriptor, which is used in later algorithms.

7.1 Check if there exists an edge with a certain name

Before modifying our edges, let's first determine if we can find an edge by its name in a graph. After obtaining a name map, we obtain the edge iterators, dereference these to obtain the edge descriptors and then compare each edge its name with the one desired.

Algorithm 87 Find if there is an edge with a certain name

```
#include <string>
#include <boost/graph/properties.hpp>

template <typename graph>
bool has_edge_with_name(
    const std::string& name,
    const graph& g
) noexcept
{
    const auto edge_name_map
        = get( //not boost::get
              boost::edge_name,
              g
            );
    const auto eip
        = edges( //not boost::edges
               g
            );
    const auto j = eip.second;
    for (auto i = eip.first; i!=j; ++i) {
        if (get(edge_name_map, *i) == name) {
            return true;
        }
    }
    return false;
}
```

This function can be demonstrated as in algorithm 88, where a certain name cannot be found in an empty graph. After adding the desired name, it is found.

Algorithm 88 Demonstration of the 'has_edge_with_name' function

```
#include <cassert>

#include "add_named_edge.h"
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"
#include "has_edge_with_name.h"

void has_edge_with_name_demo() noexcept
{
    auto g =
        create_empty_undirected_named_edges_and_vertices_graph
        ();
    assert(!has_edge_with_name("Edward", g));
    add_named_edge("Edward", g);
    assert(has_edge_with_name("Edward", g));
}
```

Note that this function only finds if there is at least one edge with that name: it does not tell how many edges with that name exist in the graph.

7.2 Find an edge by its name

Where STL functions work with iterators, here we obtain an edge descriptor (see chapter 2.12) to obtain a handle to the desired edge. Algorithm 89 shows how to obtain an edge descriptor to the first (name) edge found with a specific name.

Algorithm 89 Find the first edge by its name

```
#include <string>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "has_edge_with_name.h"

template <typename graph>
typename boost::graph_traits<graph>::edge_descriptor
find_first_edge_with_name(
    const std::string& name,
    const graph& g
) noexcept
{
    assert(has_edge_with_name(name, g));

    const auto edge_name_map
        = get( //not boost::get
              boost::edge_name, g
              );
    const auto eip
        = edges(g); //not boost::edges
    const auto j = eip.second;

    for (auto i = eip.first; i!=j; ++i) {

        const std::string s{
            get(edge_name_map, *i)
        };
        if (s == name) { return *i; }
    }
    assert(!"Should_not_get_here");
    throw; //Will crash the program
}
```

With the edge descriptor obtained, one can read and modify the graph. Algorithm 90 shows some examples of how to do so.

Algorithm 90 Demonstration of the 'find_first_edge_by_name' function

```
#include <cassert>

#include "create_named_edges_and_vertices_k3_graph.h"
#include "find_first_edge_with_name.h"

void find_first_edge_with_name_demo() noexcept
{
    const auto g
        = create_named_edges_and_vertices_k3_graph();
    const auto ed
        = find_first_edge_with_name("AB", g);
    assert(boost::source(ed,g) != boost::target(ed,g));
}
```

7.3 Get a (named) edge its name from its edge descriptor

This may seem a trivial paragraph, as chapter 6.4 describes the 'get_edge_names' algorithm, in which we get all edges' names. But it does not allow to first find an edge of interest and subsequently getting only that one its name.

To obtain the name from an edgedescriptor, one needs to pull out the name map and then look up the edge of interest.

Algorithm 91 Get an edge its name from its edge descriptor

```
#include <string>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

template <typename graph>
std::string get_edge_name(
    const typename boost::graph_traits<graph>::
        edge_descriptor& ed,
    const graph& g
) noexcept
{
    const auto edge_name_map
        = get( //not boost::get
            boost::edge_name,
            g
        );
    return edge_name_map[ed];
}
```

To use 'get_edge_name', one first needs to obtain an edge descriptor. Algorithm 92 shows a simple example.

Algorithm 92 Demonstration if the 'get_edge_name' function

```
#include <cassert>

#include "add_named_edge.h"
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"
#include "find_first_edge_with_name.h"
#include "get_edge_name.h"

void get_edge_name_demo() noexcept
{
    auto g =
        create_empty_undirected_named_edges_and_vertices_graph
        ();
    const std::string name{"Dex"};
    add_named_edge(name, g);
    const auto ed = find_first_edge_with_name(name, g);
    assert(get_edge_name(ed, g) == name);
}
```

7.4 Set a (named) edge its name from its edge descriptor

If you know how to get the name from an edge descriptor, setting it is just as easy, as shown in algorithm 93.

Algorithm 93 Set an edge its name from its edge descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

template <typename graph>
void set_edge_name(
    const std::string& any_edge_name,
    const typename boost::graph_traits<graph>::
        edge_descriptor& vd,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");

    auto edge_name_map = get(boost::edge_name, g);
    edge_name_map[vd] = any_edge_name;
}
```

To use 'set_edge_name', one first needs to obtain an edge descriptor. Algorithm 94 shows a simple example.

Algorithm 94 Demonstration if the 'set_edge_name' function

```
#include <cassert>

#include "add_named_edge.h"
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"
#include "find_first_edge_with_name.h"
#include "get_edge_name.h"
#include "set_edge_name.h"

void set_edge_name_demo() noexcept
{
    auto g =
        create_empty_undirected_named_edges_and_vertices_graph
        ();
    const std::string old_name{"Dex"};
    add_named_edge(old_name, g);
    const auto vd = find_first_edge_with_name(old_name, g);
    assert(get_edge_name(vd, g) == old_name);
    const std::string new_name{"Diggy"};
    set_edge_name(new_name, vd, g);
    assert(get_edge_name(vd, g) == new_name);
}
```

7.5 Removing the first edge with a certain name

An edge descriptor can be used to remove an edge from a graph.

Removing a named edge goes as follows: use the name of the edge to get a first edge descriptor, then call 'boost::remove_edge', shown in algorithm 62:

Algorithm 95 Remove the first edge with a certain name

```
#include <boost/graph/adjacency_list.hpp>
#include "find_first_edge_with_name.h"
#include "has_edge_with_name.h"

template <typename graph>
void remove_first_edge_with_name(
    const std::string& name,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");

    assert(has_edge_with_name(name, g));
    const auto vd
        = find_first_edge_with_name(name, g);
    boost::remove_edge(vd, g);
}
```

Algorithm 96 shows the removal of the first named edge found.

Algorithm 96 Demonstration of the 'remove_first_edge_with_name' function

```
#include <cassert>

#include "create_named_edges_and_vertices_k3_graph.h"
#include "remove_first_edge_with_name.h"

void remove_first_edge_with_name_demo() noexcept
{
    auto g = create_named_edges_and_vertices_k3_graph();
    assert(boost::num_edges(g) == 3);
    assert(boost::num_vertices(g) == 3);
    remove_first_edge_with_name("AB", g);
    assert(boost::num_edges(g) == 2);
    assert(boost::num_vertices(g) == 3);
}
```

7.6 Saving an undirected graph with named edges and vertices as a .dot

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 84) to produce a K_3 graph with named edges and vertices, you can store these names additionally with algorithm 97:

Algorithm 97 Saving an undirected graph with named edges and vertices to a .dot file

```
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_edge_names.h"
#include "get_vertex_names.h"

template <typename graph>
void save_named_edges_and_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
)
{
    using my_edge_descriptor = typename graph::
        edge_descriptor;

    std::ofstream f(filename);
    const auto vertex_names = get_vertex_names(g);
    const auto edge_name_map = boost::get(boost::edge_name,
        g);
    boost::write_graphviz(
        f,
        g,
        boost::make_label_writer(&vertex_names[0]),
        [edge_name_map](std::ostream& out, const
            my_edge_descriptor& e) {
            out << "[label=\"" << edge_name_map[e] << "\"]";
        }
    );
}
```

If you created a graph with edges more complex than just a name, you will still just write these to the .dot file. Chapter 13.6 shows how to write custom vertices to a .dot file.

So, the 'save_named_edges_and_vertices_graph_to_dot' function (algorithm 29) saves only the structure of the graph and its edge and vertex names.

7.7 Loading a directed graph with named edges and vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with named edges and vertices is loaded, as shown in algorithm 98:

Algorithm 98 Loading a directed graph with named edges and vertices from a .dot file

```

#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_directed_named_edges_and_vertices_graph.h
"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_name_t, std::string
    >,
    boost::property<
        boost::edge_name_t, std::string
    >
>
load_directed_named_edges_and_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_directed_named_edges_and_vertices_graph
        ();
    boost::dynamic_properties p; //_do_default_construct
    p.property("node_id", get(boost::vertex_name, g));
    p.property("label", get(boost::vertex_name, g));
    p.property("edge_id", get(boost::edge_name, g));
    p.property("label", get(boost::edge_name, g));
    boost::read_graphviz(f, g, p);
    return g;
}

```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created. Next to this, a `boost::dynamic_properties` is created with its default constructor, after which we direct the `boost::dynamic_properties` to find a 'node_id' and 'label' in the vertex name map, 'edge_id' and 'label' to the edge name map. From this and the empty graph, 'boost::read_graphviz' is called to build up the graph.

Algorithm 99 shows how to use the 'load_directed_graph_from_dot' function:

Algorithm 99 Demonstration of the 'load_directed_named_edges_and_vertices_graph_from_dot' function

```
#include "create_named_edges_and_vertices_markov_chain.h"
#include "
    load_directed_named_edges_and_vertices_graph_from_dot.
    h"
#include "save_named_edges_and_vertices_graph_to_dot.h"
#include "get_vertex_names.h"

void
load_directed_named_edges_and_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_named_edges_and_vertices_markov_chain();
    const std::string filename{
        "create_named_edges_and_vertices_markov_chain.dot"
    };
    save_named_edges_and_vertices_graph_to_dot(g, filename)
        ;
    const auto h
        =
            load_directed_named_edges_and_vertices_graph_from_dot
            (
                filename
            );
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_vertex_names(g) == get_vertex_names(h));
}
```

This demonstration shows how the Markov chain is created using the 'create_named_edges_and_vertices_markov_chain' function (algorithm 81), saved and then loaded. The loaded graph is checked to be a directed graph similar to the Markov chain with the same edge and vertex names (using the 'get_edge_names' function, algorithm 79, and the 'get_vertex_names' function, algorithm 41).

7.8 Loading an undirected graph with named edges and vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with named edges and vertices is loaded, as shown in algorithm 100:

Algorithm 100 Loading an undirected graph with named edges and vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_undirected_named_edges_and_vertices_graph
    .h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >,
    boost::property<
        boost::edge_name_t, std::string
    >
>
>
load_undirected_named_edges_and_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_undirected_named_edges_and_vertices_graph
        ();
    boost::dynamic_properties p; //_do_default_construct
    p.property("node_id", get(boost::vertex_name, g));
    p.property("label", get(boost::vertex_name, g));
    p.property("edge_id", get(boost::edge_name, g));
    p.property("label", get(boost::edge_name, g));
    boost::read_graphviz(f, g, p);
    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 7.7 describes the rationale of this function.

Algorithm 101 shows how to use the 'load_undirected_graph_from_dot' function:

Algorithm 101 Demonstration of the 'load_undirected_named_edges_and_vertices_graph_from_dot' function

```
#include "create_named_edges_and_vertices_k3_graph.h"
#include "
    load_undirected_named_edges_and_vertices_graph_from_dot
    .h"
#include "save_named_edges_and_vertices_graph_to_dot.h"
#include "get_vertex_names.h"

void
load_undirected_named_edges_and_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_named_edges_and_vertices_k3_graph();
    const std::string filename{
        "create_named_edges_and_vertices_k3_graph.dot"
    };
    save_named_edges_and_vertices_graph_to_dot(g, filename)
        ;
    const auto h
        =
            load_undirected_named_edges_and_vertices_graph_from_dot
            (
                filename
            );
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_vertex_names(g) == get_vertex_names(h));
}
```

This demonstration shows how K_3 with named edges and vertices is created using the 'create_named_edges_and_vertices_k3_graph' function (algorithm 84), saved and then loaded. The loaded graph is checked to be an undirected graph similar to K_3 , with the same edge and vertex names (using the 'get_edge_names' function, algorithm 79, and the 'get_vertex_names'

function, algorithm 41).

8 Building graphs with bundled vertices

Up until now, the graphs created have had edges and vertices with the built-in name property. In this chapter, graphs will be created, in which the vertices can have a bundled 'my_bundled_vertex' type⁸. The following graphs will be created:

- An empty directed graph that allows for bundled vertices: see chapter 103
- An empty undirected graph that allows for bundled vertices: see chapter 8.2
- A two-state Markov chain with bundled vertices: see chapter 8.6
- K_2 with bundled vertices: see chapter 8.7

In the process, some basic (sometimes bordering trivial) functions are shown:

- Create the vertex class, called 'my_bundled_vertex': see chapter 8.1
- Adding a 'my_bundled_vertex': see chapter 8.4
- Getting the vertices 'my_bundled_vertex'-es: see chapter 8.5

These functions are mostly there for completion and showing which data types are used.

8.1 Creating the bundled vertex class

Before creating an empty graph with bundled vertices, that bundled vertex class must be created. In this tutorial, it is called 'my_bundled_vertex'. 'my_bundled_vertex' is a class that is nonsensical, but it can be replaced by any other class type.

Here I will show the header file of 'my_bundled_vertex', as the implementation of it is not important:

⁸I do not intend to be original in naming my data types

Algorithm 102 Declaration of `my_bundled_vertex`

```
#include <string>
#include <iosfwd>
#include <boost/property_map/dynamic_property_map.hpp>

struct my_bundled_vertex
{
    explicit my_bundled_vertex(
        const std::string& name = "",
        const std::string& description = "",
        const double x = 0.0,
        const double y = 0.0
    ) noexcept;
    std::string m_name;
    std::string m_description;
    double m_x;
    double m_y;
};

bool operator==(const my_bundled_vertex& lhs, const
    my_bundled_vertex& rhs) noexcept;
bool operator!=(const my_bundled_vertex& lhs, const
    my_bundled_vertex& rhs) noexcept;
```

'my_bundled_vertex' is a class that has multiple properties:

- It has four public member variables: the double 'm_x' ('m_' stands for member), the double 'm_y', the `std::string m_name` and the `std::string m_description`. These variables must be public
- It has a default constructor
- It is copyable
- It is comparable for equality (it has `operator==`), which is needed for searching

'my_bundled_vertex' does not have to have the stream operators defined for file I/O, as this goes via the public member variables.

8.2 Create the empty directed graph with bundled vertices

Algorithm 103 Creating an empty directed graph with bundled vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "my_bundled_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    my_bundled_vertex
>
create_empty_directed_bundled_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        my_bundled_vertex
    >();
}
```

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is directed (due to the `boost::directedS`)
- The vertices have one property: they have a bundled type, that is of data type `'my_bundled_vertex'`
- The edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument `'my_bundled_vertex'`. This can be read as: “vertices have the bundled property `'my_bundled_vertex'`”. Or simply: “vertices have a bundled type called `my_bundled_vertex`”.

8.3 Create the empty undirected graph with bundled vertices

Algorithm 104 Creating an empty undirected graph with bundled vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "my_bundled_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    my_bundled_vertex
>
create_empty_undirected_bundled_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        my_bundled_vertex
    >();
}
```

This code is very similar to the code described in chapter 8.2, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`).

8.4 Add a bundled vertex

Adding a bundled vertex is very similar to adding a named vertex (chapter 4.3).

Algorithm 105 Add a bundled vertex

```
#include <boost/graph/adjacency_list.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
void add_bundled_vertex(const my_bundled_vertex& v, graph
    & g) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
    ;

    const auto vd_a = boost::add_vertex(g);
    g[vd_a] = v;
}
```

When having added a new (abstract) vertex to the graph, the vertex descriptor is used to set the 'my_bundled_vertex' in the graph.

8.5 Getting the bundled vertices' my_vertexes⁹

When the vertices of a graph have any bundled 'my_bundled_vertex', one can extract these as such:

⁹the name 'my_vertexes' is chosen to indicate this function returns a container of my_vertex

Algorithm 106 Get the bundled vertices' my_vertexes

```
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
std::vector<my_bundled_vertex>
    get_bundled_vertex_my_vertexes(
        const graph& g
    ) noexcept
{
    std::vector<my_bundled_vertex> v;

    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        v.emplace_back(g[*i]);
    }
    return v;
}
```

The 'my_bundled_vertex' bundled in each vertex is obtained from a vertex descriptor and then put into a std::vector.

The order of the 'my_bundled_vertex' objects may be different after saving and loading.

When trying to get the vertices' my_bundled_vertex from a graph without these, you will get the error 'formed reference to void' (see chapter 24.1).

8.6 Creating a two-state Markov chain with bundled vertices

8.6.1 Graph

Figure 18 shows the graph that will be reproduced:




Figure 18: A two-state Markov chain where the vertices have bundled properties and the edges have no properties. The vertices' properties are nonsensical

8.6.2 Function to create such a graph

Here is the code creating a two-state Markov chain with bundled vertices:

Algorithm 107 Creating the two-state Markov chain as depicted in figure 18

```
#include <cassert>
#include "create_empty_directed_bundled_vertices_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    my_bundled_vertex
>
create_bundled_vertices_markov_chain() noexcept
{
    auto g
        = create_empty_directed_bundled_vertices_graph();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    g[vd_a] = my_bundled_vertex("Sunny",
        "Yellow_thing", 1.0, 2.0
    );
    g[vd_b] = my_bundled_vertex("Rainy",
        "Grey_things", 3.0, 4.0
    );

    return g;
}
```

8.6.3 Creating such a graph

Here is the demo:

Algorithm 108 Demo of the 'create_bundled_vertices_markov_chain' function (algorithm 107)

```
#include <cassert>
#include "create_bundled_vertices_markov_chain.h"
#include "get_bundled_vertex_my_vertexes.h"
#include "my_bundled_vertex.h"

void create_bundled_vertices_markov_chain_demo() noexcept
{
    const auto g
        = create_bundled_vertices_markov_chain();
    const std::vector<my_bundled_vertex>
        expected_my_vertexes{
            my_bundled_vertex("Sunny","Yellow_thing",1.0,2.0),
            my_bundled_vertex("Rainy","Grey_things",3.0,4.0)
        };
    const std::vector<my_bundled_vertex> vertex_my_vertexes
        {
            get_bundled_vertex_my_vertexes(g)
        };
    assert(expected_my_vertexes == vertex_my_vertexes);
}
```

8.6.4 The .dot file produced

Algorithm 109 .dot file created from the 'create_bundled_vertices_markov_chain' function (algorithm 107), converted from graph to .dot file using algorithm 122

```
digraph G {
0[label="Sunny", comment="Yellow thing", width=1, height=2];
1[label="Rainy", comment="Grey things", width=3, height=4];
0->0 ;
0->1 ;
1->0 ;
1->1 ;
}
```

8.6.5 The .svg file produced




Figure 19: .svg file created from the 'create_bundled_vertices_markov_chain' function (algorithm 107) its .dot file, converted from .dot file to .svg using algorithm 254

8.7 Creating K_2 with bundled vertices

8.7.1 Graph

We reproduce the K_2 with named vertices of chapter 4.6 , but with our bundled vertices instead.

8.7.2 Function to create such a graph

Algorithm 110 Creating K_2 as depicted in figure 12

```
#include "create_empty_undirected_bundled_vertices_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    my_bundled_vertex
>
create_bundled_vertices_k2_graph() noexcept
{
    auto g = create_empty_undirected_bundled_vertices_graph
        ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);
    g[vd_a] = my_bundled_vertex("A", "source", 0.0, 0.0);
    g[vd_b] = my_bundled_vertex("B", "target", 3.14, 3.14);
    return g;
}
```

Most of the code is a slight modification of the 'create_named_vertices_k2_graph' function (algorithm 46). In the end, (references to) the my_bundled_vertices are obtained and set with two bundled my_bundled_vertex objects.

8.7.3 Creating such a graph

Demo:

Algorithm 111 Demo of the 'create_bundled_vertices_k2_graph' function (algorithm 110)

```
#include <cassert>
#include "create_bundled_vertices_k2_graph.h"
#include "has_bundled_vertex_with_my_vertex.h"

void create_bundled_vertices_k2_graph_demo() noexcept
{
    const auto g = create_bundled_vertices_k2_graph();
    assert(boost::num_edges(g) == 1);
    assert(boost::num_vertices(g) == 2);
    assert(has_bundled_vertex_with_my_vertex(
        my_bundled_vertex("A", "source", 0.0, 0.0), g)
    );
    assert(has_bundled_vertex_with_my_vertex(
        my_bundled_vertex("B", "target", 3.14, 3.14), g)
    );
}
```

8.7.4 The .dot file produced

Algorithm 112 .dot file created from the 'create_bundled_vertices_k2_graph' function (algorithm 110), converted from graph to .dot file using algorithm 29

8.7.5 The .svg file produced

:-(


Figure 20: .svg file created from the 'create_bundled_vertices_k2_graph' function (algorithm 110) its .dot file, converted from .dot file to .svg using algorithm 254

9 Working on graphs with bundled vertices

When using graphs with bundled vertices, their state gives a way to find a vertex and working with it. This chapter shows some basic operations on graphs with bundled vertices.

- Check if there exists a vertex with a certain 'my_bundled_vertex': chapter 9.1
- Find a vertex with a certain 'my_bundled_vertex': chapter 9.2

- Get a vertex its 'my_bundled_vertex' from its vertex descriptor: chapter 9.3
- Set a vertex its 'my_bundled_vertex' using its vertex descriptor: chapter 9.4
- Setting all vertices their 'my_bundled_vertex'-es: chapter 9.5
- Storing an directed/undirected graph with bundled vertices as a .dot file: chapter 9.6
- Loading a directed graph with bundled vertices from a .dot file: chapter 9.7
- Loading an undirected directed graph with bundled vertices from a .dot file: chapter 9.8

9.1 Has a bundled vertex with a my_bundled_vertex

Before modifying our vertices, let's first determine if we can find a vertex by its bundled type ('my_bundled_vertex') in a graph. After obtain the vertex iterators, we can dereference each these to obtain the vertex descriptors and then compare each vertex its 'my_bundled_vertex' with the one desired.

Algorithm 113 Find if there is vertex with a certain my_bundled_vertex

```
#include <string>
#include <boost/graph/properties.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
bool has_bundled_vertex_with_my_vertex(
    const my_bundled_vertex& v,
    const graph& g
) noexcept
{
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;
    for (auto i = vip.first; i!=j; ++i) {
        if (g[*i] == v) {
            return true;
        }
    }
    return false;
}
```

This function can be demonstrated as in algorithm 114, where a certain `my_bundled_vertex` cannot be found in an empty graph. After adding the desired `my_bundled_vertex`, it is found.

Algorithm 114 Demonstration of the 'has_bundled_vertex_with_my_vertex' function

```
#include <cassert>
#include <iostream>

#include "add_bundled_vertex.h"
#include "create_empty_undirected_bundled_vertices_graph.h"
#include "has_bundled_vertex_with_my_vertex.h"
#include "my_bundled_vertex.h"

void has_bundled_vertex_with_my_vertex_demo() noexcept
{
    auto g = create_empty_undirected_bundled_vertices_graph();
    assert(!has_bundled_vertex_with_my_vertex(my_bundled_vertex("Felix"), g));
    add_bundled_vertex(my_bundled_vertex("Felix"), g);
    assert(has_bundled_vertex_with_my_vertex(my_bundled_vertex("Felix"), g));
}
```

Note that this function only finds if there is at least one bundled vertex with that `my_bundled_vertex`: it does not tell how many bundled vertices with that `my_bundled_vertex` exist in the graph.

9.2 Find a bundled vertex with a certain `my_bundled_vertex`

Where STL functions work with iterators, here we obtain a vertex descriptor (see chapter 2.6) to obtain a handle to the desired vertex. Algorithm 115 shows how to obtain a vertex descriptor to the first vertex found with a specific 'my_bundled_vertex' value.

Algorithm 115 Find the first vertex with a certain `my_bundled_vertex`

```
#include <cassert>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "has_bundled_vertex_with_my_vertex.h"
#include "my_bundled_vertex.h"

template <typename graph>
typename boost::graph_traits<graph>::vertex_descriptor
find_first_bundled_vertex_with_my_vertex(
    const my_bundled_vertex& v,
    const graph& g
) noexcept
{
    assert(has_bundled_vertex_with_my_vertex(v, g));
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        if (g[*i] == v) { return *i; }
    }
    assert(!"Should_not_get_here");
    throw; //Will crash the program
}
```

With the vertex descriptor obtained, one can read and modify the vertex and the edges surrounding it. Algorithm 116 shows some examples of how to do so.

Algorithm 116 Demonstration of the 'find_first_bundled_vertex_with_my_vertex' function

```
#include <cassert>

#include "create_bundled_vertices_k2_graph.h"
#include "find_first_bundled_vertex_with_my_vertex.h"

void find_first_bundled_vertex_with_my_vertex_demo()
    noexcept
{
    const auto g = create_bundled_vertices_k2_graph();
    const auto vd =
        find_first_bundled_vertex_with_my_vertex(
            my_bundled_vertex("A", "source", 0.0, 0.0),
            g
        );
    assert(out_degree(vd, g) == 1); //not boost::out_degree
    assert(in_degree(vd, g) == 1); //not boost::in_degree
}
```

9.3 Get a bundled vertex its 'my_bundled_vertex'

To obtain the 'my_bundled_vertex' from a vertex descriptor is simple:

Algorithm 117 Get a bundled vertex its my_vertex from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
my_bundled_vertex get_bundled_vertex_my_vertex(
    const typename boost::graph_traits<graph>::
        vertex_descriptor& vd,
    const graph& g
) noexcept
{
    return g[vd];
}
```

One can just use the graph as a property map and let it be looked-up.

To use 'get_bundled_vertex_my_vertex', one first needs to obtain a vertex descriptor. Algorithm 118 shows a simple example.

Algorithm 118 Demonstration if the 'get_bundled_vertex_my_vertex' function

```
#include <cassert>
#include "add_bundled_vertex.h"
#include "create_empty_undirected_bundled_vertices_graph.h"
#include "find_first_bundled_vertex_with_my_vertex.h"
#include "get_bundled_vertex_my_vertex.h"

void get_bundled_vertex_my_vertex_demo() noexcept
{
    auto g
        = create_empty_undirected_bundled_vertices_graph();
    const my_bundled_vertex v{"Dex"};
    add_bundled_vertex(v, g);
    const auto vd
        = find_first_bundled_vertex_with_my_vertex(v, g);
    assert(get_bundled_vertex_my_vertex(vd, g) == v);
}
```

9.4 Set a bundled vertex its my_vertex

If you know how to get the 'my_bundled_vertex' from a vertex descriptor, setting it is just as easy, as shown in algorithm 119.

Algorithm 119 Set a bundled vertex its my_vertex from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
void set_bundled_vertex_my_vertex(
    const my_bundled_vertex& v,
    const typename boost::graph_traits<graph>::
        vertex_descriptor& vd,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    g[vd] = v;
}
```

To use 'set_bundled_vertex_my_vertex', one first needs to obtain a vertex descriptor. Algorithm 120 shows a simple example.

Algorithm 120 Demonstration if the 'set_bundled_vertex_my_vertex' function

```
#include <cassert>

#include "add_bundled_vertex.h"
#include "create_empty_undirected_bundled_vertices_graph.h"
#include "find_first_bundled_vertex_with_my_vertex.h"
#include "get_bundled_vertex_my_vertex.h"
#include "set_bundled_vertex_my_vertex.h"

void set_bundled_vertex_my_vertex_demo() noexcept
{
    auto g = create_empty_undirected_bundled_vertices_graph();
    const my_bundled_vertex old_name{"Dex"};
    add_bundled_vertex(old_name, g);
    const auto vd =
        find_first_bundled_vertex_with_my_vertex(old_name, g);
    assert(get_bundled_vertex_my_vertex(vd, g) == old_name);
    const my_bundled_vertex new_name{"Diggy"};
    set_bundled_vertex_my_vertex(new_name, vd, g);
    assert(get_bundled_vertex_my_vertex(vd, g) == new_name);
}
```

9.5 Setting all bundled vertices' my_vertex objects

When the vertices of a graph are 'my_bundled_vertex' objects, one can set these as such:

Algorithm 121 Setting the bundled vertices' 'my_bundled_vertex'-es

```
#include <string>
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
void set_bundled_vertex_my_vertexes(
    graph& g,
    const std::vector<my_bundled_vertex>& my_vertexes
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
};

auto my_vertexes_begin = std::begin(my_vertexes);
const auto my_vertexes_end = std::end(my_vertexes);
const auto vip = vertices(g); //not boost::vertices
const auto j = vip.second;
for (
    auto i = vip.first;
    i!=j; ++i,
    ++my_vertexes_begin
) {
    assert(my_vertexes_begin != my_vertexes_end);
    g[*i] = *my_vertexes_begin;
}
}
```

9.6 Storing a graph with bundled vertices as a .dot

If you used the 'create_bundled_vertices_k2_graph' function (algorithm 110) to produce a K_2 graph with vertices associated with 'my_bundled_vertex' objects, you can store these with algorithm 122:

Algorithm 122 Storing a graph with bundled vertices as a .dot file

```
#include <fstream>
#include <string>
#include <boost/graph/graphviz.hpp>
#include "install_vertex_custom_type.h"
#include "install_vertex_is_selected.h"
#include "make_bundled_vertices_writer.h"
#include "my_custom_vertex.h"

template <typename graph>
void save_bundled_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
)
{
    std::ofstream f(filename);

    write_graphviz(f, g,
        make_bundled_vertices_writer(g)
    );
}

/*
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>
#include "my_bundled_vertex.h"

template <typename graph>
void save_bundled_vertices_graph_to_dot(const graph& g,
    const std::string& filename)
{
    using my_vertex_descriptor = typename graph::
        vertex_descriptor;
    std::ofstream f(filename);
    boost::write_graphviz(
        f,
        g,
        [g](std::ostream& out, const my_vertex_descriptor& vd
        ) {
            const my_bundled_vertex m{g[vd]};
            out << "[label="
                << m.m_name
                << ", "
                << m.m_description
                << ", "
                << m.m_x
                << ", "
                << m.m_y
                << "]"
            );
        }
    );
}
```

This code looks small, because we call the 'make_bundled_vertices_writer' function, which is shown in algorithm 123:

Algorithm 123 The 'make_bundled_vertices_writer' function

```
template <typename graph>
inline bundled_vertices_writer<graph>
make_bundled_vertices_writer(
    const graph& g
)
{
    return bundled_vertices_writer<
        graph
    >(g);
}
```

Also this function is forwarding the real work to the 'bundled_vertices_writer', shown in algorithm 124:

Algorithm 124 The 'bundled_vertices_writer' function

```
#include <ostream>

template <
    typename my_bundled_vertex_map
>
class bundled_vertices_writer {
public:
    bundled_vertices_writer(
        my_bundled_vertex_map any_bundled_vertex_map
    ) : m_bundled_vertex_map{any_bundled_vertex_map}
    {

    }

    template <class vertex_descriptor>
    void operator()(
        std::ostream& out,
        const vertex_descriptor& vd
    ) const noexcept {
        out
            << "[label=\"" << m_bundled_vertex_map[vd].m_name
            << "\",comment=\"" << m_bundled_vertex_map[vd].
                m_description
            << "\",width=" << m_bundled_vertex_map[vd].m_x
            << ",height=" << m_bundled_vertex_map[vd].m_y
            << "]"
        ;
    }
private:
    my_bundled_vertex_map m_bundled_vertex_map;
};
```

Here, some interesting things are happening: the writer needs the bundled property maps to work with and thus copies the whole graph to its internals. I have chosen to map the 'my_bundled_vertex' member variables to Graphviz attributes (see chapter 25.2 for most Graphviz attributes) as shown in table 2:

my_bundled_vertex variable	C++ data type	Graphviz data type	Graphviz attribute	
m_name	std::string	string	label	
m_description	std::string	string	comment	
m_x	double	double	width	
m_y	double	double	height	

Table 2: Mapping of my_bundled_vertex member variable and Graphviz attributes

Important in this mapping is that the C++ and the Graphviz data types match. I also chose attributes that matched as closely as possible.

9.7 Loading a directed graph with bundled vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with bundled vertices is loaded, as shown in algorithm 125:

Algorithm 125 Loading a directed graph with bundled vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_directed_bundled_vertices_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    my_bundled_vertex
>
load_directed_bundled_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_directed_bundled_vertices_graph();
        ;

    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id", get(&my_bundled_vertex::m_name, g));
    p.property("label", get(&my_bundled_vertex::m_name, g));
    p.property("comment", get(&my_bundled_vertex::
        m_description, g));
    p.property("width", get(&my_bundled_vertex::m_x, g));
    p.property("height", get(&my_bundled_vertex::m_y, g));
    boost::read_graphviz(f, g, p);

    return g;
}
```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created, to save typing the typename explicitly.

Then a `boost::dynamic_properties` is created with its default constructor, after which we set it to follow the same mapping as in the previous chapter. From this and the empty graph, '`boost::read_graphviz`' is called to build up the graph.

Algorithm 126 shows how to use the '`load_directed_bundled_vertices_graph_from_dot`' function:

Algorithm 126 Demonstration of the 'load_directed_bundled_vertices_graph_from_dot' function

```
#include "create_bundled_vertices_markov_chain.h"
#include "load_directed_bundled_vertices_graph_from_dot.h"
"

#include "save_bundled_vertices_graph_to_dot.h"
#include "get_bundled_vertex_my_vertexes.h"

void load_directed_bundled_vertices_graph_from_dot_demo()
    noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_bundled_vertices_markov_chain();
    const std::string filename{
        "create_bundled_vertices_markov_chain.dot"
    };
    save_bundled_vertices_graph_to_dot(g, filename);
    const auto h
        = load_directed_bundled_vertices_graph_from_dot(
            filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_bundled_vertex_my_vertexes(g)
        == get_bundled_vertex_my_vertexes(h)
    );
}
```

This demonstration shows how the Markov chain is created using the 'create_bundled_vertices_markov_chain' function (algorithm 107), saved and then loaded. The loaded graph is checked to be the same as the original.

9.8 Loading an undirected graph with bundled vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with bundled vertices is loaded, as shown in algorithm 127:

Algorithm 127 Loading an undirected graph with bundled vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_undirected_bundled_vertices_graph.
    h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    my_bundled_vertex
>
load_undirected_bundled_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_undirected_bundled_vertices_graph
        ();

    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id", get(&my_bundled_vertex::m_name, g)
    );
    p.property("label", get(&my_bundled_vertex::m_name, g));
    p.property("comment", get(&my_bundled_vertex::
        m_description, g));
    p.property("width", get(&my_bundled_vertex::m_x, g));
    p.property("height", get(&my_bundled_vertex::m_y, g));
    boost::read_graphviz(f, g, p);

    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 9.7 describes the rationale of this function.

Algorithm 128 shows how to use the 'load_undirected_bundled_vertices_graph_from_dot' function:

Algorithm 128 Demonstration of the 'load_undirected_bundled_vertices_graph_from_dot' function

```
#include <cassert>
#include "create_bundled_vertices_k2_graph.h"
#include "load_undirected_bundled_vertices_graph_from_dot
.h"
#include "save_bundled_vertices_graph_to_dot.h"
#include "get_bundled_vertex_my_vertexes.h"

void load_undirected_bundled_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_bundled_vertices_k2_graph();
    const std::string filename{
        "create_bundled_vertices_k2_graph.dot"
    };
    save_bundled_vertices_graph_to_dot(g, filename);
    const auto h
        = load_undirected_bundled_vertices_graph_from_dot(
            filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_bundled_vertex_my_vertexes(g)
        == get_bundled_vertex_my_vertexes(h)
    );
}
```

This demonstration shows how K_2 with bundled vertices is created using the 'create_bundled_vertices_k2_graph' function (algorithm 110), saved and then loaded. The loaded graph is checked to be the same as the original.

10 Building graphs with bundled edges and vertices

Up until now, the graphs created have had only bundled vertices. In this chapter, graphs will be created, in which both the edges and vertices have a bundled 'my_bundled_edge' and 'my_bundled_vertex' type¹⁰.

¹⁰I do not intend to be original in naming my data types

- An empty directed graph that allows for bundled edges and vertices: see chapter 10.2
- An empty undirected graph that allows for bundled edges and vertices: see chapter 10.3
- A two-state Markov chain with bundled edges and vertices: see chapter 10.6
- K_3 with bundled edges and vertices: see chapter 10.7

In the process, some basic (sometimes bordering trivial) functions are shown:

- Creating the 'my_bundled_edge' class: see chapter 10.1
- Adding a bundled 'my_bundled_edge': see chapter 10.4

These functions are mostly there for completion and showing which data types are used.

10.1 Creating the bundled edge class

In this example, I create a 'my_bundled_edge' class. Here I will show the header file of it, as the implementation of it is not important yet.

Algorithm 129 Declaration of my_bundled_edge

```
#include <string>
#include <iosfwd>

class my_bundled_edge
{
public:
    explicit my_bundled_edge(
        const std::string& name = "",
        const std::string& description = "",
        const double width = 1.0,
        const double height = 1.0
    ) noexcept;
    std::string m_name;
    std::string m_description;
    double m_width;
    double m_height;
};

bool operator==(const my_bundled_edge& lhs, const
    my_bundled_edge& rhs) noexcept;
bool operator!=(const my_bundled_edge& lhs, const
    my_bundled_edge& rhs) noexcept;
```

`my_bundled_edge` is a class that has multiple properties: two doubles `'m_width'` (`'m_'` stands for member) and `'m_height'`, and two `std::strings` `m_name` and `m_description`. `'my_bundled_edge'` is copyable, but cannot trivially be converted to a `std::string`. `'my_bundled_edge'` is comparable for equality (that is, `operator==` is defined).

`'my_bundled_edge'` does not have to have the stream operators defined for file I/O, as this goes via the public member variables.

10.2 Create an empty directed graph with bundled edges and vertices

Algorithm 130 Creating an empty directed graph with bundled edges and vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "my_bundled_edge.h"
#include "my_bundled_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    my_bundled_vertex,
    my_bundled_edge
>
create_empty_directed_bundled_edges_and_vertices_graph()
    noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        my_bundled_vertex,
        my_bundled_edge
    >();
}
```

This code is very similar to the code described in chapter 12.3, except that there is a new, fifth template argument:

```
boost::property<boost::edge_bundled_type_t, my_edge>
```

This can be read as: “edges have the property `'boost::edge_bundled_type_t'`, which is of data type `'my_bundled_edge'`”. Or simply: “edges have a bundled type called `my_bundled_edge`”.

Demo:

Algorithm 131 Demonstration of the 'create_empty_directed_bundled_edges_and_vertices_graph' function

```
#include "
    create_empty_directed_bundled_edges_and_vertices_graph
    .h"

void
    create_empty_directed_bundled_edges_and_vertices_graph_demo
    () noexcept
{
    const auto g =
        create_empty_directed_bundled_edges_and_vertices_graph
        ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

10.3 Create an empty undirected graph with bundled edges and vertices

Algorithm 132 Creating an empty undirected graph with bundled edges and vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "my_bundled_edge.h"
#include "my_bundled_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    my_bundled_vertex,
    my_bundled_edge
>
create_empty_undirected_bundled_edges_and_vertices_graph
(
    ) noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        my_bundled_vertex,
        my_bundled_edge
    >();
}
```

This code is very similar to the code described in chapter 10.2, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`).

Demo:

Algorithm 133 Demonstration of the 'create_empty_undirected_bundled_edges_and_vertices_graph' function

```
#include <cassert>
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"

void
    create_empty_undirected_bundled_edges_and_vertices_graph_demo
    () noexcept
{
    const auto g
        =
            create_empty_undirected_bundled_edges_and_vertices_graph
            ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

10.4 Add a bundled edge

Adding a bundled edge is very similar to adding a named edge (chapter 6.3).

Algorithm 134 Add a bundled edge

```
#include <cassert>
#include <boost/graph/adjacency_list.hpp>
#include "my_bundled_edge.h"

template <typename graph>
void add_bundled_edge(
    const my_bundled_edge& v,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);

    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);
    g[aer.first] = v;
}
```

When having added a new (abstract) edge to the graph, the edge descriptor is used to set the `my_edge` in the graph.

Here is the demo:

Algorithm 135 Demo of 'add_bundled_edge'

```
#include <cassert>
#include "add_bundled_edge.h"
#include "
    create_empty_directed_bundled_edges_and_vertices_graph
    .h"
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"

void add_bundled_edge_demo() noexcept
{
    auto g =
        create_empty_directed_bundled_edges_and_vertices_graph
        ();
    add_bundled_edge(my_bundled_edge("X"), g);
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 1);

    auto h =
        create_empty_undirected_bundled_edges_and_vertices_graph
        ();
    add_bundled_edge(my_bundled_edge("Y"), h);
    assert(boost::num_vertices(h) == 2);
    assert(boost::num_edges(h) == 1);
}
```

10.5 Getting the bundled edges my_edges

When the edges of a graph are 'my_bundled_edge' objects, one can extract these all as such:

Algorithm 136 Get the edges' my_bundled_edges

```
#include <vector>
#include "my_bundled_edge.h"

template <typename graph>
std::vector<my_bundled_edge> get_bundled_edge_my_edges(
    const graph& g
) noexcept
{
    std::vector<my_bundled_edge> v;

    const auto vip
        = edges(g); //not boost::edges
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        v.emplace_back(g[*i]);
    }
    return v;
}
```

The 'my_bundled_edge' object associated with the edges are obtained from the graph its property_map and then put into a std::vector.

Note: the order of the my_bundled_edge objects may be different after saving and loading.

When trying to get the edges' my_bundled_edge objects from a graph without bundled edges objects associated, you will get the error 'formed reference to void' (see chapter 24.1).

10.6 Creating a Markov-chain with bundled edges and vertices

10.6.1 Graph

Figure 21 shows the graph that will be reproduced:




Figure 21: A two-state Markov chain where the edges and vertices have bundled properties. The edges' and vertices' properties are nonsensical

10.6.2 Function to create such a graph

Here is the code creating a two-state Markov chain with bundled edges and vertices:

Algorithm 137 Creating the two-state Markov chain as depicted in figure 21

```
#include <cassert>
#include "
    create_empty_directed_bundled_edges_and_vertices_graph
    .h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    my_bundled_vertex,
    my_bundled_edge
>
create_bundled_edges_and_vertices_markov_chain() noexcept
{
    auto g
        =
            create_empty_directed_bundled_edges_and_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    g[vd_a]
        = my_bundled_vertex("Sunny", "Yellow_thing", 1.0, 2.0);
    g[vd_b]
        = my_bundled_vertex("Rainy", "Grey_things", 3.0, 4.0);

    g[aer_aa.first]
        = my_bundled_edge("Sometimes", "20%", 1.0, 2.0);
    g[aer_ab.first]
        = my_bundled_edge("Often", "80%", 3.0, 4.0);
    g[aer_ba.first]
        = my_bundled_edge("Rarely", "10%", 5.0, 6.0);
    g[aer_bb.first]
        = my_bundled_edge("Mostly", "90%", 7.0, 8.0);

    return g;
}
```

10.6.3 Creating such a graph

Here is the demo:

Algorithm 138 Demo of the 'create_bundled_edges_and_vertices_markov_chain' function (algorithm 137)

```
#include <cassert>
#include "create_bundled_edges_and_vertices_markov_chain.h"
#include "get_bundled_vertex_my_vertexes.h"
#include "my_bundled_vertex.h"

void create_bundled_edges_and_vertices_markov_chain_demo
() noexcept
{
    const auto g
    = create_bundled_edges_and_vertices_markov_chain();
    const std::vector<my_bundled_vertex>
    expected_my_bundled_vertexes{
        my_bundled_vertex("Sunny",
            "Yellow_thing",1.0,2.0
        ),
        my_bundled_vertex("Rainy",
            "Grey_things",3.0,4.0
        )
    };
    const std::vector<my_bundled_vertex>
    vertex_my_bundled_vertexes{
        get_bundled_vertex_my_vertexes(g)
    };
    assert(expected_my_bundled_vertexes
        == vertex_my_bundled_vertexes
    );
}
```

10.6.4 The .dot file produced

Algorithm 139 .dot file created from the 'create_bundled_edges_and_vertices_markov_chain' function (algorithm 137), converted from graph to .dot file using algorithm 29

```
digraph G {
0[label="Sunny, Yellow thing, 1, 2"];
1[label="Rainy, Grey things, 3, 4"];
0->0 [label="Sometimes, 20%, 1, 2"];
0->1 [label="Often, 80%, 3, 4"];
1->0 [label="Rarely, 10%, 5, 6"];
1->1 [label="Mostly, 90%, 7, 8"];
}
```

10.6.5 The .svg file produced

:-(

Figure 22: .svg file created from the 'create_bundled_edges_and_vertices_markov_chain' function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

10.7 Creating K_3 with bundled edges and vertices

Instead of using edges with a name, or other properties, here we use a bundled edge class called 'my_bundled_edge'.

10.7.1 Graph

We reproduce the K_3 with named edges and vertices of chapter 6.6 , but with our bundled edges and vertices instead:

[graph here]

10.7.2 Function to create such a graph

Algorithm 140 Creating K_3 as depicted in figure 16

```
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    my_bundled_vertex,
    my_bundled_edge
>
create_bundled_edges_and_vertices_k3_graph() noexcept
{
    auto g
        =
            create_empty_undirected_bundled_edges_and_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto vd_c = boost::add_vertex(g);
    const auto aer_a = boost::add_edge(vd_a, vd_b, g);
    const auto aer_b = boost::add_edge(vd_b, vd_c, g);
    const auto aer_c = boost::add_edge(vd_c, vd_a, g);
    assert(aer_a.second);
    assert(aer_b.second);
    assert(aer_c.second);

    g[vd_a]
        = my_bundled_vertex("top", "source", 0.0, 0.0);
    g[vd_b]
        = my_bundled_vertex("right", "target", 3.14, 0);
    g[vd_c]
        = my_bundled_vertex("left", "target", 0, 3.14);

    g[aer_a.first]
        = my_bundled_edge("AB", "first", 0.0, 0.0);
    g[aer_b.first]
        = my_bundled_edge("BC", "second", 3.14, 3.14);
    g[aer_c.first]
        = my_bundled_edge("CA", "third", 3.14, 3.14);

    return g;
}
```

Most of the code is a slight modification of algorithm 84. In the end, the `my_edges` and `my_vertices` are obtained as the graph its `property_map` and set with the `'my_bundled_edge'` and `'my_bundled_vertex'` objects.

10.7.3 Creating such a graph

Here is the demo:

Algorithm 141 Demo of the `'create_bundled_edges_and_vertices_k3_graph'` function (algorithm 140)

```
#include <cassert>
#include "add_bundled_edge.h"
#include "add_bundled_vertex.h"
#include "create_bundled_edges_and_vertices_k3_graph.h"

void create_bundled_edges_and_vertices_k3_graph_demo()
    noexcept
{
    auto g
        = create_bundled_edges_and_vertices_k3_graph();
    assert(boost::num_edges(g) == 3);
    assert(boost::num_vertices(g) == 3);
    add_bundled_vertex(my_bundled_vertex("v"), g);
    add_bundled_edge(my_bundled_edge("e"), g);
}
```

10.7.4 The .dot file produced

Algorithm 142 .dot file created from the `'create_bundled_edges_and_vertices_markov_chain'` function (algorithm 140), converted from graph to .dot file using algorithm 29

```
:-(
```

10.7.5 The .svg file produced

```
:-(
```

Figure 23: .svg file created from the `'create_bundled_edges_and_vertices_k3_graph'` function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

11 Working on graphs with bundled edges and vertices

11.1 Has a my_bundled_edge

Before modifying our edges, let's first determine if we can find an edge by its bundled type ('my_bundled_edge') in a graph. After obtaining a my_bundled_edge map, we obtain the edge iterators, dereference these to obtain the edge descriptors and then compare each edge its my_bundled_edge with the one desired.

Algorithm 143 Find if there is a bundled edge with a certain my_bundled_edge

```
#include <boost/graph/properties.hpp>
#include "my_bundled_edge.h"

template <typename graph>
bool has_bundled_edge_with_my_edge(
    const my_bundled_edge& e,
    const graph& g
) noexcept
{
    const auto eip
        = edges(g); //not boost::edges
    const auto j = eip.second;

    for (auto i = eip.first; i!=j; ++i) {
        if (g[*i] == e) {
            return true;
        }
    }
    return false;
}
```

This function can be demonstrated as in algorithm 144, where a certain 'my_bundled_edge' cannot be found in an empty graph. After adding the desired my_bundled_edge, it is found.

Algorithm 144 Demonstration of the 'has_bundled_edge_with_my_edge' function

```
#include <cassert>
#include "add_bundled_edge.h"
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"
#include "has_bundled_edge_with_my_edge.h"

void has_bundled_edge_with_my_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_bundled_edges_and_vertices_graph
                ();
    assert (
        !has_bundled_edge_with_my_edge(
            my_bundled_edge("Edward"), g
        )
    );
    add_bundled_edge(my_bundled_edge("Edward"), g);
    assert (
        has_bundled_edge_with_my_edge(
            my_bundled_edge("Edward"), g
        )
    );
}
```

Note that this function only finds if there is at least one edge with that my_bundled_edge: it does not tell how many edges with that my_bundled_edge exist in the graph.

11.2 Find a my_bundled_edge

Where STL functions work with iterators, here we obtain an edge descriptor (see chapter 2.12) to obtain a handle to the desired edge. Algorithm 145 shows how to obtain an edge descriptor to the first edge found with a specific my_bundled_edge value.

Algorithm 145 Find the first bundled edge with a certain `my_bundled_edge`

```
#include <cassert>
#include <boost/graph/graph_traits.hpp>
#include "has_bundled_edge_with_my_edge.h"
#include "has_custom_edge_with_my_edge.h"
#include "my_bundled_edge.h"

template <typename graph>
typename boost::graph_traits<graph>::edge_descriptor
find_first_bundled_edge_with_my_edge(
    const my_bundled_edge& e,
    const graph& g
) noexcept
{
    assert(has_bundled_edge_with_my_edge(e, g));
    const auto eip = edges(g); //not boost::edges
    const auto j = eip.second;

    for (auto i = eip.first; i!=j; ++i) {
        if (g[*i] == e) {
            return *i;
        }
    }
    assert(!"Should_not_get_here");
    throw; //Will crash the program
}
```

With the edge descriptor obtained, one can read and modify the edge and the vertices surrounding it. Algorithm 146 shows some examples of how to do so.

Algorithm 146 Demonstration of the 'find_first_bundled_edge_with_my_edge' function

```
#include <cassert>

#include "create_bundled_edges_and_vertices_k3_graph.h"
#include "find_first_bundled_edge_with_my_edge.h"

void find_first_bundled_edge_with_my_edge_demo() noexcept
{
    const auto g
        = create_bundled_edges_and_vertices_k3_graph();
    const auto ed
        = find_first_bundled_edge_with_my_edge(
            my_bundled_edge("AB", "first", 0.0, 0.0),
            g
        );
    assert(boost::source(ed, g)
        != boost::target(ed, g)
    );
}
```

11.3 Get an edge its my_bundled_edge

To obtain the my_edeg from an edge descriptor, one needs to pull out the my_bundled_edges map and then look up the my_edge of interest.

Algorithm 147 Get a vertex its `my_bundled_vertex` from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
my_custom_edge get_custom_edge_my_edge(
    const typename boost::graph_traits<graph>::
        edge_descriptor& vd,
    const graph& g
) noexcept
{
    const auto my_edge_map
        = get( //not boost::get
            boost::edge_custom_type,
            g
        );
    return my_edge_map[vd];
}
```

To use 'get_bundled_edge_my_bundled_edge', one first needs to obtain an edge descriptor. Algorithm 148 shows a simple example.

Algorithm 148 Demonstration if the 'get_bundled_edge_my_edge' function

```
#include <cassert>

#include "add_bundled_edge.h"
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"
#include "find_first_bundled_edge_with_my_edge.h"
#include "get_bundled_edge_my_edge.h"

void get_bundled_edge_my_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_bundled_edges_and_vertices_graph
            ();
    const my_bundled_edge edge{"Dex"};
    add_bundled_edge(edge, g);
    const auto ed
        = find_first_bundled_edge_with_my_edge(edge, g);
    assert(get_bundled_edge_my_edge(ed,g) == edge);
}
```

11.4 Set an edge its my_bundled_edge

If you know how to get the my_bundled_edge from an edge descriptor, setting it is just as easy, as shown in algorithm 149.

Algorithm 149 Set a bundled edge its `my_bundled_edge` from its edge descriptor

```
#include <boost/graph/properties.hpp>
#include "my_bundled_edge.h"

template <typename graph>
void set_bundled_edge_my_edge(
    const my_bundled_edge& name,
    const typename boost::graph_traits<graph>::
        edge_descriptor& ed,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
    g[ed] = name;
}
```

To use 'set_bundled_edge_my_edge', one first needs to obtain an edge descriptor. Algorithm 150 shows a simple example.

Algorithm 150 Demonstration if the 'set_bundled_edge_my_edge' function

```
#include <cassert>

#include "add_bundled_edge.h"
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"
#include "find_first_bundled_edge_with_my_edge.h"
#include "get_bundled_edge_my_edge.h"
#include "set_bundled_edge_my_edge.h"

void set_bundled_edge_my_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_bundled_edges_and_vertices_graph
            ();
    const my_bundled_edge old_edge{"Dex"};
    add_bundled_edge(old_edge, g);
    const auto vd
        = find_first_bundled_edge_with_my_edge(old_edge, g);
    assert(get_bundled_edge_my_edge(vd, g)
        == old_edge
    );
    const my_bundled_edge new_edge{"Diggy"};
    set_bundled_edge_my_edge(new_edge, vd, g);
    assert(get_bundled_edge_my_edge(vd, g)
        == new_edge
    );
}
```

11.5 Storing a graph with bundled edges and vertices as a .dot

If you used the 'create_bundled_edges_and_vertices_k3_graph' function (algorithm 140) to produce a K_3 graph with edges and vertices associated with `my_bundled_edge` and `my_bundled_vertex` objects, you can store these `my_bundled_edges` and `my_bundled_vertex`-es additionally with algorithm 151:

Algorithm 151 Storing a graph with bundled edges and vertices as a .dot file

```
#include <fstream>
#include <string>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>
#include "get_bundled_edge_my_edge.h"
#include "get_bundled_vertex_my_vertexes.h"

template <typename graph>
void save_bundled_edges_and_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
)
{
    using my_vertex_descriptor = typename graph::
        vertex_descriptor;
    using my_edge_descriptor = typename graph::
        edge_descriptor;
    std::ofstream f(filename);
    boost::write_graphviz(
        f,
        g,
        [g](
            std::ostream& out,
            const my_vertex_descriptor& v
        ) {
            const my_bundled_vertex m{g[v]};
            out << "[label=\"
                << m.m_name
                << "\",\"
                << m.m_description
                << "\",\"
                << m.m_x
                << "\",\"
                << m.m_y
                << "\\\""]\"
            ;
        },
        [g](std::ostream& out,
            const my_edge_descriptor& e
        ) {
            const my_bundled_edge m{get_bundled_edge_my_edge(e,
                g)};
            out << "[label=\"
                << m.m_name
                << "\",\"
                << m.m_description
                << "\",\"
                << m.m_width
                << "\",\"
                << m.m_height
                << "\\\""]\"
            ;
        }
    );
};
```


11.6 Load a directed graph with bundled edges and vertices from a .dot file

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with bundled edges and vertices is loaded, as shown in algorithm 152:

Algorithm 152 Loading a directed graph with bundled edges and vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_directed_bundled_edges_and_vertices_graph
    .h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    my_bundled_vertex,
    my_bundled_edge
>
load_directed_bundled_edges_and_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_directed_bundled_edges_and_vertices_graph
        ();

    //Something like this...
    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id",get(&my_bundled_vertex::m_name, g)
    );
    p.property("label",get(&my_bundled_vertex::m_name, g));
    p.property("edge_id",get(&my_bundled_edge::m_name, g));
    p.property("label",get(&my_bundled_edge::m_name, g));

    boost::read_graphviz(f,g,p);
    return g;
}
```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created. Next to this, a `boost::dynamic_properties` is created with its default constructor, after which we direct the `boost::dynamic_properties` to find a `'node_id'` and `'label'` in the vertex name map, `'edge_id'` and `'label'` to the edge name map. From this and the empty graph, `'boost::read_graphviz'` is called to build up the graph.

Algorithm 153 shows how to use the `'load_directed_bundled_edges_and_vertices_graph_from_dot'` function:

Algorithm 153 Demonstration of the 'load_directed_bundled_edges_and_vertices_graph_from_dot' function

```

#include "create_bundled_edges_and_vertices_markov_chain.h"
#include "get_sorted_bundled_vertex_my_vertexes.h"
#include "load_directed_bundled_edges_and_vertices_graph_from_dot.h"
#include "save_bundled_edges_and_vertices_graph_to_dot.h"

void
load_directed_bundled_edges_and_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_bundled_edges_and_vertices_markov_chain();
    const std::string filename{
        "create_bundled_edges_and_vertices_markov_chain.dot"
    };
    save_bundled_edges_and_vertices_graph_to_dot(g,
        filename);
    const auto h
        =
            load_directed_bundled_edges_and_vertices_graph_from_dot
            (
                filename
            );
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    if (get_sorted_bundled_vertex_my_vertexes(g)
        == get_sorted_bundled_vertex_my_vertexes(h))
    {
        std::cout << __func__ << ":_fixed_#16" << std::endl;
        assert(!_fixed_#16);
    }
    else
    {
        std::cout << __func__ << ":_TODO" << std::endl;
    }
}

```

This demonstration shows how the Markov chain is created using the 'create_bundled_edges_and_vertices_markov_chain' function (algorithm 137), saved and then loaded.

11.7 Load an undirected graph with bundled edges and vertices from a .dot file

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with bundled edges and vertices is loaded, as shown in algorithm 154:

Algorithm 154 Loading an undirected graph with bundled edges and vertices from a .dot file

```

#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_undirected_bundled_edges_and_vertices_graph
    .h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    my_bundled_vertex,
    my_bundled_edge
>
load_undirected_bundled_edges_and_vertices_graph_from_dot
(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_undirected_bundled_edges_and_vertices_graph
        ();

    //Something like this...
    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id",get(&my_bundled_vertex::m_name, g)
    );
    p.property("label",get(&my_bundled_vertex::m_name, g));
    p.property("edge_id",get(&my_bundled_edge::m_name, g));
    p.property("label",get(&my_bundled_edge::m_name, g));

    boost::read_graphviz(f,g,p);
    return g;
}

```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 11.6 describes the rationale of this function.

Algorithm 155 shows how to use the 'load_undirected_bundled_vertices_graph_from_dot' function:

Algorithm 155 Demonstration of the 'load_undirected_bundled_edges_and_vertices_graph_from_dot' function

```
#include "create_bundled_edges_and_vertices_markov_chain.h"
#include "get_sorted_bundled_vertex_my_vertexes.h"
#include "load_undirected_bundled_edges_and_vertices_graph_from_dot.h"
#include "save_bundled_edges_and_vertices_graph_to_dot.h"

void
load_undirected_bundled_edges_and_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_bundled_edges_and_vertices_markov_chain();
    const std::string filename{
        "create_bundled_edges_and_vertices_markov_chain.dot"
    };
    save_bundled_edges_and_vertices_graph_to_dot(g,
        filename);
    try
    {
        const auto h
            =
                load_undirected_bundled_edges_and_vertices_graph_from_dot
                (
                    filename
                );
        assert(num_edges(g) == num_edges(h));
        assert(num_vertices(g) == num_vertices(h));
        assert(get_sorted_bundled_vertex_my_vertexes(g)
            == get_sorted_bundled_vertex_my_vertexes(h)
        );
        assert(!"Fixed_#16");
    }
    catch (std::exception&)
    {
        std::cout << __func__ << ":_TODO" << std::endl;
    }
}
```

This demonstration shows how K_2 with bundled vertices is created using the 'create_bundled_vertices_k2_graph' function (algorithm 169), saved and then loaded. The loaded graph is checked to be a graph similar to the original.

12 Building graphs with custom vertices

Instead of using bundled properties, you can also add a new custom property. The difference is that instead of having a class *as* a vertex, vertices have *an additional property* where the 'my_custom_vertex' is stored, next to properties like vertex name, edge delay (see chapter 25.1 for all properties). The following graphs will be created:

- An empty directed graph that allows for custom vertices: see chapter 158
- An empty undirected graph that allows for custom vertices: see chapter 12.3
- A two-state Markov chain with custom vertices: see chapter 12.7
- K_2 with custom vertices: see chapter 12.8

In the process, some basic (sometimes bordering trivial) functions are shown:

- Installing a new vertex property, called 'vertex_custom_type': chapter 12.2
- Adding a custom vertex: see chapter 12.5
- Getting the custom vertices my_vertex-es: see chapter 12.6

These functions are mostly there for completion and showing which data types are used.

12.1 Creating the vertex class

Before creating an empty graph with custom vertices, that custom vertex class must be created. In this tutorial, it is called 'my_custom_vertex'. 'my_custom_vertex' is a class that is nonsensical, but it can be replaced by any other class type.

Here I will show the header file of 'my_custom_vertex', as the implementation of it is not important:

Algorithm 156 Declaration of `my_custom_vertex`

```
#include <string>
#include <iosfwd>

class my_custom_vertex
{
public:
    explicit my_custom_vertex(
        const std::string& name = "",
        const std::string& description = "",
        const double x = 0.0,
        const double y = 0.0
    ) noexcept;
    const std::string& get_description() const noexcept;
    const std::string& get_name() const noexcept;
    double get_x() const noexcept;
    double get_y() const noexcept;
private:
    std::string m_name;
    std::string m_description;
    double m_x;
    double m_y;
};

bool operator==(const my_custom_vertex& lhs, const
    my_custom_vertex& rhs) noexcept;
bool operator!=(const my_custom_vertex& lhs, const
    my_custom_vertex& rhs) noexcept;
std::ostream& operator<<(std::ostream& os, const
    my_custom_vertex& v) noexcept;
std::istream& operator>>(std::istream& os,
    my_custom_vertex& v) noexcept;
```

'`my_custom_vertex`' is a class that has multiple properties:

- It has four private member variables: the double '`m_x`' ('`m_`' stands for member), the double '`m_y`', the `std::string m_name` and the `std::string m_description`. These variables are private, but there are getters supplied
- It has a default constructor
- It is copyable
- It is comparable for equality (it has `operator==`), which is needed for searching

- It can be streamed (it has both operator<< and operator>>), which is needed for file I/O.

Special characters like comma's, quotes and whitespace cannot be streamed without problems. The function 'graphviz_encode' (algorithm 251) can convert the elements to be streamed to a Graphviz-friendly version, which can be decoded by 'graphviz_decode' (algorithm 252).

12.2 Installing the new vertex property

Before creating an empty graph with custom vertices, this type must be installed as a vertex property. Installing a new property would have been easier, if 'more C++ compilers were standards conformant' ([8] chapter 3.6). Boost.Graph uses the BOOST_INSTALL_PROPERTY macro to allow using a custom property:

Algorithm 157 Installing the vertex_custom_type property

```
#include <boost/graph/properties.hpp>

namespace boost {
    enum vertex_custom_type_t { vertex_custom_type = 314 };
    BOOST_INSTALL_PROPERTY(vertex, custom_type);
}
```

The enum value 314 must be unique.

12.3 Create the empty directed graph with custom vertices

Algorithm 158 Creating an empty directed graph with custom vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >
>
>
create_empty_directed_custom_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        boost::property<
            boost::vertex_custom_type_t, my_custom_vertex
        >
    >();
}
```

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is directed (due to the `boost::directedS`)
- The vertices have one property: they have a custom type, that is of data type `my_vertex` (due to the `boost::property< boost::vertex_custom_type_t, my_vertex>`)
- The edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property< boost::vertex_custom_type_t, my_vertex>`'. This can be read as: "vertices

have the property 'boost::vertex_custom_type_t', which is of data type 'my_vertex'.
Or simply: "vertices have a custom type called my_vertex".

The demo:

Algorithm 159 Demo how to create an empty directed graph with custom vertices

```
#include "create_empty_directed_custom_vertices_graph.h"

void create_empty_directed_custom_vertices_graph_demo()
    noexcept
{
    const auto g
        = create_empty_directed_custom_vertices_graph();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

12.4 Create the empty undirected graph with custom vertices

Algorithm 160 Creating an empty undirected graph with custom vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >
>
>
create_empty_undirected_custom_vertices_graph() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_custom_type_t, my_custom_vertex
        >
    >();
}
```

This code is very similar to the code described in chapter 12.3, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`).

The demo:

Algorithm 161 Demo how to create an empty undirected graph with custom vertices

```
#include "create_empty_undirected_custom_vertices_graph.h"

void create_empty_undirected_custom_vertices_graph_demo()
    noexcept
{
    const auto g
        = create_empty_undirected_custom_vertices_graph();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

12.5 Add a custom vertex

Adding a custom vertex is very similar to adding a named vertex (chapter 4.3).

Algorithm 162 Add a custom vertex

```
#include <type_traits>
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
void add_custom_vertex(
    const my_custom_vertex& v,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");

    const auto vd_a = boost::add_vertex(g);
    const auto my_custom_vertex_map
        = get( //not boost::get
            boost::vertex_custom_type,
            g
        );
    my_custom_vertex_map[vd_a] = v;
}
```

When having added a new (abstract) vertex to the graph, the vertex descriptor is used to set the `my_vertex` in the graph its `my_vertex` map (using `'get(boost::vertex_custom_type,g)'`).

Here is the demo:

Algorithm 163 Demo of 'add_custom_vertex'

```
#include <cassert>
#include "add_custom_vertex.h"
#include "create_empty_directed_custom_vertices_graph.h"
#include "create_empty_undirected_custom_vertices_graph.h"
"

void add_custom_vertex_demo() noexcept
{
    auto g
        = create_empty_directed_custom_vertices_graph();
    assert(boost::num_vertices(g) == 0);
    assert(boost::num_edges(g) == 0);
    add_custom_vertex(my_custom_vertex("X"), g);
    assert(boost::num_vertices(g) == 1);
    assert(boost::num_edges(g) == 0);

    auto h
        = create_empty_undirected_custom_vertices_graph();
    assert(boost::num_vertices(h) == 0);
    assert(boost::num_edges(h) == 0);
    add_custom_vertex(my_custom_vertex("X"), h);
    assert(boost::num_vertices(h) == 1);
    assert(boost::num_edges(h) == 0);
}
```

12.6 Getting the vertices' `my_vertexes`¹¹

When the vertices of a graph have any associated `my_vertex`, one can extract these as such:

¹¹the name 'my_vertexes' is chosen to indicate this function returns a container of `my_vertex`

Algorithm 164 Get the vertices' my_vertexes

```
#include <vector>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
std::vector<my_custom_vertex>
    get_custom_vertex_my_vertexes(
        const graph& g
    ) noexcept
{
    std::vector<my_custom_vertex> v;

    const auto my_custom_vertexes_map
        = get( //not boost::get
              boost::vertex_custom_type, g
            );
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        v.emplace_back(
            get( //not boost::get
                my_custom_vertexes_map, *i
            )
        );
    }
    return v;
}
```

The my_vertex object associated with the vertices are obtained from a boost::property_map and then put into a std::vector.

The order of the 'my_custom_vertex' objects may be different after saving and loading.

When trying to get the vertices' my_vertex from a graph without my_vertex objects associated, you will get the error 'formed reference to void' (see chapter 24.1).

Demo:

Algorithm 165 Demo how to the vertices' my_custom_vertex objects

```
#include <cassert>
#include "create_custom_vertices_k2_graph.h"
#include "get_custom_vertex_my_vertexes.h"

void get_custom_vertex_my_vertexes_demo() noexcept
{
    const auto g = create_custom_vertices_k2_graph();
    const std::vector<my_custom_vertex>
        expected_my_custom_vertexes{
            my_custom_vertex("A","source",0.0,0.0),
            my_custom_vertex("B","target",3.14,3.14)
        };
    const std::vector<my_custom_vertex> vertexes{
        get_custom_vertex_my_vertexes(g)
    };
    assert(expected_my_custom_vertexes == vertexes);
}
```

12.7 Creating a two-state Markov chain with custom vertices

12.7.1 Graph

Figure 24 shows the graph that will be reproduced:




Figure 24: A two-state Markov chain where the vertices have custom properties and the edges have no properties. The vertices' properties are nonsensical

12.7.2 Function to create such a graph

Here is the code creating a two-state Markov chain with custom vertices:

Algorithm 166 Creating the two-state Markov chain as depicted in figure 24

```
#include <cassert>
#include "create_empty_directed_custom_vertices_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >
>
>
create_custom_vertices_markov_chain() noexcept
{
    auto g
        = create_empty_directed_custom_vertices_graph();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    auto my_custom_vertex_map = get( //not boost::get
        boost::vertex_custom_type, g
    );
    my_custom_vertex_map[vd_a] = my_custom_vertex("Sunny",
        "Yellow_thing", 1.0, 2.0
    );
    my_custom_vertex_map[vd_b] = my_custom_vertex("Rainy",
        "Grey_things", 3.0, 4.0
    );

    return g;
}
```

12.7.3 Creating such a graph

Here is the demo:

Algorithm 167 Demo of the 'create_custom_vertices_markov_chain' function (algorithm 166)

```
#include <cassert>
#include "create_custom_vertices_markov_chain.h"
#include "get_custom_vertex_my_vertexes.h"

void create_custom_vertices_markov_chain_demo() noexcept
{
    const auto g
        = create_custom_vertices_markov_chain();
    const std::vector<my_custom_vertex>
        expected_my_custom_vertexes{
            my_custom_vertex("Sunny", "Yellow_thing", 1.0, 2.0),
            my_custom_vertex("Rainy", "Grey_things", 3.0, 4.0)
        };
    const std::vector<my_custom_vertex>
        vertex_my_custom_vertexes{
            get_custom_vertex_my_vertexes(g)
        };
    assert(expected_my_custom_vertexes
        == vertex_my_custom_vertexes
    );
}
```

12.7.4 The .dot file produced

Algorithm 168 .dot file created from the 'create_custom_vertices_markov_chain' function (algorithm 166), converted from graph to .dot file using algorithm 181

```
digraph G {
0[label="Sunny, Yellow[[:SPACE:]]thing,1,1"];
1[label="Rainy, Grey[[:SPACE:]]things,3,3"];
0->0 ;
0->1 ;
1->0 ;
1->1 ;
}
```

This .dot file may look unexpectedly different: instead of a space, there is this '[:SPACE:]' thing. This is because the function 'graphviz_encode' (algorithm 251) made this conversion. In this example, I could have simply surrounded the content by quotes, and this would have worked. I chose to use 'graphviz_encode'

because it works in all contexts.

12.7.5 The .svg file produced




Figure 25: .svg file created from the 'create_custom_vertices_markov_chain' function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

This .svg file may look unexpectedly different: instead of a space, there is this '[:SPACE:]' thing. This is because the function 'graphviz_encode' (algorithm 251) made this conversion.

12.8 Creating K_2 with custom vertices

12.8.1 Graph

We reproduce the K_2 with named vertices of chapter 4.6 , but with our custom vertices instead.

12.8.2 Function to create such a graph

Algorithm 169 Creating K_2 as depicted in figure 12

```
#include "create_empty_undirected_custom_vertices_graph.h"
"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >
>
create_custom_vertices_k2_graph() noexcept
{
    auto g = create_empty_undirected_custom_vertices_graph
        ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);

    auto my_custom_vertex_map = get( //not boost::get
        boost::vertex_custom_type, g
    );
    my_custom_vertex_map[vd_a]
        = my_custom_vertex("A", "source", 0.0, 0.0);
    my_custom_vertex_map[vd_b]
        = my_custom_vertex("B", "target", 3.14, 3.14);

    return g;
}
```

Most of the code is a slight modification of the 'create_named_vertices_k2_graph' function (algorithm 46). In the end, the my_vertices are obtained as a boost::property_map and set with two custom my_vertex objects.

12.8.3 Creating such a graph

Demo:

Algorithm 170 Demo of the 'create_custom_vertices_k2_graph' function (algorithm 169)

```
#include <cassert>
#include <iostream>
#include "create_custom_vertices_k2_graph.h"
#include "has_custom_vertex_with_my_vertex.h"

void create_custom_vertices_k2_graph_demo() noexcept
{
    const auto g = create_custom_vertices_k2_graph();
    assert(boost::num_edges(g) == 1);
    assert(boost::num_vertices(g) == 2);
    assert(has_custom_vertex_with_my_custom_vertex(
        my_custom_vertex("A", "source", 0.0, 0.0), g)
    );
    assert(has_custom_vertex_with_my_custom_vertex(
        my_custom_vertex("B", "target", 3.14, 3.14), g)
    );
}
```

12.8.4 The .dot file produced

Algorithm 171 .dot file created from the 'create_custom_vertices_k2_graph' function (algorithm 169), converted from graph to .dot file using algorithm 29

```
graph G {
0[label="A,source,0,0"];
1[label="B,target,3.14,3.14"];
0--1 ;
}
```

12.8.5 The .svg file produced




Figure 26: .svg file created from the 'create_custom_vertices_k2_graph' function (algorithm 169) its .dot file, converted from .dot file to .svg using algorithm 254

13 Working on graphs with custom vertices (as a custom property)

When using graphs with custom vertices, their state gives a way to find a vertex and working with it. This chapter shows some basic operations on graphs with custom vertices.

- Check if there exists a vertex with a certain 'my_vertex': chapter 13.1
- Find a vertex with a certain 'my_vertex': chapter 13.2
- Get a vertex its 'my_vertex' from its vertex descriptor: chapter 13.3
- Set a vertex its 'my_vertex' using its vertex descriptor: chapter 13.4
- Setting all vertices their 'my_vertex'es: chapter 13.5
- Storing an directed/undirected graph with custom vertices as a .dot file: chapter 13.6
- Loading a directed graph with custom vertices from a .dot file: chapter 13.7
- Loading an undirected directed graph with custom vertices from a .dot file: chapter 13.8

13.1 Has a custom vertex with a my_vertex

Before modifying our vertices, let's first determine if we can find a vertex by its custom type ('my_vertex') in a graph. After obtaining a my_vertex map, we

obtain the vertex iterators, dereference these to obtain the vertex descriptors and then compare each vertex its `my_vertex` with the one desired.

Algorithm 172 Find if there is vertex with a certain `my_vertex`

```
#include <string>
#include <boost/graph/properties.hpp>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
bool has_custom_vertex_with_my_custom_vertex(
    const my_custom_vertex& v,
    const graph& g
) noexcept
{
    const auto my_custom_vertexes_map
        = get(boost::vertex_custom_type, g);
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;
    for (auto i = vip.first; i!=j; ++i) {
        if (
            get( //not boost::get
                my_custom_vertexes_map,
                *i
            ) == v) {
            return true;
        }
    }
    return false;
}
```

This function can be demonstrated as in algorithm 173, where a certain `my_vertex` cannot be found in an empty graph. After adding the desired `my_vertex`, it is found.

Algorithm 173 Demonstration of the 'has_custom_vertex_with_my_vertex' function

```
#include <cassert>
#include <iostream>

#include "add_custom_vertex.h"
#include "create_empty_undirected_custom_vertices_graph.h"
#include "has_custom_vertex_with_my_vertex.h"
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

void has_custom_vertex_with_my_custom_vertex_demo()
    noexcept
{
    auto g = create_empty_undirected_custom_vertices_graph
        ();
    assert(!has_custom_vertex_with_my_custom_vertex(
        my_custom_vertex("Felix"), g));
    add_custom_vertex(my_custom_vertex("Felix"), g);
    assert(has_custom_vertex_with_my_custom_vertex(
        my_custom_vertex("Felix"), g));
}
```

Note that this function only finds if there is at least one custom vertex with that my_vertex: it does not tell how many custom vertices with that my_vertex exist in the graph.

13.2 Find a custom vertex with a certain my_vertex

Where STL functions work with iterators, here we obtain a vertex descriptor (see chapter 2.6) to obtain a handle to the desired vertex. Algorithm 174 shows how to obtain a vertex descriptor to the first vertex found with a specific my_vertex value.

Algorithm 174 Find the first vertex with a certain `my_vertex`

```
#include <cassert>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "has_custom_vertex_with_my_vertex.h"
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
typename boost::graph_traits<graph>::vertex_descriptor
find_first_custom_vertex_with_my_vertex(
    const my_custom_vertex& v,
    const graph& g
) noexcept
{
    assert(has_custom_vertex_with_my_custom_vertex(v, g));
    const auto my_custom_vertexes_map = get(boost::
        vertex_custom_type, g);
    const auto vip
        = vertices(g); //not boost::vertices
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        const auto w
            = get( //not boost::get
                my_custom_vertexes_map,
                *i
            );
        if (w == v) { return *i; }
    }
    assert(!"Should_not_get_here");
    throw; //Will crash the program
}
```

With the vertex descriptor obtained, one can read and modify the vertex and the edges surrounding it. Algorithm 175 shows some examples of how to do so.

Algorithm 175 Demonstration of the 'find_first_custom_vertex_with_my_vertex' function

```
#include <cassert>

#include "create_custom_vertices_k2_graph.h"
#include "find_first_custom_vertex_with_my_vertex.h"

void find_first_custom_vertex_with_my_vertex_demo()
    noexcept
{
    const auto g = create_custom_vertices_k2_graph();
    const auto vd = find_first_custom_vertex_with_my_vertex
        (
            my_custom_vertex("A", "source", 0.0, 0.0),
            g
        );
    assert(out_degree(vd, g) == 1); //not boost::out_degree
    assert(in_degree(vd, g) == 1); //not boost::in_degree
}
```

13.3 Get a custom vertex its my_vertex

To obtain the name from a vertex descriptor, one needs to pull out the my_vertexes¹² map and then look up the vertex of interest.

¹²Bad English intended: my_vertexes = multiple my_vertex objects, vertices = multiple graph nodes

Algorithm 176 Get a custom vertex its my_vertex from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
my_custom_vertex get_custom_vertex_my_custom_vertex(
    const typename boost::graph_traits<graph>::
        vertex_descriptor& vd,
    const graph& g
) noexcept
{
    const auto my_custom_vertexes_map
        = get( //not boost::get
            boost::vertex_custom_type,
            g
        );
    return my_custom_vertexes_map[vd];
}
```

To use 'get_custom_vertex_my_vertex', one first needs to obtain a vertex descriptor. Algorithm 177 shows a simple example.

Algorithm 177 Demonstration if the 'get_custom_vertex_my_vertex' function

```
#include <cassert>
#include "add_custom_vertex.h"
#include "create_empty_undirected_custom_vertices_graph.h"
"

#include "find_first_custom_vertex_with_my_vertex.h"
#include "get_custom_vertex_my_vertex.h"

void get_custom_vertex_my_custom_vertex_demo() noexcept
{
    auto g = create_empty_undirected_custom_vertices_graph
        ();
    const my_custom_vertex name{"Dex"};
    add_custom_vertex(name, g);
    const auto vd
        = find_first_custom_vertex_with_my_vertex(name, g);
    assert(get_custom_vertex_my_custom_vertex(vd, g) == name
        );
}
```

13.4 Set a custom vertex its my_vertex

If you know how to get the my_vertex from a vertex descriptor, setting it is just as easy, as shown in algorithm 178.

Algorithm 178 Set a custom vertex its `my_vertex` from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
void set_custom_vertex_my_custom_vertex(
    const my_custom_vertex& v,
    const typename boost::graph_traits<graph>::
        vertex_descriptor& vd,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
};

const auto my_custom_vertexes_map
    = get( //not boost::get
        boost::vertex_custom_type, g
    );
my_custom_vertexes_map[vd] = v;
}
```

To use 'set_vertex_my_vertex', one first needs to obtain a vertex descriptor. Algorithm 179 shows a simple example.

Algorithm 179 Demonstration if the 'set_custom_vertex_my_vertex' function

```
#include <cassert>

#include "add_custom_vertex.h"
#include "create_empty_undirected_custom_vertices_graph.h"
#include "find_first_custom_vertex_with_my_vertex.h"
#include "get_custom_vertex_my_vertex.h"
#include "set_custom_vertex_my_vertex.h"

void set_custom_vertex_my_custom_vertex_demo() noexcept
{
    auto g
        = create_empty_undirected_custom_vertices_graph();
    const my_custom_vertex old_vertex{"Dex"};
    add_custom_vertex(old_vertex, g);
    const auto vd
        = find_first_custom_vertex_with_my_vertex(old_vertex,
            g);
    assert(get_custom_vertex_my_custom_vertex(vd, g)
        == old_vertex
    );
    const my_custom_vertex new_vertex{"Diggy"};
    set_custom_vertex_my_custom_vertex(
        new_vertex, vd, g
    );
    assert(get_custom_vertex_my_custom_vertex(vd, g)
        == new_vertex
    );
}
```

13.5 Setting all custom vertices' my_vertex objects

When the vertices of a graph are associated with my_vertex objects, one can set these my_vertexes as such:

Algorithm 180 Setting the custom vertices' my_vertexes

```
#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

template <typename graph>
void set_custom_vertex_my_custom_vertexes(
    graph& g,
    const std::vector<my_custom_vertex>& my_custom_vertexes
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    const auto my_custom_vertex_map
        = get( //not boost::get
            boost::vertex_custom_type, g
        );

    auto my_custom_vertexes_begin = std::begin(
        my_custom_vertexes);
    const auto my_custom_vertexes_end = std::end(
        my_custom_vertexes);
    const auto vip = vertices(g); //not boost::vertices
    const auto j = vip.second;
    for (
        auto i = vip.first;
        i!=j; ++i,
        ++my_custom_vertexes_begin
    ) {
        assert(my_custom_vertexes_begin !=
            my_custom_vertexes_end);
        put(my_custom_vertex_map, *i, *
            my_custom_vertexes_begin);
    }
}
```

An impressive feature is that getting the property map holding the graph its names is not a copy, but a reference. Otherwise, modifying 'my_vertexes_map'

(obtained by non-reference) would only modify a copy.

13.6 Storing a graph with custom vertices as a .dot

If you used the `create_custom_vertices_k2_graph` function (algorithm 169) to produce a K_2 graph with vertices associated with `my_vertex` objects, you can store these `my_vertexes` additionally with algorithm 181:

Algorithm 181 Storing a graph with custom vertices as a .dot file

```
#include <fstream>
#include <string>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>
#include "get_custom_vertex_my_vertexes.h"

template <typename graph>
void save_custom_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
)
{
    using my_custom_vertex_descriptor
        = typename graph::vertex_descriptor;
    std::ofstream f(filename);

    const auto my_custom_vertexes_map
        = get( //not boost::get
              boost::vertex_custom_type, g
            );
    boost::write_graphviz(
        f,
        g,
        [my_custom_vertexes_map](
            std::ostream& out,
            const my_custom_vertex_descriptor& v
        ) {
            const my_custom_vertex m{my_custom_vertexes_map[v]};
            out << "[label=\"\" << m << "\"\"";
        }
    );
}
```

13.7 Loading a directed graph with custom vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with custom vertices is loaded, as shown in algorithm 182:

Algorithm 182 Loading a directed graph with custom vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_directed_custom_vertices_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >
>
>
load_directed_custom_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_directed_custom_vertices_graph();
    boost::dynamic_properties p; //_do_default_construct
    p.property("node_id", get(boost::vertex_custom_type, g));
    p.property("label", get(boost::vertex_custom_type, g));
    boost::read_graphviz(f, g, p);
    return g;
}
```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created. Next to this, a `boost::dynamic_properties` is created with its default constructor, after which we direct the `boost::dynamic_properties` to find a 'node_id' and 'label' in the vertex name map, 'edge_id' and 'label' to the edge name map. From this and the empty graph, 'boost::read_graphviz' is called to build up the graph.

Algorithm 183 shows how to use the 'load_directed_custom_vertices_graph_from_dot' function:

Algorithm 183 Demonstration of the 'load_directed_custom_vertices_graph_from_dot' function

```
#include "create_custom_vertices_markov_chain.h"
#include "load_directed_custom_vertices_graph_from_dot.h"
#include "save_custom_vertices_graph_to_dot.h"
#include "get_custom_vertex_my_vertexes.h"

void load_directed_custom_vertices_graph_from_dot_demo()
    noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_custom_vertices_markov_chain();
    const std::string filename{
        "create_custom_vertices_markov_chain.dot"
    };
    save_custom_vertices_graph_to_dot(g, filename);
    const auto h
        = load_directed_custom_vertices_graph_from_dot(
            filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_custom_vertex_my_vertexes(g)
        == get_custom_vertex_my_vertexes(h)
    );
}
```

This demonstration shows how the Markov chain is created using the 'create_custom_vertices_markov_chain' function (algorithm 166), saved and then loaded. The loaded graph is then checked to be identical to the original.

13.8 Loading an undirected graph with custom vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with custom vertices is loaded, as shown in algorithm 184:

Algorithm 184 Loading an undirected graph with custom vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>

#include "create_empty_undirected_custom_vertices_graph.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >
>
>
load_undirected_custom_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_undirected_custom_vertices_graph
        ();
    boost::dynamic_properties p; //_do_default_construct
    p.property("node_id", get(boost::vertex_custom_type, g)
    );
    p.property("label", get(boost::vertex_custom_type, g));
    boost::read_graphviz(f, g, p);
    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 13.7 describes the rationale of this function.

Algorithm 185 shows how to use the 'load_undirected_custom_vertices_graph_from_dot' function:

Algorithm 185 Demonstration of the 'load_undirected_custom_vertices_graph_from_dot' function

```
#include <cassert>
#include "create_custom_vertices_k2_graph.h"
#include "load_undirected_custom_vertices_graph_from_dot.h"
#include "save_custom_vertices_graph_to_dot.h"
#include "get_custom_vertex_my_vertexes.h"

void load_undirected_custom_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_custom_vertices_k2_graph();
    const std::string filename{
        "create_custom_vertices_k2_graph.dot"
    };
    save_custom_vertices_graph_to_dot(g, filename);
    const auto h
        = load_undirected_custom_vertices_graph_from_dot(
            filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_custom_vertex_my_vertexes(g) ==
        get_custom_vertex_my_vertexes(h));
}
```

This demonstration shows how K_2 with custom vertices is created using the 'create_custom_vertices_k2_graph' function (algorithm 169), saved and then loaded. The loaded graph is then checked to be identical to the original.

14 Building graphs with custom and selectable vertices

We have added one custom vertex property, here we add a second: if the vertex is selected.

- An empty directed graph that allows for custom and selectable vertices: see chapter 14.2
- An empty undirected graph that allows for custom and selectable vertices:

see chapter 14.3

- A two-state Markov chain with custom and selectable vertices: see chapter 14.5
- K_3 with custom and selectable vertices: see chapter 14.6

In the process, some basic (sometimes bordering trivial) functions are shown:

- Installing the new edge property: see chapter 14.1
- Adding a custom and selectable vertex: see chapter 14.4

These functions are mostly there for completion and showing which data types are used.

14.1 Installing the new `is_selected` property

Installing a new property would have been easier, if 'more C++ compilers were standards conformant' ([8], chapter 3.6, footnote at page 52). Boost.Graph uses the `BOOST_INSTALL_PROPERTY` macro to allow using a custom property:

Algorithm 186 Installing the `vertex_is_selected` property

```
#include <boost/graph/properties.hpp>

namespace boost {
    enum vertex_is_selected_t { vertex_is_selected = 31415 };
    BOOST_INSTALL_PROPERTY(vertex, is_selected);
}
```

The enum value 31415 must be unique.

14.2 Create an empty directed graph with custom and selectable vertices

Algorithm 187 Creating an empty directed graph with custom and selectable vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "install_vertex_is_selected.h"
#include "my_custom_vertex.h"

boost::adjacency_list<
    boost::vecS ,
    boost::vecS ,
    boost::directedS ,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex ,
        boost::property<
            boost::vertex_is_selected_t , bool
        >
    >
>
>
>
create_empty_directed_custom_and_selectable_vertices_graph(
    () noexcept
{
    return boost::adjacency_list<
        boost::vecS ,
        boost::vecS ,
        boost::directedS ,
        boost::property<
            boost::vertex_custom_type_t, my_custom_vertex ,
            boost::property<
                boost::vertex_is_selected_t , bool
            >
        >
    >() ;
}
```

This code is very similar to the code described in chapter 12.3, except that there is a new, fourth template argument:

```
boost::property<boost::vertex_custom_type_t, my_custom_vertex,
    boost::property<boost::vertex_is_selected_t, bool,
>
```

This can be read as: “vertices have two properties: an associated custom type (of type `my_custom_vertex`) and an associated `is_selected` property (of type `bool`)”.

Demo:

Algorithm 188 Demonstration of the ‘create_empty_directed_custom_and_selectable_vertices_graph’ function

```
#include "
    create_empty_directed_custom_and_selectable_vertices_graph
    .h"

void
    create_empty_directed_custom_and_selectable_vertices_graph_demo
    () noexcept
{
    const auto g
        =
            create_empty_directed_custom_and_selectable_vertices_graph
            ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

14.3 Create an empty undirected graph with custom and selectable vertices

Algorithm 189 Creating an empty undirected graph with custom and selectable vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "install_vertex_is_selected.h"
#include "my_custom_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex,
        boost::property<
            boost::vertex_is_selected_t, bool
        >
    >
>
>
>
create_empty_undirected_custom_and_selectable_vertices_graph
    () noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_custom_type_t, my_custom_vertex,
            boost::property<
                boost::vertex_is_selected_t, bool
            >
        >
    >
    >();
}
```

This code is very similar to the code described in chapter 14.2, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`).

Demo:

Algorithm 190 Demonstration of the 'create_empty_undirected_custom_and_selectable_vertices_graph' function

```
#include "
    create_empty_undirected_custom_and_selectable_vertices_graph
    .h"

void
    create_empty_undirected_custom_and_selectable_vertices_graph_demo
    () noexcept
{
    const auto g
        =
            create_empty_undirected_custom_and_selectable_vertices_graph
            ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

14.4 Add a custom and selectable vertex

Adding a custom and selectable vertex is very similar to adding a custom vertex (chapter 12.5).

Algorithm 191 Add a custom and selectable vertex

```
#include <type_traits>
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "install_vertex_is_selected.h"
#include "my_custom_vertex.h"

template <typename graph>
void add_custom_and_selectable_vertex(
    const my_custom_vertex& v,
    const bool is_selected,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value,
        "graph_cannot_be_const");
};

const auto vd_a = boost::add_vertex(g);

const auto my_custom_vertex_map
    = get( //not boost::get
        boost::vertex_custom_type,
        g
    );
my_custom_vertex_map[vd_a] = v;

const auto is_selected_map
    = get( //not boost::get
        boost::vertex_is_selected,
        g
    );
is_selected_map[vd_a] = is_selected;
}
```

When having added a new (abstract) vertex to the graph, the vertex descriptor is used to set the `my_custom_vertex` and the selectedness in the graph its `my_custom_vertex` and `is_selected` map .

Here is the demo:

Algorithm 192 Demo of 'add_custom_and_selectable_vertex'

```
#include <cassert>
#include "add_custom_and_selectable_vertex.h"
#include "
    create_empty_directed_custom_and_selectable_vertices_graph
    .h"
#include "
    create_empty_undirected_custom_and_selectable_vertices_graph
    .h"

void add_custom_and_selectable_vertex_demo() noexcept
{
    auto g
        =
            create_empty_directed_custom_and_selectable_vertices_graph
            ();
    assert(boost::num_vertices(g) == 0);
    assert(boost::num_edges(g) == 0);
    add_custom_and_selectable_vertex(
        my_custom_vertex("X"),
        true,
        g
    );
    assert(boost::num_vertices(g) == 1);
    assert(boost::num_edges(g) == 0);

    auto h
        =
            create_empty_undirected_custom_and_selectable_vertices_graph
            ();
    assert(boost::num_vertices(h) == 0);
    assert(boost::num_edges(h) == 0);
    add_custom_and_selectable_vertex(
        my_custom_vertex("X"),
        false,
        h
    );
    assert(boost::num_vertices(h) == 1);
    assert(boost::num_edges(h) == 0);
}
```

14.5 Creating a Markov-chain with custom and selectable vertices

14.5.1 Graph

Figure 27 shows the graph that will be reproduced:




Figure 27: A two-state Markov chain where the edges and vertices have custom properties. The edges' and vertices' properties are nonsensical

14.5.2 Function to create such a graph

Here is the code creating a two-state Markov chain with custom edges and vertices:

Algorithm 193 Creating the two-state Markov chain as depicted in figure 27

```
#include <cassert>
#include "
    create_empty_directed_custom_and_selectable_vertices_graph
    .h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex,
        boost::property<
            boost::vertex_is_selected_t, bool
        >
    >
>
>
create_custom_and_selectable_vertices_markov_chain()
    noexcept
{
    auto g
        =
            create_empty_directed_custom_and_selectable_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    auto my_custom_vertex_map
        = get( //not boost::get
            boost::vertex_custom_type, g
        );
    my_custom_vertex_map[vd_a] = my_custom_vertex("Sunny",
        "Yellow_thing", 1.0, 2.0
    );
    my_custom_vertex_map[vd_b] = my_custom_vertex("Rainy",
        "Grey_things", 3.0, 4.0
    );

    auto is_selected_map
        = get( //not boost::get 205
            boost::vertex_is_selected, g
        );
    is_selected_map[vd_a] = true;
    is_selected_map[vd_b] = false;

    return g;
}
```

14.5.3 Creating such a graph

Here is the demo:

Algorithm 194 Demo of the 'create_custom_and_selectable_vertices_markov_chain' function (algorithm 193)

```
#include <cassert>
#include "
    create_custom_and_selectable_vertices_markov_chain.h"
#include "get_vertex_selectednesses.h"

void
    create_custom_and_selectable_vertices_markov_chain_demo
    () noexcept
{
    const auto g
        = create_custom_and_selectable_vertices_markov_chain
        ();
    const std::vector<bool>
        expected_selectednesses{
            true, false
        };
    const std::vector<bool>
        vertex_selectednesses{
            get_vertex_selectednesses(g)
        };
    assert(expected_selectednesses
        == vertex_selectednesses
    );
}
```

14.5.4 The .dot file produced

Algorithm 195 .dot file created from the 'create_custom_and_selectable_vertices_markov_chain' function (algorithm 193), converted from graph to .dot file using algorithm 29

```
digraph G {
0[label="Sunny,Yellow[:SPACE:]thing,1,1", regular="1"];
1[label="Rainy,Grey[:SPACE:]things,3,3", regular="0"];
0->0 ;
0->1 ;
1->0 ;
1->1 ;
}
```

14.5.5 The .svg file produced




Figure 28: .svg file created from the 'create_custom_and_selectable_vertices_markov_chain' function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

Note how the .svg changed its appearance due to the Graphviz 'regular' property (see chapter 25.2): the vertex labeled 'Sunny' is drawn according to the Graphviz 'regular' attribute, which makes it a circle. The other vertex, labeled 'Rainy' is not drawn as such and retained its ellipsoid appearance.

14.6 Creating K_2 with custom and selectable vertices

14.6.1 Graph

We reproduce the K_2 with custom vertices of chapter 12.8 , but now are vertices can be selected as well:

[graph here]

14.6.2 Function to create such a graph

Algorithm 196 Creating K_3 as depicted in figure 16

```
#include "
    create_empty_undirected_custom_and_selectable_vertices_graph
    .h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex,
        boost::property<
            boost::vertex_is_selected_t, bool
        >
    >
>
>
>
create_custom_and_selectable_vertices_k2_graph() noexcept
{
    auto g
        =
            create_empty_undirected_custom_and_selectable_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);

    auto my_custom_vertexes_map
        = get( //not boost::get
            boost::vertex_custom_type,
            g
        );
    my_custom_vertexes_map[vd_a]
        = my_custom_vertex("A", "source", 0.0, 0.0);
    my_custom_vertexes_map[vd_b]
        = my_custom_vertex("B", "target", 3.14, 3.14);

    auto is_selected_map
        = get( //not boost::get
            boost::vertex_is_selected,
            g
        );
    is_selected_map[vd_a] = true;
    is_selected_map[vd_b] = false;

    return g;
}
210
```

Most of the code is a slight modification of algorithm 169. In the end, the associated `my_custom_vertex` and `is_selected` properties are obtained as `boost::property_maps` and set with the desired `my_custom_vertex` objects and `selectednesses`.

14.6.3 Creating such a graph

Here is the demo:

Algorithm 197 Demo of the 'create_custom_and_selectable_vertices_k2_graph' function (algorithm 196)

```
#include <cassert>
#include "create_custom_and_selectable_vertices_k2_graph.h"
#include "has_custom_vertex_with_my_vertex.h"

void create_custom_and_selectable_vertices_k2_graph_demo
() noexcept
{
    const auto g =
        create_custom_and_selectable_vertices_k2_graph();
    assert(boost::num_edges(g) == 1);
    assert(boost::num_vertices(g) == 2);
    assert(has_custom_vertex_with_my_custom_vertex(
        my_custom_vertex("A", "source", 0.0, 0.0), g)
    );
    assert(has_custom_vertex_with_my_custom_vertex(
        my_custom_vertex("B", "target", 3.14, 3.14), g)
    );
}
```

14.6.4 The .dot file produced

Algorithm 198 .dot file created from the 'create_custom_and_selectable_vertices_k2_graph' function (algorithm 196), converted from graph to .dot file using algorithm 29

```
graph G {
0[label="A,source,0,0", regular="1"];
1[label="B,target,3.14,3.14", regular="0"];
0--1 ;
}
```

14.6.5 The .svg file produced




Figure 29: .svg file created from the 'create_custom_and_selectable_vertices_k2_graph' function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

Note how the .svg changed its appearance due to the Graphviz 'regular' property (see chapter 25.2): the vertex labeled 'A' is drawn according to the Graphviz 'regular' attribute, which makes it a circle. The other vertex, labeled 'B' is not drawn as such and retained its ellipsoid appearance.

15 Working on graphs with custom and selectable vertices

This chapter shows some basic operations to do on graphs with custom and selectable vertices.

- Storing an directed/undirected graph with custom and selectable vertices as a .dot file: chapter 15.1
- Loading a directed graph with custom and selectable vertices from a .dot file: chapter 15.2
- Loading an undirected directed graph with custom and selectable vertices from a .dot file: chapter 15.3

15.1 Storing a graph with custom and selectable vertices as a .dot

If you used the 'create_custom_and_selectable_vertices_k2_graph' function (algorithm 196) to produce a K_2 graph with vertices associated with (1) my_custom_vertex objects, and (2) a boolean indicating its selectedness, you can store such graphs with algorithm 199:

Algorithm 199 Storing a graph with custom and selectable vertices as a .dot file

```
#include <fstream>
#include <string>
#include <boost/graph/graphviz.hpp>
#include "install_vertex_custom_type.h"
#include "install_vertex_is_selected.h"
#include "make_custom_and_selectable_vertices_writer.h"
#include "my_custom_vertex.h"

template <typename graph>
void save_custom_and_selectable_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
)
{
    std::ofstream f(filename);

    write_graphviz(f, g,
        make_custom_and_selectable_vertices_writer(
            get(boost::vertex_custom_type, g),
            get(boost::vertex_is_selected, g)
        )
    );
}
```

This code looks small, because we call the 'make_custom_and_selectable_vertices_writer' function, which is shown in algorithm 200:

Algorithm 200 The 'make_custom_and_selectable_vertices_writer' function

```
template <
    typename my_custom_vertex_map,
    typename is_selected_map
>
inline custom_and_selectable_vertices_writer<
    my_custom_vertex_map,
    is_selected_map
>
make_custom_and_selectable_vertices_writer(
    const my_custom_vertex_map& any_my_custom_vertex_map,
    const is_selected_map& any_is_selected_map
)
{
    return custom_and_selectable_vertices_writer<
        my_custom_vertex_map,
        is_selected_map
    >(
        any_my_custom_vertex_map,
        any_is_selected_map
    );
}
```

Also this function is forwarding the real work to the 'custom_and_selectable_vertices_writer', shown in algorithm 201:

Algorithm 201 The 'custom_and_selectable_vertices_writer' function

```
#include <ostream>

template <
    typename my_custom_vertex_map,
    typename is_selected_map
>
class custom_and_selectable_vertices_writer {
public:
    custom_and_selectable_vertices_writer(
        my_custom_vertex_map any_my_custom_vertex_map,
        is_selected_map any_is_selected_map
    ) : m_my_custom_vertex_map{any_my_custom_vertex_map},
        m_is_selected_map{any_is_selected_map}
    {
    }

    template <class vertex_descriptor>
    void operator()(
        std::ostream& out,
        const vertex_descriptor& vd
    ) const noexcept {
        out << "[label=\"" << m_my_custom_vertex_map[vd]
            << "\",regular=\"" << m_is_selected_map[vd]
            << "\"]"
        ;
    }
private:
    my_custom_vertex_map m_my_custom_vertex_map;
    is_selected_map m_is_selected_map;
};
```

Here, some interesting things are happening: the writer needs both property maps to work with (that is, the 'my_custom_vertex' and is_selected maps). The 'my_custom_vertex' are written to the Graphviz 'label' attribute, and the is_selected is written to the 'regular' attribute (see chapter 25.2 for most Graphviz attributes).

15.2 Loading a directed graph with custom and selectable vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with custom and selectable vertices is loaded, as shown in algorithm 202:

Algorithm 202 Loading a directed graph with custom vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_directed_custom_and_selectable_vertices_graph
    .h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex,
        boost::property<
            boost::vertex_is_selected_t, bool
        >
    >
>
>
load_directed_custom_and_selectable_vertices_graph_from_dot
(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_directed_custom_and_selectable_vertices_graph
        ();
    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id", get(boost::vertex_custom_type, g)
    );
    p.property("label", get(boost::vertex_custom_type, g));
    p.property("regular", get(boost::vertex_is_selected, g)
    );
    boost::read_graphviz(f, g, p);
    return g;
}
```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created. Then, a `boost::dynamic_properties` is created with its default constructor, after which

- The Graphviz attribute 'node_id' (see chapter 25.2 for most Graphviz attributes) is connected to a vertex its 'my_custom_vertex' property

- The Graphviz attribute 'label' is connected to a vertex its 'my_custom_vertex' property
- The Graphviz attribute 'regular' is connected to a vertex its 'is_selected' vertex property

Algorithm 203 shows how to use the 'load_directed_custom_vertices_graph_from_dot' function:

Algorithm 203 Demonstration of the 'load_directed_custom_and_selectable_vertices_graph_from_dot' function

```
#include <cassert>
#include "
    create_custom_and_selectable_vertices_markov_chain.h"
#include "is_regular_file.h"
#include "
    save_custom_and_selectable_vertices_graph_to_dot.h"

void
load_directed_custom_and_selectable_vertices_graph_from_dot_demo
() noexcept
{
    const auto g
        = create_custom_and_selectable_vertices_markov_chain
          ();
    const std::string filename{
        "create_custom_and_selectable_vertices_markov_chain.
        dot"
    };
    save_custom_and_selectable_vertices_graph_to_dot(
        g,
        filename
    );
    assert(is_regular_file(filename));
}
```

This demonstration shows how the Markov chain is created using the 'create_custom_vertices_markov_chain' function (algorithm 166), saved and then checked to exist.

15.3 Loading an undirected graph with custom and selectable vertices from a .dot

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with custom and selectable vertices is loaded, as shown in algorithm 204:

Algorithm 204 Loading an undirected graph with custom vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_undirected_custom_and_selectable_vertices_graph
    .h"
#include "install_vertex_custom_type.h"
#include "is_regular_file.h"
#include "my_custom_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex,
        boost::property<
            boost::vertex_is_selected_t, bool
        >
    >
>
>
>
load_undirected_custom_and_selectable_vertices_graph_from_dot
(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_undirected_custom_and_selectable_vertices_graph
        ();
    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id", get(boost::vertex_custom_type, g)
    );
    p.property("label", get(boost::vertex_custom_type, g));
    p.property("regular", get(boost::vertex_is_selected, g)
    );
    boost::read_graphviz(f, g, p);
    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 15.2 describes the rationale of this func-

tion.

Algorithm 205 shows how to use the 'load_undirected_custom_vertices_graph_from_dot' function:

Algorithm 205 Demonstration of the 'load_undirected_custom_and_selectable_vertices_graph_from_dot' function

```
#include <cassert>
#include "create_custom_and_selectable_vertices_k2_graph.h"
#include "is_regular_file.h"
#include "save_custom_and_selectable_vertices_graph_to_dot.h"

void
load_undirected_custom_and_selectable_vertices_graph_from_dot_demo
() noexcept
{
    const auto g
        = create_custom_and_selectable_vertices_k2_graph();
    const std::string filename{
        "create_custom_and_selectable_vertices_k2_graph.dot"
    };
    save_custom_and_selectable_vertices_graph_to_dot(
        g,
        filename
    );
    assert(is_regular_file(filename));
}
```

This demonstration shows how K_2 with custom vertices is created using the 'create_custom_vertices_k2_graph' function (algorithm 169), saved and then checked to exist.

16 Building graphs with custom edges and vertices

Up until now, the graphs created have had edges and vertices with the built-in name property. In this chapter, graphs will be created, in which the edges and vertices can have a custom 'my_custom_edge' and 'my_custom_edge' type¹³.

- An empty directed graph that allows for custom edges and vertices: see chapter 16.3

¹³I do not intend to be original in naming my data types

- An empty undirected graph that allows for custom edges and vertices: see chapter 16.4
- A two-state Markov chain with custom edges and vertices: see chapter 16.7
- K_3 with custom edges and vertices: see chapter 16.8

In the process, some basic (sometimes bordering trivial) functions are shown:

- Creating the custom edge class: see chapter 16.1
- Installing the new edge property: see chapter 16.2
- Adding a custom edge: see chapter 16.5

These functions are mostly there for completion and showing which data types are used.

16.1 Creating the custom edge class

In this example, I create a custom edge class. Here I will show the header file of it, as the implementation of it is not important yet.

Algorithm 206 Declaration of `my_custom_edge`

```
#include <string>
#include <iosfwd>

class my_custom_edge
{
public:
    explicit my_custom_edge(
        const std::string& name = "",
        const std::string& description = "",
        const double width = 1.0,
        const double height = 1.0
    ) noexcept;
    const std::string& get_description() const noexcept;
    const std::string& get_name() const noexcept;
    double get_width() const noexcept;
    double get_height() const noexcept;
private:
    std::string m_name;
    std::string m_description;
    double m_width;
    double m_height;
};

bool operator==(const my_custom_edge& lhs, const
    my_custom_edge& rhs) noexcept;
bool operator!=(const my_custom_edge& lhs, const
    my_custom_edge& rhs) noexcept;
std::ostream& operator<<(std::ostream& os, const
    my_custom_edge& v) noexcept;
std::istream& operator>>(std::istream& os, my_custom_edge
    & v) noexcept;
```

`my_custom_edge` is a class that has multiple properties: two doubles '`m_width`' (`'m_'` stands for member) and '`m_height`', and two `std::string`s `m_name` and `m_description`. '`my_custom_edge`' is copyable, but cannot trivially be converted to a `std::string`. '`my_custom_edge`' is comparable for equality (that is, `operator==` is defined).

Special characters like comma's, quotes and whitespace cannot be streamed without problems. The function '`graphviz_encode`' (algorithm 251) can convert the elements to be streamed to a Graphviz-friendly version, which can be decoded by '`graphviz_decode`' (algorithm 252).

16.2 Installing the new edge property

Installing a new property would have been easier, if 'more C++ compilers were standards conformant' ([8], chapter 3.6, footnote at page 52). Boost.Graph uses the BOOST_INSTALL_PROPERTY macro to allow using a custom property:

Algorithm 207 Installing the edge_custom_type property

```
#include <boost/graph/properties.hpp>

namespace boost {
    enum edge_custom_type_t { edge_custom_type = 3142 };
    BOOST_INSTALL_PROPERTY(edge, custom_type);
}
```

The enum value 3142 must be unique.

16.3 Create an empty directed graph with custom edges and vertices

Algorithm 208 Creating an empty directed graph with custom edges and vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "install_edge_custom_type.h"
#include "install_vertex_custom_type.h"
#include "my_custom_edge.h"
#include "my_custom_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >,
    boost::property<
        boost::edge_custom_type_t, my_custom_edge
    >
>
create_empty_directed_custom_edges_and_vertices_graph()
    noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        boost::property<
            boost::vertex_custom_type_t, my_custom_vertex
        >,
        boost::property<
            boost::edge_custom_type_t, my_custom_edge
        >
    >();
}
```

This code is very similar to the code described in chapter 12.3, except that there is a new, fifth template argument:

```
boost::property<boost::edge_custom_type_t, my_edge>
```

This can be read as: “edges have the property ‘boost::edge_custom_type_t’, which is of data type ‘my_custom_edge’”. Or simply: “edges have a custom

type called `my_custom_edge`".

Demo:

Algorithm 209 Demonstration of the 'create_empty_directed_custom_edges_and_vertices_graph' function

```
#include "
    create_empty_directed_custom_edges_and_vertices_graph.
h"

void
    create_empty_directed_custom_edges_and_vertices_graph_demo
    () noexcept
{
    const auto g =
        create_empty_directed_custom_edges_and_vertices_graph
        ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

16.4 Create an empty undirected graph with custom edges and vertices

Algorithm 210 Creating an empty undirected graph with custom edges and vertices

```
#include <boost/graph/adjacency_list.hpp>
#include "install_edge_custom_type.h"
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"
#include "my_custom_edge.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >,
    boost::property<
        boost::edge_custom_type_t, my_custom_edge
    >
>
create_empty_undirected_custom_edges_and_vertices_graph()
    noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_custom_type_t, my_custom_vertex
        >,
        boost::property<
            boost::edge_custom_type_t, my_custom_edge
        >
    >();
}
```

This code is very similar to the code described in chapter 16.3, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`).

Demo:

Algorithm 211 Demonstration of the 'create_empty_undirected_custom_edges_and_vertices_graph' function

```
#include <cassert>
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"

void
    create_empty_undirected_custom_edges_and_vertices_graph_demo
    () noexcept
{
    const auto g
        =
            create_empty_undirected_custom_edges_and_vertices_graph
            ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

16.5 Add a custom edge

Adding a custom edge is very similar to adding a named edge (chapter 6.3).

Algorithm 212 Add a custom edge

```
#include <cassert>
#include <boost/graph/adjacency_list.hpp>
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
void add_custom_edge(
    const my_custom_edge& v,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);

    const auto aer
        = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);
    const auto my_edge_map
        = get( //not boost::get
            boost::edge_custom_type, g
        );
    my_edge_map[aer.first] = v;
}
```

When having added a new (abstract) edge to the graph, the edge descriptor is used to set the my_edge in the graph its my_custom_edge map (using 'get(boost::edge_custom_type,g)').

Here is the demo:

Algorithm 213 Demo of 'add_custom_edge'

```
#include <cassert>
#include "add_custom_edge.h"
#include "
    create_empty_directed_custom_edges_and_vertices_graph.
    h"
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"

void add_custom_edge_demo() noexcept
{
    auto g =
        create_empty_directed_custom_edges_and_vertices_graph
        ();
    add_custom_edge(my_custom_edge("X"), g);
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 1);

    auto h =
        create_empty_undirected_custom_edges_and_vertices_graph
        ();
    add_custom_edge(my_custom_edge("Y"), h);
    assert(boost::num_vertices(h) == 2);
    assert(boost::num_edges(h) == 1);
}
```

16.6 Getting the custom edges my_edges

When the edges of a graph have an associated 'my_custom_edge', one can extract these all as such:

Algorithm 214 Get the edges' my_custom_edges

```
#include <vector>
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
std::vector<my_custom_edge> get_custom_edge_my_edges(
    const graph& g
) noexcept
{
    std::vector<my_custom_edge> v;

    const auto my_custom_edges_map
        = get( //not boost::get
              boost::edge_custom_type, g
            );
    const auto vip
        = edges(g); //not boost::edges
    const auto j = vip.second;

    for (auto i = vip.first; i!=j; ++i) {
        v.emplace_back(
            get( //not boost::get
                my_custom_edges_map, *i
            )
        );
    }
    return v;
}
```

The 'my_custom_edge' object associated with the edges are obtained from a boost::property_map and then put into a std::vector.

Note: the order of the my_custom_edge objects may be different after saving and loading.

When trying to get the edges' my_custom_edge objects from a graph without custom edges objects associated, you will get the error 'formed reference to void' (see chapter 24.1).

16.7 Creating a Markov-chain with custom edges and vertices

16.7.1 Graph

Figure 30 shows the graph that will be reproduced:




Figure 30: A two-state Markov chain where the edges and vertices have custom properties. The edges' and vertices' properties are nonsensical

16.7.2 Function to create such a graph

Here is the code creating a two-state Markov chain with custom edges and vertices:

Algorithm 215 Creating the two-state Markov chain as depicted in figure 30

```
#include <cassert>
#include "
    create_empty_directed_custom_edges_and_vertices_graph.
    h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >,
    boost::property<
        boost::edge_custom_type_t, my_custom_edge
    >
>
>
create_custom_edges_and_vertices_markov_chain() noexcept
{
    auto g
        =
            create_empty_directed_custom_edges_and_vertices_graph
                ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    auto my_custom_vertexes_map = get( //not boost::get
        boost::vertex_custom_type, g
    );
    my_custom_vertexes_map[vd_a]
        = my_custom_vertex("Sunny", "Yellow_thing", 1.0, 2.0);
    my_custom_vertexes_map[vd_b]
        = my_custom_vertex("Rainy", "Grey_things", 3.0, 4.0);

    auto my_edges_map = get( //not boost::get
        boost::edge_custom_type, g
    );
    my_edges_map[aer_aa.first]
        = my_custom_edge("Sometimes", "20%", 1.0, 2.0);
    my_edges_map[aer_ab.first]231
        = my_custom_edge("Often", "80%", 3.0, 4.0);
    my_edges_map[aer_ba.first]
        = my_custom_edge("Rarely", "10%", 5.0, 6.0);
    my_edges_map[aer_bb.first]
        = my_custom_edge("Mostly", "90%", 7.0, 8.0);

    return g;
}
```

16.7.3 Creating such a graph

Here is the demo:

Algorithm 216 Demo of the 'create_custom_edges_and_vertices_markov_chain' function (algorithm 215)

```
#include <cassert>
#include "create_custom_edges_and_vertices_markov_chain.h"
"
#include "get_custom_vertex_my_vertexes.h"
#include "install_vertex_custom_type.h"
#include "my_custom_vertex.h"

void create_custom_edges_and_vertices_markov_chain_demo()
    noexcept
{
    const auto g
        = create_custom_edges_and_vertices_markov_chain();
    const std::vector<my_custom_vertex>
        expected_my_custom_vertexes{
            my_custom_vertex("Sunny",
                "Yellow_thing",1.0,2.0
            ),
            my_custom_vertex("Rainy",
                "Grey_things",3.0,4.0
            )
        };
    const std::vector<my_custom_vertex>
        vertex_my_custom_vertexes{
            get_custom_vertex_my_vertexes(g)
        };
    assert(expected_my_custom_vertexes
        == vertex_my_custom_vertexes
    );
}
```

16.7.4 The .dot file produced

Algorithm 217 .dot file created from the 'create_custom_edges_and_vertices_markov_chain' function (algorithm 215), converted from graph to .dot file using algorithm 29

```

digraph G {
0[label="Sunny,Yellow[:SPACE:]thing,1,1"];
1[label="Rainy,Grey[:SPACE:]things,3,3"];
0->0 [label="Sometimes,20%,1,2"];
0->1 [label="Often,80%,3,4"];
1->0 [label="Rarely,10%,5,6"];
1->1 [label="Mostly,90%,7,8"];
}

```

16.7.5 The .svg file produced




Figure 31: .svg file created from the 'create_custom_edges_and_vertices_markov_chain' function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

16.8 Creating K_3 with custom edges and vertices

Instead of using edges with a name, or other properties, here we use a custom edge class called 'my_custom_edge'.

16.8.1 Graph

We reproduce the K_3 with named edges and vertices of chapter 6.6 , but with our custom edges and vertices instead:

[graph here]

16.8.2 Function to create such a graph

Algorithm 218 Creating K_3 as depicted in figure 16

```
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >,
    boost::property<
        boost::edge_custom_type_t, my_custom_edge
    >
>
create_custom_edges_and_vertices_k3_graph() noexcept
{
    auto g
        =
            create_empty_undirected_custom_edges_and_vertices_graph
            ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto vd_c = boost::add_vertex(g);
    const auto aer_a = boost::add_edge(vd_a, vd_b, g);
    const auto aer_b = boost::add_edge(vd_b, vd_c, g);
    const auto aer_c = boost::add_edge(vd_c, vd_a, g);
    assert(aer_a.second);
    assert(aer_b.second);
    assert(aer_c.second);

    auto my_custom_vertex_map
        = get( //not boost::get
            boost::vertex_custom_type, g
        );
    my_custom_vertex_map[vd_a]
        = my_custom_vertex("top", "source", 0.0, 0.0);
    my_custom_vertex_map[vd_b]
        = my_custom_vertex("right", "target", 3.14, 0);
    my_custom_vertex_map[vd_c]
        = my_custom_vertex("left", "target", 0, 3.14);

    auto my_edge_map = get(boost::edge_custom_type, g);
    my_edge_map[aer_a.first] 234
        = my_custom_edge("AB", "first", 0.0, 0.0);
    my_edge_map[aer_b.first]
        = my_custom_edge("BC", "second", 3.14, 3.14);
    my_edge_map[aer_c.first]
        = my_custom_edge("CA", "third", 3.14, 3.14);

    return g;
}
```

Most of the code is a slight modification of algorithm 84. In the end, the `my_edges` and `my_vertices` are obtained as a `boost::property_map` and set with the `'my_custom_edge'` and `'my_custom_vertex'` objects.

16.8.3 Creating such a graph

Here is the demo:

Algorithm 219 Demo of the `'create_custom_edges_and_vertices_k3_graph'` function (algorithm 218)

```
#include <cassert>
#include "add_custom_edge.h"
#include "add_custom_vertex.h"
#include "create_custom_edges_and_vertices_k3_graph.h"

void create_custom_edges_and_vertices_k3_graph_demo()
    noexcept
{
    auto g
        = create_custom_edges_and_vertices_k3_graph();
    assert(boost::num_edges(g) == 3);
    assert(boost::num_vertices(g) == 3);
    add_custom_vertex(my_custom_vertex("v"), g);
    add_custom_edge(my_custom_edge("e"), g);
}
```

16.8.4 The .dot file produced

Algorithm 220 .dot file created from the `'create_custom_edges_and_vertices_markov_chain'` function (algorithm 218), converted from graph to .dot file using algorithm 29

```
graph G {
0[label="top,source,0,0"];
1[label="right,target,3.14,3.14"];
2[label="left,target,0,0"];
0--1 [label="AB,first,0,0"];
1--2 [label="BC,second,3.14,3.14"];
2--0 [label="CA,third,3.14,3.14"];
}
```

16.8.5 The .svg file produced




Figure 32: .svg file created from the 'create_custom_edges_and_vertices_k3_graph' function (algorithm 166) its .dot file, converted from .dot file to .svg using algorithm 254

17 Working on graphs with custom edges and vertices

17.1 Has a my_custom_edge

Before modifying our edges, let's first determine if we can find an edge by its custom type ('my_custom_edge') in a graph. After obtaining a my_custom_edge map, we obtain the edge iterators, dereference these to obtain the edge descriptors and then compare each edge its my_custom_edge with the one desired.

Algorithm 221 Find if there is a custom edge with a certain `my_custom_edge`

```
#include <boost/graph/properties.hpp>
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
bool has_custom_edge_with_my_edge(
    const my_custom_edge& e,
    const graph& g
) noexcept
{
    const auto my_edges_map
        = get(boost::edge_custom_type, g);
    const auto eip
        = edges(g); //not boost::edges
    const auto j = eip.second;

    for (auto i = eip.first; i!=j; ++i) {
        if (
            get( //not boost::get
                my_edges_map,
                *i
            ) == e) {
            return true;
        }
    }
    return false;
}
```

This function can be demonstrated as in algorithm 222, where a certain 'my_custom_edge' cannot be found in an empty graph. After adding the desired my_custom_edge, it is found.

Algorithm 222 Demonstration of the 'has_custom_edge_with_my_edge' function

```
#include <cassert>
#include "add_custom_edge.h"
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"
#include "has_custom_edge_with_my_edge.h"

void has_custom_edge_with_my_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_custom_edges_and_vertices_graph
                ();
    assert (
        !has_custom_edge_with_my_edge(
            my_custom_edge("Edward"), g
        )
    );
    add_custom_edge(my_custom_edge("Edward"), g);
    assert (
        has_custom_edge_with_my_edge(
            my_custom_edge("Edward"), g
        )
    );
}
```

Note that this function only finds if there is at least one edge with that my_custom_edge: it does not tell how many edges with that my_custom_edge exist in the graph.

17.2 Find a my_custom_edge

Where STL functions work with iterators, here we obtain an edge descriptor (see chapter 2.12) to obtain a handle to the desired edge. Algorithm 223 shows how to obtain an edge descriptor to the first edge found with a specific my_custom_edge value.

Algorithm 223 Find the first custom edge with a certain `my_custom_edge`

```
#include <cassert>
#include <boost/graph/graph_traits.hpp>
#include "has_custom_edge_with_my_edge.h"
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
typename boost::graph_traits<graph>::edge_descriptor
find_first_custom_edge_with_my_edge(
    const my_custom_edge& e,
    const graph& g
) noexcept
{
    assert(has_custom_edge_with_my_edge(e, g));
    const auto my_edges_map = get(boost::edge_custom_type,
        g);
    const auto eip = edges(g); //not boost::edges
    const auto j = eip.second;

    for (auto i = eip.first; i!=j; ++i) {
        if (
            get( //not boost::get
                my_edges_map,
                *i
            ) == e) {
            return *i;
        }
    }
    assert(!"Should_not_get_here");
    throw; //Will crash the program
}
```

With the edge descriptor obtained, one can read and modify the edge and the vertices surrounding it. Algorithm 224 shows some examples of how to do so.

Algorithm 224 Demonstration of the 'find_first_custom_edge_with_my_edge' function

```
#include <cassert>

#include "create_custom_edges_and_vertices_k3_graph.h"
#include "find_first_custom_edge_with_my_edge.h"

void find_first_custom_edge_with_my_edge_demo() noexcept
{
    const auto g
        = create_custom_edges_and_vertices_k3_graph();
    const auto ed
        = find_first_custom_edge_with_my_edge(
            my_custom_edge("AB", "first", 0.0, 0.0),
            g
        );
    assert(boost::source(ed, g)
        != boost::target(ed, g)
    );
}
```

17.3 Get an edge its my_custom_edge

To obtain the my_edeg from an edge descriptor, one needs to pull out the my_custom_edges map and then look up the my_edge of interest.

Algorithm 225 Get a vertex its `my_custom_vertex` from its vertex descriptor

```
#include <boost/graph/graph_traits.hpp>
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
my_custom_edge get_custom_edge_my_edge(
    const typename boost::graph_traits<graph>::
        edge_descriptor& vd,
    const graph& g
) noexcept
{
    const auto my_edge_map
        = get( //not boost::get
            boost::edge_custom_type,
            g
        );
    return my_edge_map[vd];
}
```

To use 'get_custom_edge_my_custom_edge', one first needs to obtain an edge descriptor. Algorithm 226 shows a simple example.

Algorithm 226 Demonstration if the 'get_custom_edge_my_edge' function

```
#include <cassert>

#include "add_custom_edge.h"
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"
#include "find_first_custom_edge_with_my_edge.h"
#include "get_custom_edge_my_edge.h"

void get_custom_edge_my_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_custom_edges_and_vertices_graph
            ();
    const my_custom_edge edge{"Dex"};
    add_custom_edge(edge, g);
    const auto ed
        = find_first_custom_edge_with_my_edge(edge, g);
    assert(get_custom_edge_my_edge(ed, g) == edge);
}
```

17.4 Set an edge its my_custom_edge

If you know how to get the my_custom_edge from an edge descriptor, setting it is just as easy, as shown in algorithm 227.

Algorithm 227 Set a custom edge its `my_custom_edge` from its edge descriptor

```
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>
#include "install_edge_custom_type.h"
#include "my_custom_edge.h"

template <typename graph>
void set_custom_edge_my_edge(
    const my_custom_edge& name,
    const typename boost::graph_traits<graph>::
        edge_descriptor& vd,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    auto my_edge_map = get(boost::edge_custom_type, g);
    my_edge_map[vd] = name;
}
```

To use 'set_custom_edge_my_edge', one first needs to obtain an edge descriptor. Algorithm 228 shows a simple example.

Algorithm 228 Demonstration if the 'set_custom_edge_my_edge' function

```
#include <cassert>

#include "add_custom_edge.h"
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"
#include "find_first_custom_edge_with_my_edge.h"
#include "get_custom_edge_my_edge.h"
#include "set_custom_edge_my_edge.h"

void set_custom_edge_my_edge_demo() noexcept
{
    auto g
        =
            create_empty_undirected_custom_edges_and_vertices_graph
            ();
    const my_custom_edge old_edge{"Dex"};
    add_custom_edge(old_edge, g);
    const auto vd
        = find_first_custom_edge_with_my_edge(old_edge, g);
    assert(get_custom_edge_my_edge(vd, g)
        == old_edge
    );
    const my_custom_edge new_edge{"Diggy"};
    set_custom_edge_my_edge(new_edge, vd, g);
    assert(get_custom_edge_my_edge(vd, g)
        == new_edge
    );
}
```

17.5 Storing a graph with custom edges and vertices as a .dot

If you used the `create_custom_edges_and_vertices_k3_graph` function (algorithm 218) to produce a K_3 graph with edges and vertices associated with `my_custom_edge` and `my_custom_vertex` objects, you can store these `my_custom_edges` and `my_custom_vertex-es` additionally with algorithm 229:

Algorithm 229 Storing a graph with custom edges and vertices as a .dot file

```
#include <fstream>
#include <string>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>
#include "get_custom_edge_my_edge.h"
#include "get_custom_vertex_my_vertexes.h"

template <typename graph>
void save_custom_edges_and_vertices_graph_to_dot(
    const graph& g,
    const std::string& filename
)
{
    using my_vertex_descriptor = typename graph::
        vertex_descriptor;
    using my_edge_descriptor = typename graph::
        edge_descriptor;
    std::ofstream f(filename);
    const auto my_custom_vertexes =
        get_custom_vertex_my_vertexes(g);
    boost::write_graphviz(
        f,
        g,
        [my_custom_vertexes](
            std::ostream& out,
            const my_vertex_descriptor& v
        ) {
            const my_custom_vertex m{my_custom_vertexes[v]};
            out << "[label=\"" << m << "\"]";
        },
        [g](std::ostream& out,
            const my_edge_descriptor& e
        ) {
            const my_custom_edge m{get_custom_edge_my_edge(e,g)};
            out << "[label=\"" << m << "\"]";
        }
    );
}
```

17.6 Load a directed graph with custom edges and vertices from a .dot file

When loading a graph from file, one needs to specify a type of graph. In this example, an directed graph with custom edges and vertices is loaded, as shown in algorithm 230:

Algorithm 230 Loading a directed graph with custom edges and vertices from a .dot file

```

#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_directed_custom_edges_and_vertices_graph.
    h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >,
    boost::property<
        boost::edge_custom_type_t, my_custom_edge
    >
>
load_directed_custom_edges_and_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_directed_custom_edges_and_vertices_graph
        ();
    boost::dynamic_properties p; //_do_ default construct
    p.property("node_id", get(boost::vertex_custom_type, g)
    );
    p.property("label", get(boost::vertex_custom_type, g));
    p.property("edge_id", get(boost::edge_custom_type, g));
    p.property("label", get(boost::edge_custom_type, g));
    boost::read_graphviz(f,g,p);
    return g;
}

```

In this algorithm, first it is checked if the file to load exists. Then an empty directed graph is created. Next to this, a `boost::dynamic_properties` is created with its default constructor, after which we direct the `boost::dynamic_properties` to find a 'node_id' and 'label' in the vertex name map, 'edge_id' and 'label' to the edge name map. From this and the empty graph, 'boost::read_graphviz' is

called to build up the graph.

Algorithm 231 shows how to use the 'load_directed_custom_edges_and_vertices_graph_from_dot' function:

Algorithm 231 Demonstration of the 'load_directed_custom_edges_and_vertices_graph_from_dot' function

```
#include "create_custom_edges_and_vertices_markov_chain.h"
"
#include "get_custom_vertex_my_vertexes.h"
#include "
    load_directed_custom_edges_and_vertices_graph_from_dot
    .h"
#include "save_custom_edges_and_vertices_graph_to_dot.h"

void
load_directed_custom_edges_and_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_custom_edges_and_vertices_markov_chain();
    const std::string filename{
        "create_custom_edges_and_vertices_markov_chain.dot"
    };
    save_custom_edges_and_vertices_graph_to_dot(g, filename
    );
    const auto h
        =
            load_directed_custom_edges_and_vertices_graph_from_dot
            (
                filename
            );
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_custom_vertex_my_vertexes(g)
        == get_custom_vertex_my_vertexes(h)
    );
}
```

This demonstration shows how the Markov chain is created using the 'create_custom_edges_and_vertices_markov_chain' function (algorithm 215), saved and then loaded.

17.7 Load an undirected graph with custom edges and vertices from a .dot file

When loading a graph from file, one needs to specify a type of graph. In this example, an undirected graph with custom edges and vertices is loaded, as shown in algorithm 232:

Algorithm 232 Loading an undirected graph with custom edges and vertices from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "
    create_empty_undirected_custom_edges_and_vertices_graph
    .h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_custom_vertex
    >,
    boost::property<
        boost::edge_custom_type_t, my_custom_edge
    >
>
load_undirected_custom_edges_and_vertices_graph_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g =
        create_empty_undirected_custom_edges_and_vertices_graph
        ();
    boost::dynamic_properties p; //_do_default_construct
    p.property("node_id", get(boost::vertex_custom_type, g)
    );
    p.property("label", get(boost::vertex_custom_type, g));
    p.property("edge_id", get(boost::edge_custom_type, g));
    p.property("label", get(boost::edge_custom_type, g));
    boost::read_graphviz(f, g, p);
    return g;
}
```

The only difference with loading a directed graph, is that the initial empty graph is undirected instead. Chapter 17.6 describes the rationale of this function.

Algorithm 233 shows how to use the 'load_undirected_custom_vertices_graph_from_dot' function:

Algorithm 233 Demonstration of the 'load_undirected_custom_edges_and_vertices_graph_from_dot' function

```
#include "create_custom_edges_and_vertices_k3_graph.h"
#include "
    load_undirected_custom_edges_and_vertices_graph_from_dot
    .h"
#include "save_custom_edges_and_vertices_graph_to_dot.h"
#include "get_custom_vertex_my_vertexes.h"

void
load_undirected_custom_edges_and_vertices_graph_from_dot_demo
() noexcept
{
    using boost::num_edges;
    using boost::num_vertices;

    const auto g
        = create_custom_edges_and_vertices_k3_graph();
    const std::string filename{
        "create_custom_edges_and_vertices_k3_graph.dot"
    };
    save_custom_edges_and_vertices_graph_to_dot(g, filename
    );
    const auto h
        =
        load_undirected_custom_edges_and_vertices_graph_from_dot
        (filename);
    assert(num_edges(g) == num_edges(h));
    assert(num_vertices(g) == num_vertices(h));
    assert(get_custom_vertex_my_vertexes(g) ==
        get_custom_vertex_my_vertexes(h));
}
```

This demonstration shows how K_2 with custom vertices is created using the 'create_custom_vertices_k2_graph' function (algorithm 169), saved and then loaded. The loaded graph is checked to be a graph similar to the original.

18 Building graphs with a graph name

Up until now, the graphs created have had no properties themselves. Sure, the edges and vertices have had properties, but the graph itself has had none. Until now.

In this chapter, graphs will be created with a graph name of type `std::string`

- An empty directed graph with a graph name: see chapter
- An empty undirected graph with a graph name: see chapter
- A two-state Markov chain with a graph name: see chapter
- K_3 with a graph name: see chapter

In the process, some basic (sometimes bordering trivial) functions are shown:

- Getting a graph its name: see chapter
- Setting a graph its name: see chapter

18.1 Create an empty directed graph with a graph name property

Algorithm 234 shows the function to create an empty directed graph with a graph name.

Algorithm 234 Creating an empty directed graph with a graph name

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::no_property,
    boost::no_property,
    boost::property<
        boost::graph_name_t, std::string
    >
>
>
create_empty_directed_graph_with_graph_name() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::directedS,
        boost::no_property,
        boost::no_property,
        boost::property<
            boost::graph_name_t, std::string
        >
    >();
}
```

This `boost::adjacency_list` is of the following type:

- the first '`boost::vecS`': select (that is what the '`S`' means) that out edges are stored in a `std::vector`. This is the default way.
- the second '`boost::vecS`': select that the graph vertices are stored in a `std::vector`. This is the default way.
- '`boost::directedS`': select that the graph is directed. This is the default selectedness
- the first '`boost::no_property`': the vertices have no properties. This is the default (non-)property
- the second '`boost::no_property`': the vertices have no properties. This is the default (non-)property
- '`boost::property<boost::graph_name_t, std::string>`': the graph itself has a single property: its `boost::graph_name` has type `std::string`

Algorithm 235 demonstrates the '`create_empty_directed_graph_with_graph_name`' function.

Algorithm 235 Demonstration of '`create_empty_directed_graph_with_graph_name`'

```
#include <cassert>
#include "create_empty_directed_graph_with_graph_name.h"

void create_empty_directed_graph_with_graph_name_demo()
    noexcept
{
    auto g
        = create_empty_directed_graph_with_graph_name();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

18.2 Create an empty undirected graph with a graph name property

Algorithm 236 shows the function to create an empty undirected graph with a graph name.

Algorithm 236 Creating an empty undirected graph with a graph name

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::no_property,
    boost::no_property,
    boost::property<
        boost::graph_name_t, std::string
    >
>
>
create_empty_undirected_graph_with_graph_name() noexcept
{
    return boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::no_property,
        boost::no_property,
        boost::property<
            boost::graph_name_t, std::string
        >
    >();
}
```

This code is very similar to the code described in chapter 234, except that the directedness (the third template argument) is undirected (due to the `boost::undirectedS`).

Algorithm 237 demonstrates the 'create_empty_undirected_graph_with_graph_name' function.

Algorithm 237 Demonstration of 'create_empty_undirected_graph_with_graph_name'

```
#include <cassert>

#include "create_empty_undirected_graph_with_graph_name.h"

void create_empty_undirected_graph_with_graph_name_demo()
    noexcept
{
    auto g = create_empty_undirected_graph_with_graph_name
        ();
    assert(boost::num_edges(g) == 0);
    assert(boost::num_vertices(g) == 0);
}
```

18.3 Get a graph its name property

Algorithm 238 Get a graph its name

```
#include <string>
#include <boost/graph/properties.hpp>

template <typename graph>
std::string get_graph_name(
    const graph& g
) noexcept
{
    return
        get_property( //not boost::get_property
            g, boost::graph_name
        );
}
```

Algorithm 239 demonstrates the 'get_graph_name' function.

Algorithm 239 Demonstration of 'get_graph_name'

```
#include <cassert>

#include "create_empty_directed_graph_with_graph_name.h"
#include "get_graph_name.h"
#include "set_graph_name.h"

void get_graph_name_demo() noexcept
{
    auto g = create_empty_directed_graph_with_graph_name();
    const std::string name{"Dex"};
    set_graph_name(name, g);
    assert(get_graph_name(g) == name);
}
```

18.4 Set a graph its name property

Algorithm 240 Set a graph its name

```
#include <cassert>
#include <string>
#include <boost/graph/properties.hpp>

template <typename graph>
void set_graph_name(
    const std::string& name,
    graph& g
) noexcept
{
    static_assert(!std::is_const<graph>::value, "graph_
        cannot_be_const");

    get_property( //not boost::get_property
        g, boost::graph_name
    ) = name;
}
```

Algorithm 241 demonstrates the 'set_graph_name' function.

Algorithm 241 Demonstration of 'set_graph_name'

```
#include <cassert>

#include "create_empty_directed_graph_with_graph_name.h"
#include "get_graph_name.h"
#include "set_graph_name.h"

void set_graph_name_demo() noexcept
{
    auto g = create_empty_directed_graph_with_graph_name();
    const std::string name{"Dex"};
    set_graph_name(name, g);
    assert(get_graph_name(g) == name);
}
```

18.5 Create a directed graph with a graph name property

18.5.1 Graph

See figure 6.

18.5.2 Function to create such a graph

Algorithm 242 shows the function to create an empty directed graph with a graph name.

Algorithm 242 Creating a two-state Markov chain with a graph name

```
#include <cassert>
#include "create_empty_directed_graph_with_graph_name.h"
#include "set_graph_name.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::no_property,
    boost::no_property,
    boost::property<boost::graph_name_t, std::string>
>
create_markov_chain_with_graph_name() noexcept
{
    auto g = create_empty_directed_graph_with_graph_name();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer_aa = boost::add_edge(vd_a, vd_a, g);
    assert(aer_aa.second);
    const auto aer_ab = boost::add_edge(vd_a, vd_b, g);
    assert(aer_ab.second);
    const auto aer_ba = boost::add_edge(vd_b, vd_a, g);
    assert(aer_ba.second);
    const auto aer_bb = boost::add_edge(vd_b, vd_b, g);
    assert(aer_bb.second);

    set_graph_name("Two-state_Markov_chain", g);
    return g;
}
```

18.5.3 Creating such a graph

Algorithm 243 demonstrates the 'create_markov_chain_with_graph_name' function.

Algorithm 243 Demonstration of 'create_markov_chain_with_graph_name'

```
#include <cassert>
#include "create_markov_chain_with_graph_name.h"
#include "get_graph_name.h"

void create_markov_chain_with_graph_name_demo() noexcept
{
    const auto g = create_markov_chain_with_graph_name();
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 4);
    assert(get_graph_name(g) == "Two-state Markov chain");
}
```

18.5.4 The .dot file produced

Algorithm 244 .dot file created from the 'create_markov_chain_with_graph_name' function (algorithm 242), converted from graph to .dot file using algorithm 29

```
digraph G {
name="Two-state Markov chain";
0;
1;
0->0 ;
0->1 ;
1->0 ;
1->1 ;
}
```

18.5.5 The .svg file produced




Figure 33: .svg file created from the 'create_markov_chain_with_graph_name' function (algorithm 242) its .dot file, converted from .dot file to .svg using algorithm 254

18.6 Create an undirected graph with a graph name property

18.6.1 Graph

See figure 8.

18.6.2 Function to create such a graph

Algorithm 245 shows the function to create K2 graph with a graph name.

Algorithm 245 Creating a K2 graph with a graph name

```
#include "create_empty_undirected_graph_with_graph_name.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::no_property,
    boost::no_property,
    boost::property<boost::graph_name_t, std::string>
>
create_k2_graph_with_graph_name() noexcept
{
    auto g = create_empty_undirected_graph_with_graph_name
        ();
    const auto vd_a = boost::add_vertex(g);
    const auto vd_b = boost::add_vertex(g);
    const auto aer = boost::add_edge(vd_a, vd_b, g);
    assert(aer.second);

    get_property( //not boost::get_property
        g, boost::graph_name
    ) = "K2";

    return g;
}
```

18.6.3 Creating such a graph

Algorithm 246 demonstrates the 'create_k2_graph_with_graph_name' function.

Algorithm 246 Demonstration of 'create_k2_graph_with_graph_name'

```
#include <cassert>

#include "create_k2_graph_with_graph_name.h"
#include "get_graph_name.h"

void create_k2_graph_with_graph_name_demo() noexcept
{
    const auto g = create_k2_graph_with_graph_name();
    assert(boost::num_vertices(g) == 2);
    assert(boost::num_edges(g) == 1);
    assert(get_graph_name(g) == "K2");
}
```

18.6.4 The .dot file produced

Algorithm 247 .dot file created from the 'create_k2_graph_with_graph_name' function (algorithm 245), converted from graph to .dot file using algorithm 29

```
graph G {
name="K2";
0;
1;
0--1 ;
}
```

18.6.5 The .svg file produced




Figure 34: .svg file created from the 'create_k2_graph_with_graph_name' function (algorithm 245) its .dot file, converted from .dot file to .svg using algorithm 254

19 Working on graphs with a graph name

19.1 Storing a graph with a graph name property as a .dot file

I am unsure if this results in a .dot file that can produce a graph with a graph name, but this is what I came up with.

Algorithm 248 Storing a graph with a graph name as a .dot file

```
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_graph_name.h"

template <typename graph>
void save_graph_with_graph_name_to_dot(
    const graph& g,
    const std::string& filename
)
{
    std::ofstream f(filename);
    boost::write_graphviz(
        f,
        g,
        boost::default_writer(),
        boost::default_writer(),
        //Unsure if this results in a graph
        //that can be loaded correctly
        //from a .dot file
        [g](std::ostream& os) {
            os << "name=\"\"";
            << get_graph_name(g);
            << "\";\n\"";
        }
    );
}
```

19.2 Loading a directed graph with a graph name property from a .dot file

This will result in a directed graph without a name [ISSUE #12]. Please email me if you know how to do this correctly.

Algorithm 249 Loading a directed graph with a graph name from a .dot file

```
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include "create_empty_directed_graph_with_graph_name.h"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::directedS,
    boost::no_property,
    boost::no_property,
    boost::property<
        boost::graph_name_t, std::string
    >
>
>
load_directed_graph_with_graph_name_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_directed_graph_with_graph_name();

    #ifdef TODO_KNOW_HOW_TO_LOAD_A_GRAPH_ITS_NAME
    boost::dynamic_properties p; //_do_ default construct
    p.property("name", get_property(g, boost::graph_name));
    //AFAIK, this should work
    #else
    boost::dynamic_properties p(
        boost::ignore_other_properties
    );
    #endif
    boost::read_graphviz(f, g, p);
    return g;
}
```

Note the part that I removed using `#ifdef`: I read that that is a valid approach, according to the Boost.Graph documentation (see http://www.boost.org/doc/libs/1_60_0/libs/graph/doc/read_graphviz.html), but it failed to compile.

19.3 Loading an undirected graph with a graph name property from a .dot file

This will result in an undirected graph without a name. [ISSUE #12] Please email me if you know how to do this correctly.

Algorithm 250 Loading an undirected graph with a graph name from a .dot file

```
#include <fstream>
#include <string>
#include <boost/graph/graphviz.hpp>
#include "create_empty_undirected_graph_with_graph_name.h"
"
#include "is_regular_file.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::no_property,
    boost::no_property,
    boost::property<
        boost::graph_name_t, std::string
    >
>
>
load_undirected_graph_with_graph_name_from_dot(
    const std::string& dot_filename
)
{
    assert(is_regular_file(dot_filename));
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_undirected_graph_with_graph_name
        ();

    #ifdef TODO_KNOW_HOW_TO_LOAD_A_GRAPH_ITS_NAME
    boost::dynamic_properties p; //_do_default_construct
    p.property("name", get_property(g, boost::graph_name));
    //AFAIK, this should work
    #else
    boost::dynamic_properties p(
        boost::ignore_other_properties
    );
    #endif
    boost::read_graphviz(f, g, p);
    return g;
}
```

Note the part that I removed using `#ifdef`: I read that that is a valid approach, according to the Boost.Graph documentation (see http://www.boost.org/doc/libs/1_60_0/libs/graph/doc/read_graphviz.html), but it failed

to compile.

20 Building graphs with custom graph properties

I will write this chapter if and only if I can save and load a graph with a graph name (as in chapter 18). That is, if Issue #12 is fixed.

21 Working on graphs with custom graph properties

I will write this chapter if and only if I can save and load a graph with a graph name (as in chapter 18). That is, if Issue #12 is fixed.

22 Other graph functions

Some functions that did not fit in

22.1 Encode a `std::string` to a Graphviz-friendly format

You may want to use a label with spaces, comma's and/or quotes. Saving and loading these, will result in problem. This function replaces these special characters by a rare combination of ordinary characters.

Algorithm 251 Encode a `std::string` to a Graphviz-friendly format

```
#include <boost/algorithm/string/replace.hpp>

std::string graphviz_encode(std::string s) noexcept
{
    boost::algorithm::replace_all(s, ",", "[[:COMMA:]]");
    boost::algorithm::replace_all(s, " ", "[[:SPACE:]]");
    boost::algorithm::replace_all(s, "\"", "[[:QUOTE:]]");
    return s;
}
```

22.2 Decode a `std::string` from a Graphviz-friendly format

This function undoes the 'graphviz_encode' function (algorithm 251) and thus converts a Graphviz-friendly `std::string` to the original human-friendly `std::string`.

Algorithm 252 Decode a `std::string` from a Graphviz-friendly format to a human-friendly format

```
#include <boost/algorithm/string/replace.hpp>

std::string graphviz_decode(std::string s) noexcept
{
    boost::algorithm::replace_all(s, "[[:COMMA:]]", ",");
    boost::algorithm::replace_all(s, "[[:SPACE:]]", "_");
    boost::algorithm::replace_all(s, "[[:QUOTE:]]", "\"");
    return s;
}
```

23 Misc functions

These are some function I needed for creating this tutorial. Although they are not important for working with graphs, I used these heavily. These functions may be compiler-dependent, platform-dependent and/or there may be superior alternatives. I just add them for completeness.

23.1 Getting a data type as a `std::string`

This function will only work under GCC. I found this code at: <http://stackoverflow.com/questions/1055452/c-get-name-of-type-in-template>. Thanks to 'm-dudley' (Stack Overflow userpage at <http://stackoverflow.com/users/111327/m-dudley>).

Algorithm 253 Getting a data type its name as a `std::string`

```
#include <cstdlib>
#include <string>
#include <typeinfo>
#include <cxxabi.h>

template<typename T>
std::string get_type_name() noexcept
{
    std::string tname = typeid(T).name();
    int status = -1;
    char * const demangled_name{
        abi::__cxa_demangle(
            tname.c_str(), NULL, NULL, &status
        )
    };
    if(status == 0) {
        tname = demangled_name;
        std::free(demangled_name);
    }
    return tname;
}
```

23.2 Convert a .dot to .svg

All illustrations in this tutorial are created by converting .dot to a .svg ('Scalable Vector Graphic') file. This function assumes the program 'dot' is installed, which is part of Graphviz.

Algorithm 254 Convert a .dot file to a .svg

```
#include <cassert>
#include <string>
#include <sstream>
#include "has_dot.h"
#include "is_regular_file.h"
#include "is_valid_dot_file.h"

void convert_dot_to_svg(
    const std::string& dot_filename,
    const std::string& svg_filename
)
{
    assert(has_dot());
    assert(is_valid_dot_file(dot_filename));
    std::stringstream cmd;
    cmd << "dot-Tsvg_" << dot_filename << "_-o_" <<
        svg_filename;
    std::system(cmd.str().c_str());
    assert(is_regular_file(svg_filename));
}
```

'convert_dot_to_svg' makes a system call to the program 'dot' to convert the .dot file to an .svg file.

23.3 Check if a file exists

Not the most smart way perhaps, but it does only use the STL.

Algorithm 255 Check if a file exists

```
#include <fstream>

bool is_regular_file(const std::string& filename)
    noexcept
{
    std::fstream f;
    f.open(filename.c_str(), std::ios::in);
    return f.is_open();
}
```

24 Errors

Some common errors.

24.1 Formed reference to void

This compile-time error occurs when you create a graph without a certain property, then subsequently reading that property, as in algorithm 256:

Algorithm 256 Creating the error 'formed reference to void'

```
#include "create_k2_graph.h"
#include "get_vertex_names.h"

void formed_reference_to_void() noexcept
{
    get_vertex_names(create_k2_graph());
}
```

In algorithm 256 a graph is created with vertices of no properties. Then the names of these vertices, which do not exist, are tried to be read. If you want to read the names of the vertices, supply a graph that has this property.

24.2 No matching function for call to 'clear_out_edges'

This compile-time error occurs when you want to clear the outward edges from a vertex in an undirected graph.

Algorithm 257 Creating the error 'no matching function for call to clear_out_edges'

```
#include "create_k2_graph.h"

void no_matching_function_for_call_to_clear_out_edges()
    noexcept
{
    auto g = create_k2_graph();
    const auto vd = *vertices(g).first; //not boost::
        vertices
    boost::clear_in_edges(vd,g);
}
```

In algorithm 257 an undirected graph is created, a vertex descriptor is obtained, then its out edges are tried to be cleared. Either use a directed graph (which has out edges), or use the 'boost::clear_vertex' function instead.

24.3 No matching function for call to 'clear_in_edges'

See chapter 24.2.

24.4 Undefined reference to boost::detail::graph::read_graphviz_new

You will have to link against the Boost.Graph and Boost.Regex libraries. In Qt Creator, this is achieved by adding these lines to your Qt Creator project file:

```
LIBS += -lboost_graph -lboost_regex
```

24.5 Property not found: node_id

When loading a graph from file (as in chapter 3.4) you will be using `boost::read_graphviz`. `boost::read_graphviz` needs a third argument, of type `boost::dynamic_properties`. When a graph does not have properties, do not use a default constructed version, but initialize with `'boost::ignore_other_properties'` as a constructor argument instead. Algorithm 258 shows how to trigger this run-time error.

Algorithm 258 Creating the error 'Property not found: node_id'

```
#include <cassert>
#include <fstream>
#include "is_regular_file.h"
#include "create_empty_undirected_graph.h"
#include "create_k2_graph.h"
#include "save_graph_to_dot.h"

void property_not_found_node_id() noexcept
{
    const std::string dot_filename{"
        property_not_found_node_id.dot"};
    // Create a file
    {
        const auto g = create_k2_graph();
        save_graph_to_dot(g, dot_filename);
        assert(is_regular_file(dot_filename));
    }

    // Try to read that file
    std::ifstream f(dot_filename.c_str());
    auto g = create_empty_undirected_graph();

    // Line below should have been
    // boost::dynamic_properties p(boost::
    ignore_other_properties);
    boost::dynamic_properties p; // Error

    try {
        boost::read_graphviz(f,g,p);
    }
    catch (std::exception&) {
        return; // Should get here
    }
    assert(!"Should_not_get_here");
}
```

25 Appendix

25.1 List of all edge, graph and vertex properties

The following list is obtained from the file 'boost/graph/properties.hpp'.

Edge	Graph	Vertex
edge_all	graph_all	vertex_all
edge_bundle	graph_bundle	vertex_bundle
edge_capacity	graph_name	vertex_centrality
edge_centrality	graph_visitor	vertex_color
edge_color		vertex_current_degree
edge_discover_time		vertex_degree
edge_finished		vertex_discover_time
edge_flow		vertex_distance
edge_global		vertex_distance2
edge_index		vertex_finish_time
edge_local		vertex_global
edge_local_index		vertex_in_degree
edge_name		vertex_index
edge_owner		vertex_index1
edge_residual_capacity		vertex_index2
edge_reverse		vertex_local
edge_underlying		vertex_local_index
edge_update		vertex_lowpoint
edge_weight		vertex_name
edge_weight2		vertex_out_degree
		vertex_owner
		vertex_potential
		vertex_predecessor
		vertex_priority
		vertex_rank
		vertex_root
		vertex_underlying
		vertex_update

25.2 Graphviz attributes

List created from www.graphviz.org/content/attrs, where only the attributes that are supported by all formats are listed:

Edge	Graph	Vertex
arrowhead	_background	color
arrowsize	bgcolor	colorscheme
arrowtail	center	comment
color	charset	distortion
colorscheme	color	fillcolor
comment	colorscheme	fixedsize
decorate	comment	fontcolor
dir	concentrate	fontname
fillcolor	fillcolor	fontsize
fontcolor	fontcolor	gradientangle
fontname	fontname	height
fontsize	fontpath	image
gradientangle	fontsize	imagescale
headclip	forcelabels	label
headlabel	gradientangle	labelloc
headport	imagepath	layer
label	label	margin
labelangle	labeljust	nojustify
labeldistance	labelloc	orientation
labelfloat	landscape	penwidth
labelfontcolor	layerlistsep	peripheries
labelfontname	layers	pos
labelfontsize	layerselect	regular
layer	layersep	samplepoints
nojustify	layout	shape
penwidth	margin	shapefile
pos	nodesep	sides
style	nojustify	skew
tailclip	orientation	sortv
taillabel	outputorder	style
tailport	pack	width
weight	packmode	xlabel
xlabel	pad	z
	page	
	pagedir	
	penwidth	
	quantum	
	ratio	
	rotate	
	size	
	sortv	
	splines	
	style	
	viewport	

References

- [1] Eckel Bruce. Thinking in c++, volume 1. 2002.
- [2] Marshall P Cline, Greg Lomow, and Mike Girou. *C++ FAQs*. Pearson Education, 1998.
- [3] Jarrod Hollingworth, Bob Swart, and Jamie Allsop. *C++ Builder 5 Developer's Guide with Cdrom*. Sams, 2000.
- [4] John Lakos. *Large-scale C++ software design*, volume 10. Addison-Wesley Reading, 1996.
- [5] Jesse Liberty. *Sams teach yourself C++ in 24 hours*. Sams Publishing, 2001.
- [6] Steve McConnell. *Code complete*. Pearson Education, 2004.
- [7] Scott Meyers. *Effective C++: 55 specific ways to improve your programs and designs*. Pearson Education, 2005.
- [8] Jeremy G Siek, Lie-Quan Lee, and Andrew Lumsdaine. *Boost Graph Library: User Guide and Reference Manual, The*. Pearson Education, 2001.
- [9] Bjarne Stroustrup. *The C++ Programming Language (3rd edition)*. 1997.
- [10] Bjarne Stroustrup. *The C++ Programming Language (4th edition)*. 2013.
- [11] Herb Sutter and Andrei Alexandrescu. *C++ coding standards: 101 rules, guidelines, and best practices*. Pearson Education, 2004.

Index

- #include, 15
- K_2 with named vertices, create, 53
- K_2 , create, 33
- K_3 with named edges and vertices, create, 91
- 'demo' function, 8
- 'do' function, 8
- [[:SPACE:]], 178, 179

- Add a vertex, 20
- Add an edge, 25
- Add bundled edge, 143
- Add bundled vertex, 115
- Add custom and selectable vertex, 202
- Add custom edge, 227
- Add custom vertex, 173
- Add named edge, 83, 84
- Add named vertex, 47
- Add vertex, 21
- add_edge, 26
- aer_, 27
- All edge properties, 273
- All graph properties, 273
- All vertex properties, 273
- assert, 18, 26
- auto, 16

- boost::add_edge, 25, 26, 31, 34, 84
- boost::add_edge result, 27
- boost::add_vertex, 21, 31, 34
- boost::adjacency_list, 16, 45, 81, 83, 170
- boost::adjacency_matrix, 16
- boost::clear_in_edges, 67
- boost::clear_out_edges, 66
- boost::clear_vertex, 66
- boost::degree does not exist, 36
- boost::directedS, 17, 45, 80, 113, 170, 253
- boost::dynamic_properties, 40, 75, 107, 134, 162, 193, 216, 247, 272
- boost::edge_bundled_type_t, 139
- boost::edge_custom_type, 227
- boost::edge_custom_type_t, 223
- boost::edge_name_t, 80–83
- boost::edges does not exist, 27–29
- boost::get does not exist, 9, 48, 66
- boost::graph_name, 253
- boost::graph_name_t, 253
- boost::ignore_other_properties, 40, 272
- boost::in_degree does not exist, 36
- boost::make_label_writer, 72
- boost::no_property, 253
- boost::num_edges, 19, 20
- boost::num_vertices, 18
- boost::out_degree does not exist, 36, 37
- boost::property, 45, 80–83, 139, 170, 223, 253
- boost::put does not exist, 66
- boost::read_graphviz, 40, 75, 107, 134, 162, 193, 247, 272
- boost::remove_edge, 69, 103
- boost::remove_vertex, 68
- boost::undirectedS, 17, 46, 82, 114, 141, 172, 200, 225, 254
- boost::vecS, 17, 45, 80, 82, 113, 170, 253
- boost::vertex_custom_type, 174
- boost::vertex_custom_type_t, 170
- boost::vertex_name, 48
- boost::vertex_name_t, 45, 80, 82
- boost::vertices does not exist, 22, 24, 29
- boost::write_graphviz, 39, 72
- BOOST_INSTALL_PROPERTY, 169, 197, 222
- bundled_vertices_writer, 132

- Clear first vertex with name, 67
- const, 16
- const-correctness, 16
- Convert dot to svg, 270
- Counting the number of edges, 19
- Counting the number of vertices, 18
- Create K_2 , 33

Create K_2 graph, 34	Create directed graph with named vertices from .dot, 74
Create K_2 with named vertices, 53	
Create K_3 with named edges and vertices, 91	Create empty directed bundled edges and vertices graph, 139
Create .dot from graph, 38	Create empty directed bundled vertices graph, 113
Create .dot from graph with bundled edges and vertices, 159	Create empty directed custom and selectable vertices graph, 198
Create .dot from graph with custom edges and vertices, 244	Create empty directed custom edges and vertices graph, 223
Create .dot from graph with named edges and vertices, 105	Create empty directed custom vertices graph, 170
Create .dot from graph with named vertices, 71	Create empty directed graph, 15
Create an empty directed graph, 15	Create empty directed graph with graph name, 252
Create an empty directed graph with named edges and vertices, 79	Create empty directed named edges and vertices graph, 80
Create an empty directed graph with named vertices, 44	Create empty directed named vertices graph, 44
Create an empty graph, 17	
Create an empty graph with named edges and vertices, 81	Create empty undirected bundled edges and vertices graph, 141
Create an empty undirected graph with named vertices, 45	Create empty undirected bundled vertices graph, 114
Create bundled edges and vertices K_3 graph, 150	Create empty undirected custom and selectable vertices graph, 200
Create bundled edges and vertices Markov chain, 147	Create empty undirected custom edges and vertices graph, 225
Create bundled vertices K_2 graph, 121	Create empty undirected custom vertices graph, 172
Create bundled vertices Markov chain, 118	Create empty undirected graph, 17
Create custom and selectable vertices K_2 graph, 210	Create empty undirected graph with graph name, 254
Create custom and selectable vertices Markov chain, 205	Create empty undirected named edges and vertices graph, 82
Create custom edges and vertices K_3 graph, 234	Create empty undirected named vertices graph, 46
Create custom edges and vertices Markov chain, 231	Create K_2 graph with graph name, 261
Create custom vertices K_2 graph, 180	Create Markov chain, 31
Create custom vertices Markov chain, 177	Create Markov chain with graph name, 258
Create directed graph, 30	Create Markov chain with named edges and vertices, 87
Create directed graph from .dot, 39	Create Markov chain with named vertices, 50
Create directed graph with named edges and vertices from .dot, 106	Create named edges and vertices K_3 graph, 93

Create named edges and vertices Markov chain, 89	Find first bundled edge with my_bundled_edge, 154
Create named vertices K2 graph, 54	Find first bundled vertex with my_vertex, 125
Create named vertices Markov chain, 51	Find first custom edge with my_custom_edge, 239
Create undirected graph from .dot, 41	Find first custom vertex with my_vertex, 185
Create undirected graph with bundled edges and vertices from .dot, 164	Find first edge by name, 99
Create undirected graph with custom edges and vertices from .dot, 249	Find first vertex with name, 59
Create undirected graph with named vertices from .dot, 76	Formed reference to void, 271
custom_and_selectable_vertices_writer, 215	get, 9, 48, 66, 174, 227
	Get bundled edge my_bundled_edge, 156
	Get bundled vertex my_bundled_vertex, 126
Declaration, my_bundled_edge, 138	Get bundled vertex my_vertexes, 116
Declaration, my_bundled_vertex, 112	Get custom edge my_custom_edge, 241
Declaration, my_custom_edge, 221	Get custom vertex my_custom_vertex objects, 176
Declaration, my_custom_vertex, 168	Get custom vertex my_vertex, 187
decltype(auto), 9	Get edge descriptors, 29
directed graph, 11	Get edge iterators, 28
Directed graph, create, 30	Get edge my_bundled_edges, 145
	Get edge my_custom_edges, 229
ed_, 29	Get edge name, 100
Edge descriptor, 28	Get first vertex with name out degree, 61
Edge descriptors, get, 29	Get graph name, 255
Edge iterator, 27	Get n edges, 20
Edge iterator pair, 27	Get n vertices, 18
Edge properties, 273	Get type name, 269
Edge, add, 25	Get vertex descriptors, 24
edges, 27, 29	Get vertex my_vertexes, 175
Edges, counting, 19	Get vertex name, 63
eip_, 27	Get vertex names, 49
Empty directed graph with named edges and vertices, create, 79	Get vertex out degrees, 37
Empty directed graph with named vertices, create, 44	Get vertices, 22
Empty directed graph, create, 15	get_edge_names, 86
Empty graph with named edges and vertices, create, 81	Graph properties, 273
Empty graph, create, 17	Graphviz, 38
Empty undirected graph with named vertices, create, 45	graphviz decode, 268
	graphviz encode, 267

Has bundled edge with my_bundled_edge, 152	Load undirected graph from .dot, 42
Has bundled vertex with my_vertex, 123	Load undirected graph with bundled edges and vertices from .dot, 164
Has custom edge with my_custom_edge, 237	Load undirected graph with custom edges and vertices from .dot, 249
Has custom vertex with my_vertex, 183	Load undirected graph with named vertices from .dot, 76
Has edge with name, 97	Load undirected named edges and vertices graph from dot, 109
Has vertex with name, 57	Load undirected named vertices graph from dot, 77
header file, 15	
idegree, 36	
in_degree, 36	
Install edge custom type, 222	m_, 112, 139, 168, 221
Install vertex custom type, 169	macro, 169, 197, 222
Install vertex_is_selected, 197	make_bundled_vertices_writer, 131
Is regular file, 270	make_custom_and_selectable_vertices_writer, 214
link, 272	Markov chain with named edges and vertices, create, 87
Load directed bundled edges and vertices graph from dot, 161	Markov chain with named vertices, create, 50
Load directed bundled vertices graph from dot, 134	member, 112, 139, 168, 221
Load directed custom edges and vertices graph from dot, 247, 264	my_bundled_edge, 138
Load directed custom vertices graph from dot, 193, 216	my_bundled_edge declaration, 138
Load directed graph from .dot, 39	my_bundled_edge.h, 138
Load directed graph from dot, 40	my_bundled_vertex, 112, 113
Load directed graph with named edges and vertices from .dot, 106	my_bundled_vertex.h, 112
Load directed graph with named vertices from .dot, 74	my_custom_edge, 221
Load directed named edges and vertices graph from dot, 107	my_custom_edge declaration, 221
Load directed named vertices graph from dot, 75	my_custom_edge.h, 221
Load undirected bundled edges and vertices graph from dot, 165	my_custom_vertex, 168
Load undirected bundled vertices graph from dot, 136	my_custom_vertex declaration, 168
Load undirected custom edges and vertices graph from dot, 250, 266	my_custom_vertex.h, 168
Load undirected custom vertices graph from dot, 195, 218	my_edge, 139, 223
Load undirected graph from .dot, 41	my_vertex, 170
	my_vertex declaration, 112
	Named edge, add, 83
	Named edges and vertices, create empty directed graph, 79
	Named edges and vertices, create empty graph, 81
	Named vertex, add, 47
	Named vertices, create empty directed graph, 44

Named vertices, create empty undirected graph, 45	Set bundled edge my_bundled_edge, 158
No matching function for call to clear_out_degree, 271	Set bundled vertex my_bundled_vertexes, 129
node_id, 272	Set custom edge my_custom_edge, 243
noexcept, 16	Set custom vertex my_vertexes, 191
noexcept specification, 16	Set edge name, 102
	Set graph name, 256
out_degree, 36, 37	Set vertex my_vertex, 127, 189
Property not found: node_id, 272, 273	Set vertex name, 64
Property not found, 272	Set vertex names, 66
put, 66	Set vertices names, 65
	static_assert, 21, 48
read_graphviz_new, 272	static_cast, 18
read_graphviz_new, undefined reference, 272	std::cout, 39
	std::ifstream, 40
Remove edge between vertices with names, 70	std::list, 16
	std::ofstream, 39
Remove first edge with name, 104	std::pair, 26
Remove first vertex with name, 68	std::vector, 16
	STL, 16
S, 17, 253	
Save bundled edges and vertices graph to dot, 160	Undefined reference to read_graphviz_new, 272
Save bundled vertices graph to dot, 130	undirected graph, 11
Save custom edges and vertices graph to dot, 245	unsigned long, 18
Save custom vertices graph to dot, 192, 213	vd, 26
	vd_, 22
Save graph as .dot, 38	Vertex descriptor, 22, 25
Save graph to dot, 39	Vertex descriptors, get, 23
Save graph with bundled edges and vertices as .dot, 159	Vertex iterator, 22
	Vertex iterator pair, 22
Save graph with custom edges and vertices as .dot, 244	Vertex properties, 273
	Vertex, add, 20
Save graph with graph name to dot, 263	Vertex, add named, 47
	vertex_custom_type, 167
Save graph with name edges and vertices as .dot, 105	vertex_is_selected, 197
	vertex_is_selected_t, 197
Save graph with named vertices as .dot, 71	vertices, 22, 24
	Vertices, counting, 18
Save named edges and vertices graph to dot, 105	Vertices, set names, 65
	vip_, 22
Save named vertices graph to dot, 72	
Save named vertices graph to dot using lambda function, 73	