

# Boost.Graph tutorial

Richel Bilderbeek

December 6, 2015

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Coding style used . . . . .	2
1.2	Pitfalls . . . . .	2
<b>2</b>	<b>Building graphs</b>	<b>3</b>
2.1	Creating an empty graph . . . . .	3
2.2	Add a vertex . . . . .	3
2.3	Add an edge . . . . .	4
2.4	Creating $K_2$ , a fully connected graph with two vertices . . . . .	5
2.5	Creating an empty graph with named vertices . . . . .	7
2.6	Add a vertex with a name . . . . .	8
2.7	Creating $K_2$ with named vertices . . . . .	8
2.8	Creating an empty graph with named edges and vertices . . . . .	11
2.9	Add an edge with a name . . . . .	12
2.10	Creating $K_3$ with named edges and vertices . . . . .	13
2.11	Create an empty graph with custom vertices . . . . .	16
2.11.1	Creating the custom vertex class . . . . .	16
2.11.2	Installing the new property . . . . .	17
2.11.3	Create the empty graph with custom vertices . . . . .	18
2.12	Add a custom vertex . . . . .	19
2.13	Creating $K_2$ with custom vertices . . . . .	20
2.14	Create an empty graph with custom edges and vertices . . . . .	22
2.15	Add a custom edge . . . . .	22
2.16	Creating $K_2$ with custom edges and vertices . . . . .	22
<b>3</b>	<b>Measuring simple graphs traits</b>	<b>22</b>
3.1	Getting the vertices . . . . .	22
3.2	Getting the edges . . . . .	22
3.3	Counting the number of vertices . . . . .	22
3.4	Counting the number of edges . . . . .	23
3.5	Getting the vertices' names . . . . .	23
3.6	Getting the edges' names . . . . .	24
3.7	Find a vertex by its name . . . . .	26

3.8	Replace a vertex its name . . . . .	26
<b>4</b>	<b>Modifying simple graphs traits</b>	<b>26</b>
4.1	Setting all vertices' names . . . . .	26
<b>5</b>	<b>Visualizing graphs</b>	<b>27</b>
5.1	Storing a graph as a .dot . . . . .	27
5.2	Storing a graph with named vertices as a .dot . . . . .	28
5.3	Storing a graph with named vertices and edges as a .dot . . . . .	30
<b>6</b>	<b>TODO's in general</b>	<b>33</b>
6.1	Personal experciences with Boost.Graph . . . . .	33
6.2	To add . . . . .	33
<b>7</b>	<b>Graph of this tutorial</b>	<b>34</b>

# 1 Introduction

I needed this tutorial in 2006, when I started experimenting with Boost.Graph. More specifically, I needed a tutorial that:

- Orders concepts chronologically
- Increases complexity gradually
- Shows complete pieces of code

What I had were the book [1] and the Boost.Graph website, both did not satisfy these requirements.

## 1.1 Coding style used

I use the coding style from the Core C++ Guidelines.

I prefer not to use the keyword `auto`, but to explicitly mention the type instead. I think this is beneficial to beginners. When using Boost.Graph in production code, I do prefer to use `auto`.

OTOH, while writing this tutorial, I use `auto` when I loose too much time figuring out the type

All coding snippets are taken from compiled C++ code.

## 1.2 Pitfalls

The choice between `'boost::get'`, `'std::get'` and `'get'`. AFAIKS, when in doubt, use `'get'`.

## 2 Building graphs

Boost.Graph is about creating graphs. In this chapter we create graphs, starting from simple to more complex.

### 2.1 Creating an empty graph

Let's create a trivial empty graph:

---

**Algorithm 1** Creating an empty graph

---

```
#include "create_empty_graph.h"

boost::adjacency_list<>
create_empty_graph() noexcept
{
    return boost::adjacency_list<>();
}
```

---

Congratulations, you've just created a `boost::adjacency_list` in which:

- The out edges are stored in a `std::vector`
- The vertices are stored in a `std::vector`
- The graph is directed
- Vertices, edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` is the most commonly used graph type, the other is the `boost::adjacency_matrix`.

### 2.2 Add a vertex

To add a vertex to a graph, the `boost::add_vertex` function is used as such:

---

**Algorithm 2** Adding a vertex to a graph

---

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_vertex(graph& g)
{
    boost::add_vertex(g);
}
```

---

Note that `boost::add_vertex` returns a vertex descriptor, which is ignored for now. A vertex descriptor can be used to, for example, connect two vertices by an edge

## 2.3 Add an edge

To add an edge to a graph, two vertex descriptors are needed. A vertex descriptor is a handle to the vertex within graph. Algorithm 3 adds two vertices to a graph, and connects these two using `boost::add_edge`:

---

**Algorithm 3** Adding (two vertices and) an edge to a graph

---

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_edge(graph& g)
{
    using boost::graph_traits;
    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;

    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);

    assert(ea.second);
}
```

---

Note that half of the code consists out of using statements. This algorithm only shows how to add an isolated edge to a graph, instead of allowing for graphs with higher connectivities. The function `boost::add_edge` returns a `std::pair`, consisting of an edge descriptor and a boolean success indicator. In algorithm 3 we assert that this insertion was successful. Insertion can fail if an edge is already present and duplicates are not allowed.

## 2.4 Creating $K_2$ , a fully connected graph with two vertices

To create a fully connected graph with two vertices (also called  $K_2$ ), one needs two vertices and one (undirected) edge, as depicted in figure 1.



Figure 1:  $K_2$ : a fully connected graph with two vertices named  $a$  and  $b$

To create  $K_2$ , the following code can be used:

---

**Algorithm 4** Creating  $K_2$  as depicted in figure 1

---

```
#include "create_k2_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS
>
create_k2_graph() noexcept
{
    using boost::graph_traits;

    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS
    >;

    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);
    return g;
}
```

---

Note that this code has more lines of using statements than actual code! In this code, the third template argument of `boost::adjacency_list` is `boost::undirectedS`, to select (that is what the S means) for an undirected graph. Adding a vertex with `boost::add_vertex` results in a vertex descriptor, which is a handle to the vertex added to the graph. Two vertex descriptors are then used to add an edge to the graph. Adding an edge using `boost::add_edge` returns two things: an edge descriptor and a boolean indicating success. In the code example, we assume insertion is successful.

Note that the graph lacks all properties: nodes do not have names, nor do edges.

## 2.5 Creating an empty graph with named vertices

Let's create a trivial empty graph, in which the vertices can have a name:

---

**Algorithm 5** Creating an empty graph with named vertices

---

```
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_name_t, std::string
    >
>
>
create_empty_named_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    >
    >;

    graph g;
    return g;
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- Edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property< boost::vertex_name_t, std::string>`'. This can be read as: "vertices have the

property 'boost::vertex\_name\_t', that is of data type 'std::string'. Or simply: "vertices have a name that is stored as a std::string".

## 2.6 Add a vertex with a name

Adding a vertex without a name was trivially easy (see chapter 2). Adding a vertex with a name is less easy:

---

**Algorithm 6** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>

template <typename graph>
void add_named_vertex(graph& g, const std::string& name)
{
    using boost::graph_traits;
    using boost::property_map;
    using boost::vertex_name_t;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using name_map_t
        = typename property_map<graph, vertex_name_t>::type;

    const vertex_descriptor vd{
        boost::add_vertex(g)
    };

    name_map_t name_map{boost::get(boost::vertex_name, g)};
    name_map[vd] = name;
}
```

---

Instead of calling 'boost::add\_vertex' with an additional argument containing the name of the vertex, multiple things need to be done. When adding a new vertex to the graph, the vertex descriptor is stored. After obtaining the name map from the graph (using 'boost::get(boost::vertex\_name,g)'), the name of the vertex is set using that vertex descriptor.

## 2.7 Creating $K_2$ with named vertices

We extend  $K_2$  of chapter 2.4 by naming the vertices 'from' and 'to', as depicted in figure 2:






Figure 2:  $K_2$ : a fully connected graph with two vertices with the text 'from' and 'to'

To create  $K_2$ , the following code can be used:

---

**Algorithm 7** Creating  $K_2$  as depicted in figure 2

---

```
#include "create_named_vertices_k2_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>
>
create_named_vertices_k2_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using name_map_t
        = boost::property_map<graph, boost::vertex_name_t>::
            type;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);

    //Add names
    name_map_t name_map{boost::get(boost::vertex_name, g)};
    name_map[va] = "from";
    name_map[vb] = "to";

    return g;
}
```

---

Most of the code is a repeat of algorithm 4. In the end, the names are obtained as a `boost::property_map` and set.

## 2.8 Creating an empty graph with named edges and vertices

Let's create a trivial empty graph, in which the both the edges and vertices can have a name:

---

**Algorithm 8** Creating an empty graph with named edges and vertices

---

```
#include <string>
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_empty_named_edges_and_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    >;

    graph g;
    return g;
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)

- The vertices have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::vertex_name_t, std::string>`)
- The edges have one property: they have a name, that is of data type `std::string` (due to the `boost::property< boost::edge_name_t, std::string>`)
- The graph has no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fifth template argument '`boost::property< boost::edge_name_t, std::string>`'. This can be read as: “edges have the property '`boost::edge_name_t`', that is of data type '`std::string`'”. Or simply: “edges have a name that is stored as a `std::string`”.

## 2.9 Add an edge with a name

Adding an edge with a name:

---

**Algorithm 9** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>

#include <cassert>

template <typename graph>
void add_named_edge(graph& g, const std::string&
    edge_name)
{
    using boost::edge_name_t;
    using boost::graph_traits;
    using boost::property_map;
    using vertex_descriptor
        = typename graph_traits<graph>::vertex_descriptor;
    using edge_descriptor
        = typename graph_traits<graph>::edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using name_map_t
        = typename property_map<graph, edge_name_t>::type;

    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);

    assert(ea.second);

    name_map_t name_map{
        boost::get(boost::edge_name, g)
    };
    name_map[ea.first] = edge_name;
}
```

---

In this code snippet, the edge descriptor when using 'boost::add\_edge' is used as a key to change the edge name map.

## 2.10 Creating $K_3$ with named edges and vertices

We extend the graph  $K_2$  with named vertices of chapter 2.7 by adding names to the edges, as depicted in figure 3:




Figure 3:  $K_3$ : a fully connected graph with three named edges and vertices

To create  $K_3$ , the following code can be used:

---

**Algorithm 10** Creating  $K_3$  as depicted in figure 3

---

```
#include "create_named_edges_and_vertices_k3_graph.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<boost::vertex_name_t, std::string>,
    boost::property<boost::edge_name_t, std::string>
>
create_named_edges_and_vertices_k3_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_name_t, std::string
        >,
        boost::property<
            boost::edge_name_t, std::string
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using vertex_name_map_t
        = boost::property_map<graph, boost::vertex_name_t>::
            type;
    using edge_name_map_t
        = boost::property_map<graph, boost::edge_name_t>::type
        ;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const vertex_descriptor vc = boost::add_vertex(g);
    const edge_insertion_result eab
        = boost::add_edge(va, vb, g);
    assert(eab.second);
    const edge_insertion_result ebc
        = boost::add_edge(vb, vc, g);
    assert(ebc.second);
    const edge_insertion_result eca
        = boost::add_edge(vc, va, g);
    assert(eca.second);

    //Add vertex names
    vertex_name_map_t vertex_name_map{boost::get(boost::
        vertex_name, g)};
```

Most of the code is a repeat of algorithm 7. In the end, the edge names are obtained as a `boost::property_map` and set.

## 2.11 Create an empty graph with custom vertices

Say we want to use our own vertex class as graph nodes. This is done in multiple steps:

1. Create a custom vertex class, called 'my\_vertex'
2. Install a new property, called 'vertex\_custom\_type'
3. Use the new property in creating a `boost::adjacency_list`

### 2.11.1 Creating the custom vertex class

In this example, I create a custom vertex class. Here I will show the header file of it, as the implementation of it is not important yet.

---

**Algorithm 11** Declaration of `my_vertex`

---

```
#ifndef MY_VERTEX_H
#define MY_VERTEX_H

#include <string>

class my_vertex
{
public:
    my_vertex(
        const std::string& name = "",
        const std::string& description = "",
        const double x = 0.0,
        const double y = 0.0
    );
    std::string m_name;
    std::string m_description;
    double m_x;
    double m_y;
};

#endif // MY_VERTEX_H
```

---

`my_vertex` is a class that has multiple properties: two doubles 'm\_x' ('m\_' stands for member) and 'm\_y', and two `std::string`s `m_name` and `m_description`. `my_vertex` is copyable, but cannot trivially be converted to a `std::string`.



### 2.11.2 Installing the new property

Installing a new property would have been easier, if 'more C++ compilers were standards conformant' ([1], chapter 3.6, footnote at page 52). Boost.Graph uses the BOOST\_INSTALL\_PROPERTY macro to allow using a custom property:

---

**Algorithm 12** Installing the vertex\_custom\_type property

---

```
#include <boost/graph/properties.hpp>

namespace boost {
    enum vertex_custom_type_t { vertex_custom_type = 314 };
    BOOST_INSTALL_PROPERTY(vertex, custom_type);
}
```

---

The enum value 314 must be unique.

### 2.11.3 Create the empty graph with custom vertices

---

**Algorithm 13** Creating an empty graph with custom vertices

---

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_vertex.h"

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_vertex
    >
>
>
create_empty_custom_vertices_graph() noexcept
{
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_custom_type_t, my_vertex
        >
    >;

    graph g;
    return g;
}
```

---

This graph:

- has its out edges stored in a `std::vector` (due to the first `boost::vecS`)
- has its vertices stored in a `std::vector` (due to the second `boost::vecS`)
- is undirected (due to the `boost::undirectedS`)
- The vertices have one property: they have a custom type, that is of data type `my_vertex` (due to the `boost::property< boost::vertex_custom_type_t, my_vertex>`)
- The edges and graph have no properties
- Edges are stored in a `std::list`

The `boost::adjacency_list` has a new, fourth template argument '`boost::property<boost::vertex_custom_type_t, my_vertex>`'. This can be read as: "vertices have the property '`boost::vertex_custom_type_t`', which is of data type '`my_vertex`'". Or simply: "vertices have a custom type called `my_vertex`".

## 2.12 Add a custom vertex

Adding a custom vertex is very similar to adding a named vertex (chapter 6).

---

**Algorithm 14** Add a vertex with a name

---

```
#include <boost/graph/adjacency_list.hpp>
#include "install_vertex_custom_type.h"
#include "my_vertex.h"

template <typename graph>
void add_custom_vertex(graph& g, const my_vertex& v)
{
    using boost::graph_traits;
    using boost::property_map;
    using boost::vertex_name_t;
    using boost::vertex_custom_type_t;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using my_vertex_map_t
        = typename property_map<graph, vertex_custom_type_t>::
            type;

    const vertex_descriptor vd{
        boost::add_vertex(g)
    };

    my_vertex_map_t name_map{boost::get(boost::
        vertex_custom_type, g)};
    name_map[vd] = v;
}
```

---

When having added a new (abstract) vertex to the graph, the vertex descriptor is used to set the `my_vertex` in the graph its `my_vertex` map (using '`boost::get(boost::vertex_custom_type, g)`').

### 2.13 Creating $K_2$ with custom vertices

We reproduce the  $K_2$  with named vertices of chapter 2.7 , but with our custom vertices instead:

---

**Algorithm 15** Creating  $K_2$  as depicted in figure 2

---

```
#include "install_vertex_custom_type.h"
#include "my_vertex.h"
#include <boost/graph/adjacency_list.hpp>

boost::adjacency_list<
    boost::vecS,
    boost::vecS,
    boost::undirectedS,
    boost::property<
        boost::vertex_custom_type_t, my_vertex
    >
>
>
create_custom_vertices_k2_graph() noexcept
{
    using boost::property_map;
    using boost::vertex_custom_type_t;
    using graph = boost::adjacency_list<
        boost::vecS,
        boost::vecS,
        boost::undirectedS,
        boost::property<
            boost::vertex_custom_type_t, my_vertex
        >
    >;
    using vertex_descriptor
        = typename boost::graph_traits<graph>::
            vertex_descriptor;
    using edge_descriptor
        = typename boost::graph_traits<graph>::
            edge_descriptor;
    using edge_insertion_result
        = std::pair<edge_descriptor, bool>;
    using my_vertex_map_t
        = typename property_map<graph, vertex_custom_type_t>::
            type;

    graph g;
    const vertex_descriptor va = boost::add_vertex(g);
    const vertex_descriptor vb = boost::add_vertex(g);
    const edge_insertion_result ea
        = boost::add_edge(va, vb, g);
    assert(ea.second);

    //Add names
    my_vertex_map_t name_map{boost::get(boost::
        vertex_custom_type, g)};
    name_map[va] = my_vertex("from");
    name_map[vb] = my_vertex("to");

    return g;
}
```

---

Most of the code is a slight modification of algorithm 7. In the end, the `my_vertices` are obtained as a `boost::property_map` and set with two custom `my_vertex` objects.

## 2.14 Create an empty graph with custom edges and vertices

## 2.15 Add a custom edge

## 2.16 Creating $K_2$ with custom edges and vertices

Instead of using edges with a name, or other properties, here we use a custom edge class called `'my_edge'`.

# 3 Measuring simple graphs traits

Measuring simple traits of the graphs created allows you to debug your code.

## 3.1 Getting the vertices

You can use `boost::vertices` to obtain an iterator pair. The first iterator points to the first vertex, the second points to beyond the last vertex.

## 3.2 Getting the edges

You can use `boost::edges` to obtain an iterator pair. The first iterator points to the first edge, the second points to beyond the last edge.

## 3.3 Counting the number of vertices

Use `boost::num_vertices`, as shown here:

---

**Algorithm 16** Count the numbe of vertices

---

```
#include <boost/graph/adjacency_list.hpp>

///Get the number of vertices a graph has
template <class graph>
int get_n_vertices(const graph& g)
{
    return static_cast<int>(boost::num_vertices(g));
}
```

---

### 3.4 Counting the number of edges

Use `boost::num_edges`, as shown here:

---

**Algorithm 17** Count the number of edges

---

```
#include <boost/graph/adjacency_list.hpp>

///Get the number of edges a graph has
template <class graph>
int get_n_edges(const graph& g)
{
    return static_cast<int>(boost::num_edges(g));
}
```

---

### 3.5 Getting the vertices' names

When the vertices of a graph have named vertices, one can extract them as such:

---

**Algorithm 18** Get the vertices' names

---

```
#include <string>
#include <vector>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_vertex_names(const graph& g)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    std::vector<std::string> v;

    //TODO: remove auto
    const auto name_map = get(boost::vertex_name, g);

    for (vertex_iterators p = vertices(g);
         p.first != p.second;
         ++p.first)
    {
        v.emplace_back(get(name_map, *p.first));
    }
    return v;
}
```

---

The names of the vertices are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the vertices' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

### 3.6 Getting the edges' names

When the edges of a graph have named vertices, one can extract them as such:



---

**Algorithm 19** Get the edges' names

---

```
#include <string>
#include <vector>
#include <boost/graph/adjacency_list.hpp>
#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize to return any type
template <typename graph>
std::vector<std::string> get_edge_names(const graph& g)
{
    using boost::graph_traits;
    using edge_iterator
        = typename graph_traits<graph>::edge_iterator;
    using edge_iterators
        = std::pair<edge_iterator, edge_iterator>;

    std::vector<std::string> v;

    //TODO: remove auto
    const auto name_map = get(boost::edge_name, g);

    for (edge_iterators p = boost::edges(g);
         p.first != p.second;
         ++p.first)
    {
        v.emplace_back(get(name_map, *p.first));
    }
    return v;
}
```

---

The names of the edges are obtained from a `boost::property_map` and then put into a `std::vector`.

When trying to get the edges' names from a graph without vertices with names, you will get the error 'formed reference to void' (for example, with the code `'get_vertex_names(create_k2_graph());'`).

### 3.7 Find a vertex by its name

### 3.8 Replace a vertex its name

## 4 Modifying simple graphs traits

It is useful to be able to modify every aspect of a graph. Adding nodes and edges are found in earlier chapters.

### 4.1 Setting all vertices' names

When the vertices of a graph have named vertices, one set their names as such:

---

**Algorithm 20** Setting the vertices' names

---

```
#include <string>
#include <vector>

#include <boost/graph/graph_traits.hpp>
#include <boost/graph/properties.hpp>

//TODO: generalize 'names'
template <typename graph>
void set_vertex_names(
    graph& g,
    const std::vector<std::string>& names
)
{
    using vertex_iterator
        = typename boost::graph_traits<graph>::
            vertex_iterator;
    using vertex_iterators
        = std::pair<vertex_iterator, vertex_iterator>;

    const auto name_map = get(boost::vertex_name, g);

    auto names_begin = std::begin(names);
    const auto names_end = std::end(names);
    for (vertex_iterators vi = vertices(g);
        vi.first != vi.second;
        ++vi.first, ++names_begin)
    {
        assert(names_begin != names_end);
        put(name_map, *vi.first, *names_begin);
    }
}
```

---

An impressive feature is that getting the property map holding the graph its names is not a copy, but a reference. Otherwise, modifying 'name\_map' (obtained by non-reference) would only modify a copy.

## 5 Visualizing graphs

Before graphs are visualized, they are stored as a file first. Here, I use the .dot file format.

### 5.1 Storing a graph as a .dot

Graph are easily saved to a .dot file:

---

**Algorithm 21** Storing a graph as a .dot file

---

```
#include <fstream>
#include <boost/graph/graphviz.hpp>

///Save a graph to a .dot file
template <typename graph>
void save_graph_to_dot(const graph& g, const std::string&
    filename)
{
    std::ofstream f(filename);
    boost::write_graphviz(f,g);
}
```

---

Using the create\_k2\_graph function (algorithm 4) to create a  $K_2$  graph, the .dot file created is displayed in algorithm 22:

---

**Algorithm 22** .dot file created from the create\_k2\_graph function (algorithm 4)

---

```
graph G {
0;
1;
0--1 ;
}
```

---

This .dot file corresponds to figure 4:




Figure 4: .svg file created from the `create_k2_graph` function (algorithm 4)

If you used the `create_named_vertices_k2_graph` function (algorithm 7) to produce a  $K_2$  graph with named vertices, you see that the .dot file does not have stored the vertex names:

---

**Algorithm 23** .dot file created from the `create_named_vertices_k2_graph` function (algorithm 7)

---

```

graph G {
0;
1;
0--1 ;
}

```

---

So, the 'save\_graph\_to\_dot' function (algorithm 21) saves the structure of the graph.

## 5.2 Storing a graph with named vertices as a .dot

If you used the `create_named_vertices_k2_graph` function (algorithm 7) to produce a  $K_2$  graph with named vertices, you can store these names additionally with algorithm 24:

---

**Algorithm 24** Storing a graph with named vertices as a .dot file

---

```
#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_vertices_graph_to_dot(const graph& g,
    const std::string& filename)
{
    std::ofstream f(filename);
    const auto names = get_vertex_names(g);
    boost::write_graphviz(f, g, boost::make_label_writer(&
        names[0]));
}
```

---

The .dot file created is displayed in algorithm 25:

---

**Algorithm 25** .dot file created from the create\_named\_vertices\_k2\_graph function (algorithm 7)

---

```
graph G {
0[label=from];
1[label=to];
0--1 ;
}
```

---

This .dot file corresponds to figure 5:




Figure 5: .svg file created from the create\_k2\_graph function (algorithm 7)

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 10) to produce a  $K_3$  graph with named edges and vertices, you see that the `.dot` file does not have stored the edge names:

---

**Algorithm 26** `.dot` file created from the `create_named_edges_and_vertices_k3_graph` function (algorithm 10)

---

```
graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 ;
1--2 ;
2--0 ;
}
```

---

So, the `'save_named_vertices_graph_to_dot'` function (algorithm 21) saves only the structure of the graph and its vertex names.

### 5.3 Storing a graph with named vertices and edges as a `.dot`

If you used the `create_named_edges_and_vertices_k3_graph` function (algorithm 10) to produce a  $K_3$  graph with named edges and vertices, you can store these names additionally with algorithm 27:

---

**Algorithm 27** Storing a graph with named edges and vertices as a .dot file

---

```

#include <string>
#include <fstream>
#include <boost/graph/graphviz.hpp>
#include <boost/graph/properties.hpp>

#include "get_edge_names.h"
#include "get_vertex_names.h"

///Save a graph with named vertices to a .dot file
template <typename graph>
void save_named_edges_and_vertices_graph_to_dot(const
    graph& g, const std::string& filename)
{
    std::ofstream f(filename);
    const auto vertex_names = get_vertex_names(g);
    const auto edge_name_map = boost::get(boost::edge_name,
        g);
    boost::write_graphviz(
        f,
        g,
        boost::make_label_writer(&vertex_names[0]),
        [edge_name_map](std::ostream& out, const auto& e) {
            out << "[label=\"" << edge_name_map[e] << "\"]";
        })
    );
}

```

---

The .dot file created is displayed in algorithm 28:

---

**Algorithm 28** .dot file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 7)

---

```

graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}

```

---

This .dot file corresponds to figure 6:




Figure 6: .svg file created from the create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 7)

If you used the MORE\_COMPLEX\_create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 10) to produce a  $K_3$  graph with named edges and vertices, you see that the .dot file does not have stored the edge names:

---

**Algorithm 29** .dot file created from the MORE\_COMPLEX\_create\_named\_edges\_and\_vertices\_k3\_graph function (algorithm 10)

---

```

graph G {
0[label=top];
1[label=right];
2[label=left];
0--1 [label="AB"];
1--2 [label="BC"];
2--0 [label="CA"];
}

```

---

So, the 'save\_named\_edges\_and\_vertices\_graph\_to\_dot' function (algorithm 21) saves only the structure of the graph and its edge and vertex names.



## 6 TODO's in general

### 6.1 Personal experiences with Boost.Graph

I have been experimenting with Boost.Graph since 2006 and I both use the documentation on the Boost website [1] and the book [1].

- Boost.Graph seems like the most type-safe extendable graph library around: learning it will pay off!
- Boost.Graph requires a good compiler, like GCC
- The book [2] will not help a beginner: all code snippets are written 'too smart', where a beginner might prefer four easy-to-understand lines, instead of one using magic. Most code snippets are scattered as part of a complete project, where a beginner might prefer simple short projects
- The website [1] will not help a beginner, for the same reasons as above
- I have never found Boost.Graph documentation or code snippets a beginner would understand (except for (hopefully) at my website), as if nobody understands Boost.Graph and/or everybody that understands Boost.Graph cannot explain simply anymore
- I learned most of Boost.Graph from my IDE ( the helpful Qt Creator): by viewing the code that failed, I could understand what was expected for me. I would never have understood Boost.Graph if I would have used a text editor for programming

### 6.2 To add

Code snippets show include guards , use header\_impl instead.

- `std::pair<edge_iterator, edge_iterator> edges(const adjacency_list& g)`  
. Returns an iterator pair corresponding to the edges in graph g
- `vertex_descriptor source(edge_descriptor e, const adjacency_list& g)`  
. Returns the source vertex of an edge
- `vertex_descriptor target(edge_descriptor e, const adjacency_list& g)`  
. Returns the target vertex of an edge
- `degree_size_type in_degree(vertex_descriptor u, const adjacency_list& g)`  
. Returns the in-degree of a vertex
- `degree_size_type out_degree(vertex_descriptor u, const adjacency_list& g)`  
. Returns the out-degree of a vertex
- `void remove_edge(vertex_descriptor u, vertex_descriptor v, adjacency_list& g)`  
. Removes an edge from g

- `void remove_edge(edge_descriptor e, adjacency_list& g)` . Removes an edge from `g`
- `void clear_vertex(vertex_descriptor u, adjacency_list& g)` . Removes all edges to and from `u`
- `void clear_out_edges(vertex_descriptor u, adjacency_list& g)` . Removes all outgoing edges from vertex `u` in the directed graph `g` (not applicable for undirected graphs)
- `void clear_in_edges(vertex_descriptor u, adjacency_list& g)` . Removes all incoming edges from vertex `u` in the directed graph `g` (not applicable for undirected graphs)
- `void remove_vertex(vertex_descriptor u, adjacency_list& g)` . Removes a vertex from graph `g` (It is expected that all edges associated with this vertex have already been removed using `clear_vertex` or another appropriate function.)

## 7 Graph of this tutorial

This tutorial would not be complete with a graph that connects all chapter chronologically:




Figure 7: .svg file created from the `create_tutorial_chapters_graph` function

## References

- [1] Jeremy G Siek, Lie-Quan Lee, and Andrew Lumsdaine. *Boost Graph Library: User Guide and Reference Manual, The*. Pearson Education, 2001.

## Index

- $K_2$  with named vertices, create, 8
- $K_2$ , create, 5
- $K_3$  with named edges and vertices, create, 13
- $100\pi$ , 17
- Add a vertex, 3
- Add an edge, 4
- Add named edge, 12
- Add named vertex, 8
- add\_edge, 4
- add\_named\_edge, 13
- add\_named\_vertex, 8, 19
- add\_vertex, 3
- assert, 4
- boost::add\_edge, 4, 6, 13
- boost::add\_vertex, 3, 6
- boost::adjacency\_list, 3, 6, 7, 12, 19
- boost::adjacency\_matrix, 3
- boost::edge\_name\_t, 12
- boost::get(boost::vertex\_custom\_type,g), 19
- boost::get(boost::vertex\_name,g), 8
- boost::num\_edges, 23
- boost::num\_vertices, 22
- boost::property, 7, 12, 18
- boost::property<boost::edge\_name\_t,std::string>, 12
- boost::property<boost::vertex\_custom\_type\_t,my\_vertex>, 18, 19
- boost::property<boost::vertex\_name\_t,my\_vertex>, 7, 12
- boost::undirectedS, 6, 7, 11, 18
- boost::vecS, 7, 11, 18
- boost::vertex\_custom\_type, 19
- boost::vertex\_custom\_type\_t, 18, 19
- boost::vertex\_name, 8
- boost::vertex\_name\_t, 7, 12
- BOOST\_INSTALL\_PROPERTY, 17
- Counting the number of edges, 23
- Counting the number of vertices, 22
- Create  $K_2$ , 5
- Create  $K_2$  with named vertices, 8
- Create  $K_3$  with named edges and vertices, 13
- Create .dot from graph, 27
- Create .dot from graph with named edges and vertices, 30
- Create .dot from graph with named vertices, 28
- Create an empty graph, 3
- Create an empty graph with named edges and vertices, 11
- Create an empty graph with named vertices, 7
- create\_custom\_vertices\_k2\_graph, 21
- create\_empty\_custom\_vertices\_graph, 18
- create\_empty\_graph, 3
- create\_empty\_named\_edges\_and\_vertices\_graph, 11
- create\_empty\_named\_vertices\_graph, 7
- create\_k2\_graph, 6
- create\_named\_edges\_and\_vertices\_k3, 15
- create\_named\_vertices\_k2\_graph, 10
- create\_tutorial\_chapters\_graph, 35
- Declaration, my\_vertex, 16
- edge descriptor, 13
- Edge\_t, 4
- edges, counting, 23
- Empty graph with named edges and vertices, create, 11
- Empty graph with named vertices, create, 7
- Empty graph, create, 3
- get\_edge\_names, 25
- get\_n\_edges, 23
- get\_n\_vertices, 22
- get\_vertex\_names, 24

- install\_vertex\_custom\_type, 17
- m\_, 16
- macro, 17
- member, 16
- my\_vertex, 16
- my\_vertex declaration, 16
- my\_vertex.h, 16
- Named edge, add, 12
- Named edges and vertices, create empty graph, 11
- Named vertex, add, 8
- Named vertices, create empty graph, 7
- Save graph as .dot, 27
- Save graph with name edges and vertices as .dot, 30
- Save graph with name vertices as .dot, 28
- save\_graph\_to\_dot, 27
- save\_named\_edges\_and\_vertices\_graph\_to\_dot, 31
- save\_named\_vertices\_graph\_to\_dot, 29
- Set vertex names, 26
- set\_vertex\_names, 26
- std::pair, 4
- vertex descriptor, 4, 6
- Vertex, add, 3
- Vertex, add named, 8
- vertex\_custom\_type, 16
- vertices, counting, 22
- Vertices, set names, 26