

Extending Classifiers for Incomplete Data

A dissertation submitted in partial fulfillment of
the requirements for the degree of
BACHELOR OF ENGINEERING in Computer Science
in
The Queen's University of Belfast
by

Christopher McKee

February 21, 2017

SCHOOL OF ELECTRONICS, ELECTRICAL ENGINEERING and COMPUTER SCIENCE

CSC3002 – COMPUTER SCIENCE PROJECT

Dissertation Cover Sheet

A signed and completed cover sheet must accompany the submission of the Software Engineering dissertation submitted for assessment.

Work submitted without a cover sheet will **NOT** be marked.

Student Name:

Student Number:

Project Title:

Supervisor:

Declaration of Academic Integrity

Before signing the declaration below please check that the submission:

1. Has a full bibliography attached laid out according to the guidelines specified in the Student Project Handbook
2. Contains full acknowledgement of all secondary sources used (paper-based and electronic)
3. Does not exceed the specified page limit
4. Is clearly presented and proof-read
5. Is submitted on, or before, the specified or agreed due date. Late submissions will only be accepted in exceptional circumstances or where a deferment has been granted in advance.

I declare that I have read both the University and the School of Electronics, Electrical Engineering and Computer Science guidelines on plagiarism - <http://www.qub.ac.uk/schools/eeecs/Education/StudentStudyInformation/Plagiarism/> - and that the attached submission is my own original work. No part of it has been submitted for any other assignment and I have acknowledged in my notes and bibliography all written and electronic sources used.

Student's signature

Date of submission

Abstract

Abstract goes here

Contents

1	Introduction	2
2	Design and Implementation	4
2.1	Design	4
2.2	Implementation	4
2.2.1	Weka Architecture	5
2.2.2	Weka Command Line Interface	5
2.2.3	Weka Graphical User Interface	5
2.2.4	StateAnalyser	5
2.2.5	ProjectClassifier	5
3	Experiments	6
3.1	Results	6
3.1.1	Naive Bayes	6
3.1.2	Bayesian Network	6
3.1.3	J48 Decision Tree	6
4	Conclusion	7
A	JavaDoc	8

Chapter 1

Introduction

The reliability of a machine learning model is heavily dependent on the data which was used to train it. Training data sets with missing values are therefore an interesting problem since there is no way of knowing what any given missing value could have been, and so the only two useful approaches involve either making statistical approximations of missing or ignoring any record which contains missing data. Both mentioned approaches have positives as well as negatives. Ignoring a record prevents you from using unreliable data, but also may lead to valuable data in the other, non-missing attributes of the same record being discounted. Attempts to predict a missing value have no guarantee of being correct, but may be worth the risk to gain value from the other complete attributes. Using either approach may produce false outcomes. It is therefore extremely important that any imputation is carried out with care, and it must be very likely to be correct.

This project aims to investigate the usage of machine learning techniques on incomplete sets of discrete data. It will attempt to impute any missing values in the training data, by iteratively building and applying models until no further change is observed. It is expected that predicted missing values will trend towards the mean, leading to more reliable classification when this trained model is then applied to target data. Given sufficient time, it is also intended that this approach can be used to infer 'hidden variables', similarly to how neural networks produce hidden layers to create relationships between data. This will be achieved by adding a new attribute to a data set, and initially filling it full of random valid data. We will then repeatedly build, apply and rebuild models to classify this attribute until it stops changing, in an identical manner to how missing data is imputed in the training set. New data will be added to the training data set by this method, and this project aims to determine whether or not these hidden variables lead to a greater classification accuracy.

The goal of this project is to study the effects of iteratively building common classifiers and comparing the performance of classifiers built this way against the performance of the same classifier, but without attempting to impute missing training data. The main aims of the software to be developed will therefore be:

- A Weka plugin will be developed. This should integrate smoothly into any version of Weka >3.6, and will be made freely available.
- The classifier developed within the plugin should be usable from both the CLI and GUI.
- Running experiments using the plugin should be easy, and have well explained documen-

tation.

- Allow any currently implemented Weka classifier which is valid to use for a given dataset to be used upon it, and for this to be easily configurable.
- Run a number of experiments to compare the performance of the iteratively trained classifier against some control cases on the same data sets.

Chapter 2

Design and Implementation

2.1 Design

This body of work is mainly interested in common classifiers, and in trying to use them in a novel way. It therefore makes sense to extend a package in which these are already implemented, and in which they are easily accessible. The Weka project therefore suits this purpose since it has well maintained, efficient implementations of most machine learning algorithms, as well as handling file I/O, and having both command line and graphical user interfaces. Since these are written in Java, it follows that the plugin should also be written in Java.

It also follows that any files which are used for testing should be in either .csv, or .arff format. The former is commonly used in data processing while the latter is a proprietary Weka format which is very similar, but differs in that it contains additional data at the top of the file pertaining to the dataset. Both are supported by Weka, and therefore either is usable.

Since the project relies upon the idea that predictions for missing training data values should converge, it is assumed that the developed classifier will initially only work on nominal data sets. This is because nominal data sets should eventually settle on concrete values, whilst numeric values are not guaranteed to every settle on a particular value at all. It is more likely that numeric predictions would just change less and less between iterations, until the changes were miniscule. While it would be possible to implement a solution which stops iterating once a numeric data set only changes to a certain degree, as a proof of concept it is sensible to stick to nominal data.

2.2 Implementation

As an existing piece of software is being extended, much of the work to implement the various classifiers to be tested is already done. The main aim of this work is to integrate successfully into Weka as a plugin, and to interface with it as necessary.

2.2.1 Weka Architecture

Stuff about how weka is laid out

2.2.2 Weka Command Line Interface

Stuff about passing options to classifiers

2.2.3 Weka Graphical User Interface

Stuff about setter methods etc

2.2.4 StateAnalyser

Stuff about how we're measuring sameness

2.2.5 ProjectClassifier

Stuff about implementation, mostly pseudocode

Chapter 3

Experiments

3.1 Results

3.1.1 Naive Bayes

3.1.2 Bayesian Network

3.1.3 J48 Decision Tree

Chapter 4

Conclusion

Do result discussion stuff

Appendix A

JavaDoc

Contents

1	Package <code>cdc04</code>	2
1.1	Class <code>StateAnalyser</code>	2
1.1.1	Declaration	2
1.1.2	Constructor summary	2
1.1.3	Method summary	2
1.1.4	Constructors	2
1.1.5	Methods	2
2	Package <code>weka.classifiers.meta</code>	4
2.1	Class <code>ProjectClassifier</code>	4
2.1.1	Declaration	4
2.1.2	Constructor summary	5
2.1.3	Method summary	5
2.1.4	Constructors	5
2.1.5	Methods	6
2.1.6	Members inherited from class <code>SingleClassifierEnhancer</code>	12
2.1.7	Members inherited from class <code>AbstractClassifier</code>	12

Chapter 1

Package cdc04

<i>Package Contents</i>	<i>Page</i>
Classes	
StateAnalyser	2

1.1 Class StateAnalyser

1.1.1 Declaration

```
public class StateAnalyser
    extends java.lang.Object implements java.io.Serializable
```

1.1.2 Constructor summary

```
StateAnalyser()
```

1.1.3 Method summary

```
addInstances(Instances)
getNumberDifferences()
getNumberIterations()
```

1.1.4 Constructors

- StateAnalyser

```
public StateAnalyser()
```

1.1.5 Methods

- addInstances

```
public void addInstances(weka.core.Instances toAdd)
```

- **getNumberDifferences**

```
public int getNumberDifferences()
```

- **getNumberIterations**

```
public int getNumberIterations()
```

Chapter 2

Package weka.classifiers.meta

Package Contents

Page

Classes

ProjectClassifier	4
A classifier which is iteratively trained, imputing missing values into copies of the training data until no further change is observed.	

2.1 Class ProjectClassifier

A classifier which is iteratively trained, imputing missing values into copies of the training data until no further change is observed. Builds one learner per attribute, and therefore can take quite a while to run. Valid options are:

-W classifier

Full path to the target classifier to use, e.g. weka.classifiers.trees.J48

-S

Defines whether or not the classifier will impute a value for the class attribute as it trains.

-R

If set, the classifiers will be trained with any missing arguments filled in by random data. The classifier will then only iterate once.

-M integer

Sets the maximum number of times that a particular classifier will iterate before determining that it is trained.

Options after – are passed to the currently selected classifier.

2.1.1 Declaration

```
public class ProjectClassifier
```

extends `weka.classifiers.SingleClassifierEnhancer` **implements** `weka.classifiers.IterativeClassifier`

2.1.2 Constructor summary

ProjectClassifier() Constructor

2.1.3 Method summary

buildClassifier(Instances) Builds a set of classifiers based on the training data.
classifierOptionsTipText() Tip text to be displayed in the GUI for this property
classifyInstance(Instance) Classifies an instance.
defaultClassifierString() String describing default classifier.
distributionForInstance(Instance) Returns class probabilities for an instance.
done() Method called when iteration has terminated.
getCapabilities() Returns default capabilities of the classifier.
getClassifierOptions() Gets classifier options
getMaxIterations() Get the value of `m_MaxIterations`
getOptions() Gets the current settings of the Classifier.
getRandomData() Get the value of `m_RandomData`
getSupervised() Get the value of `m_Supervised`
globalInfo() Global information about the class
initializeClassifier(Instances) Makes copies of the training data which can be mutated, and initialise the array of Classifier objects
listOptions() Returns an enumeration describing the available options.
main(String[]) Main method for testing this class.
maxIterationsTipText() Tip text to be displayed in the GUI for this property
next() Retrains each of the classifiers, then attempts to impute missing data in a copy of the training data.
randomDataTipText() Tip text to be displayed in the GUI for this property
setClassifierOptions(String[]) Sets classifier options
setMaxIterations(int) Set the value of `m_MaxIterations`.
setOptions(String[]) Parses a given list of options.
setRandomData(boolean) Set the value of `m_RandomData`
setSupervised(boolean) Set the value of `m_Supervised`
supervisedTipText() Tip text to be displayed in the GUI for this property

2.1.4 Constructors

- **ProjectClassifier**

public ProjectClassifier()

- **Description**
Constructor

2.1.5 Methods

- **buildClassifier**

```
public void buildClassifier(weka.core.Instances data) throws
    java.lang.Exception
```

- **Description**

Builds a set of classifiers based on the training data. These are iteratively trained on copies of the data.

- **Parameters**

- * **data** – the Instances object which comprises the training data

- **Throws**

- * **java.lang.Exception** – exception thrown is raised to a Weka error handler

- **classifierOptionsTipText**

```
public java.lang.String classifierOptionsTipText()
```

- **Description**

Tip text to be displayed in the GUI for this property

- **Returns** – tip text to be displayed in the GUI

- **classifyInstance**

```
public double classifyInstance(weka.core.Instance instance)
    throws java.lang.Exception
```

- **Description**

Classifies an instance.

- **Parameters**

- * **instance** – the instance to classify

- **Returns** – the classification for the instance

- **Throws**

- * **java.lang.Exception** – if instance can't be classified successfully

- **defaultClassifierString**

```
protected java.lang.String defaultClassifierString()
```

- **Description**

String describing default classifier.

- **distributionForInstance**

```
public double [] distributionForInstance(weka.core.Instance  
instance) throws java.lang.Exception
```

- **Description**

Returns class probabilities for an instance.

- **Parameters**

- * **instance** – the instance to calculate the class probabilities for

- **Returns** – the class probabilities

- **Throws**

- * **java.lang.Exception** – if distribution can't be computed successfully

- **done**

```
public void done() throws java.lang.Exception
```

- **Description**

Method called when iteration has terminated. Imputes class values if m_Supervised is set.

- **getCapabilities**

```
public weka.core.Capabilities getCapabilities()
```

- **Description**

Returns default capabilities of the classifier.

- **Returns** – the capabilities of this classifier

- **getClassifierOptions**

```
public java.lang.String [] getClassifierOptions()
```

- **Description**

Gets classifier options

- **Returns** – array of String objects to be passed to each classifier

- **getMaxIterations**

```
public int getMaxIterations()
```

- **Description**

Get the value of m_MaxIterations

- **Returns** – value of m_MaxIterations

- **getOptions**

```
public java.lang.String [] getOptions()
```

- **Description**

Gets the current settings of the Classifier.

- **Returns** – an array of strings suitable for passing to setOptions

- **getRandomData**

```
public boolean getRandomData()
```

- **Description**

Get the value of m_RandomData

- **Returns** – value of m_RandomData

- **getSupervised**

```
public boolean getSupervised()
```

- **Description**

Get the value of m_Supervised

- **Returns** – value of m_Supervised

- **globalInfo**

```
public java.lang.String globalInfo()
```

- **Description**

Global information about the class

- **Returns** – information about the classifier which is displayed in the CLI/GUI

- **initializeClassifier**

```
public void initializeClassifier(weka.core.Instances instances)
    throws java.lang.Exception
```

- **Description**

Makes copies of the training data which can be mutated, and initialise the array of Classifier objects

- **Parameters**

* `instances` – the training data

- **listOptions**

```
public java.util.Enumeration listOptions()
```

- **Description**

Returns an enumeration describing the available options.

- **Returns** – an enumeration of all the available options.

- **main**

```
public static void main(java.lang.String[] args)
```

- **Description**

Main method for testing this class.

- **Parameters**

* `args` – the options

- **maxIterationsTipText**

```
public java.lang.String maxIterationsTipText()
```

- **Description**

Tip text to be displayed in the GUI for this property

- **Returns** – tip text to be displayed in the GUI

- **next**

```
public boolean next() throws java.lang.Exception
```

- **Description**

Retrains each of the classifiers, then attempts to impute missing data in a copy of the training data. Does not iterate again if the results of current iteration match the results of the previous iteration, or the max number of iterations has been reached.

- **Returns** – true if another iteration should be performed, otherwise false.

- **randomDataTipText**

```
public java.lang.String randomDataTipText()
```

- **Description**

Tip text to be displayed in the GUI for this property

- **Returns** – tip text to be displayed in the GUI

- **setClassifierOptions**

```
public void setClassifierOptions(java.lang.String []  
    classifierOptions)
```

- **Description**

Sets classifier options

- **Parameters**

* **classifierOptions** – array of String objects to be passed to each classifier

- **setMaxIterations**

```
public void setMaxIterations(int maxIterations)
```

- **Description**

Set the value of m_MaxIterations. Defaults to Integer.MAX_VALUE if value less than 0 is supplied.

- **Parameters**

* **maxIterations** – new value of m_MaxIterations

- **setOptions**

```
public void setOptions(java.lang.String [] options) throws java.  
    lang.Exception
```

- **Description**

Parses a given list of options. Valid options are:

-W classifier

Full path to the target classifier to use, e.g. weka.classifiers.trees.J48

-S

Defines whether or not the classifier will impute a value for the class attribute as it trains.

-R

If set, the classifiers will be trained with any missing arguments filled in by random data. The classifier will then only iterate once.

-M integer

Sets the maximum number of times that a particular classifier will iterate before determining that it is trained.

Options after – are passed to the currently selected classifier.

– **Parameters**

* **options** – The list of options as an array of Strings

– **Throws**

* `java.lang.Exception` – if an option is not supported

• **setRandomData**

```
public void setRandomData(boolean randomData)
```

– **Description**

Set the value of `m_RandomData`

– **Parameters**

* **randomData** – new value of `m_RandomData`

• **setSupervised**

```
public void setSupervised(boolean supervised)
```

– **Description**

Set the value of `m_Supervised`

– **Parameters**

* **supervised** – the new value of `m_Supervised`

• **supervisedTipText**

```
public java.lang.String supervisedTipText()
```

– **Description**

Tip text to be displayed in the GUI for this property

– **Returns** – tip text to be displayed in the GUI

2.1.6 Members inherited from class SingleClassifierEnhancer

weka.classifiers.SingleClassifierEnhancer

- public String classifierTipText()
- protected String defaultClassifierOptions()
- protected String defaultClassifierString()
- public Capabilities getCapabilities()
- public Classifier getClassifier()
- protected String getClassifierSpec()
- public String getOptions()
- public Enumeration listOptions()
- protected m_Classifier
- public void postExecution() throws java.lang.Exception
- public void preExecution() throws java.lang.Exception
- public void setClassifier(Classifier arg0)
- public void setOptions(java.lang.String[] arg0) throws java.lang.Exception

2.1.7 Members inherited from class AbstractClassifier

weka.classifiers.AbstractClassifier

- public static BATCH_SIZE_DEFAULT
- public String batchSizeTipText()
- public double classifyInstance(weka.core.Instance arg0) throws java.lang.Exception
- public String debugTipText()
- public double distributionForInstance(weka.core.Instance arg0) throws java.lang.Exception
- public double distributionsForInstances(weka.core.Instances arg0) throws java.lang.Exception
- public String doNotCheckCapabilitiesTipText()
- public static Classifier.forName(java.lang.String arg0, java.lang.String[] arg1) throws java.lang.Exception
- public String getBatchSize()
- public Capabilities getCapabilities()
- public boolean getDebug()
- public boolean getDoNotCheckCapabilities()
- public int getNumDecimalPlaces()
- public String getOptions()
- public String getRevision()
- public boolean implementsMoreEfficientBatchPrediction()
- public Enumeration listOptions()
- protected m_BatchSize
- protected m_Debug
- protected m_DoNotCheckCapabilities
- protected m_numDecimalPlaces
- public static Classifier makeCopies(Classifier arg0, int arg1) throws java.lang.Exception
- public static Classifier makeCopy(Classifier arg0) throws java.lang.Exception
- public static NUM_DECIMAL_PLACES_DEFAULT
- public String numDecimalPlacesTipText()
- public void postExecution() throws java.lang.Exception
- public void preExecution() throws java.lang.Exception
- public void run(java.lang.Object arg0, java.lang.String[] arg1) throws java.lang.Exception
- public static void runClassifier(Classifier arg0, java.lang.String[] arg1)
- public void setBatchSize(java.lang.String arg0)
- public void setDebug(boolean arg0)
- public void setDoNotCheckCapabilities(boolean arg0)
- public void setNumDecimalPlaces(int arg0)
- public void setOptions(java.lang.String[] arg0) throws java.lang.Exception