
Table of Contents

1. Overview
2. Class Declaration
3. Core Purpose and Features
4. Fields and Configuration
 - 4.1 Waypoint Navigation
 - 4.2 Target Following / Chasing
 - 4.3 Obstacle Avoidance
 - 4.4 Steering/Throttle/Brake Inputs
 - 4.5 Speed Limits and Lap Tracking
 - 4.6 Brake Zones
 - 4.7 Events
5. Initialization
 - 5.1 Awake()
 - 5.2 OnEnable()
6. Update Flow
 - 6.1 Update()
 - 6.2 FixedUpdate()
7. Navigation Logic
 - 7.1 FollowWaypoints Mode
 - 7.2 ChaseTarget Mode
 - 7.3 FollowTarget Mode
8. Obstacle Avoidance (Raycasts)
9. Reversing Logic
10. Feeding Inputs to RCC
11. Target and Brake Zone Management
12. Stopping the AI
13. Disabling the AI
14. Usage Notes and Best Practices
15. Summary

1. Overview

RCC_AICarController is the **AI driver** component for **Realistic Car Controller** (RCC). It directs the assigned vehicle to **follow waypoints**, **chase** a target, or **follow** a target. It also provides **raycast-based obstacle avoidance**, reversing logic, and optional **speed limiting**. The AI sets external inputs on the underlying **RCC_CarControllerV4**, effectively taking control away from user input.

2. Class Declaration

```
[RequireComponent(typeof(RCC_CarControllerV4))]  
public class RCC_AICarController : RCC_Core {  
    // ...  
}
```

- Inherits from **RCC_Core**, granting usage of shared RCC utilities and references.
 - Requires an **RCC_CarControllerV4** on the same GameObject, so it can directly drive the vehicle.
-

3. Core Purpose and Features

1. **Navigation**
 - **FollowWaypoints** using a container of waypoints.
 - **ChaseTarget** (e.g., a player or other object).
 - **FollowTarget** from a distance.
 2. **Raycast-based** obstacle detection and avoidance.
 3. **Reversing** logic if stuck.
 4. **Speed limiting, lap counting, brake zones.**
 5. **External** input feed to the **CarController**
(**CarController.externalController = true**).
-

4. Fields and Configuration

4.1 Waypoint Navigation

- **public RCC_AIWaypointsContainer waypointsContainer**: Holds a list of waypoints for the car to follow in **FollowWaypoints** mode.
- **public int currentWaypointIndex**: The current waypoint we're heading towards.
- **public int lap**: Tracks how many laps are completed if the waypoint list is looped.

4.2 Target Following / Chasing

- **public string targetTag = "Player"**: AI searches for objects with this tag to chase or follow.
- **public enum NavigationMode { FollowWaypoints, ChaseTarget, FollowTarget }**

- **public Transform targetChase:** The actual transform the AI is chasing/following.
- **public List<Transform> targetsInZone:** Potential chase/follow targets within a detection radius.

4.3 Obstacle Avoidance

- **public bool useRaycasts = true:** If enabled, the AI casts forward and angled rays to detect obstacles.
- **public float raycastLength = 3f** and **public float raycastAngle = 30f** define the range and spread of rays.
- **public LayerMask obstacleLayers:** Layers considered obstacles.
- **private bool raycasting = false:** True if any ray hit an obstacle.
- **private float rayInput = 0f:** Additional steering from the raycast to avoid the obstacle.

4.4 Steering/Throttle/Brake Inputs

- **public float steerInput, throttleInput, brakeInput, handbrakeInput** store final values.
- Computed by **Navigation()** each frame, then fed into **RCC_CarControllerV4**.

4.5 Speed Limits and Lap Tracking

- **public bool limitSpeed:** If true, we clamp at **maximumSpeed**.
- **public float maximumSpeed = 100f:** Speed limit for the AI.
- **public bool stopAfterLap / public int stopLap = 10:** AI can stop after completing a certain number of laps.

4.6 Brake Zones

- **public List<RCC_AI BrakeZone> brakeZones:** Lists brake zones within detection range.
- **public RCC_AI BrakeZone targetBrake:** The closest zone we must slow down in.

4.7 Events

- **public static event onRCCAI Spawmed(RCC_AI CarController RCCAI):** Fired when AI car is enabled/spawmed.
 - **public static event onRCCAI Destroyed(RCC_AI CarController RCCAI):** Fired when AI car is disabled/destroyed.
-

5. Initialization

5.1 Awake()

- If `waypointsContainer` is null, tries to find `RCC_AIWaypointsContainer` in the scene.
- Creates an internal `NavMeshAgent` named "Navigator" so the AI can get direction from Unity's pathfinding logic.

5.2 OnEnable()

- `CarController.externalController = true` so the vehicle is AI-driven.
 - Invokes `OnRCCAISpawned(this)` event.
-

6. Update Flow

6.1 Update()

- If AI is active (`CarController.canControl`), updates:
 - Possibly resets `maximumSpeed` if `limitSpeed` is false.
 - Moves the `navigator` transform to the front wheels area.
 - `CheckTargets()` if in chase or follow mode.
 - `CheckBrakeZones()` for upcoming slow-down areas.

6.2 FixedUpdate()

1. If `CarController.canControl` is false, return.
 2. `FixedRaycasts()` if `useRaycasts` is true, tries to avoid obstacles by steering away.
 3. `Navigation()` sets `steerInput`, `throttleInput`, `brakeInput`, `handbrakeInput` for the AI logic.
 4. `CheckReset()` if stuck, switch to reversing.
 5. `FeedRCC()` inputs to `CarController`.
-

7. Navigation Logic

7.1 FollowWaypoints Mode

1. Requires `waypointsContainer` not null and has at least one waypoint.

2. If distance to next waypoint < that waypoint's radius, increment `currentWaypointIndex`.
3. If we cycle through all waypoints, increment `lap`. If `stopAfterLap` is true and `lap` \geq `stopLap`, we call `Stop()`.
4. Sets `navigator.SetDestination(nextWaypointPos)`.
5. Adjusts throttle/brake based on distance or target speed in the waypoint.
6. If speed is high, reduce throttle or add brake proportionally to turn angle.

7.2 ChaseTarget Mode

1. Must have a `targetChase` transform. If none, calls `Stop()`.
2. `navigator.SetDestination(targetChase.position)`.
3. Usually sets `throttleInput = 1f`, unless speed is too high (then reduce).
4. If turning, also blend in brake.

7.3 FollowTarget Mode

1. Also sets `navigator.SetDestination(targetChase.position)`.
 2. Distance-based logic: if close to the target (`stopFollowDistance`), reduce or zero throttle and raise brake.
 3. If far, accelerate more.
 4. If speed is high, also reduce throttle.
-

8. Obstacle Avoidance (Raycasts)

- Casts 5 rays from the front: center, $\pm(\text{raycastAngle}/3)$, $\pm(\text{raycastAngle})$.
 - Any hits on `obstacleLayers` sets `rayInput`, a steering offset.
 - If absolute `rayInput` > 0.5f, we ignore the normal navigation steer for that moment.
 - If `raycasting` is true, an `obstacle` is set to the hit object.
-

9. Reversing Logic

- If speed < 5 and velocity is small for >2 seconds, we go `reversingNow = true`.
 - If stuck for 4 seconds or speed >25, we revert to forward.
 - While reversing, we set `throttleInput=0`, `brakeInput=1` so the car goes backward (car's `direction` is effectively -1).
-

10. Feeding Inputs to RCC

```
private void FeedRCC() {  
    CarController.throttleInput = ...  
    CarController.brakeInput = ...  
    CarController.steerInput = ...  
    CarController.handbrakeInput = ...  
}
```

- If not changing gears or cutGas, passes the AI's `throttleInput`, `brakeInput`, `steerInput`, `handbrakeInput` to the `RCC_CarControllerV4`.
 - This effectively **drives** the vehicle from the AI logic.
-

11. Target and Brake Zone Management

- `CheckTargets()`: Every 1 second, we do a sphere overlap of radius `detectorRadius` around the AI. If objects have `targetTag`, add them to `targetsInZone`. We remove any that left range or is inactive, then pick the closest.
 - `CheckBrakeZones()`: Similarly collects `RCC_AIBrakeZone` references and picks the closest as `targetBrake`.
-

12. Stopping the AI

- `Stop()` sets `throttleInput=0`, `brakeInput=0`, `steerInput=0`, `handbrakeInput=1`. The car halts.
-

13. Disabling the AI

- On `OnDisable()`, sets `CarController.externalController = false`. The user could then drive it.
 - Invokes `OnRCCAIDestroyed(this)` event.
-

14. Usage Notes and Best Practices

1. **Attach** this script to a car with `RCC_CarControllerV4`.
2. **Waypoints**

- If using **FollowWaypoints**, ensure an `RCC_AIWaypointsContainer` with at least one waypoint is present.
 - 3. **Chase or Follow**
 - The script tries to find an object with `targetTag` within `detectorRadius`. If none found, it halts.
 - 4. **Raycasts**
 - `useRaycasts` can be toggled off for simpler pathing. Ray-based obstacle avoidance is basic but helps avoid collisions.
 - 5. **Performance**
 - For many AI cars with large `detectorRadius`, the sphere overlap every second can be costly. Consider chunking or culling.
 - 6. **Stop After Lap**
 - If `stopAfterLap` is true and `lap >= stopLap`, the AI calls `Stop()`.
 - 7. **Interaction with `RCC_CarControllerV4`**
 - The `CarController` is placed in **external controller** mode. The AI sets `throttleInput` etc. every frame.
 - 8. **Smoothed Steering**
 - If `smoothedSteer`, we interpolate steer from old to new over time.
-

15. Summary

`RCC_AICarController` is a straightforward **AI driver** for **Realistic Car Controller** vehicles. By setting **NavigationMode**:

- **FollowWaypoints**
- **ChaseTarget**
- **FollowTarget**

the script uses a **NavMeshAgent** plus optional **raycast** obstacle avoidance to produce steering, throttle, brake, and handbrake inputs. It also handles reversing if stuck, speed limiting, brake zones, lap counting, and vantage targeting. This gives you a simple but effective way to make AI-driven RCC cars.