Computer Networks

WILEY

Allergy EUROPEAN JOURNAL OF ALLERGY AND CLINICAL IMMUNOLOGY EAACI

ORIGINAL ARTICLE OPEN ACCESS

Campus-DDoS-SDN: A Python-based testbed for multi-vector DDoS attack detection in software-defined campus networks

Anna Olenka Calderón Leiva[1] | Ricardo Alexander Llanos Lozano[2] | Cristhian Emilio Martínez Casas[3] | Alessandro Piero Poves Martínez[4]

[1]Facultad de Ingeniería de Sistemas y Electrónica, Universidad Nacional del Centro del Perú, Huancayo, Peru | [2]Facultad de Ingeniería de Sistemas y Electrónica, Universidad Nacional del Centro del Perú, Huancayo, Peru | [3]Facultad de Ingeniería de Sistemas y Electrónica, Universidad Nacional del Centro del Perú, Huancayo, Peru | [4]Facultad de Ingeniería de Sistemas y Electrónica, Universidad Nacional del Centro del Perú, Huancayo, Peru

Correspondence: Cristhian Emilio Martínez Casas (cristhianmartinezcasas@gmail.com)

Received: 4 November 2026 | **Revised:** 4 November 2026 | **Accepted:** 4 November 2026

Academic Editor: Network security and SDN systems

Funding: This research received no external funding.

Keywords: Software-defined networking | machine learning | DDoS attack detection | Mininet | network traffic classification

ABSTRACT

Campus-DDoS-SDN is a Docker testbed that generates and classifies four DDoS attacks against the portal of a campus emulated with Mininet and Ryu. Students keep browsing during the attack, and each flow is labelled by source IP rather than by capture file. A random forest trained without IP addresses and tested on the Ciencias Agrarias laboratory, which was held out of training, reaches a macro F1 of 1.000. On the portal probe, httpflood: the page slows down; packet rate rises; icmpflood: packet rate at the portal rises; slowloris: the page stops opening; synflood: packet rate at the portal rises. ICMP is not claimed as a settled class: the Agrarias test contains 24 flows.

1 | Introduction

Software-defined networking (SDN) decouples the control plane from the data plane, concentrating network intelligence in a logically centralized controller [1]. This centralization simplifies network management, but it also turns the controller into a single point of failure: a distributed denial-of-service (DDoS) attack that saturates the controller, the switches, or a hosted service can degrade or take down the entire network segment it governs. Detecting such attacks early, and separating them reliably from legitimate traffic spikes, requires datasets that are both representative of real SDN deployments and precisely labelled.

Most publicly available intrusion-detection datasets, such as NSL-KDD [6], CICIDS2017 [4], and CICDDoS2019 [5], were not captured inside an SDN environment: they lack OpenFlow-specific signals, such as flow-table occupancy or controller load, and are nonetheless often reused out of context to train SDN-targeted classifiers. Recent work has started to close this gap by generating DDoS datasets directly inside Mininet/Ryu testbeds. Kumar and Gupta released two single-vector datasets built this way: a TCP-SYN flood dataset [2] and, more recently, an ICMP-flood dataset [3] in which normal traffic is captured by connecting a Mininet host to a live internet connection and browsing real websites (YouTube, Facebook, news, etc.), instead of relying on synthetic traffic generators. This real-traffic approach increases realism, but it introduces two practical limitations for a reusable benchmark: the resulting dataset is tied to a single attack vector, and it is not reproducible across runs, since the captured content and timing depend on whatever the live internet happens to serve at capture time.

This work, Campus-DDoS-SDN, addresses both limitations within a single, fully reproducible testbed. Four attack vectors (TCP-SYN flood, HTTP flood, Slowloris, and ICMP flood) are launched from already-compromised hosts against one shared victim, a web portal, inside a Mininet/Ryu topology that mimics a university campus: a core/DMZ switch layout plus one emulated laboratory per academic area. Unlike prior single-vector or fully-separated-capture datasets, legitimate users keep browsing the portal throughout every attack, so each capture mixes benign

This work is distributed for academic and research purposes. The authors retain the right to reuse and adapt the content for scholarly publication.

and malicious flows against the same target, as a real DDoS incident would. Ground-truth labels are assigned per source IP rather than per capture file, and every run additionally logs the attack's effect on the victim as perceived by a real client (HTTP response code, latency, active connections), alongside network-level indicators (packets and bytes per second) and OpenFlow controller telemetry collected by a custom Ryu application (flow-table statistics, per-source flow counts and source-IP entropy sampled at a fixed interval). The complete environment, including the traffic generators, the custom web portal, and the labelling pipeline, is packaged as a Docker image to remove any dependency on a live internet connection or on a specific host operating system.

The main contributions of this work are:

i. A multi-class DDoS dataset covering four attack vectors against a single victim inside a realistic, multi-segment SDN topology, instead of a single attack type against a flat network.
ii. Per-flow, per-source-IP labelling that keeps legitimate and malicious traffic mixed within the same capture, closer to a real attack scenario than the fully-separated captures used in prior work.
iii. Combined network-level (flow and packet statistics via CICFlowMeter) and application-level (HTTP status, latency, connection saturation) impact metrics, captured automatically on every run.
iv. A one-command, fully reproducible Docker environment that does not depend on a live internet connection, addressing the reproducibility limitation of real-traffic-based SDN datasets.
v. A random-forest classifier trained without IP addresses that reaches a macro F1 of 1.000on the held-out Ciencias Agrarias laboratory, plus a pipeline ready to mix authorized Wireshark captures of benign student traffic with simulation-only attacks.
vi. OpenFlow controller telemetry exported on every run by a custom Ryu application: it installs IP-based flows and periodically polls flow-table statistics, which the pipeline merges with the per-flow CICFlowMeter features by source IP. This supplies the SDN-specific signals that the reused non-SDN datasets lack.
vii. A time-window dataset (one row per second with portal counters and aggregated SDN telemetry) and an early-detection pipeline that decides while the attack is ongoing, rather than only classifying completed flows. It is evaluated with a repeatable multi-run driver, leave-one-run-out cross-validation reporting mean ± standard deviation, and a feature-group ablation that isolates the contribution of the SDN telemetry.

2 | Research design

2.1 | Problem, objective and working hypothesis

High accuracy on one attack type and separated captures does not show that a detector can recognize malicious traffic while legitimate users continue using the same service. Live internet browsing also changes between runs. The objective is therefore to implement and evaluate a reproducible Docker testbed that mixes benign traffic and four attacks against one portal, measures service impact, and tests a model on a laboratory excluded from training. The working hypothesis is that flow size, duration and rate features, without IP addresses, ports or time, can yield a macro F1 above 0.90 on that held-out laboratory. This hypothesis is first tested at home; validation with authorized real UNCP traffic is the proposed next phase.

3 | Software description

3.1 | Architecture overview

The topology is a reduced campus: an edge modem, a core switch, a DMZ holding the portal, and one laboratory per academic area. Each laboratory has students and compromised hosts. Switches are Open vSwitch in userspace, controlled by Ryu. Students keep requesting portal pages during an attack. The operator's browser, at `http://127.0.0.1:8080/`, joins as one more benign client (`10.9.0.1`). The attack does not leave the container.

3.2 | Software functionalities

`scripts/docker/run_scenario.sh` runs one scenario (`baseline`, `synflood`, `httpflood`, `slowloris`, `icmpflood`) or all five; its `repeat N` mode runs N independent repetitions, each with a different seed and sampled attack intensities, so results can be reported as mean ± standard deviation instead of from a single run. `scripts/mininet/flow_monitor_13.py` is the Ryu controller: it learns like an L2 switch but installs IP-based flows and periodically polls OpenFlow flow statistics, writing them per run. `scripts/mininet/capture_campus.py` stores the pcap and the student probe. `scripts/mininet/pcap_to_csv.py` labels each flow by source IP (a student stays `BENIGN` and a compromised host takes the attack name) and merges the controller telemetry by source IP. `scripts/mininet/build_windows.py` builds a time-window dataset (one row per second) from the portal counters and the aggregated SDN telemetry. `notebooks/analisis_completo.py` trains the per-flow forest without IP addresses and tests it on Ciencias Agrarias, while `notebooks/deteccion_ventanas.py` evaluates the per-window detector with leave-one-run-out cross-validation and a feature-group ablation. `scripts/docker/preparar_hibrido.sh` anonymizes authorized student Wireshark captures, mixes them with simulation attacks, and writes `notebooks/resultados/informe_hibrido.txt`. The attack is never run against the real campus network.

3.3 | Experimental design and variables

Five independent scenarios are run: one baseline and four attacks. Each lasts 120 s, starts from a clean topology and uses 20 students, 10 compromised hosts, one portal, one C2, one modem and seven switches. The scenario is the independent variable. Responses are HTTP availability, mean and 95th-percentile latency, packets per second at the portal, maximum core flows, and container CPU, memory and network use. The model receives bidirectional flow statistics from CICFlowMeter and the ICMP aggregator.




FIGURE 1 | Emulated topology. The C2 remains outside the campus; compromised hosts attack the portal while students keep browsing.

3.4 | From pcap to the model

The run in this article comes from one command, `run_scenario.sh all 120`. Inside the container, Open vSwitch, Ryu and the topology start together. Each scenario lasts 120 s and leaves three artifacts: the pcap on the portal interface, the student probe (HTTP status, latency, packets per second), and container use sampled with `docker stats`.

`pcap_to_csv.py` splits each pcap in two. TCP and UDP go through CICFlowMeter. ICMP is outside that filter, so a custom aggregator closes a flow after 10 s. Without that cut, each compromised host would leave one long flow and the class would collapse to a handful of rows. The label does not come from the file name. The JSON beside the pcap lists the compromised addresses. If the source is one of those addresses and the scenario is not the baseline, the flow takes the attack name. Students, the portal and the whole baseline stay `BENIGN`. This run has 40,877 flows. The baseline contributes 2,671, all benign. During an attack the student flows stay inside the same CSV.

Before training, source IP, destination IP, both ports and the timestamp are dropped. An infinity or a missing value becomes zero, and any column that does not vary in the training set is removed. If the IP stayed, the forest would memorize which machine is compromised rather than how the flow behaves. The model is a forest of 200 trees with class weights, because the SYN flood contributes 23,539 flows and would otherwise dominate. The split is not random: Salud, Ingenierías, Empresariales and Sociales train it (32,784 flows) and only Agrarias is tested (8,091).

4 | Results and impact overview

The single-vector reference dataset cannot be repeated, because its benign traffic comes from the live internet [3]. This testbed can be repeated, mixes student and attack traffic in the same capture, and already yields a classifier. On Ciencias Agrarias, a laboratory excluded from training, macro F1 is 1.000. The probe states what the page feels, not only which label was assigned. With institutional authorization, the same pipeline admits real benign traffic (Wireshark) while keeping the attack inside the container. The probe from that run is in Table 1: only Slowloris takes the portal down.

TABLE 1 | Portal probe. Each scenario lasts 120 s.

Scenario	HTTP 200	Failures	Latency (ms)	Packets/s
baseline	120	0	407	111
synflood	120	0	404	466
httpflood	120	0	564	386
slowloris	1	117	403	86
icmpflood	120	0	404	271

4.1 | Dataset composition

The five CSVs contain 40,877 flows: 9,400 `BENIGN`, 23,539 `synflood`, 7,188 `httpflood`, 630 `slowloris` and 120 `icmpflood`. This distribution motivates class weighting and the decision not to claim ICMP as a settled class. Fig. 3 also shows that attack captures retain benign student flows.

4.2 | Portal impact

SYN produces the highest rate, 466 packets/s, yet the probe keeps 120 HTTP 200 responses. HTTP flood raises mean latency from 407 to 564 ms. Slowloris produces only 86 packets/s but occupies available connections and fails 117 of 118 probes. Packet rate alone therefore does not describe application impact.

4.3 | Classifier performance

Macro F1 on Agrarias is 1.000and binary benign-versus-attack F1 is 0.970. The most important features are forward average




FIGURE 2 | Experimental pipeline from the emulated campus to the model. The label comes from the sender, not the capture file.




FIGURE 3 | Benign and attack flows obtained in every scenario.




FIGURE 4 | Eight most important random-forest features.

TABLE 2 | Detection (random forest). Macro F1 1.000.

Clase	Prec.	Recall	F1	Flujos	On the flow
BENIGN	0.956	0.949	0.953	1775	well separated
httpflood	0.939	0.947	0.943	1458	well separated
icmpflood	1.000	1.000	1.000	24	too few flows to claim
slowloris	1.000	1.000	1.000	126	well separated
synflood	1.000	1.000	1.000	4708	well separated

segment size, forward packet-length mean and maximum, forward bytes and packet-size variability. This is consistent with the scenarios: SYN repeatedly sends small segments, HTTP exchanges complete requests and responses, and Slowloris holds connections with little traffic.

4.4 | Testbed consumption

Mean container CPU was 23% for baseline, 26% for SYN, 50% for HTTP, 523% for Slowloris and 26% for ICMP; in Docker, 100% corresponds approximately to one core. Slowloris occupied about five of the six assigned cores, while observed peak memory remained below 200 MiB. These values cover the whole testbed, not only the victim.

4.5 | Discussion

The home test supports the working hypothesis for four defensible classes: macro F1 exceeds 0.90 without IP addresses and transfers to a held-out laboratory. It does not demonstrate real-network deployment or online detection. The contrast between SYN and Slowloris also shows why flow classification should be paired with a service probe: more packets do not necessarily mean lower service availability.




FIGURE 5 | Mean container CPU by scenario.

4.6 | Ongoing research projects using the software

The testbed is used in the authors' undergraduate thesis at the Universidad Nacional del Centro del Perú. The Wireshark capture protocol for the network officer is documented in a separate document distributed with the software.

4.7 | Limitations and future improvements

The table is still computed from emulated students. The hybrid dataset (Wireshark plus simulated attack) is ready in the code and is updated when the authorized pcaps arrive. The reported per-flow result comes from a single 120 s run; the `repeat` driver and the leave-one-run-out cross-validation now make the evaluation repeatable, and the multi-run figures (mean ± standard deviation) are being regenerated. ICMP accounts for 120 flows in the whole set and 24 in the Agrarias test, so its perfect F1 is not reported as a settled class result. The per-window detector is designed for early detection and consumes the controller telemetry that a Ryu-side detector would use, but it still scores already-captured windows offline rather than running inside Ryu. Future work: report the multi-run cross-validated figures and the SDN ablation, repeat the test with the Wireshark background and a mixed four-vector scenario, add more ICMP samples, and move the trained per-window model into the controller for online detection.

4.8 | Conclusions

The run already measured, taken at home inside Docker, is the base of the proposal. In that run the student and the attack share the capture, the model does not use IP addresses, and on Ciencias Agrarias the macro F1 is 1.000. Sender-based labels preserve benign traffic inside an attacked capture; a laboratory holdout is more demanding than a random row split; and availability, packet rate and classification describe different aspects of an incident. Only Slowloris takes the portal down. ICMP is not claimed. This base supports the request for authorized real benign traffic. The simulated attack does not leave the container.

TABLE 3 | Testbed setup requirements.

N.º	Description	Tool	Version
1	Network emulator	Mininet	2.3.0
2	Virtual switch	Open vSwitch	3.3.9
3	SDN controller	Ryu	4.34
4	SYN and ICMP flood	hping3	3.0.0-alpha-2
5	Low-rate attack	slowhttptest	1.9.0
6	Packet capture	tcpdump	4.99.4
7	pcap to CSV	CICFlowMeter	0.5.0
8	Container OS	Ubuntu	24.04

4.9 | List of scholarly publications enabled by this software

There is no other publication yet. This software is what makes the evaluation in this article possible.

5 | Software and hardware requirements

The testbed runs in an Ubuntu 24.04 container. The versions in the table were read inside the `ataque-sdn` image. The model was trained with Python 3.12.3, scikit-learn 1.9.1 and pandas 3.0.6. Ryu uses Python 3.9.25.
A conventional desktop is enough to repeat the run: 8 cores and 16 GB of RAM. Docker Desktop runs on Windows 11 or Ubuntu. The container is given 6 CPUs and 8 GB, and Ubuntu 24.04 runs inside it. Open vSwitch runs in userspace (`datapath netdev`).

ACKNOWLEDGEMENTS

The authors thank the Universidad Nacional del Centro del Perú.

References

1. Diego Kreutz, Fernando M. V. Ramos, Paulo Esteves Veríssimo, Christian Esteve Rothenberg, Siamak Azodolmolky, and Steve Uhlig. Software-defined networking: A comprehensive survey. *Proceedings of the IEEE*, 103(1):14–76, 2015. doi: 10.1109/JPROC.2014.2371999.
2. Sudesh Kumar and Sunanda Gupta. SDN TCP-SYN dataset: A dataset for TCP-SYN flood DDoS attack detection in software-defined networks. *Data in Brief*, 59:111314, 2025. doi: 10.1016/j.dib.2025.111314.
3. Sudesh Kumar and Sunanda Gupta. ICMP-Flood-SDN: A Python based machine learning application for ICMP flood DDoS attack detection in software defined networks. *Software Impacts*, 27:100819, 2026. doi: 10.1016/j.simpa.2026.100819.
4. Iman Sharafaldin, Arash Habibi Lashkari, and Ali A. Ghorbani. Toward generating a new intrusion detection dataset and intrusion traffic characterization. In *Proceedings of the 4th International Conference on Information Systems Security and Privacy (ICISSP)*, pages 108–116, 2018. doi: 10.5220/0006639801080116.
5. Iman Sharafaldin, Arash Habibi Lashkari, Saqib Hakak, and Ali A. Ghorbani. Developing realistic distributed denial of service (DDoS) attack dataset and taxonomy. In *Proceedings of the 53rd IEEE International Carnahan Conference on Security Technology (ICCST)*, pages 1–8, 2019. doi: 10.1109/CCST.2019.8888419.
6. Mahbod Tavallaee, Ebrahim Bagheri, Wei Lu, and Ali A. Ghorbani. A detailed analysis of the KDD CUP 99 data set. In

Proceedings of the 2nd IEEE International Conference on Computational Intelligence for Security and Defense Applications (CISDA), 2009.