

Cristian Mauricio Rodríguez Cruz 00082923

Ejercicio 1 Static

```
84 bytes from 10.21.41.1 icmp_seq=1 ttl=255 time=31.958 ms
84 bytes from 10.21.41.1 icmp_seq=2 ttl=255 time=16.762 ms
84 bytes from 10.21.41.1 icmp_seq=3 ttl=255 time=16.646 ms
84 bytes from 10.21.41.1 icmp_seq=4 ttl=255 time=15.977 ms
84 bytes from 10.21.41.1 icmp_seq=5 ttl=255 time=15.605 ms

PC1> ping 10.21.41.66
10.21.41.66 icmp_seq=1 timeout
84 bytes from 10.21.41.66 icmp_seq=2 ttl=63 time=29.999 ms
84 bytes from 10.21.41.66 icmp_seq=3 ttl=63 time=30.557 ms
84 bytes from 10.21.41.66 icmp_seq=4 ttl=63 time=30.703 ms
84 bytes from 10.21.41.66 icmp_seq=5 ttl=63 time=32.073 ms

PC1> ping 10.21.41.98
10.21.41.98 icmp_seq=1 timeout
84 bytes from 10.21.41.98 icmp_seq=2 ttl=63 time=32.078 ms
84 bytes from 10.21.41.98 icmp_seq=3 ttl=63 time=30.575 ms
84 bytes from 10.21.41.98 icmp_seq=4 ttl=63 time=33.285 ms
84 bytes from 10.21.41.98 icmp_seq=5 ttl=63 time=31.829 ms

PC1>
PC1> ping 10.21.41.114
10.21.41.114 icmp_seq=1 timeout
10.21.41.114 icmp_seq=2 timeout
10.21.41.114 icmp_seq=3 timeout
84 bytes from 10.21.41.114 icmp_seq=4 ttl=61 time=94.386 ms
84 bytes from 10.21.41.114 icmp_seq=5 ttl=61 time=93.120 ms

PC1> trace 10.21.41.114
trace to 10.21.41.114, 8 hops max, press Ctrl+C to stop
 1  10.21.41.1  16.511 ms  14.842 ms  15.440 ms
 2  10.21.41.122  45.624 ms  45.994 ms  46.113 ms
 3  10.21.41.126  76.802 ms  77.191 ms  77.741 ms
 4  *10.21.41.114  92.629 ms (ICMP type:3, code:3, Destination port unreachable)

PC1> █
```

```
o up
*Mar  1 00:01:05.987: %LINK-3-UPDOWN: Interface FastEthernet0/1, changed state t
o up
*Mar  1 00:01:06.511: %LINK-3-UPDOWN: Interface FastEthernet1/0, changed state t
o up
*Mar  1 00:01:06.747: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthern
et0/0, changed state to up
*Mar  1 00:01:06.759: %LINK-3-UPDOWN: Interface FastEthernet2/0, changed state t
o up
R1#wr
*Mar  1 00:01:06.987: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthern
et0/1, changed state to up
*Mar  1 00:01:07.511: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthern
et1/0, changed state to up
*Mar  1 00:01:07.759: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthern
et2/0, changed state to up
R1#
R1#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

  10.0.0.0/8 is variably subnetted, 6 subnets, 5 masks
C       10.21.41.0/26 is directly connected, FastEthernet0/0
S       10.21.41.112/29 [1/0] via 10.21.41.122
S       10.21.41.124/30 [1/0] via 10.21.41.122
C       10.21.41.120/30 is directly connected, FastEthernet2/0
C       10.21.41.96/28 is directly connected, FastEthernet1/0
C       10.21.41.64/27 is directly connected, FastEthernet0/1
R1#
```

```
R2
R3
PC1
R1

R2(config)#ip route 10.21.41.0 255.255.255.192 10.21.41.121
R2(config)#ip route 10.21.41.64 255.255.255.224 10.21.41.121
R2(config)#ip route 10.21.41.96 255.255.255.240 10.21.41.121
R2(config)#ip route 10.21.41.112 255.255.255.248 10.21.41.126
R2(config)#
R2(config)#end
R2#wr
*Mar 1 00:01:39.319: %SYS-5-CONFIG_I: Configured from console by console
R2#wr
Building configuration...
[OK]
R2#
*Mar 1 00:01:40.295: %LINK-3-UPDOWN: Interface FastEthernet0/0, changed state to up
*Mar 1 00:01:40.539: %LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to up
*Mar 1 00:01:41.479: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
*Mar 1 00:01:41.691: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
R2#
R2#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 5 masks
S       10.21.41.0/26 [1/0] via 10.21.41.121
S       10.21.41.112/29 [1/0] via 10.21.41.126
C       10.21.41.124/30 is directly connected, FastEthernet0/1
C       10.21.41.120/30 is directly connected, FastEthernet0/0
S       10.21.41.96/28 [1/0] via 10.21.41.121
S       10.21.41.64/27 [1/0] via 10.21.41.121
R2#
```

solarwinds | Solar-PuTTY free tool

© 2019-2024 SolarWinds Worldwide, LLC. All rights reserved.

```

R3#wr
*Mar 1 00:01:50.963: %LINK-3-UPDOWN: Interface FastEthernet0/0, changed state to up
*Mar 1 00:01:51.211: %LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to up
*Mar 1 00:01:51.963: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
R3#wr
*Mar 1 00:01:52.211: %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
R3#wr
Building configuration...
[OK]
R3#show ip interface briefly
      ^
% Invalid input detected at '^' marker.

R3#show ip interface brief
Interface      IP-Address      OK? Method Status      Protocol
FastEthernet0/0 10.21.41.126    YES manual up          up
FastEthernet0/1 10.21.41.113    YES manual up          up
R3#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 6 subnets, 5 masks
S       10.21.41.0/26 [1/0] via 10.21.41.125
C       10.21.41.112/29 is directly connected, FastEthernet0/1
C       10.21.41.124/30 is directly connected, FastEthernet0/0
S       10.21.41.120/30 [1/0] via 10.21.41.125
S       10.21.41.96/28 [1/0] via 10.21.41.125
S       10.21.41.64/27 [1/0] via 10.21.41.125
R3#
```


Name		Host	Dir	Mass	i host	U/H-Act	Broad
Pc1	50	10.21.41.0	/26	10.21.41.1	10.21.41.62	10.21.41.63	
Pc2	25	10.21.41.64	/27	10.21.41.65	10.21.41.94	10.21.41.95	
Pc3	12	10.21.41.96	/28	10.21.41.97	10.21.41.110	10.21.41.111	
Pc4	6	10.21.41.112	/29	10.21.41.113	10.21.41.117	10.21.41.117	
Pc5	2	10.21.41.120	/30	10.21.41.121	10.21.41.122	10.21.41.123	
Pc6	2	10.21.41.124	/30	10.21.41.125	10.21.41.126	10.21.41.127	

Ejercicio 2 OSPF

```
PC1 : 10.21.41.2 255.255.255.192 gateway 10.21.41.1

PC1> ping 10.21.41.66
10.21.41.66 icmp_seq=1 timeout
10.21.41.66 icmp_seq=2 timeout
84 bytes from 10.21.41.66 icmp_seq=3 ttl=62 time=61.058 ms
84 bytes from 10.21.41.66 icmp_seq=4 ttl=62 time=62.261 ms
84 bytes from 10.21.41.66 icmp_seq=5 ttl=62 time=61.871 ms

PC1> ping 10.21.41.98
10.21.41.98 icmp_seq=1 timeout
84 bytes from 10.21.41.98 icmp_seq=2 ttl=61 time=92.440 ms
84 bytes from 10.21.41.98 icmp_seq=3 ttl=61 time=91.669 ms
84 bytes from 10.21.41.98 icmp_seq=4 ttl=61 time=91.587 ms
84 bytes from 10.21.41.98 icmp_seq=5 ttl=61 time=93.421 ms

PC1> ping 10.21.41.114
10.21.41.114 icmp_seq=1 timeout
84 bytes from 10.21.41.114 icmp_seq=2 ttl=61 time=92.326 ms
84 bytes from 10.21.41.114 icmp_seq=3 ttl=61 time=91.825 ms
84 bytes from 10.21.41.114 icmp_seq=4 ttl=61 time=91.360 ms
84 bytes from 10.21.41.114 icmp_seq=5 ttl=61 time=91.081 ms

PC1> ping 10.21.41.130
10.21.41.130 icmp_seq=1 timeout
84 bytes from 10.21.41.130 icmp_seq=2 ttl=62 time=92.048 ms
84 bytes from 10.21.41.130 icmp_seq=3 ttl=62 time=93.433 ms
84 bytes from 10.21.41.130 icmp_seq=4 ttl=62 time=93.409 ms
84 bytes from 10.21.41.130 icmp_seq=5 ttl=62 time=93.789 ms

PC1> trace 10.21.41.130
trace to 10.21.41.130, 8 hops max, press Ctrl+C to stop
 1  10.21.41.1    14.964 ms  15.297 ms  14.900 ms
 2  10.21.41.158  46.225 ms  45.720 ms  46.285 ms
 3  10.21.41.145  76.127 ms  76.506 ms  76.783 ms
 4  10.21.41.150  75.680 ms  75.637 ms  76.597 ms
 5  *10.21.41.130 90.334 ms (ICMP type:3, code:3, Destination port unreachable)

PC1> █
```

solarwinds | Solar-PuTTY free tool | © 2019-2024 SolarWinds Worldwide, LLC. All rights reserved.

```
et1/0, changed state to up
R1#wr
Building configuration...
[OK]
R1#
*Mar  1 00:01:41.695: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.158 on FastEtherne
t1/0 from LOADING to FULL, Loading Done
R1#
*Mar  1 00:01:58.063: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.149 on FastEtherne
t0/1 from LOADING to FULL, Loading Done
R1#show ip ospf neighbor

Neighbor ID      Pri   State           Dead Time   Address        Interface
10.21.41.158      1    FULL/DR         00:00:38    10.21.41.142   FastEthernet1/0
10.21.41.149      1    FULL/DR         00:00:32    10.21.41.138   FastEthernet0/1
R1#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 11 subnets, 5 masks
O    10.21.41.0/26 [110/12] via 10.21.41.142, 00:02:58, FastEthernet1/0
C    10.21.41.112/28 is directly connected, FastEthernet0/0
O    10.21.41.96/28 [110/12] via 10.21.41.142, 00:04:01, FastEthernet1/0
O    10.21.41.64/27 [110/11] via 10.21.41.142, 00:04:28, FastEthernet1/0
O    10.21.41.148/30 [110/3] via 10.21.41.142, 00:03:43, FastEthernet1/0
O    10.21.41.144/30 [110/2] via 10.21.41.142, 00:04:28, FastEthernet1/0
O    10.21.41.156/30 [110/2] via 10.21.41.142, 00:04:30, FastEthernet1/0
O    10.21.41.152/30 [110/4] via 10.21.41.142, 00:03:35, FastEthernet1/0
O    10.21.41.128/29 [110/13] via 10.21.41.142, 00:03:35, FastEthernet1/0
C    10.21.41.140/30 is directly connected, FastEthernet1/0
C    10.21.41.136/30 is directly connected, FastEthernet0/1
R1#
```

solarwinds | Solar-PuTTY free tool | © 2019-2024 SolarWinds Worldwide, LLC. All rights reserved.


```

R2#
*Mar 1 00:01:31.635: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.141 on FastEtherne
t0/1 from LOADING to FULL, Loading Done
R2#
*Mar 1 00:01:51.023: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.149 on FastEtherne
t1/0 from LOADING to FULL, Loading Done
R2#
*Mar 1 00:02:53.791: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.157 on FastEtherne
t2/0 from LOADING to FULL, Loading Done
R2#show ip ospf neighbor

Neighbor ID      Pri   State           Dead Time   Address        Interface
10.21.41.157     1     FULL/BDR        00:00:36   10.21.41.157   FastEthernet2/0
10.21.41.149     1     FULL/BDR        00:00:34   10.21.41.145   FastEthernet1/0
10.21.41.141     1     FULL/BDR        00:00:39   10.21.41.141   FastEthernet0/1
R2#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 11 subnets, 5 masks
O    10.21.41.0/26 [110/11] via 10.21.41.157, 00:03:23, FastEthernet2/0
O    10.21.41.112/28 [110/20] via 10.21.41.141, 00:04:53, FastEthernet0/1
O    10.21.41.96/28 [110/11] via 10.21.41.145, 00:04:27, FastEthernet1/0
C    10.21.41.64/27 is directly connected, FastEthernet0/0
O    10.21.41.148/30 [110/2] via 10.21.41.145, 00:04:08, FastEthernet1/0
C    10.21.41.144/30 is directly connected, FastEthernet1/0
C    10.21.41.156/30 is directly connected, FastEthernet2/0
O    10.21.41.152/30 [110/3] via 10.21.41.145, 00:04:00, FastEthernet1/0
O    10.21.41.128/29 [110/12] via 10.21.41.145, 00:04:00, FastEthernet1/0
C    10.21.41.140/30 is directly connected, FastEthernet0/1
O    10.21.41.136/30 [110/11] via 10.21.41.145, 00:04:29, FastEthernet1/0
R2#
```

```

C 10.21.41.148/30 is directly connected, FastEthernet2/0
C 10.21.41.144/30 is directly connected, FastEthernet1/0
O 10.21.41.156/30 [110/2] via 10.21.41.146, 00:04:51, FastEthernet1/0
O 10.21.41.152/30 [110/2] via 10.21.41.150, 00:04:32, FastEthernet2/0
O 10.21.41.128/29 [110/11] via 10.21.41.150, 00:04:32, FastEthernet2/0
O 10.21.41.140/30 [110/11] via 10.21.41.146, 00:04:51, FastEthernet1/0
[110/11] via 10.21.41.137, 00:05:01, FastEthernet0/1

R3#show ip ospf neighbor

Neighbor ID Pri State Dead Time Address Interface
10.21.41.153 1 FULL/DR 00:00:32 10.21.41.150 FastEthernet2/0
10.21.41.158 1 FULL/DR 00:00:33 10.21.41.146 FastEthernet1/0
10.21.41.141 1 FULL/BDR 00:00:35 10.21.41.137 FastEthernet0/1

R3#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 11 subnets, 5 masks
O 10.21.41.0/26 [110/12] via 10.21.41.150, 00:04:13, FastEthernet2/0
[110/12] via 10.21.41.146, 00:04:03, FastEthernet1/0
O 10.21.41.112/28 [110/20] via 10.21.41.137, 00:05:16, FastEthernet0/1
C 10.21.41.96/28 is directly connected, FastEthernet0/0
O 10.21.41.64/27 [110/11] via 10.21.41.146, 00:05:06, FastEthernet1/0
C 10.21.41.148/30 is directly connected, FastEthernet2/0
C 10.21.41.144/30 is directly connected, FastEthernet1/0
O 10.21.41.156/30 [110/2] via 10.21.41.146, 00:05:08, FastEthernet1/0
O 10.21.41.152/30 [110/2] via 10.21.41.150, 00:04:50, FastEthernet2/0
O 10.21.41.128/29 [110/11] via 10.21.41.150, 00:04:50, FastEthernet2/0
O 10.21.41.140/30 [110/11] via 10.21.41.146, 00:05:08, FastEthernet1/0
[110/11] via 10.21.41.137, 00:05:18, FastEthernet0/1
C 10.21.41.136/30 is directly connected, FastEthernet0/1
R3#
```

```
et1/0, changed state to up
R4#wr
Building configuration...
[OK]
R4#
R4#
*Mar 1 00:01:46.271: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.149 on FastEtherne
t0/1 from LOADING to FULL, Loading Done
R4#
*Mar 1 00:02:21.383: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.157 on FastEtherne
t1/0 from LOADING to FULL, Loading Done
R4# show ip ospf neighbor

Neighbor ID      Pri   State           Dead Time   Address        Interface
10.21.41.157     1     FULL/BDR        00:00:35    10.21.41.154   FastEthernet1/0
10.21.41.149     1     FULL/BDR        00:00:32    10.21.41.149   FastEthernet0/1
R4#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 11 subnets, 5 masks
O       10.21.41.0/26 [110/11] via 10.21.41.154, 00:04:39, FastEthernet1/0
O       10.21.41.112/28 [110/22] via 10.21.41.154, 00:04:29, FastEthernet1/0
O       10.21.41.96/28 [110/13] via 10.21.41.154, 00:04:29, FastEthernet1/0
O       10.21.41.64/27 [110/12] via 10.21.41.154, 00:04:29, FastEthernet1/0
C       10.21.41.148/30 is directly connected, FastEthernet0/1
O       10.21.41.144/30 [110/3] via 10.21.41.154, 00:04:29, FastEthernet1/0
O       10.21.41.156/30 [110/2] via 10.21.41.154, 00:04:30, FastEthernet1/0
C       10.21.41.152/30 is directly connected, FastEthernet1/0
C       10.21.41.128/29 is directly connected, FastEthernet0/0
O       10.21.41.140/30 [110/12] via 10.21.41.154, 00:04:30, FastEthernet1/0
O       10.21.41.136/30 [110/13] via 10.21.41.154, 00:04:30, FastEthernet1/0
R4#
```

solarwinds | Solar-PuTTY *free tool* © 2019-2024 SolarWinds Worldwide, LLC. All rights reserved.

```
et1/0, changed state to up
R5#wr
Building configuration...
[OK]
R5#
*Mar  1 00:02:01.359: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.153 on FastEtherne
t0/1 from LOADING to FULL, Loading Done
R5#
*Mar  1 00:02:03.391: %OSPF-5-ADJCHG: Process 1, Nbr 10.21.41.158 on FastEtherne
t1/0 from LOADING to FULL, Loading Done
R5#
R5#show ip ospf neighbor

Neighbor ID      Pri   State           Dead Time   Address        Interface
10.21.41.158     1     FULL/DR         00:00:35    10.21.41.158   FastEthernet1/0
10.21.41.153     1     FULL/DR         00:00:34    10.21.41.153   FastEthernet0/1
R5#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 11 subnets, 5 masks
C       10.21.41.0/26 is directly connected, FastEthernet0/0
O       10.21.41.112/28 [110/21] via 10.21.41.158, 00:04:58, FastEthernet1/0
O       10.21.41.96/28 [110/12] via 10.21.41.158, 00:04:58, FastEthernet1/0
O       10.21.41.64/27 [110/11] via 10.21.41.158, 00:04:58, FastEthernet1/0
O       10.21.41.148/30 [110/3] via 10.21.41.158, 00:04:58, FastEthernet1/0
O       10.21.41.144/30 [110/2] via 10.21.41.158, 00:04:58, FastEthernet1/0
C       10.21.41.156/30 is directly connected, FastEthernet1/0
C       10.21.41.152/30 is directly connected, FastEthernet0/1
O       10.21.41.128/29 [110/13] via 10.21.41.158, 00:05:00, FastEthernet1/0
O       10.21.41.140/30 [110/11] via 10.21.41.158, 00:05:00, FastEthernet1/0
O       10.21.41.136/30 [110/12] via 10.21.41.158, 00:05:00, FastEthernet1/0
R5#
```


10.21.41.0/24 = 1st 10.21.41.0/24							
/24 / 255.255.255.0							
Nom	Host	Dir	mask	1st host	VA host	Broad	
PC1	50	10.21.41.0	/20	10.21.41.1	10.21.41.62	10.21.41.63	
			25				
PC2	25	10.21.41.64	/27	10.21.41.65	10.21.41.94	10.21.41.95	
PC3	12	10.21.41.96	/28	10.21.41.97	10.21.41.110	10.21.41.111	
PC4	6	10.21.41.112	/29	10.21.41.113	10.21.41.119	10.21.41.120	
R1-R2	2	10.21.41.120	/30	10.21.41.121	10.21.41.122	10.21.41.123	
R2-R3	2	10.21.41.124	/30	10.21.41.125	10.21.41.126	10.21.41.127	