

Branch and Bound (1)

By: Aminul Islam

Based on Chapter 6 of Foundations of Algorithms

Objectives

Objectives

- Describe the branch-and-bound technique for solving optimization problems
- Contrast the branch-and-bound technique with the backtracking
- Apply the branch-and-bound technique to solve the 0-1 Knapsack Problem

Branch-and-Bound Design Strategy

Branch-and-Bound Design Strategy

- Branch-and-bound design strategy is similar to backtracking

Branch-and-Bound Design Strategy

- Branch-and-bound design strategy is similar to backtracking
 - State space tree used to solve problem

Branch-and-Bound Design Strategy

- Branch-and-bound design strategy is similar to backtracking
 - State space tree used to solve problem
- Difference between branch-and-bound and backtracking:

Branch-and-Bound Design Strategy

- Branch-and-bound design strategy is similar to backtracking
 - State space tree used to solve problem
- Difference between branch-and-bound and backtracking:
 1. branch-and-bound is not limited to a particular tree traversal

Branch-and-Bound Design Strategy

- Branch-and-bound design strategy is similar to backtracking
 - State space tree used to solve problem
- Difference between branch-and-bound and backtracking:
 1. branch-and-bound is not limited to a particular tree traversal
 2. branch-and-bound is usually used for optimization problems

Branch-and-Bound Design Strategy (2)

Branch-and-Bound Design Strategy (2)

- **Bound** (which is generally a number) is computed at a node to determine whether the node is promising

Branch-and-Bound Design Strategy (2)

- **Bound** (which is generally a number) is computed at a node to determine whether the node is promising
- **Bound** indicates the value of the solution that could be obtained by expanding beyond the node.

Branch-and-Bound Design Strategy (2)

- **Bound** (which is generally a number) is computed at a node to determine whether the node is promising
- **Bound** indicates the value of the solution that could be obtained by expanding beyond the node.
 - We had a similar concept in “upper bound” of 0-1 Knapsack using Backtracking

Branch-and-Bound Design Strategy (2)

- **Bound** (which is generally a number) is computed at a node to determine whether the node is promising
- **Bound** indicates the value of the solution that could be obtained by expanding beyond the node.
 - We had a similar concept in “upper bound” of 0-1 Knapsack using Backtracking
- If **Bound** is not better than the value of the **best** solution found so far, node is non-promising

Branch-and-Bound Design Strategy (2)

- **Bound** (which is generally a number) is computed at a node to determine whether the node is promising
- **Bound** indicates the value of the solution that could be obtained by expanding beyond the node.
 - We had a similar concept in “upper bound” of 0-1 Knapsack using Backtracking
- If **Bound** is not better than the value of the **best** solution found so far, node is non-promising
 - Otherwise, the node is promising

Breadth-first Search Tree

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree
- Recap of the breadth-first search

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree
- Recap of the breadth-first search
 - Use Queue - FIFO

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree
- Recap of the breadth-first search
 - Use Queue - FIFO
 - Visit root first

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree
- Recap of the breadth-first search
 - Use Queue - FIFO
 - Visit root first
 - Visit all nodes at level 1 next

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree
- Recap of the breadth-first search
 - Use Queue - FIFO
 - Visit root first
 - Visit all nodes at level 1 next
 - Visit all nodes at level 2 next

Breadth-first Search Tree

- Branch and Bound uses (variations) of breadth-first search on the tree
- Recap of the breadth-first search
 - Use Queue - FIFO
 - Visit root first
 - Visit all nodes at level 1 next
 - Visit all nodes at level 2 next
 - Visit all nodes at level n

General Branch and Bound Structure based on Breadth First Search

General Branch and Bound Structure based on Breadth First Search

```
void breadth_first_branch_and_bound (state_space_tree T,  
                                     number& best)  
{  
    queue_of_node Q;  
    node u, v;  
  
    initialize(Q);  
    v = root of T;  
    enqueue(Q, v);  
    best = value(v);  
    while (! empty(Q)){  
        dequeue(Q, v);  
        for (each child u of v){  
            if (value(u) is better than best)  
                best = value(u);  
            if (bound(u) is better than best)  
                enqueue(Q, u);  
        }  
    }  
}
```

General Branch and Bound Structure based on Breadth First Search

```
void breadth_first_branch_and_bound (state_space_tree T,  
                                     number& best)  
{  
    queue_of_node Q;  
    node u, v;  
  
    initialize(Q);    // Make an empty queue  
    v = root of T;  
    enqueue(Q, v);  
    best = value(v);  
    while (! empty(Q)){  
        dequeue(Q, v);  
        for (each child u of v){  
            if (value(u) is better than best)  
                best = value(u);  
            if (bound(u) is better than best)  
                enqueue(Q, u);  
        }  
    }  
}
```

General Branch and Bound Structure based on Breadth First Search

```
void breadth_first_branch_and_bound (state_space_tree T,  
                                     number& best)  
{  
    queue_of_node Q;  
    node u, v;  
  
    initialize(Q);           // Make an empty queue  
    v = root of T;  
    enqueue(Q, v);  
    best = value(v);  
    while (! empty(Q)){  
        dequeue(Q, v);  
        for (each child u of v){  
            if (value(u) is better than best)  // Check if a better  
                best = value(u);              // solution is found  
            if (bound(u) is better than best)  
                enqueue(Q, u);  
        }  
    }  
}
```

General Branch and Bound Structure based on Breadth First Search

```
void breadth_first_branch_and_bound (state_space_tree T,  
                                     number& best)  
{  
    queue_of_node Q;  
    node u, v;  
  
    initialize(Q);           // Make an empty queue  
    v = root of T;  
    enqueue(Q, v);  
    best = value(v);  
    while (! empty(Q)){  
        dequeue(Q, v);  
        for (each child u of v){  
            if (value(u) is better than best)           // Check if a better  
                best = value(u);                        // solution is found  
            if (bound(u) is better than best)           // Check if promising  
                enqueue(Q, u);  
        }  
    }  
}
```

0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

- Similar to the Backtracking version but breadth-first rather than depth-first

0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

- Similar to the Backtracking version but breadth-first rather than depth-first
- Let *weight* and *profit* be the total weight and total profit of the items that have been included up to a node.

Determine if a Node is Promising

Determine if a Node is Promising

Promising cases (Same as backtracking):

Determine if a Node is Promising

Promising cases (Same as backtracking):

- Sum of the weights up to the node $< W$ (i.e, knapsack capacity)

Determine if a Node is Promising

Promising cases (Same as backtracking):

- Sum of the weights up to the node $< W$ (i.e, knapsack capacity)
- A node at level i is promising if:
(upper bound) $_i > \text{maxprofit}$

Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

$$n = 4, W = 16$$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit =

Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

$n = 4, W = 16$

\$0
0
\$115

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:


- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$0

Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2



Promising:


- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$40

Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound

$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2



Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$40

Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$$n = 4, W = 16$$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$$n = 4, W = 16$$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Example of 0-1 Knapsack Problem using Breadth-First Search with Branch and Bound


$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Summary of breadth-first search with Branch-and-Bound Pruning

Summary of breadth-first search with Branch-and-Bound Pruning

- In general, Breadth-First Search strategy has no advantage over a depth-first search (backtracking)

Summary of breadth-first search with Branch-and-Bound Pruning

- In general, Breadth-First Search strategy has no advantage over a depth-first search (backtracking)
- However, we can improve our search by using our **bound** to do more than just determine whether a node is promising.

Use Bound to Improve Search

Use Bound to Improve Search

- Why not using **Bound** to guide us to the solution quicker?

Use Bound to Improve Search

- Why not using **Bound** to guide us to the solution quicker?
 - The node with a higher **Bound** will have a better potential for an optimal solution.

Use Bound to Improve Search

- Why not using **Bound** to guide us to the solution quicker?
 - The node with a higher **Bound** will have a better potential for an optimal solution.
- Order for expansion can be determined by the best bound rather than pre-determined methods (i.e., DFS or BFS)

Use Bound to Improve Search

- Why not using **Bound** to guide us to the solution quicker?
 - The node with a higher **Bound** will have a better potential for an optimal solution.
- Order for expansion can be determined by the best bound rather than pre-determined methods (i.e., DFS or BFS)
- Use priority queue for implementation

Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$$n = 4, W = 16$$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit =

Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4, W = 16$

\$0
0
\$115

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:


- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$0

Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4, W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2



- Determine promising, unexpanded node with the greatest bound

Promising:


- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$40

Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4$, $W = 16$

Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2



- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$40

Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4, W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4$, $W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$70



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4, W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$70



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4, W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$70



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4, W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4$, $W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$90



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4$, $W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$90



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4$, $W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound > maxprofit
- (current node) weight < W

maxprofit = \$90



Example of 0-1 Knapsack Problem using Best-First Search with Branch and Bound

$n = 4$, $W = 16$


Item i	P_i	W_i	P_i/W_i
1	40	2	20
2	30	5	6
3	50	10	5
4	10	5	2

- Determine promising, unexpanded node with the greatest bound

Promising:

- (current node) bound $>$ maxprofit
- (current node) weight $< W$

maxprofit = \$90



General Algorithm for B&B based on Best First Search

General Algorithm for B&B based on Best First Search

```
void best-first-branch-and-bound (state-space-tree T,  
                                number& best)  
{  
    priority-queue-of-node PQ;  
    node u, v;  
  
    initialize(PQ);  
    v = root of T;  
    best = value(v);  
    insert(PQ, v);  
    while (! empty(PQ)){  
        remove(PQ, v);  
        if (bound(v) is better than best)  
            for (each child u of v){  
                if (value(u) is better than best)  
                    (best = value(u));  
                if (bound(u) is better than best)  
                    insert(PQ, u);  
            }  
    }  
}
```

General Algorithm for B&B based on Best First Search

```
void best_first_branch_and_bound (state_space_tree T,  
                                number& best)  
{  
    priority_queue_of_node PQ; // Priority queue  
    node u, v;                // instead of a  
                                // normal queue  
  
    initialize(PQ);  
    v = root of T;  
    best = value(v);  
    insert(PQ, v);  
    while (! empty(PQ)){  
        remove(PQ, v);  
        if (bound(v) is better than best)  
            for (each child u of v){  
                if (value(u) is better than best)  
                    (best = value(u);  
                if (bound(u) is better than best)  
                    insert(PQ, u);  
            }  
    }  
}
```

General Algorithm for B&B based on Best First Search

```
void best_first_branch_and_bound (state_space_tree T,  
                                number& best)  
{  
    priority_queue_of_node PQ; // Priority queue  
    node u, v;                // instead of a  
                                // normal queue  
  
    initialize(PQ);  
    v = root of T;  
    best = value(v);  
    insert(PQ, v);  
    while (!empty(PQ)){ // Check if the node  
        remove(PQ, v);  // is still promising  
        if (bound(v) is better than best)  
            for (each child u of v){  
                if (value(u) is better than best)  
                    (best = value(u);  
                if (bound(u) is better than best)  
                    insert(PQ, u);  
            }  
    }  
}
```


B&B Algorithm based on Best First Search to Solve 0-1 Knapsack Problem

B&B Algorithm based on Best First Search to Solve 0-1 Knapsack Problem

```
void knapsack3 (int n,  
                const int p[], const int w[],  
                int W,  
                int& maxprofit)  
{  
    priority_queue_of_node PQ;  
    node u, v;  
  
    initialize(PQ);  
    v.level = 0; v.profit = 0; v.weight = 0;  
    maxprofit = 0;  
    v.bound = bound(v);  
    insert(PQ, v);
```

Continue ...

Continue ...

```
while (!empty(PQ)){
    remove(PQ, v);
    if (v.bound > maxprofit){
        u.level = v.level + 1;
        u.weight = v.weight + w[u.level];
        u.profit = v.profit + p[u.level];

        if (u.weight <= W && u.profit > maxprofit)
            maxprofit = u.profit;
        u.bound = bound(u);
        if (u.bound > maxprofit)
            insert(PQ, u);
        u.weight = v.weight;
        u.profit = v.profit;
        u.bound = bound(u);
        if (u.bound > maxprofit)
            insert(PQ, u);
    }
}
```


Bound Function for the 0-1 Knapsack Problem

Bound Function for the 0-1 Knapsack Problem

```
float bound (node u)
{
    index j, k;
    int totweight;
    float result;
    if (u.weight >= W)
        return 0;
    else{
        result = u.profit;
        j = u.level + 1;
        totweight = u.weight;
        while (j <= n && totweight + w[j] <= W){
            totweight = totweight + w[j];
            result = result + p[j];
            j++;
        }
        k = j;
        if (k <= n)
            result = result + (W - totweight) * p[k];
        return result;
    }
}
```


Time Complexity and Space Complexity of **Breadth-First Search**

Time Complexity and Space Complexity of Breadth-First Search



Time Complexity and Space Complexity of Breadth-First Search

Time
Complexity
 $= O(b^d)$



Time Complexity and Space Complexity of Breadth-First Search

Time


Complexity

$$= O(b^d)$$

Space


Complexity

$$= O(b^d)$$




Time Complexity and Space Complexity of **Depth-First Search**

Time Complexity and Space Complexity of Depth-First Search




Time Complexity and Space Complexity of Depth-First Search

Time
Complexity
 $= O(b^d)$



Time Complexity and Space Complexity of Depth-First Search

Time
Complexity
 $= O(b^d)$



Time Complexity and Space Complexity of Depth-First Search

Time


Complexity

$$= O(b^d)$$

Space


Complexity

$$= O(bd)$$



Time Complexity and Space Complexity of **Best-First Search**

Time Complexity and Space Complexity of Best-First Search




Time Complexity and Space Complexity of Best-First Search

Worst case

Time

Complexity

$$= O(b^m)$$



Time Complexity and Space Complexity of Best-First Search

Worst case

Time

Complexity

$$= O(b^m)$$

Worst case

Space

Complexity

$$= O(b^m)$$

