Computational Complexity and Intractability

By: Aminul Islam

Based on Chapter 9 of Foundations of Algorithms

Objectives

Objectives

- Classify problems as tractable or intractable
- Define decision problems
- Define the class P
- Define the class NP
- Define the class of NP-Complete

A problem is tractable if there exists a polynomial-bound algorithm that solves it.

- A problem is tractable if there exists a polynomial-bound algorithm that solves it.
- $P(n) = a_n n^k + \dots a_1 n + a_0$ where k is a constant

- A problem is tractable if there exists a polynomial-bound algorithm that solves it.
- $P(n) = a_n n^k + \dots a_1 n + a_0$ where k is a constant
- $P(n) \in \Theta(n^k)$

- A problem is tractable if there exists a polynomial-bound algorithm that solves it.
- $P(n) = a_n n^k + \dots a_1 n + a_0$ where k is a constant
- $P(n) \in \Theta(n^k)$
- \blacksquare $n \lg n$ is not a ploynomial

- A problem is tractable if there exists a polynomial-bound algorithm that solves it.
- $P(n) = a_n n^k + \dots a_1 n + a_0$ where k is a constant
- $P(n) \in \Theta(n^k)$
- \blacksquare $n \lg n$ is not a ploynomial
 - $n \lg n < n^2$

- A problem is tractable if there exists a polynomial-bound algorithm that solves it.
- $P(n) = a_n n^k + \dots a_1 n + a_0$ where k is a constant
- $P(n) \in \Theta(n^k)$
- \blacksquare $n \lg n$ is not a ploynomial
 - $n \lg n < n^2$ bound by a polynomial

■ Means "difficult to treat or work"

- Means "difficult to treat or work"
- A problem is intractable if a computer has difficulty solving it

- Means "difficult to treat or work"
- A problem is intractable if a computer has difficulty solving it
- A problem is intractable if it is not tractable

- Means "difficult to treat or work"
- A problem is intractable if a computer has difficulty solving it
- A problem is intractable if it is not tractable
- Any algorithm with a growth rate not bounded by a polynomial

- Means "difficult to treat or work"
- A problem is intractable if a computer has difficulty solving it
- A problem is intractable if it is not tractable
- Any algorithm with a growth rate not bounded by a polynomial
 - c^n , $c^{0.01n}$, $n^{\lg n}$, n!

- Means "difficult to treat or work"
- A problem is intractable if a computer has difficulty solving it
- A problem is intractable if it is not tractable
- Any algorithm with a growth rate not bounded by a polynomial
 - c^n , $c^{0.01n}$, $n^{\lg n}$, n!
- It is the property of the problem not the algorithm

1. Problems for which polynomial-time algorithms have been found

- Problems for which polynomial-time algorithms have been found
- 2. Problems that have been proven to be intractable

- Problems for which polynomial-time algorithms have been found
- 2. Problems that have been proven to be intractable
- 3. Problems that have not been proven to be intractable, but for which polynomial-time algorithms have never been found

■ Traveling salesperson

- Traveling salesperson
- 0-1 Knapsack

- Traveling salesperson
- 0-1 Knapsack
- Sum of subsets

- Traveling salesperson
- 0-1 Knapsack
- Sum of subsets
- Graph coloring

- Traveling salesperson
- 0-1 Knapsack
- Sum of subsets
- Graph coloring
- . . .

Define

Define

- Decision problems
- The class P
- Nondeterministic algorithms
- The class NP
- Polynomial transformations
- The class of NP-Complete

■ Problem where the output is a simple "yes" or "no"

- Problem where the output is a simple "yes" or "no"
- Theory of NP-completeness is developed by restricting problems to decision problems

- Problem where the output is a simple "yes" or "no"
- Theory of NP-completeness is developed by restricting problems to decision problems
- Optimization problems can be transformed into decision problems

- Problem where the output is a simple "yes" or "no"
- Theory of NP-completeness is developed by restricting problems to decision problems
- Optimization problems can be transformed into decision problems
- Optimization problems are at least as hard as the associated decision problem

- Problem where the output is a simple "yes" or "no"
- Theory of NP-completeness is developed by restricting problems to decision problems
- Optimization problems can be transformed into decision problems
- Optimization problems are at least as hard as the associated decision problem
- If polynomial-time algorithm for the optimization problem is found, we would have a polynomial-time algorithm for the corresponding decision problem



■ Traveling Salesperson

- Traveling Salesperson
 - For a given positive number d, is there a tour having length
 d ?

- Traveling Salesperson
 - For a given positive number d, is there a tour having length
 d ?
- 0-1 Knapsack

- Traveling Salesperson
 - For a given positive number d, is there a tour having length
 d ?
- 0-1 Knapsack
 - For a given profit P, is it possible to load the knapsack such that total weight <= W?

■ The set of all decision problems that can be solved by polynomial-time algorithms

- The set of all decision problems that can be solved by polynomial-time algorithms
- Decision versions of searching, shortest path, spanning tree, etc. belong to P

- The set of all decision problems that can be solved by polynomial-time algorithms
- Decision versions of searching, shortest path, spanning tree, etc. belong to P
- Do problems such as traveling salesperson and 0-1 Knapsack (no polynomial-time algorithm has been found), etc., belong to P?

- The set of all decision problems that can be solved by polynomial-time algorithms
- Decision versions of searching, shortest path, spanning tree, etc. belong to P
- Do problems such as traveling salesperson and 0-1 Knapsack (no polynomial-time algorithm has been found), etc., belong to P?
 - No one knows

- The set of all decision problems that can be solved by polynomial-time algorithms
- Decision versions of searching, shortest path, spanning tree, etc. belong to P
- Do problems such as traveling salesperson and 0-1 Knapsack (no polynomial-time algorithm has been found), etc., belong to P?
 - No one knows
 - To know a decision problem is not in P, it must be proven it is not possible to develop a polynomial-time algorithm to solve it

For a problem to be in NP, there must be an algorithm that does the verification of results in polynomial time

- For a problem to be in NP, there must be an algorithm that does the verification of results in polynomial time
 - You cannot solve the problem in polynomial time

- For a problem to be in NP, there must be an algorithm that does the verification of results in polynomial time
 - You cannot solve the problem in polynomial time
 - BUT, if you have a solution, you can verify its correctness

- For a problem to be in NP, there must be an algorithm that does the verification of results in polynomial time
 - You cannot solve the problem in polynomial time
 - BUT, if you have a solution, you can verify its correctness
- For instance <u>Traveling salesperson decision problem</u> belongs to NP

It has not been proven that there is a problem in NP that is not in P


- It has not been proven that there is a problem in NP that is not in P
- NP-P may be empty

- It has not been proven that there is a problem in NP that is not in P
- NP-P may be empty
- P=NP? One of the most important questions in CS

- It has not been proven that there is a problem in NP that is not in P
- NP-P may be empty
- P=NP? One of the most important questions in CS
- To show P!=NP, find a problem in NP that is not in P

- It has not been proven that there is a problem in NP that is not in P
- NP-P may be empty
- P=NP? One of the most important questions in CS
- To show P!=NP, find a problem in NP that is not in P
- To show P = NP, find polynomial-time algorithm for each problem in NP

- It has not been proven that there is a problem in NP that is not in P
- NP-P may be empty
- P=NP? One of the most important questions in CS
- To show P!=NP, find a problem in NP that is not in P
- To show P = NP, find polynomial-time algorithm for each problem in NP



■ NP-Compete are problems that other NP problems can be reduced to them

- NP-Compete are problems that other NP problems can be reduced to them
- How to prove that a problem is NP-complete?

- NP-Compete are problems that other NP problems can be reduced to them
- How to prove that a problem is NP-complete?
 - Suppose that you want to know if problem B is NP-complete or not?

- NP-Compete are problems that other NP problems can be reduced to them
- How to prove that a problem is NP-complete?
 - Suppose that you want to know if problem B is NP-complete or not?
 - You know problem A as an NP-complete problem

- NP-Compete are problems that other NP problems can be reduced to them
- How to prove that a problem is NP-complete?
 - Suppose that you want to know if problem B is NP-complete or not?
 - You know problem A as an NP-complete problem
 - If you can reduce problem A to B, you have proved that B is also NP-complete