

# LFTS - Integrate the Design

---

## 31. Convert the HTML and CSS to Blade

Agarramos un código de un repositorio que nos brindan y empezamos a modificar nuestro código HTML con este acomodándolo según especificaciones de blade

```
<x-layout>
  @include ('_posts-header')

  <main class="max-w-6xl mx-auto mt-6 lg:mt-20 space-y-6">
    <x-post-featured-card />

    <div class="lg:grid lg:grid-cols-2">
      <x-post-card />
      <x-post-card />
    </div>

    <div class="lg:grid lg:grid-cols-3">
      <x-post-card />
      <x-post-card />
      <x-post-card />
    </div>
  </main>
</body>
```

```

<article
  class="transition-colors duration-300 hover:bg-gray-100 border border-black border-opacity-0 hover:border-opacity-5 rounded-xl">
  <div class="py-6 px-5">
    <div>
      
    </div>

    <div class="mt-8 flex flex-col justify-between">
      <header>
        <div class="space-x-2">
          <a href="#"
            class="px-3 py-1 border border-blue-300 rounded-full text-blue-300 text-xs uppercase font-semibold"
            style="font-size: 10px">Techniques</a>
          <a href="#"
            class="px-3 py-1 border border-red-300 rounded-full text-red-300 text-xs uppercase font-semibold"
            style="font-size: 10px">Updates</a>
        </div>

        <div class="mt-4">
          <h1 class="text-3xl">
            This is a big title and it will look great on two or even three lines. Woohoo!
          </h1>

          <span class="mt-2 block text-gray-400 text-xs">
            Published <time>1 day ago</time>
          </span>
        </div>
      </header>

      <div class="text-sm mt-4">
        <p>
          Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt
          ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation
          ullamco laboris nisi ut aliquip ex ea commodo consequat.
        </p>

        <p class="mt-4">
          Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla
          pariatur.
        </p>
      </div>

      <footer class="flex justify-between items-center mt-8">
        <div class="flex items-center text-sm">
          
          <div class="ml-3">
            <h5 class="font-bold">Lary Laracore</h5>
            <h6>Mascot at Laracasts</h6>
          </div>
        </div>

        <div>
          <a href="#"
            class="transition-colors duration-300 text-xs font-semibold bg-gray-200 hover:bg-gray-300 rounded-full py-2 px-8">Read
            More</a>
        </div>
      </footer>
    </div>
  </div>
</article>

```

```
1 <article class="transition-colors duration-300 hover:bg-gray-100 border border-black border-opacity-0 hover:border-opacity-5 rounded-xl">
2   <div class="py-6 px-5 lg:flex">
3     <div class="flex-1 lg:mr-8">
4       
5     </div>
6
7     <div class="flex-1 flex flex-col justify-between">
8       <header class="mt-8 lg:mt-0">
9         <div class="space-x-2">
10           <a href="#" class="px-3 py-1 border border-blue-300 rounded-full text-blue-300 text-xs uppercase font-semibold" style="font-size: 10px">Techniques</a>
11           <a href="#" class="px-3 py-1 border border-red-300 rounded-full text-red-300 text-xs uppercase font-semibold" style="font-size: 10px">Updates</a>
12         </div>
13
14         <div class="mt-4">
15           <h1 class="text-3xl">
16             This is a big title and it will look great on two or even three lines. Wooohoo!
17           </h1>
18
19           <span class="mt-2 block text-gray-400 text-xs">
20             Published <time>1 day ago</time>
21           </span>
22         </div>
23       </header>
24
25       <div class="text-sm mt-2">
26         <p>
27           Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt
28           ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation
29           ullamco laboris nisi ut aliquip ex ea commodo consequat.
30         </p>
31
32         <p class="mt-4">
33           Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.
34         </p>
35       </div>
36
37       <footer class="flex justify-between items-center mt-8">
38         <div class="flex items-center text-sm">
39           
40           <div class="ml-3">
41             <h5 class="font-bold">Lary Laracore</h5>
42             <h6>Mascot at Laracasts</h6>
43           </div>
44         </div>
45
46         <div class="hidden lg:block">
47           <a href="#" class="transition-colors duration-300 text-xs font-semibold bg-gray-200 hover:bg-gray-300 rounded-full py-2 px-8">Read More</a>
48         </div>
49       </footer>
50     </div>
51   </div>
52 </article>
```

```

<header class="max-w-xl mx-auto mt-20 text-center">
  <h1 class="text-4xl">
    Latest <span class="text-blue-500">Laravel From Scratch</span> News
  </h1>

  <h2 class="inline-flex mt-2">By Lary Laracore </h2>

  <p class="text-sm mt-14">
    Another year. Another update. We're refreshing the popular Laravel series with new content.
    I'm going to keep you guys up to speed with what's going on!
  </p>

  <div class="space-y-2 lg:space-y-0 lg:space-x-4 mt-8">
    <!-- Category -->
    <div class="relative flex lg:inline-flex items-center bg-gray-100 rounded-xl">
      <select class="flex-1 appearance-none bg-transparent py-2 pl-3 pr-9 text-sm font-semibold">
        <option value="category" disabled selected>Category
      </option>
        <option value="personal">Personal</option>
        <option value="business">Business</option>
      </select>

      <svg class="transform -rotate-90 absolute pointer-events-none" style="right: 12px; width="22" height="22" viewBox="0 0 22 22">
        <g fill="none" fill-rule="evenodd">
          <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
          </path>
          <path fill="#222" d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z"></path>
        </g>
      </svg>
    </div>

    <!-- Other Filters -->
    <div class="relative flex lg:inline-flex items-center bg-gray-100 rounded-xl">
      <select class="flex-1 appearance-none bg-transparent py-2 pl-3 pr-9 text-sm font-semibold">
        <option value="category" disabled selected>Other Filters
      </option>
        <option value="foo">Foo
        <option value="bar">Bar
      </option>
      </select>

      <svg class="transform -rotate-90 absolute pointer-events-none" style="right: 12px; width="22" height="22" viewBox="0 0 22 22">
        <g fill="none" fill-rule="evenodd">
          <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
          </path>
          <path fill="#222" d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z"></path>
        </g>
      </svg>
    </div>

    <!-- Search -->
    <div class="relative flex lg:inline-flex items-center bg-gray-100 rounded-xl px-3 py-2">
      <form method="GET" action="#">
        <input type="text" name="search" placeholder="Find something" class="bg-transparent placeholder-black font-semibold text-sm">
      </form>
    </div>
  </div>
</header>

```

## 32. Blade Components and CSS Grids

Le seguimos dando forma a nuestra pagina web y le agregamos los componentes dinamicos

```

1  <x-layout>
2    @include ('_posts-header')
3
4    <main class="max-w-6xl mx-auto mt-6 lg:mt-20 space-y-6">
5      @if ($posts->count())
6        <x-posts-grid :posts="$posts" />
7      @else
8        <p class="text-center">No posts yet. Please check back later.</p>
9      @endif
10
11    </main>
12  </x-layout>

```

```

1  @props(['post'])
2
3  <article class="transition-colors duration-300 hover:bg-gray-100 border border-black border-opacity-0 hover:border-opacity-5 rounded-xl">
4    <div class="py-6 px-5 lg:flex">
5      <div class="flex-1 lg:mr-8">
6
7        
8      </div>
9
10     <div class="flex-1 flex flex-col justify-between">
11       <header class="mt-8 lg:mt-0">
12         <div class="space-x-2">
13           <a href="/categories/{{ $post->category->slug }}" class="px-3 py-1 border border-blue-300 rounded-full text-blue-300 text-xs uppercase font-semibold" style="font-size: 10px;">{{ $post->category->name }}</a>
14         </div>
15
16         <div class="mt-4">
17           <h1 class="text-3xl">
18             <a href="/posts/{{ $post->slug }}">
19               {{ $post->title }}
20             </a>
21           </h1>
22
23           <span class="mt-2 block text-gray-400 text-xs">
24             Published <time>{{ $post->created_at->diffForHumans() }}</time>
25           </span>
26         </div>
27       </header>
28
29       <div class="text-sm mt-2">
30         <p>
31           {{ $post->excerpt }}
32         </p>
33       </div>
34
35       <footer class="flex justify-between items-center mt-8">
36         <div class="flex items-center text-sm">
37           
38           <div class="ml-3">
39             <h5 class="font-bold">{{ $post->author->name }}</h5>
40             <h6>Mascot at Laracasts</h6>
41           </div>
42         </div>
43
44         <div class="hidden lg:block">
45           <a href="/posts/{{ $post->slug }}" class="transition-colors duration-300 text-xs font-semibold bg-gray-200 hover:bg-gray-300 rounded-full py-2 px-8">Read More</a>
46         </div>
47       </footer>
48     </div>
49   </div>
50 </article>

```

```

@props(['post'])

<article
  {{{attributes->merge(['class' => 'transition-colors duration-300 hover:bg-gray-100 border border-black border-opacity-0 hover:border-opacity-5 rounded-xl'])}}}
>
  <div class="py-6 px-5">
    <div>
      
    </div>

    <div class="mt-8 flex flex-col justify-between">
      <header>
        <div class="space-x-2">
          <a href="/categories/{{ $post->category->slug }}" class="px-3 py-1 border border-blue-300 rounded-full text-blue-300 text-xs uppercase font-semibold" style="font-size: 10px;">{{ $post->category->name }}</a>
        </div>

        <div class="mt-4">
          <h1 class="text-3xl">
            <a href="/posts/{{ $post->slug }}">
              {{ $post->title }}
            </a>
          </h1>
          <span class="mt-2 block text-gray-400 text-xs">
            Published <time>{{ $post->created_at->diffForHumans() }}</time>
          </span>
        </div>
      </header>

      <div class="text-sm mt-4">
        <p>
          {{ $post->excerpt }}
        </p>
      </div>

      <footer class="flex justify-between items-center mt-8">
        <div class="flex items-center text-sm">
          
          <div class="ml-3">
            <h5 class="font-bold">{{ $post->author->name }}</h5>
            <h6>Mascot at Laracasts</h6>
          </div>
        </div>

        <div>
          <a href="/posts/{{ $post->slug }}" class="transition-colors duration-300 text-xs font-semibold bg-gray-200 hover:bg-gray-300 rounded-full py-2 px-8">Read More</a>
        </div>
      </footer>
    </div>
  </div>
</article>

```

```

1  @props(['posts'])
2
3  <x-post-featured-card :post="$posts[0]" />
4
5  @if ($posts->count() > 1)
6    <div class="lg:grid lg:grid-cols-6">
7      @foreach ($posts->skip(1) as $post)
8        {{-- @dd(loop) --}}
9        <x-post-card :post="$post" class="{{ $loop->iteration < 3 ? 'col-span-3' : 'col-span-2' }}" />
10      @endforeach
11    </div>
12  @endif

```

### 33. Convert the Blog Post Page

Ahora le damos forma a nuestro post de la misma manera en la que la hemos venido haciendo

```
<x-layout>
<section class="px-6 py-8">

  <main class="max-w-6xl mx-auto mt-10 lg:mt-20 space-y-6">
    <article class="max-w-4xl mx-auto lg:grid lg:grid-cols-12 gap-x-10">
      <div class="col-span-4 lg:text-center lg:pt-14 mb-10">
        

        <p class="mt-4 block text-gray-400 text-xs">
          Published <time>{{ $post->created_at->diffForHumans() }}</time>
        </p>

        <div class="flex items-center lg:justify-center text-sm mt-4">
          
          <div class="ml-3 text-left">
            <h5 class="font-bold">{{ $post->author->name }}</h5>
          </div>
        </div>
      </div>

      <div class="col-span-8">
        <div class="hidden lg:flex justify-between mb-6">
          <a href="/" class="transition-colors duration-300 relative inline-flex items-center text-lg hover:text-blue-500">
            <svg width="22" height="22" viewBox="0 0 22 22" class="mr-2">
              <g fill="none" fill-rule="evenodd">
                <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
                </path>
                <path class="fill-current" d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z">
                </path>
              </g>
            </svg>
            Back to Posts
          </a>

          <div class="space-x-2">
            <x-category-button :category="$post->category" />
          </div>
        </div>

        <h1 class="font-bold text-3xl lg:text-4xl mb-10">
          {{ $post->title }}
        </h1>

        <div class="space-y-4 lg:text-lg leading-loose">
          {{ $post->body }}
        </div>
      </div>
    </article>
  </main>
</section>
</x-layout>
```

```

@props(['post'])

<article {{attributes->merge(['class' => 'transition-colors duration-300 hover:bg-gray-100 border border-black border-opacity-0 hover:border-opacity-5 rounded-xl'])}}>
  <div class="py-6 px-5">
    <div>
      
    </div>

    <div class="mt-8 flex flex-col justify-between">
      <header>
        <div class="space-x-2">
          <x-category-button :category="$post->category" />
        </div>

        <div class="mt-4">
          <h1 class="text-3xl">
            <a href="/posts/{{ $post->slug }}">
              {{ $post->title }}
            </a>
            <span class="mt-2 block text-gray-400 text-xs">
              Published <time>{{ $post->created_at->diffForHumans() }}</time>
            </span>
          </div>
        </header>

        <div class="text-sm mt-4">
          <p>
            {{ $post->excerpt }}
          </p>
        </div>

        <footer class="flex justify-between items-center mt-8">
          <div class="flex items-center text-sm">
            
            <div class="ml-3">
              <h5 class="font-bold">{{ $post->author->name }}</h5>
            </div>
          </div>

          <div>
            <a href="/posts/{{ $post->slug }}" class="transition-colors duration-300 text-xs font-semibold bg-gray-200 hover:bg-gray-300 rounded-full py-2 px-8">Read More</a>
          </div>
        </footer>
      </div>
    </article>

```

```

1 @props(['post'])
2
3 <article class="transition-colors duration-300 hover:bg-gray-100 border border-black border-opacity-0 hover:border-opacity-5 rounded-xl">
4   <div class="py-6 px-5 lg:flex">
5     <div class="flex-1 lg:mr-8">
6       
7     </div>
8
9     <div class="flex-1 flex flex-col justify-between">
10      <header class="mt-8 lg:mt-0">
11        <div class="space-x-2">
12          <x-category-button :category="$post->category" />
13        </div>
14
15        <div class="mt-4">
16          <h1 class="text-3xl">
17            <a href="/posts/{{ $post->slug }}">
18              {{ $post->title }}
19            </a>
20          </h1>
21
22          <span class="mt-2 block text-gray-400 text-xs">
23            Published <time>{{ $post->created_at->diffForHumans() }}</time>
24          </span>
25        </div>
26      </header>
27
28      <div class="text-sm mt-2">
29        <p>
30          {{ $post->excerpt }}
31        </p>
32      </div>
33
34      <footer class="flex justify-between items-center mt-8">
35        <div class="flex items-center text-sm">
36          
37          <div class="ml-3">
38            <h5 class="font-bold">{{ $post->author->name }}</h5>
39          </div>
40        </div>
41
42        <div class="hidden lg:block">
43          <a href="/posts/{{ $post->slug }}" class="transition-colors duration-300 text-xs font-semibold bg-gray-200 hover:bg-gray-300 rounded-full py-2 px-8">Read More</a>
44        </div>
45      </footer>
46    </div>
47  </div>
48 </article>

```

```

1 @props(['category'])
2
3 <a href="/categories/{{ $category->slug }}"
4   class="px-3 py-1 border border-blue-300 rounded-full text-blue-300 text-xs uppercase font-semibold"
5   style="font-size: 10px">{{ $category->name }}</a>

```

## 34. A Small JavaScript Dropdown Detour

Ahora vamos a hacer el dropdown menu funcionar para que sirva como filtro de Categorías

```
<div class="space-y-2 lg:space-y-0 lg:space-x-4 mt-8">
  <!-- Category -->
  <div class="relative lg:inline-flex bg-gray-100 rounded-xl">

    <div x-data="{show:false}" @click.away="show=false">
      <button @click="show=!show" class="py-2 pl-3 pr-9 text-sm font-semibold w-full lg:w-32 text-left flex lg:inline-flex">
        {{isset($currentCategory) ? ucwords($currentCategory->name) : 'Categories'}}

        <svg class="transform -rotate-90 absolute pointer-events-none" style="right: 12px; width="22" height="22" viewBox="0 0 22 22">
          <g fill="none" fill-rule="evenodd">
            <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
            </path>
            <path fill="#222" d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z"></path>
          </g>
        </svg>
      </button>

      <div x-show="show" class="py-2 absolute bg-gray-100 w-full mt-2 rounded-xl z-50" style="display: none">
        <a href="/" class="block text-left px-3 text-sm leading-5 hover:bg-blue-500 focus:bg-blue-500 hover:text-white focus:text-white">
          All Categories
        </a>
        @foreach ($categories as $category)
          <a href="/categories/{{ $category->slug }}" class="block text-left px-3 text-sm leading-5 hover:bg-blue-500 focus:bg-blue-500 hover:text-white focus:text-white">
            {{isset($currentCategory) && $currentCategory->id === $category->id ? 'bg-blue-500 text-white' : ''}}
            {{ucwords($category->name)}}
          </a>
        @endforeach
      </div>
    </div>
  </div>
</div>
```

es importante recordar Cargar el Script de JS

```
<div class="space-y-2 lg:space-y-0 lg:space-x-4 mt-8">
  <!-- Category -->
  <div class="relative lg:inline-flex bg-gray-100 rounded-xl">

    <div x-data="{show:false}" @click.away="show=false">
      <button @click="show=!show" class="py-2 pl-3 pr-9 text-sm font-semibold w-full lg:w-32 text-left flex lg:inline-flex">
        {{isset($currentCategory) ? ucwords($currentCategory->name) : 'Categories'}}

        <svg class="transform -rotate-90 absolute pointer-events-none" style="right: 12px; width="22" height="22" viewBox="0 0 22 22">
          <g fill="none" fill-rule="evenodd">
            <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
            </path>
            <path fill="#222" d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z"></path>
          </g>
        </svg>
      </button>

      <div x-show="show" class="py-2 absolute bg-gray-100 w-full mt-2 rounded-xl z-50" style="display: none">
        <a href="/" class="block text-left px-3 text-sm leading-5 hover:bg-blue-500 focus:bg-blue-500 hover:text-white focus:text-white">
          All Categories
        </a>
        @foreach ($categories as $category)
          <a href="/categories/{{ $category->slug }}" class="block text-left px-3 text-sm leading-5 hover:bg-blue-500 focus:bg-blue-500 hover:text-white focus:text-white">
            {{isset($currentCategory) && $currentCategory->id === $category->id ? 'bg-blue-500 text-white' : ''}}
            {{ucwords($category->name)}}
          </a>
        @endforeach
      </div>
    </div>
  </div>
</div>
```



```

Route::get('/', function () {
    return view('posts', [
        'posts' => Post::latest()->with('category', 'author')->get(),
        'categories' => Category::all()
    ]);
});

Route::get('posts/{post:slug}', function (Post $post){

    return view('post',[
        'post'=> $post
    ]);
});

Route::get('categories/{category:slug}', function (Category $category){

    return view('posts',[
        'posts' => $category->posts,
        'currentCategory' => $category,
        'categories' => Category::all()
    ]);
});

Route::get('authors/{author:username}', function (User $author){
    return view('posts',[
        'posts' => $author->posts,
        'categories' => Category::all()
    ]);
});

```

## 35. How to Extract a Dropdown Blade Component

Ahora el código JS que creamos en el anterior episodio lo vamos a convertir a un formato válido para Blade, de esta manera nuestro código quedará mucho más limpio e incluso fácil de entender

```

resources > views > components > dropdown-item.blade.php > a
1 <a {{attributes(['class' => "block text-left px-3 text-sm leading-5 hover:bg-blue-500 focus:bg-blue-500 hover:text-white focus:text-white"])}}>
2 | {{slot}}
3 </a>

```

```

resources > views > components > dropdown.blade.php > div
1 @props(['trigger'])
2
3 <div x-data="{show:false}" @click.away="show=false">
4
5     <div @click="show=!show">
6         {{ $trigger }}
7     </div>
8
9     <div x-show="show" class="py-2 absolute bg-gray-100 w-full mt-2 rounded-xl z-50" style="display: none">
10         {{ $slot }}
11     </div>
12 </div>

```

```

1  @props(['name'])
2
3  @if ($name === 'down-arrow')
4      <svg {{ $attributes(['class' => "transform -rotate-90"]) }} style="right: 12px;" width="22"
5          height="22" viewBox="0 0 22 22">
6          <g fill="none" fill-rule="evenodd">
7              <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
8              </path>
9              <path fill="#222"
10                  d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z"></path>
11          </g>
12      </svg>
13  @endif

```

```


<!-- Category -->
    <div class="relative lg:inline-flex bg-gray-100 rounded-xl">

        <x-dropdown>
            <x-slot name="trigger">
                <button class="py-2 pl-3 pr-9 text-sm font-semibold w-full lg:w-32 text-left flex lg:inline-flex">
                    {{isset($currentCategory) ? ucwords($currentCategory->name) : 'Categories'}}

                    <x-icon name="down-arrow" class="absolute pointer-events-none" />
                </button>
            </x-slot>

            <x-dropdown-item href="/" class="{{request()->routeIs('home') ? 'bg-blue-500 text-white' : ''}}">All Categories</x-dropdown-item>
            @foreach ($categories as $category)
                <x-dropdown-item href="/categories/{{ $category->slug }}"
                    class="{{isset($currentCategory) && $currentCategory->id === $category->id ? 'bg-blue-500 text-white' : ''}}">
                    {{ucwords($category->name)}}
                </x-dropdown-item>
            @endforeach
        </x-dropdown>
    </div>


```

```

Route::get('/', function () {
    return view('posts', [
        'posts' => Post::latest()->with('category', 'author')->get(),
        'categories' => Category::all()
    ]);
})->name('home');

Route::get('posts/{post:slug}', function (Post $post){
    return view('post',[
        'post'=> $post
    ]);
})->name('post');

Route::get('categories/{category:slug}', function (Category $category){
    return view('posts',[
        'posts' => $category->posts,
        'currentCategory' => $category,
        'categories' => Category::all()
    ]);
})->name('category');

Route::get('authors/{author:username}', function (User $author){
    return view('posts',[
        'posts' => $author->posts,
        'categories' => Category::all()
    ]);
})->name('author');

```

## 36. Quick Tweaks and Clean-Up

En este episodio hacemos un poco de limpieza y modificamos unas partes del código para que se vea mejor

```

<div class="space-y-4 lg:text-lg leading-loose">
    {!! $post->body !!}
</div>

```

```

<div class="space-y-2 lg:space-y-0 lg:space-x-4 mt-4">
  <!-- Category -->
  <div class="relative lg:inline-flex bg-gray-100 rounded-xl">
    <x-dropdown>
      <x-slot name="trigger">
        <button class="py-2 pl-3 pr-9 text-sm font-semibold w-full lg:w-32 text-left flex lg:inline-flex">
          {{isset($currentCategory) ? ucwords($currentCategory->name) : 'Categories'}}
          <x-icon name="down-arrow" class="absolute pointer-events-none" />
        </button>
      </x-slot>
      <x-dropdown-item href="/" class="{{request()->routeIs('home') ? 'bg-blue-500 text-white' : ''}}">All Categories</x-dropdown-item>
      @foreach ($categories as $category)
        <x-dropdown-item href="/categories/{{ $category->slug }}" class="{{isset($currentCategory) && $currentCategory->id === $category->id ? 'bg-blue-500 text-white' : ''}}">
          {{ucwords($category->name)}}
        </x-dropdown-item>
      @endforeach
    </x-dropdown>
  </div>

  <!-- Other Filters -->
  <!-- <div class="relative flex lg:inline-flex items-center bg-gray-100 rounded-xl">
    <select class="flex-1 appearance-none bg-transparent py-2 pl-3 pr-9 text-sm font-semibold">
      <option value="category" disabled selected>Other Filters
    </option>
    <option value="foo">Foo
    </option>
    <option value="bar">Bar
    </option>
    </select>

    <svg class="transform -rotate-90 absolute pointer-events-none" style="right: 12px; width: 22px; height: 22px; viewBox="0 0 22 22">
      <g fill="none" fill-rule="evenodd">
        <path stroke="#000" stroke-opacity=".012" stroke-width=".5" d="M21 1v20.16H.84V1z">
        </path>
        <path fill="#222" d="M13.854 7.2241-3.847 3.856 3.847 3.856-1.184 1.184-5.04-5.04 5.04-5.04z"></path>
      </g>
    </svg>
  </div> -->

```

```

* Define the model's default state.
*
* @return array
*/
public function definition()
{
    return [
        'user_id' => User::factory(),
        'category_id' => Category::factory(),
        'title' => $this->faker->sentence,
        'slug' => $this->faker->slug,
        'excerpt' => '<p>' . implode('</p><p>', $this->faker->paragraphs(2)) . '</p>',
        'body' => '<p>' . implode('</p><p>', $this->faker->paragraphs(6)) . '</p>',
    ];
}

```

```

<div class="text-sm mt-2 space-y-4">
  <p>
    {!! $post->excerpt !!}
  </p>

```

Hasta el momento al menos la pagina principal deberia estar algo asi

