

**Cristian Dávila**  
**Enrique Gonzalez**


**1**

socket: 2  
core: 6  
threads core: 2  
threads total: 24  
L1 cache: 64K (private)  
L2 cache: 256K (private)  
L3 cache: 12288K (shared)  
ShMem: 72kB  
Main memory: 24 Gb/node

**2**

```
<sys/time.h>
struct timeval{
    long tv_sec;
    long tv_usec;
};
```

**3**



At beginning of the execution we don't have any thread, but during the execution, the program increase the number of threads executing at the same time, so the computation work is divided between the all threads.

4

<b>Name</b>	<b>PI_COMP</b>	<b>REST_MAIN</b>	<b>TIMING</b>	<b>TOTAL</b>	<b>OVHD</b>
<b>pi_omp_sum_local.c</b>	1,991,860	8,470	21,978	30,794,980	29.87
<b>pi_omp_critical.c</b>	655,433,035	37,766	100,898	253,400,501	2.81


5

	<b>PI_COMPUTATION</b>	<b>REST_MAIN</b>	<b>TIMING</b>	<b>TOTAL</b>	<b>OVHD</b>
<b>pi_omp_sum_local.c</b>	48.56%	0.21%	0.54%	93.84%	53.17%
<b>pi_omp_critical.c</b>	72.11%	0.03%	0.09%	27.88%	27.88%

6

<b>Versió</b>	<b>T<sub>1</sub></b>	<b>T<sub>∞</sub></b>	<b>Parallelism</b>
<b>seq</b>	25163336	24156947	2
<b>v1</b>	25163558	24157169	2
<b>v2</b>	24494445	21064576	2
<b>v3</b>	25170818	14548112	2
<b>v4</b>	25701840	13165421	20

Processadors	seq	v4
2	24,170,661,015 ns	12,618,563,001 ns
4	24,170,661,015 ns	6,330,483,001 ns
8	24,170,661,015 ns	3,171,856,001 ns
16	24,170,661,015 ns	1,802,153,001 ns
32	24,170,661,015 ns	1,398,367,001 ns
64	24,170,661,015 ns	1,320,786,001 ns



The minimum number of cores that we need to execute 'seq' with the maximum speed is 1, so the execution time doesn't change with the increment of cores.

'v4' need 32 cores to execute at full speed, so with the increment of cores, the execution time decrease, until the number of cores is 32.