

Package ‘diaQTL’

April 26, 2021

Title QTL Analysis in Diallel Populations

Version 0.96

Author Jeffrey B. Endelman and Rodrigo R. Amadeu

Maintainer Jeffrey Endelman <endelman@wisc.edu>

Description QTL analysis of diploid and autotetraploid diallel populations. Phenotypes are regressed on genotype probabilities, and the regression coefficients are random effects.

Depends R (>= 3.5.0)

License GPL-3 + file LICENSE

LazyData true

RoxygenNote 7.1.1

Roxygen list(markdown = TRUE)

Encoding UTF-8

Imports BGLR, ggplot2, methods, coda, Matrix, scam, parallel, arrangements, tidyr, ggfittext, ggden-
dro, labeling, rlang

Suggests knitr, rmarkdown

VignetteBuilder knitr

R topics documented:

BayesCI	2
diallel_geno-class	3
diallel_geno_pheno-class	3
DIC_thresh	4
diplo_freq	5
diplo_get	5
F1codes	6
fine_map	6
fitQTL	7
get_map	9
haplo_cluster	9
haplo_freq	10
haplo_get	11
haplo_plot	12
IBDmat	13
phased_parents	14

read_data	14
read_polyancestry	16
S1codes	16
scan1	17
scan1_permute	18
scan1_summary	19
set_params	20
Index	22

BayesCI	<i>Bayesian Credible Interval for QTL position</i>
---------	--

Description

Bayesian Credible Interval for QTL position

Usage

```
BayesCI(scan1_data, data, chrom, CI.prob = 0.9)
```

Arguments

scan1_data	data frame output from scan1
data	variable of class <code>diallel_geno_pheno</code>
chrom	chromosome
CI.prob	probability for the credible interval

Details

Parameter `CI.prob` sets the probability for the Bayesian credible interval (e.g., 0.90, 0.95) using the profile likelihood (posterior mean).

Value

subset of `scan1_data` with markers in the CI

Examples

```
## Not run:
BayesCI(scan1_example, diallel_example, chrom="10", CI.prob=0.9)

## End(Not run)
```

diallel_geno-class *S4 class with genotype data*

Description

S4 class with genotype data

Slots

ploidy Either 2 or 4
polyorigin matrix of character strings from the genotype input file, one row per bin
Xa list of matrices with the expected haplotype dosage (rows) for each parental origin genotype (columns)
dominance Maximum dosage stored in slot geno. Integer 1-4 indicating 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance.
X.GCA Incidence matrix for GCA effects
map data frame with marker,chrom, position (cM and/or bp) and bin
geno list of length equal to the number of marker bins. Each element is a list of length dominance. The elements in the nested list are sparse matrices with dimensions (id x effects), containing the dosage for each effect.
A list with the additive relationship matrix for each chromosome

diallel_geno_pheno-class
S4 class with genotype and phenotype data

Description

S4 class with genotype and phenotype data

Slots

ploidy Either 2 or 4
polyorigin matrix of character strings from the genotype input file
Xa list of matrices with the expected haplotype dosage (rows) for each parental origin genotype (columns)
dominance Maximum dosage stored in slot geno. Integer 1-4 indicating 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance.
X.GCA Incidence matrix for GCA effects
map data frame with marker,chrom, position (cM and/or bp) and bin
geno list of length equal to the number of marker bins. Each element is a list of length dominance. The elements in the nested list are sparse matrices with dimensions (id x effects), containing the dosage for each effect.
A list with the additive relationship matrix for each chromosome
pheno data frame of phenotypes
X incidence matrix for fixed effects
Z incidence matrix for individuals

DIC_thresh	<i>delta DIC thresholds for scan1</i>
------------	---------------------------------------

Description

delta DIC thresholds for scan1

Usage

```
DIC_thresh(genome.size, num.parents, ploidy, alpha = 0.05, dominance = 1)
```

Arguments

genome.size	Genome size in Morgans (not centiMorgans)
num.parents	Number of parents
ploidy	2 or 4
alpha	false positive rate: 0.01, 0.05, 0.10, or 0.20
dominance	1 (additive) or 2 (digenic dominance)

Details

delta DIC thresholds to control the genome-wide false positive rate at level alpha were determined via simulation for up to 20 parents and genome sizes up to 12 Morgans. A monotone decreasing concave curve was fit to these results using R package scam and is used for prediction.

Value

deltaDIC threshold

Examples

```
## Not run:
  DIC_thresh(genome.size=10,
             num.parents=4,
             ploidy=4,
             dominance=1,
             alpha=0.05)

## End(Not run)
```

diplo_freq	<i>Diplotype frequencies</i>
------------	------------------------------

Description

Plot the frequency of individuals with diplotype dosage above a threshold

Usage

```
diplo_freq(data, diplotypes, dosage, position, chrom = NULL)
```

Arguments

data	Variable inheriting from class <code>diallel_genotype</code>
diplotypes	Names of diplotypes
dosage	Dosage threshold
position	Either "cM" or "bp" for plotting
chrom	Names of chromosomes (default is all)

Details

Useful for visualizing selection in selfed populations.

Value

List containing

result Data frame with the map and frequency

plot ggplot object

diplo_get	<i>Dosage of parental diplotypes</i>
-----------	--------------------------------------

Description

Dosage of parental diplotypes

Usage

```
diplo_get(data, marker = NULL, id = NULL)
```

Arguments

data	Variable inheriting from class <code>diallel_genotype</code>
marker	Name of marker
id	Name of individual

Details

Function can be used to get parental diplotype dosage estimates at a single marker for all individuals (in which case `id` should be `NULL`) or for a single individual for all markers (in which case `marker` should be `NULL`)

Value

Matrix of (id or markers) x parental diplotypes

Examples

```
## Not run:
diplo_example = diplo_get(data = diallel_example,
                          marker = "solcap_snp_c2_25522")
diplo_example = diplo_get(data = diallel_example,
                          id = "W15263-8R")

## End(Not run)
```

F1codes	<i>Genotype codes for F1 populations</i>
---------	--

Description

Character vector with the 100 possible tetraploid genotypes for a F1 population. Maternal haplotypes are denoted 1,2,3,4 and paternal haplotypes 5,6,7,8.

Usage

```
data(F1codes)
```

Format

character vector

<code>fine_map</code>	<i>Visualize haplotype switches for fine mapping</i>
-----------------------	--

Description

Visualize haplotype switches for fine mapping

Usage

```
fine_map(data, haplotype, interval, trait = NULL, marker = NULL)
```

Arguments

data	Variable inheriting from class <code>diallel_geno</code>
haplotype	Name of parental haplotype
interval	2-vector with marker names
trait	Name of trait to plot (optional)
marker	Optional, marker to indicate with dashed line

Details

Function returns graphic for all individuals with a haplotype switch (defined as change in dosage from 0 to ≥ 1 or vice versa) for haplotype within interval. If trait is included, the trait values for each individual are displayed on the right side. The function requires map positions in bp to be included in data.

Value

ggplot2 variable

Examples

```
## Not run:
fine_map(data = diallel_example,
  haplotype = "W6511-1R.2",
  interval = c("solcap_snp_c2_40766", "solcap_snp_c1_15225"))

fine_map(data = diallel_example,
  haplotype = "W6511-1R.2",
  interval = c("solcap_snp_c2_40766", "solcap_snp_c1_15225"),
  marker = "solcap_snp_c2_25522")

## End(Not run)
```

fitQTL

Fit multiple QTL model

Description

Fit multiple QTL model

Usage

```
fitQTL(
  data,
  trait,
  qtl,
  epistasis = NULL,
  polygenic = FALSE,
  params,
  CI.prob = 0.9
)
```

Arguments

<code>data</code>	variable of class <code>diallel_geno_pheno</code>
<code>trait</code>	name of trait
<code>qtl</code>	data frame, see Details
<code>epistasis</code>	optional data frame, see Details
<code>polygenic</code>	TRUE/FALSE whether to include additive polygenic effect
<code>params</code>	list containing the number of burn-in (<code>burnIn</code>) and total iterations (<code>nIter</code>)
<code>CI.prob</code>	probability for Bayesian credible interval

Details

Argument `qtl` is a data frame with columns `marker` and `dominance` to specify the marker name and highest order effect (1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance). All effects up to the value in `dominance` are included. Optional argument `epistasis` is a data frame with columns `marker1` and `marker2`, where each row specifies an additive x additive epistatic interaction. The number of burn-in and total iterations in `params` can be estimated using `set_params`. Parameter `CI.prob` sets the probability (e.g., 0.90, 0.95) for the Bayesian credible interval for the estimated effects (to disable plotting of the CI, use `CI.prob=NULL`).

Value

List containing

deltaDIC DIC relative to model with GCA but no QTL effects

resid residuals

var matrix with proportion of variance for the effects

effects list with two matrices, additive and digenic, with markers on the rows and effects on the columns

plots list of ggplot objects, one for each marker, containing elements additive and digenic. The digenic plot has digenic effects above the diagonal and the sum of additive and digenic effects below the diagonal.

Examples

```
## Not run:
## additive effects
params1 <- set_params( diallel_example, trait = "tuber_shape" ,q=0.05,r=0.05)

fit1 <- fitQTL( data = diallel_example,
               trait = "tuber_shape",
               params = params1,
               marker = "solcap_snp_c2_25522",
               CI.prob = 0.9)

## additive + dominance effects
params2 <- set_params( diallel_example, trait = "tuber_shape", dominance=2,q=0.05,r=0.05)

fit2 <- fitQTL( data = diallel_example,
               trait = "tuber_shape",
               params = params2,
               marker = "solcap_snp_c2_25522",
```



```

                                dominance = 2,
                                CI.prob=0.9)

## End(Not run)

```

get_map

*Get map summary from diallel_geno object***Description**

Get map summary from diallel_geno object

Usage

```
get_map(data, summary = TRUE)
```

Arguments

data	Variable inheriting from class <code>diallel_geno</code>
summary	logical, if TRUE (default) returns total sizes per chromosome, if FALSE returns the map

Value

data frame with map summary or the map

Examples

```

## Not run:
  get_map(diallel_example)

## End(Not run)

```

haplo_cluster

*Cluster parental haplotypes***Description**

Cluster parental haplotypes

Usage

```
haplo_cluster(filename, marker, haplotypes = NULL)
```

Arguments

filename	Name of CSV input file
marker	Either target marker or marker interval (see Details).
haplotypes	Vector of haplotype names (default is all)

Details

The input file (diaQTL_parents.csv) should be generated by [read_polyancestry](#). The argument marker can be either a single marker or vector of two markers. If a single marker, the function finds the smallest interval containing that marker such that the phased SNP haplotypes are all unique. If two markers are provided, that interval is used. Clustering utilizes hclust(method="average"). See also [phased_parents](#) for an additional visualization tool.

Value

- List containing
 - haplo** Data frame of haplotypes
 - dendro** Dendrogram

haplo_freq	<i>Haplotype frequencies</i>
------------	------------------------------

Description

Plots the frequency of individuals with haplotype dosage above a threshold

Usage

```
haplo_freq(  
  data,  
  haplotypes,  
  dosage,  
  id = NULL,  
  position = "cM",  
  chrom = NULL,  
  markers = NULL  
)
```

Arguments

- data Variable inheriting from class [diallel_geno](#)
- haplotypes Names of haplotypes
- dosage Dosage threshold
- id Vector of id names (default is entire population)
- position Either "cM" (default) or "bp" for plotting
- chrom Names of chromosomes (default is all)
- markers Optional, markers to indicate with dashed line. Only available when plotting a single chromosome.

Details

Useful for visualizing selection in selfed populations. For multiple chromosomes, each haplotype is shown in its own panel using facet_wrap. For one chromosome, the haplotypes are shown on the same set of axes.

haplo_plot

*Plot parental haplotype dosage***Description**

Plot parental haplotype dosages across the chromosome for one individual

Usage

```
haplo_plot(data, id, chrom, position = "cM", markers = NULL)
```

Arguments

data	Variable inheriting from class <code>diallel_geno</code>
id	Name of individual(s)
chrom	Name of chromosome
position	Either "cM" (default) or "bp"
markers	Optional, markers to indicate with dashed line

Details

For "cM" plotting, only one marker per bin is displayed. For "bp" plotting, all markers are included. If multiple individuals are included in `id`, then the plot shows the probability that a haplotype is present in all individuals.

Value

ggplot object

Examples

```
## Not run:
haplo_plot(data = diallel_example,
            id = "W15263-8R",
            chrom = 10)

haplo_plot(data = diallel_example,
            id = "W15263-8R",
            chrom = 10,
            marker = "solcap_snp_c2_25522")

## End(Not run)
```

IBDmat	<i>Realized IBD relationship</i>
--------	----------------------------------

Description

Calculates realized relationship matrices (additive and dominance) from founder genotype probabilities

Usage

```
IBDmat(data, dominance = 1, chrom = NULL, n.core = 1)
```

Arguments

data	Variable inheriting from class <code>diallel_geno</code>
dominance	One of 1,2,3,4
chrom	Optional, vector of chromosome names to include
n.core	number of cores for parallel execution

Details

Parameter dominance refers to 1 = additive, 2 = digenic, 3 = trigenic, 4 = quadrigenic (Gallais 2003). Can specify to use only a subset of the chromosomes (by default, all chromosomes are used). Calculated for each chromosome based on the marker bins and then averaged across chromosomes.

Value

Relationship matrix

References

Gallais, A. 2003. Quantitative Genetics and Breeding Methods in Autopolyploid Plants. Institut National de la Recherche Agronomique, Paris.

Examples

```
## Not run:  
  IBD_example = IBDmat(data = diallel_example, dominance=1) #additive  
  IBD_example = IBDmat(data = diallel_example, dominance=2) #digenic dominance  
  
## End(Not run)
```

phased_parents	<i>Visualize phased SNPs of parents</i>
----------------	---

Description

Visualize phased SNPs of parents

Usage

```
phased_parents(filename, interval, markers, parents)
```

Arguments

filename	Name of CSV input file
interval	Vector of length 2 with the first and last marker names
markers	Vector of marker names to plot
parents	Vector of parent names to plot

Details

The input file can be generated by [read_polyancestry](#). The solid circles in the figure represent the allele counted by dosage.

Value

ggplot2 object

read_data	<i>Read data files</i>
-----------	------------------------

Description

Reads genotype, pedigree, and phenotype data files

Usage

```
read_data(  
  genofile,  
  ploidy = 4,  
  pedfile,  
  phenofile = NULL,  
  fixed = NULL,  
  bin.markers = TRUE,  
  dominance = 4,  
  n.core = 1  
)
```

Arguments

genofile	File with map and genotype probabilities
ploidy	Either 2 or 4
pedfile	File with pedigree data (id,parent1,parent2)
phenofile	File with phenotype data (optional)
fixed	If there are fixed effects, this is a character vector of "factor" or "numeric"
bin.markers	TRUE/FALSE whether to bin markers with the same cM position
dominance	Maximum value of dominance that will be used for analysis (1-4). See Details.
n.core	Number of cores for parallel execution

Details

Genotype and pedigree input files can be created from PolyOrigin output using [read_polyancestry](#). The first 3 columns of the genotype file should be the genetic map (labeled marker, chrom, cM), and a fourth column for a reference genome position (labeled bp) can also be included. The map is followed by the members of the population. The genotype data for each marker x individual combination is a string with the format "state1state2state...=>prob1prob2prob...", where "state" refers to the genotype state and "prob" is the genotype probability in decimal format. Only states with nonzero probabilities need to be listed. The encoding for the states in tetraploids is described in the documentation for the F1codes and S1codes datasets that come with the package. For diploids, there are 4 F1 genotype codes, 1,2,3,4, which correspond to haplotype combinations 1-3,1-4,2-3,2-4, respectively; the S1 genotype codes 1,2,3 correspond to 1-1,1-2,2-2, respectively. For the phenotype file, first column is id, followed by traits, and then any fixed effects. Pass a character vector for the function argument "fixed" to specify whether each effect is a factor or numeric covariate. The number of traits is deduced based on the number of columns. Binary traits must be coded N/Y and are converted to 0/1 internally for analysis by probit regression. Missing data in the phenotype file should be coded as NA. The parameter dominance specifies the maximum value of dominance that can be used in subsequent analysis: 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance. The default is dominance = 4, which allows the full range of dominance models in functions such as [scan1](#) and [fitQTL](#), but this requires the most RAM. Output files from the BGLR package are stored in a folder named 'tmp' in the current directory.

Value

Variable of class [diallel_geno](#) if phenofile is NULL, otherwise [diallel_geno_pheno](#)

Examples

```
## Not run:
## Get the location of raw csv files examples
genocsv = system.file( "vignette_data", "potato_genocsv.csv", package = "diaQTL" )
pedcsv = system.file( "vignette_data", "potato_ped.csv", package = "diaQTL" )
phenocsv = system.file( "vignette_data", "potato_phenocsv.csv", package = "diaQTL" )

## Check their location in the system
print(genocsv)
print(pedcsv)
print(phenocsv)

## Load them in R
diallel_example <- read_data(genofile = genocsv,
                             ploidy = 4,
```

```
pedfile = pedcsv,
phenofile = phenocsv)

## End(Not run)
```

read_polyancestry	Create diaQTL input files from polyancestry file
-------------------	--

Description

Create diaQTL input files from polyancestry file

Usage

```
read_polyancestry(
  filename,
  mapfile = NULL,
  remove.outliers = TRUE,
  outstem = ""
)
```

Arguments

filename	Name of polyancestry file
mapfile	Optional name of CSV file containing the physical map (marker, chrom, bp)
remove.outliers	Should offspring flagged as outliers be removed (default is TRUE)
outstem	prefix for output filenames

Details

Creates the pedigree (diaQTL_pedfile.csv) and genotype (diaQTL_genofile.csv) input files needed for [read_data](#) from the polyancestry output file generated by the PolyOrigin software. PolyOrigin outputs a genetic map in cM. To add a physical map in bp, use the option mapfile. The input file needed for [phased_parents](#) (diaQTL_parents.csv) is also created.

S1codes	Genotype codes for S1 populations
---------	-----------------------------------

Description

Character vector with the 35 possible tetraploid genotypes for a S1 population. Haplotypes are denoted 1,2,3,4.

Usage

```
data(S1codes)
```

Format

character vector

scan1	<i>Single QTL scan</i>
-------	------------------------

Description

Performs a linear regression for each position in the map.

Usage

```
scan1(
  data,
  trait,
  params,
  dominance = 1,
  cofactor = NULL,
  chrom = NULL,
  n.core = 1
)
```

Arguments

data	variable of class diallel_geno_pheno
trait	name of trait
params	list containing burnIn and nIter
dominance	maximum dominance for the scan, see Details
cofactor	optional data frame, see Details
chrom	names of chromosomes to scan (default is all)
n.core	number of cores for parallel execution

Details

Parameter dominance has possible values of 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance. MCMC params can be estimated using [set_params](#). Optional argument cofactor is used to include other markers in the model during the scan, which can improve statistical power with multiple QTL. It is a data frame with three columns: marker = name of the marker, dominance = 1 to 4, and epistasis = TRUE/FALSE. Function returns deltaDIC = DIC for the QTL model relative to null model with only GCA effects for the parents, as well as LL = posterior mean of the log-likelihood, which is used by [BayesCI](#).

Value

Data frame containing the map, LL, and deltaDIC.

Examples

```
## Not run:
par1 <- set_params(data = diallel_example,
  trait = "tuber_shape")

scan1_example <- scan1(data = diallel_example,
```

```

        chrom = 10,
        trait = "tuber_shape",
        params = par1)

## End(Not run)

```

scan1_permute	<i>Permutation test for scan1</i>
---------------	-----------------------------------

Description

Permutation test for scan1

Usage

```

scan1_permute(
  data,
  trait,
  params,
  n.permute = 1000,
  chrom = NULL,
  dominance = 1,
  cofactor = NULL,
  n.core = 1
)

```

Arguments

data	Variable of class diallel_geno_pheno
trait	Name of trait
params	List containing burnIn and nIter
n.permute	Number of permutations
chrom	Names of chromosomes to scan (default is all)
dominance	Dominance degree (1-4)
cofactor	Optional name of marker to include as cofactor in the scan
n.core	Number of cores for parallel execution

Value

Data frame with maximum LOD and minimum deltaDIC for each iteration

Examples

```

## Not run:
par1 <- set_params(data = diallel_example,
                   trait = "tuber_shape")

ans1_permut <- scan1_permute(data = diallel_example,
                             chrom = 10,

```

```

        trait = "tuber_shape",
        params = par1,
        n.permute = 100)

## End(Not run)

```

scan1_summary	<i>Summary of scan1 result</i>
---------------	--------------------------------

Description

Summary of scan1 result

Usage

```

scan1_summary(
  scan1_data,
  thresh = NULL,
  chrom = NULL,
  position = "cM",
  flip = TRUE
)

```

Arguments

scan1_data	output from scan1
thresh	optional, threshold for plotting
chrom	optional, subset of chromosomes to plot
position	Either "cM" (default) or "bp"
flip	should QTL be plotted as peaks (TRUE) or valleys (FALSE)

Value

List containing

peaks data frame of markers with the lowest DIC on each chromosome

plot ggplot object

Examples

```

## Not run:
scan1_summary( scan1_example )
scan1_summary( scan1_example, chrom = "10" )
scan1_summary( scan1_example, chrom = c( "10", "12" ) )

## End(Not run)

```

set_params

Determine number of iterations for MCMC

Description

Determine number of iterations for MCMC

Usage

```
set_params(
  data,
  trait,
  qtl = NULL,
  epistasis = NULL,
  polygenic = FALSE,
  q = 0.5,
  r = 0.1,
  nIter = 2000
)
```

Arguments

data	variable of class diallel_geno_pheno
trait	name of trait
qtl	optional data frame, see Details
epistasis	optional data frame, see Details
polygenic	TRUE/FALSE whether to include additive polygenic effect
q	quantile to estimate
r	tolerance for quantile
nIter	number of iterations

Details

Determines the burn-in and total number of iterations using the Raftery and Lewis diagnostic from R package coda, based on a 95% probability that the estimate for quantile q of the additive genetic variance is within the interval $(q-r, q+r)$. If marker=NULL (default), the first marker of each chromosome is analyzed, and the largest value across this set is returned. Parameter dominance specifies which genetic model (1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance) to use when determining the number of iterations, but this parameter must still be specified when calling functions such as [scan1](#) or [fitQTL](#). The default values of $q=0.5$ and $r=0.1$ are recommended for [scan1](#) based on the idea of estimating the posterior mean. For estimating the 90% Bayesian CI with [fitQTL](#), suggested values are $q=0.05$, $r=0.025$. Parameter nIter sets the number of iterations used to apply the Raftery and Lewis diagnostic; the default value is 2000, and if a larger number is needed, an error will be generated with this information.

Value

matrix showing the number of burn-in and total iterations for the genetic variances in the model

Examples

```
## Not run:
# Parameters for scan1
par1 <- set_params(data = diallel_example,
                   trait = "tuber_shape", q=0.5, r=0.1)

# Parameters for fitQTL
par2 <- set_params(data = diallel_example,
                   trait = "tuber_shape", q=0.05, r=0.025, marker="solcap_c2_25522")

## End(Not run)
```

Index

* datasets

F1codes, [6](#)

S1codes, [16](#)

BayesCI, [2](#), [17](#)

diallel_genotype, [5](#), [7](#), [9–13](#), [15](#)

diallel_genotype (diallel_genotype-class), [3](#)

diallel_genotype-class, [3](#)

diallel_genotype_phenotype, [2](#), [8](#), [15](#), [17](#), [18](#), [20](#)

diallel_genotype_phenotype
(diallel_genotype_phenotype-class), [3](#)

diallel_genotype_phenotype-class, [3](#)

DIC_thresh, [4](#)

diplo_freq, [5](#)

diplo_get, [5](#)

F1codes, [6](#)

fine_map, [6](#)

fitQTL, [7](#), [15](#), [20](#)

get_map, [9](#)

haplo_cluster, [9](#)

haplo_freq, [10](#)

haplo_get, [11](#)

haplo_plot, [12](#)

IBDmat, [13](#)

phased_parents, [10](#), [14](#), [16](#)

read_data, [14](#), [16](#)

read_polyancestry, [10](#), [14](#), [15](#), [16](#)

S1codes, [16](#)

scan1, [15](#), [17](#), [20](#)

scan1_permute, [18](#)

scan1_summary, [19](#)

set_params, [8](#), [17](#), [20](#)