


ODL300

Linear Light

CONNECT-A-LIGHT | OVERDRIVE™



The ODL300 is an OverDrive™ linear light featuring an integrated OverDrive current driver with a lux value of up to 90,000 and a strobe rate of up to 5000 strobes per second. NPN or PNP triggers can be used to control the strobe rate and duration. Light intensity can be controlled via 1 - 10 VDC analog intensity line or set manually by the intensity adjustment potentiometer. The ODL300 can be daisy-chained with up to six lights in series using a standard 5-PIN M12 jumper cable.

ODL300 HIGHLIGHTS

Warranty
**10
YEAR**

Tested
**IEC
62471**

Compliant
**CE
ROHS**

Rated
**IP
50**

Connector
**5-PIN
M12**

- ✓ Daisy-chain up to six ODL300 linear lights using a standard 5-pin M12 jumper cable
- ✓ High-impact injection molded housing
- ✓ Built-in potentiometer for physical intensity adjustment
- ✓ Up to 5,000 strobes per second
- ✓ OverDrive™ - up to five times brighter than a standard linear connect-a-light




SPECIFICATIONS

Electrical Input	24 VDC +/- 5%
Input Current	Max. 4.6 A during strobe
Input Power	Max. 110 W during strobe
PNP Trigger	2.8 mA @ 4VDC 8.8 mA @ 12VDC 17.6 mA @ 24VDC
NPN Trigger	14.4 mA @ Common (0VDC)
Trigger Input	PNP > +4 VDC (24 VDC max.) to activate or NPN ≥ GND <1VDC to activate (not both)
Strobe Duration	Min. 1 μs Max. ∞
Power Indicator	Turns green when powered up
Status Indicators	Strobe indicator will turn red while resting and turn off when ready
Analog Intensity	The output is adjustable from 10% - 100% by a 1 - 10 VDC signal or front potentiometer. Jumpering pin 5 to pin 1 will provide maximum intensity
Connection	5-pin M12 connector
Operating Temperature	-10° to 40° C (14° to 104° F) RH max 80% non-condensing humidity
Storage Temperature	-20° to 70° C (-4° to 158° F) RH max 80% non-condensing humidity
IP Rating	IP50
Weight	~370 g
Compliances	CE, IEC 62471, RoHS
Warranty	10 years*

*See SmartVisionLights.com/warranty for details

WIRING CONFIGURATION



Pin layout for light (Male Connector)

Pins	Function	Signal	Wire Color
1	Power In	+24VDC	BROWN
2	NPN	Sinking Signal	WHITE
3	GND	Ground	BLUE
4	PNP	Sourcing Signal	BLACK
5	Intensity Control	1-10VDC	GREY*

For maximum intensity, tie pin 5 to pin 1 at +24VDC.

For proper light function, apply either a PNP or NPN signal, not both.

Failure to supply light with correct input current will result in inconsistent lighting behavior.

(see Product Specifications for requirements)

LENS OPTICS


NARROW (Standard)

Narrow, 16° angle-cone lenses are standard. Standard lenses create a narrow beam of illumination and are used for long working distances.




LINE

Line, with a 10° width and a 50° fan angle, projects a thin, narrow beam of illumination.



WIDE

Wide, 30° angle-cone lenses create a large area of illumination. They create a floodlight effect and can be used for short working distances.




LIGHTING PATTERNS


The ODL300 is recommended to be used at a working distance between 300 mm to 2000 mm. Illuminance values taken on white light - 5700K

Standard (16°) lighting patterns

Illuminance -vs- Working Distance




Beam Size at 80% Max Intensity -vs- Working Distance




Wide (30°) lighting patterns

Illuminance -vs- Working Distance




Beam Size at 80% Max Intensity -vs- Working Distance




Line (10° x 50°) lighting patterns

Illuminance -vs- Working Distance



Beam Size at 80% Max Intensity -vs- Working Distance




BEAM PATTERNS

The LO300 is recommended to be used at a working distance between 300 mm to 2000 mm. Illuminance values taken on white light - 5700K


Standard (16°) beam patterns

Grid set to 75 mm




Wide (30°) beam patterns

Grid set to 75 mm



Line (10° x 50°) beam patterns

Grid set to 75 mm



EYE SAFETY

According to IEC 62471:2006. Full documentation available upon request with purchase of product.

Notice

Exempt Group: No photobiological hazard to eyes or skin even for continuous, unrestricted use. Applicable for wavelengths 625, 850, 940, 1050, 1200, 1300, 1450, 1550, and 1650.

Caution

Risk Group 1: Possibly hazardous optical radiation emitted from this product. Do not stare at operating lamp. May be harmful to eyes. Safe for most applications except prolonged exposure. Applicable for wavelengths 470, 505, 530, and WHI.

Caution


Risk Group 1: UV emitted from this product. Minimize exposure to eyes and skin. Use appropriate shielding. Safe for most applications except prolonged exposure. Applicable for wavelength 395.

Warning


Risk Group 2: UV emitted from this product. Eye or skin irritation may result from exposure. Use appropriate shielding. Does not pose optical hazard if aversion responses limit exposure. Applicable for wavelength 365.

ILLUMINATION


The ODL300 works best for:



Dark Field




Bright Field




Direct Lighting

DAISY-CHAIN LIGHTS

ODL300 Series of lights requires the use of a standard 5-pin M12 jumper cable to effectively parallel up to six ODL300 lights.




There is consistent spacing between LEDs as lights are connected together.



DUTY CYCLE

The Duty Cycle (D) is related to the Strobe Time (ST) and Rest Time (RT).

Maximum Duty Cycle for OverDrive™ light is 10% (0.1)



Calculating Rest Time

$$RT = \frac{ST}{D} - ST$$

RT = Rest Time
ST = Strobe Time
D = Duty Cycle

Example

$$RT = \frac{10 \text{ ms}}{.1} - 10 \text{ ms} = 90 \text{ ms}$$

Rest Time is 90 ms for 10 ms Strobe Time

OVERDRIVE™

OverDrive is an integrated strobe driver that provides up to 10 times the intensity of a standard driver. Utilizing SafeStrobe™ technology, an OverDrive light can be safely strobed up to 5,000 times a second.



SAFESTROBE™


SafeStrobe™ is a unique technology that applies safe working parameters to ensure high current LEDs are not damaged by driving them beyond their limits, such as maximum strobe time or duty cycle. This is especially beneficial for overdriving our high current LEDs.

PART NUMBER GUIDE

ODL300



COLOR:



LENS:

Leave blank for Standard (Narrow)
W = Wide (30°)

L = Line (10° x 50°)



LINEAR POLARIZER:

Leave blank for none
LPI = Factory Installed

Part Number Examples:


ODL300-625 ODL300, 625 nm Wavelength, Standard Lens

ODL300-WHI-L ODL300, White, Line Lens

ODL300-470-W-LPI ODL300, 470 nm Blue Wavelength, with Linear Polarizer Installed



This light is available in our SWIR LEDs.



Line lens optic not available for UV wavelengths.
Additional wavelengths and lens options available upon request.

ACCESSORIES

Power Cables



Length	Part Number
5 m	5PM12-5
10 m	5PM12-10
15 m	5PM12-15

Jumper Cables (Daisy Chain)



Length	Part Number
300 mm	5PM12-J300
1000 mm	5PM12-J1000
2000 mm	5PM12-J2000

Mount



Description	Part Number
3-Axis Pan and Tilt Mount	PB300-M5

Mounting Rails



Length	Part Number
300 mm	LEXT300
600 mm	LEXT600
900 mm	LEXT900
1200 mm	LEXT1200
Custom sizes available	

Diffuser



Description	Part Number
Diffuser Kit	L300-DKIT

Linear Polarizer



Description	Part Number
Linear Polarizer Kit	L300-LP

Power Adapters *




Description	Part Number
AC, 24 V, 1.7 A	T1 Power Supply
24 V DC, 9 A / AC input	T2 Power Supply

* European Versions Available (Add "-EURO" to end of T1. Ex: T1-EURO Power Supply.)

PRODUCT DRAWINGS

*CAD files available on our website
Drawings are in mm



GLOSSARY

This glossary covers all Smart Vision Lights product families; some content in this section may not apply to this specific light.

TERMINOLOGY

OverDrive™ Light includes an integrated high-pulse driver for complete LED light control.

Continuous Operation Light stays on continuously.

Multi-Drive™ Combines continuous operation and OverDrive™ strobe (high-pulse operation) mode into one easy-to-use light.


Built-in Driver The built-in driver allows full function without the need of an external controller.

Camera to Light Connect the light directly to the camera, without the need for additional controllers or equipment.


Polarizers Filters that reduce reflections on specular surfaces.

Diffusers Used to widen the angle of light emission, reduce reflections, and increase uniformity.


TYPES OF ILLUMINATION




Projector




Dark Field




Radial




Bright Field




Direct




Axial



Line




Diffuse Panel



Backlight

COMMON COLOR/WAVELENGTHS LEGEND

Wavelengths options range from 365 nm to 1650 nm.*
Additional wavelengths available for many light families.



*See Part Number section for **this light's** available standard wavelengths.



Shortwave Infrared LEDs are available in 1050 nm, 1200 nm, 1300 nm, 1450 nm, 1550 nm, and 1650 nm.*

*Check Part Number section to see if **this light** is available in SWIR wavelengths.



ISO 9001:2015 Certified QMS