

Integrating PowerApps with External Systems



Agenda

- Calling External Services using HTTP Actions
- Executing Child Flows from a Parent Flow
- Creating and Testing Custom Connector
- Configuring a Custom Connector to use OAuth



HTTP Request and Response

- HTTP Request
 - URL
 - Verb (e.g. GET, POST, PUT, PATCH, etc)
 - Headers
 - Body
- HTTP Response
 - Status code
 - Headers
 - Body



Working With REST-based Web Service

- Calling REST-based web service involve creating structured URLs
 - `http://subliminalsystems.com/api/Customers/?$select=LastName,FirstName,CustomerId`
- REST-based URL structured into several parts

<code>http://subliminalsystems.com/api/</code>	<code>Customers/</code>	?	<code>\$select=LastName,FirstName,CustomerId</code>
Web Service Base URL	Resource		Query String Parameters




OData Query String Parameters

- Many web services support OData
 - OData is a REST-based specification for CRUD operations
 - OData defines standard query string parameters
- Commonly-used OData query string parameters
 - **\$select** – allows you to select which properties are returned
 - **\$filter** – allows you to filter rows returned in result
 - **\$orderby** – allows you to sort rows in result
 - **\$top** – allows you to specify how many rows should be returned
 - **\$skip** – allows you to skip over rows that are not needed
 - **\$expand** – allows you to retrieve more data in one round trip




Using the JSON Viewer Chrome Extension


- Install the JSON Viewer extension



- Now you can inspect JSON in the browser



Retrieving a Single OData Instance




A screenshot of a web browser window. The address bar shows the URL `subliminalsystems.com/api/Custo` with a plus sign to the right. Below the address bar, there's a navigation bar with icons for Apps, Google, MSDN, PowerApps, Flow, and CPT Github. The main content area displays a JSON object representing an OData instance for a customer with ID 10. The JSON is formatted with syntax highlighting: curly braces are blue, strings are green, and numbers are black. The object includes metadata and various contact and address details for a customer named Barbra Bigglesworth at Soylent Corporation.


```
{
  odata.metadata: "http://subliminalsystems.com/api/$metadata#Customers/@Element",
  CustomerId: 10,
  FirstName: "Barbra",
  LastName: "Bigglesworth",
  Company: "Soylent Corporation",
  EmailAddress: "Barbra.Bigglesworth@SoylentCorporation.com",
  WorkPhone: "1(408)111-2222",
  HomePhone: "1(408)222-6666",
  Address: "6944 Glenwood Drive",
  City: "San Jose",
  State: "CA",
  Zipcode: "95133",
}
```



Using the HTTP Action



Inspecting the body of the HTTP Response





A screenshot of an HTTP response body. A large white arrow points to the "Body" label on the left. The response is a JSON object displayed in a code editor with syntax highlighting. The JSON contains metadata and customer information.


```
{
  "odata.metadata": "http://subliminalsystems.com/api/$metadata#C",
  "CustomerId": 47,
  "FirstName": "Cordell",
  "LastName": "Bridges",
  "Company": "Massive Dynamic",
  "EmailAddress": "Cordell.Bridges@MassiveDynamic.com",
  "WorkPhone": "1(800)444-5555"
}
```



Parsing JSON



Adding a New Item to a SharePoint List





DEMO

Calling an External Web Service with the HTTP Action


Agenda

- ✓ Calling External Services using HTTP Actions
- Executing Child Flows from a Parent Flow
- Creating and Testing Custom Connector
- Configuring a Custom Connector to use OAuth




Creating the Child Flow

- Child flow creating with HTTP trigger




- Select an HTTP operation (e.g. GET, POST, PUT, DELET, PATCH, etc.)




Discovering the URL for an HTTP Trigger


- HTTP POST URL is not generated until you first save the flow




- After saving the flow you can copy the HTTP POST URL



- Copy and paste the URL into Notepad




- Try executing the flow by adding the URL into address bar in browser




Parent Flow

- Parent flow uses HTTP action to execute child flow



- Set Method parameter to Get and paste in URL for child flow





DEMO

Calling a Child Flow from a Parent Flow


Agenda

- ✓ Calling External Services using HTTP Actions
- ✓ Executing Child Flows from a Parent Flow
- Creating and Testing Custom Connector
- Configuring a Custom Connector to use OAuth




Standard Connectors vs Custom Connectors












- PowerApps Supports two types of connectors
 - Standard connectors supplied out-of-box and vetted by Microsoft
 - Custom connectors created by organizations for their own use



Creating a New Custom Connector



The screenshot shows the PowerApps interface. The top navigation bar includes the PowerApps logo, the environment name 'SharePoint Confessions AAD ...', and icons for download, settings, help, and user profile. The left sidebar contains a menu with 'Home', 'Learn', 'Apps', 'Data', 'Entities', 'Option sets', 'Data integration', 'Connections', and 'Custom connectors'. The 'Custom connectors' section is active, displaying a table of existing connectors. A button labeled '+ Create custom connector' is highlighted with a blue border and a black arrow pointing to it. The dropdown menu for this button is open, showing four options: 'Create from blank', 'Import an OpenAPI file', 'Import an OpenAPI from URL', and 'Import a Postman collection'.

Name	
 Customers API Ted Pattison	
 Customers Web Service Ted Pattison	   
 Power BI Datasets API Ted Pattison	   



Defining Requests

Request

+ Import from sample

* Verb

The verb describes the operations available on a single path.

GET

* URL

This is the request URL.

http://subliminalsystems.com/api/Customers/

Path

Path is used together with Path Templating, where the parameter value is actually part of the operation's URL.

Query

Query parameters are appended to the URL. For example, in /items?id=####, the query parameter is id.

Headers

These are custom headers that are part of the request.

Body

The body is the payload that's appended to the HTTP request. There can only be one body parameter.

Request

+ Import from sample

* Verb

The verb describes the operations available on a single path.

GET

* URL

This is the request URL.

http://subliminalsystems.com/api/Customers({CustomerId})

Path

Path is used together with Path Templating, where the parameter value is actually part of the operation's URL.

* CustomerId

...

Query

Query parameters are appended to the URL. For example, in /items?id=####, the query parameter is id.

Headers

These are custom headers that are part of the request.

Body

The body is the payload that's appended to the HTTP request. There can only be one body parameter.



Defining the Response

← Connector Name Customers Web Service

1. General > 2. Security > **3. Definition** > 4. Test

✓ Update connector ✕ Close

▼ Actions (2)

Actions determine the operations that users can perform. Actions can be used to read, create, update or delete resources in the underlying connector.

1 GetCustomers ...

2 **GetCustomer** ...

+ New action

▼ References (0)

References are reusable parameters used by both actions and triggers.

← Back

Response

+ Import from sample

* Name

default

Headers

These are custom headers that are part of the response.

References Used

The following are the references used by this entity

Body

The payload that is available on the response. These are the tokens that will show up as the outputs in designer.

Address ... BirthDate ... City ... Company ... CustomerId ...

EmailAddress ... FirstName ... FirstPurchaseDate ... Gender ...

HomePhone ... LastName ... LastPurchaseDate ... State ... WorkPhone ...

Zipcode ... odata.metadata ...

Validation

This helps you identify potential issues with this response.

Validation

✓

Validation succeeded.

← Security

Test →

OpenAPI Specification and Swagger

- OpenAPI specification (OAS)
 - Community-driven open specification
 - Defines standard interface description for REST APIs
 - allows humans and computers to discover web service API
 - OpenAPI Specification removes guesswork in calling a service.
- API description defined using JSON

```
{ CustomerFactoryAPI.swagger.json x
1  {
2    "swagger": "2.0",
3    "info": {
4      "title": "CustomerFactoryApi",
5      "description": "Sample custom connector providing sample customer data",
6      "version": "1.0"
7    },
8    "host": "cptlabs.azurewebsites.net",
9    "basePath": "/api/",
10   "schemes": [ "https" ],
11   "consumes": [],
12   "produces": [],
13   "paths": {
14     "/NextCustomer": {
15       "get": {
16         "responses": {
17           "default": {
18             "description": "default",
19             "schema": {
20               "type": "object",
21               "properties": { "firstName": { "type": "string", "description": "firstName" },
22                             "lastName": { "type": "string", "description": "lastName" },
23                             "company": { "type": "string", "description": "company" },
24                             "emailAddress": { "type": "string", "description": "emailAddress" },
```





DEMO


Creating a Simple Custom Connector

Agenda

- ✓ Calling External Services using HTTP Actions
- ✓ Executing Child Flows from a Parent Flow
- ✓ Creating and Testing Custom Connector
- Configuring a Custom Connector to use OAuth



Creating an Azure AD Application



The screenshot displays the Microsoft Azure portal interface. On the left is a dark sidebar with navigation options: 'Create a resource', 'All services', 'FAVORITES', 'Dashboard', 'All resources', 'Resource groups', 'App Services', and 'Azure Active Directory'. The main content area shows a breadcrumb trail: 'Home > sharepoint confessions aad directory - App registrations > Create'. Below this is a 'Create' form with three fields: 'Name' (filled with 'Power BI Customer Connector'), 'Application type' (set to 'Web app / API'), and 'Sign-on URL' (filled with 'https://localhost'). Each field has a green checkmark indicating it is valid. A blue 'Create' button is at the bottom of the form.

Microsoft Azure

Home > sharepoint confessions aad directory - App registrations > Create

Create

* Name ⓘ
Power BI Customer Connector ✓

Application type ⓘ
Web app / API ▼

* Sign-on URL ⓘ
https://localhost ✓

Create




Application ID (aka Client ID)

Home > sharepoint confessions aad directory - App registrations > Power BI Customer Connector

Power BI Customer Connector

Registered app

⚙ Settings ✎ Manifest 🗑 Delete

Display name	Application ID
Power BI Customer Connector	0d956d63-2b3a-4a6b-8b21-5b43db48cc77 
Application type	Object ID
Web app / API	07aee325-93c9-44bb-a770-71773f948223
Home page	Managed application in local directory
https://localhost	Power BI Customer Connector

⏶

Click to copy



Configuring Permissions

Home > sharepoint confessions aad directory - App registrations > Power BI Customer Connector > Settings

Power BI Customer Connector

Registered app

⚙ Settings ✎ Manifest 🗑 Delete

Display name	Application ID
Power BI Customer Connector	0d956d63-2b3a-4a6b-8b21-5b43db48cc77
Application type	Object ID
Web app / API	07aee325-93c9-44bb-a770-71773f948223
Home page	Managed application in local directory
https://localhost	Power BI Customer Connector

⌵

Settings


🔍 Filter settings

GENERAL

- 📄 Properties >
- 🔗 Reply URLs >
- 👤 Owners >

API ACCESS

- 🔑 Required permissions >
- 🔑 Keys >



Select the Power BI Service for the API

BI Customer Connector > Settings > Required permissions > Add API access > Select an API

Add API access

1 Select an API
Power BI Service

2 Select permissions

Done

Select an API

Windows Azure Active Directory

Office 365 Exchange Online

Microsoft Graph

Office 365 SharePoint Online

Skype for Business Online

Office 365 Yammer

Dynamics CRM Online

Power BI Service

Microsoft Rights Management Services

Microsoft Intune API

Windows Azure Service Management API

Select



Select the Required Permissions

Enable Access

☐ DELEGATED PERMISSIONS

↑↓

REQUIRES ADMIN

<input type="checkbox"/>	Read and write all dataflows	No
<input type="checkbox"/>	View all dataflows	No
<input type="checkbox"/>	Read and write all content in tenant	Yes
<input checked="" type="checkbox"/>	Read and Write all Reports	No
<input type="checkbox"/>	View users Groups	No
<input type="checkbox"/>	View all Groups	No
<input type="checkbox"/>	View all Reports (preview)	No
<input type="checkbox"/>	Create content (preview)	No
<input type="checkbox"/>	View content properties (preview)	No
<input checked="" type="checkbox"/>	Read and Write all Datasets	No
<input type="checkbox"/>	View all Datasets	No

Select



Generating a Key Secret

onfessions aad directory - App registrations > Power BI Customer Connector > Settings > Keys

Settings

Filter settings

GENERAL

- Properties >
- Reply URLs >
- Owners >

API ACCESS

- Required permissions >
- Keys >**

Keys

Save Discard Upload Public Key

⚠ Copy the key value. You won't be able to retrieve after you leave this blade.

Passwords

DESCRIPTION	EXPIRES	VALUE
Key1	8/14/2019	ejVnaC0zTLRcc3ErbAhgchilb3CTC5SVyKgbvS9HLPk=

Public Keys



Data Required to Create Custom Connector

CustomConnectorAzureAD.txt - Notepad

File Edit Format View Help

Application ID (aka Client ID)

0d956d63-2b3a-4a6b-8b21-5b43db48cc77

Secret Key

ejVnaC0zTLRcc3ErbAhgchi1b3CTC5SVyKgbvS9HLPk=




Creating the New Custom Connector

1. General > 2. Security > 3. Definition > 4. Test

✓ Update connector ✕ Close

General information

Add an icon and short description to your custom connector. Your host and base URL will be automatically generated from the swagger file.



Upload connector icon
Supported file formats are PNG and JPG. (< 1MB)

↑ Upload

Icon background color
#FFFFFF

Description
A custom connector to manage Power BI datasets using the Power BI Service API

☐ Connect via on-premises data gateway [Learn more](#)

Scheme
☒ HTTPS ☐ HTTP

* Host
api.powerbi.com

Base URL
/v1.0/myorg/

Security →



Configuring the Client Id and Client Secret

← Connector Name Power BI Datasets API

1. General > **2. Security** > 3. Definition > 4. Test ✓ Create connector ✗ Cancel


Security

Choose the authentication type and fill in the required fields to set the security for your custom connector.
[Learn more](#)

Authentication type

Choose what authentication is implemented by your API *

OAuth 2.0

 Edit

OAuth 2.0

Identity Provider

Azure Active Directory

Client id *

0d956d63-2b3a-4a6b-8b21-5b43db48cc77

Client secret *

.....



What About the Redirect URL?

The image shows two side-by-side screenshots of an OAuth 2.0 configuration interface. The left screenshot shows a form with a 'Redirect URL' field containing the text 'Save the custom connector to generate the redirect URL'. A red arrow points to this field. The right screenshot shows the same form, but the 'Redirect URL' field contains the URL 'https://msmanaged-na.consent.azure-apim.net/redirect'. A red arrow points to this field. Both forms have identical values for other fields: Identity Provider (Azure Active Directory), Client id (0d956d63-2b3a-4a6b-8b21-5b43db48cc77), Client secret (masked), Login URL (https://login.windows.net), Tenant ID (common), Resource URL (https://analysis.windows.net/powerbi/api), and Scope (scope).

OAuth 2.0 Configuration Form (Left):

- Identity Provider: Azure Active Directory
- Client id *: 0d956d63-2b3a-4a6b-8b21-5b43db48cc77
- Client secret *: [Masked]
- Login URL: https://login.windows.net
- Tenant ID: common
- Resource URL *: https://analysis.windows.net/powerbi/api
- Scope: scope
- Redirect URL: Save the custom connector to generate the redirect URL
- Edit: [Icon]

OAuth 2.0 Configuration Form (Right):

- Identity Provider: Azure Active Directory
- Client id *: 0d956d63-2b3a-4a6b-8b21-5b43db48cc77
- Client secret *: [Masked]
- Login URL: https://login.windows.net
- Tenant ID: common
- Resource URL *: https://analysis.windows.net/powerbi/api
- Scope: Scope
- Redirect URL: https://msmanaged-na.consent.azure-apim.net/redirect
- Edit: [Icon]



Adding the Redirect URL back in Azure AD






Scope

Scope

Redirect URL



<https://msmanaged-na.consent.azure-apim.net/redirect>

Click to copy

Settings	×	Reply URLs
<input type="text" value="Filter settings"/>		 Save  Discard
GENERAL		https://msmanaged-na.consent.azure-apim.net/redirect
 Properties >		<input type="text"/>
 Reply URLs >		
 Owners >		



Creating a New Connection



Summary

- ✓ Calling External Services using HTTP Actions
- ✓ Executing Child Flows from a Parent Flow
- ✓ Creating and Testing Custom Connector
- ✓ Configuring a Custom Connector to use OAuth

