

Power BI Desktop Primer



Agenda

- Power BI Desktop Overview
 - Building Queries
 - Designing Data Models
 - Designing Reports




Power BI Desktop Projects

- Design queries to create a dataset
 - Most datasets created using import model
 - Datasets can be created with DirectQuery and Live Connect
- Enrich the dataset using data modeling features
 - Add calculated columns, measures, hierarchies, etc
- Visualize insights from your dataset by creating reports
 - Build reports using visuals
- Publish projects to the Power BI Service
 - Your datasets & reports can be used in Power BI embedding





Working with Power BI Desktop

- Power BI Desktop is a Windows application
 - Work is saved and published in terms of PBIX projects
 - You can work on multiple projects at once
 - Each project runs in its own Power BI Desktop instance
 - Power BI Desktop can freeze up or act buggy
 - Quit & restart Power BI Desktop if it acts strangely





Getting Around in Power BI Desktop

- What do you need to learn to use Power BI Desktop?
 - Query features for importing data
 - Designing data model & writing DAX expressions
 - Designing reports with Power BI Desktop report designer
- Navigating between view modes



Projects and PBIX Files

- Power BI Desktop projects saved using PBIX files
 - PBIX file contains data source definitions
 - PBIX file contains query definitions
 - PBIX file contains data imported from queries
 - PBIX file contains exactly one data model definition
 - PBIX file contains exactly one report
 - PBIX file never contains data source credentials




Agenda

- ✓ Power BI Desktop Overview
- Building Queries
 - Designing Data Models
 - Designing Reports




Power BI Desktop is an ETL Tool

- ETL process is essential part of any BI Project
 - **Extract** the data from wherever it lives
 - **Transform** the shape of the data for better analysis
 - **Load** the data into dataset for analysis and reporting



Query Editor Window

- Power BI Desktop provides separate Query Editor window
 - Provides powerful features for designing queries
 - Displays list of all queries in project on the left
 - Displays **Properties** and **Applied Steps** for selected query on right
 - Preview of table generated by query output shown in the middle
 - Query can be executed using **Apply** or **Close & Apply** command



Query Steps

- A query is created as a sequence of steps
 - Each step is a parameterized operation on the data
 - Each step has formula which can be viewed/edited in formula bar
 - Query starts with Source step to extract data from a data source
 - Additional steps added to perform transform operations on data
 - You can replay query operations one by one by clicking on steps

The screenshot displays the Power BI Query Editor interface. At the top, the ribbon includes 'File', 'Home', 'Transform', 'Add Column', and 'View'. Below the ribbon, the 'Formula Bar' is active, showing the formula: `= Table.ReplaceValue("#Replaced Female Values","M","Male",Replacer.ReplaceText,`. A red dashed box highlights the formula bar, with a callout box labeled 'step formula bar' pointing to it. On the left, the 'Queries [6]' pane lists 'Customers', 'Sales', 'Purchases', 'Products', 'SalesRegions', and 'SalesRegionsSort'. The main area shows a table with columns: CustomerId, Customer, State, City, Zipcode, and Gender. The table contains 14 rows of data. On the right, the 'Query Settings' pane is open, showing the 'Properties' tab with the name 'Customers'. Below the properties, the 'Applied Steps' list is visible, containing a sequence of steps: Source, Navigation, Removed Other Columns, Merged Columns, Reordered Columns, Replaced Female Values, Replaced Male Values (selected), Changed Type, and Added Conditional Column. A red dashed box highlights the 'Applied Steps' list, with a callout box labeled 'sequential list of steps for query' pointing to it.

CustomerId	Customer	State	City	Zipcode	Gender
1	Nina Diaz	CA	Eureka	95501	Female
2	Melinda Carter	CA	Napa	94558	Female
3	Pam Miller	CA	Napa	94558	Female
4	Merle Blackwell	CA	Sacramento	95823	Female
5	Ariel Hale	CA	Sacramento	95818	Male
6	Randy Carter	CA	Sacramento	95818	Male
7	Lillie Hinton	CA	Eureka	95501	Female
8	Ladonna Moody	CA	Napa	94559	Female
9	Buddy McKay	OR	Bend	97701	Male
10	Warren Sykes	CA	Sacramento	95818	Male
11	Jan Rutledge	OR	Portland	97216	Female
12	Dallas Lester	OR	Eugene	97402	Male
13	Matthew Zimmerman	OR	Portland	97220	Male
14	Sheryl Hernandez	CA	Sacramento	95823	Female


Examples of Basic Power BI Desktop Steps

- Rename column
- Convert column type
- Trim and clean column values
- Replace column values
- Format column values
- Expanding related column
- Merging columns
- Splitting columns




Sample OLTP Database: WingtipSalesDB

- Online Transaction Processing (OLTP) System
 - Used for real-time data access and transaction-based data entry
 - Optimized for faster transactions (e.g. inserts, updates & deletes)
 - Tables normalized to reduce/eliminate redundancies
 - Table schemas can be hard for business users to understand




Data Modeling using a Star Schema

- OLAP Modeling often based on Star Schema
 - Tables defined as fact tables or dimension tables
 - Fact tables related to dimension table using 1-to-many relationships




Designing Queries to Build a Star Schema

- Converts OLTP Data Model to OLAP Data Model
 - Sales table is modeled as a OLAP Fact Table
 - Other tables are modeled as OLAP Dimension tables
 - Requires pulling CustomerId column into Sales table
 - All dimension tables should be directly related to fact table



Adding a Custom Column

- Custom column provide custom logic
 - Logic must be written in M programming language



Add Custom Column

New column name:

Custom column formula:

```
= if [FirstPurchaseDate]=[LastPurchaseDate]  
then "One-time Customer"  
else "Repeat Customer"
```

Available columns:
CustomerId
Customer
State
City
ZipCode
Gender
BirthDate
FirstPurchaseDate
LastPurchaseDate
CustomerType

<< Insert

[Learn about Power BI Desktop formulas](#)

✓ No syntax errors have been detected.


OK Cancel

FirstPurchaseDate	LastPurchaseDate	CustomerType
1/28/2012	1/28/2012	One-time Customer
1/28/2012	1/28/2012	One-time Customer
1/28/2012	1/28/2012	One-time Customer
1/28/2012	1/28/2012	One-time Customer
1/28/2012	1/28/2012	One-time Customer
1/28/2012	1/28/2012	One-time Customer
1/29/2012	11/22/2015	Repeat Customer
1/29/2012	10/2/2015	Repeat Customer
1/29/2012	1/29/2012	One-time Customer
1/29/2012	5/6/2015	Repeat Customer
1/29/2012	1/29/2012	One-time Customer



Advanced Editor

- Power BI Desktop based on "M" functional language
 - Query in Power BI Desktop saved as set of M statements in code
 - Query Editor generates code in M behind the scenes
 - Advanced users can view & modify query code in Advanced Editor



Understanding Function Queries

- Query can be converted into reusable function
 - Requires editing query M code in Advanced Editor
 - Function query can be defined to accept parameters

```
GetExpensesFromFile

(FilePath as text) =>

let
    Source = Csv.Document(Web.Contents(FilePath))
    #"Changed Type" = Table.TransformColumnTypes
```

- Function query can't be edited with visual designer




Agenda

- ✓ Power BI Desktop Overview
- ✓ Building Queries
- Designing Data Models
 - Designing Reports



Table Relationships

- Tables in data model associated with relationships
 - Relationships based on single columns
 - Tabular model supports [1-to-1] and [1-to-many] relationships



Relationship Properties

- Cardinality

Cardinality

Many to One (*:1)

Many to One (*:1)

One to One (1:1)

One to Many (1:*)

- Cross filter direction

Cross filter direction

Both

Single

Both

Edit Relationship

Select tables and columns that relate to one another.

Sales

Id	Quantity	SalesAmount	InvoiceId	ProductId	CustomerId	PurchaseDate	ProductCost
2899	100	100	1457	14	888	Thursday, June 21, 2012	\$8
3824	100	100	1901	14	1137	Saturday, July 21, 2012	\$8
3968	100	100	1969	14	1173	Wednesday, July 25, 2012	\$8

Customers

CustomerId	City	State	ZipCode	Gender	BirthDate	Customer	CustomerType
55	San Jose	CA	95110	Female	Thursday, March 10, 1949	Jewell Ryan	Repeat Customer
73	San Jose	CA	95123	Male	Thursday, May 9, 1985	Granville Perry	Repeat Customer
74	San Jose	CA	95122	Female	Tuesday, June 19, 1979	Sheri Mercado	Repeat Customer

Cardinality

Many to One (*:1)

Cross filter direction

Both


☒ Make this relationship active

OK Cancel



How Do You Create a Relationship Here?

- Two tables don't have fields to create relationship
 - The solution is to create two new calculated columns



Creating Composite Key Fields

- Create composite key column in Budgets

The screenshot shows the Power BI interface with a table view of Budgets. The formula bar at the top displays the formula: `Budget Key = [Year] & "-" & [Quarter] & "-" & [Category]`. The table has five columns: Year, Quarter, Category, Amount, and Budget Key. The Budget Key column contains values like "2017-Q1-Marketing". On the right, the FIELDS pane shows the Budgets table with fields Amount, Budget Key (highlighted), and Category.

Year	Quarter	Category	Amount	Budget Key
2017	Q1	Marketing	\$5,000	2017-Q1-Marketing
2017	Q1	Office Supplies	\$8,000	2017-Q1-Office Supplies
2017	Q1	Operations	\$8,000	2017-Q1-Operations
2017	Q1	Research & Development	\$5,000	2017-Q1-Research & Development
2017	Q2	Marketing	\$6,000	2017-Q2-Marketing
2017	Q2	Office Supplies	\$4,000	2017-Q2-Office Supplies
2017	Q2	Operations	\$7,000	2017-Q2-Operations


- Create composite key column in Expenses

The screenshot shows the Power BI interface with a table view of Expenses. The formula bar at the top displays the formula: `Budget Key = VAR BudgetYear = YEAR([Date]) VAR BudgetMonth = "Q" & FORMAT([Date], "q") RETURN BudgetYear & "-" & BudgetMonth & "-" & [Category]`. The table has five columns: Date, Amount, Category, Description, and Budget Key. The Budget Key column contains values like "2017-Q2-Operations". On the right, the FIELDS pane shows the Expenses table with fields Amount, Budget Key (highlighted), and Category.

Date	Amount	Category	Description	Budget Key
Sunday, April 2, 2017	\$925	Operations	Verizon - Telephone and Internet	2017-Q2-Operations
Monday, April 3, 2017	\$142	Office Supplies	Postage Stamps	2017-Q2-Office Supplies
Wednesday, April 5, 2017	\$294	Operations	Electricity Bill	2017-Q2-Operations
Wednesday, April 5, 2017	\$120.25	Office Supplies	Coffee Supplies	2017-Q2-Office Supplies
Thursday, April 13, 2017	\$1,200	Operations	Cleaning Service	2017-Q2-Operations



Create Relationship Using Composite Keys



Working with DAX

- DAX is the language used to create data models
 - DAX stands for "Data Analysis Expression Language"
- DAX expressions are similar to Excel formulas
 - They always start with an equal sign (=)
 - DAX provides many built-in functions similar to Excel
- DAX Expressions are unlike Excel formulas...
 - DAX expressions cannot reference cells (e.g. A1 or C4)
 - Instead DAX expressions reference columns and tables

```
=SUM('Sales' [SalesAmount])
```



Writing DAX Expressions

- Some DAX expressions are simple

```
Sales Revenue = Sum(Sales[SalesAmount])
```

- Some DAX expressions are far more complex

```
Sales Growth PM = IF(
  ( ISFILTERED(Calendar[Month]) && ISFILTERED(Calendar[Date]) = FALSE() ),
  DIVIDE(
    SUM(Sales[SalesAmount]) -
    CALCULATE(
      SUM(Sales[SalesAmount]),
      PREVIOUSMONTH(Calendar[Date])
    ),
    CALCULATE(
      SUM(Sales[SalesAmount]),
      PREVIOUSMONTH(Calendar[Date])
    )
  ),
  BLANK()
)
```



Creating Variables in DAX Expressions

- Variables can be added at start of expression
 - Use **VAR** keyword once for each variable
 - Use **RETURN** keyword to return expression value

```
Budget Key =  
    VAR BudgetYear = YEAR([Date])  
    VAR BudgetMonth = "Q" & FORMAT([Date], "q")  
    RETURN  
    BudgetYear & "-" & BudgetMonth & "-" & [Category]
```



Calculated Columns vs Measures

- Calculated Columns (aka Columns)
 - Evaluated based on context of a single row
 - Evaluated when data is loaded into memory

`Column1 = <DAX expression>`



- Measures
 - Evaluated at query time based on current filter context
 - Commonly used for aggregations (e.g. SUM, AVG, etc.)
 - Used more frequently than calculated columns

`Measure1 = <DAX expression>`




Creating Measures

- Measures have advantage over calculated columns
 - They are evaluated based on the current evaluation context
- Creating a measure with Power BI Desktop
 1. Click New Measure button
 2. Give measure a name and write DAX expressions
 3. Configure formatting



Creating Tables Dynamically using DAX



The screenshot shows the Power BI Desktop interface with the 'Modeling' tab selected. A large black arrow points to the 'New Table' button in the ribbon. Below the ribbon, the DAX formula for the 'Sales Regions' table is displayed in the formula bar:

```
Sales Regions =  
DATATABLE (  
    "State", STRING,  
    "State Name", STRING,  
    "Sales Region", STRING, {  
        { "AK", "Alaska", "Western Region" },  
        { "AL", "Alabama", "Central Region" },  
        { "AR", "Arkansas", "Central Region" },  
        { "AZ", "Arizona", "Western Region" },  
        { "CA", "California", "Western Region" },  
        { "CO", "Colorado", "Western Region" },  
    }  
)
```


Below the formula bar, a preview of the 'Sales Regions' table is shown:

State	State Name	Sales Region
AK	Alaska	Western Region
AL	Alabama	Central Region
AR	Arkansas	Central Region
AZ	Arizona	Western Region
CA	California	Western Region

On the right side of the interface, the 'FIELDS' pane is visible, showing a list of tables: Sales, Calendar, Customers, Products, Purchases, and Sales Regions. The 'Sales Regions' table is selected, and its columns (Sales Region, State, State Name) are listed below it.

Integrating the Lookup Table into the Data Model

- Lookup table must be integrated into data model
 - Accomplished by creating relationship to one or more tables



The RELATED Function

- RELATED function performs cross-table lookup
 - Effectively replaces older VLOOKUP function
 - Used in many-side table to look up value from one-side
 - Used to pull data from lookup table into primary table


Sales Region = RELATED(SalesRegions[SalesRegion])										
CustomerId	City	State	ZipCode	Gender	BirthDate	Customer	CustomerType	Age	Age Group	Sales Region
55	San Jose	CA	95110	Female	3/10/49	Jewell Ryan	Repeat Customer	66	Ages 65 and over	Western Region
73	San Jose	CA	95123	Male	5/9/85	Granville Perry	Repeat Customer	30	Ages 30 TO 39	Western Region
74	San Jose	CA	95122	Female	6/19/79	Sheri Mercado	Repeat Customer	36	Ages 30 TO 39	Western Region
78	San Jose	CA	95110	Male	6/16/78	Raleigh Olson	Repeat Customer	37	Ages 30 TO 39	Western Region
136	San Jose	CA	95124	Female	1/2/45	Carrie Foreman	Repeat Customer	70	Ages 65 and over	Western Region
150	San Jose	CA	95134	Female	8/11/84	Renee McMillan	Repeat Customer	31	Ages 30 TO 39	Western Region

State Name = RELATED(SalesRegions[StateFullName])

State	ZipCode	Gender	BirthDate	Customer	CustomerType	Age	Age Group	Sales Region	State Name
CA	95110	Female	3/10/49	Jewell Ryan	Repeat Customer	66	Ages 65 and over	Western Region	California
CA	95123	Male	5/9/85	Granville Perry	Repeat Customer	30	Ages 30 TO 39	Western Region	California
CA	95122	Female	6/19/79	Sheri Mercado	Repeat Customer	36	Ages 30 TO 39	Western Region	California
CA	95110	Male	6/16/78	Raleigh Olson	Repeat Customer	37	Ages 30 TO 39	Western Region	California
CA	95124	Female	1/2/45	Carrie Foreman	Repeat Customer	70	Ages 65 and over	Western Region	California
CA	95134	Female	8/11/84	Renee McMillan	Repeat Customer	31	Ages 30 TO 39	Western Region	California



Geographic Field Metadata

- Fields in data model have metadata properties
 - Metadata used by visuals and reporting tools
 - Used as hints to Bing Mapping service



Eliminate Geographic Ambiguity


- City name alone is ambiguous
 - "Athens" defaults to Greece not Georgia
 - Concatenate city name with state to disambiguate

 		City = [City Name] & ", " & [State]			
	Age Group	Sales Region	State Name	SalesRegionSort	City
48	Ages 40 TO 49	Western Region	California	1	San Jose, CA
74	Ages 65 and over	Western Region	California	1	San Jose, CA
73	Ages 65 and over	Western Region	California	1	San Jose, CA
25	Ages 18 TO 23	Western Region	California	1	San Jose, CA
61	Ages 50 TO 65	Western Region	California	1	San Jose, CA
65	Ages 65 and over	Western Region	California	1	San Jose, CA



Dimensional Hierarchies

- Hierarchy created from two or more columns
 - All columns in hierarchy must be from the same table
 - Defines parent-child relationship between columns
 - Provides path to navigate through data
 - Provides path to drill down into greater level of detail



A Tale of Two Evaluation Contexts

- Row Context
 - Context includes all columns in iteration of current row
 - Used to evaluate DAX expression in calculated column
 - Only available in measures with iterator function (e.g. SUMX)
- Filter Context
 - Context includes filter(s) defining current set of rows
 - Used by default to evaluate DAX expressions in measures
 - Can be fully ignored or partially ignored using DAX code
 - Not used to evaluate DAX in calculated columns



Understanding Row Context

- Row context used to evaluate calculated columns

✕	✓	City = [City Name] & ", " & [State]			
	Age Group	Sales Region	State Name	SalesRegionSort	City
48	Ages 40 TO 49	Western Region	California	1	San Jose, CA
74	Ages 65 and over	Western Region	California	1	San Jose, CA
73	Ages 65 and over	Western Region	California	1	San Jose, CA
25	Ages 18 TO 23	Western Region	California	1	San Jose, CA
61	Ages 50 TO 65	Western Region	California	1	San Jose, CA
65	Ages 65 and over	Western Region	California	1	San Jose, CA

✕	✓	Age = Floor((TODAY()-Customers[BirthDate])/365, 1)			
Customer	Customer Type	Age	Age Group	Sales Region	State Name
Lucile Blake	One-time Customer	48	Ages 40 TO 49	Western Region	California
Rochelle Owen	One-time Customer	74	Ages 65 and over	Western Region	California
Corinne Finch	One-time Customer	73	Ages 65 and over	Western Region	California



Understanding Filter Context

- Visuals apply various filters in different evaluation contexts

Month in Year	2012	2013	2014	2015	Total
January	\$6,306	\$164,334	\$385,275	\$512,822	\$1,068,737
February	\$48,815	\$126,501	\$358,244	\$597,684	\$1,131,244
March	\$53,958	\$243,676	\$381,309	\$532,123	\$1,211,067
April	\$52,601	\$300,872	\$381,157	\$602,751	\$1,337,381
May	\$61,756	\$334,948	\$438,261	\$647,276	\$1,482,241
June	\$76,756	\$321,715	\$378,749	\$608,448	\$1,385,668
July	\$104,408	\$287,800	\$359,744	\$620,316	\$1,372,268
August	\$111,167	\$298,483	\$457,312	\$678,499	\$1,545,461
September	\$110,716	\$376,207	\$505,332	\$613,971	\$1,606,229
October	\$145,999	\$362,943	\$602,448	\$620,735	\$1,732,125
November	\$156,751	\$340,228	\$545,572	\$590,220	\$1,632,770
December	\$147,593	\$331,526	\$581,977	\$686,814	\$1,747,910
Total	\$1,076,826	\$3,489,234	\$5,375,379	\$7,311,660	\$17,253,100

Filters on this evaluation

[Year] = 2015

[Month in Year] = "October"

- Filter context also affected by slicers and other filters

	Month in Year	2012	2013	2014	2015	Total
Sales Region	January	\$425	\$50,169	\$61,295	\$76,614	\$188,503
<input type="checkbox"/> Select All	February	\$13,891	\$40,133	\$63,670	\$101,542	\$219,236
<input type="checkbox"/> Central Region	March	\$19,121	\$58,411	\$73,839	\$84,180	\$235,551
<input type="checkbox"/> Eastern Region	April	\$19,128	\$53,711	\$67,919	\$91,762	\$232,520
<input checked="" type="checkbox"/> Western Region	May	\$22,939	\$64,259	\$78,668	\$109,689	\$275,555
	June	\$29,082	\$50,564	\$73,504	\$88,047	\$241,197
	July	\$34,809	\$62,971	\$69,053	\$80,749	\$247,582
	August	\$36,096	\$61,217	\$76,009	\$94,719	\$268,041
Customer Type	September	\$39,415	\$68,653	\$82,697	\$94,805	\$285,570
<input type="checkbox"/> One-time customer	October	\$51,994	\$69,122	\$99,344	\$84,177	\$304,637
<input checked="" type="checkbox"/> Repeat Customer	November	\$47,020	\$52,548	\$85,924	\$74,611	\$260,102
	December	\$50,580	\$66,260	\$102,088	\$94,877	\$313,804
	Total	\$364,500	\$698,018	\$934,009	\$1,075,771	\$3,072,298

Filters on this evaluation

[Year] = 2015

[Month in Year] = "October"

[Sales Region] = "Western Region"

[Customer Type] = "Repeat Customer"



Using the CALCULATE Function

- CALCULATE function provides greatest amount of control
 - First argument defines expression to evaluate
 - Second argument defines table on which to evaluate expression
 - You can evaluate expressions with or without current filter context


```
Pct of All Products =  
DIVIDE(  
    SUM( Sales[SalesAmount] ),  
    CALCULATE(  
        Sum (Sales[SalesAmount] ),  
        ALL(Products[Category], Products[Subcategory], Products[Product])  
    )  
)
```

```
Pct of Product Category =  
DIVIDE(  
    SUM( Sales[SalesAmount] ),  
    CALCULATE(  
        Sum (Sales[SalesAmount] ),  
        ALL( Products[Subcategory], Products[Product] )  
    )  
)
```




Creating Calendar Table as Calculated Table

- Use **New Table** command in ribbon



- Create calendar table using DAX **CALENDAR** function



Adding Columns to Calendar Table

- Creating the **Year** column

X ✓ Year = YEAR('Calendar'[Date])	
Date	Year
1/1/2012	2012
1/2/2012	2012
1/3/2012	2012

- Creating the **Quarter** column

X ✓ Quarter = YEAR('Calendar'[Date]) & "-Q" & FORMAT('Calendar'[Date], "q")			
Date	Year	Quarter	
01/01/2012	2012	2012-Q1	
01/02/2012	2012	2012-Q1	
01/03/2012	2012	2012-Q1	
01/04/2012	2012	2012-Q1	
01/05/2012	2012	2012-Q1	

- Creating the **Month** column

X ✓ Month = FORMAT('Calendar'[Date], "MMM yyyy")				
Date	Year	Quarter	Month	
1/1/2012	2012	2012-Q1	Jan 2012	
1/2/2012	2012	2012-Q1	Jan 2012	
1/3/2012	2012	2012-Q1	Jan 2012	



Configuring Sort Columns

- Month column will not sort in desired fashion by default
 - For example, April will sort before January, February and March
- Creating a sort column for the **Month** column
 - MonthSort** sorts alphabetically & chronologically at same time

MonthSort = FORMAT('Calendar'[Date], "yyyy-MM")				
Date	Year	Quarter	Month	MonthSort
1/1/2012	2012	2012-Q1	Jan 2012	2012-01
1/2/2012	2012	2012-Q1	Jan 2012	2012-01

- Configure **Month** column with **MonthSort** as sort column


The screenshot shows the Power BI Desktop interface. In the 'Table' view, the 'Month' column is selected. The 'Sort By Column' dropdown menu is open, and 'MonthSort' is selected. The 'MonthSort' column is highlighted in yellow in the table view. The formula bar shows the DAX formula: `MonthSort = FORMAT('Calendar'[Date], "yyyy-MM")`. The table view shows the following data:

Date	Year	Quarter	Month	MonthSort
1/1/2012	2012	2012-Q1	Jan 2012	2012-01
1/2/2012	2012	2012-Q1	Jan 2012	2012-01




Integrating Calendar Table into Data Model

- Calendar table needs relationship to one or more tables




Calculated Fields for QTD and YTD Sales

- TOTALQTD function calculates quarter-to-date totals




- TOTALYTD function calculates year-to-date totals



Creating Running Total using CALCULATE

- Calculate a running total of sales revenue across years
 - This must be done using **CALCULATE** function




Agenda

- ✓ Power BI Desktop Overview
- ✓ Building Queries
- ✓ Designing Data Models
- Designing Reports



Creating Reports

- Power BI Desktop project contains one report
 - Report within project can contain multiple pages
 - Report pages contains visuals
- Reports can be created using filters
 - You can add visual level filters
 - You can add page level filters
 - You can add drillthrough filters
 - You can add report level filters



Built-in Visualization Types

- Table and Matrix
- Bar charts and Column charts
- Pie charts and Doughnut chart
- Line chart and Area chart
- Scatter chart and Combo charts
- Card and Multi-row Card
- Treemap
- Ribbon chart
- Waterfall chart
- Funnel chart
- Gauge
- Map and Filled Map
- Slicer
- R script visual
- Shape map (in preview)



Designing Reports with Interactive Filtering

- Slicers
 - Provide report consumers with intuitive filtering
- Visual Highlighting
 - Filtering applied when user clicks on a visual data element
- Drilldown Mode
 - Allows report consumer to drill into field hierarchy
e.g. Sales Region > State > City > Zipcode
- Drillthrough Pages
 - Allows report consumer to navigate to drillthrough page



Summary

- ✓ Power BI Desktop Overview
- ✓ Building Queries
- ✓ Designing Data Models
- ✓ Designing Reports

