Building a Canvas App with a Shopping Cart



- Caching State using Variables and Collections
- Using a Collection to Track Shopping Cart Data
- Using Patch Instead of an Edit Form
- Writing Shopping Cart Data to Back to SharePoint
- Designing Reusable Components




Designing with Variables and Collections

- Context variables
 - Created as primitive, record or table at screen scope
 - Managed using UpdateContext and Navigate
- Global variables
 - Created as primitive, record or table at app scope
 - Created and managed using Set function
- Collections
 - Created as tables at app scope
 - Managed using Collect, Clear and ClearCollect
 - Can be stored to local device using SaveData & LoadData



Code Naming Conventions


- Consistent naming conventions for variables & collections
 - Names should indicate type, purpose and scope
 - Collection names start with col such as colProductCatalog
 - Global variable names start with gbl such as gblCustomApiUrl
 - Context variables start with loc such as locCustomerFilter






Designing Canvas Apps using Collections

Browse Products Screen allows user to build collection



Submit Order Screen allows user to save to SharePoint





App OnStart

- App OnStart property used to initialize state in app
 - Event provides support for initializing state in app at startup
 - Commonly used to initialize global variables and collections
 - Right-click App in left navigation to run OnStart while in editor

```
variables ⊕ Advanced
                             : Collections
  ♠ Data sources
                  Media
                                   ClearCollect(colProductCatalog, AddColumns('[dbo].[Products]',"Quantity", 1));
   OnStart
                                   ClearCollect(colNavigationTable, Table(
                                       {NavTitle: "Home", NavTarget: 'Welcome Screen'},
        Components
Screens
                                       {NavTitle: "Browse Customers", NavTarget: 'Browse Customers Screen'},
{NavTitle: "Add Customer", NavTarget: 'Add Customer Screen'},
                                       {NavTitle: "Browse Products", NavTarget: 'Browse Products Screen'}
 P App
                                   ))
  Welcome Screen
    Browse Customers Screen
                                     Format text
                                                    Remove formatting
   Add Customer Screen
```



- ✓ Caching State using Variables and Collections
- Using a Collection to Track Shopping Cart Data
- Using Patch Instead of an Edit Form
- Writing Shopping Cart Data to Back to SharePoint
- Designing Reusable Components



Updatable Collection Columns

Often helpful to add updatable column to collections





Columns updated using calls to Patch

```
Patch(colProductCatalog, galProducts.Selected, { Quantity: (ThisItem.Quantity + 1) } )

Patch(colProductCatalog, galProducts.Selected, { Quantity: (ThisItem.Quantity - 1) } )
```





- ✓ Caching State using Variables and Collections
- ✓ Using a Collection to Track Shopping Cart Data
- Using Patch Instead of an Edit Form
- Writing Shopping Cart Data to Back to SharePoint
- Designing Reusable Components



Using Patch Instead of an Edit Form

- Sometimes edit forms are not the best option
 - Patch function used to create and update records in data source

```
Patch(
    '[dbo].[Orders]',
    Defaults('[dbo].[Orders]'),
    {
        CustomerId: galCustomers.Selected.CustomerId,
        OrderAmount: Sum(
            colShoppingCart,
            Total
        ),
        OrderDate: Today()
    }
)
```

Patch function can be used with ForAll to insert multiple records



- ✓ Caching State using Variables and Collections
- ✓ Using a Collection to Track Shopping Cart Data
- ✓ Using Patch Instead of an Edit Form
- Writing Shopping Cart Data to Back to SharePoint
- Designing Reusable Components



Capturing Return Value from Patch

```
ClearCollect(
    collastOrder,
    Patch(
        '[dbo].[Orders]',
        Defaults('[dbo].[Orders]'),
            CustomerId: galCustomers.Selected.CustomerId,
            OrderAmount: Sum(
                colShoppingCart,
                Total
            OrderDate: Today()
);
ClearCollect(
    collastOrderDetails,
    ForAll(
        colShoppingCart,
        Patch(
            '[dbo].[OrderDetails]',
            Defaults('[dbo].[OrderDetails]'),
                OrderId: First(colLastOrder).OrderId,
                ProductId: ProductId,
                Quantity: Quantity,
                Total: Total
);
```


CustomerId	OrderAmount	OrderDate	OrderId				
10	44.85	4/3/2019		14			
colLastOrder							

Id	OrderId	ProductId	Quantity	Total
36	14	1	1	14.95
37	14	4	2	19.9
38	14	6	10	10

colLastOrderDetails



Populating UI from Cached State






- ✓ Caching State using Variables and Collections
- ✓ Using a Collection to Track Shopping Cart Data
- ✓ Writing Shopping Cart Data to Back to SharePoint
- Designing Reusable Components



Enabling Components in a Canvas App







 	PowerApps	5 ~	
File	Home Inser	t View	Action
_,	New screen ∨	∠ Label	₽ Bu
F	ill		
Screens	Components	= =	
⊅ Se	earch		
+ Ne	w component		

Designing Components

- Steps to using components
 - Create new component
 - Add component properties
 - Implement component UI and behavior
 - Add component to screens in your canvas apps







Summary

- ✓ Caching State using Variables and Collections
- ✓ Using a Collection to Track Shopping Cart Data
- ✓ Writing Shopping Cart Data to Back to SharePoint
- ✓ Designing Reusable Components

