RPractical

Crizalin Wilma Salvador

2026-11-11

PART A: Basic Operations

A1: Create v as the sequence 5, 10 ,15. . . ,50 using seq(). Print its length, sum and mean.

```
v <- seq(from = 5, to = 50, by = 5)

length(v)
```

```
## [1] 10
```

```
sum(v)
```

```
## [1] 275
```

```
mean(v)
```

```
## [1] 27.5
```

A2: Create w that repeats the vector c(1, 2, 3) four times, and z that repeats each element of c(1, 2, 3) four times. Print both.

```
w <- rep(c(1, 2, 3), times = 4)

z <- rep(c(1, 2, 3), each = 4)

print(w)
```

```
##  [1] 1 2 3 1 2 3 1 2 3 1 2 3
```

```
print(z)
```

```
##  [1] 1 1 1 1 2 2 2 2 3 3 3 3
```

A3: Compute and print: remainder of 17 divided 5, integer division of 17 by 5, 2 to the of 10, the square root of 144, and pi rounded to 3 decimals.

```
17 %% 5        # Remainder
```

```
## [1] 2
```

```
17 %/% 5       # Integer division
```

```
## [1] 3
```

```
2^10           # 2 to the power of 10
```

```
## [1] 1024
```

```
sqrt(144)      # Square root of 144
```

```
## [1] 12
```

```r
round(pi, 3)   # Pi rounded to 3 decimals
```

```
## [1] 3.142
```

A4: Given a <- c(2, 4, 6, 8) and b <- c(1, 3, 5, 7), print a + b, a * b, the logical comparison a > b, and the dot product sum(a * b).

```r
a <- c(2, 4, 6, 8)
b <- c(1, 3, 5, 7)

a + b
```

```
## [1]  3  7 11 15
```

```r
a * b
```

```
## [1]  2 12 30 56
```

```r
a > b
```

```
## [1] TRUE TRUE TRUE TRUE
```

```r
sum(a * b)
```

```
## [1] 100
```

A5: Use paste() to produce "Student-1" "Student-2" "Student-3". Then identify the datatype of 42, 42L, "42", 41i, and TRUE.

```r
paste("Student", 1:3, sep = "-")
```

```
## [1] "Student-1" "Student-2" "Student-3"
```

```r
typeof(42)
```

```
## [1] "double"
```

```r
typeof(42L)
```

```
## [1] "integer"
```

```r
typeof("42")
```

```
## [1] "character"
```

```r
typeof(41i)
```

```
## [1] "complex"
```

```r
typeof(TRUE)
```

```
## [1] "logical"
```

PART B: Data Frame and Conditional Statements

B1: Create the students data frame with 8 rows using stringsAsFactors = FALSE; sex is "M", or "F"):

```r
students <- data.frame(
  id = 1:8,
  name = c("Alice", "Bruno", "Chen", "Dana", "Elif", "Farid", "Grace", "Hiro"),
  sex = c("F", "M", "M", "F", "F", "M", "F", "M"),
  section = c("A", "B", "A", "C", "B", "C", "A", "B"),
  midterm = c(78, 85, 92, 67, 74, 88, 95, 59),
  final = c(82, 79, 96, 71, 80, 91, 93, 65),
```

```
  attendance = c(95, 88, 100, 72, 90, 85, 98, 60),
  stringsAsFactors = FALSE
)

print(students)
```

```
##   id  name sex section midterm final attendance
## 1  1 Alice   F       A      78    82         95
## 2  2 Bruno   M       B      85    79         88
## 3  3  Chen   M       A      92    96        100
## 4  4  Dana   F       C      67    71         72
## 5  5  Elif   F       B      74    80         90
## 6  6 Farid   M       C      88    91         85
## 7  7 Grace   F       A      95    93         98
## 8  8  Hiro   M       B      59    65         60
```

B2: Display the structure, dimensions, column names, and summary of students.

```
str(students)
```

```
## 'data.frame':    8 obs. of  7 variables:
##  $ id        : int  1 2 3 4 5 6 7 8
##  $ name      : chr  "Alice" "Bruno" "Chen" "Dana" ...
##  $ sex       : chr  "F" "M" "M" "F" ...
##  $ section   : chr  "A" "B" "A" "C" ...
##  $ midterm   : num  78 85 92 67 74 88 95 59
##  $ final     : num  82 79 96 71 80 91 93 65
##  $ attendance: num  95 88 100 72 90 85 98 60
```

```
dim(students)
```

```
## [1] 8 7
```

```
colnames(students)
```

```
## [1] "id"         "name"       "sex"        "section"    "midterm"
## [6] "final"      "attendance"
```

```
summary(students)
```

```
##        id              name               sex             section     
##  Min.   :1.00   Length   :8   Length   :8   Length   :8   Min.   :59.00
##  1st Qu.:2.75   N.unique :8   N.unique :2   N.unique :3   1st Qu.:72.25
##  Median :4.50   N.blank  :0   N.blank  :0   N.blank  :0   Median :81.50
##  Mean   :4.50   Min.nchar:4   Min.nchar:1   Min.nchar:1   Mean   :79.75
##  3rd Qu.:6.25   Max.nchar:5   Max.nchar:1   Max.nchar:1   3rd Qu.:89.00
##  Max.   :8.00                                           Max.   :95.00
##      final         attendance
##  Min.   :65.00   Min.   : 60.00
##  1st Qu.:77.00   1st Qu.: 81.75
##  Median :81.00   Median : 89.00
##  Mean   :82.12   Mean   : 86.00
##  3rd Qu.:91.50   3rd Qu.: 95.75
##  Max.   :96.00   Max.   :100.00
```

B3: Add a column average representing the mean of midterm and final for each student, rounded to 1 decimal place.

```r
students$average <- round((students$midterm + students$final) / 2, 1)

print(students)
```

```
##   id  name sex section midterm final attendance average
## 1  1 Alice   F       A      78    82         95    80.0
## 2  2 Bruno   M       B      85    79         88    82.0
## 3  3  Chen   M       A      92    96        100    94.0
## 4  4  Dana   F       C      67    71         72    69.0
## 5  5  Elif   F       B      74    80         90    77.0
## 6  6 Farid   M       C      88    91         85    89.5
## 7  7 Grace   F       A      95    93         98    94.0
## 8  8  Hiro   M       B      59    65         60    62.0
```

B4: Add a logical column passed that is TRUE when average >= 70 and attendance >= 75.

```r
students$passed <- students$average >= 70 & students$attendance >= 75

students$passed
```

```
## [1]  TRUE  TRUE  TRUE FALSE  TRUE  TRUE  TRUE FALSE
```

B5: Add column 'standing' using nested ifelse()

```r
students$standing <- ifelse(students$average >= 90, "Honors",
                     ifelse(students$average >= 75, "Good", "Needs Support"))

students$passed
```

```
## [1]  TRUE  TRUE  TRUE FALSE  TRUE  TRUE  TRUE FALSE
```

B6: Write a function classify(score) that uses an if / else if / else chain and returns "Distinction" for 85 or above, "Merit" for 70 to 84, "Pass" for 50 to 69, and "Fail" below 50. Test it with sapply(c(90, 73, 55, 40), classify) and print the result.

```r
classify <- function(score) {
  if (score >= 85) {
    return("Distinction")
  } else if (score >= 70) {
    return("Merit")
  } else if (score >= 50) {
    return("Pass")
  } else {
    return("Fail")
  }
}

result <- sapply(c(90, 73, 55, 40), classify)
print(result)
```

```
## [1] "Distinction" "Merit"       "Pass"        "Fail"
```

PART C: rbind() and cbind()

C1: Create a data frame new_students with two students. Its columns must match the original, including average, passed and standing, computed the same way:

id 9, Ines, F, section C, midterm 81, final 84, attendance 92 id 10, Jamal, M, S]section A, midterm 70, final 68, attendance 80

Use rbind() to append them to students, saving the result as students_all.

```
new_students <- data.frame(
  id = c(9, 10),
  name = c("Ines", "Jamal"),
  sex = c("F", "M"),
  section = c("C", "A"),
  midterm = c(81, 70),
  final = c(84, 68),
  attendance = c(92, 80),
  stringsAsFactors = FALSE
)

new_students$average <- round((new_students$midterm + new_students$final) / 2, 1)
new_students$passed <- new_students$average >= 70 & new_students$attendance >= 75
new_students$standing <- ifelse(new_students$average >= 90, "Honors",
                         ifelse(new_students$average >= 75, "Good", "Needs Support"))

students_all <- rbind(students, new_students)

print (students_all)
```

```
##    id  name sex section midterm final attendance average passed      standing
## 1   1 Alice   F       A      78    82         95    80.0   TRUE          Good
## 2   2 Bruno   M       B      85    79         88    82.0   TRUE          Good
## 3   3  Chen   M       A      92    96        100    94.0   TRUE        Honors
## 4   4  Dana   F       C      67    71         72    69.0  FALSE Needs Support
## 5   5  Elif   F       B      74    80         90    77.0   TRUE          Good
## 6   6 Farid   M       C      88    91         85    89.5   TRUE          Good
## 7   7 Grace   F       A      95    93         98    94.0   TRUE        Honors
## 8   8  Hiro   M       B      59    65         60    62.0  FALSE Needs Support
## 9   9  Ines   F       C      81    84         92    82.5   TRUE          Good
## 10 10 Jamal   M       A      70    68         80    69.0  FALSE Needs Support
```

C2: Create the numeric vector quiz <- c(8, 7, 10, 6, 7, 9, 10, 5, 8, 6). Use cbind() to attach it to students_all as a column named quiz. Confirm the result is still a data frame with class().

```
quiz <- c(8, 7, 10, 6, 7, 9, 10, 5, 8, 6)
students_all <- cbind(students_all, quiz = quiz)
class(students_all)
```

```
## [1] "data.frame"
```

```
print (students_all)
```

```
##    id  name sex section midterm final attendance average passed      standing
## 1   1 Alice   F       A      78    82         95    80.0   TRUE          Good
## 2   2 Bruno   M       B      85    79         88    82.0   TRUE          Good
## 3   3  Chen   M       A      92    96        100    94.0   TRUE        Honors
## 4   4  Dana   F       C      67    71         72    69.0  FALSE Needs Support
## 5   5  Elif   F       B      74    80         90    77.0   TRUE          Good
## 6   6 Farid   M       C      88    91         85    89.5   TRUE          Good
## 7   7 Grace   F       A      95    93         98    94.0   TRUE        Honors
## 8   8  Hiro   M       B      59    65         60    62.0  FALSE Needs Support
```

```
## 9   9  Ines   F       C      81    84         92    82.5   TRUE          Good
## 10 10 Jamal   M       A      70    68         80    69.0  FALSE Needs Support
##    quiz
## 1     8
## 2     7
## 3    10
## 4     6
## 5     7
## 6     9
## 7    10
## 8     5
## 9     8
## 10    6
```

C3: Create the matrix m <- cbind(midterm = students_all$midterm, final = students_all$final) and use rbind() to append a final row containing the column means, labelled "mean".

```
m <- cbind(midterm = students_all$midterm, final = students_all$final)
m <- rbind(m, mean = colMeans(m))

print (m)
```

```
##      midterm final
##         78.0  82.0
##         85.0  79.0
##         92.0  96.0
##         67.0  71.0
##         74.0  80.0
##         88.0  91.0
##         95.0  93.0
##         59.0  65.0
##         81.0  84.0
##         70.0  68.0
## mean    78.9  80.9
```

C4: In a comment (2-3 sentences), explain what error rbind() produces if the data frames have different column names, and show the output if you safely catch it with tryCatch().

```
bad <- data.frame(id = 11, student_name = "Kira", score = 90)

tryCatch(
  rbind(students, bad),
  error = function(e) {
    message("rbind failed: ", conditionMessage(e));
    NULL
  }
)
```

```
## rbind failed: numbers of columns of arguments do not match
```

```
## NULL
```

PART D: Subsetting

D1: Extract the name column in three ways: $, [["name"]], and [, "name"].

```
way1 <- students_all$name
print(way1)
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

D2: Extract rows 2 to 5 and only the columns name, midterm, final.

```
result_D2 <- students_all[2:5, c("name", "midterm", "final")]
print(result_D2)
```

```
##    name midterm final
## 2 Bruno      85    79
## 3  Chen      92    96
## 4  Dana      67    71
## 5  Elif      74    80
```

D3: Using logical subsetting, select students with attendance above 90.

```
result_D3 <- students_all[students_all$attendance > 90, ]
print(result_D3)
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 1  1 Alice   F       A      78    82         95    80.0   TRUE     Good    8
## 3  3  Chen   M       A      92    96        100    94.0   TRUE   Honors   10
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 9  9  Ines   F       C      81    84         92    82.5   TRUE     Good    8
```

D4: Using subset(), select students of sex "F" in section "A" or "C" whose final is at least 75; return only name, section and final.

```
result_D4 <- subset(
  students_all,
  sex == "F" & (section == "A" | section == "C") & final >= 75,
  select = c(name, section, final)
)
print(result_D4)
```

```
##    name section final
## 1 Alice       A    82
## 7 Grace       A    93
## 9  Ines       C    84
```

D5: Use which.max() and which.min() to report the name of the student with the highest and lowest average.

```
highest_student <- students_all$name[which.max(students_all$average)]
lowest_student  <- students_all$name[which.min(students_all$average)]

cat("Highest average:", highest_student, "\n")
```

```
## Highest average: Chen
```

```
cat("Lowest average:", lowest_student, "\n")
```

```
## Lowest average: Hiro
```

D6: Sort students_all by average in descending order, then print the top 3 rows.

```
sorted_students <- students_all[order(-students_all$average), ]
top_3 <- head(sorted_students, 3)
print(top_3)
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 3  3  Chen   M       A      92    96        100    94.0   TRUE   Honors   10
```

```
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 6  6 Farid   M       C      88    91         85    89.5   TRUE     Good    9
```

PART E: Basic Factors

E1: Convert section and sex in students_all to factors with factor(). Print levels() of each.

```
students_all$section <- factor(students_all$section)
students_all$sex     <- factor(students_all$sex)

print(levels(students_all$section))
```

```
## [1] "A" "B" "C"
```

```
print(levels(students_all$sex))
```

```
## [1] "F" "M"
```

E2: Use table() to count students per sex and per section. *Try the two-way table of sex by section. table(students_all$sex, students_all$section). What is the output?

```
table(students_all$sex)
```

```
##
## F M
## 5 5
```

```
table(students_all$section)
```

```
##
## A B C
## 4 3 3
```

E3: Print as.integer() of the sex factor. In a comment, explain what the integers represent.

```
as.integer(students_all$sex)
```

```
##  [1] 1 2 2 1 1 2 1 2 1 2
```

E4: Create a new factor sex_label from sex using factor() with levels = c("F", "M") and labels = c("Female", "Male"). Add it to students_all and print its levels().

```
students_all$sex_label <- factor(
  students_all$sex,
  levels = c("F", "M"),
  labels = c("Female", "Male")
)

print(levels(students_all$sex_label))
```

```
## [1] "Female" "Male"
```

E5: Print summary() of sex_label. Then, using logical subsetting and mean(), print the mean average for each level of sex_label.

```
summary(students_all$sex_label)
```

```
## Female   Male
##      5      5
```

```
female_mean <- mean(students_all$average[students_all$sex_label == "Female"])
male_mean   <- mean(students_all$average[students_all$sex_label == "Male"])
```

```r
cat("Female Mean Average:", female_mean, "\n")
```

```
## Female Mean Average: 80.5
```

```r
cat("Male Mean Average:", male_mean, "\n")
```

```
## Male Mean Average: 79.3
```