

Relay Node Placement Problem

Zackary Crosley*, Maxfield Lehman*, and Zahra Zahedi*

April 2019

1 Introduction

In this project we study the problem of relay node deployment, where a number of sensors have been placed in a deployment area and the goal is to place the relay nodes while optimizing for various connectedness properties. In this problem, we have limitations on the placement of relay nodes due to the cost associated with them. As a result, we may not have sufficient relay nodes to make the entire network connected. This is why we instead optimize for a "high" level of connection where the definition of "highly connected" varies based on which connectedness property we deem most important. Our reference paper [?] (henceforth referred to as 'the paper') used a notion of connectedness for a partially disconnected graph and then introduced two explicit metrics to measure this connectedness. These metrics are as follows:

- The number of components of a graph in which a lower number of components indicates a higher degree of connectedness of a graph.
- The size of the largest component of the graph where the larger size indicates a higher degree of connectedness.

Note that a component refers to a subset V of the graph's vertices which are connected. In our problem, this corresponds to a subgraph of the desired measurement areas induced by V .

2 Problem Formulation

As discussed in the introduction, we have two metrics for connectedness. In both cases, we are given:

1. A set $P = \{p_1, \dots, p_n\}$ sensor node locations in a Euclidean plane,
2. A communication range R related to the sensors and relay nodes, and

*Names are listed in alphabetical order.

3. A budget B on the number of relay nodes.

The problem is represented by a graph $G = (V, E)$, where each $v_i \in V$ is a node corresponding to point $p_i \in P$, and edge $e_{ij} \in E$ between nodes v_i and v_j exists if the distance between p_i and p_j are less than R . This graph $G(V, E)$ may be disconnected with some number of connected components. From the graph $G = (V, E)$ an augmented graph $G' = (V', E')$ can be produced that optimizes a metric of connectedness while using at most B relay nodes in locations $Q = \{q_1, \dots, q_{|B|}\}$. These measures of connectedness for graph $G' = (V', E')$ are either the minimizing the number of connected components or maximizing the size of the largest component.

3 Problem Solutions

First Solution

To minimize the number of connected components of G' , the paper [?] has introduces the *Budget Constrained Relay node Placement with Minimum Number of Connected Component (BCRP-MNCC)* algorithm. Given the location of n sensor nodes with locations $P = \{p_1, \dots, p_n\}$, a communication range R , a constant C , and budget B_1 , we can find a set of B locations $Q = \{q_1, \dots, q_{|B|}\}$ to deploy relay-nodes such that the number of components in the graph $G' = (V', E')$ is at most C .

The following algorithm is the heuristic solution to this problem offered by [?].

Algorithm 4: Heuristic for BCRP-MNCC problem

- 1: Create an MST T' on the set of given terminal points P .
 - 2: Assign each edge e of T' a weight of
 $w(e) = \lceil \frac{\text{length}(e)}{R} \rceil - 1$
 - 3: **while** $\sum_{e \in E(T')} w(e) > B_1$ **do**
 - 4: Remove the edge that has the maximum weight
 from T' ; breaking ties arbitrarily
 - 5: **end while**
 - 6: Return the resulting forest obtained from T'
-

Figure 1: Algorithm 4 from Mazumder et. al.

As can be seen in Figure 1, calculating the location of relay-nodes that minimizes the number of components utilizes iterative reduction of a minimum spanning tree (MST). A minimum spanning tree returns the shortest possible way of connecting all the vertices of the graph. In an ideal case, this minimum spanning tree would provide us a solution to how to place our relay nodes with a single

connected network. However, this is not possible in all cases. In conditions with limited resources connecting all components may not be feasible. The algorithm introduces the concept of a budget as an upper limit, where the cost being minimized is a ratio of the euclidean distance and the communication range for a relay node. Since we are operating on a minimum spanning tree at first and on minimally-connected components in subsequent iterations, removing a single edge results in the creation of an additional component. We remove the largest cost edges in the tree necessary to fall under our budget, resulting in the minimum number of edges being removed. In this way, we minimize the number of connected components.

Second Solution

To maximize the size of the largest connected component of G' , the paper introduces the *Budget Constrained Relay node Placement with Maximum size of Largest Connected Component (BCRP-MLCC)* algorithm. Given the location of n sensor node locations $P = \{p_1, \dots, p_n\}$, a communication range R , a constant C and budget B_2 , we can find a subset of B locations $Q = \{q_1, \dots, q_{|B|}\}$ to deploy relay-nodes such that the size of the largest connected component in the graph $G' = (V', E')$ is at least C . The algorithm is given as follows.

Algorithm 5: Heuristic for solving BCRP-MLCC problem

```

1: for  $k \in n$  to 2 do
2:   Create an approximate  $k$ -MST  $T'$  on the set of
     given target points  $P$ 
3:   To each edge  $e$  of  $T'$ , assign the weight
      $w(e) = \lceil \frac{length(e)}{R} \rceil - 1$ 
4:   if  $\sum_{e \in E(T')} w(e) \leq B_2$  then
5:     Return  $T'$  as the solution of BCRP-MLCC
6:   end if
7: end for
8: Return any arbitrary terminal point as solution

```

Figure 2: Algorithm 5 from Mazumder et. al.

To determine the locations of relay-nodes that maximizes the size of the largest connected component, we find the largest approximate minimum spanning tree that comes under budget. To do this we implement a k -minimum

spanning tree (k-MST) approximation. The k-MST problem is to find a minimum spanning tree of k vertices and is NP-Hard, but many approximations with varying bounds exist. Note that the output of a k -minimum spanning tree algorithm with $k = |V|$ would be equivalent to the MST algorithm. In this implementation we iteratively decrement the value of k from the number of vertices in the graph n to a minimum of two. With each k , we calculate the k-MST. If the resulting MST is under budget, that tree is returned as the largest possible component under budget. Else, we continue with a decremented value for k . By returning the first approximate MST to fall under this budget we maximize the single connected component size.

4 Implementation of The Algorithms

We chose to implement this project in Clojure for several reasons, but particularly the spiritual enlightenment attained from working with graphs and trees from within a language whose source is itself directly manipulated as a tree. Tying into this, Clojure has a well-defined protocol for graph operations called Loom, enabling us to choose any of the various Loom implementations based on their ergonomics. Since we knew we would be implementing algorithms from the graph primitives provided by Loom and any implementation thereof, these ergonomics were of particular importance. For instance, implementing both algorithms described above requires the calculation of minimum spanning trees.

4.1 BCRP-MNCC

In the first case, Algorithm 4 from the paper, this is a standard fully spanning tree, while the next algorithm requires k -minimal spanning trees. The main benefits of Clojure for our implementation in this case are two-fold: a base protocol that would allow us to swap implementations later if we ran into teething issues with our initial choice of implementation and maximum code flexibility which allows us to wrap any unwieldy aspects of library APIs with minimal effort.

An important part of our implementation has been our use of a disjoint-set library in the process of computing minimum spanning trees, which leans heavily on the disjoint set data structure. We weren't sure if this was something we were expected to implement ourselves for this algorithm, so we implemented a set of lightweight wrapper functions to allow swapping this library out for an implementation of our own if that turns out to be required.

These well-designed abstractions allow us to implement the required algorithms with minimal cognitive overhead and with our code neatly mapping onto the pseudocode given in the paper. For example, compare the following code snippet to Figure 1:

```
(defn algorithm4
  [graph comm-range budget])
```

```

(let [mst (minimum-spanning-tree graph)
      weighted (atom (weight-tree mst comm-range))]
  (while (> (total-edge-weight @weighted)
            budget)
    (swap! weighted
      remove-edge
      (max-edge-by @weighted :weight)))
  @weighted))

```

4.2 BCRP-MLCC

For Algorithm 5 from the paper, the most difficult portion was the k-MST approximation. Selecting a k-MST implementation was challenging. Many k-MST implementations had a large time complexity, which would have dramatically slowed our program. However, the k-MST implementations with fairly low complexities were far more complicated. In the end, the more complicated but faster implementation won out and we implemented the k-MST algorithm defined by Garg in [?].

The Garg approximation works for items in the Euclidean plane. For each pair of two points $p_i, p_j \in P$ where P is the set of sensor locations derive the euclidean distance $d(i, j)$ and midpoint m . From these, form a circle centered at m with diameter $\sqrt{3}d(i, j)$. Note that if p_i and p_j are the furthest points from one another all points will be contained in the resulting circle. The approximation of this circle is merely to find the region in space which we are interested. Circumscribe the aforementioned circle with a square Q that shares the same center and edge length of $\sigma = \sqrt{3}d(i, j)$, same as the circle diameter. Finding k points that are as near to one another as possible. To do this, we divide the square into quarters, recursively, to produce a grid. Simply minimizing the number of grid squares the k-MST spans is insufficient, however, as the grid spaces may be opposite corners of Q and a smaller tree may exist. To tackle this issue, Garg introduces a potential function for a set of points to determine their proximity. The potential of a set of points S for a grid G_i is designated $G_i(S)$ as with cells of size x_i is equal to $x_i t_i$ where t_i is the number of cells in Q containing points of S . This results in the minimum potential occuring when k points occur in the fewest cells for the smallest cell size.

The size of the smallest grid size is $x_0 = \frac{\sigma}{k}$ where σ is the square edge length and k is the number of points desired for the k-MST. Further grid sizes $x_i = 2^i x_0$. At $i = \log k$, $x_i = \sigma$ or the edge size of the square. Since nothing is gained from considering this option, we consider options $i = 0, 1, \dots, \log k - 1$. The total potential for a set of points S is the sum of G_i potentials for this range. That is, $P(S) = \sum_{i=0}^{\log k - 1} G_i(S)$.

The full k-MST simply iterates over each possible combination of points p_i and p_j , creates the circle at the midpoint between them with diameter $\sqrt{3}d(i, j)$, calculate the minimum potential of points in the circumscribing square, and produces the k-MST for this minimum potential. The function returns the k-

MST produced that has the minimum weight. This algorithm can be seen below in Figure 3.

Algorithm E-MST(k);
for all pairs of points i, j **do**
 1. Construct a circle centered at the midpoint of the line
 segment (i, j) with diameter $\sigma = \sqrt{3}d(i, j)$.
 2. if circle contains at least k points **then**
 { Let Q be a square of side σ circumscribing the circle. }
 2.1. $S^* = \text{minpot}(Q)$
 { find set with minimum potential in Q }
 2.2. Compute the minimum tree spanning S^*
 Output the minimum weight tree found in Step 2.2 and the set S^* corresponding to it.
end.

Figure 3: k Minimum Spanning Tree from Garg 1997

Our implementation of this algorithm is as follows.

```
(defn k-mst
  [])
```

Once this algorithm was implemented, we could make a fairly exact duplicate of algorithm 5 from the paper. Our final implementation can be found below.

```
(defn algorithm5
  ([graph comm-range budget]
   (algorithm5 graph comm-range budget (uber/count-nodes graph)))
  ([graph comm-range budget k]
   (let [kmst (k-minimum-spanning-tree graph k)
         weighted (weight-tree kmst comm-range)]
     (if (> (total-edge-weight weighted) budget)
         weighted
         (recur graph comm-range budget (dec k))))))
```

5 Result

We have successfully implemented the first of the two algorithms from the paper, which is the budget constrained relay node placement with minimum number of connected components (BCRP-MNCC). This algorithm finds the optimal placement of nodes to minimize the number of separate networks of relay nodes. To accomplish this, we first used a graph library in Clojure and implemented a generic minimum spanning tree (MST) function. We then implemented the fourth algorithm from the paper using this and other utility functions and evaluated its results using randomly generated graphs as input. Our manual testing shows correct output, suggesting a completed implementation.

The second algorithm to implement, algorithm 5 from the paper, is the budget constrained relay node placement with maximum size of largest connected component (BCRP-MLCC). This algorithm finds the optimal node placement for sensors given a budget while maximizing the number of nodes in a single large component. This problem is still being researched before implementation. The algorithm is built off of a k-node minimum spanning tree, the calculation of which is an NP-Hard problem. As such this algorithm is an approximation, and many different implementations exist. We are still exploring the different implementations to determine which is best for our use case. One question we are trying to answer in order to make this determination is what type of k-MST is best for this problem. Some k-MST implementations require an initial root node, which may or may not be a good decision for this algorithm. Once this determination is made, we will implement the k-MST on top of our chosen graph structure, after which the completion of this algorithm is straight forward.

6 Conclusion

This project discusses and implements two algorithms designed to make placement decisions for sensor relay nodes in a limited budget environment. We implement algorithms that perform this placement while using either number of components or largest component as a placement metric. We have completed the first of the two algorithms and validated its accuracy. We are evaluating which k-MST algorithm to implement for the second algorithm, after which the remaining portion of BCRP-MLCC should be trivial to implement. We are well on track for the project to be completed and written up on time.