



MUST WINDS



KEY FEATURES

- ❖ Plug and Play – Easy setup and operation
- ❖ From 30 sec data update (Configurable)
- ❖ Ambient temperature and humidity Sensor
- ❖ Wind Speed and Direction Sensor
- ❖ Rain Gauge with Day, week, month or total
- ❖ Solar Radiation Sensor
- ❖ Built in data logging for 10000 readings
- ❖ Solar Powered Device
- ❖ Battery life 15 days with one Recharge
- ❖ Free EasyWeather remote control Windows software

APPLICATIONS

- ❖ Weather Tracking and Forecasting for Disaster management Team, Pollution control Team
- ❖ Record wind speed at site over time to determine available true wind power at Wind Turbine Site
- ❖ Remote Temperature and Humidity Monitoring
- ❖ Solar Radiation Tracking at Solar Power Plants
- ❖ Wind Speed, Direction and Temp, Humidity at Substation sites.



+91-80-23624347

Email : sales@v3novus.com





MUST WINDS

POWER SUPPLY

Input voltage	5V to 30V
Current	< 16mA (Output 1 second) @12 V
Solar Powered / Battery Powered	
Input voltage	12V nominal (9.6-16 V)
Current	< 6.5mA Low power operation

OUTPUTS

GPRS	Directly to Server on FTP, HTTP, TCP
Rs485	MODBUS (Optional)
Data Output	Configurable (1S, 2S, 4S or polled mode)

ENVIRONMENTAL

Protection class	IP65
EMC	EN 61326
Operating temperature	-35°C to +70°C
Storage temperature	-40°C to +80°C
Operating humidity	0% to 100% humidity

MECHANICAL

External Enclosure	IP 65 MS Enclosure (UV Stabilized)
Weight	10 KG with all the Sensors and Data Loggers

SOFTWARE

Server Software	For Data Display, Data Logging and Reporting
-----------------	--

OPTIONAL ACCESSORIES

Cables	15m Power & Data cable USB Configuration cable
Hardware	Heater Interface Box

WIND MEASUREMENT

Parameters	Wind speed & direction
Units of measure	m/s, knots, mph, kph, ft/min

	WIND SPEED	WIND DIRECTION
Range	0-60m/s (134 mph)	0 to 359° - No dead band
Accuracy	±2% @12m/s	±3° @12m/s
Resolution	0.01m/s (0.02 mph)	1°

AIR TEMPERATURE

Air temperature	Pt100 1/3 Class B
Range	-50°C to +100°C
Accuracy	±0.1°C
Resolution	0.1°C (0.1°F)
Units of measure	°C or °F

RELATIVE HUMIDITY

Range	0-100% RH
Accuracy	±0.8% @ 23°C
Resolution	0.1% RH
Units of measure	% RH
Compensated for temperature dependency	



+91-80-23624347

Email : sales@v3novus.com

