

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

1

2

3

4

5

6

7

8

9

10

11

12

14

9

DETAIL A

R

Y1

W1/0

G

W2

Y2

X2

T

COM

9

DETAIL B

NOTES:

1

MATERIALS AND FINISH
HOUSING: PA 6-6, UL 94-V0, COLOR GREEN.
CLAMP: BRASS, NICKEL PLATED.
TERMINAL: BRASS, TIN PLATED.
CLAMPING SCREW: M3, BRASS, NICKEL PLATED.

2.

MECHANICAL
WIRE STRIPPING LENGTH : 5.0-6.0 mm
MIN. PC BOARD HOLES DIAMETER : 1.1 mm
MAX. PC BOARD THICKNESS : 2.4 mm
RECOMMENDED TIGHTENING TORQUE FOR SCREW: 0.5 Nm.

3.

ELECTRICAL
WIRE RANGE : 16-30 AWG.
MAX. VOLTAGE : 300 V
MAX CURRENT : 13.5 A
CONTACT RESISTANCE : <15 m Ohm
INSULATION RESISTANCE : >1000 M Ohm (500V DC)

4.

OPERATING TEMPERATURE RANGE: -40°C TO +110°C

5.

END-TO-END STACKABLE W/INTERLOCK WITHOUT LOSS OF CENTERLINE SPACING.

6.

PACKED IN TRAY.

7.

RECOGNIZED UNDER THE COMPONENT PROGRAM OF UNDERWRITERS LABORATORIES INC., FILE NO E60677.

8

NOT CUMULATIVE TOLERANCE.

9

CHARACTERS INK MARKED BLACK.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±-

1 PLC ±.3

2 PLC ±.25

3 PLC ±-

4 PLC ±-

ANGLES ±2

FINISH

MATERIAL

DWN S. WELDON 20MAY2003

CHK C. RICHARD 20MAY2003

APVD C. RICHARD 20MAY2003

PRODUCT SPEC 108-20166

APPLICATION SPEC 114-20079

WEIGHT -

CUSTOMER DRAWING

TE

TE Connectivity

NAME

TERMINAL BLOCK, PCB MOUNT
SIDE ENTRY WIRE, STACKING
W/INTERLOCK, 5.08mm PITCH

SIZE

A2

CAGE CODE

00779

DRAWING NO

C-282837

RESTRICTED TO

-

SCALE

4:1

SHEET

2

OF

2

REV

H

1471-9 (3/13)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[282837-3](#)