




The
University
Of
Sheffield.

COM3504/6504 The Intelligent Web

Lecture 3: Async programming



Dr Vitaveska Lanfranchi
v.lanfranchi@sheffield.ac.uk
<https://www.sheffield.ac.uk/dcs/people/academic/vitaveska-lanfranchi>



Mr. Andy Stratton
a.stratton@sheffield.ac.uk
<https://www.sheffield.ac.uk/dcs/people/academic/andrew-stratton>



Dr Fatima Maikore
F.Maikore@sheffield.ac.uk
<https://www.sheffield.ac.uk/dcs/people/research-staff/fatima-maikore>



Let's start

- Why real-time communication?
- What are the main technologies involved
 - Async JavaScript
 - callbacks
 - timeouts
 - Promises



Real-time communication

- Ability to get resources when they are available and add new ones when we want to
- Examples of real-time applications
 - real-time messaging
 - Notifications
 - Live-streaming
- To build a real-time web application it is important to consider
 - Scalability
 - Security
 - **Async programming**
 - **Data Format**
 - **Bi-directional communication**



Scalability and Node.JS

- Node is event-based
- A single process can execute multiple requests
 - handling a huge number of simultaneous connections with high throughput



Security and Node.JS

- Allows to integrate with existing security layers to support SSO (Single Sign-on)
 - identity and access management (IAM) that enables users to securely authenticate with multiple applications and website
 - Module called passport
- Allows control access to data and systems based on the user's role.



Data Formats and Node.JS

- Streaming data consists of a series of time-stamped data packets.
- Node.JS provides an application programming interface to work with streams and allows creating readable and writable data streams
 - module called stream



The
University
Of
Sheffield.

ASYNC PROGRAMMING



What is async programming

- Async programming is a strategy whereby the program is able to control occurrences of events outside the normal flow of the main thread
 - i.e. some code is executed when an event occurs rather than when the flow of programming requires it
- Typical example is the click of a button
 - this raises an event (buttonClick) which is intercepted by the program
 - to execute some code



Why async programming?

- Many Web API features use asynchronous code
 - especially those that access or fetch resources from external devices,
 - e.g. files from the network, data from databases, video streams from a web cam, etc.
- You should learn how because
 - computational resources are scarce,
 - battery power is scarce
 - computing is very expensive



How is it done in JavaScript?

- Async operations are stored into an event queue
- The queue is dealt with after the main thread has finished processing
 - not in parallel as Js is single threaded!!
- The queued operations are completed as soon as possible
- They return their results to the JavaScript environment
- 4 methods
 - Callbacks (classic)
 - Timeouts and Intervals (delayed and repeated execution)
 - Promises (new)
 - Await/async (newer)



The
University
Of
Sheffield.

CALLBACKS



Callbacks

- JavaScript runs code sequentially in top-down order
 - However there are cases where you want your code to run only after something happens and not sequentially
- A callback is a function that is called only when another function is performed AND finished
- It is a function passed as parameter to another function `otherFunction`, and is called (or executed) inside the `otherFunction`.
 - So if the function takes time to finish, the callback is called only at the end



Callbacks – how can they be used?

- Callbacks can be used to perform an action at the end of an asynchronous action
 - i.e. an action that is executed outside the current flow
 - e.g. an action that requires to go to the server to get data
- When you pass a callback function as a parameter you pass just the name of the function without ()



Example

```
var numbers = [1, 2, 3, 4, 5, 6, 7];
```

```
function isOddNumber(number) {  
    return number % 2;  
}
```

```
var oddNumbers = numbers.filter(isOddNumber);  
console.log(oddNumbers);
```



Explanation

- I have an array of numbers and want to check which ones are odd
- I use the method filter that allows me to filter an array based on a condition
 - The filter method returns a new array
- I create a function isOddNumber(number)
- I pass isOddNumber as parameter to numbers.filter



The
University
Of
Sheffield.

TIMING EVENTS



JavaScript timing methods

- JavaScript has a series of methods that allow to execute functions in a specified timeframe
- They are ideal for running asynchronous functions
- And for callbacks



setTimeout()

- setTimeout() calls a function or evaluates an expression after a specified number of milliseconds.
- It is a method of the window object
- It is executed only once



setTimeout() – example with callback

```
<button onclick="myFunction()">Try it</button>
<script>
var myVar;
function myFunction() {
  myVar = setTimeout(alertFunc, 3000);
}
function alertFunc() {
  alert("Hello!");
}
</script>
```



setInterval()

- setInterval() calls a function or evaluates an expression at specified intervals (in milliseconds)
- It is a method of the window object
- It is repeatedly executed until stopped
 - clearInterval()
 - Window is closed



setInterval() - example

- setInterval() calls a function or evaluates an expression at specified intervals (in milliseconds)
- It is a method of the window object
- It is repeatedly executed until stopped
 - clearInterval()
 - Window is closed



What will this code output?

```
<script>  
  function myFunction()  
  { x=123;  
  }  
  var x=0;  
  myFunction();  
  alert(x);  
</script>
```



Ex.1 - What will this code output?

```
<script>  
  function myFunction()  
  { x=123;  
  }  
  var x=0;  
  myFunction();  
  alert(x);  
</script>
```



Ex.1 - Explanation

- X is first set sequentially to 0
- Then the function myFunction is called
- X is set to 123
- The alert prints 123



Ex.2 - What will this code output?

```
<script>  
function myFunction()  
{ x=123;  
}  
var x=0;  
setTimeout(myFunction, 3000);  
alert(x);  
</script>
```



Ex.2 - Explanation

- X is first set sequentially to 0
- Then the function myFunction is called but on a timeout
- Whilst waiting for myFunction to set the variable of x to 123
 - The alert prints the current value that is 0



Ex.3 - What will this code output?

```
<script>  
function myFunction() {  
    x=x*2;  
    alert(x);  
}  
var x=1;  
setTimeout(myFunction, 3000);  
</script>
```



Ex.3 - Explanation

- X is first set sequentially to 1
- Then the function myFunction is called but on a timeout
- In myFunction the value of x is multiplied by 2.
- The alert is inside my function so after the timeout will prints the current value that is 2



Ex.4 - What will this code output?

```
<script>  
function myFunction() {  
    x=x*2;  
    setTimeout(myFunction2, 3000);  
    alert(x);  
}  
function myFunction2() {  
    x=1234;  
}  
var x=1;  
setTimeout(myFunction, 3000);  
</script>
```



Ex.4 - Explanation

- X is first set sequentially to 1
- Then the function myFunction is called but on a timeout
- In myFunction the value of x is multiplied by 2.
- myFunction2 is called on a setTimeout to set the value of x to 1234
- The alert is inside my function so whilst waiting for myFunction2 to set the new value will prints the current value that is 2



Ex.5 - What will this code output?

<script>

function *myFunction*() {

x=*x**2;

setInterval(*myFunction*2, 3000);

alert(*x*);

}

function *myFunction*2() {

x=1234;

}

var *x*=1;

setTimeout(*myFunction*, 3000);

</script>



Ex.5 - Explanation

- X is first set sequentially to 1
- Then the function myFunction is called but on a timeout
- In myFunction the value of x is multiplied by 2.
- myFunction2 is called on a setInterval to repeatedly set the value of x to 1234
- The alert is inside my function so whilst waiting for myFunction2 to set the new value will prints the current value that is 2



The
University
Of
Sheffield.

JAVASCRIPT PROMISES



What are promises

- Promises are a way to create asynchronous code that allows easy sequencing of async processes
- Following a very familiar structure:
- if x
 - do Y
 - then do W
 - then do Z



Promise status

- A Promise can be:
 - *pending*: initial state
 - *fulfilled*: the operation was completed successfully.
 - Returns a value
 - *rejected*: the operation failed.
 - Returns an error



How promises work

- Declaration
 - it declares a long running computation
 - it declares placeholders for the behaviour to adopt in case of success and in case of error (resolve and reject represent functions passed as parameters)
- Consumption
 - it declares the functions actual functions to be used for success/error
- Execution
 - it runs the promise code and calls the actual success/reject function



Promises methods

- `Promise.then()` takes two arguments
 - a callback for success
 - A callback for failure.
- `Promise.catch()` deals with the rejected promise
- You can chain promises
- You can combine them with timed operations



Example

```
function myDisplayer(username) {  
  document.getElementById("demo").innerHTML = username;  
}
```

// declaration

```
var myPromise = new Promise(function(myResolve, myReject) {  
  var x = prompt("What is your name?")
```



The
University
Of
Sheffield.

Example 2

```
// consumption
```

```
if (x !== null) {  
  myResolve(x);  
} else {  
  myReject("Error");  
}  
});
```

```
//execution
```

```
myPromise.then(  
  function(value) {myDisplayer(value);}  
);  
  
myPromise.catch(  
  function(error) {myDisplayer(error);}  
);
```



Example in ES6

```
let myPromise = time => new Promise((resolve) => setTimeout(resolve, time));
```


```
myPromise(3000).then(() => alert('Hello'));
```

```
myPromise.catch(  
  (error) => console.log(error.message)  
);
```




IntelliJ errors with ES6?

- Make sure ES6 is enabled in IntelliJ
 - Preferences -> Languages and Frameworks -> Javascript





Async and await

- Javascript has a keyword `async`
 - takes as input a function and makes it asynchronous
 - returns a promise
- The keyword `await` before a function makes the function wait for a promise
- Keeps syntax tidy
- You could for example use it to verify user data from a database



Async and await example

```
const getUserData = async () => {  
  const response = await prompt('what is your name');  
  document.getElementById("username").innerHTML = response;  
  
}  
getUserData();
```



The
University
Of
Sheffield.

Questions

