## CERTIFICATE SPIKE ISOTOPIC REFERENCE MATERIAL IRMM-646

4.586(27) · 10<sup>-3</sup> mol (<sup>34</sup>S) · kg<sup>-1</sup> (solution)

The Spike Isotopic Reference Material is supplied with an isotope amount content of <sup>34</sup>S certified as above.

The amount content of other sulphur isotopes present are related to the <sup>34</sup>S content through the following certified amount ratios:

> $n(^{32}S)/n(^{34}S)$ : 0.038 314 9(31)  $n(^{33}S)/n(^{34}S)$ : 0.000 470 88(15)  $n(^{36}S)/n(^{34}S)$ : 0.000 018 1(37)

This corresponds to an isotopic composition with the following abundances:

amount fraction (-100)		mass fraction (·100)	
$n(^{32}S)/n(S)$	3.688 37(30)	$m(^{32}S)/m(S)$	3.479 24(27)
$n(^{33}S)/n(S)$	0.045 329(14)	$m(^{33}S)/m(S)$	0.044 095(14)
$n(^{34}S)/n(S)$	96.264 56(46)	$m(^{34}S)/m(S)$	96.474 82(46)
$n(^{36}S)/n(S)$	0.001 74(36)	$m(^{36}S)/m(S)$	0.001 85(38)

The molar mass of the sulphur in this sample is 33.893 84(22) q·mol<sup>-1</sup>

From the certified values, the following amount content and mass fractions are derived:

> $4.764(28) \cdot 10^{-3} \text{ mol (S)} \cdot \text{kg}^{-1} \text{ (solution)}$  $1.614 8(94) \cdot 10^{-4} \text{ kg (S)} \cdot \text{kg}^{-1} \text{ (solution)}$ 1.554 5(91) · 10<sup>-4</sup> kg (<sup>34</sup>S) · kg<sup>-1</sup> (solution)

B-2440 GEEL (Belgium) Tel.: +32-(0)14-571 608 • Fax: +32-(0)14-571 863

## **NOTES**

- 1. All uncertainties indicated are expanded uncertainties  $U = k \cdot u_c$  where  $u_c$  is the combined standard uncertainty estimated following the ISO/BIPM Guide to the Expression of Uncertainty in Measurement. They are given in parentheses and include a coverage factor k=2. They apply to the last two digits of the value. The values certified are traceable to the SI.
- 2. The Spike Isotopic Reference Material IRMM-646 comes in a flame-sealed quartz ampoule containing about  $24\mu mol$  sulphur in 5mL of a nitric acid solution. The molarity is about 2.8 M HNO<sub>3</sub>.
- 3. The atomic masses, used in the calculations, are<sup>1</sup>

32S : 31.97207073(15) g·mol<sup>-1</sup>
33S : 32.97145854(15) g·mol<sup>-1</sup>
34S : 33.96786687(14) g·mol<sup>-1</sup>
36S : 35.96708088(25) g·mol<sup>-1</sup>

- 4. IRMM-646 was obtained by reverse IDMS using IRMM-643, IRMM-644 and IRMM-645. The acid used was prepared in house by subboiling distillation of analytical grade nitric acid. Full details of the preparation procedure can be found in IRMM internal Report GE/IM/R/03/00.
- 5. The values of this Spike Isotopic Reference Material are traceable to the SI in the shortest possible way. Measurements calibrated against these Isotopic Reference Materials have therefore the potential of being traceable to the SI.

The chemical preparation of this Spike Isotopic Reference Material was performed by M Ostermann.

Metrological weighings required in the preparation and certification were performed by B Dyckmans – Van Hout. The ampoulation of this Spike Isotopic Reference Material was accomplished by M Ostermann, M Berglund and G Van Baelen.

M Berglund co-ordinated the work leading to the establishment, certification and issuance of this Isotopic Reference Material. A Verbruggen was responsible for the preparation and issuance of the certificate.

B-2440 GEEL June 2005

Dr P Taylor Head IRMM Isotope Measurements

Lit

\_

<sup>&</sup>lt;sup>1</sup> G. Audi and A.H. Wapstra, The 1993 atomic mass evaluation, Nucl Phys A565 (1993) 1-65.