

Model ensembles and mixtures of experts

MIPT

2022





Model ensembling

Definition (Wiki)

In statistics and machine learning, ensemble methods use multiple learning algorithms to obtain better predictive performance than could be obtained from any of the constituent learning algorithms alone. A machine learning ensemble consists of only a concrete finite set of alternative models, but typically allows for much more flexible structure to exist among those alternatives.

Mixture model

$$f = \sum \gamma_i f_i(x)$$



Model selection: coherent Bayesian inference

First level: find optimal parameters:

$$w = \arg \max \frac{p(\mathcal{D}|w)p(w|h)}{p(\mathcal{D}|h)},$$


Second level: find optimal model:

Evidence:

$$p(\mathcal{D}|h) = \int_w p(\mathcal{D}|w)p(w|h)dw.$$



Model selection scheme



Polynomial regression example

Mixture vs Bayesian model averaging

Mixture:




$$f = \sum \gamma_i f_i(X) = \sum \prod_x p(x, \gamma_i)$$

Averaging:


$$f = \sum p(f_i) f_i(X).$$

Mixture of experts


$$f = \sum \gamma_i(x) f_i(x)$$



MLP: mixture?



Mixutre of experts with hierarchy




Multimodels


$$f = \sum \gamma_i(x) f_i(x),$$
$$\sum \gamma = 1, \quad \gamma_i \in 0, 1.$$

Structure restrictions


An example of restrictions for structure parameter γ , $|\gamma| = 3$.




Cube vertices



Simplex vertices



Cube interior




Simplex interior

Prior distribution for the model structure

Every point in a simplex defines a model.


Gumbel-Softmax distribution: $\boldsymbol{\Gamma} \sim \text{GS}(\mathbf{s}, \lambda_{\text{temp}})$



$$\lambda_{\text{temp}} \rightarrow 0$$




$$\lambda_{\text{temp}} = 0.995$$



$$\lambda_{\text{temp}} = 5.0$$


Dirichlet distribution: $\boldsymbol{\Gamma} \sim \text{Dir}(\mathbf{s}, \lambda_{\text{temp}})$



$$\lambda_{\text{temp}} \rightarrow 0$$



$$\lambda_{\text{temp}} = 0.995$$




$$\lambda_{\text{temp}} = 5.0$$

Multi-domain tasks

Original Image, x



Translated Image, $f(x)$




Original Image, y




Translated Image, $g(y)$



Multi-domain tasks



Neural architecture search example



Structure selection: neural architecture search space


The model f is defined by the **structure** $\Gamma = [\gamma^{0,1}, \gamma^{1,2}]$.

$$\text{Model: } f(x) = \mathbf{softmax} \left((w_0^{1,2})^T f_1(x) \right), \quad f(x) : \mathbb{R}^n \rightarrow [0, 1]^{|Y|}, \quad x \in \mathbb{R}^n.$$

$$f_1(x) = \gamma_0^{0,1} g_0^{0,1}(x) + \gamma_1^{0,1} g_1^{0,1}(x),$$

where $w = [w_0^{0,1}, w_0^{1,2}]^T$ — parameter matrices, $g_0^{0,1}$ is a convolution, $g_1^{0,1}$ is a pooling operation, $g_{1,2}^0$ is a generalized-linear function.

$$\gamma_0^{0,1} g_0^{0,1}(x) = \gamma_0^{0,1} \mathbf{Conv}(x, w_0^{0,1})$$



Deep learning model structure as a graph

Define:

- ① acyclic graph (V, E) ;
- ② for each edge $(j, k) \in E$: a vector primitive differentiable functions $g^{j,k} = [g_0^{j,k}, \dots, g_{K^{j,k}}^{j,k}]$ with length of $K^{j,k}$;
- ③ for each vertex $v \in V$: a differentiable aggregation function \mathbf{agg}_v .
- ④ a function $f = f_{|V|-1}$:

$$f_v(w, x) = \mathbf{agg}_v \left(\{ \langle \gamma^{j,k}, g^{j,k} \rangle \circ f_j(x) \mid j \in \text{Adj}(v_k) \} \right), v \in \{1, \dots, |V| - 1\}, \quad f_0(x) = x \quad (1)$$

that is a function from \mathbb{X} into a set of labels \mathbb{Y} for any value of $\gamma^{j,k} \in [0, 1]^{K^{j,k}}$.

Definition

A *parametric set of models* \mathfrak{F} is a graph (V, E) with a set of primitive functions $\{g^{j,k}, (j, k) \in E\}$ and aggregation functions $\{\mathbf{agg}_v, v \in V\}$.

Statement

A function $f \in \mathfrak{F}$ is a model for each $\gamma^{j,k} \in [0, 1]^{K^{j,k}}$.

Neural Architecture Search: problem statement

w are model parameters.

Γ is a structure.


$$\Gamma^* = \arg \max Q(w^*, \Gamma),$$

$$w^* = \arg \max L(w, \Gamma).$$

DARTS

The model is a multigraph, where edges $[g^e]$ correspond to submodels, vertices $f_v(x)$ are the results of submodels:

$$f_v = \langle \gamma, \text{softmax}([g^e(x)]) \rangle.$$






XNAS

Algorithm 1 XNAS for a single forecaster

- 1: **Input:** The learning rate η ,
Loss-gradient bound \mathcal{L} ,
Experts predictions $\{f_{t,i}\}_{i=1}^N \forall t = 1, \dots, T$
 - 2: **Init:** $I_0 = \{1, \dots, N\}$, $v_{0,i} \leftarrow 1, \forall i \in I_0$
 - 3: **for** rounds $t = 1, \dots, T$ **do**
 - 4: Update ω by descending $\nabla_{\omega} \ell_{\text{train}}(\omega, v)$
 - 5: $p_t \leftarrow \frac{\sum_{i \in I_{t-1}} v_{t-1,i} \cdot f_{t-1,i}}{\sum_{i \in I_{t-1}} v_{t-1,i}}$ #Predict
 - 6: {loss gradient revealed: $\nabla_{p_t} \ell_{\text{val}}(p_t)$ }
 - 7: **for** $i \in I_{t-1}$ **do**
 - 8: $R_{t,i} = -\nabla_{p_t} \ell_{\text{val}}(p_t) \cdot f_{t,i}$ #Rewards
 - 9: $v_{t,i} \leftarrow v_{t-1,i} \cdot \exp\{\eta R_{t,i}\}$ #EG step
 - 10: **end for**
 - 11: $\theta_t \leftarrow \max_{i \in I_{t-1}} \{v_{t,i}\} \cdot \exp\{-2\eta \mathcal{L}(T-t)\}$
 - 12: $I_t \leftarrow I_{t-1} \setminus \{i \mid v_{t,i} < \theta_t\}$ #Wipeout
 - 13: **end for**
-

ImageNet Architecture	Test error	Params (M)	Search cost
SNAS [50]	27.3	4.3	1.5
ASAP [29]	26.7	5.1	0.2
DARTS [25]	26.7	4.9	1
NASNet-A [56]	26.0	5.3	1800
PNAS [24]	25.8	5.1	150
Amoeba-A [33]	25.5	5.1	3150
RandWire [48]	25.3	5.6	0
SharpDarts [17]	25.1	4.9	0.8
Amoeba-C [33]	24.3	6.4	3150
XNAS	24.0	5.2	0.3

XNAS



Model selection: hybrid approach


Definition

Given a set Λ .

Hypernetwork is a parametric mapping from Λ to set \mathbb{R}^n of the model f parameters:


$$G : \Lambda \times \mathbb{R}^u \rightarrow \mathbb{R}^n,$$

where \mathbb{R}^u is a set of hypernetwork parameters.



Hypernetworks for the optimal model selection

Hypernetworks allow to select the optimal model on the inference step.



Architecture complexity control

The hypernetworks can approximate not only the model parameter w , but also structural parameters γ .

Baseline: DARTS

A model architecture is a directed graph with non-linear operations $f^{(i,j)}$ that are induced by basic functions $g^{(i,j)}$ with weights obtained by softmax function application:

$$f^{(i,j)}(x) = \langle \text{softmax}(\gamma^{(i,j)}), g^{(i,j)}(x) \rangle$$


Our proposal

To use a mapping $\gamma(\lambda)$ instead of constant structural parameters γ , where λ is a regularization term for the loss function:

$$E_{\lambda} \left(\log p(y|X, w, \Gamma(\lambda)) + \lambda \sum_{(i,j)} \langle \text{softmax}(\gamma(\lambda)^{(i,j)}), n(g^{(i,j)}) \rangle \right),$$

where $n(g^{(i,j)})$ is a vector of amount of parameters for all the basic functions g .

Example: CIFAR-10



$$E_{\lambda} \left(\log p(y|X, w, \Gamma(\lambda)) + \lambda \sum_{(i,j)} \langle \text{softmax} \left(\gamma(\lambda)^{(i,j)} \right), n(g^{(i,j)}) \rangle \right).$$

Uncertainty estimation using ensembles




Figure 1: Results on a toy regression task: x -axis denotes x . On the y -axis, the blue line is the *ground truth* curve, the red dots are observed noisy training data points and the gray lines correspond to the predicted mean along with three standard deviations. Left most plot corresponds to empirical variance of 5 networks trained using MSE, second plot shows the effect of training using NLL using a single net, third plot shows the additional effect of adversarial training, and final plot shows the effect of using an ensemble of 5 networks respectively.

Neural ensemble search





Figure 3: Illustration of one iteration of NES-RE. Network architectures are represented as colored bars of different lengths illustrating different layers and widths. Starting with the current population, ensemble selection is applied to select parent candidates, among which one is sampled as the parent. A mutated copy of the parent is added to the population, and the oldest member is removed.

Neural ensemble search




Algorithm 1: NES with Regularized Evolution

- Data:** Search space \mathcal{A} ; ensemble size M ; comp. budget K ; $\mathcal{D}_{\text{train}}, \mathcal{D}_{\text{val}}$; population size P ; number of parent candidates m .
- 1 Sample P architectures $\alpha_1, \dots, \alpha_P$ independently and uniformly from \mathcal{A} .
 - 2 Train each architecture α_i using $\mathcal{D}_{\text{train}}$, and initialize $\mathbf{p} = \mathcal{P} = \{f_{\theta_1, \alpha_1}, \dots, f_{\theta_P, \alpha_P}\}$.
 - 3 **while** $|\mathcal{P}| < K$ **do**
 - 4 Select m parent candidates $\{f_{\tilde{\theta}_1, \tilde{\alpha}_1}, \dots, f_{\tilde{\theta}_m, \tilde{\alpha}_m}\} = \text{ForwardSelect}(\mathbf{p}, \mathcal{D}_{\text{val}}, m)$.
 - 5 Sample uniformly a parent architecture α from $\{\tilde{\alpha}_1, \dots, \tilde{\alpha}_m\}$. // α stays in \mathbf{p} .
 - 6 Apply mutation to α , yielding child architecture β .
 - 7 Train β using $\mathcal{D}_{\text{train}}$ and add the trained network $f_{\theta, \beta}$ to \mathbf{p} and \mathcal{P} .
 - 8 Remove the oldest member in \mathbf{p} . // as done in RE [49].
 - 9 Select base learners $\{f_{\theta_1^*, \alpha_1^*}, \dots, f_{\theta_M^*, \alpha_M^*}\} = \text{ForwardSelect}(\mathcal{P}, \mathcal{D}_{\text{val}}, M)$ by forward step-wise selection without replacement.
 - 10 **return** ensemble $\text{Ensemble}(f_{\theta_1^*, \alpha_1^*}, \dots, f_{\theta_M^*, \alpha_M^*})$
-


Neural ensemble search



Neural ensemble search




Neural ensemble search



$$\mathbb{E}_{\hat{P}} \left[\left| \mathbb{P} \left(\hat{Y} = Y \mid \hat{P} = p \right) - p \right| \right]$$
$$\text{ECE} = \sum_{m=1}^M \frac{|B_m|}{n} \left| \text{acc}(B_m) - \text{conf}(B_m) \right|,$$

Neural ensemble search



References

- Bishop C. M., Nasrabadi N. M. Pattern recognition and machine learning. – New York : springer, 2006. – Т. 4. – №. 4. – С. 738.
- Адуенко А. А. 2017. Выбор мультимоделей в задачах классификации. Диссертация.
- Jordan M. I., Jacobs R. A. Hierarchical mixtures of experts and the EM algorithm //Neural computation. – 1994. – Т. 6. – №. 2. – С. 181-214.
- Бахтеев О. Ю. 2020. Байесовский выбор субоптимальной структуры модели глубокого обучения. Диссертация.
- Kuznetsova R., Bakhteev O., Ogaltsov A. Variational learning across domains with triplet information //arXiv preprint arXiv:1806.08672. – 2018.
- Wang Q. et al. Multi-path neural networks for on-device multi-domain visual classification //Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision. – 2021. – С. 3019-3028.
- Liu H., Simonyan K., Yang Y. Darts: Differentiable architecture search //arXiv preprint arXiv:1806.09055. – 2018.
- Nayman N. et al. Xnas: Neural architecture search with expert advice //Advances in neural information processing systems. – 2019. – Т. 32.
- Ha D., Dai A., Le Q. V. Hypernetworks //arXiv preprint arXiv:1609.09106. – 2016.
- Grebenkova O., Bakhteev O. Y., Strijov V. Variational deep learning model optimization with complexity control //Informatika i Ee Primeneniya (Inform. Appl.). – 2021. – Т. 15. – №. 1. – С. 42-49.
- Yakovlev K. D. et al. Neural Architecture Search with Structure Complexity Control //International Conference on Analysis of Images, Social Networks and Texts. – Springer, Cham, 2022. – С. 207-219.
- Lakshminarayanan B., Pritzel A., Blundell C. Simple and scalable predictive uncertainty estimation using deep ensembles //Advances in neural information processing systems. – 2017. – Т. 30.
- Zaidi S. et al. Neural ensemble search for uncertainty estimation and dataset shift //Advances in Neural Information Processing Systems. – 2021. – Т. 34. – С. 7898-7911.
- Guo C. et al. On calibration of modern neural networks //International conference on machine learning. – PMLR, 2017. – С. 1321-1330