



Topic

- CRUD concepts with PHP and Bootstrap

Objectives

Students are expected to:

1. Students are able to create CRUD forms using PHP
2. Students are able to create CRUD forms using Bootstrap
3. Students are able to create CRUD forms using JQuery and Ajax

Creating a Member (Anggota) Table

The first step in creating a CRUD feature is to create a “anggota” table. In this practicum, we will use a database. Create a database on MySQL named "prakwebdb". Next, the thing that must be done is to create a “anggota” table. The “anggota” table consists of *nama*, *jenis_kelamin*, *alamat*, and *no_telp*. The following are the conditions made in the “anggota” table:

The screenshot shows the MySQL Structure tool interface for creating a table named 'anggota'. The table has 5 columns:

Name	Type	Length/Values	Default	Collation	Attributes	Null	Index
id	INT		None			<input type="checkbox"/>	PRIMARY
nama	VARCHAR	100	None			<input type="checkbox"/>	---
jenis_kelamin	ENUM	'L','P'	None			<input type="checkbox"/>	---
alamat	VARCHAR	200	None			<input type="checkbox"/>	---
no_telp	VARCHAR	20	None			<input type="checkbox"/>	---

If successful, it will appear as below, make sure *jenis_kelamin* is of the enum type. An enum is a type of data in a Mysql database that contains predefined string values. An enum column can only contain one of several specified string values .

Server: 127.0.0.1 » Database: prakwebdb » Table: anggota

Browse

Structure

SQL

Search

Insert

Export

Import

Privileges

















Operations

Tracking

T

Table structure

Relation view

	#	Name	Type	Collation	Attributes	Null	Default	Comments	Extra	Action
<input type="checkbox"/>	1	id 	int(11)			No	None		AUTO_INCREMENT	 Change  Drop  More
<input type="checkbox"/>	2	nama	varchar(100)	utf8mb4_general_ci		No	None			 Change  Drop  More
<input type="checkbox"/>	3	jenis_kelamin	enum('L', 'P')	utf8mb4_general_ci		No	None			 Change  Drop  More
<input type="checkbox"/>	4	alamat	varchar(200)	utf8mb4_general_ci		No	None			 Change  Drop  More
<input type="checkbox"/>	5	no_telp	varchar(20)	utf8mb4_general_ci		No	None			 Change  Drop  More

Practical Section 1. CRUD - Read

Step	Information
1	Create a new file in the week10 directory, naming it koneksi.php.
2	Type into the koneksi.php file the code below.
3	<pre><?php // Koneksi ke database \$koneksi = mysqli_connect("localhost", "root", "", "prakwebdb"); // Periksa koneksi if (mysqli_connect_errno()) { die("Koneksi database gagal: " . mysqli_connect_error()); }</pre>
4	Create a new file in the week10 directory, naming it index.php.
5	Type into the index.php file the code below.

	<pre><!DOCTYPE html> <html> <head> <title>Data Anggota</title> <link rel="stylesheet" href="style.css"> </head> <body> <div class="container"> <h2>Data Anggota</h2> Tambah Anggota <?php include('koneksi.php'); \$query = "SELECT * FROM anggota order by id desc"; \$result = mysqli_query(\$koneksi, \$query); if (mysqli_num_rows(\$result) > 0) { \$no = 1; echo "<table>"; echo "<tr><th>No</th><th>Nama</th><th>Jenis Kelamin</th> <th>Alamat</th><th>No. Telp</th><th>Aksi</th></tr>"; while (\$row = mysqli_fetch_array(\$result)) { \$kelamin = (\$row["jenis_kelamin"] === 'L' ? 'Laki-Laki':'Perempuan'; echo "<tr> <td>" . \$no++ . "</td><td>" . \$row["nama"] . "</td> <td>" . \$kelamin . "</td><td>" . \$row["alamat"] . "</td> <td>" . \$row["no_telp"] . "</td> <td>Edit Hapus</td> </tr>"; } echo "</table>"; } else { echo "Tidak ada data."; } mysqli_close(\$koneksi); <?> </div> <script> function konfirmasiHapus(id, nama) { var konfirmasi = confirm("Apakah Anda yakin ingin menghapus data dengan Nama " + nama + "?"); if (konfirmasi) { window.location.href = "proses.php?aksi=hapus&id=" + id; } } </script> </body> </html></pre>
6	Create a new file in the week10 directory, naming it style.css.
7	Type into the style.css file the code below.

	<pre> body { font-family: Arial, sans-serif; background-color: #f2f2f2; } .container { max-width: 600px; margin: 0 auto; padding: 20px; background-color: #fff; border-radius: 5px; box-shadow: 0px 0px 5px #888888; } h2 { text-align: center; } table { width: 100%; border-collapse: collapse; margin-top: 20px; } table, th, td { border: 1px solid #ddd; } th, td { padding: 8px; text-align: left; } th { background-color: #f2f2f2; } .btn-tambah { display: inline-block; background-color: #4CAF50; color: white; padding: 10px 20px; text-align: center; text-decoration: none; font-size: 16px; margin-top: 20px; border: none; cursor: pointer; border-radius: 5px; } .btn-tambah:hover { background-color: #45a049; } form { margin-top: 20px; } label { display: block; font-weight: bold; } input[type="text"] { width: 95%; padding: 10px; margin-bottom: 10px; border: 1px solid #ccc; border-radius: 3px; } .radio-group label { display: inline; margin-right: 20px; } input[type="radio"] { margin-right: 5px; } button[type="submit"], .btn-kembali { text-decoration: none; background-color: #4CAF50; color: white; padding: 10px 20px; border: none; border-radius: 5px; cursor: pointer; } button[type="submit"]:hover, .btn-kembali:hover { background-color: #45a049; } .btn-kembali { background-color: #e74c3c; } </pre>
8	<p>Save the file, then open a browser and run localhost/week10 . What do you understand from the use of the script. Record below your understanding. (Question No. 1)</p>

Practical Section 2. CRUD - Create

Step	Information
1	Create a new file in the week10 directory, naming it create.php.
2	Type into the create.php file the code below.

3	<pre> <!DOCTYPE html> <html> <head> <title>Tambah Data Anggota</title> <link rel="stylesheet" href="style.css"> </head> <body> <div class="container"> <h2>Tambah Data Anggota</h2> <form action="proses.php?aksi=tambah" method="post"> <label for="nama">Nama:</label> <input type="text" name="nama" id="nama" required> <label for="jenis_kelamin">Jenis Kelamin:</label> <div class="radio-group"> <input type="radio" name="jenis_kelamin" value="L" id="laki" required><label for="laki">Laki-laki</label> <input type="radio" name="jenis_kelamin" value="P" id="perempuan" required><label for="perempuan"> Perempuan</label> </div> <label for="alamat">Alamat:</label> <input type="text" name="alamat" id="alamat" required> <label for="no_telp">No. Telp:</label> <input type="text" name="no_telp" id="no_telp" required> <button type="submit">Simpan Data</button> Kembali </form> </div> </body> </html> </pre>
4	Create a new file in the week10 directory, naming it proses.php.
5	Type into the proses.php file the code below.
6	<pre> <?php include('koneksi.php'); \$aksi = \$_GET['aksi']; \$nama = \$_POST['nama']; \$jenis_kelamin = \$_POST['jenis_kelamin']; \$alamat = \$_POST['alamat']; \$no_telp = \$_POST['no_telp']; if(\$aksi == 'tambah'){ \$query = "INSERT INTO anggota (nama, jenis_kelamin, alamat, no_telp) VALUES (\$nama, '\$jenis_kelamin', ' \$alamat', '\$no_telp')"; if (mysqli_query(\$koneksi, \$query)) { header("Location: index.php"); exit(); } else { echo "Gagal menambahkan data: " . mysqli_error(\$koneksi); } } mysqli_close(\$koneksi); </pre>
7	Save the file, then open a browser and run localhost/week10. Add anggota data and then save. What do you understand from the script in the file. Record below your understanding. (Question No. 2)

Practical Section 3. CRUD - Update

Step	Information
------	-------------

1	Create a new file in the week10 directory, naming it edit.php.
2	Type into the edit.php file the code below.
3	<pre> <!DOCTYPE html> <html> <head> <title>Edit Data Anggota</title> <link rel="stylesheet" href="style.css"> </head> <body> <?php include('koneksi.php'); \$id = \$_GET['id']; \$query = "SELECT * FROM anggota WHERE id = \$id"; \$result = mysqli_query(\$koneksi, \$query); \$row = mysqli_fetch_assoc(\$result); mysqli_close(\$koneksi); ?> <div class="container"> <h2>Edit Data Anggota</h2> <form action="proses.php?aksi=ubah" method="post"> <input type="hidden" name="id" value="<?php echo \$row['id']; ?>"> <label for="nama">Nama:</label> <input type="text" name="nama" id="nama" value="<?php echo \$row['nama']; ?>" required> <label for="jenis_kelamin">Jenis Kelamin:</label> <div class="radio-group"> <input type="radio" name="jenis_kelamin" value="L" id="laki" <?php if (\$row['jenis_kelamin'] === 'L') echo 'checked'; ?> required><label for="laki">Laki-laki</label> <input type="radio" name="jenis_kelamin" value="P" id="perempuan" <?php if (\$row['jenis_kelamin'] === 'P') echo 'checked'; ?> required><label for="perempuan">Perempuan</label> </div> <label for="alamat">Alamat:</label> <input type="text" name="alamat" id="alamat" value="<?php echo \$row['alamat']; ?>" required> <label for="no_telp">No. Telp:</label> <input type="text" name="no_telp" id="no_telp" value="<?php echo \$row['no_telp']; ?>" required> <button type="submit">Simpan Perubahan</button> Kembali </form> </div> </body> </html> </pre>
4	Add the contents of the file inside the week10 directory, with the name proses.php.
5	Type into the proses.php file the code below.
6	<pre> elseif(\$aksi == 'ubah'){ if (isset(\$_POST['id'])) { \$id = \$_POST['id']; \$query = "UPDATE anggota SET nama='\$nama', jenis_kelamin='\$jenis_kelamin', alamat='\$alamat', no_telp= '\$no_telp' WHERE id = \$id"; if (mysqli_query(\$koneksi, \$query)) { header("Location: index.php"); exit(); } else { echo "Gagal mengupdate data: " . mysqli_error(\$koneksi); } } else { echo "ID tidak valid."; } } mysqli_close(\$koneksi); </pre>
7	Save the file, then open a browser and run localhost/week10. Make changes to the anggota data and then save it. What do you understand from the script in the file. Record below your understanding. (Question No. 3)

Practical Section 4. CRUD Section Delete

Step	Information
1	Add the contents of the file inside the week10 directory, with the name proses.php.
2	Type into the proses.php file the code below.
3	<pre>elseif(\$aksi == 'hapus'){ if (isset(\$_GET['id'])) { \$id = \$_GET['id']; \$query = "DELETE FROM anggota WHERE i d=\$id"; if (mysqli_query(\$koneksi, \$query)) { header("Location: index.php"); exit(); } else { echo "Gagal menghapus data: " . mysqli_error(\$koneksi); } } else { echo "ID tidak valid."; } } else { header("Location: index.php"); } mysqli_close(\$koneksi);</pre>
4	Save the file, then open a browser and run localhost/week10. Delete member data. What do you understand from the script in the file. Record below your understanding. (Question No. 4)

Practical Section 5. CRUD View with Bootstrap

Step	Information
1	Change the contents of the file to the name index.php in the week10 directory.
2	Type into the index.php file the code below.

3

```

<!DOCTYPE html>
<html>
<head>
  <title>Data Anggota</title>
  <link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/css/bootstrap.min.css">
</head>
<body>
  <div class="container mt-4">
    <h2>Data Anggota</h2>
    <a class="btn btn-success mt-2" href="create.php">Tambah Data</a>
    <br><br>
    <?php
      include('koneksi.php');
      $query = "SELECT * FROM anggota order by id desc";
      $result = mysqli_query($koneksi, $query);
      ?>
    <table class="table">
      <thead class="thead-light">
        <tr>
          <th>No</th>
          <th>Nama</th>
          <th>Jenis Kelamin</th>
          <th>Alamat</th>
          <th>No. Telp</th>
          <th>Aksi</th>
        </tr>
      </thead>
      <tbody>
        <?php
          $no = 1;
          while ($row = mysqli_fetch_assoc($result)) {
            $kelamin = ($row["jenis_kelamin"] == 'L')?'Laki-Laki':'Perempuan';
            ?>
            <tr>
              <td><?=$no++?></td>
              <td><?=$row["nama"]?></td>
              <td><?=$kelamin?></td>
              <td><?=$row["alamat"]?></td>
              <td><?=$row["no_telp"]?></td>
              <td>
                <a class="btn btn-primary" href="edit.php?id=<?=$row["id"]?>">Edit</a>
                <a class="btn btn-danger" href="#" data-toggle="modal" data-target="#hapusModal<?=$row["id"]?>">
Hapus</a>
              </td>
            </tr>
            <div class="modal fade" id="hapusModal<?=$row["id"]?>" tabindex="-1" role="dialog" aria-labelledby=
'exampleModalLabel' aria-hidden="true">
              <div class="modal-dialog" role="document">
                <div class="modal-content">
                  <div class="modal-header">
                    <h5 class="modal-title" id="exampleModalLabel">Konfirmasi Hapus</h5>
                    <button type="button" class="close" data-dismiss="modal" aria-label="Close">
                      <span aria-hidden="true">&times;</span>
                    </button>
                  </div>
                  <div class="modal-body">
                    <?="Apakah Anda yakin ingin menghapus data dengan nama " . $row["nama"] . "?" ?>
                  </div>
                  <div class="modal-footer">
                    <a class="btn btn-danger" href="proses.php?aksi=hapus&id=<?=$row["id"]?>">Hapus</a>
                    <button type="button" class="btn btn-secondary" data-dismiss="modal">Batal</button>
                  </div>
                </div>
              </div>
            </div>
          <?php
            ?>
          </tbody>
        </table>
      </div>

      <script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"></script>
      <script src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.5.3/dist/umd/popper.min.js"></script>
      <script src="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.js"></script>
    </body>
  </html>

```

4

Save the file, then open a browser and run localhost/week10. What do you understand from the script in the file. Record below your understanding. (Question No. 5)

5	Change the contents of the file to the name <code>create.php</code> in the <code>week10</code> directory.
6	Type into the <code>create.php</code> file the code below.
7	<pre> <!DOCTYPE html> <html> <head> <title>Tambah Data Anggota</title> <link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/css/bootstrap.min.css"> </head> <body> <div class="container mt-4"> <h2>Tambah Data Anggota</h2> <form action="proses.php?aksi=tambah" method="post"> <div class="form-group"> <label for="nama">Nama:</label> <input type="text" class="form-control" name="nama" id="nama" required> </div> <div class="form-group"> <label for="jenis_kelamin">Jenis Kelamin:</label> <div class="form-check"> <input type="radio" class="form-check-input" name="jenis_kelamin" value="L" id="laki" required> <label class="form-check-label" for="laki">Laki-laki</label> </div> <div class="form-check"> <input type="radio" class="form-check-input" name="jenis_kelamin" value="P" id="perempuan" required> <label class="form-check-label" for="perempuan">Perempuan</label> </div> </div> <div class="form-group"> <label for="alamat">Alamat:</label> <input type="text" class="form-control" name="alamat" id="alamat" required> </div> <div class="form-group"> <label for="no_telp">No. Telp:</label> <input type="text" class="form-control" name="no_telp" id="no_telp" required> </div> <button type="submit" class="btn btn-primary">Simpan Data</button> </form> Kembali </div> <script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"></script> <script src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.5.3/dist/umd/popper.min.js"></script> <script src="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.js"></script> </body> </html> </pre>
8	Save the file, then open a browser and run <code>localhost/week10</code> . Add anggota data and then save. What do you understand from the script in the file. Record below your understanding. (Question No. 6)
9	Change the contents of the file in the <code>week10</code> directory, with the name <code>edit.php</code>
10	Type into the <code>edit.php</code> file the code below.

11	<pre> <!DOCTYPE html> <html> <head> <title>Edit Data Anggota</title> <link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/css/bootstrap.min.css"> </head> <body> <?php include('koneksi.php'); \$id = \$_GET['id']; \$query = "SELECT * FROM anggota WHERE id = \$id"; \$result = mysqli_query(\$koneksi, \$query); \$row = mysqli_fetch_assoc(\$result); mysqli_close(\$koneksi); ?> <div class="container mt-4"> <h2>Edit Data Anggota</h2> <form action="proses.php?aksi=ubah" method="post"> <input type="hidden" name="id" value="<?php echo \$row['id']; ?>"> <div class="form-group"> <label for="nama">Nama:</label> <input type="text" class="form-control" name="nama" id="nama" value="<?php echo \$row['nama']; ?>" required> </div> <div class="form-group"> <label for="jenis_kelamin">Jenis Kelamin:</label> <div class="form-check"> <input type="radio" class="form-check-input" name="jenis_kelamin" value="L" id="laki" <?php if (\$row['jenis_kelamin'] == 'L') echo 'checked'; ?> required> <label class="form-check-label" for="laki">Laki-laki</label> </div> <div class="form-check"> <input type="radio" class="form-check-input" name="jenis_kelamin" value="P" id="perempuan" <?php if (\$row['jenis_kelamin'] == 'P') echo 'checked'; ?> required> <label class="form-check-label" for="perempuan">Perempuan</label> </div> </div> <div class="form-group"> <label for="alamat">Alamat:</label> <input type="text" class="form-control" name="alamat" id="alamat" value="<?php echo \$row['alamat']; ?>" required> </div> <div class="form-group"> <label for="no_telp">No. Telp:</label> <input type="text" class="form-control" name="no_telp" id="no_telp" value="<?php echo \$row['no_telp']; ?>" required> </div> <button type="submit" class="btn btn-primary">Simpan Perubahan</button> </form> Kembali </div> <script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"></script> <script src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.5.3/dist/umd/popper.min.js"></script> <script src="https://maxcdn.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.js"></script> </body> </html> </pre>
12	<p>Save the file, then open a browser and run localhost/week10. Make changes at anggota data, then save. What do you understand from the script in the file. Record below your understanding. (Question No. 7)</p>

Practical Section 6. CRUD Display with Ajax

Step	Information
1	Create a new folder inside week10 with the name ajax. In that folder, create a new file with the name koneksi.php.
2	Type into the koneksi.php file the code below.

3	<pre> <?php define('HOST','localhost'); define('USER','root'); define('PASS',''); define('DB1','prakwebdb'); // Buat Koneksinya \$db1 = new mysqli(HOST, USER, PASS, DB1); </pre>
4	Create a auth.php file to authenticate it and for its security. Fill in the code below
5	<pre> <?php //Membuat Token Keamanan Ajax Request (Csrf Token) session_start(); if (empty(\$_SESSION['csrf_token'])) { \$_SESSION['csrf_token'] = bin2hex(random_bytes(32)); } ?> </pre>
6	Create a index.php file and fill it in with the script below

```

<?php
include 'auth.php';
?>
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <!-- Csrf Token -->
  <meta name="csrf-token" content="<?= $_SESSION['csrf_token'] ?>">
  <!-- Bootstrap -->
  <link href="https://cdnjs.cloudflare.com/ajax/libs/twitter-bootstrap/4.1.3/css/bootstrap.css" rel="stylesheet">
  <!-- Font Awesome -->
  <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.2/css/all.css" integrity=
"sha384-fnMOCqBILlWl+jLS9j07m0UStjKC4p0pQbqy1/RrhN7udi9RwhKkMIipviBIG9Sr" crossorigin="anonymous">
  <!-- DataTable -->
  <link rel="stylesheet" type="text/css" href="https://cdn.datatables.net/1.10.19/css/dataTables.bootstrap4.min.css">
  <title>Data Anggota</title>
</head>
<body>
  <nav class="navbar navbar-dark bg-primary">
    <a class="navbar-brand" href="index.php" style="color: #fff;">
      CRUD Dengan Ajax
    </a>
  </nav>

  <div class="container">
    <h2 align="center" style="margin: 30px;">Data Anggota</h2>

    <form method="post" class="form-data" id="form-data">
      <div class="row">
        <div class="col-sm-9">
          <div class="form-group">
            <label>Nama</label>
            <input type="hidden" name="id" id="id">
            <input type="text" name="nama" id="nama" class="form-control" required="true">
          </div>
          <div class="col-sm-3">
            <div class="form-group">
              <label>Jenis Kelamin</label><br>
              <input type="radio" name="jenis_kelamin" id="jenkel1" value="L" required="true"> Laki-laki
              <input type="radio" name="jenis_kelamin" id="jenkel2" value="P"> Perempuan
            </div>
          </div>
        </div>

        <div class="form-group">
          <label>Alamat</label>
          <textarea name="alamat" id="alamat" class="form-control" required="true"></textarea>
        </div>

        <div class="form-group">
          <label>No Telepon</label>
          <input type="number" name="no_telp" id="no_telp" class="form-control" required="true">
        </div>

        <div class="form-group">
          <button type="button" name="simpan" id="simpan" class="btn btn-primary">
            <i class="fa fa-save"></i> Simpan
          </button>
        </div>
      </form>
      <hr>

      <div class="data"></div>
    </div>

    <div class="text-center">© <?php echo date('Y'); ?> Copyright:
      <a href="https://google.com/"> Desain Dan Pemrograman Web</a>
    </div>

    <!-- JQuery -->
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.1/jquery.min.js"></script>
    <!-- DataTable -->
    <script src="https://cdn.datatables.net/1.10.19/js/jquery.dataTables.min.js"></script>
    <script src="https://cdn.datatables.net/1.10.19/js/dataTables.bootstrap4.min.js"></script>
    <script src="https://maxcdn.bootstrapcdn.com/bootstrap/4.3.1/js/bootstrap.min.js"></script>

    <script type="text/javascript">
      $(document).ready(function(){
        //Mengirimkan Token Keamanan
        $.ajaxSetup({
          headers : {
            'Csrf-Token': $('meta[name="csrf-token"]').attr('content')
          }
        });

        $('data').load("data.php");
      });
    </script>
  </body>
</html>

```

	<pre> <!-- Bootstrap --> <link href="https://cdnjs.cloudflare.com/ajax/libs/twitter-bootstrap/4.1.3/css/bootstrap.css" rel="stylesheet"> <!-- Font Awesome --> <link rel="stylesheet" href="https://use.fontawesome.com/releases/v5.7.2/css/all.css" integrity="sha384- fnmOCqbTlWIlj8LyTjo7mOUStjsKC4pOpQbqyi7RrhN7udi9RwhKkMHpvLbHG9 Sr" crossorigin="anonymous"> </pre>
8	<p>Create a data.php file that functions to reload data using ajax so that the application does not need to load when saving data or there is data update. Fill in data.php with the script below</p>
9	<pre> <table id="example" class="table table-striped table-bordered" style="width:100%"> <thead> <tr> <td>No</td> <td>Nama</td> <td>Jenis Kelamin</td> <td>Alamat</td> <td>No Telp</td> <td>Action</td> </tr> </thead> <tbody> <?php include 'koneksi.php'; \$no = 1; \$query = "SELECT * FROM anggota ORDER BY id DESC"; \$sql = \$db1->prepare(\$query); \$sql->execute(); \$res1 = \$sql->get_result(); if (\$res1->num_rows > 0) { while (\$row = \$res1->fetch_assoc()) { \$id = \$row['id']; \$nama = \$row['nama']; \$jenis_kelamin = (\$row['jenis_kelamin'] == 'L')?'Laki-Laki':'Perempuan'; \$alamat = \$row['alamat']; \$no_telp = \$row['no_telp']; ?> <tr> <td><?php echo \$no++; ?></td> <td><?php echo \$nama; ?></td> <td><?php echo \$jenis_kelamin; ?></td> <td><?php echo \$alamat; ?></td> <td><?php echo \$no_telp; ?></td> <td> <button id="<?php echo \$id; ?>" class="btn btn-success btn-sm edit_data"> <i class="fa fa-edit"></i> Edit </button> <button id="<?php echo \$id; ?>" class="btn btn-danger btn-sm hapus_data"> <i class="fa fa-trash"></i> Hapus </button> </td> </tr> <?php } } else { ?> <tr> <td colspan='7'>Tidak ada data ditemukan</td> </tr> <?php } ?> </tbody> </table> <script type="text/javascript"> \$(document).ready(function() { \$('#example').DataTable(); }); </script> </pre>
10	<p>For security because we use headers in ajax, we need to create a csrf.php file and then fill it with the script below</p>

11

```

<?php
header('Content-Type: application/json');

//Mengirimkan Token Keamanan
if (empty($_SESSION['csrf_token'])) {
    $_SESSION['csrf_token'] = bin2hex(random_bytes(32));
}

$headers = apache_request_headers();
if (isset($headers['Csrftoken'])) {
    if ($headers['Csrftoken'] !== $_SESSION['csrf_token']) {
        exit(json_encode(['error' => 'Wrong CSRF token.']));
    }
} else {
    exit(json_encode(['error' => 'No CSRF token.']));
}
?>

```

12

Save the file, then open a browser and run localhost/week10/ajax. It should appear like the image below

CRUD Dengan Ajax

Data Anggota

Nama Jenis Kelamin ☐ Laki-laki ☐ Perempuan

Alamat

No telepon

Show 10 entries Search:

No	T1	Nama	T1	Jenis Kelamin	T1	Alamat	T1	No Telp	T1	Action	T1
1		David		Laki-Laki		Jl. in aja dulu ya		068545123		<input checked="" type="checkbox"/> Edit <input type="checkbox"/> Hapus	

Showing 1 to 1 of 1 entries

© 2023 Copyright: Desain Dan Pemrograman Web

Previous **1** Next

What do you understand from the scripts on those files. Record below your understanding.
(Question No. 8)

13

Next, create a form with data that can be saved. Open the **index.php** file and add some scripts below so that the ones added are only for the error check section with examples

```

<p class="text-danger" id="err_jenis_kelamin"></p>

```

14	<pre> <form method="post" class="form-data" id="form-data"> <div class="row"> <div class="col-sm-9"> <div class="form-group"> <label>Nama</label> <input type="hidden" name="id" id="id"> <input type="text" name="nama" id="nama" class="form-control" required="true"> <p class="text-danger" id="err_nama"></p> </div> </div> <div class="col-sm-3"> <div class="form-group"> <label>Jenis Kelamin</label>
 <input type="radio" name="jenis_kelamin" id="jenkel1" value="L" required="true"> Laki-laki <input type="radio" name="jenis_kelamin" id="jenkel2" value="P"> Perempuan </div> <p class="text-danger" id="err_jenis_kelamin"></p> </div> </div> <div class="form-group"> <label>Alamat</label> <textarea name="alamat" id="alamat" class="form-control" required="true"></textarea> <p class="text-danger" id="err_alamat"></p> </div> <div class="form-group"> <label>No Telepon</label> <input type="number" name="no_telp" id="no_telp" class="form-control" required="true"> <p class="text-danger" id="err_no_telp"></p> </div> <div class="form-group"> <button type="button" name="simpan" id="simpan" class="btn btn-primary"> <i class="fa fa-save"></i> Simpan </button> </div> </form> </pre>
15	<p>Still in the index.php file with the addition of the javascript script, insert the script below in the jquery that is already in step 7</p>
16	<pre> \$("#simpan").click(function(){ var data = \$('form-data').serialize(); var jenkel1 = document.getElementById("jenkel1").value; var jenkel2 = document.getElementById("jenkel2").value; var nama = document.getElementById("nama").value; var alamat = document.getElementById("alamat").value; var no_telp = document.getElementById("no_telp").value; if (nama=="") { document.getElementById("err_nama").innerHTML = "Nama Harus Diisi"; } else { document.getElementById("err_nama").innerHTML = ""; } if (alamat=="") { document.getElementById("err_alamat").innerHTML = "Alamat Harus Diisi"; } else { document.getElementById("err_alamat").innerHTML = ""; } if (document.getElementById("jenkel1").checked==false && document.getElementById("jenkel2").checked==false) { document.getElementById("err_jenis_kelamin").innerHTML = "Jenis Kelamin Harus Dipilih"; } else { document.getElementById("err_jenis_kelamin").innerHTML = ""; } if (no_telp=="") { document.getElementById("err_no_telp").innerHTML = "No Telepon Harus Diisi"; } else { document.getElementById("err_no_telp").innerHTML = ""; } } </pre>


```

        if (nama!="" && alamat!="" && (document.getElementById("jenkel1").checked==true || document.
getElementById("jenkel2").checked==true) && no_telp!="") {
            $.ajax({
                type: 'POST',
                url: "form_action.php",
                data: data,
                success: function() {
                    $('data').load("data.php");
                    document.getElementById("id").value = "";
                    document.getElementById("form-data").reset();
                }, error: function(response){
                    console.log(response.responseText);
                }
            });
        }
    });
});

```

17

Next is to create a **form_action.php** file that functions to save into the database. Then fill it in with the script below

18

```

<?php
session_start();
include 'koneksi.php';
include 'csrf.php';

$nama = stripslashes(strip_tags(htmlspecialchars($_POST['nama'], ENT_QUOTES)));
$jenis_kelamin = stripslashes(strip_tags(htmlspecialchars($_POST['jenis_kelamin'], ENT_QUOTES)));
$alamat = stripslashes(strip_tags(htmlspecialchars($_POST['alamat'], ENT_QUOTES)));
$no_telp = stripslashes(strip_tags(htmlspecialchars($_POST['no_telp'], ENT_QUOTES)));

$query = "INSERT into anggota (nama, jenis_kelamin, alamat, no_telp) VALUES (?, ?, ?, ?)";
$sql = $db1->prepare($query);
$sql->bind_param("ssss", $nama, $jenis_kelamin, $alamat, $no_telp);
$sql->execute();

echo json_encode(['success' => 'Sukses']);

$db1->close();
?>

```

19

Save the file, then open a browser and run localhost/week10/ajax. It should appear like the image below if you click the save button without filling in any data

What do you understand from the scripts on those files. Record below your understanding.
(Question No. 9)

20	Next, create a form with data that can be changed. Open the data.php file and add some scripts below so the ones added in the jquery section
21	<pre> <script type="text/javascript"> \$(document).ready(function() { \$('#example').DataTable(); }); function reset(){ document.getElementById("err_nama").innerHTML = ""; document.getElementById("err_jenis_kelamin").innerHTML = ""; document.getElementById("err_alamat").innerHTML = ""; document.getElementById("err_no_telp").innerHTML = ""; } \$(document).on('click', '.edit_data', function(){ \$('html, body').animate({ scrollTop: 0 }, 'slow'); var id = \$(this).attr('id'); \$.ajax({ type: 'POST', url: "get_data.php", data: {id:id}, dataType:'json', success: function(response) { reset(); \$('html, body').animate({ scrollTop: 30 }, 'slow'); document.getElementById("id").value = response.id; document.getElementById("nama").value = response.nama; document.getElementById("alamat").value = response.alamat; document.getElementById("no_telp").value = response.no_telp; if (response.jenis_kelamin=="L") { document.getElementById("jenkel1").checked = true; } else { document.getElementById("jenkel2").checked = true; } }, error: function(response){ console.log(response.responseText); } }); }); </script> </pre>
22	Create a get_data.php file and fill it in with the script below
23	<pre> <?php session_start(); include 'koneksi.php'; include 'csrf.php'; \$id = \$_POST['id']; \$query = "SELECT * FROM anggota WHERE id=? ORDER BY id DESC"; \$sql = \$db1->prepare(\$query); \$sql->bind_param('i', \$id); \$sql->execute(); \$res1 = \$sql->get_result(); while (\$row = \$res1->fetch_assoc()) { \$h['id'] = \$row["id"]; \$h['nama'] = \$row["nama"]; \$h['jenis_kelamin'] = \$row["jenis_kelamin"]; \$h['alamat'] = \$row["alamat"]; \$h['no_telp'] = \$row["no_telp"]; } echo json_encode(\$h); \$db1->close(); ?> </pre>
24	Finally, change the form_action.php file to the one below so that you can edit the form

25

```

<?php
session_start();
include 'koneksi.php';
include 'csrf.php';

$id = stripslashes(strip_tags(htmlspecialchars($_POST['id'], ENT_QUOTES)));
$name = stripslashes(strip_tags(htmlspecialchars($_POST['nama'], ENT_QUOTES)));
$jenis_kelamin = stripslashes(strip_tags(htmlspecialchars($_POST['jenis_kelamin'], ENT_QUOTES)));
$alamat = stripslashes(strip_tags(htmlspecialchars($_POST['alamat'], ENT_QUOTES)));
$no_telp = stripslashes(strip_tags(htmlspecialchars($_POST['no_telp'], ENT_QUOTES)));

if ($id == "") {
    $query = "INSERT into anggota (nama, jenis_kelamin, alamat, no_telp) VALUES (?, ?, ?, ?)";
    $sql = $db1->prepare($query);
    $sql->bind_param("ssss", $name, $jenis_kelamin, $alamat, $no_telp);
    $sql->execute();
} else {
    $query = "UPDATE anggota SET nama=?, jenis_kelamin=?, alamat=?, no_telp=? WHERE id=?";
    $sql = $db1->prepare($query);
    $sql->bind_param("ssssi", $name, $jenis_kelamin, $alamat, $no_telp, $id);
    $sql->execute();
}

echo json_encode(['success' => 'Sukses']);

$db1->close();
?>

```

26

Save the file, then open a browser and run localhost/week10/ajax. When clicking the edit button, it should appear as shown in the image below with the form auto-filled from the previous data

CRUD Dengan Ajax

Data Anggota

Nama Jenis Kelamin ☒ Laki-laki ☐ Perempuan

Alamat

No Telepon

Show 10 entries Search:

No	Nama	Jenis Kelamin	Alamat	No Telp	Action
1	David	Laki-Laki	Jl. in aja dulu ya	068545123	<input checked="" type="button" value="Edit"/> <input type="button" value="Hapus"/>

Showing 1 to 1 of 1 entries

Previous 1 Next

© 2023 Copyright: Desain Dan Pemrograman Web

What do you understand from the scripts on those files. Record below your understanding.
(Question No. 10)

27

On the <script>... </script> in the data.php file add the code below

28	<pre> \$(document).on('click', '.hapus_data', function(){ var id = \$(this).attr('id'); \$.ajax({ type: 'POST', url: "hapus_data.php", data: {id:id}, success: function() { \$('data').load("data.php"); }, error: function(response){ console.log(response.responseText); } }); }); </pre>
29	Create a hapus_data.php file on your project and type the script below
30	<pre> <?php session_start(); include 'koneksi.php'; include 'csrf.php'; \$id = \$_POST['id']; \$query = "DELETE FROM anggota WHERE id=?"; \$sql = \$db1->prepare(\$query); \$sql->bind_param("i", \$id); \$sql->execute(); echo json_encode(['success' => 'Sukses']); \$db1->close(); ?> </pre>
31	Save the file, then open a browser and run localhost/week10/ajax. When you click the delete button, the data should be deleted. What do you understand from the scripts on those files. Record below your understanding. (Question No. 11)