

The Figure Class

Basic plotting in C++

Contents

1	Installation	1
2	Commands	1
2.1	grid	1
2.2	xlabel	2
2.3	ylabel	2
2.4	legend	2
2.5	setlog	3
2.6	plot	3
2.7	ranges	3
2.8	save	4
2.9	title	4
3	Line characteristics	5

1 Installation

Follow the steps in the `INSTALL` file.

In the directory of the `CMakeLists.txt` do:

Under Linux/Mac OS:

```
$ mkdir build
$ cd build
$ cmake ..
$ sudo make install
```

Under Windows:

- open a terminal with administrator rights
- do the same as above but without the `sudo`

This installation requires CMake (<https://cmake.org/download/>). The “manual” way of installing it is described in `INSTALL`.

2 Commands

2.1 grid

Definition:

```
void grid( const bool on = true,
           const std::string gridType = "-",
           const std::string gridCol = "h" )
```

Restrictions: None. **Examples:**

```
Figure fig;
fig.plot(x, y, "r");
fig.grid(false); // unset grid
fig.save("plot.eps");

Figure fig;
fig.plot(x, y, "r");
fig.grid(true, "!", "b"); // blue fine mesh
fig.save("plot.eps");
```

2.2 xlabel

Definition:

```
void xlabel( const char* label,
             const double pos = 0 )
```

Restrictions: If setlog is called xlabel should be called beforehand.

Examples:

```
Figure fig;
fig.plot(x, y, "+g"); // '+g' equals matlab/python '+-g'
fig.xlabel("Linear x axis");
fig.save("plot.eps");

Figure fig;
fig.setlog(true, true);
fig.plot(x, y, "+g");
fig.xlabel("Logarithmic x axis"); // Not good - should be called before 'setlog'
fig.save("plot.eps");

Figure fig;
fig.xlabel("Logarithmic x axis"); // Good
fig.setlog(true, true);
fig.plot(x, y, "+g");
fig.save("plot.eps");
```

2.3 ylabel

Definition:

```
void ylabel( const char* label,
             const double pos = 0 )
```

Restrictions: If setlog is called ylabel should be called beforehand.

Examples: See xlabel.

2.4 legend

Definition:

```
void legend( const double xPos = 1,
             const double yPos = 1 )
```

Restrictions: None.

2.5 setlog

Definition:

```
void setlog( const bool logx = true,
             const bool logy = true )
```

Restrictions: All plots will use the latest `setlog` options or default if none have been set.

Examples:

```
Figure fig;
fig.setlog(true, false); // -> semilogx
fig.plot(x0, y0, "b");
fig.setlog(false, true); // -> semilogy
fig.plot(x1, y1, "r");
fig.setlog(true, true); // -> loglog
fig.plot(x2, y2, "g");
fig.save("plot.eps"); // ATTENTION: all plots will have been plotted in loglog-scale
```

```
Figure fig;
fig.plot(x, y, "b");
fig.save("plot.eps"); // -> default (= linear) scaling
```

2.6 plot

Definition:

```
void plot( const std::vector<double> x,
           const std::vector<double> y,
           const char* style,
           const char* legend = 0 )

void plot( const Eigen::VectorXd x,
           const Eigen::VectorXd y,
           const char* style,
           const char* legend = 0 )
```

Restrictions: x and y must have same length. Also note that the `style`-argument is required!

Examples:

```
Figure fig;
fig.plot(x, y, "b");
fig.save("data.eps");
```

```
Figure fig;
fig.plot(x, y); // Not OK - style missing
fig.save("data.eps");
```

```
Figure fig;
fig.plot(x, y, " *r", "Data w/ red dots"); // ' *r' equals matlab/python 'r*'
fig.save("data.eps");
```

2.7 ranges

Definition:

```
void ranges( const double xMin,
            const double xMax,
            const double yMin,
            const double yMax )
```

Restricitons: $xMin < xMax$, $yMin < yMax$ and ranges must be > 0 for axis in logarithmic scale.

Examples:

```
Figure fig;
fig.ranges(-1,1,-1,1);
fig.plot(x, y, "b");
```

```
Figure fig;
fig.plot(x, y, "b");
fig.ranges(0, 2.3, 4, 5); // ranges can be called before or after 'plot'
```

```
Figure fig;
fig.ranges(-1, 1, 0, 5);
fig.setlog(true, true); // will run but MathGL will throw a warning
fig.plot(x, y, "b");
```

2.8 save

Definition:

```
void save( const char* file )
```

Restrictions: The filename *must* end on .eps!

Examples:

```
Figure fig;
fig.save("plot.eps"); // OK
```

```
Figure fig;
fig.save("plot.png"); // Not OK - Only eps-format supported!
```

2.9 title

Definition:

```
void title( const char* text )
```

Restricitons: None.

3 Line characteristics

Linecolors^a:

blue	b
green	g
red	r
cyan	c
magenta	m
yellow	y
gray	h
green-blue	l
sky-blue	n
orange	q
green-yellow	e
blue-violet	u
purple	p

^a Upper-case letters will give a darker version of the lower-case version.

Linestyles:

none	
solid	-
dashed	;
small dashed	=
long dashed	
dotted	:
dash-dotted	j
small dash-dotted	i

None is used as follows:
" r*" gives red stars w/o
any lines

Linemarkers:

+	+
o	o
◇	d
·	·
△	^
▽	v
<	<
>	>
⊙	#.
⊕	#+
⊗	#x