
PULSECHAIN · ON-CHAIN ARBITRAGE SCANNER

Arb-Me-Now

Process Manual & White Paper

Methodology, operating procedure, verified parameters and risk model



PulseX v1 · v2 | 9mm v2 | LibertySwap V3 | 2-pool + triangular | BigInt engine | read-only

Version 4.8.1 · November 2026 · Analysis tool, not financial advice

cryptales.github.io/Arb-Me-Now

Contents

1. Purpose 3
2. Architecture 3
3. Methodology 4
4. Operating Procedure (step by step) 6
5. Interpreting results 7
6. Risks and limitations 7
7. Security model 8
8. Maintenance 8
9. Roadmap 8
10. Version history 8

At a glance. Arb-Me-Now reads every pool from one PulseChain block, models each swap with exact integer maths, finds the optimal size for 2-pool and triangular routes, and reports profit before and after estimated gas. It never connects a wallet or sends a transaction.

1. Purpose

Arb-Me-Now finds price differences between decentralised exchanges (DEXs) on PulseChain and tells you whether a round-trip trade would make money **after DEX fees**. It reads live pool data straight from the chain, so all numbers come from a single block. It never signs or sends transactions, and it never asks for a wallet or private key.

2. Architecture

Layer	What it does
Data	Public RPC `rpc.pulsechain.com`. All pool states are read in **one** Multicall3 `tryBlockAndAggregate` call (selector `0x399542e9`), so every price comes from the same block. PulseChain RPC rejects JSON-RPC batch requests, so Multicall3 is required.
Tick data (v4.5, adaptive since v4.8)	A second Multicall3 call, pinned to the **same block**, reads `ticks(int24)` (selector `0xf30dba93`) for an adaptive number of boundary ticks on each side of every v3 pool (see §3.9; cap 1–8, default 4), giving `liquidityNet` at each crossing. If this read fails, the engine falls back to single-interval maths.
Discovery	`getPair` / `getPool` lookups on each factory for a fixed list of liquid pairs over the watch list (v4.7: WPLS, PLSX, HEX, eHEX, INC, WETH, DAI and bridged stables; new pairs WPLS/eHEX, HEX/eHEX, eHEX/DAI, WPLS/INC, PLSX/INC, INC/HEX, WETH/DAI, WETH/PLSX, WETH/HEX).
Engine	Pure BigInt maths (`engine.js`) with exact integer swap formulas and no floating-point rounding in the money path. It is unit-tested in Node (`test.js`).
UI	A single self-contained `index.html` hosted on GitHub Pages, with no backend.
External	LibertySwap quote API (bridge checks) and Coinbase spot (ETH/USD reference only).

Venues and verified fees

Venue	Factory	Fee
PulseX v1	`0x1715a3E4A142d8b698131108995174F37aEBA10D`	0.29%
PulseX v2	`0x29eA7545DEf87022BAdc76323F373EA1e707C523`	0.29%
9mm v2	`0x3a0Fa7884dD93f3cd234bBE2A0958Ef04b05E13b`	0.25%
LibertySwap V3	`0x796fcbDC956b85797EFe21145Aa97599B7FB36a6`	0.01 / 0.05 / 0.25 / 1% tiers

All fees were checked on-chain, not taken from documentation.

3. Methodology

3.1 Swap maths

- **v2 (constant product):** `out = in·(10000−fee)·R_out / (R_in·10000 + in·(10000−fee))`, using integer division the same way the pool contract does.
- **v3 (concentrated liquidity, multi-tick since v4.5):** exact swap maths using `sqrtPriceX96` and active liquidity `L`, walking across up to **N tickSpacing intervals per direction** (N adaptive since v4.8, §3.9; cap 1–8, default 4). When the price crosses a boundary tick, `liquidityNet` is added (moving up) or subtracted (moving down) to get the next interval's `L`. The fee is taken on the gross input. Any trade that would go beyond the last interval read, or into an interval with zero liquidity, is treated as infeasible. If tick data is unavailable, the engine falls back to the conservative single-interval model.

3.2 Safe-depth caps

- A v2 leg may use at most **10% of the input reserve**.
- A v3 leg may not move the price beyond the **4th tick interval** read in its direction (or the current interval in single-interval fallback).

3.3 Route types

1. **Two-pool cycles:** S → Y on pool A, then Y → S on pool B, where A and B are different pools for the same pair.
2. **Triangular 3-hop routes (v4.4):** S → Y → Z → S across three different pools.

3.4 Optimal sizing

For each route, the engine first finds the largest feasible input size by binary search. It then runs a ternary search for the size with the highest profit, which works because profit rises and then falls as size grows. Finally it checks every size in the last narrow window exhaustively. It also evaluates the size you typed in, so you can compare your size with the best one.

3.5 Filtering and pricing

- **Suspicious/dust:** routes where any leg has under the dust threshold in USD depth, or an implausibly large price gap, are hidden by default.
- **USD values:** WPLS/USD comes from the deepest WPLS/stablecoin pool, treating bridged stables as $1. Other tokens are priced through their deepest WPLS pool.
- **Snapshot age:** data is marked stale after 20 seconds.

3.6 Bridge price check (LibertySwap)

`GET apis.libertyswap.finance/v3/swap/quote` gives the real quote from PulseChain to Ethereum (fee 0.5% for USDC and WETH from 369 → 1). The result is compared with the PulseChain purchase price and the Coinbase spot price. **This is not atomic:** the bridge takes minutes and you carry price risk while it runs. The API rate limit is 30 requests per 60 seconds and is enforced on the client.

3.7 Atomic execution: ArbExecutor (v4.6)

`contracts/src/ArbExecutor.sol` (Solidity 0.8.24, Foundry) runs a 2- to 4-leg closed cycle S → … → S in **one transaction**: - **Flash swap on leg 0:** the first pool sends its output first; the remaining legs run inside its callback; leg 0 is repaid in S at the end. No starting capital is needed. - **All-or-nothing:** if the cycle returns less than the amount owed it reverts `NoProfit(returned, required)`; it also reverts if the leftover is below `minProfit`. Only gas can be lost. Profit is sent to the owner. - **Callbacks (verified in on-chain bytecode):** PulseX v1/v2 `uniswapV2Call`, 9mm v2 `pancakeCall`, LibertySwap V3 `libertyV3SwapCallback` (`0x31e2ba55`). - **Safety:** owner-only `execute` / `withdraw`; callbacks accepted only from the pool currently being swapped while a run is active; deadline; token-continuity check; fee-on-transfer tokens unsupported. - **Leg encoding (uint256):** bits 0–159 pool · 160–167 kind (0 v2, 1 v3) · 168–175 zeroForOne · 176–191 v2 fee bps. Call: `execute(uint256[] legs, uint256 amountIn, uint256 minProfit, uint256 deadline)` (selector `0x29df2c6f`). - **Testing:** 11/11 Foundry tests on a PulseChain fork (live route reverts NoProfit; induced gaps profitable for v2→v2, v3-flash→v2, v2→v3 and a 3-hop; access control, stray callbacks, expiry, open cycles). A JS end-to-end test on an anvil fork drove the scanner's own encoder: contract profit matched the engine's prediction **exactly** for v2→v2 and within **2 wei** with a v3 leg, and a real execute tx paid the owner. Measured `execute` gas (Foundry report): median ≈ 294k, max ≈ 612k.

3.8 Wallet send (v4.7)

Trade Companion's opt-in **Connect & Send** uses the injected EIP-1193 wallet (MetaMask): `eth_requestAccounts` → `wallet_switchEthereumChain` to `0x171` (369) → `owner()` read on the executor; sending is blocked unless the connected account is the owner → `eth_sendTransaction` with the built `execute(...)` calldata → the tx hash is shown with an explorer link. Keys never leave the wallet.

3.9 Adaptive tick depth (v4.8)

For each V3 pool the engine first computes the current interval's capacity C in start-token (S) units: the smaller of `v3MaxIn` with S as input and `v3MaxIn` with the other token as input, converted to S at the pool's sqrtPrice. It then reads `d = clamp(⌊size / C⌋ + 2, 2, cap)` tick intervals per direction, where cap is the user's slider value (1–8; cap 1 means single-interval maths). Pools that do not contain S (middle legs of 3-hop routes) read the full cap. Live check (2026-11-01, WPLS start): at 1,000 WPLS deep pools read 2 intervals; at 10^8 WPLS they read 6–8; with cap 1 every pool reads 1.

3.10 Piteas cross-check and the Tide venue (v4.8.1)

Piteas (piteas.io) is a DEX aggregator, not a DEX: it holds no liquidity and routes swaps across PulseChain venues through its router `0x6BF2…88A6`. Trade Companion's opt-in **Check with Piteas** button asks `GET https://sdk.piteas.io/quote` for the cycle's first hop (S → first intermediate token, at your input size) and then the way back (intermediate → S), i.e. 2 requests. It shows both outputs, the venues used, and the Piteas round trip against your input and against our route's output: - **Piteas round trip ≥ our route:** the gap is likely available market-wide, so other traders can take it too. - **Our route beats it:** the gap looks specific to the pools we found.

Piteas allows **10 requests per minute** (going over can block the IP for an hour) and states the API is not meant for arbitrage bots. So the check is manual only, capped locally at 6 requests per rolling 60 s, and never part of the automatic scan. The scanner does not depend on Piteas; if the API is down (it returned HTTP 500 for a period on 3 Nov 2026), the panel shows "Piteas unavailable" and everything else keeps working. Piteas quotes cannot be an ArbExecutor leg: they have no flash callback, and their calldata is built off-chain for one exact amount.

Tide appeared in a Piteas route. On-chain inspection (3 Nov 2026) shows the pool `0x6926…E38B` ("RISKOFF") is a **Balancer V3-style weighted pool**, not a Uniswap-style pair: it exposes `getVault()` (vault `0x634f…4b2d`), `onSwap`, `getWeightedPoolImmutableData` and `getCurrentLiveBalances`, and reverts on `getReserves()`. It holds 5 tokens (HEX, INC, CST, PLSX, WPLS) at weights 5/5/80/5/5 %, with a 0.30 % swap fee. Its live balances were small (≈14.8k HEX, 74 INC, 61k CST, 4.49M PLSX, 3.26M WPLS). Adding it would need weighted-pool maths in the engine **and** a Balancer-V3 vault integration in ArbExecutor, for very little depth, so it is **not scanned** for now. The Piteas panel labels Tide hops "(not scanned here)".

4. Operating Procedure (step by step)

1. Open https://cryptales.github.io/Arb-Me-Now/.
2. Under **Settings**, choose the start token and the trade size, and turn venues on or off.
   - **Min profit (bps of input):** the smallest return you care about, in basis points of the amount you put in (1 bp = 0.01%; 10 bps = 0.1%; 100 bps = 1%). It is checked against the profit at the **optimal size**, before gas. It only takes effect when **Only rows ≥ min profit** is ticked; otherwise every row is shown. The default is 0, so any profitable route passes. Example: 1,000 WPLS in, 1,002 WPLS out = 2 WPLS profit = 20 bps. The LibertySwap bridge quotes and Triangular 3-hop routes toggles are on by default.
3. Click **Scan**. Check the telemetry bar: RPC is **OK**, the snapshot block is shown, and the snapshot age is under 20 s.
4. Read the results table, which is sorted by profit in USD. Each row shows the route, venues, mid-price gap, best size, profit at the best size, profit at your size, and flags.
5. Click **Inspect** to open the Trade Companion. It shows reserves or v3 state for every leg, the depth caps, and the exact BigInt calculation.
6. **Before acting on any row:**
   - Re-scan to confirm the opportunity is still there in a fresh block.
   - Check the **net after gas** line. Gas is estimated from the live `eth_gasPrice` × 250,000 gas (2-hop) or 350,000 gas (3-hop), valued at WPLS/USD. Real gas use depends on your execution contract.
   - Allow for MEV and front-running risk. A public mempool trade can be sandwiched.
   - Check the pool addresses on scan.pulsechain.com.
7. **Alerts (v4.5):** tick 🔔 **Alert on new profitable route** and allow browser notifications when asked. Pair it with **Auto-refresh every 15 s**. The scanner beeps, shows a banner and sends a notification **once** for each newly profitable route that is ≥ your min bps and still positive after gas (suspicious rows never alert). Alerts only work while the tab stays open.
8. **Execute (v4.6, optional):** deploy your own ArbExecutor once (`forge create src/ArbExecutor.sol:ArbExecutor --rpc-url https://rpc.pulsechain.com --private-key <your key> --broadcast`, run on your own machine). In Trade Companion, enter its address, keep or edit size and min profit (default 50% of expected), click **Build calldata**, then **Dry run** (an `eth_call` from the owner; nothing is signed). If it says "Would succeed", send the calldata from your owner wallet (value 0) before the 120 s deadline.
9. **Piteas cross-check (v4.8.1, optional):** in Trade Companion, click **Check with Piteas** to compare the route with the aggregator's whole-market round trip (2 requests; max 6 per minute). Use it sparingly.

10. For bridge checks, treat the edge as an upper bound. Gas on both chains, bridge time and slippage reduce it.

5. Interpreting results

Display	Meaning
`not profitable at any size`	Fees are larger than the price gap at every size.
`+x TOKEN` profit	Gross profit at the optimal size, before gas.
`net after gas`	Profit in USD minus the estimated gas cost (green = still profitable).
`v3 multi-tick (≤N intervals)`	v3 legs are sized across up to N tick intervals; liquidity beyond that is not modelled.
`v3 in-interval (conservative cap)`	Fallback when tick data could not be read: size limited to the current tick.
✅ `Would succeed` / ❌ `Would revert NoProfit`	ArbExecutor dry-run result at the latest block.
🔔 banner / notification	A new profitable, net-of-gas route ≥ min bps appeared (deduplicated per route).
`3-hop triangular`	Triangular route. Only profitable ones are listed.
Hidden: suspicious/dust	Thin or anomalous pools have been left out for your safety.

Live findings (1 Nov 2026, block ~27.94M): no profitable two-pool or triangular routes after DEX fees. The best gross gap was 0.22% (WPLS–WETH, PulseX v2 → LibertySwap V3 0.25%), which is below the combined 0.54% in fees. At about 444,000 gwei, the estimated gas is under $0.001 per route, so DEX fees, not gas, are what close the gap. The WETH bridge check showed about +0.17% to +0.30% against Coinbase before gas and slippage. Efficient markets tend to close these gaps fast, so the tool is most useful during volatility.

6. Risks and limitations

- Gas is an estimate (fixed gas units × live gas price). MEV and pending-block state are not modelled.
- v3 depth is limited to the adaptive tick depth (max 8 intervals per direction); liquidity beyond that is not modelled.
- ArbExecutor: a public-mempool tx can be front-run or the price can move after the dry run; then it reverts and gas is lost. The contract is unaudited; use small sizes first.
- Alerts run in the browser only: the tab must stay open, and the browser or OS may block notifications or sound.
- The results are a snapshot. By the time a transaction lands, reserves may have changed.
- Bridge round-trips are non-atomic and carry price risk.

- The public RPC can lag or rate-limit you.
- **This is analysis, not financial advice. Always verify on-chain before trading.**

7. Security model

By default the page is read-only: it uses only `eth_call` and HTTPS GET requests (PulseChain RPC, LibertySwap API, and, only when you click the button, the Piteas quote API). Since v4.7 there is an **opt-in** wallet connection: a transaction is sent only when you click Connect & Send and approve it in your wallet, and only from the executor owner. The page never sees or stores private keys; there is no tracking and no backend. All code is in one auditable HTML file.

8. Maintenance

- **Source files:** `engine.js` (engine), `ui.js` (UI logic), `body.html` (markup) and `test.js` (Node tests: `node test.js`).
- **Build:** the CSS + `body.html` + `engine.js` (without module exports) + `ui.js` are combined into one `index.html`.
- **Deploy:** commit `index.html` to `main`. GitHub Pages serves it within about a minute.
- **When fees or factories change:** re-verify on-chain and update the constants in `engine.js`.

9. Roadmap

Deployment kit + **keeper role** for ArbExecutor (a separate bot key that can execute but never withdraw; profits still go to the owner) · v4.9 private/bundled submission (MEV protection) · v5.0 server-side / Telegram alerts · Balancer-V3 / Tide support if its liquidity grows · more venues and tokens.

10. Version history

- **v4.8.1:** Opt-in Piteas aggregator cross-check in Trade Companion (2 quotes, local 6/min guard, graceful "unavailable" handling); Tide venue identified on-chain as a Balancer-V3 weighted pool and documented (not scanned).
- **v4.8:** Adaptive V3 tick depth: per-pool interval count sized to the trade (1–8 cap slider, same-block reads), depth range in telemetry.
- **v4.7:** New tokens eHEX, INC (and WETH pairs) with 9 liquid pairs; opt-in MetaMask Connect & Send (chain switch, owner check, wallet-signed tx).
- **v4.6.1:** Fixed stale browser tab title (v4.3 → v4.6); white paper PDF regenerated.
- **v4.6:** ArbExecutor atomic flash-swap contract (PulseX v1/v2, 9mm, LibertySwap V3; 2–4 legs), fork-tested; Trade Companion execution panel with calldata builder and read-only dry run.
- **v4.5:** multi-tick LibertySwap V3 depth (up to 4 intervals per direction, same-block tick reads) and profitability alerts (sound + browser notification, deduplicated).

- **v4.4:** triangular 3-hop routes, gas-adjusted net profit, separate route counts in the summary, and old pages redirected to the scanner.
- **v4.3:** live Multicall3 reserves, verified fees, LibertySwap V3 and bridge quotes, and a BigInt engine.