

May 27, 2026

Vulnerability Scan Report

Prepared By

HostedScan Security



hostedscan.com

Table of Contents

1	Executive Summary	3
2	Trends	4
3	Vulnerabilities By Target	6
4	Network Vulnerabilities	8
5	Glossary	14

1 Executive Summary

Vulnerability scans were conducted on select servers, networks, websites, and applications. This report contains the discovered potential vulnerabilities from these scans. Vulnerabilities have been classified by severity. Higher severity indicates a greater risk of a data breach, loss of integrity, or availability of the targets.


1.1 Total Vulnerabilities

Below are the total number of vulnerabilities found by severity. Critical vulnerabilities are the most severe and should be evaluated first. An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive detection or an intentional part of the system's architecture.



1.2 Report Coverage


This report includes findings for **1 target** scanned. Each target is a single URL, IP address, or fully qualified domain name (FQDN).



2 Trends

2.1 Open Risks

Total number of vulnerabilities grouped by severity level.



2.2 Exposure Window

Total number of unresolved vulnerabilities grouped by age (time since first detection).



2.3 Health Score

Total score based on the cumulated risks for all targets.



3 Vulnerabilities By Target

This section contains the vulnerability findings for each scanned target. Prioritization should be given to the targets with the highest severity vulnerabilities. However, it is important to take into account the purpose of each system and consider the potential impact a breach or an outage would have for the particular target.

3.1 Targets Summary (1)

The number of potential vulnerabilities found for each target by severity.

Target	 Critical	 High	 Medium	 Low	 Accepted
 https://amity.edu	1	0	2	1	0

3.2 Target Breakdowns


Details for the potential vulnerabilities found for each target by scan type.

Dhttps://amity.edu

Scans run:

OpenVAS

Total Risks




Network Vulnerabilities Last scanned: 05/27/2026	Severity	First Detected
jQuery End of Life (EOL) Detection - Windows cvss score: 9.9	Critical	05/27/2026
jQuery < 1.6.3 XSS Vulnerability cvss score: 4.3	Medium	05/27/2026
jQuery < 1.9.0 XSS Vulnerability cvss score: 6.1	Medium	05/27/2026
TCP Timestamps Information Disclosure cvss score: 2.6	Low	05/27/2026

4 Network Vulnerabilities

The OpenVAS network vulnerability scan tests servers and internet connected devices for over 150,000 vulnerabilities. OpenVAS uses the Common Vulnerability Scoring System (CVSS) to quantify the severity of findings. 0.0 is the lowest severity and 10.0 is the highest.


4.1 Scan Coverage

Shows how recently the included targets were last scanned.



4.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.



4.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	CVSS Score	EPSS Score	Open	Accepted
jQuery End of Life (EOL) Detection - Windows	Critical	9.9		1	0

jQuery < 1.9.0 XSS Vulnerability	Medium	6.1	0.9%	1	0
TCP Timestamps Information Disclosure	Low	2.6		1	0

4.4 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

jQuery End of Life (EOL) Detection - Windows

SEVERITY	AFFECTED TARGETS	LAST DETECTED	CVSS SCORE
Critical	1 target	0 minutes ago	9.9

Description

The jQuery version on the remote host has reached the end of life (EOL) and should not be used anymore.

An EOL version of jQuery is not receiving any security updates from the vendor. Unfixed security vulnerabilities might be leveraged by an attacker to compromise the security of this host.

The "jQuery" version on the remote host has reached the end of life.

CPE: cpe:/a:jquery:jquery:1.12.4
Installed version: 1.12.4
Location/URL: /aihas/assets/js/jquery.min.js
EOL version: 1
EOL date: unknown
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):
- Identified file: <https://amity.edu/aihas/assets/js/jquery.min.js>
- Referenced at: <https://amity.edu/aihas/>

Solution

Update jQuery on the remote host to a still supported version.

References

<https://github.com/jquery/jquery.com/pull/163>

Vulnerable Target	First Detected	Last Detected
https://amity.edu	05/27/2026	05/27/2026

jQuery < 1.6.3 XSS Vulnerability

SEVERITY	AFFECTED TARGETS	LAST DETECTED	CVSS SCORE	EPSS SCORE
Medium	1 target	0 minutes ago	4.3	6%

Description

jQuery is prone to a cross-site scripting (XSS) vulnerability.

Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.

Installed version: 1.3.2
Fixed version: 1.6.3
Installation
path / port: /Admission/amity_gallery/gallery/./jquery.fancybox/jquery-1.3.2.min.js

Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):

- Identified file: https://amity.edu/Admission/amity_gallery/gallery/./jquery.fancybox/jquery-1.3.2.min.js
- Referenced at: https://amity.edu/Admission/amity_gallery/gallery/

Solution

Update to version 1.6.3 or later.

References

CVE-2011-4969
<https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/>

Vulnerable Target	First Detected	Last Detected
https://amity.edu	05/27/2026	05/27/2026

jQuery < 1.9.0 XSS Vulnerability

SEVERITY

Medium

AFFECTED TARGETS

1 target

LAST DETECTED

0 minutes ago

CVSS SCORE

6.1

EPSS SCORE

0.9%

Description

jQuery is prone to a cross-site scripting (XSS) vulnerability.

The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.

Installed version: 1.8.2

Fixed version: 1.9.0

Installation

path / port: Externally hosted

Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):

- Identified file: src="http://ajax.googleapis.com/ajax/libs/jquery/1.8.3/jquery.min.js"

- Referenced at: <https://amity.edu/GreaterNoida/>

Note: The jQuery library is hosted on a different server. Because of this it is not possible to gather the version by a direct file access. Please manually inspect the version which gets included on this web page.

Solution

Update to version 1.9.0 or later.

References

CVE-2012-6708

<https://bugs.jquery.com/ticket/11290>

Vulnerable Target	First Detected	Last Detected
https://amity.edu	05/27/2026	05/27/2026



TCP Timestamps Information Disclosure

SEVERITY

Low

AFFECTED TARGETS

1 target

LAST DETECTED

0 minutes ago

CVSS SCORE

2.6

Description

The remote host implements TCP timestamps and therefore allows to compute the uptime.

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:

Packet 1: 889441040

Packet 2: 889442252

Solution

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'

Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

See the references for more information.

References

<https://datatracker.ietf.org/doc/html/rfc1323>

<https://datatracker.ietf.org/doc/html/rfc7323>

<https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152>

<https://www.fortiguard.com/psirt/FG-IR-16-090>

Vulnerable Target	First Detected	Last Detected
https://amity.edu	05/27/2026	05/27/2026

5 Glossary

Accepted Vulnerability

An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive scan result or an intentional part of the system's architecture.

Fully Qualified Domain Name (FQDN)

A fully qualified domain name is a complete domain name for a specific website or service on the internet. This includes not only the website or service name, but also the top-level domain name, such as .com, .org, .net, etc. For example, 'www.example.com' is an FQDN.

Network Vulnerabilities

The OpenVAS network vulnerability scan tests servers and internet connected devices for over 150,000 vulnerabilities. OpenVAS uses the Common Vulnerability Scoring System (CVSS) to quantify the severity of findings. 0.0 is the lowest severity and 10.0 is the highest.

Vulnerability

A weakness in the computational logic (e.g., code) found in software and hardware components that, when exploited, results in a negative impact to confidentiality, integrity, or availability. Mitigation of the vulnerabilities in this context typically involves coding changes, but could also include specification changes or even specification deprecations (e.g., removal of affected protocols or functionality in their entirety).

Target

A target represents target is a single URL, IP address, or fully qualified domain name (FQDN) that was scanned.

Severity

Severity represents the estimated impact potential of a particular vulnerability. Severity is divided into 5 categories: Critical, High, Medium, Low and Accepted.

CVSS Score

The CVSS 3.0 score is a global standard for evaluating vulnerabilities with a 0 to 10 scale. CVSS maps to threat levels:

0.1 - 3.9 = Low

4.0 - 6.9 = Medium

7.0 - 8.9 = High

9.0 - 10.0 = Critical

EPSS Score

The EPSS score is the estimated probability that a given vulnerability will be exploited in the wild within the next 30 days, on a 0% to 100% scale.

This report was prepared using

HostedScan Security®

For more information, visit hostedscan.com

Founded in Seattle, Washington in 2019, HostedScan, LLC. is dedicated to making continuous vulnerability scanning and risk management much more easily accessible to more businesses.



HostedScan, LLC.

2212 Queen Anne Ave N
Suite #521
Seattle, WA 98109

hostedscan.com

[Terms & Policies](#)
hello@hostedscan.com