```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Documents</title>
    <script src="first.js"></script>
    <link rel="stylesheet" href="docs.css">
</head>
<body>
    <script src="first.js"></script>
    <h1>Basic Linux Commands: Debian vs. Arch</h1>
    <p>you can see the apps you need in linux <a href="lapp.html">here</a>
</p>
    <div class="search-container">
        <input type="text" id="searchInput" placeholder="Search commands..
." onkeyup="filterTable()">
    </div>
    <table id="commandsTable">
        <tr>
            <th>Command</th>
            <th>Description</th>
            <th>Debian</th>
            <th>Arch</th>
        </tr>
        <tr>
            <td>Update Package List</td>
            <td>Updates the list of available packages and their versions.
</td>
            <td>`sudo apt update`</td>
            <td>`sudo pacman -Sy`</td>
        </tr>
        <tr>
            <td>Upgrade Installed Packages</td>
            <td>Upgrades all installed packages to the latest version.</td
>
            <td>`sudo apt upgrade`</td>
            <td>`sudo pacman -Su`</td>
        </tr>
        <tr>
            <td>Install a Package</td>
            <td>Installs a specified package.</td>
            <td>`sudo apt install package_name`</td>
            <td>`sudo pacman -S package_name`</td>
        </tr>
        <tr>
            <td>Remove a Package</td>
            <td>Removes a specified package.</td>
            <td>`sudo apt remove package_name`</td>
            <td>`sudo pacman -R package_name`</td>
        </tr>
        <tr>
            <td>Search for a Package</td>
            <td>Searches for a package in the repository.</td>
            <td>`apt search package_name`</td>
            <td>`pacman -Ss package_name`</td>
        </tr>
        <tr>
            <td>Show Package Information</td>
            <td>Displays information about a specific package.</td>
```

```
        <td>`apt show package_name`</td>
        <td>`pacman -Qi package_name`</td>
    </tr>
    <tr>
        <td>Open a folder</td>
        <td>open a specific directory </td>
        <td>cd 'folder name'</td>
        <td>cd 'folder name'</td>
    </tr>
    <tr>
        <td>back to previous folder</td>
        <td>go back to the previous folder</td>
        <td>cd ..</td>
        <td>cd ..</td>
    </tr>
    <tr>
        <td>Monitor System Performance</td>
        <td>Real-time monitoring of system resources.</td>
        <td>`htop`</td>
        <td>`htop`</td>
    </tr>

    <tr>
        <td>View System Logs</td>
        <td>Displays system logs for troubleshooting.</td>
        <td>`journalctl -xe`</td>
        <td>`journalctl -xe`</td>
    </tr>
    <tr>
        <td>Check Disk Usage</td>
        <td>Shows disk usage of file systems.</td>
        <td>`df -h`</td>
        <td>`df -h`</td>
    </tr>
    <tr>
        <td>Monitor System Performance</td>
        <td>Real-time monitoring of system resources.</td>
        <td>`htop`</td>
        <td>`htop`</td>
    </tr>
    <tr>
        <td>Find Files</td>
        <td>Searches for files in the directory hierarchy.</td>
        <td>`find /path/to/search -name "filename"`</td>
        <td>`find /path/to/search -name "filename"`</td>
    </tr>
    <tr>
        <td>Change File Permissions</td>
        <td>Changes the permissions of a file or directory.</td>
        <td>`chmod 755 filename`</td>
        <td>`chmod 755 filename`</td>
    </tr>
    <tr>
        <td>Change File Ownership</td>
        <td>Changes the owner and/or group of a file.</td>
        <td>`chown user:group filename`</td>
        <td>`chown user:group filename`</td>
    </tr>
    <tr>
        <td>Network Configuration</td>
```

```html
            <td>Displays network interfaces and configurations.</td>
            <td>`ip addr show`</td>
            <td>`ip addr show`</td>
        </tr>
        <tr>
            <td>Package Cleanup</td>
            <td>Removes unused packages and dependencies.</td>
            <td>`sudo apt autoremove`</td>
            <td>`sudo pacman -Rns $(pacman -Qdtq)`</td>
        </tr>
        <tr>
            <td>Backup and Restore</td>
            <td>Creates a backup of files/directories.</td>
            <td>`tar -czvf backup.tar.gz /path/to/backup`</td>
            <td>`tar -czvf backup.tar.gz /path/to/backup`</td>
        </tr>
        <tr>
            <td>Find Files</td>
            <td>Searches for files in the directory hierarchy.</td>
            <td>`find /path/to/search -name "filename"`</td>
            <td>`find /path/to/search -name "filename"`</td>
        </tr>
        <tr>
            <td>Network Configuration</td>
            <td>Displays network interfaces and configurations.</td>
            <td>`ip addr show`</td>
            <td>`ip addr show`</td>
        </tr>
        <tr>
            <td>Package Cleanup</td>
            <td>Removes unused packages and dependencies.</td>
            <td>`sudo apt autoremove`</td>
            <td>`sudo pacman -Rns $(pacman -Qdtq)`</td>
        </tr>
    </table>
</body>
</html>
    </table>


</body>
</html>
```