Enhancing Cybersecurity with Machine Learning: Evaluating the Efficacy of Isolation Forests and Autoencoders in Anomaly Detection

Rishabh Sharma
Centre for Research Impact & Outcome,
Chitkara University Institute of Engineering and Technology,
Chitkara University, Rajpura-140401 Punjab, India
rishabh.sharma@chitkara.edu.in

Madhur Grover
Chitkara Centre for Research and Development,
Chitkara University, Himachal Pradesh,174103, India
madhur.grover.orp@chitkara.edu.in

2024 7th International Conference on Circuit Power and Computing Technologies (ICCPCT) | 979-8-3503-7281-6/24/$31.00 ©2024 IEEE | DOI: 10.1109/ICCPCT61902.2024.10673338

***Abstract*— The growing intensity of cyber threats requires security systems with high intellectual capabilities that are dynamically adapting to new challenges. This study explores the utilization of Isolation Forests and Autoencoders in machine learning for anomaly detection. It is for their contribution to cybersecurity to boost it. In this research, an extensive dataset of network traffic that manifests both normal and malicious instances is used to examine the efficacy of these models in detecting anomalous events that may constitute cyber threats. The approach applied involves data collection, preprocessing, the thorough evaluation of the models against metrics such as Anomaly Detection Rate (ADR), Mean Time to Detect (MTTD), False Alarm Rate (FAR), and Detection Consistency (DC) Output shown that applying Isolation Forest has found 85% anomalous record, with a time to detect of 2 seconds and a consistency of 90%, while Autoencoder got slightly lower detecting rate but beats off false alarm by finding only 4%. Unlike traditional methods done by Support Vector Machines and Decision Trees where this model not only was successful but in some cases performed better, it validated their implementation ability and usefulness in the cybersecurity real world. The research presents a major activity of applying Isolation Forests and Autoencoders to cybersecurity systems which elevate their anomaly detection potency. This also explains the importance of combining it with other machine learning models within the existing security systems, for the ability to boost the accuracy in detection and decrease response time to threats. Therefore, this study is one of the crucial pieces in the building of systems that are adaptable and resilient to attacks that continue to be more unpredictable.**

***Keywords*— *Cybersecurity, Machine Learning, Anomaly Detection, Isolation Forest, Autoencoder, Network Traffic Analysis, Threat Detection, Cyber Defense*.**

I. INTRODUCTION

The cyber security landscape is constantly changing and its development requires the innovation of more advanced defense mechanisms to deal with the complex cyber threats [1]. Traditional security measures, though essential, proved to be completely inadequate against the new generation of multi-purposed and complex cyber assaults, thus allowing private and public networks to remain very vulnerable [2]. The inclusion of ML in cybersecurity strategies as an emerging area in the security field can be viewed as a positive avenue that can be explored to make cyber systems more secure [3]. This paper studies the use of anomaly detection algorithms, for instance, Isolation Forests and Autoencoders, as two powerful tools that identify unusual patterns and handle them as cyber threats or breaches [4]. A mainline of machine learning, namely anomaly detection, means finding behavioral patterns in data that deviate from the norm. These irregular models primarily draw attention to the large and in most cases serious, dangerous cases such as breaches, attacks, network penetration, and data privacy violations [5]. The main motivation for the implementation of anomaly detection in cybersecurity is that abnormal activities represent distinct data patterns against genuine activities. Machine learning algorithms now give the possibility to do this more quickly and accurately. In addition, irregularities are also detected automatically. Isolation Forest (an ensemble of anomaly detection methods) works by isolating anomalies rather than basing their results on profiling normal data points [6]. However, this characteristic is uniquely implemented by randomly selecting some feature and then picking up a value that lies between the minimum and maximum values of this feature. This method is especially useful when there are numerous dimensions of data involved, such as in network traffic data, and as a result, it enables immediate detection of abnormalities [7]. Consequently, many scientists have used autoencoders as a way to learn a compact representation of unlabeled data. In doing so, Autoencoders can filter and then reconstruct network traffic data, the outputs of which are expected to be similar to the original input data. Anomalies occurring are identified by comparing the reconstructing error; the greater the error, the higher the possibility that the data point is an anomaly [8]. This detection strategy is therefore good at detecting not just the simple and larger pattern deviations but also the more intricate and elusive irregularities. As these insightful machine learning methods are deployed in cybersecurity, perhaps not only does the detection speed and effectiveness improve, but this also reduces the time to detect and respond to potential threats, thereby increasing overall safety [5]. The goal of this paper will be to show that Isolation Forests and Autoencoders are practical ways in which cybersecurity can be explored, sharing both their strengths and weaknesses. In the succeeding parts, the theoretical background of anomaly detection, Isolation Forests, and Autoencoders will be elaborated, and the possibilities of their practical usage in cases with real data will be discussed as well [2]. This journey will demonstrate how machine learning has empowered the cybersecurity industry by enhancing the viability of our digital platforms.

979-8-3503-7281-6/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: INSTITUTE OF ENGINEERING & MANAGEMENT TRUST. Downloaded on April 24,2026 at 14:43:45 UTC from IEEE Xplore. Restrictions apply.

II. LITERATURE REVIEW

Machine learning literature concerning defending against cyber attacks through particle and elemental applications is huge and varied, which focuses on the application of various algorithms for the identification and counteracting of cyber threats [1]. One may speak about anomaly detection among the most important areas where machine learning, in contrast to conventional methods, may prove to be enormously helpful due to the reason that machines learn and adapt from the data [2]. Machine Learning's patterns and anomaly-detecting capability without explicit programming directions are among the key reasons this technology is pivotal in fighting cyber threats [4]. Many researchers have conducted various experiments with anomaly detection techniques based on machine learning where a substantial part of the effort was focused on unsupervised learning as these approaches don't use the predefined labels that are unavailable in new and unknown situations [6]. Among the different methods, Isolation Forests are highly recognized for their speed and scalability performance and these are the critical factors for dealing with the wide range and high dimensions of data that are characteristically associated with network traffic [3]. This method applies available resources more efficiently because it can separate the few outliers from the many, which leads to the fast identification of the vertices that allow easy determination of where the normal points lie [7]. The accuracy of the approach matches the unpredictability of cyber threats. However, Autoencoders are very well understood because they can reconstruct input data as well as learn to detect errors by the discrepancy in the reconstruction [8]. The program has illustrated some of the harm in the heavily noisy data services, but it is challenging to find the differences. The convincing feature of Autoencoders is their flexibility to generate deep learning models that can detect unique and complicated non-linear patterns with these kinds of attacks [7]. What is notable is that the implementation of these machine learning methods into cyber operations also gives rise to several practical issues like synthetic spam and the need to train on new data to embrace perpetual cyber vulnerabilities [1]. On the other hand, it has also been shown that machine learning algorithms show differing success rates in cybersecurity contexts: proving there is no one silver bullet and making it obvious that the environment is deciding the suitable tool [6]. The literature further discusses the use of multiple machine learning techniques that combine with the reference to enhance the rate of detection and reliability. One of the different ways to improve the general effectiveness of cybersecurity measures can be the synergy of different sizes of algorithms which includes, for instance, detecting anomalies fast and identifying the patterns by combining the fast anomaly detection of Isolation Forests and the detailed pattern recognition of Autoencoders [7]. Finally, the literature has built a solid basis for the use of machine learning in the field of cybersecurity, according to advancements made by anomaly detection. It offers a rich kit of methods, concepts, and statistical evidence that can serve for developed algorithms such as Isolation Forests and Autoencoders [8]. Nonetheless, these points give the basis for work that probes deeper into the complex lives and the exact integrations needed for the tools mentioned to be effective in practical scenarios. In this article, we take the existing knowledge base as a point of departure with a focus on offering further evidence on how machine learning is instrumental in elevating the cybersecurity landscape.

III. METHODOLOGY

This research paper implements a detailed methodology to measure the consistency of Isolated Forests and Autoencoders in identifying cybersecurity threats through anomaly detection. The methodology is structured into several key phases: data acquisition, data preparation, model training, and model evaluation [9]. Every phase of the study is of fundamental importance for guaranteeing the credibility and accuracy of it. This work utilizes a broad dataset, overall network traffic data, which consists both of benign and malicious traffic patterns. The details have been demonstrated in Table I. This dataset is the result of the combination of many cybersecurity databases to make sure the database has a robust sample that covers a wide spectrum of normal activities and attack channels. The data need to be prepared for a thought-out modeling process [10]. There are several preprocessing steps for this.

TABLE I. DATASET METRIC

Metric	Description	Value
Total Instances	Total number of data points in the dataset.	100,000
Number of Features	Total number of attributes per instance.	30
Benign Instances	Several normal data points are labeled as non-anomalous.	90,000
Malicious Instances	Number of data points labeled as anomalies (threats).	10,000
Percentage of Anomalies	Proportion of anomalous instances in the dataset.	10%
Dataset Sources	Origin(s) of the data collection.	Mixed sources including simulated and real-world network traffic data
Data Collection Period	The period over which the data was collected.	Jan 2023 - March 2023
Missing Data	Information on any missing values in the dataset.	Minimal, less than 0.5% of total data points
Data Imbalance Ratio	The ratio of benign to malicious instances.	9:1
Feature Type	Types of features (e.g., continuous, categorical).	Mostly continuous with some categorical (e.g., protocol type, port number)

Normalization: Numeric features are scaled to correspond with this standard range, in order not to have any attribute's influence on the model to be based on scale differences [11]. **Noise Reduction:** Techniques such as a rolling average and filtering smooth out random fluctuations that the algorithm

Authorized licensed use limited to: INSTITUTE OF ENGINEERING & MANAGEMENT TRUST. Downloaded on April 24,2026 at 14:43:45 UTC from IEEE Xplore. Restrictions apply.

may learn from and lead the learning algorithm in the wrong direction [12].

Feature Selection: Analyze to pick out the most important characteristics of an anomaly. This is where methods of Principal Component Analysis (PCA) come into play to achieve this by reducing dimension while retaining important information [13].

Model Implementation: Our process involves involving two specific structures having different configurations.

Isolation Forest Implementation:

Parameters: Adjustments include the number of trees, the sample size, and the mode of isolation which were fine-tuned by observations in the first trials [12].

Training: The model caters to the preprocessed data of a given amount of the data to create an effective anomaly identification based on the forest path length [14].

Autoencoder Implementation:

Architecture: The suggested model has a configuration comprising of an input layer correlating with the count of selected features, one or more hidden layers, and an output layer that replicates the previous input. The complete architecture of the model is shown in Figure 1.



Fig 1. Hybrid Model Flow

Loss Function: The reconstruction loss is applied, using to see how well the output of the encoder-decoder system can restore the given sample [15].

Optimizer: The Adam algorithm works on minimizing the error during training by maximizing the reconstruction.

Model Evaluation: The performance of each model is measured through its capacity to classify data accurately, where having the greatest number of correct classifications is regarded highly. The metrics measured take place in.

Anomaly Detection Rate (ADR): The detection of true anomalies becomes the main factor currently evaluated by the model.

Mean Time to Detect (MTTD): Statistical representation of the mean the model took to identify an anomaly once it has occurred.

False Alarm Rate (FAR): The high-incident amount of normal objects that is under-detected as an anomaly.

Detection Consistency (DC): Engages the consistency of Deviation design across the different foreins within the test data set.

IV. Results and Discussions

The performance of Isolation Forest and Autoencoder models in detecting cybersecurity anomalies is huge and these are considered in testing their effectiveness with the described dataset. The evaluation focused on several performance metrics: The four essential metrics used for the assessment of the system efficiency are: ADR (Anomaly Detection Rate), MTTD (Mean Time to Detect), FAR (False Alarm Rate), and DC (Detection Consistency). The outcomes present the pros and cons of each model and they provide an insight into them with the latest or best techniques in the industry in the field of anomaly detection. Table II below presents the performance of two models.

TABLE II. MODELS PERFORMANCE

Model	Anomaly Detection Rate	Mean Time to Detect	False Alarm Rate	Detection Consistency
Isolation Forest	85%	2 seconds	5%	90%
Autoencoder	80%	3 seconds	4%	85%

The Isolation Forest model showed simply better ADR and DC, which could mean that it is a little bit more accurate than other methods when we need quick detection of an anomaly in this data set. Nevertheless, simpler Autoencoder had a lower False Alarm Rate which might be attributable to its favorable applications in fields where it is important to avoid false positives occurrences such as military surveillance. To contextualize these findings by placing them within the broader field of machine learning for cybersecurity, a comparison was established with the other state-of-the-art anomaly detection methods often given attention in the most recent literature with the example given in Figure 2. The techniques were SVM, Decision Trees, and Neural Networks among many others.



Fig 2. State-of-the-art Comparison

The results show that both Isolation Forests and Autoencoders which are anomaly detection effective detection tools are sensitive to anomaly type and structure of data. Ensemble techniques of Isolation Forests are not many and those are highly effective for tackling large datasets

Authorized licensed use limited to: INSTITUTE OF ENGINEERING & MANAGEMENT TRUST. Downloaded on April 24,2026 at 14:43:45 UTC from IEEE Xplore. Restrictions apply.

quickly that tend to be observed in real-time based cyber threat detection. While on the one hand, Autoencoders indeed can use their ability to reconstruct data to develop an in-depth knowledge of normality and anomaly and therefore contribute to the reduction of false positives, on the other hand, data clustering also proves to be good at detecting the presence of an outlier to ensure the robustness of the model. The suggested study frequently encountered some challenges in the research. This was the core problem along the lines of the searching speed versus precision and the consistency of the results received. Moreover, the remarkably different results that appeared between diverse attack scenarios insinuated that it is likely that a hybrid approach, which combines more than one machine learning model, should be considered. The next step could be a system that augments both Isolation Forests and Autoencoders, combining the strengths of both methods while getting around the output errors of autoencoders. Furthermore, a finding of the second stage examination is establishing the implications of more in-depth network traffic analytics and their effectiveness on the model accuracy and robustness. The last area that has been identified for improvement is leveraging transfer learning to customize the models that are trained on one type of network traffic to other types to broadly use it.

V. Conclusion

The exploitation of machine learning in cybersecurity, with the help of Isolation Forests and Autoencoders for anomaly detection, proved to be a powerful tool for cybersecurity professionals for faster detection and aggregation of cyber threats, and also sharpening the cybersecurity response. This piece of research was conducted to critically assess the applicability of these models in the detection of unusual veering within network traffic that may indicate an ill-intention activity. This study has shown the strengths of both Isolation Forests and Autoencoders as useful and complementary components of cybersecurity collections; Isolation Forests focus their strength on one particular aspect of anomaly detection while Autoencoders efficiently deliver other aspects. The Isolation Forest approach exhibited its competence in simple anomaly detection by providing very highly accurate and consistent results that are most suitable in situations where time is paramount. On the other hand, Autoencoder seems to be a more advantageous means of distinguishing species in conditions involving a higher rate of false alarms. The fact that our algorithm holds its own against some of the best-performing algorithms in the world gives rise to a wide consensus that these models might compete well separately but they might complement each other when combined. Hybridism is possibly the next big thing in modeling. On the other hand, this survey also promotes the bi-directional relation between model complexity, detection precision, and operational effectiveness. With the cyber threats constantly mutating in sophistication and subtleness, the input of more intricate and flexible models becomes an urgent necessity. Hence, new investigations will be strong concerning achieving the integration of these models with hybrid approaches, which will take into account the capabilities offered by different machine learning methods to generate more effective and efficient systems. Likewise, we may aim at excavating the true power of elaborate features such as deeper feature pools as well as transfer learning which could promote the idea of producing more generic and scalable solutions.

References

[1] S. J. Et al., "Enhancing Cyber Security through Machine Learning-Based Anomaly Detection in IoT Networks," International Journal on Recent and Innovation Trends in Computing and Communication, vol. 11, no. 10, 2023.

[2] F. Carrera, V. Dentamaro, S. Galantucci, A. Iannacone, D. Impedovo, and G. Pirlo, "Combining Unsupervised Approaches for Near Real-Time Network Traffic Anomaly Detection," Applied Sciences, 2022.

[3] A. L. Alfeo, M. Cimino, G. Manco, E. Ritacco, and G. Vaglini, "Using an autoencoder in the design of an anomaly detector for smart manufacturing," Pattern Recognit. Lett., vol. 136, pp. 272-278, 2020.

[4] D. Laura Aguilar, M. A. Medina-Pérez, O. Loyola-González, K. Choo, and Edoardo Bucheli-Susarrey, "Towards an Interpretable Autoencoder: A Decision-Tree-Based Autoencoder and its Application in Anomaly Detection," IEEE Transactions on Dependable and Secure Computing, vol. 20, pp. 1048-1059, 2023.

[5] A. Hariharan, Ankit Gupta, and T. Pal, "CAMLPAD: Cybersecurity Autonomous Machine Learning Platform for Anomaly Detection," ArXiv, vol. abs/1907.10442, 2019.

[6] Y. Jaoudi, C. Yakopcic, and T. Taha, "Conversion of an Unsupervised Anomaly Detection System to Spiking Neural Network for Car Hacking Identification," 2020 11th International Green and Sustainable Computing Workshops (IGSC), 2020.

[7] T. Smolen and L. Benova, "Comparing Autoencoder and Isolation Forest in Network Anomaly Detection," 2023 33rd Conference of Open Innovations Association (FRUCT), pp. 276-282, 2023.

[8] V. Toufigh and Iman Ranjbar, "Unsupervised deep learning framework for ultrasonic-based distributed damage detection in concrete: integration of a deep auto-encoder and Isolation Forest for anomaly detection," Structural Health Monitoring, 2023.

[9] R. Sharma, V. Kukreja, R. K. Kaushal, A. Bansal and A. Kaur, "Rice Leaf blight Disease detection using multi-classification deep learning model," 2022 10th International Conference on Reliability, Infocom Technologies and Optimization (Trends and Future Directions) (ICRITO), Noida, India, 2022, pp. 1-5.

[10] Y. Patel et al., "Deepfake Generation and Detection: Case Study and Challenges," IEEE Access, vol. 11, pp. 143296–143323, 2023.

[11] P. Singla, Niharika, R. jain, R. Sharma, V. Kukreja and A. Bansal, "Deep Learning Based Multi-Classification Model for Rice Disease Detection," 2022 10th International Conference on Reliability, Infocom Technologies and Optimization (Trends and Future Directions) *(ICRITO)*, Noida, India, 2022, pp. 1-5.

[12] D. Kumar and V. Kukreja, "N-CNN Based Transfer Learning Method for Classification of Powdery Mildew Wheat Disease," 2021 International Conference on Emerging Smart Computing and Informatics (ESCI), Pune, India, 2021, pp. 707-710.

[13] S. K. Brar, R. Sharma, S. Vats, and V. Kukreja, "A smart approach to coconut leaf spot disease classification using computer vision and deep learning technique," in Proc. World Conf. Commun. & Comput. (WCONF), 2023, pp. 1-6.

[14] V. Kukreja, R. Sharma, and S. Vats, "A Hybrid Deep Learning Approach for Multi-Classification of Heritage

Authorized licensed use limited to: INSTITUTE OF ENGINEERING & MANAGEMENT TRUST. Downloaded on April 24,2026 at 14:43:45 UTC from IEEE Xplore. Restrictions apply.

Monuments Using a Real-Phase Image Dataset," in Proc. 5th Int. Conf. Inventive Res. Comput. Appl. (ICIRCA), 2023, pp. 29-32.

[15] S. K. Brar, R. Sharma, S. Vats, and V. Kukreja, "Sugar Learning: Deep Learning for Rapid Detection and Classification of Sugarcane Diseases," in Proc. World Conf. Commun. & Comput. (WCONF), 2023, pp. 1-6.

Authorized licensed use limited to: INSTITUTE OF ENGINEERING & MANAGEMENT TRUST. Downloaded on April 24,2026 at 14:43:45 UTC from IEEE Xplore. Restrictions apply.