

Bootstrap 4 Toast

[< Previous](#)[Next >](#)

Bootstrap 4 Toast

The toast component is like an alert box that is only shown for a couple of seconds when something happens (i.e. when the user clicks on a button, submits a form, etc.).

Toast Header

5 mins ago ✕


Some text inside the toast body

How To Create a Toast

To create a toast, use the `.toast` class, and add a `.toast-header` and a `.toast-body` inside of it:

```
<div class="attribute" style="color:red"> class="attribute" style="color:mediumblue">="toast"="tag" style="color:mediumblue">>
  <div class="attribute" style="color:red"> class="attribute" style="color:mediumblue">>
```

COLOR
PICKER



 Get Certified

ADVERTISEMENT

```
style="color:mediumblue">="toast-header"="tagcolor" style="color:mediumblue">>
    Toast Header
</div class="tagcolor" style="color:mediumblue">>
<div class="attributevaluecolor" style="color:red"> class="attributevaluecolor"
style="color:mediumblue">="toast-body"="tagcolor" style="color:mediumblue">>
    Some text inside the toast body
</div class="tagcolor" style="color:mediumblue">>
</div class="tagcolor" style="color:mediumblue">>
```

Note: Toasts must be initialized with jQuery: select the specified element and call the `toast()` method.

The following code will show all "toasts" in the document:

Example

```
<script class="tagcolor" style="color:mediumblue">>
$(document).ready(function() {
    $('.toast').toast('show');
});
</script class="tagcolor" style="color:mediumblue">>
```

Try it Yourself »

Show and Hide a Toast

Toasts are hidden by default. Use the `data-autohide="false"` attribute to show it by default. To close it, use a `<button>` element and add `data-dismiss="toast"` :

Example

```
<div class="attributecolor" style="color:red"> class="attributevaluecolor"
style="color:mediumblue">="toast" data-autohide="attributevaluecolor"
style="color:mediumblue">="false"="tagcolor" style="color:mediumblue">>
  <div class="attributecolor" style="color:red"> class="attributevaluecolor"
style="color:mediumblue">="toast-header"="tagcolor" style="color:mediumblue">>
    <strong class="attributecolor" style="color:red"> class="attributevaluecolor"
style="color:mediumblue">="mr-auto text-primary"="tagcolor"
style="color:mediumblue">>Toast Header</strong class="tagcolor"
style="color:mediumblue">>
    <small class="attributecolor" style="color:red"> class="attributevaluecolor"
style="color:mediumblue">="text-muted"="tagcolor" style="color:mediumblue">>5 mins
ago</small class="tagcolor" style="color:mediumblue">>
    <button class="attributecolor" style="color:red"> type="attributevaluecolor"
style="color:mediumblue">="button" class="attributevaluecolor"
style="color:mediumblue">="ml-2 mb-1 close" data-dismiss="attributevaluecolor"
style="color:mediumblue">="toast"="tagcolor" style="color:mediumblue">>&times;
</button class="tagcolor" style="color:mediumblue">>
  </div class="tagcolor" style="color:mediumblue">>
  <div class="attributecolor" style="color:red"> class="attributevaluecolor"
style="color:mediumblue">="toast-body"="tagcolor" style="color:mediumblue">>
    Some text inside the toast body
  </div class="tagcolor" style="color:mediumblue">>
</div class="tagcolor" style="color:mediumblue">>
```

Try it Yourself »

Notice the `mr-auto`, `ml-2` and `mb-1` classes? They are used to add specific margins. You will learn more about them in the [Bootstrap 4 Utilities Chapter](#).

Complete Bootstrap Toast Reference

For a complete reference of all toast options, methods and events, go to our [Bootstrap JS Toast Reference](#).

[◀ Previous](#)[Log in to track progress](#)[Next ▶](#)

ADVERTISEMENT

ADVERTISEMENT

