

# Power Distribution System for a CubeSat

Presented by :

Ansaf Niyaz | TRV19EE016   Govind Murali | TRV19EE025  
Jijesh J. Kumar | TRV19EE029   Naveen A.B. | TRV19EE038

GEC Barton Hill, Thiruvananthapuram

December 21, 2022

Guided by: Dr.Dinesh Gopinath

# Contents

1. Objectives
2. Project Outline
3. Literature Review
4. Methodology
5. System Architecture
6. Power Budget
7. Hardware Design
8. Requirements
9. Budget Estimate
10. Project Timeline
11. References

# Objective

To design and implement a fully autonomous power generation, storage and distribution system for a CubeSat

# Project Outline

## Electrical Power System (EPS):

- Harvests energy from the solar panels
- Manages power storage and distribution
- Protects circuits from damage
- Redundant architecture

# Literature Review

S.No.	Title	Author	Features
1	A Comprehensive Review on CubeSat Electrical Power System Architectures, in IEEE Transactions on Power Electronics, vol. 37, no. 3, pp. 3161-3177, March 2022	Amarendra Edpuganti , Vinod Khadkikar, Mohamed Shawky El Moursi, Hatem Zeineldin , Naji Al-Sayari, Khalifa Al Hosani	Architecture with PPT an regulated DC-bus was selected.
2	Output power analysis of Tel-USat electrical power system, AIP Conference Proceedings 2226, 030007 (2020)	Aulia Indana, Dharu Arseno, Edwar, Adilla Safira	Centralised architecture was selected.
3	Comparison of Peak Power Tracking Based Electric Power System Architecture for CubeSats, IEEE Transactions on Industry Applications, vol. 57, no. 3, pp. 2758-2768, May-June 2021	A. Edpuganti, V. Khadkikar, H. Zeineldin, M. S. E. Moursi, M. Al Hosani	Peak power transfer is preferred to direct power transfer.

## Literature Review (contd...)

S.No	Title and Journal	Author	Features
4	A Review of Battery Technology in CubeSats and Small Satellite Solutions, Energies, vol. 13, 2020	Knap, Vaclav & Vestergaard, Lars & Stroe, Daniel-loan	Solar cells with Li-ion batteries for storage is preferred.
5	Review on the charging techniques of a Li-Ion battery, Third International Conference on Technological Advances in Electrical, Electronics and Computer Engineering (TAEECE), 2015	E. Ayoub and N. Karami	Charging at 5-45°C

# Methodology

- Identifying the power requirements
- Architecture design and topology selection
- Forming Specifications
- Design and simulation
- Procurement of components
- Fabrication and testing

# Power Budget

Sub-system		Voltage (V)	Max. Current (mA)	Power (mW)	Contingency 5%	Margin 20%	Duty Cycle (%)	Energy (Wh)
<b>ADCS</b>	ADCS	3.3	20	66	69.3	83.16	100	0.133725438
	Magnetorquer	3.3	100	330	346.5	415.8	50	0.334313595
<b>OBC</b>	OBC	5	40	200	210	252	100	0.4052286
<b>CxTx</b>	Telemetry	5	300	1500	1575	1890	11	0.334313595
	Beacon	5	20	100	105	126	100	0.2026143
	GPS	3.3	40	132	138.6	166.32	30	0.0802352628
<b>Payload</b>	LoRa	5	20	100	105	126	10	0.02026143
<b>EPS</b>	EPS	-	-	160	168	201.6	100	0.32418288
	Thermal	-	-	250	262.5	315	32	0.16209144
					<b>Tot Power(mW)</b>	<b>3575.88</b>	<b>Tot. Energy</b>	<b>1.997</b>



# System Architecture




Figure 1: CubeSat EPS Architecture

# Hardware Design- Buck and Boost converters




Figure 2: Circuit design of buck and boost converters.

# Hardware Design- Battery Charger




Figure 3: Circuit design of Battery Charger

# Hardware Design- MPPT




Figure 4: Circuit design of MPPT.

# Hardware Design- Solar panels and Battery

# Requirements

## Equipments Requirements:

- SMD Soldering Station
- Oscilloscope
- Power Supply
- Function Generator

## Software Requirements:

- MATLAB/Spice
- KiCad
- STM32 CubeIDE

## Budget Estimate: Component cost

SI No.	Component	Description	No.	Cost per unit	Total Cost
1	SPV1040T	MPPT IC	6	400	2400
2	BQ25302	Battery Charger IC	2	150	300
3	NCR18650	Battery	2	800	1600
4	TPS62203DBVTGH	Buck Converter	2	150	300
5	LTC3426ES6#TRPBF	Boost Converter	2	500	1000
6	LTC2990CMS#TRPBF	Voltage, Current Measuring	5	560	2800
7	LTC 4361CT68-1	Overvoltage, overcurrent protection	5	500	2500
8	STM 32 F401RE	Microcontroller	1	2500	2500
9	Miscellaneous costs				2000
					15400

## Budget Estimate: Fabrication cost

Sl. No.	Item	Amount (Rs.)
1	PCB Printing	5000
2	SMD soldering	990
3	Inductor Fabrication	1000



# Project Timeline

Activity	Oct week 3-4	Nov week 1-2	Nov week 3-4	Dec week 1-2	Dec week 3-4
Literature Review					
Hardware Design					
Report Writing					
Component selection					
Component Procurement					

# References

- [1] Knap, Vaclav & Vestergaard, Lars & Stroe, Daniel-loan (2020 )  
A Review of Battery Technology in CubeSats and Small Satellite Solutions  
*Energies, vol. 13*
- [2] A. Edpuganti, V. Khadkikar, H. Zeineldin, M. S. E. Moursi and M. Al Hosani (2021)  
Comparison of Peak Power Tracking Based Electric Power System Architectures for CubeSats  
*IEEE Transactions on Industry Applications, vol. 57, no. 3, pp. 2758-2768, May-June 2021*
- [3] E. Ayoub and N. Karami  
Review on the charging techniques of a Li-Ion battery  
*Third International Conference on Technological Advances in Electrical, Electronics and Computer Engineering (TAECE), 2015, pp. 50-55*

## References (Contd.)

- [4] B. Hussein, A. M. Massoud and T. Khattab (2022)  
Centralized, Distributed, and Module-Integrated Electric Power System Schemes in CubeSats: Performance Assessment  
*IEEE Access*, vol. 10, pp. 55396-55407
- [5] A. Edpuganti, V. Khadkikar, M. S. E. Moursi, H. Zeineldin, N. Al-Sayari and K. Al Hosani (2022)  
A Comprehensive Review on CubeSat Electrical Power System Architectures  
*IEEE Transactions on Power Electronics*, vol. 37, no. 3, pp. 3161-3177, March 2022
- [6] Aulia Indana, Dharu Arseno, Edwar, and Adilla Safira (2020)  
Output Power Analysis of Tel-USat Electrical Power System  
AIP Conference Proceedings 2226

# Thank You