

RAPP Platform

v0.5.5

Generated by Doxygen 1.8.6

Wed Dec 16 2015 02:01:26

Contents

1	Todo List	1
2	Namespace Index	3
2.1	Namespace List	3
3	Hierarchical Index	5
3.1	Class Hierarchy	5
4	Class Index	7
4.1	Class List	7
5	File Index	9
5.1	File List	9
6	Namespace Documentation	11
6.1	cognitive_exercise Namespace Reference	11
6.2	cognitive_exercise_main Namespace Reference	11
6.2.1	Variable Documentation	11
6.2.1.1	CognitiveExerciseNode	11
6.3	mysql_wrapper Namespace Reference	11
6.4	mysql_wrapper_main Namespace Reference	11
6.4.1	Variable Documentation	12
6.4.1.1	MySQLWrapperNode	12
6.5	rapp_audio_processing Namespace Reference	12
6.6	rapp_audio_processing.rapp_audio_processing Namespace Reference	12
6.6.1	Variable Documentation	12
6.6.1.1	AudioProcessingNode	12
6.7	rapp_audio_processing.rapp_detect_silence Namespace Reference	12
6.8	rapp_audio_processing.rapp_energy_denoise Namespace Reference	12
6.9	rapp_audio_processing.rapp_set_noise_profile Namespace Reference	13
6.10	rapp_audio_processing.rapp_sox_denoise Namespace Reference	13
6.11	rapp_audio_processing.rapp_transform_audio Namespace Reference	13
6.12	rapp_audio_processing.rapp_utilities Namespace Reference	13

6.13	rapp_exceptions Namespace Reference	13
6.14	rapp_speech_detection_sphinx4 Namespace Reference	13
6.15	rapp_speech_detection_sphinx4.english_support Namespace Reference	14
6.16	rapp_speech_detection_sphinx4.global_parameters Namespace Reference	14
6.17	rapp_speech_detection_sphinx4.greek_support Namespace Reference	14
6.18	rapp_speech_detection_sphinx4.limited_vocabulary_creator Namespace Reference	14
6.19	rapp_speech_detection_sphinx4.rapp_exceptions Namespace Reference	14
6.20	rapp_speech_detection_sphinx4.rapp_tools Namespace Reference	14
6.20.1	Function Documentation	14
6.20.1.1	rapp_print	14
6.21	rapp_speech_detection_sphinx4.speech_recognition_sphinx4 Namespace Reference	15
6.21.1	Variable Documentation	15
6.21.1.1	SpeechRecognitionSphinx4Node	15
6.22	rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node Namespace Reference	15
6.22.1	Variable Documentation	15
6.22.1.1	SpeechRecognitionSphinx4HandlerNode	15
6.23	rapp_speech_detection_sphinx4.sphinx4_configuration_params Namespace Reference	15
6.24	rapp_speech_detection_sphinx4.sphinx4_wrapper Namespace Reference	16
6.25	speech_recognition_google Namespace Reference	16
6.25.1	Variable Documentation	16
6.25.1.1	speech_to_text_node	16
6.26	text_to_speech_espeak Namespace Reference	16
6.26.1	Variable Documentation	16
6.26.1.1	text_to_speech_espeak_ros_node	16
7	Class Documentation	17
7.1	rapp_audio_processing.rapp_audio_processing.AudioProcessing Class Reference	17
7.1.1	Detailed Description	18
7.1.2	Constructor & Destructor Documentation	18
7.1.2.1	__init__	18
7.1.3	Member Function Documentation	18
7.1.3.1	denoiseCallback	18
7.1.3.2	detectSilenceCallback	18
7.1.3.3	energyDenoiseCallback	18
7.1.3.4	setNoiseProfileCallback	19
7.1.3.5	transformAudioCallback	19
7.1.4	Member Data Documentation	19
7.1.4.1	_detect_silence_module	19
7.1.4.2	_energy_denoise_module	19
7.1.4.3	_energy_denoising_debug	20

7.1.4.4	_set_noise_profile_module	20
7.1.4.5	_sox_denoise_module	20
7.1.4.6	_transform_audio_module	20
7.1.4.7	_utilities_module	20
7.2	cognitive_exercise.CognitiveExercise Class Reference	20
7.2.1	Detailed Description	21
7.2.2	Constructor & Destructor Documentation	21
7.2.2.1	__init__	21
7.2.3	Member Function Documentation	21
7.2.3.1	chooserDataHandler	21
7.2.3.2	cognitiveTestCreatorDataHandler	21
7.2.3.3	recordUserCognitiveTestPerformanceDataHandler	21
7.2.4	Member Data Documentation	21
7.2.4.1	serv	22
7.2.4.2	serv_topic	22
7.3	rapp_audio_processing.rapp_detect_silence.DetectSilence Class Reference	22
7.3.1	Detailed Description	22
7.3.2	Member Function Documentation	22
7.3.2.1	detectSilence	22
7.4	rapp_audio_processing.rapp_energy_denoise.EnergyDenoise Class Reference	22
7.4.1	Detailed Description	23
7.4.2	Member Function Documentation	23
7.4.2.1	energyDenoise	23
7.5	rapp_speech_detection_sphinx4.english_support.EnglishSupport Class Reference	23
7.5.1	Detailed Description	24
7.5.2	Constructor & Destructor Documentation	24
7.5.2.1	__init__	24
7.5.3	Member Function Documentation	25
7.5.3.1	getGenericConfiguration	25
7.5.3.2	getLimitedVocebularyConfiguration	25
7.5.3.3	getWordPhonemes	25
7.5.4	Member Data Documentation	25
7.5.4.1	_english_dict_file	25
7.5.4.2	_english_dict_mapping	25
7.5.4.3	_generic_sphinx_configuration	26
7.5.4.4	_vocabulary	26
7.6	FaceDetection Class Reference	26
7.6.1	Detailed Description	27
7.6.2	Constructor & Destructor Documentation	27
7.6.2.1	FaceDetection	27

7.6.3	Member Function Documentation	27
7.6.3.1	faceDetectionCallback	27
7.6.4	Member Data Documentation	27
7.6.4.1	face_detector_	27
7.6.4.2	faceDetectionService_	27
7.6.4.3	faceDetectionTopic_	28
7.6.4.4	nh_	28
7.7	FaceDetector Class Reference	28
7.7.1	Detailed Description	28
7.7.2	Constructor & Destructor Documentation	28
7.7.2.1	FaceDetector	28
7.7.3	Member Function Documentation	29
7.7.3.1	detectFaces	29
7.7.3.2	detectFaces	29
7.7.3.3	findFaces	29
7.7.3.4	identifyUniqueFaces	29
7.7.3.5	loadImage	30
7.8	rapp_speech_detection_sphinx4.global_parameters.GlobalParams Class Reference	30
7.8.1	Detailed Description	31
7.8.2	Constructor & Destructor Documentation	31
7.8.2.1	__init__	31
7.8.3	Member Data Documentation	31
7.8.3.1	_acoustic_models_url	31
7.8.3.2	_allow_sphinx_output	31
7.8.3.3	_language_models_url	31
7.8.3.4	_noise_profiles_url	31
7.8.3.5	_socket_host	31
7.8.3.6	_sphinx_jar_file	31
7.8.3.7	_sphinx_jar_files_url	31
7.8.3.8	_sphinx_package_url	32
7.8.3.9	_tmp_language_models_url	32
7.8.3.10	rospack	32
7.9	rapp_speech_detection_sphinx4.greek_support.GreekSupport Class Reference	32
7.9.1	Detailed Description	34
7.9.2	Constructor & Destructor Documentation	34
7.9.2.1	__init__	34
7.9.3	Member Function Documentation	34
7.9.3.1	_configureLetters	34
7.9.3.2	_englify_words	34
7.9.3.3	_separateEngGrWords	34

7.9.3.4	_transformWords	35
7.9.3.5	getGenericConfiguration	35
7.9.3.6	getLimitedVocebularyConfiguration	35
7.9.4	Member Data Documentation	36
7.9.4.1	_all_special_two_digit_letters	36
7.9.4.2	_capital_letters	36
7.9.4.3	_english_support	36
7.9.4.4	_generic_sphinx_configuration	36
7.9.4.5	_letters	36
7.9.4.6	_literal_letters	36
7.9.4.7	_phonemes	36
7.9.4.8	_s_specific_rules	36
7.9.4.9	_special_two_digit_letters	37
7.9.4.10	_two_digit_letters	37
7.9.4.11	_vocabulary	37
7.10	KnowrobWrapper Class Reference	37
7.10.1	Detailed Description	38
7.10.2	Constructor & Destructor Documentation	38
7.10.2.1	KnowrobWrapper	38
7.10.3	Member Function Documentation	39
7.10.3.1	assertAttributeValue	39
7.10.3.2	clear_user_cognitive_tests_performance_records	40
7.10.3.3	cognitive_tests_of_type	40
7.10.3.4	create_cognitive_tests	40
7.10.3.5	create_ontology_alias	41
7.10.3.6	create_ontology_alias_for_new_user	41
7.10.3.7	createInstanceQuery	41
7.10.3.8	dumpOntologyQuery	41
7.10.3.9	get_ontology_alias	42
7.10.3.10	isSubSuperclassOfQuery	42
7.10.3.11	loadOntologyQuery	42
7.10.3.12	record_user_cognitive_tests_performance	42
7.10.3.13	subclassesOfQuery	43
7.10.3.14	superclassesOfQuery	43
7.10.3.15	user_instances_of_class	43
7.10.3.16	user_performance_cognitive_tests	44
7.10.4	Member Data Documentation	44
7.10.4.1	mysql_fetch_client	44
7.10.4.2	mysql_update_client	44
7.10.4.3	mysql_write_client	44

7.10.4.4	nh_	44
7.10.4.5	pl	45
7.11	KnowrobWrapperCommunications Class Reference	45
7.11.1	Detailed Description	47
7.11.2	Constructor & Destructor Documentation	47
7.11.2.1	KnowrobWrapperCommunications	47
7.11.3	Member Function Documentation	47
7.11.3.1	clear_user_cognitive_tests_performance_records_callback	47
7.11.3.2	cognitive_tests_of_type_callback	47
7.11.3.3	create_cognitive_tests_callback	48
7.11.3.4	create_ontology_alias_callback	48
7.11.3.5	createInstanceCallback	48
7.11.3.6	dumpOntologyCallback	49
7.11.3.7	isSubSuperclassOfCallback	49
7.11.3.8	loadOntologyCallback	49
7.11.3.9	record_user_cognitive_tests_performance_callback	50
7.11.3.10	subclassesOfCallback	50
7.11.3.11	superclassesOfCallback	50
7.11.3.12	user_instances_of_class_callback	51
7.11.3.13	user_performance_cognitive_tests_callback	51
7.11.4	Member Data Documentation	51
7.11.4.1	clear_user_cognitive_tests_performance_records_service_	51
7.11.4.2	clear_user_cognitive_tests_performance_records_topic_	51
7.11.4.3	cognitive_tests_of_type_service_	52
7.11.4.4	cognitive_tests_of_type_topic_	52
7.11.4.5	create_cognitive_tests_service_	52
7.11.4.6	create_cognitive_tests_topic_	52
7.11.4.7	create_ontology_alias_service_	52
7.11.4.8	create_ontology_alias_topic_	52
7.11.4.9	createInstanceService_	52
7.11.4.10	createInstanceServiceTopic_	52
7.11.4.11	dumpOntologyService_	52
7.11.4.12	dumpOntologyServiceTopic_	53
7.11.4.13	is_subsuperclass_of_service_	53
7.11.4.14	is_subsuperclass_of_service_topic_	53
7.11.4.15	knowrob_wrapper	53
7.11.4.16	loadOntologyService_	53
7.11.4.17	loadOntologyServiceTopic_	53
7.11.4.18	nh_	53
7.11.4.19	record_user_cognitive_tests_performance_service_	53

7.11.4.20 record_user_cognitive_tests_performance_topic_	53
7.11.4.21 subclasses_of_service_	54
7.11.4.22 subclasses_of_service_topic_	54
7.11.4.23 superclasses_of_service_	54
7.11.4.24 superclasses_of_service_topic_	54
7.11.4.25 user_instances_of_class_service_	54
7.11.4.26 user_instances_of_class_topic_	54
7.11.4.27 user_performance_cognitive_tests_service_	54
7.11.4.28 user_performance_cognitive_tests_topic_	54
7.12 rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator Class Reference	55
7.12.1 Detailed Description	56
7.12.2 Constructor & Destructor Documentation	56
7.12.2.1 __init__	56
7.12.3 Member Function Documentation	56
7.12.3.1 createConfigurationFiles	56
7.12.4 Member Data Documentation	56
7.12.4.1 _allow_sphinx_output	56
7.12.4.2 languages_package	56
7.12.4.3 sphinx_configuration	56
7.13 mysql_wrapper.MySQLdbWrapper Class Reference	57
7.13.1 Detailed Description	58
7.13.2 Constructor & Destructor Documentation	59
7.13.2.1 __init__	59
7.13.3 Member Function Documentation	59
7.13.3.1 checkConnection	59
7.13.3.2 constructAndQuery	59
7.13.3.3 constructCommaColumns	59
7.13.3.4 deleteData	59
7.13.3.5 fetchData	60
7.13.3.6 getLogin	60
7.13.3.7 getTableColumnNames	60
7.13.3.8 tblAppsRobotsDeleteDataHandler	60
7.13.3.9 tblAppsRobotsFetchDataHandler	61
7.13.3.10 tblAppsRobotsUpdateDataHandler	62
7.13.3.11 tblAppsRobotsWriteDataHandler	62
7.13.3.12 tblModelDeleteDataHandler	62
7.13.3.13 tblModelFetchDataHandler	62
7.13.3.14 tblModelUpdateDataHandler	63
7.13.3.15 tblModelWriteDataHandler	64

7.13.3.16	tblRappDeleteDataHandler	64
7.13.3.17	tblRappFetchDataHandler	64
7.13.3.18	tblRappUpdateDataHandler	64
7.13.3.19	tblRappWriteDataHandler	65
7.13.3.20	tblRobotDeleteDataHandler	65
7.13.3.21	tblRobotFetchDataHandler	65
7.13.3.22	tblRobotUpdateDataHandler	65
7.13.3.23	tblRobotWriteDataHandler	65
7.13.3.24	tblUserDeleteDataHandler	66
7.13.3.25	tblUserFetchDataHandler	66
7.13.3.26	tblUsersOntologyInstancesDeleteDataHandler	66
7.13.3.27	tblUsersOntologyInstancesFetchDataHandler	66
7.13.3.28	tblUsersOntologyInstancesUpdateDataHandler	67
7.13.3.29	tblUsersOntologyInstancesWriteDataHandler	68
7.13.3.30	tblUserUpdateDataHandler	68
7.13.3.31	tblUserWriteDataHandler	68
7.13.3.32	updateData	68
7.13.3.33	viewUsersRobotsAppsFetchDataHandler	69
7.13.3.34	whatRappsCanRun	69
7.13.3.35	whatRappsCanRunDataHandler	69
7.13.3.36	writeData	69
7.13.4	Member Data Documentation	69
7.13.4.1	serv	69
7.13.4.2	serv_topic	70
7.14	QrCode Class Reference	70
7.14.1	Detailed Description	70
7.14.2	Member Data Documentation	70
7.14.2.1	center	70
7.14.2.2	message	70
7.15	QrDetection Class Reference	70
7.15.1	Detailed Description	71
7.15.2	Constructor & Destructor Documentation	71
7.15.2.1	QrDetection	71
7.15.3	Member Function Documentation	71
7.15.3.1	qrDetectionCallback	71
7.15.4	Member Data Documentation	72
7.15.4.1	nh_	72
7.15.4.2	qr_detector_	72
7.15.4.3	qrDetectionService_	72
7.15.4.4	qrDetectionTopic_	72

7.16	QrDetector Class Reference	72
7.16.1	Detailed Description	73
7.16.2	Constructor & Destructor Documentation	73
7.16.2.1	QrDetector	73
7.16.3	Member Function Documentation	73
7.16.3.1	detectQrs	73
7.16.3.2	findQrs	73
7.16.3.3	loadImage	73
7.17	rapp_exceptions.RappError Class Reference	74
7.17.1	Detailed Description	75
7.17.2	Constructor & Destructor Documentation	75
7.17.2.1	__init__	75
7.17.2.2	__init__	75
7.17.3	Member Function Documentation	75
7.17.3.1	__str__	75
7.17.3.2	__str__	75
7.17.4	Member Data Documentation	75
7.17.4.1	value	75
7.18	rapp_speech_detection_sphinx4.rapp_exceptions.RappError Class Reference	76
7.18.1	Detailed Description	76
7.18.2	Constructor & Destructor Documentation	77
7.18.2.1	__init__	77
7.18.3	Member Function Documentation	77
7.18.3.1	__str__	77
7.18.4	Member Data Documentation	77
7.18.4.1	value	77
7.19	rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile Class Reference	77
7.19.1	Detailed Description	77
7.19.2	Constructor & Destructor Documentation	78
7.19.2.1	__init__	78
7.19.3	Member Function Documentation	78
7.19.3.1	setNoise_profile	78
7.19.4	Member Data Documentation	78
7.19.4.1	utilities	78
7.20	rapp_audio_processing.rapp_sox_denoise.SoxDenoise Class Reference	78
7.20.1	Detailed Description	78
7.20.2	Member Function Documentation	78
7.20.2.1	soxDenoise	79
7.21	rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4 Class Reference	79

7.21.1	Detailed Description	81
7.21.2	Constructor & Destructor Documentation	81
7.21.2.1	__init__	81
7.21.3	Member Function Documentation	81
7.21.3.1	_configureSpeechRecognition	81
7.21.3.2	_speechRecognition	81
7.21.3.3	speechRecognitionBatch	81
7.21.4	Member Data Documentation	82
7.21.4.1	_authentication_service	82
7.21.4.2	_configuration_params	82
7.21.4.3	_english_support	82
7.21.4.4	_greek_support	82
7.21.4.5	_sphinx4	82
7.21.4.6	_use_db_authentication	83
7.21.4.7	_word_mapping	83
7.22	rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognition-Sphinx4HandlerNode Class Reference	83
7.22.1	Detailed Description	84
7.22.2	Constructor & Destructor Documentation	84
7.22.2.1	__init__	84
7.22.3	Member Function Documentation	84
7.22.3.1	_calculateRequestHash	84
7.22.3.2	handleSpeechRecognitionCallback	84
7.22.4	Member Data Documentation	85
7.22.4.1	_availableProcesses	85
7.22.4.2	_lock	85
7.22.4.3	_speech_recognition_batch_service	85
7.22.4.4	_threadCounter	85
7.22.4.5	_threads	85
7.23	speech_recognition_google.SpeechToTextGoogle Class Reference	85
7.23.1	Detailed Description	86
7.23.2	Constructor & Destructor Documentation	86
7.23.2.1	__init__	86
7.23.3	Member Function Documentation	86
7.23.3.1	speech_to_text	86
7.23.3.2	speech_to_text_callback	86
7.23.4	Member Data Documentation	86
7.23.4.1	serv	86
7.23.4.2	serv_topic	87
7.24	Sphinx4 Class Reference	87

7.24.1	Detailed Description	88
7.24.2	Member Function Documentation	88
7.24.2.1	main	88
7.24.2.2	updateConfiguration	88
7.24.3	Member Data Documentation	88
7.24.3.1	acoustic_model_path	88
7.24.3.2	acoustic_model_path_prev	88
7.24.3.3	bufferRead	88
7.24.3.4	bufferWrite	88
7.24.3.5	cm	88
7.24.3.6	configuration	88
7.24.3.7	configuration_model_path	89
7.24.3.8	configuration_model_path_prev	89
7.24.3.9	dictionary_path	89
7.24.3.10	dictionary_path_prev	89
7.24.3.11	grammar_enabled	89
7.24.3.12	grammar_enabled_prev	89
7.24.3.13	grammar_model_file_path	89
7.24.3.14	grammar_model_file_path_prev	89
7.24.3.15	grammar_model_folder_path	89
7.24.3.16	grammar_model_folder_path_prev	89
7.24.3.17	language_path	89
7.24.3.18	language_path_prev	89
7.24.3.19	recognizer	90
7.25	rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper Class Reference	90
7.25.1	Detailed Description	91
7.25.2	Constructor & Destructor Documentation	92
7.25.2.1	__init__	92
7.25.3	Member Function Documentation	92
7.25.3.1	_callSphinxJava	92
7.25.3.2	_createProcessingProfile	92
7.25.3.3	_createSocket	92
7.25.3.4	_performEnergyDenoising	92
7.25.3.5	_readLine	93
7.25.3.6	_respawnSphinx	93
7.25.3.7	configureSphinx	93
7.25.3.8	initializeSphinx	93
7.25.3.9	performSpeechRecognition	93
7.25.4	Member Data Documentation	94
7.25.4.1	_allow_sphinx_output	94

7.25.4.2	_audio_transform_srv	94
7.25.4.3	_conf	94
7.25.4.4	_denoise_service	94
7.25.4.5	_detect_silence_service	94
7.25.4.6	_energy_denoise_service	94
7.25.4.7	_sphinx_socket	94
7.25.4.8	_sphinx_socket_PORT	95
7.25.4.9	_sphinxDied	95
7.25.4.10	_sphinxSubprocess	95
7.26	rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams Class Reference	95
7.26.1	Detailed Description	96
7.26.2	Constructor & Destructor Documentation	96
7.26.2.1	__init__	96
7.26.3	Member Function Documentation	97
7.26.3.1	equals	97
7.26.4	Member Data Documentation	98
7.26.4.1	_grammar	98
7.26.4.2	_language	98
7.26.4.3	_sentences	98
7.26.4.4	_words	98
7.27	text_to_speech_espeak.TextToSpeechEspeak Class Reference	98
7.27.1	Detailed Description	99
7.27.2	Constructor & Destructor Documentation	99
7.27.2.1	__init__	99
7.27.3	Member Function Documentation	99
7.27.3.1	text_to_speech_callback	99
7.27.4	Member Data Documentation	99
7.27.4.1	serv	99
7.27.4.2	serv_topic	99
7.28	rapp_audio_processing.rapp_transform_audio.TransformAudio Class Reference	99
7.28.1	Detailed Description	100
7.28.2	Member Function Documentation	100
7.28.2.1	_assertArgs	100
7.28.2.2	_convertType	100
7.28.2.3	_validateSourceType	100
7.28.2.4	transform_audio	101
7.29	rapp_audio_processing.rapp_utilities.Utilities Class Reference	101
7.29.1	Detailed Description	101
7.29.2	Member Function Documentation	101

7.29.2.1	cleanup	101
8	File Documentation	103
8.1	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/__init__.py File Reference	103
8.2	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/__init__.py File Reference	103
8.3	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_audio_processing.py File Reference	103
8.4	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_detect_silence.py File Reference	103
8.5	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_energy_denoise.py File Reference	104
8.6	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_set_noise_profile.py File Reference	104
8.7	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_sox_denoise.py File Reference	104
8.8	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_transform_audio.py File Reference	105
8.9	/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_utilities.py File Reference	105
8.10	/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise.py File Reference	105
8.11	/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise_main.py File Reference	105
8.12	/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detection.h File Reference	106
8.13	/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detector.h File Reference	106
8.14	/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection.cpp File Reference	107
8.15	/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection_node.cpp File Reference	108
8.15.1	Function Documentation	108
8.15.1.1	main	108
8.16	/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detector.cpp File Reference	109
8.17	/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_wrapper.h File Reference	109
8.18	/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_wrapper_communications.h File Reference	110
8.19	/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper.cpp File Reference	111
8.19.1	Function Documentation	112
8.19.1.1	checkIfFileExists	112
8.19.1.2	intToString	113
8.19.1.3	split	113
8.19.1.4	SplitFilename	113

8.20	/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_communications.cpp File Reference	114
8.21	/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_node.cpp File Reference	114
8.21.1	Function Documentation	114
8.21.1.1	main	114
8.22	/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper.py File Reference	114
8.23	/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper_main.py File Reference	115
8.24	/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detection.h File Reference	115
8.25	/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detector.h File Reference	116
8.26	/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection.cpp File Reference	117
8.27	/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection_node.cpp File Reference	117
8.27.1	Function Documentation	117
8.27.1.1	main	117
8.28	/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detector.cpp File Reference	118
8.29	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/rapp_exceptions.py File Reference	118
8.30	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_exceptions.py File Reference	118
8.31	/home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/rapp_exceptions.py File Reference	118
8.32	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/speech_recognition_google.py File Reference	119
8.33	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/english_support.py File Reference	119
8.34	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/global_parameters.py File Reference	119
8.35	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/greek_support.py File Reference	120
8.36	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/limited_vocabulary_creator.py File Reference	120
8.37	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_tools.py File Reference	120
8.38	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/speech_recognition_sphinx4.py File Reference	120
8.39	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/speech_recognition_sphinx4_handler_node.py File Reference	121
8.40	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/sphinx4_configuration_params.py File Reference	121
8.41	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/sphinx4_wrapper.py File Reference	121
8.42	/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/Sphinx4.java File Reference	122

8.43 /home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/text_to_speech_espeak.py	
File Reference	122
Index	123

Chapter 1

Todo List

Member [rapp_speech_detection_sphinx4.greek_support.GreekSupport._generic_sphinx_configuration](#)

Fix this according to the generic Greek model

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

cognitive_exercise	11
cognitive_exercise_main	11
mysql_wrapper	11
mysql_wrapper_main	11
rapp_audio_processing	12
rapp_audio_processing.rapp_audio_processing	12
rapp_audio_processing.rapp_detect_silence	12
rapp_audio_processing.rapp_energy_denoise	12
rapp_audio_processing.rapp_set_noise_profile	13
rapp_audio_processing.rapp_sox_denoise	13
rapp_audio_processing.rapp_transform_audio	13
rapp_audio_processing.rapp_utilities	13
rapp_exceptions	13
rapp_speech_detection_sphinx4	13
rapp_speech_detection_sphinx4.english_support	14
rapp_speech_detection_sphinx4.global_parameters	14
rapp_speech_detection_sphinx4.greek_support	14
rapp_speech_detection_sphinx4.limited_vocabulary_creator	14
rapp_speech_detection_sphinx4.rapp_exceptions	14
rapp_speech_detection_sphinx4.rapp_tools	14
rapp_speech_detection_sphinx4.speech_recognition_sphinx4	15
rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node	15
rapp_speech_detection_sphinx4.sphinx4_configuration_params	15
rapp_speech_detection_sphinx4.sphinx4_wrapper	16
speech_recognition_google	16
text_to_speech_espeak	16

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

rapp_audio_processing.rapp_audio_processing.AudioProcessing	17
cognitive_exercise.CognitiveExercise	20
rapp_audio_processing.rapp_detect_silence.DetectSilence	22
rapp_audio_processing.rapp_energy_denoise.EnergyDenoise	22
Exception	
rapp_exceptions.RappError	74
rapp_exceptions.RappError	74
rapp_speech_detection_sphinx4.rapp_exceptions.RappError	76
FaceDetection	26
FaceDetector	28
rapp_speech_detection_sphinx4.global_parameters.GlobalParams	30
KnowrobWrapper	37
KnowrobWrapperCommunications	45
mysql_wrapper.MySQLdbWrapper	57
QRcode	70
QRDetection	70
QRDetector	72
rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile	77
rapp_audio_processing.rapp_sox_denoise.SoxDenoise	78
rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognition- Sphinx4HandlerNode	83
speech_recognition_google.SpeechToTextGoogle	85
Sphinx4	87
text_to_speech_espeak.TextToSpeechEspeak	98
rapp_audio_processing.rapp_transform_audio.TransformAudio	99
rapp_audio_processing.rapp_utilities.Utilities	101
GlobalParams	
rapp_speech_detection_sphinx4.english_support.EnglishSupport	23
rapp_speech_detection_sphinx4.greek_support.GreekSupport	32
rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator	55
rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4	79
rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams	95
rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper	90

Chapter 4

Class Index

4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

rapp_audio_processing.rapp_audio_processing.AudioProcessing	
Provides audio processing utilities	17
cognitive_exercise.CognitiveExercise	
The Cognitive exercise ros node	20
rapp_audio_processing.rapp_detect_silence.DetectSilence	
Performs silence detection on an audio file	22
rapp_audio_processing.rapp_energy_denoise.EnergyDenoise	
Performs energy denoising on an audio file	22
rapp_speech_detection_sphinx4.english_support.EnglishSupport	
Allows the creation of configuration files for English Sphinx speech recognition	23
FaceDetection	
Class FaceDetection uptakes the task of handling the ROS service callbacks	26
FaceDetector	
Class that implements a face detection algorithm based on a Haar cascade classifier	28
rapp_speech_detection_sphinx4.global_parameters.GlobalParams	
Contains global Sphinx parameters	30
rapp_speech_detection_sphinx4.greek_support.GreekSupport	
Allows the creation of configuration files for Greek Sphinx speech recognition	32
KnowrobWrapper	
Class KnowrobWrapperCommunications contains all the necessary knowrob wrapper functions	37
KnowrobWrapperCommunications	
Class KnowrobWrapperCommunications uptakes the task of handling the ROS service callbacks	45
rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator	
Creates temporary configuration files for the input limited vocabulary	55
mysql_wrapper.MySQLdbWrapper	
The mysql wrapper ros node	57
QRCode	
Structure holding the essential info for a QR code	70
QRDetection	
Uptakes the task of setting up the ROS service callbacks towards qr detection	70
QRDetector	
Provides the QR detection functionality	72
rapp_exceptions.RappError	
Inherits Exception and is used to catch only RAPP-specific exceptions	74
rapp_speech_detection_sphinx4.rapp_exceptions.RappError	
Provides a RAPP specific exception	76
rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile	
Evaluates the noise profile for an audio file	77

rapp_audio_processing.rapp_sox_denoise.SoxDenoise	
Performs denoising on an audio file employing Sox application	78
rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4	
Provides a complete Rapp Sphinx Entity	79
rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognition-Sphinx4HandlerNode	
Maintains Sphinx instances to perform speech recognition	83
speech_recognition_google.SpeechToTextGoogle	
Implements calls the Google ASR API	85
Sphinx4	
Performs speech recognition employing Sphinx	87
rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper	
Contains the Sphinx subprocess and is responsible for configuring Sphinx and performing the recognition request	90
rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams	
Contains the parameters required for the Sphinx configuration	95
text_to_speech_espeak.TextToSpeechEspeak	
Provides audio type tranformation functionalities	98
rapp_audio_processing.rapp_transform_audio.TransformAudio	
Provides audio type tranformation functionalities	99
rapp_audio_processing.rapp_utilities.Utilities	
Provides audio processing utilities	101

Chapter 5

File Index

5.1 File List

Here is a list of all files with brief descriptions:

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/___init___py . . .	103
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_audio_- processing.py	103
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_detect_- silence.py	103
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_energy_- denoise.py	104
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_set_- noise_profile.py	104
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_sox_- denoise.py	104
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_transform- _audio.py	105
/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_utilities_- py	105
/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise.py	105
/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise_main.py	105
/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detection.h . . .	106
/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detector.h . . .	106
/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection.cpp	107
/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection_node.cpp	108
/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detector.cpp	109
/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_- wrapper.h	109
/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_- wrapper_communications.h	110
/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper.cpp	111
/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_communications_- cpp	114
/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_node.cpp	114
/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper.py	114
/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper_main.py	115
/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detection.h	115
/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detector.h	116
/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection.cpp	117
/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection_node.cpp	117
/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detector.cpp	118
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/rapp_exceptions.py	118

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/ speech_recognition_google.py	119
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/ Sphinx4.java	122
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ __init__.py	103
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ english_support.py	119
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ global_parameters.py	119
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ greek_support.py	120
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ limited_vocabulary_creator.py	120
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ rapp_exceptions.py	118
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ rapp_tools.py	120
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ speech_recognition_sphinx4.py	120
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ speech_recognition_sphinx4_handler_node.py	121
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ sphinx4_configuration_params.py	121
/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/ sphinx4_wrapper.py	121
/home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/ rapp_exceptions.py	118
/home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/ text_to_speech_espeak.py	122

Chapter 6

Namespace Documentation

6.1 cognitive_exercise Namespace Reference

Classes

- class [CognitiveExercise](#)
The Cognitive exercise ros node.

6.2 cognitive_exercise_main Namespace Reference

Variables

- tuple [CognitiveExerciseNode](#) = [CognitiveExercise\(\)](#)
The main function that initiates the CognitiveExercise ROS Node.

6.2.1 Variable Documentation

6.2.1.1 tuple cognitive_exercise_main.CognitiveExerciseNode = CognitiveExercise()

The main function that initiates the CognitiveExercise ROS Node.

Definition at line 27 of file cognitive_exercise_main.py.

6.3 mysql_wrapper Namespace Reference

Classes

- class [MySQLdbWrapper](#)
The mysql wrapper ros node.

6.4 mysql_wrapper_main Namespace Reference

Variables

- tuple [MySQLWrapperNode](#) = [MySQLdbWrapper\(\)](#)
The main function that initiates the rapp mysql wrapper ROS Node.

6.4.1 Variable Documentation

6.4.1.1 tuple mysql_wrapper_main.MySQLWrapperNode = MySQLdbWrapper()

The main function that initiates the rapp mysql wrapper ROS Node.

Definition at line 26 of file mysql_wrapper_main.py.

6.5 rapp_audio_processing Namespace Reference

Namespaces

- [rapp_audio_processing](#)
- [rapp_detect_silence](#)
- [rapp_energy_denoise](#)
- [rapp_set_noise_profile](#)
- [rapp_sox_denoise](#)
- [rapp_transform_audio](#)
- [rapp_utilities](#)

6.6 rapp_audio_processing.rapp_audio_processing Namespace Reference

Classes

- class [AudioProcessing](#)
Provides audio processing utilities.

Variables

- tuple [AudioProcessingNode](#) = [AudioProcessing](#)()

6.6.1 Variable Documentation

6.6.1.1 tuple rapp_audio_processing.rapp_audio_processing.AudioProcessingNode = AudioProcessing()

Definition at line 236 of file rapp_audio_processing.py.

6.7 rapp_audio_processing.rapp_detect_silence Namespace Reference

Classes

- class [DetectSilence](#)
Performs silence detection on an audio file.

6.8 rapp_audio_processing.rapp_energy_denoise Namespace Reference

Classes

- class [EnergyDenoise](#)
Performs energy denoising on an audio file.

6.9 rapp_audio_processing.rapp_set_noise_profile Namespace Reference

Classes

- class [SetNoiseProfile](#)
Evaluates the noise profile for an audio file.

6.10 rapp_audio_processing.rapp_sox_denoise Namespace Reference

Classes

- class [SoxDenoise](#)
Performs denoising on an audio file employing Sox application.

6.11 rapp_audio_processing.rapp_transform_audio Namespace Reference

Classes

- class [TransformAudio](#)
Provides audio type tranformation functionalities.

6.12 rapp_audio_processing.rapp_utilities Namespace Reference

Classes

- class [Utilities](#)
Provides audio processing utilities.

6.13 rapp_exceptions Namespace Reference

Classes

- class [RappError](#)
Inherits Exception and is used to catch only RAPP-specific exceptions.

6.14 rapp_speech_detection_sphinx4 Namespace Reference

Namespaces

- [english_support](#)
- [global_parameters](#)
- [greek_support](#)
- [limited_vocabulary_creator](#)
- [rapp_exceptions](#)
- [rapp_tools](#)
- [speech_recognition_sphinx4](#)
- [speech_recognition_sphinx4_handler_node](#)
- [sphinx4_configuration_params](#)
- [sphinx4_wrapper](#)

6.15 rapp_speech_detection_sphinx4.english_support Namespace Reference

Classes

- class [EnglishSupport](#)
Allows the creation of configuration files for English Sphinx speech recognition.

6.16 rapp_speech_detection_sphinx4.global_parameters Namespace Reference

Classes

- class [GlobalParams](#)
Contains global Sphinx parameters.

6.17 rapp_speech_detection_sphinx4.greek_support Namespace Reference

Classes

- class [GreekSupport](#)
Allows the creation of configuration files for Greek Sphinx speech recognition.

6.18 rapp_speech_detection_sphinx4.limited_vocabulary_creator Namespace Reference

Classes

- class [LimitedVocabularyCreator](#)
Creates temporary configuration files for the input limited vocabulary.

6.19 rapp_speech_detection_sphinx4.rapp_exceptions Namespace Reference

Classes

- class [RappError](#)
Provides a RAPP specific exception.

6.20 rapp_speech_detection_sphinx4.rapp_tools Namespace Reference

Functions

- def [rapp_print](#)

6.20.1 Function Documentation

6.20.1.1 def rapp_speech_detection_sphinx4.rapp_tools.rapp_print (var)

Definition at line 21 of file rapp_tools.py.

6.21 rapp_speech_detection_sphinx4.speech_recognition_sphinx4 Namespace Reference

Classes

- class [SpeechRecognitionSphinx4](#)
Provides a complete Rapp Sphinx Entity.

Variables

- tuple [SpeechRecognitionSphinx4Node](#) = [SpeechRecognitionSphinx4\(\)](#)

6.21.1 Variable Documentation

- 6.21.1.1 tuple rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4Node = [SpeechRecognitionSphinx4\(\)](#)

Definition at line 283 of file speech_recognition_sphinx4.py.

6.22 rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node Namespace Reference

Classes

- class [SpeechRecognitionSphinx4HandlerNode](#)
Maintains Sphinx instances to perform speech recognition.

Variables

- tuple [SpeechRecognitionSphinx4HandlerNode](#) = [SpeechRecognitionSphinx4HandlerNode\(\)](#)

6.22.1 Variable Documentation

- 6.22.1.1 tuple rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode = [SpeechRecognitionSphinx4HandlerNode\(\)](#)

Definition at line 149 of file speech_recognition_sphinx4_handler_node.py.

6.23 rapp_speech_detection_sphinx4.sphinx4_configuration_params Namespace Reference

Classes

- class [SphinxConfigurationParams](#)
Contains the parameters required for the Sphinx configuration.

6.24 rapp_speech_detection_sphinx4.sphinx4_wrapper Namespace Reference

Classes

- class [Sphinx4Wrapper](#)

Contains the Sphinx subprocess and is responsible for configuring Sphinx and performing the recognition request.

6.25 speech_recognition_google Namespace Reference

Classes

- class [SpeechToTextGoogle](#)

Implements calls the Google ASR API.

Variables

- tuple [speech_to_text_node](#) = [SpeechToTextGoogle\(\)](#)

The main function.

6.25.1 Variable Documentation

6.25.1.1 tuple `speech_recognition_google.speech_to_text_node = SpeechToTextGoogle()`

The main function.

Creates a [SpeechToTextGoogle](#) object

Definition at line 285 of file `speech_recognition_google.py`.

6.26 text_to_speech_espeak Namespace Reference

Classes

- class [TextToSpeechEspeak](#)

Variables

- tuple [text_to_speech_espeak_ros_node](#) = [TextToSpeechEspeak\(\)](#)

6.26.1 Variable Documentation

6.26.1.1 tuple `text_to_speech_espeak.text_to_speech_espeak_ros_node = TextToSpeechEspeak()`

Definition at line 81 of file `text_to_speech_espeak.py`.

Chapter 7

Class Documentation

7.1 rapp_audio_processing.rapp_audio_processing.AudioProcessing Class Reference

Provides audio processing utilities.

Public Member Functions

- def [__init__](#)
Constructor performing initializations.
- def [denoiseCallback](#)
Service callback for denoising.
- def [detectSilenceCallback](#)
Service callback for Detecting silence.
- def [energyDenoiseCallback](#)
Service callback for Energy denoising.
- def [setNoiseProfileCallback](#)
Service callback for setting noise profile.
- def [transformAudioCallback](#)
Service callback for Audio transformation.

Private Attributes

- [_detect_silence_module](#)
Instantiates [rapp_detect_silence.DetectSilence](#).
- [_energy_denoise_module](#)
Instantiates [rapp_energy_denoise.EnergyDenoise](#).
- [_energy_denoising_debug](#)
Energy denoising debug flag.
- [_set_noise_profile_module](#)
Instantiates [rapp_set_noise_profile.SetNoiseProfile](#).
- [_sox_denoise_module](#)
Instantiates [rapp_sox_denoise.SoxDenoise](#).
- [_transform_audio_module](#)
Instantiates [rapp_transform_audio.TransformAudio](#).
- [_utilities_module](#)
Instantiates [rapp_utilities.Utilities](#).

7.1.1 Detailed Description

Provides audio processing utilities.

Implements service servers to perform denoising, audio transformation etc.

Definition at line 66 of file rapp_audio_processing.py.

7.1.2 Constructor & Destructor Documentation

7.1.2.1 `def rapp_audio_processing.rapp_audio_processing.AudioProcessing.__init__(self)`

Constructor performing initializations.

Definition at line 69 of file rapp_audio_processing.py.

7.1.3 Member Function Documentation

7.1.3.1 `def rapp_audio_processing.rapp_audio_processing.AudioProcessing.denoiseCallback(self, req)`

Service callback for denoising.

Parameters

<i>req</i>	[rapp_platform_ros_communications::AudioProcessing::AudioProcessingDenoiseSrv] The denoise request
------------	--

Returns

res [rapp_platform_ros_communications::AudioProcessing::AudioProcessingDenoiseSrvResponse] The denoise response

Definition at line 177 of file rapp_audio_processing.py.

7.1.3.2 `def rapp_audio_processing.rapp_audio_processing.AudioProcessing.detectSilenceCallback(self, req)`

Service callback for Detecting silence.

Parameters

<i>req</i>	[rapp_platform_ros_communications::AudioProcessing::AudioProcessingDetectSilence] The detect silence request
------------	--

Returns

res [rapp_platform_ros_communications::AudioProcessing::AudioProcessingDetectSilenceSrvResponse] The detect silence response

Definition at line 192 of file rapp_audio_processing.py.

7.1.3.3 `def rapp_audio_processing.rapp_audio_processing.AudioProcessing.energyDenoiseCallback(self, req)`

Service callback for Energy denoising.

Parameters

<i>req</i>	[rapp_platform_ros_communications::AudioProcessing::AudioProcessingDenoiseSrv] The denoise request
------------	---

Returns

res [rapp_platform_ros_communications::AudioProcessing::AudioProcessingDenoiseSrvResponse] The energy denoise response

Definition at line 207 of file rapp_audio_processing.py.

7.1.3.4 def rapp_audio_processing.rapp_audio_processing.AudioProcessing.setNoiseProfileCallback (self, req)

Service callback for setting noise profile.

Parameters

<i>req</i>	[rapp_platform_ros_communications::AudioProcessing::AudioProcessingSetNoiseProfileSrv] The set noise profile request
------------	---

Returns

res [rapp_platform_ros_communications::AudioProcessing::AudioProcessingSetNoiseProfileSrvResponse]
The set noise profile response

Definition at line 142 of file rapp_audio_processing.py.

7.1.3.5 def rapp_audio_processing.rapp_audio_processing.AudioProcessing.transformAudioCallback (self, req)

Service callback for Audio transformation.

Parameters

<i>req</i>	[rapp_platform_ros_communications::AudioProcessing::AudioProcessingTransformAudioSrv] The transform audio request
------------	--

Returns

res [rapp_platform_ros_communications::AudioProcessing::AudioProcessingTransformAudioSrvResponse]
The transform audio response

Definition at line 223 of file rapp_audio_processing.py.

7.1.4 Member Data Documentation

7.1.4.1 rapp_audio_processing.rapp_audio_processing.AudioProcessing._detect_silence_module [private]

Instantiates [rapp_detect_silence.DetectSilence](#).

Definition at line 72 of file rapp_audio_processing.py.

7.1.4.2 rapp_audio_processing.rapp_audio_processing.AudioProcessing._energy_denoise_module [private]

Instantiates [rapp_energy_denoise.EnergyDenoise](#).

Definition at line 74 of file rapp_audio_processing.py.

7.1.4.3 `rapp_audio_processing.rapp_audio_processing.AudioProcessing._energy_denoising_debug` [private]

Energy denoising debug flag.

Definition at line 109 of file `rapp_audio_processing.py`.

7.1.4.4 `rapp_audio_processing.rapp_audio_processing.AudioProcessing._set_noise_profile_module` [private]

Instantiates `rapp_set_noise_profile.SetNoiseProfile`.

Definition at line 80 of file `rapp_audio_processing.py`.

7.1.4.5 `rapp_audio_processing.rapp_audio_processing.AudioProcessing._sox_denoise_module` [private]

Instantiates `rapp_sox_denoise.SoxDenoise`.

Definition at line 76 of file `rapp_audio_processing.py`.

7.1.4.6 `rapp_audio_processing.rapp_audio_processing.AudioProcessing._transform_audio_module` [private]

Instantiates `rapp_transform_audio.TransformAudio`.

Definition at line 82 of file `rapp_audio_processing.py`.

7.1.4.7 `rapp_audio_processing.rapp_audio_processing.AudioProcessing._utilities_module` [private]

Instantiates `rapp_utilities.Utilities`.

Definition at line 78 of file `rapp_audio_processing.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_audio_processing.py`

7.2 `cognitive_exercise.CognitiveExercise` Class Reference

The Cognitive exercise ros node.

Public Member Functions

- `def __init__`
Default constructor.
- `def chooserDataHandler`
The cognitive exercise chooser service callback.
- `def cognitiveTestCreatorDataHandler`
The cognitive test creator service callback.
- `def recordUserCognitiveTestPerformanceDataHandler`
The record user cognitive test performance service callback.

Public Attributes

- `serv`
- `serv_topic`

7.2.1 Detailed Description

The Cognitive exercise ros node.

Definition at line 57 of file cognitive_exercise.py.

7.2.2 Constructor & Destructor Documentation

7.2.2.1 def cognitive_exercise.CognitiveExercise.__init__(self)

Default contructor.

Waits for services the node depends on and declares the callbacks of the node's services

Definition at line 62 of file cognitive_exercise.py.

7.2.3 Member Function Documentation

7.2.3.1 def cognitive_exercise.CognitiveExercise.chooserDataHandler (self, req)

The cognitive exercise chooser service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::testSelectorSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::testSelectorSrvResponse::Response&] The ROS service response

Definition at line 114 of file cognitive_exercise.py.

7.2.3.2 def cognitive_exercise.CognitiveExercise.cognitiveTestCreatorDataHandler (self, req)

The cognitive test creator service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::cognitiveTestCreatorSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::cognitiveTestCreatorSrvResponse::Response&] The ROS service response

Definition at line 131 of file cognitive_exercise.py.

7.2.3.3 def cognitive_exercise.CognitiveExercise.recordUserCognitiveTestPerformanceDataHandler (self, req)

The record user cognitive test performance service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::recordUserCognitiveTestPerformanceSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::recordUserCognitiveTestPerformanceSrvResponse::Response&] The ROS service response

Definition at line 123 of file cognitive_exercise.py.

7.2.4 Member Data Documentation

7.2.4.1 `cognitive_exercise.CognitiveExercise.serv`

Definition at line 99 of file `cognitive_exercise.py`.

7.2.4.2 `cognitive_exercise.CognitiveExercise.serv_topic`

Definition at line 65 of file `cognitive_exercise.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise.py`

7.3 `rapp_audio_processing.rapp_detect_silence.DetectSilence` Class Reference

Performs silence detection on an audio file.

Public Member Functions

- def `detectSilence`
Detects silence.

7.3.1 Detailed Description

Performs silence detection on an audio file.

Definition at line 29 of file `rapp_detect_silence.py`.

7.3.2 Member Function Documentation

7.3.2.1 `def rapp_audio_processing.rapp_detect_silence.DetectSilence.detectSilence (self, audio_file, threshold)`

Detects silence.

Handles service callback `rapp_audio_processing.AudioProcessing::detectSilenceCallback`

Parameters

<i>audio_file</i>	[string] Audio file path
<i>threshold</i>	[float] Silence threshold

Returns

`rsd_sq` [float] Noise relative standard deviation
`has_silence` [bool] Indicates the existence of silence

Definition at line 41 of file `rapp_detect_silence.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_detect_silence.py`

7.4 `rapp_audio_processing.rapp_energy_denoise.EnergyDenoise` Class Reference

Performs energy denoising on an audio file.

Public Member Functions

- def [energyDenoise](#)
Performs energy-based denoising.

7.4.1 Detailed Description

Performs energy denoising on an audio file.

Definition at line 29 of file rapp_energy_denoise.py.

7.4.2 Member Function Documentation

7.4.2.1 `def rapp_audio_processing.rapp_energy_denoise.EnergyDenoise.energyDenoise (self, audio_file, scale, denoised_audio_file, energy_denoising_debug)`

Performs energy-based denoising.

Handles service callback [rapp_audio_processing.AudioProcessing::energyDenoiseCallback](#)

Parameters

<i>audio_file</i>	[string] Audio file path
<i>scale</i>	[float] Energy denoise scale
<i>denoised_audio-_file</i>	[string] Path to write denoised audio file

Definition at line 39 of file rapp_energy_denoise.py.


The documentation for this class was generated from the following file:

- /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/[rapp_energy_denoise.py](#)


7.5 rapp_speech_detection_sphinx4.english_support.EnglishSupport Class Reference

Allows the creation of configuration files for English Sphinx speech recognition.

Inheritance diagram for rapp_speech_detection_sphinx4.english_support.EnglishSupport:



Collaboration diagram for `rapp_speech_detection_sphinx4.english_support.EnglishSupport`:



Public Member Functions

- `def __init__`
Performs initializations.
- `def getGenericConfiguration`
Returns the Generic English Configuration.
- `def getLimitedVocebularyConfiguration`
Computes the Limited English Configuration.
- `def getWordPhonemes`
Compute the English word phonemes.

Private Attributes

- `_english_dict_file`
The English dictionary file.
- `_english_dict_mapping`
The mmap of the English dictionary file contents.
- `_generic_sphinx_configuration`
The generic Sphinx configuration.
- `_vocabulary`
The limited vocabulary creator.

7.5.1 Detailed Description

Allows the creation of configuration files for English Sphinx speech recognition.

Definition at line 32 of file `english_support.py`.

7.5.2 Constructor & Destructor Documentation

7.5.2.1 `def rapp_speech_detection_sphinx4.english_support.EnglishSupport.__init__(self)`

Performs initializations.

Definition at line 35 of file `english_support.py`.

7.5.3 Member Function Documentation

7.5.3.1 `def rapp_speech_detection_sphinx4.english_support.EnglishSupport.getGenericConfiguration (self)`

Returns the Generic English Configuration.

Returns

[_generic_sphinx_configuration](#) [dictionary] The Generic English configuration

Definition at line 149 of file english_support.py.

7.5.3.2 `def rapp_speech_detection_sphinx4.english_support.EnglishSupport.getLimitedVocebularyConfiguration (self, words, grammar, sentences)`

Computes the Limited English Configuration.

Parameters

<i>words</i>	[list::string] The set of words to be identified
<i>grammar</i>	[list::string] The Sphinx grammar parameter
<i>sentences</i>	[list::string] The Sphinx sentences parameter

Returns

`limited_sphinx_configuration` [dictionary] The Limited English configuration

Definition at line 133 of file english_support.py.

7.5.3.3 `def rapp_speech_detection_sphinx4.english_support.EnglishSupport.getWordPhonemes (self, words)`

Compute the English word phonemes.

Parameters

<i>words</i>	[list::string] The set of English words
--------------	---

Returns

`enhanced_words` [dictionary] The English word->phonemes mapping

Definition at line 89 of file english_support.py.

7.5.4 Member Data Documentation

7.5.4.1 `rapp_speech_detection_sphinx4.english_support.EnglishSupport._english_dict_file` [private]

The English dictionary file.

Located in path [global_parameters.GlobalParams::_language_models_url](#) + "/englishPack/cmudict-en-us.dict"

Definition at line 72 of file english_support.py.

7.5.4.2 `rapp_speech_detection_sphinx4.english_support.EnglishSupport._english_dict_mapping` [private]

The mmap of the English dictionary file contents.

Definition at line 74 of file english_support.py.

7.5.4.3 `rapp_speech_detection_sphinx4.english_support.EnglishSupport.generic_sphinx_configuration` [private]

The generic Sphinx configuration.

Note

Check acoustic model!!

Definition at line 57 of file `english_support.py`.

7.5.4.4 `rapp_speech_detection_sphinx4.english_support.EnglishSupport.vocabulary` [private]

The limited vocabulary creator.

Instantiates [limited_vocabulary_creator.LimitedVocabularyCreator](#)

Definition at line 41 of file `english_support.py`.

The documentation for this class was generated from the following file:


- `/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/`[english_support.py](#)

7.6 FaceDetection Class Reference

Class [FaceDetection](#) uptakes the task of handling the ROS service callbacks.

```
#include <face_detection.h>
```

Collaboration diagram for FaceDetection:



Public Member Functions

- [FaceDetection](#) (void)
Default constructor.
- bool [faceDetectionCallback](#) (`rapp_platform_ros_communications::FaceDetectionRosSrv::Request &req`, `rapp_platform_ros_communications::FaceDetectionRosSrv::Response &res`)
Serves the face detection ROS service callback.

Private Attributes

- [FaceDetector](#) `face_detector_`
- `ros::ServiceServer` `faceDetectionService_`
- `std::string` `faceDetectionTopic_`
- `ros::NodeHandle` `nh_`

7.6.1 Detailed Description

Class [FaceDetection](#) uptakes the task of handling the ROS service callbacks.

Definition at line 31 of file `face_detection.h`.

7.6.2 Constructor & Destructor Documentation

7.6.2.1 `FaceDetection::FaceDetection (void)`

Default constructor.

Default constructor. Performs initializations.

Definition at line 24 of file `face_detection.cpp`.

7.6.3 Member Function Documentation

7.6.3.1 `bool FaceDetection::faceDetectionCallback (rapp_platform_ros_communications::FaceDetectionRosSrv::Request & req, rapp_platform_ros_communications::FaceDetectionRosSrv::Response & res)`

Serves the face detection ROS service callback.

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::FaceDetectionRosSrv::Request&</code>] The ROS service request
<i>res</i>	[<code>rapp_platform_ros_communications::FaceDetectionRosSrv::Response&</code>] The ROS service response

Returns

`bool` - The success status of the call

Definition at line 42 of file `face_detection.cpp`.

7.6.4 Member Data Documentation

7.6.4.1 `FaceDetector FaceDetection::face_detector_ [private]`

Definition at line 62 of file `face_detection.h`.

7.6.4.2 `ros::ServiceServer FaceDetection::faceDetectionService_ [private]`

Member variable holding the face detection ROS service topic

Definition at line 56 of file `face_detection.h`.

7.6.4.3 `std::string FaceDetection::faceDetectionTopic_` [private]

Object of type [FaceDetector](#)

Definition at line 59 of file `face_detection.h`.

7.6.4.4 `ros::NodeHandle FaceDetection::nh_` [private]

< The ROS node handle The face detection service server

Definition at line 53 of file `face_detection.h`.

The documentation for this class was generated from the following files:

- `/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detection.h`
- `/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection.cpp`

7.7 FaceDetector Class Reference

Class that implements a face detection algorithm based on a Haar cascade classifier.

```
#include <face_detector.h>
```

Public Member Functions

- [FaceDetector](#) (void)
Default constructor.
- `std::vector< cv::Rect > detectFaces` (const `cv::Mat` &input_img)
Detects faces from a cv::Mat.
- `std::vector< cv::Rect > findFaces` (std::string file_name)
Finds faces in an image retrieved from a file URL.
- `cv::Mat loadImage` (std::string file_name)
Loads an image from a file URL.

Private Member Functions

- `std::vector< cv::Rect > detectFaces` (const `cv::Mat` &input_img, const std::string &haar_path)
Detects faces from a cv::Mat.
- `std::vector< cv::Rect > identifyUniqueFaces` (const std::vector< cv::Rect > firstFaceVector, const std::vector< cv::Rect > secondFaceVector)
Identify unique faces from two sets of faces.

7.7.1 Detailed Description

Class that implements a face detection algorithm based on a Haar cascade classifier.

Definition at line 33 of file `face_detector.h`.

7.7.2 Constructor & Destructor Documentation

7.7.2.1 `FaceDetector::FaceDetector (void)`

Default constructor.

Definition at line 26 of file `face_detector.cpp`.

7.7.3 Member Function Documentation

7.7.3.1 `std::vector< cv::Rect > FaceDetector::detectFaces (const cv::Mat & input_img)`

Detects faces from a `cv::Mat`.

Parameters

<i>input_img</i>	[const cv::Mat&] The input image
------------------	----------------------------------

Returns

[std::vector<cv::Rect>] A vector containing the detected faces. Each face is represented by a rectangle.

Definition at line 49 of file `face_detector.cpp`.

7.7.3.2 `std::vector< cv::Rect > FaceDetector::detectFaces (const cv::Mat & input_img, const std::string & haar_path)` [private]

Detects faces from a `cv::Mat`.

Parameters

<i>input_img</i>	[const cv::Mat&] The input image
<i>haar_path</i>	[const std::string] The Haar training model path

Returns

[std::vector<cv::Rect>] A vector containing the detected faces. Each face is represented by a rectangle.

Definition at line 82 of file `face_detector.cpp`.

7.7.3.3 `std::vector< cv::Rect > FaceDetector::findFaces (std::string file_name)`

Finds faces in an image retrieved from a file URL.

Parameters

<i>file_name</i>	[std::string] The image file's URL
------------------	------------------------------------

Returns

[std::vector<cv::Rect>] A vector containing the detected faces. Each face is represented by a rectangle.

Definition at line 160 of file `face_detector.cpp`.

7.7.3.4 `std::vector< cv::Rect > FaceDetector::identifyUniqueFaces (const std::vector< cv::Rect > firstFaceVector, const std::vector< cv::Rect > secondFaceVector)` [private]

Identify unique faces from two sets of faces.

Parameters

<i>frontFaceVector</i>	[const std::vector<cv::Rect>&] The first set of faces
------------------------	---

<i>secondFace-Vector</i>	[const std::vector<cv::Rect>&] The second set of faces
--------------------------	--

Returns

[std::vector<cv::Rect>] A vector containing the unique faces. Each face is represented by a rectangle.

Definition at line 133 of file face_detector.cpp.

7.7.3.5 cv::Mat FaceDetector::loadImage (std::string file_name)

Loads an image from a file URL.

Parameters

<i>file_name</i>	[std::string] The image's file URL
------------------	------------------------------------

Returns

[cv::Mat] The image in OpenCV representation

Definition at line 35 of file face_detector.cpp.

The documentation for this class was generated from the following files:

- /home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/[face_detector.h](#)
- /home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/[face_detector.cpp](#)

7.8 rapp_speech_detection_sphinx4.global_parameters.GlobalParams Class Reference

Contains global Sphinx parameters.

Public Member Functions

- [def __init__](#)

Public Attributes

- [rospack](#)

Private Attributes

- [_acoustic_models_url](#)
Acoustic models path.
- [_allow_sphinx_output](#)
True if Sphinx is allowed output on STDIN, STDERR.
- [_language_models_url](#)
Language models path.
- [_noise_profiles_url](#)
Noise profiles path.
- [_socket_host](#)
IPC socket HOST parameter.

- [_sphinx_jar_file](#)
Sphinx jar file path.
- [_sphinx_jar_files_url](#)
Java libraries path.
- [_sphinx_package_url](#)
Sphinx package path.
- [_tmp_language_models_url](#)
Temporary language models path.

7.8.1 Detailed Description

Contains global Sphinx parameters.

Definition at line 22 of file global_parameters.py.

7.8.2 Constructor & Destructor Documentation

7.8.2.1 `def rapp_speech_detection_sphinx4.global_parameters.GlobalParams.__init__(self)`

Definition at line 23 of file global_parameters.py.

7.8.3 Member Data Documentation

7.8.3.1 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._acoustic_models_url` [private]

Acoustic models path.

Definition at line 38 of file global_parameters.py.

7.8.3.2 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._allow_sphinx_output` [private]

True if Sphinx is allowed output on STDIN, STDERR.

Definition at line 43 of file global_parameters.py.

7.8.3.3 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._language_models_url` [private]

Language models path.

Definition at line 31 of file global_parameters.py.

7.8.3.4 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._noise_profiles_url` [private]

Noise profiles path.

Definition at line 36 of file global_parameters.py.

7.8.3.5 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._socket_host` [private]

IPC socket HOST parameter.

Definition at line 45 of file global_parameters.py.

7.8.3.6 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._sphinx_jar_file` `[private]`

Sphinx jar file path.

Definition at line 41 of file `global_parameters.py`.

7.8.3.7 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._sphinx_jar_files_url` `[private]`

Java libraries path.

Definition at line 27 of file `global_parameters.py`.

7.8.3.8 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._sphinx_package_url` `[private]`

Sphinx package path.

Definition at line 29 of file `global_parameters.py`.

7.8.3.9 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams._tmp_language_models_url` `[private]`

Temporary language models path.

Definition at line 33 of file `global_parameters.py`.

7.8.3.10 `rapp_speech_detection_sphinx4.global_parameters.GlobalParams.rospack`

Definition at line 24 of file `global_parameters.py`.


The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/global_parameters.py`


7.9 `rapp_speech_detection_sphinx4.greek_support.GreekSupport` Class Reference

Allows the creation of configuration files for Greek Sphinx speech recognition.

Inheritance diagram for `rapp_speech_detection_sphinx4.greek_support.GreekSupport`:



Collaboration diagram for rapp_speech_detection_sphinx4.greek_support.GreekSupport:



Public Member Functions

- def [__init__](#)
Performs initializations.
- def [getGenericConfiguration](#)
Returns the Generic Greek Configuration.
- def [getLimitedVocebularyConfiguration](#)
Computes the Limited Greek Configuration.

Private Member Functions

- def [_configureLetters](#)
Creates the basic Greek letter to English configuration.
- def [_englify_words](#)
Englify Greek words.
- def [_separateEngGrWords](#)
Separates English from Greek words.
- def [_transformWords](#)
Transforms the Greek words into phonemes for the Sphinx configuration.

Private Attributes

- [_all_special_two_digit_letters](#)
All special two digit Greek letter->English phonemes mapping.
- [_capital_letters](#)
Greek uppercase to lowercase mapping.
- [_english_support](#)
Allows the creation of configuration files for English words.
- [_generic_sphinx_configuration](#)
The generic Sphinx configuration.
- [_letters](#)
Standard Greek letter->English phonemes mapping.
- [_literal_letters](#)

- [_phonemes](#)
Greek letters->English letters mapping.
- [_s_specific_rules](#)
Greek words->English standard phonemes mapping.
- [_special_two_digit_letters](#)
Special Greek words ->English phonemes mapping.
- [_two_digit_letters](#)
Special two digit Greek letter->English phonemes mapping.
- [_vocabulary](#)
Two digit Greek letters->English phonemes mapping.
- [_vocabulary](#)
The limited vocabulary creator.

7.9.1 Detailed Description

Allows the creation of configuration files for Greek Sphinx speech recognition.

Also supports multilanguage words (English/Greek) by utilizing [english_support.EnglishSupport](#)

Definition at line 38 of file greek_support.py.

7.9.2 Constructor & Destructor Documentation

7.9.2.1 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport.__init__(self)`

Performs initializations.

Definition at line 41 of file greek_support.py.

7.9.3 Member Function Documentation

7.9.3.1 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport._configureLetters(self)` [private]

Creates the basic Greek letter to English configuration.

Definition at line 107 of file greek_support.py.

7.9.3.2 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport._englify_words(self, words)` [private]

Englify Greek words.

Parameters

<i>words</i>	[list::string] The set of Greek words
--------------	---------------------------------------

Definition at line 346 of file greek_support.py.

7.9.3.3 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport._separateEngGrWords(self, words, grammar, sentences)` [private]

Separates English from Greek words.

Parameters

<i>words</i>	[list::string] The set of words to be identified
<i>grammar</i>	[list::string] The Sphinx grammar parameter
<i>sentences</i>	[list::string] The Sphinx sentences parameter

Returns

english_words [list::string] The set of English words
 english_grammar [list::string] The set of English grammar
 english_sentences [list::string] The set of English sentences
 greek_words [list::string] The set of Greek words
 greek_grammar [list::string] The set of Greek words
 greek_sentences [list::string] The set of Greek words

Definition at line 371 of file greek_support.py.

7.9.3.4 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport._transformWords (self, words)` [private]

Transforms the Greek words into phonemes for the Sphinx configuration.

Parameters

<i>words</i>	[list::string] The set of Greek words
--------------	---------------------------------------

Returns

enhanced_words [dictionary] The Greek word->phonemes mapping
 englified_words [dictionary] The Greek word->Englified Greek word mapping

Definition at line 297 of file greek_support.py.

7.9.3.5 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport.getGenericConfiguration (self)`

Returns the Generic Greek Configuration.

Returns

[_generic_sphinx_configuration](#) [dictionary] The Generic Greek configuration

Definition at line 459 of file greek_support.py.

7.9.3.6 `def rapp_speech_detection_sphinx4.greek_support.GreekSupport.getLimitedVocebularyConfiguration (self, words, grammar, sentences)`

Computes the Limited Greek Configuration.

Parameters

<i>words</i>	[list::string] The set of words to be identified
<i>grammar</i>	[list::string] The Sphinx grammar parameter
<i>sentences</i>	[list::string] The Sphinx sentences parameter

Returns

limited_sphinx_configuration [dictionary] The Limited Greek configuration
 englified_to_greek_dict [dictionary] A dictionary to transform the englified greek words to actual greek words

Definition at line 417 of file greek_support.py.

7.9.4 Member Data Documentation

7.9.4.1 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._all_special_two_digit_letters` [private]

All special two digit Greek letter->English phonemes mapping.

Definition at line 96 of file `greek_support.py`.

7.9.4.2 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._capital_letters` [private]

Greek uppercase to lowercase mapping.

Definition at line 88 of file `greek_support.py`.

7.9.4.3 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._english_support` [private]

Allows the creation of configuration files for English words.

Instantiates [english_support.EnglishSupport](#) to identify english words

Definition at line 76 of file `greek_support.py`.

7.9.4.4 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._generic_sphinx_configuration` [private]

The generic Sphinx configuration.

Grammar is dummy here..

Todo Fix this according to the generic Greek model

Definition at line 62 of file `greek_support.py`.

7.9.4.5 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._letters` [private]

Standard Greek letter->English phonemes mapping.

Definition at line 100 of file `greek_support.py`.

7.9.4.6 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._literal_letters` [private]

Greek letters->English letters mapping.

Definition at line 102 of file `greek_support.py`.

7.9.4.7 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._phonemes` [private]

Greek words->English standard phonemes mapping.

Definition at line 90 of file `greek_support.py`.

7.9.4.8 `rapp_speech_detection_sphinx4.greek_support.GreekSupport._s_specific_rules` [private]

Special Greek words ->English phonemes mapping.

Definition at line 98 of file `greek_support.py`.

7.9.4.9 `rapp_speech_detection_sphinx4.greek_support.GreekSupport_special_two_digit_letters` [private]

Special two digit Greek letter->English phonemes mapping.

Definition at line 94 of file `greek_support.py`.

7.9.4.10 `rapp_speech_detection_sphinx4.greek_support.GreekSupport_two_digit_letters` [private]

Two digit Greek letters->English phonemes mapping.

Definition at line 92 of file `greek_support.py`.

7.9.4.11 `rapp_speech_detection_sphinx4.greek_support.GreekSupport_vocabulary` [private]

The limited vocabulary creator.

Instantiates [limited_vocabulary_creator.LimitedVocabularyCreator](#)

Definition at line 47 of file `greek_support.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/greek-support.py`

7.10 KnowrobWrapper Class Reference

Class [KnowrobWrapperCommunications](#) contains all the necessary knowrob wrapper functions.

```
#include <knowrob_wrapper.h>
```

Public Member Functions

- [KnowrobWrapper](#) (ros::NodeHandle nh)
Default constructor.
- `rapp_platform_ros_communications::assertRetractAttributeSrv::Response` [assertAttributeValue](#) (`rapp_platform_ros_communications::assertRetractAttributeSrv::Request req`)
Implements the assertRetractAttribute ROS service.
- `rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Response` [clear_user_cognitive_tests_performance_records](#) (`rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Request req`)
Implements the clear_user_cognitive_tests_performance_records ROS service.
- `rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Response` [cognitive_tests_of_type](#) (`rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Request req`)
Implements the cognitive_tests_of_type ROS service.
- `rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Response` [create_cognitive_tests](#) (`rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Request req`)
Implements the create_cognitive_tests ROS service.
- `rapp_platform_ros_communications::createOntologyAliasSrv::Response` [create_ontology_alias](#) (`rapp_platform_ros_communications::createOntologyAliasSrv::Request req`)
Implements the create_ontology_alias ROS service.
- `std::string` [create_ontology_alias_for_new_user](#) (`std::string user_id`)
Creates a new ontology alias for a user.
- `rapp_platform_ros_communications::createInstanceSrv::Response` [createInstanceQuery](#) (`rapp_platform_ros_communications::createInstanceSrv::Request req`)

Implements the createInstance ROS service.

- `rapp_platform_ros_communications::ontologyLoadDumpSrv::Response` [dumpOntologyQuery](#) (`rapp_platform_ros_communications::ontologyLoadDumpSrv::Request req`)

Implements the dumpOntology ROS service.

- `std::string` [get_ontology_alias](#) (`std::string user_id`)

Returns the ontology alias of the user.

- `rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Response` [isSubSuperclassOfQuery](#) (`rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Request req`)

Implements the isSubSuperclass ROS service.

- `rapp_platform_ros_communications::ontologyLoadDumpSrv::Response` [loadOntologyQuery](#) (`rapp_platform_ros_communications::ontologyLoadDumpSrv::Request req`)

Implements the loadOntology ROS service.

- `rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Response` [record_user_cognitive_tests_performance](#) (`rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Request req`)

Implements the record_user_cognitive_tests_performance ROS service.

- `rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response` [subclassesOfQuery](#) (`rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request req`)

Implements the subclassesOf ROS service.

- `rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response` [superclassesOfQuery](#) (`rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request req`)

Implements the superclassesOf ROS service.

- `rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Response` [user_instances_of_class](#) (`rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Request req`)

Implements the returnUserInstancesOfClass ROS service.

- `rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Response` [user_performance_cognitive_tests](#) (`rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Request req`)

Implements the user_performance_cognitive_tests ROS service.

Private Attributes

- `ros::ServiceClient` [mysql_fetch_client](#)
- `ros::ServiceClient` [mysql_update_client](#)
- `ros::ServiceClient` [mysql_write_client](#)
- `ros::NodeHandle` [nh_](#)
- `json_prolog::Prolog` [pl](#)

7.10.1 Detailed Description

Class [KnowrobWrapperCommunications](#) contains all the necessary knowrob wrapper functions.

Definition at line 46 of file `knowrob_wrapper.h`.

7.10.2 Constructor & Destructor Documentation

7.10.2.1 KnowrobWrapper::KnowrobWrapper (`ros::NodeHandle nh`)

Default constructor.

Definition at line 30 of file `knowrob_wrapper.cpp`.

7.10.3 Member Function Documentation

7.10.3.1 `rapp_platform_ros_communications::assertRetractAttributeSrv::Response` `KnowrobWrapper::assertAttributeValue (rapp_platform_ros_communications::assertRetractAttributeSrv::Request req)`

Implements the `assertRetractAttribute` ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::assertRetractAttributeSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::assertRetractAttributeSrv::Response&] The ROS service response

7.10.3.2 `rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Response`
`KnowrobWrapper::clear_user_cognitive_tests_performance_records (rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Request req)`

Implements the clear_user_cognitive_tests_performance_records ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Response&] The ROS service response

Definition at line 458 of file knowrob_wrapper.cpp.

7.10.3.3 `rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Response` `KnowrobWrapper::cognitive_tests_of_type (rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Request req)`

Implements the cognitive_tests_of_type ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Response&] The ROS service response

Definition at line 321 of file knowrob_wrapper.cpp.

7.10.3.4 `rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Response` `KnowrobWrapper::create_cognitive_tests (rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Request req)`

Implements the create_cognitive_tests ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Request&] The ROS service request
------------	--

Returns

res [rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Response&] The ROS service response

Definition at line 248 of file knowrob_wrapper.cpp.

7.10.3.5 rapp_platform_ros_communications::createOntologyAliasSrv::Response KnowrobWrapper::create_ontology_alias (rapp_platform_ros_communications::createOntologyAliasSrv::Request req)

Implements the create_ontology_alias ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::createOntologyAliasSrv::Request&] The ROS service request
------------	--

Returns

res [rapp_platform_ros_communications::createOntologyAliasSrv::Response&] The ROS service response

Definition at line 513 of file knowrob_wrapper.cpp.

7.10.3.6 std::string KnowrobWrapper::create_ontology_alias_for_new_user (std::string user_id)

Creates a new ontology alias for a user.

Parameters

<i>user_id</i>	[string] The username of the user
----------------	-----------------------------------

Returns

ontology_alias [string] The ontology_alias of the user or possible error

Definition at line 134 of file knowrob_wrapper.cpp.

7.10.3.7 rapp_platform_ros_communications::createInstanceSrv::Response KnowrobWrapper::createInstanceQuery (rapp_platform_ros_communications::createInstanceSrv::Request req)

Implements the createInstance ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::createInstanceSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::createInstanceSrv::Response&] The ROS service response

Definition at line 757 of file knowrob_wrapper.cpp.

7.10.3.8 rapp_platform_ros_communications::ontologyLoadDumpSrv::Response KnowrobWrapper::dumpOntologyQuery (rapp_platform_ros_communications::ontologyLoadDumpSrv::Request req)

Implements the dumpOntology ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologyLoadDumpSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::ontologyLoadDumpSrv::Response&] The ROS service response

Definition at line 924 of file knowrob_wrapper.cpp.

7.10.3.9 `std::string KnowrobWrapper::get_ontology_alias (std::string user_id)`

Returns the ontology alias of the user.

Parameters

<i>user_id</i>	[string] The username of the user
----------------	-----------------------------------

Returns

ontology_alias [string] The ontology_alias of the user or possible error

Definition at line 95 of file knowrob_wrapper.cpp.

7.10.3.10 `rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Response KnowrobWrapper::isSubSuperclassOfQuery (rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Request req)`

Implements the isSubSuperclass ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Request&] The ROS service request
------------	--

Returns

res [rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Response&] The ROS service response

Definition at line 687 of file knowrob_wrapper.cpp.

7.10.3.11 `rapp_platform_ros_communications::ontologyLoadDumpSrv::Response KnowrobWrapper::loadOntologyQuery (rapp_platform_ros_communications::ontologyLoadDumpSrv::Request req)`

Implements the loadOntology ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologyLoadDumpSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::ontologyLoadDumpSrv::Response&] The ROS service response

Definition at line 989 of file knowrob_wrapper.cpp.

7.10.3.12 `rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Response KnowrobWrapper::record_user_cognitive_tests_performance (rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Request req)`

Implements the record_user_cognitive_tests_performance ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Response&] The ROS service response

Definition at line 195 of file knowrob_wrapper.cpp.

```
7.10.3.13 rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response KnowrobWrapper-
::subclassesOfQuery ( rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request req
)
```

Implements the subclassesOf ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request&] The ROS service request
------------	--

Returns

res [rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response&] The ROS service response

Definition at line 546 of file knowrob_wrapper.cpp.

```
7.10.3.14 rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response KnowrobWrapper-
::superclassesOfQuery ( rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request req
)
```

Implements the superclassesOf ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request&] The ROS service request
------------	--

Returns

res [rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response&] The ROS service response

Definition at line 617 of file knowrob_wrapper.cpp.

```
7.10.3.15 rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Response KnowrobWrapper::user_
instances_of_class ( rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Request req
)
```

Implements the returnUserInstancesOfClass ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Request&] The ROS service request
------------	---

Returns

res [rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Response&] The ROS service response

Definition at line 1037 of file knowrob_wrapper.cpp.

```
7.10.3.16 rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Response KnowrobWrapper::user_
performance_cognitive_tests ( rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Request req
)
```

Implements the user_performance_cognitive_tests ROS service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Request&] The ROS service request
------------	--

Returns

res [rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Response&] The ROS service response

Definition at line 390 of file knowrob_wrapper.cpp.

7.10.4 Member Data Documentation

7.10.4.1 **ros::ServiceClient KnowrobWrapper::mysql_fetch_client** [private]

The mysql update tblUser client server

Definition at line 59 of file knowrob_wrapper.h.

7.10.4.2 **ros::ServiceClient KnowrobWrapper::mysql_update_client** [private]

Definition at line 62 of file knowrob_wrapper.h.

7.10.4.3 **ros::ServiceClient KnowrobWrapper::mysql_write_client** [private]

The mysql fetch from tblUser client server

Definition at line 56 of file knowrob_wrapper.h.

7.10.4.4 **ros::NodeHandle KnowrobWrapper::nh_** [private]

< The ROS node handle The json prolog handle

Definition at line 50 of file knowrob_wrapper.h.

7.10.4.5 json_prolog::Prolog KnowrobWrapper::pl [private]

The mysql write to tblUser client server

Definition at line 53 of file knowrob_wrapper.h.

The documentation for this class was generated from the following files:


- /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/[knowrob_wrapper.h](#)
- /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/[knowrob_wrapper.cpp](#)

7.11 KnowrobWrapperCommunications Class Reference

Class [KnowrobWrapperCommunications](#) uptakes the task of handling the ROS service callbacks.

```
#include <knowrob_wrapper_communications.h>
```

Collaboration diagram for KnowrobWrapperCommunications:



Public Member Functions

- [KnowrobWrapperCommunications](#) ()
Default constructor.
- bool [clear_user_cognitive_tests_performance_records_callback](#) (rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Request &req, rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Response &res)
Serves the clear_user_cognitive_tests_performance_records ROS service callback.
- bool [cognitive_tests_of_type_callback](#) (rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Request &req, rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Response &res)
Serves the cognitive_tests_of_type ROS service callback.
- bool [create_cognitive_tests_callback](#) (rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Request &req, rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Response &res)
Serves the create_cognitive_tests ROS service callback.
- bool [create_ontology_alias_callback](#) (rapp_platform_ros_communications::createOntologyAliasSrv::Request &req, rapp_platform_ros_communications::createOntologyAliasSrv::Response &res)
Serves the create_ontology_alias ROS service callback.
- bool [createInstanceCallback](#) (rapp_platform_ros_communications::createInstanceSrv::Request &req, rapp_platform_ros_communications::createInstanceSrv::Response &res)
Serves the createInstance ROS service callback.

- bool [dumpOntologyCallback](#) (rapp_platform_ros_communications::ontologyLoadDumpSrv::Request &req, rapp_platform_ros_communications::ontologyLoadDumpSrv::Response &res)
Serves the dumpOntology ROS service callback.
- bool [isSubSuperclassOfCallback](#) (rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Request &req, rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Response &res)
Serves the isSubSuperclassOf ROS service callback.
- bool [loadOntologyCallback](#) (rapp_platform_ros_communications::ontologyLoadDumpSrv::Request &req, rapp_platform_ros_communications::ontologyLoadDumpSrv::Response &res)
Serves the loadOntology ROS service callback.
- bool [record_user_cognitive_tests_performance_callback](#) (rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Request &req, rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Response &res)
Serves the record_user_cognitive_tests_performance ROS service callback.
- bool [subclassesOfCallback](#) (rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request &req, rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response &res)
Serves the subclassesOf ROS service callback.
- bool [superclassesOfCallback](#) (rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request &req, rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response &res)
Serves the superlassesOf ROS service callback.
- bool [user_instances_of_class_callback](#) (rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Request &req, rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Response &res)
Serves the user_instances_of_class ROS service callback.
- bool [user_performance_cognitive_tests_callback](#) (rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Request &req, rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Response &res)
Serves the user_performance_cognitive_tests ROS service callback.

Private Attributes

- ros::ServiceServer [clear_user_cognitive_tests_performance_records_service_](#)
- std::string [clear_user_cognitive_tests_performance_records_topic_](#)
- ros::ServiceServer [cognitive_tests_of_type_service_](#)
- std::string [cognitive_tests_of_type_topic_](#)
- ros::ServiceServer [create_cognitive_tests_service_](#)
- std::string [create_cognitive_tests_topic_](#)
- ros::ServiceServer [create_ontology_alias_service_](#)
- std::string [create_ontology_alias_topic_](#)
- ros::ServiceServer [createInstanceService_](#)
- std::string [createInstanceServiceTopic_](#)
- ros::ServiceServer [dumpOntologyService_](#)
- std::string [dumpOntologyServiceTopic_](#)
- ros::ServiceServer [is_subsuperclass_of_service_](#)
- std::string [is_subsuperclass_of_service_topic_](#)
- [KnowrobWrapper](#) [knowrob_wrapper](#)
- ros::ServiceServer [loadOntologyService_](#)
- std::string [loadOntologyServiceTopic_](#)
- ros::NodeHandle [nh_](#)
- ros::ServiceServer [record_user_cognitive_tests_performance_service_](#)
- std::string [record_user_cognitive_tests_performance_topic_](#)
- ros::ServiceServer [subclasses_of_service_](#)
- std::string [subclasses_of_service_topic_](#)
- ros::ServiceServer [superclasses_of_service_](#)
- std::string [superclasses_of_service_topic_](#)

- [ros::ServiceServer user_instances_of_class_service_](#)
- [std::string user_instances_of_class_topic_](#)
- [ros::ServiceServer user_performance_cognitive_tests_service_](#)
- [std::string user_performance_cognitive_tests_topic_](#)

7.11.1 Detailed Description

Class [KnowrobWrapperCommunications](#) uptakes the task of handling the ROS service callbacks.

Definition at line 28 of file `knowrob_wrapper_communications.h`.

7.11.2 Constructor & Destructor Documentation

7.11.2.1 KnowrobWrapperCommunications::KnowrobWrapperCommunications ()

Default constructor.

Default constructor Waits for services it depends on and declares the knowrob wrapper services callbacks.

Definition at line 28 of file `knowrob_wrapper_communications.cpp`.

7.11.3 Member Function Documentation

7.11.3.1 bool KnowrobWrapperCommunications::clear_user_cognitive_tests_performance_records_callback (rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Request & req, rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Response & res)

Serves the `clear_user_cognitive_tests_performance_records` ROS service callback.

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Request&</code>] The ROS service request
<i>res</i>	[<code>rapp_platform_ros_communications::clearUserPerformanceCognitiveTestsSrv::Response&</code>] The ROS service response

Returns

`bool` - The success status of the call

Definition at line 332 of file `knowrob_wrapper_communications.cpp`.

7.11.3.2 bool KnowrobWrapperCommunications::cognitive_tests_of_type_callback (rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Request & req, rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Response & res)

Serves the `cognitive_tests_of_type` ROS service callback.

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Request&</code>] The ROS service request
------------	--

<i>res</i>	[rapp_platform_ros_communications::cognitiveTestsOfTypeSrv::Response&] The ROS service response
------------	---

Returns

bool - The success status of the call

Definition at line 304 of file knowrob_wrapper_communications.cpp.

7.11.3.3 bool KnowrobWrapperCommunications::create_cognitive_tests_callback (rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Request & *req*, rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Response & *res*)

Serves the create_cognitive_tests ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::createCognitiveExerciseTestSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 290 of file knowrob_wrapper_communications.cpp.

7.11.3.4 bool KnowrobWrapperCommunications::create_ontology_alias_callback (rapp_platform_ros_communications::createOntologyAliasSrv::Request & *req*, rapp_platform_ros_communications::createOntologyAliasSrv::Response & *res*)

Serves the create_ontology_alias ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::createOntologyAliasSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::createOntologyAliasSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 248 of file knowrob_wrapper_communications.cpp.

7.11.3.5 bool KnowrobWrapperCommunications::createInstanceCallback (rapp_platform_ros_communications::createInstanceSrv::Request & *req*, rapp_platform_ros_communications::createInstanceSrv::Response & *res*)

Serves the createInstance ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::createInstanceSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::createInstanceSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 206 of file knowrob_wrapper_communications.cpp.

7.11.3.6 bool KnowrobWrapperCommunications::dumpOntologyCallback (rapp_platform_ros_communications::ontologyLoadDumpSrv::Request & *req*, rapp_platform_ros_communications::ontologyLoadDumpSrv::Response & *res*)

Serves the dumpOntology ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologyLoadDumpSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::ontologyLoadDumpSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 220 of file knowrob_wrapper_communications.cpp.

7.11.3.7 bool KnowrobWrapperCommunications::isSubSuperclassOfCallback (rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Request & *req*, rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Response & *res*)

Serves the isSubSuperclassOf ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::ontologyIsSubSuperClassOfSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 192 of file knowrob_wrapper_communications.cpp.

7.11.3.8 bool KnowrobWrapperCommunications::loadOntologyCallback (rapp_platform_ros_communications::ontologyLoadDumpSrv::Request & *req*, rapp_platform_ros_communications::ontologyLoadDumpSrv::Response & *res*)

Serves the loadOntology ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologyLoadDumpSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::ontologyLoadDumpSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 234 of file knowrob_wrapper_communications.cpp.

7.11.3.9 bool KnowrobWrapperCommunications::record_user_cognitive_tests_performance_callback (rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Request & *req*, rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Response & *res*)

Serves the record_user_cognitive_tests_performance ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::recordUserPerformanceCognitiveTestsSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 318 of file knowrob_wrapper_communications.cpp.

7.11.3.10 bool KnowrobWrapperCommunications::subclassesOfCallback (rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request & *req*, rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response & *res*)

Serves the subclassesOf ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 164 of file knowrob_wrapper_communications.cpp.

7.11.3.11 bool KnowrobWrapperCommunications::superclassesOfCallback (rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request & *req*, rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response & *res*)

Serves the superlassesOf ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::ontologySubSuperClassesOfSrv::Response&] The R-OS service response

Returns

bool - The success status of the call

Definition at line 178 of file knowrob_wrapper_communications.cpp.

7.11.3.12 bool KnowrobWrapperCommunications::user_instances_of_class_callback (rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Request & *req*, rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Response & *res*)

Serves the user_instances_of_class ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::returnUserInstancesOfClassSrv::Response&] The R-OS service response

Returns

bool - The success status of the call

Definition at line 262 of file knowrob_wrapper_communications.cpp.

7.11.3.13 bool KnowrobWrapperCommunications::user_performance_cognitive_tests_callback (rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Request & *req*, rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Response & *res*)

Serves the user_performance_cognitive_tests ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Request&] The R-OS service request
<i>res</i>	[rapp_platform_ros_communications::userPerformanceCognitiveTestsSrv::Response&] The ROS service response

Returns

bool - The success status of the call

Definition at line 276 of file knowrob_wrapper_communications.cpp.

7.11.4 Member Data Documentation

7.11.4.1 ros::ServiceServer KnowrobWrapperCommunications::clear_user_cognitive_tests_performance_records_service_
[private]

Member variable holding the clear_user_cognitive_tests_performance_records ROS service topic

Definition at line 99 of file knowrob_wrapper_communications.h.

7.11.4.2 `std::string KnowrobWrapperCommunications::clear_user_cognitive_tests_performance_records_topic_`
[private]

Definition at line 101 of file knowrob_wrapper_communications.h.

7.11.4.3 `ros::ServiceServer KnowrobWrapperCommunications::cognitive_tests_of_type_service_` [private]

Member variable holding the cognitive_tests_of_type ROS service topic

Definition at line 89 of file knowrob_wrapper_communications.h.

7.11.4.4 `std::string KnowrobWrapperCommunications::cognitive_tests_of_type_topic_` [private]

The record_user_cognitive_tests_performance service server

Definition at line 91 of file knowrob_wrapper_communications.h.

7.11.4.5 `ros::ServiceServer KnowrobWrapperCommunications::create_cognitive_tests_service_` [private]

Member variable holding the create_cognitive_tests ROS service topic

Definition at line 84 of file knowrob_wrapper_communications.h.

7.11.4.6 `std::string KnowrobWrapperCommunications::create_cognitive_tests_topic_` [private]

The cognitive_tests_of_type service server

Definition at line 86 of file knowrob_wrapper_communications.h.

7.11.4.7 `ros::ServiceServer KnowrobWrapperCommunications::create_ontology_alias_service_` [private]

Member variable holding the create_ontology_alias ROS service topic

Definition at line 74 of file knowrob_wrapper_communications.h.

7.11.4.8 `std::string KnowrobWrapperCommunications::create_ontology_alias_topic_` [private]

The user_performance_cognitive_tests service server

Definition at line 76 of file knowrob_wrapper_communications.h.

7.11.4.9 `ros::ServiceServer KnowrobWrapperCommunications::createInstanceService_` [private]

Member variable holding the createInstanceServiceTopic ROS service topic

Definition at line 54 of file knowrob_wrapper_communications.h.

7.11.4.10 `std::string KnowrobWrapperCommunications::createInstanceServiceTopic_` [private]

The dumpOntologyService service server

Definition at line 56 of file knowrob_wrapper_communications.h.

7.11.4.11 `ros::ServiceServer KnowrobWrapperCommunications::dumpOntologyService_` `[private]`

Member variable holding the dumpOntologyServiceTopic ROS service topic

Definition at line 59 of file knowrob_wrapper_communications.h.

7.11.4.12 `std::string KnowrobWrapperCommunications::dumpOntologyServiceTopic_` `[private]`

The loadOntologyService service server

Definition at line 61 of file knowrob_wrapper_communications.h.

7.11.4.13 `ros::ServiceServer KnowrobWrapperCommunications::is_subsuperclass_of_service_` `[private]`

Member variable holding the is_subsuperclass ROS service topic

Definition at line 49 of file knowrob_wrapper_communications.h.

7.11.4.14 `std::string KnowrobWrapperCommunications::is_subsuperclass_of_service_topic_` `[private]`

The createInstanceService service server

Definition at line 51 of file knowrob_wrapper_communications.h.

7.11.4.15 `KnowrobWrapper KnowrobWrapperCommunications::knowrob_wrapper` `[private]`

The subclasses_of service server

Definition at line 35 of file knowrob_wrapper_communications.h.

7.11.4.16 `ros::ServiceServer KnowrobWrapperCommunications::loadOntologyService_` `[private]`

Member variable holding the loadOntologyServiceTopic ROS service topic

Definition at line 64 of file knowrob_wrapper_communications.h.

7.11.4.17 `std::string KnowrobWrapperCommunications::loadOntologyServiceTopic_` `[private]`

The user_instances_of_class service server

Definition at line 66 of file knowrob_wrapper_communications.h.

7.11.4.18 `ros::NodeHandle KnowrobWrapperCommunications::nh_` `[private]`

< The ROS node handle Object of type knowrob_wrapper

Definition at line 32 of file knowrob_wrapper_communications.h.

7.11.4.19 `ros::ServiceServer KnowrobWrapperCommunications::record_user_cognitive_tests_performance_service_` `[private]`

Member variable holding the record_user_cognitive_tests_performance ROS service topic

Definition at line 94 of file knowrob_wrapper_communications.h.

7.11.4.20 `std::string KnowrobWrapperCommunications::record_user_cognitive_tests_performance_topic_ [private]`

The clear_user_cognitive_tests_performance_records service server

Definition at line 96 of file knowrob_wrapper_communications.h.

7.11.4.21 `ros::ServiceServer KnowrobWrapperCommunications::subclasses_of_service_ [private]`

Member variable holding the subclasses_of ROS service topic

Definition at line 38 of file knowrob_wrapper_communications.h.

7.11.4.22 `std::string KnowrobWrapperCommunications::subclasses_of_service_topic_ [private]`

The superclasses_of service server

Definition at line 41 of file knowrob_wrapper_communications.h.

7.11.4.23 `ros::ServiceServer KnowrobWrapperCommunications::superclasses_of_service_ [private]`

Member variable holding the superclasses_of ROS service topic

Definition at line 44 of file knowrob_wrapper_communications.h.

7.11.4.24 `std::string KnowrobWrapperCommunications::superclasses_of_service_topic_ [private]`

The is_subsuperclass service server

Definition at line 46 of file knowrob_wrapper_communications.h.

7.11.4.25 `ros::ServiceServer KnowrobWrapperCommunications::user_instances_of_class_service_ [private]`

Member variable holding the user_instances_of_class ROS service topic

Definition at line 69 of file knowrob_wrapper_communications.h.

7.11.4.26 `std::string KnowrobWrapperCommunications::user_instances_of_class_topic_ [private]`

The create_ontology_alias service server

Definition at line 71 of file knowrob_wrapper_communications.h.

7.11.4.27 `ros::ServiceServer KnowrobWrapperCommunications::user_performance_cognitive_tests_service_ [private]`

Member variable holding the user_performance_cognitive_tests ROS service topic

Definition at line 79 of file knowrob_wrapper_communications.h.

7.11.4.28 `std::string KnowrobWrapperCommunications::user_performance_cognitive_tests_topic_ [private]`

The create_cognitive_tests service server

Definition at line 81 of file knowrob_wrapper_communications.h.


The documentation for this class was generated from the following files:

- /home/travis/rapp_temp/rapp-platform/rapp-knowrob-wrapper/include/knowrob-wrapper/knowrob-wrapper-_communications.h
- /home/travis/rapp_temp/rapp-platform/rapp-knowrob-wrapper/src/knowrob-wrapper_communications.cpp


7.12 rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabulary-Creator Class Reference

Creates temporary configuration files for the input limited vocabulary.

Inheritance diagram for rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator:



Collaboration diagram for rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator:



Public Member Functions

- `def __init__`
Performs initializations.
- `def createConfigurationFiles`
Creates temporary configuration files for the input limited vocabulary.

Public Attributes

- [languages_package](#)
- [sphinx_configuration](#)

Private Attributes

- [_allow_sphinx_output](#)

7.12.1 Detailed Description

Creates temporary configuration files for the input limited vocabulary.

Definition at line 35 of file `limited_vocabulary_creator.py`.

7.12.2 Constructor & Destructor Documentation

7.12.2.1 `def rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator.__init__(self)`

Performs initializations.

Definition at line 38 of file `limited_vocabulary_creator.py`.

7.12.3 Member Function Documentation

7.12.3.1 `def rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator.createConfigurationFiles (self, words, grammar, sentences)`

Creates temporary configuration files for the input limited vocabulary.

The 'words' input argument is of the form: `words = { 'word1_en_chars': [phonem1, phonem2,...], 'word2_en_chars': [phonem1, phonem2,...] ... }`

Parameters

<i>words</i>	[list::string] The set of words to be identified
<i>grammar</i>	[list::string] The Sphinx grammar parameter
<i>sentences</i>	[list::string] The Sphinx sentences parameter

Returns

`conf` [dictionary] The final configuration
`status` [string] Either the error (string) or True (bool)

Definition at line 80 of file `limited_vocabulary_creator.py`.

7.12.4 Member Data Documentation

7.12.4.1 `rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator._allow_sphinx_output`
`[private]`

Definition at line 152 of file `limited_vocabulary_creator.py`.

7.12.4.2 `rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator.languages_package`

Definition at line 46 of file `limited_vocabulary_creator.py`.

7.12.4.3 rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator.sphinx_configuration

Definition at line 51 of file limited_vocabulary_creator.py.

The documentation for this class was generated from the following file:

- /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/limited_vocabulary_creator.py

7.13 mysql_wrapper.MySQLdbWrapper Class Reference

The mysql wrapper ros node.

Public Member Functions

- def [__init__](#)
Default contructor.
- def [checkConnection](#)
Checks connectivity to the DB.
- def [constructAndQuery](#)
Construcs the where= ..and where=...
- def [constructCommaColumns](#)
Places commas between columns and constructs a string.
- def [deleteData](#)
Implements the general delete data from table function.
- def [fetchData](#)
Implements the general fetch data from table function.
- def [getLogin](#)
Loads login details from file.
- def [getTableColumnNames](#)
Gets the columns of the table.
- def [tblAppsRobotsDeleteDataHandler](#)
The tbl appsRobots delete data service callback.
- def [tblAppsRobotsFetchDataHandler](#)
The tbl appsRobots fetch data service callback.
- def [tblAppsRobotsUpdateDataHandler](#)
The tbl appsRobots update data service callback.
- def [tblAppsRobotsWriteDataHandler](#)
The tbl appsRobots write data service callback.
- def [tblModelDeleteDataHandler](#)
The tbl model delete data service callback.
- def [tblModelFetchDataHandler](#)
The tbl model fetch data service callback.
- def [tblModelUpdateDataHandler](#)
The tbl model update data service callback.
- def [tblModelWriteDataHandler](#)
The tbl model write data service callback.
- def [tblRappDeleteDataHandler](#)
The tbl rapp delete data service callback.
- def [tblRappFetchDataHandler](#)
The tbl rapp fetch data service callback.

- def [tblRappUpdateDataHandler](#)
The tbl rapp update data service callback.
- def [tblRappWriteDataHandler](#)
The tbl rapp write data service callback.
- def [tblRobotDeleteDataHandler](#)
The tbl robot delete data service callback.
- def [tblRobotFetchDataHandler](#)
The tbl robot fetch data service callback.
- def [tblRobotUpdateDataHandler](#)
The tbl robot update data service callback.
- def [tblRobotWriteDataHandler](#)
The tbl robot write data service callback.
- def [tblUserDeleteDataHandler](#)
The tbl user delete data service callback.
- def [tblUserFetchDataHandler](#)
The tbl user fetch data service callback.
- def [tblUsersOntologyInstancesDeleteDataHandler](#)
The tbl usersOntologyInstances delete data service callback.
- def [tblUsersOntologyInstancesFetchDataHandler](#)
The tbl usersOntologyInstances fetch data service callback.
- def [tblUsersOntologyInstancesUpdateDataHandler](#)
The tbl usersOntologyInstances update data service callback.
- def [tblUsersOntologyInstancesWriteDataHandler](#)
The tbl usersOntologyInstances write data service callback.
- def [tblUserUpdateDataHandler](#)
The tbl user update data service callback.
- def [tblUserWriteDataHandler](#)
The tbl user write data service callback.
- def [updateData](#)
Implements the general update data from table function.
- def [viewUsersRobotsAppsFetchDataHandler](#)
The view usersRobotsApps fetch data service callback.
- def [whatRappsCanRun](#)
Implements the whatRappsCanRun service.
- def [whatRappsCanRunDataHandler](#)
The what rappRappCanRun service callback.
- def [writeData](#)
Implements the general write data to table function.

Public Attributes

- [serv](#)
- [serv_topic](#)

7.13.1 Detailed Description

The mysql wrapper ros node.

Definition at line 47 of file mysql_wrapper.py.

7.13.2 Constructor & Destructor Documentation

7.13.2.1 `def mysql_wrapper.MySQLdbWrapper.__init__ (self)`

Default constructor.

Declares the callbacks of the node's services

Definition at line 52 of file `mysql_wrapper.py`.

7.13.3 Member Function Documentation

7.13.3.1 `def mysql_wrapper.MySQLdbWrapper.checkConnection (self)`

Checks connectivity to the DB.

Returns

[void] Connection performed successfully

Definition at line 412 of file `mysql_wrapper.py`.

7.13.3.2 `def mysql_wrapper.MySQLdbWrapper.constructAndQuery (self, cols)`

Constructs the where= ..and where=...

clause

Parameters

<i>cols</i>	[list] the columns needed to construct the clause
-------------	---

Returns

returnquery [string] the And clause

Definition at line 371 of file `mysql_wrapper.py`.

7.13.3.3 `def mysql_wrapper.MySQLdbWrapper.constructCommaColumns (self, cols)`

Places commas between columns and constructs a string.

Parameters

<i>cols</i>	[list] the input columns
-------------	--------------------------

Returns

returncols [string] the output string

Definition at line 353 of file `mysql_wrapper.py`.

7.13.3.4 `def mysql_wrapper.MySQLdbWrapper.deleteData (self, req, tblName)`

Implements the general delete data from table function.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>tblName</i>	[string] the table name
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 211 of file mysql_wrapper.py.

7.13.3.5 `def mysql_wrapper.MySQLdbWrapper.fetchData (self, req, tblName)`

Implements the general fetch data from table function.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
<i>tblName</i>	[string] the table name
<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response

Definition at line 275 of file mysql_wrapper.py.

7.13.3.6 `def mysql_wrapper.MySQLdbWrapper.getLogin (self)`

Loads login details from file.

Returns

[void] Login details loaded successfully

Definition at line 402 of file mysql_wrapper.py.

7.13.3.7 `def mysql_wrapper.MySQLdbWrapper.getTableColumnNames (self, tblName)`

Gets the columns of the table.

Returns

Columns [list] the columns of the table

Definition at line 386 of file mysql_wrapper.py.

7.13.3.8 `def mysql_wrapper.MySQLdbWrapper.tblAppsRobotsDeleteDataHandler (self, req)`

The tbl appsRobots delete data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 571 of file mysql_wrapper.py.

7.13.3.9 `def mysql_wrapper.MySQLdbWrapper.tblAppsRobotsFetchDataHandler (self, req)`

The tbl appsRobots fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response

Definition at line 555 of file mysql_wrapper.py.

7.13.3.10 `def mysql_wrapper.MySQLdbWrapper.tblAppsRobotsUpdateDataHandler (self, req)`

The tbl appsRobots update data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 579 of file mysql_wrapper.py.

7.13.3.11 `def mysql_wrapper.MySQLdbWrapper.tblAppsRobotsWriteDataHandler (self, req)`

The tbl appsRobots write data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::writeDataResponse::Response&] The ROS service response

Definition at line 563 of file mysql_wrapper.py.

7.13.3.12 `def mysql_wrapper.MySQLdbWrapper.tblModelDeleteDataHandler (self, req)`

The tbl model delete data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 475 of file mysql_wrapper.py.

7.13.3.13 `def mysql_wrapper.MySQLdbWrapper.tblModelFetchDataHandler (self, req)`

The tbl model fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
------------	---

<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response
------------	--

Definition at line 459 of file mysql_wrapper.py.

7.13.3.14 def mysql_wrapper.MySQLdbWrapper.tblModelUpdateDataHandler (*self*, *req*)

The tbl model update data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 483 of file mysql_wrapper.py.

7.13.3.15 def mysql_wrapper.MySQLdbWrapper.tblModelWriteDataHandler (*self*, *req*)

The tbl model write data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::writeDataSrvResponse::Response&] The ROS service response

Definition at line 467 of file mysql_wrapper.py.

7.13.3.16 def mysql_wrapper.MySQLdbWrapper.tblRappDeleteDataHandler (*self*, *req*)

The tbl rapp delete data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 507 of file mysql_wrapper.py.

7.13.3.17 def mysql_wrapper.MySQLdbWrapper.tblRappFetchDataHandler (*self*, *req*)

The tbl rapp fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response

Definition at line 491 of file mysql_wrapper.py.

7.13.3.18 `def mysql_wrapper.MySQLdbWrapper.tblRappUpdateDataHandler (self, req)`

The tbl rapp update data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 515 of file mysql_wrapper.py.

7.13.3.19 def mysql_wrapper.MySQLdbWrapper.tblRappWriteDataHandler (*self*, *req*)

The tbl rapp write data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::writeDataResponse::Response&] The ROS service response

Definition at line 499 of file mysql_wrapper.py.

7.13.3.20 def mysql_wrapper.MySQLdbWrapper.tblRobotDeleteDataHandler (*self*, *req*)

The tbl robot delete data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 539 of file mysql_wrapper.py.

7.13.3.21 def mysql_wrapper.MySQLdbWrapper.tblRobotFetchDataHandler (*self*, *req*)

The tbl robot fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response

Definition at line 523 of file mysql_wrapper.py.

7.13.3.22 def mysql_wrapper.MySQLdbWrapper.tblRobotUpdateDataHandler (*self*, *req*)

The tbl robot update data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 547 of file mysql_wrapper.py.

7.13.3.23 `def mysql_wrapper.MySQLdbWrapper.tblRobotWriteDataHandler (self, req)`

The tbl robot write data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::writeDataResponse::Response&] The ROS service response

Definition at line 531 of file mysql_wrapper.py.

7.13.3.24 def mysql_wrapper.MySQLdbWrapper.tblUserDeleteDataHandler (*self*, *req*)

The tbl user delete data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 443 of file mysql_wrapper.py.

7.13.3.25 def mysql_wrapper.MySQLdbWrapper.tblUserFetchDataHandler (*self*, *req*)

The tbl user fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response

Definition at line 427 of file mysql_wrapper.py.

7.13.3.26 def mysql_wrapper.MySQLdbWrapper.tblUsersOntologyInstancesDeleteDataHandler (*self*, *req*)

The tbl usersOntologyInstances delete data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::deleteDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::deleteDataSrvResponse::Response&] The ROS service response

Definition at line 603 of file mysql_wrapper.py.

7.13.3.27 def mysql_wrapper.MySQLdbWrapper.tblUsersOntologyInstancesFetchDataHandler (*self*, *req*)

The tbl usersOntologyInstances fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
------------	---

<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response
------------	--

Definition at line 587 of file mysql_wrapper.py.

7.13.3.28 `def mysql_wrapper.MySQLdbWrapper.tblUsersOntologyInstancesUpdateDataHandler (self, req)`

The tbl usersOntologyInstances update data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 611 of file mysql_wrapper.py.

7.13.3.29 `def mysql_wrapper.MySQLdbWrapper.tblUsersOntologyInstancesWriteDataHandler (self, req)`

The tbl usersOntologyInstances write data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::writeDataResponse::Response&] The ROS service response

Definition at line 595 of file mysql_wrapper.py.

7.13.3.30 `def mysql_wrapper.MySQLdbWrapper.tblUserUpdateDataHandler (self, req)`

The tbl user update data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 451 of file mysql_wrapper.py.

7.13.3.31 `def mysql_wrapper.MySQLdbWrapper.tblUserWriteDataHandler (self, req)`

The tbl user write data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::writeDataResponse::Response&] The ROS service response

Definition at line 435 of file mysql_wrapper.py.

7.13.3.32 `def mysql_wrapper.MySQLdbWrapper.updateData (self, req, tblName)`

Implements the general update data from table function.

Parameters

<i>req</i>	[rapp_platform_ros_communications::updateDataSrvRequest::Request&] The ROS service request
<i>tblName</i>	[string] the table name
<i>res</i>	[rapp_platform_ros_communications::updateDataSrvResponse::Response&] The ROS service response

Definition at line 242 of file mysql_wrapper.py.

7.13.3.33 `def mysql_wrapper.MySQLdbWrapper.viewUsersRobotsAppsFetchDataHandler (self, req)`

The view usersRobotsApps fetch data service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::fetchDataSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::fetchDataSrvResponse::Response&] The ROS service response

Definition at line 619 of file mysql_wrapper.py.

7.13.3.34 `def mysql_wrapper.MySQLdbWrapper.whatRappsCanRun (self, req, tblName)`

Implements the whatRappsCanRun service.

Parameters

<i>req</i>	[rapp_platform_ros_communications::whatRappsCanRunSrvRequest::Request&] The ROS service request
<i>tblName</i>	[string] the table name
<i>res</i>	[rapp_platform_ros_communications::whatRappsCanRunSrvResponse::Response&] The ROS service response

Definition at line 318 of file mysql_wrapper.py.

7.13.3.35 `def mysql_wrapper.MySQLdbWrapper.whatRappsCanRunDataHandler (self, req)`

The what rappRappCanRun service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::whatRappsCanRunSrvRequest::Request&] The ROS service request
<i>res</i>	[rapp_platform_ros_communications::whatRappsCanRunSrvResponse::Response&] The ROS service response

Definition at line 627 of file mysql_wrapper.py.

7.13.3.36 `def mysql_wrapper.MySQLdbWrapper.writeData (self, req, tblName)`

Implements the general write data to table function.

Parameters

<i>req</i>	[rapp_platform_ros_communications::writeDataSrvRequest::Request&] The ROS service request
<i>tblName</i>	[string] the table name
<i>res</i>	[rapp_platform_ros_communications::writeDataSrvResponse::Response&] The ROS service response

Definition at line 170 of file `mysql_wrapper.py`.

7.13.4 Member Data Documentation

7.13.4.1 `mysql_wrapper.MySQLdbWrapper.serv`

Definition at line 57 of file `mysql_wrapper.py`.

7.13.4.2 `mysql_wrapper.MySQLdbWrapper.serv_topic`

Definition at line 54 of file `mysql_wrapper.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper.py`

7.14 QrCode Class Reference

Structure holding the essential info for a QR code.

```
#include <qr_detector.h>
```

Public Attributes

- `cv::Point` [center](#)
- `std::string` [message](#)

7.14.1 Detailed Description

Structure holding the essential info for a QR code.

Definition at line 35 of file `qr_detector.h`.

7.14.2 Member Data Documentation

7.14.2.1 `cv::Point QrCode::center`

Definition at line 37 of file `qr_detector.h`.

7.14.2.2 `std::string QrCode::message`

Definition at line 38 of file `qr_detector.h`.

The documentation for this class was generated from the following file:


- `/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detector.h`

7.15 QrDetection Class Reference

Uptakes the task of setting up the ROS service callbacks towards qr detection.

```
#include <qr_detection.h>
```

Collaboration diagram for QrDetection:



Public Member Functions

- [QrDetection](#) (void)
Default constructor.
- bool [qrDetectionCallback](#) (rapp_platform_ros_communications::QrDetectionRosSrv::Request &req, rapp_platform_ros_communications::QrDetectionRosSrv::Response &res)
The qr detection ROS service callback.

Private Attributes

- ros::NodeHandle [nh_](#)
- [QrDetector](#) [qr_detector_](#)
- ros::ServiceServer [qrDetectionService_](#)
- std::string [qrDetectionTopic_](#)

7.15.1 Detailed Description

Uptakes the task of setting up the ROS service callbacks towards qr detection.

Definition at line 31 of file qr_detection.h.

7.15.2 Constructor & Destructor Documentation

7.15.2.1 QrDetection::QrDetection (void)

Default constructor.

Definition at line 23 of file qr_detection.cpp.

7.15.3 Member Function Documentation

7.15.3.1 bool QrDetection::qrDetectionCallback (rapp_platform_ros_communications::QrDetectionRosSrv::Request & req, rapp_platform_ros_communications::QrDetectionRosSrv::Response & res)

The qr detection ROS service callback.

Parameters

<i>req</i>	[rapp_platform_ros_communications::QrDetectionRosSrv::Request&] The service request
<i>res</i>	[rapp_platform_ros_communications::QrDetectionRosSrv::Response&] The service response

Returns

bool - The success status of the call

Definition at line 40 of file qr_detection.cpp.

7.15.4 Member Data Documentation

7.15.4.1 ros::NodeHandle QrDetection::nh_ [private]

< The ROS node handle The service server

Definition at line 53 of file qr_detection.h.

7.15.4.2 QrDetector QrDetection::qr_detector_ [private]

Definition at line 62 of file qr_detection.h.

7.15.4.3 ros::ServiceServer QrDetection::qrDetectionService_ [private]

Topic nomeclarure. Holds the qr detection ROS service topic URI

Definition at line 56 of file qr_detection.h.

7.15.4.4 std::string QrDetection::qrDetectionTopic_ [private]

Object of [QrDetection](#) type

Definition at line 59 of file qr_detection.h.

The documentation for this class was generated from the following files:

- /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/[qr_detection.h](#)
- /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/[qr_detection.cpp](#)

7.16 QrDetector Class Reference

Provides the QR detection functionality.

```
#include <qr_detector.h>
```

Public Member Functions

- [QrDetector](#) (void)
Default constructor.
- std::vector< [QrCode](#) > [detectQrs](#) (const cv::Mat &img)
Detects QRs in a cv::Mat.
- std::vector< [QrCode](#) > [findQrs](#) (std::string file_name)
Detects QRs in an image file.

Private Member Functions

- `cv::Mat loadImage (std::string file_name)`
Loads an image into a cv::Mat structure.

7.16.1 Detailed Description

Provides the QR detection functionality.

Definition at line 45 of file qr_detector.h.

7.16.2 Constructor & Destructor Documentation

7.16.2.1 QrDetector::QrDetector (void)

Default constructor.

Definition at line 23 of file qr_detector.cpp.

7.16.3 Member Function Documentation

7.16.3.1 std::vector< QrCode > QrDetector::detectQrs (const cv::Mat & input_frame)

Detects QRs in a cv::Mat.

Parameters

<i>img</i>	[const cv::Mat&] The input image in cv::Mat form
------------	--

Returns

`std::vector<QrCode>` The detected QR codes

< [QrCode](#) scanner

Definition at line 43 of file qr_detector.cpp.

7.16.3.2 std::vector< QrCode > QrDetector::findQrs (std::string file_name)

Detects QRs in an image file.

Parameters

<i>file_name</i>	[std::string] The input image URI
------------------	-----------------------------------

Returns

`std::vector<QrCode>` The detected QR codes

Definition at line 101 of file qr_detector.cpp.

7.16.3.3 cv::Mat QrDetector::loadImage (std::string file_name) [private]

Loads an image into a cv::Mat structure.

Parameters

<i>file_name</i>	[std::string] The file URI
------------------	----------------------------

Returns

cv::Mat

Definition at line 32 of file qr_detector.cpp.


The documentation for this class was generated from the following files:

- [/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detector.h](#)
- [/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detector.cpp](#)


7.17 rapp_exceptions.RappError Class Reference

Inherits Exception and is used to catch only RAPP-specific exceptions.

Inheritance diagram for rapp_exceptions.RappError:



Collaboration diagram for rapp_exceptions.RappError:



Public Member Functions

- [def __init__](#)

- [def __init__](#)
Default constructor.
- [def __str__](#)
- [def __str__](#)
Returns the error in a string form.

Public Attributes

- [value](#)

7.17.1 Detailed Description

Inherits Exception and is used to catch only RAPP-specific exceptions.

Error handling in RAPP

Definition at line 21 of file rapp_exceptions.py.

7.17.2 Constructor & Destructor Documentation

7.17.2.1 `def rapp_exceptions.RappError.__init__(self, value)`

Default constructor.

Definition at line 25 of file rapp_exceptions.py.

7.17.2.2 `def rapp_exceptions.RappError.__init__(self, value)`

Definition at line 22 of file rapp_exceptions.py.

7.17.3 Member Function Documentation

7.17.3.1 `def rapp_exceptions.RappError.__str__(self)`

Definition at line 25 of file rapp_exceptions.py.

7.17.3.2 `def rapp_exceptions.RappError.__str__(self)`

Returns the error in a string form.

Definition at line 29 of file rapp_exceptions.py.

7.17.4 Member Data Documentation

7.17.4.1 `rapp_exceptions.RappError.value`

Definition at line 26 of file rapp_exceptions.py.


The documentation for this class was generated from the following file:

- /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/rapp_exceptions.py


7.18 rapp_speech_detection_sphinx4.rapp_exceptions.RappError Class Reference

Provides a RAPP specific exception.

Inheritance diagram for rapp_speech_detection_sphinx4.rapp_exceptions.RappError:



Collaboration diagram for rapp_speech_detection_sphinx4.rapp_exceptions.RappError:



Public Member Functions

- `def __init__`
- `def __str__`

Public Attributes

- `value`

7.18.1 Detailed Description

Provides a RAPP specific exception.

Error handling in RAPP

Definition at line 21 of file rapp_exceptions.py.

7.18.2 Constructor & Destructor Documentation

7.18.2.1 `def rapp_speech_detection_sphinx4.rapp_exceptions.RappError.__init__(self, value)`

Definition at line 24 of file rapp_exceptions.py.

7.18.3 Member Function Documentation

7.18.3.1 `def rapp_speech_detection_sphinx4.rapp_exceptions.RappError.__str__(self)`

Definition at line 27 of file rapp_exceptions.py.

7.18.4 Member Data Documentation

7.18.4.1 `rapp_speech_detection_sphinx4.rapp_exceptions.RappError.value`

Definition at line 25 of file rapp_exceptions.py.

The documentation for this class was generated from the following file:

- [/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_exceptions.py](#)

7.19 rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile Class Reference

Evaluates the noise profile for an audio file.

Public Member Functions

- `def __init__`
Performs initializations.
- `def setNoise_profile`
Evaluates the audio profile.

Public Attributes

- `utilities`

7.19.1 Detailed Description

Evaluates the noise profile for an audio file.

Definition at line 31 of file rapp_set_noise_profile.py.

7.19.2 Constructor & Destructor Documentation

7.19.2.1 `def rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile.__init__(self)`

Performs initializations.

Definition at line 34 of file `rapp_set_noise_profile.py`.

7.19.3 Member Function Documentation

7.19.3.1 `def rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile.setNoise_profile(self, user, noise_audio_file, audio_file_type)`

Evaluates the audio profile.

Handles service callback [rapp_audio_processing.AudioProcessing::setNoiseProfileCallback](#)

Parameters

<i>user</i>	[string] The system user, for environmental variable access
<i>noise_audio_file</i>	[string] Noise audio file path
<i>audio_type</i>	[string] Noise audio file's type

Definition at line 45 of file `rapp_set_noise_profile.py`.

7.19.4 Member Data Documentation

7.19.4.1 `rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile.utilities`

Definition at line 35 of file `rapp_set_noise_profile.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_set_noise_profile.py`

7.20 rapp_audio_processing.rapp_sox_denoise.SoxDenoise Class Reference

Performs denoising on an audio file employing Sox application.

Public Member Functions

- `def soxDenoise`
Performs denoising employing Sox application.

7.20.1 Detailed Description

Performs denoising on an audio file employing Sox application.

Definition at line 29 of file `rapp_sox_denoise.py`.

7.20.2 Member Function Documentation

7.20.2.1 `def rapp_audio_processing.rapp_sox_denoise.SoxDenoise.soxDenoise (self, user, audio_type, audio_file, denoised_audio_file, scale)`

Performs denoising employing Sox application.

Handles service callback [rapp_audio_processing.AudioProcessing::denoiseCallback](#)

Parameters

<i>user</i>	[string] The system user, for environmental variable access
<i>audio_file</i>	[string] Audio file path
<i>audio_type</i>	[string] Audio file's type
<i>denoised_audio_file</i>	[string] Path to write denoised audio file
<i>scale</i>	[float] Energy denoise scale

Definition at line 41 of file `rapp_sox_denoise.py`.


The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_sox_denoise.py`

7.21 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4` Class Reference


Provides a complete Rapp Sphinx Entity.

Inheritance diagram for `rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4`:



Collaboration diagram for `rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4`:

Sphinx4:



Public Member Functions

- def [__init__](#)
Constructor performing initializations.
- def [speechRecognitionBatch](#)
Performs [Sphinx4](#) configuration and speech recognition.

Private Member Functions

- def [_configureSpeechRecognition](#)
Performs [Sphinx4](#) configuration.
- def [_speechRecognition](#)
Performs [Sphinx4](#) speech recognition.

Private Attributes

- [_authentication_service](#)
The database authentication service client.
- [_configuration_params](#)
The Sphinx configuration parameters.
- [_english_support](#)
English creates necessary files for english speech recognition.
- [_greek_support](#)
Greek_support creates necessary files for Greek speech recognition.
- [_sphinx4](#)
The sphinx wrapper communicates with the actual Sphinx.java process.
- [_use_db_authentication](#)
Defines whether database authentication should be used.
- [_word_mapping](#)
A dictionary to transform the englified greek words to actual greek words.

7.21.1 Detailed Description

Provides a complete Rapp Sphinx Entity.

Maintains a complete Rapp Sphinx Entity for the [speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode](#) to perform the speech recognition.

Definition at line 64 of file `speech_recognition_sphinx4.py`.

7.21.2 Constructor & Destructor Documentation

7.21.2.1 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4.__init__(self)`

Constructor performing initializations.

Definition at line 67 of file `speech_recognition_sphinx4.py`.

7.21.3 Member Function Documentation

7.21.3.1 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4._configureSpeechRecognition(self, req) [private]`

Performs [Sphinx4](#) configuration.

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4ConfigureSrvRequest</code>] The sphinx configuration request
------------	--

Returns

`res` [`rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4ConfigureSrvRequest`] The sphinx configuration response

Definition at line 197 of file `speech_recognition_sphinx4.py`.

7.21.3.2 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4._speechRecognition(self, req) [private]`

Performs [Sphinx4](#) speech recognition.

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4SrvRequest</code>] The speech recognition request
------------	---

Returns

`res` [`rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4SrvResponse`] The speech recognition response

Definition at line 172 of file `speech_recognition_sphinx4.py`.

7.21.3.3 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4.speechRecognitionBatch(self, req)`

Performs [Sphinx4](#) configuration and speech recognition.

Parameters

<i>req</i>	[rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4TotalSrvRequest] The speech recognition request
------------	---

Returns

res [rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4TotalSrvResponse] The speech recognition response

Definition at line 129 of file speech_recognition_sphinx4.py.

7.21.4 Member Data Documentation

7.21.4.1 rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4_authentication_service [private]

The database authentication service client.

Used to identify user performed the speech recognition request. (see [mysql_wrapper.MySQLdbWrapper.fetchData](#))

Definition at line 102 of file speech_recognition_sphinx4.py.

7.21.4.2 rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4_configuration_params [private]

The Sphinx configuration parameters.

(see [sphinx4_configuration_params.SphinxConfigurationParams](#))

Definition at line 85 of file speech_recognition_sphinx4.py.

7.21.4.3 rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4_english_support [private]

English creates necessary files for english speech recognition.

(see [english_support.EnglishSupport](#))

Definition at line 81 of file speech_recognition_sphinx4.py.

7.21.4.4 rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4_greek_support [private]

Greek_support creates necessary files for Greek speech recognition.

(see [greek_support.GreekSupport](#))

Definition at line 77 of file speech_recognition_sphinx4.py.

7.21.4.5 rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4_sphinx4 [private]

The sphinx wrapper communicates with the actual Sphinx.java process.

(see [sphinx4_wrapper.Sphinx4Wrapper](#))

Definition at line 73 of file speech_recognition_sphinx4.py.

7.21.4.6 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4._use_db_authentication` [private]

Defines whether database authentication should be used.

Definition at line 91 of file `speech_recognition_sphinx4.py`.

7.21.4.7 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4._word_mapping` [private]

A dictionary to transform the englified greek words to actual greek words.

Definition at line 88 of file `speech_recognition_sphinx4.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/speech_recognition_sphinx4.py`

7.22 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.-SpeechRecognitionSphinx4HandlerNode` Class Reference

Maintains Sphinx instances to perform speech recognition.

Public Member Functions

- `def __init__`
Initializes the subprocesses and the services (constructor)
- `def handleSpeechRecognitionCallback`
The callback to perform speech recognition.

Private Member Functions

- `def _calculateRequestHash`
Calculates the service request sha1 hash for process handling purposes.

Private Attributes

- `_availableProcesses`
The subprocesses structure that contains information used for the subprocess handling.
- `_lock`
Thread conditional variable used for the subprocess scheduling.
- `_speech_recognition_batch_service`
Ros service server for sphinx speech recognition.
- `_threadCounter`
Total service callback threads waiting to execute.
- `_threads`
The number of child subprocesses.

7.22.1 Detailed Description

Maintains Sphinx instances to perform speech recognition.

Maintains a number of child processes to perform speech recognition utilizing [Sphinx4](#) ([rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4](#)). Provides ros services and handles the requests according to the child processes' status.

Definition at line 43 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.2 Constructor & Destructor Documentation

7.22.2.1 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.__init__(self)`

Initializes the subprocesses and the services (constructor)

Definition at line 46 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.3 Member Function Documentation

7.22.3.1 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode._calculateRequestHash(self, req) [private]`

Calculates the service request sha1 hash for process handling purposes.

Hash is used to identify common request configurations for proper subprocess selection. (Requests with common requests do not require reconfiguration reducing computation time)

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4TotalSrvRequest</code>] The service request
------------	---

Returns

hexdigest [string] The hash digest containing only hexadecimal digits

Definition at line 135 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.3.2 `def rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.handleSpeechRecognitionCallback(self, req)`

The callback to perform speech recognition.

Parameters

<i>req</i>	[<code>rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4TotalSrvRequest</code>] The service request
------------	---

Returns

res [`rapp_platform_ros_communications::SpeechDetectionSphinx4Wrapper::SpeechRecognitionSphinx4TotalSrvResponse`] The service response

Definition at line 79 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.4 Member Data Documentation

7.22.4.1 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.availableProcesses` [private]

The subprocesses structure that contains information used for the subprocess handling.

Definition at line 54 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.4.2 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.lock` [private]

Thread conditional variable used for the subprocess scheduling.

Definition at line 61 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.4.3 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.speech_recognition_batch_service` [private]

Ros service server for sphinx speech recognition.

Definition at line 71 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.4.4 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.threadCounter` [private]

Total service callback threads waiting to execute.

Definition at line 63 of file `speech_recognition_sphinx4_handler_node.py`.

7.22.4.5 `rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode.threads` [private]

The number of child subprocesses.

Definition at line 49 of file `speech_recognition_sphinx4_handler_node.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/speech_recognition_sphinx4_handler_node.py`

7.23 `speech_recognition_google.SpeechToTextGoogle` Class Reference

Implements calls the Google ASR API.

Public Member Functions

- `def __init__`
Default constructor.
- `def speech_to_text`
Performs the call to Google API.
- `def speech_to_text_callback`
The service callback.

Public Attributes

- [serv](#)
- [serv_topic](#)

7.23.1 Detailed Description

Implements calls the Google ASR API.

Definition at line 57 of file `speech_recognition_google.py`.

7.23.2 Constructor & Destructor Documentation

7.23.2.1 `def speech_recognition_google.SpeechToTextGoogle.__init__(self)`

Default constructor.

Declares the service callback

Definition at line 60 of file `speech_recognition_google.py`.

7.23.3 Member Function Documentation

7.23.3.1 `def speech_recognition_google.SpeechToTextGoogle.speech_to_text(self, file_path, user, audio_file_type, language)`

Performs the call to Google API.

Parameters

<i>file_path</i>	[string] The audio file
<i>user</i>	[string] The username
<i>audio_type</i>	[string] Used to check if denoising is needed. Can be one of headset, nao_ogg, nao_wav_1-_ch, nao_wav_4_ch
<i>language</i>	[string] The language in which the ASR will be performed

Returns

The transcript from Google

Definition at line 123 of file `speech_recognition_google.py`.

7.23.3.2 `def speech_recognition_google.SpeechToTextGoogle.speech_to_text_callback(self, req)`

The service callback.

Parameters

<i>req</i>	[SpeechToTextSrvRequest] The ROS service request
------------	--

Definition at line 71 of file `speech_recognition_google.py`.

7.23.4 Member Data Documentation

7.23.4.1 `speech_recognition_google.SpeechToTextGoogle.serv`

Definition at line 66 of file `speech_recognition_google.py`.

7.23.4.2 `speech_recognition_google.SpeechToTextGoogle.serv_topic`

Definition at line 62 of file `speech_recognition_google.py`.


The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/speech_recognition_google.py`

7.24 Sphinx4 Class Reference

Performs speech recognition employing Sphinx.

Collaboration diagram for Sphinx4:



Static Public Member Functions

- static void `main` (`String[] args`) throws `IOException`
The main function.
- static void `updateConfiguration` () throws `IOException`
Updates the Sphinx configuration.

Static Public Attributes

- static `String` `acoustic_model_path` = ""
- static `String` `acoustic_model_path_prev` = ""
- static `BufferedReader` `bufferRead`
- static `PrintWriter` `bufferWrite`
- static `ConfigurationManager` `cm`
- static `Configuration` `configuration` = new `Configuration`()
- static `String` `configuration_model_path` = ""
- static `String` `configuration_model_path_prev` = ""
- static `String` `dictionary_path` = ""
- static `String` `dictionary_path_prev` = ""
- static `boolean` `grammar_enabled` = false
- static `boolean` `grammar_enabled_prev` = false
- static `String` `grammar_model_file_path` = ""
- static `String` `grammar_model_file_path_prev` = ""
- static `String` `grammar_model_folder_path` = ""
- static `String` `grammar_model_folder_path_prev` = ""
- static `String` `language_path` = ""
- static `String` `language_path_prev` = ""
- static `StreamSpeechRecognizer` `recognizer`

7.24.1 Detailed Description

Performs speech recognition employing Sphinx.

Communicates with [rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper](#) via socket to configure Sphinx and perform the speech recognition and returns the result.

Definition at line 49 of file Sphinx4.java.

7.24.2 Member Function Documentation

7.24.2.1 `static void Sphinx4.main (String[] args) throws IOException` `[inline], [static]`

The main function.

Creates the Sphinx process and awaits commands from [rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper](#) to update the cconfiguration or perform the recognition.

Definition at line 134 of file Sphinx4.java.

7.24.2.2 `static void Sphinx4.updateConfiguration () throws IOException` `[inline], [static]`

Updates the Sphinx configuration.

Definition at line 79 of file Sphinx4.java.

7.24.3 Member Data Documentation

7.24.3.1 `String Sphinx4.acoustic_model_path = ""` `[static]`

Definition at line 57 of file Sphinx4.java.

7.24.3.2 `String Sphinx4.acoustic_model_path_prev = ""` `[static]`

Definition at line 58 of file Sphinx4.java.

7.24.3.3 `BufferedReader Sphinx4.bufferRead` `[static]`

Definition at line 72 of file Sphinx4.java.

7.24.3.4 `PrintWriter Sphinx4.bufferWrite` `[static]`

Definition at line 73 of file Sphinx4.java.

7.24.3.5 `ConfigurationManager Sphinx4.cm` `[static]`

Definition at line 69 of file Sphinx4.java.

7.24.3.6 `Configuration Sphinx4.configuration = new Configuration()` `[static]`

Definition at line 68 of file Sphinx4.java.

7.24.3.7 `String Sphinx4.configuration_model_path = ""` `[static]`

Definition at line 65 of file Sphinx4.java.

7.24.3.8 `String Sphinx4.configuration_model_path_prev = ""` `[static]`

Definition at line 66 of file Sphinx4.java.

7.24.3.9 `String Sphinx4.dictionary_path = ""` `[static]`

Definition at line 51 of file Sphinx4.java.

7.24.3.10 `String Sphinx4.dictionary_path_prev = ""` `[static]`

Definition at line 52 of file Sphinx4.java.

7.24.3.11 `boolean Sphinx4.grammar_enabled = false` `[static]`

Definition at line 75 of file Sphinx4.java.

7.24.3.12 `boolean Sphinx4.grammar_enabled_prev = false` `[static]`

Definition at line 76 of file Sphinx4.java.

7.24.3.13 `String Sphinx4.grammar_model_file_path = ""` `[static]`

Definition at line 60 of file Sphinx4.java.

7.24.3.14 `String Sphinx4.grammar_model_file_path_prev = ""` `[static]`

Definition at line 61 of file Sphinx4.java.

7.24.3.15 `String Sphinx4.grammar_model_folder_path = ""` `[static]`

Definition at line 62 of file Sphinx4.java.

7.24.3.16 `String Sphinx4.grammar_model_folder_path_prev = ""` `[static]`

Definition at line 63 of file Sphinx4.java.

7.24.3.17 `String Sphinx4.language_path = ""` `[static]`

Definition at line 54 of file Sphinx4.java.

7.24.3.18 `String Sphinx4.language_path_prev = ""` `[static]`

Definition at line 55 of file Sphinx4.java.

7.24.3.19 StreamSpeechRecognizer Sphinx4.recognizer [static]

Definition at line 70 of file Sphinx4.java.


The documentation for this class was generated from the following file:

- /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/Sphinx4.java


7.25 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper Class Reference

Contains the Sphinx subprocess and is responsible for configuring Sphinx and performing the recognition request.

Inheritance diagram for rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper:



Collaboration diagram for rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper:



Public Member Functions

- def [__init__](#)
Constructor Initiates service clients.
- def [configureSphinx](#)

- *Perform [Sphinx4](#) configuration.*
- `def initializeSphinx`
Perform [Sphinx4](#) initialization Initiates Sphinx subprocess, sets up socket IPC and configures Sphinx subprocess.
- `def performSpeechRecognition`
Performs the speech recognition and returns a list of words.

Private Member Functions

- `def _callSphinxJava`
Communicate with Sphinx subprocess to initiate recognition and fetch results.
- `def _createProcessingProfile`
Creates audio profile based on the audio type for processing purposes.
- `def _createSocket`
Creates socket IPC between self and Sphinx subprocess Creates the socket server with a system provided port, which is pass as an argument to the created subprocess.
- `def _performEnergyDenoising`
Perform energy denoise.
- `def _readLine`
Helper function for getting input from IPC with Sphinx subprocess.
- `def _respawnSphinx`
Respawns Sphinx subprocess, if it terminates abruptly.

Private Attributes

- `_allow_sphinx_output`
- `_audio_transform_srv`
Transform audio service client.
- `_conf`
Sphinx configuration.
- `_denoise_service`
Denoise service client.
- `_detect_silence_service`
Detect silence service client.
- `_energy_denoise_service`
Energy denoise service client.
- `_sphinx_socket`
The IPC socket.
- `_sphinx_socket_PORT`
The IPC socket port.
- `_sphinxDied`
Sphinx status flag.
- `_sphinxSubprocess`
The Sphinx subprocess.

7.25.1 Detailed Description

Contains the Sphinx subprocess and is responsible for configuring Sphinx and performing the recognition request.

Initializes a Sphinx.java subprocess and creates an IPC using sockets. It is responsible for interacting with Sphinx via the socket to send configuration params/instructions and initialize a recognition procedure.

Definition at line 46 of file sphinx4_wrapper.py.

7.25.2 Constructor & Destructor Documentation

7.25.2.1 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.__init__(self)`

Constructor Initiates service clients.

Definition at line 50 of file sphinx4_wrapper.py.

7.25.3 Member Function Documentation

7.25.3.1 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.callSphinxJava(self, audio_file)` [private]

Communicate with Sphinx subprocess to initiate recognition and fetch results.

Parameters

<i>audio_file</i>	[string] The audio file path
-------------------	------------------------------

Returns

words [list::string] The Sphinx result

Definition at line 407 of file sphinx4_wrapper.py.

7.25.3.2 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.createProcessingProfile(self, audio_type)` [private]

Creates audio profile based on the audio type for processing purposes.

Defines a set of audio processing procedures (i.e. denoising) to be performed on the audio file and the parameters of the procedures. Aims to improve to audio file quality to improve speech recognition results.

Parameters

<i>audio_type</i>	[string] The audio type
-------------------	-------------------------

Returns

processingProfile [dictionary] The profile attributes

Definition at line 187 of file sphinx4_wrapper.py.

7.25.3.3 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.createSocket(self)` [private]

Creates socket IPC between self and Sphinx subprocess Creates the socket server with a system provided port, which is pass as an argument to the created subprocess.

Definition at line 147 of file sphinx4_wrapper.py.

7.25.3.4 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.performEnergyDenoising(self, next_audio_file, audio_file, scale)` [private]

Perform energy denoise.

Calls energy denoise service `rapp_audio_processing.rapp_audio_processing.AudioProcessing::energy_denoise` (see also [rapp_audio_processing.rapp_energy_denoise.EnergyDenoise::energyDenoise](#))

Parameters

<i>audio_file</i>	[string] The audio file path
<i>scale</i>	[float] The scale parameter for the denoising procedure

Returns

file_path [string] The path of the denoised file

Definition at line 394 of file sphinx4_wrapper.py.

7.25.3.5 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._readLine (self) [private]`

Helper function for getting input from IPC with Sphinx subprocess.

Returns

line [string] A buffer read from socket

Definition at line 113 of file sphinx4_wrapper.py.

7.25.3.6 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._respawnSphinx (self) [private]`

Respawns Sphinx subprocess, if it terminates abruptly.

Definition at line 434 of file sphinx4_wrapper.py.

7.25.3.7 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.configureSphinx (self, conf)`

Perform [Sphinx4](#) configuration.

Parameters

<i>conf</i>	[dictionary] Contains the configuration parameters
-------------	--

Definition at line 158 of file sphinx4_wrapper.py.

7.25.3.8 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.initializeSphinx (self, conf)`

Perform [Sphinx4](#) initialization Initiates Sphinx subprocess, sets up socket IPC and configures Sphinx subprocess.

Parameters

<i>conf</i>	[dictionary] Contains the configuration parameters
-------------	--

Definition at line 123 of file sphinx4_wrapper.py.

7.25.3.9 `def rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper.performSpeechRecognition (self, audio_file, audio_type, user)`

Performs the speech recognition and returns a list of words.

Parameters

<i>audio_file</i>	[string] The audio file's name
<i>audio_type</i>	[string] The audio file's type

Returns

words [list::string] The result words

Exceptions

<i>RappError</i>	Audio transformation error
------------------	----------------------------

Definition at line 247 of file sphinx4_wrapper.py.

7.25.4 Member Data Documentation**7.25.4.1 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._allow_sphinx_output** [private]

Definition at line 115 of file sphinx4_wrapper.py.

7.25.4.2 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._audio_transform_srv [private]

Transform audio service client.

rapp_audio_processing.rapp_audio_processing.AudioProcessing::transform_audio

Definition at line 107 of file sphinx4_wrapper.py.

7.25.4.3 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._conf [private]

Sphinx configuration.

Definition at line 53 of file sphinx4_wrapper.py.

7.25.4.4 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._denoise_service [private]

Denoise service client.

rapp_audio_processing.rapp_audio_processing.AudioProcessing::denoise

Definition at line 89 of file sphinx4_wrapper.py.

7.25.4.5 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._detect_silence_service [private]

Detect silence service client.

rapp_audio_processing.rapp_audio_processing.AudioProcessing::detect_silence

Definition at line 101 of file sphinx4_wrapper.py.

7.25.4.6 rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._energy_denoise_service [private]

Energy denoise service client.

rapp_audio_processing.rapp_audio_processing.AudioProcessing::energy_denoise

Definition at line 95 of file sphinx4_wrapper.py.

7.25.4.7 `rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._sphinx_socket` [private]

The IPC socket.

Definition at line 58 of file `sphinx4_wrapper.py`.

7.25.4.8 `rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._sphinx_socket_PORT` [private]

The IPC socket port.

Definition at line 60 of file `sphinx4_wrapper.py`.

7.25.4.9 `rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._sphinxDied` [private]

Sphinx status flag.

Definition at line 55 of file `sphinx4_wrapper.py`.

7.25.4.10 `rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper._sphinxSubprocess` [private]

The Sphinx subprocess.

Definition at line 63 of file `sphinx4_wrapper.py`.


The documentation for this class was generated from the following file:

- [/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/sphinx4_wrapper.py](#)

7.26 `rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams` Class Reference


Contains the parameters required for the Sphinx configuration.

Inheritance diagram for `rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams`:



Collaboration diagram for `rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams`:

Params:



Public Member Functions

- `def __init__`
Initializes an empty configuration (constructor)
- `def equals`
Checks if a [SphinxConfigurationParams](#) instance equals self.

Private Attributes

- `_grammar`
Sphinx grammar attribute.
- `_language`
The language of the request.
- `_sentences`
Sphinx sentence attribute.
- `_words`
The words to be identified.

7.26.1 Detailed Description

Contains the parameters required for the Sphinx configuration.

Definition at line 25 of file sphinx4_configuration_params.py.

7.26.2 Constructor & Destructor Documentation

7.26.2.1 `def rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams.__init__(self)`

Initializes an empty configuration (constructor)

Definition at line 28 of file sphinx4_configuration_params.py.

7.26.3 Member Function Documentation

7.26.3.1 `def rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams.equals (self,
params)`

Checks if a [SphinxConfigurationParams](#) instance equals self.

Parameters

<i>params</i>	[SphinxConfigurationParams] The class instance
<i>status</i>	[bool] True if configurations match

Definition at line 45 of file sphinx4_configuration_params.py.

7.26.4 Member Data Documentation

7.26.4.1 rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams._grammar
[private]

Sphinx grammar attribute.

Definition at line 36 of file sphinx4_configuration_params.py.

7.26.4.2 rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams._language
[private]

The language of the request.

Definition at line 32 of file sphinx4_configuration_params.py.

7.26.4.3 rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams._sentences
[private]

Sphinx sentence attribute.

Definition at line 38 of file sphinx4_configuration_params.py.

7.26.4.4 rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams._words [private]

The words to be identified.

Definition at line 34 of file sphinx4_configuration_params.py.

The documentation for this class was generated from the following file:

- /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/[sphinx4-configuration_params.py](#)

7.27 text_to_speech_espeak.TextToSpeechEspeak Class Reference

Public Member Functions

- def [__init__](#)
- def [text_to_speech_callback](#)

Public Attributes

- [serv](#)
- [serv_topic](#)

7.27.1 Detailed Description

Definition at line 33 of file `text_to_speech_espeak.py`.

7.27.2 Constructor & Destructor Documentation

7.27.2.1 `def text_to_speech_espeak.TextToSpeechEspeak.__init__(self)`

Definition at line 35 of file `text_to_speech_espeak.py`.

7.27.3 Member Function Documentation

7.27.3.1 `def text_to_speech_espeak.TextToSpeechEspeak.text_to_speech_callback(self, req)`

Definition at line 45 of file `text_to_speech_espeak.py`.

7.27.4 Member Data Documentation

7.27.4.1 `text_to_speech_espeak.TextToSpeechEspeak.serv`

Definition at line 41 of file `text_to_speech_espeak.py`.

7.27.4.2 `text_to_speech_espeak.TextToSpeechEspeak.serv_topic`

Definition at line 37 of file `text_to_speech_espeak.py`.

The documentation for this class was generated from the following file:

- `/home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/text_to_speech_espeak.py`

7.28 `rapp_audio_processing.rapp_transform_audio.TransformAudio` Class Reference

Provides audio type tranformation functionalities.

Public Member Functions

- `def transform_audio`
Performs the audio transformation.

Private Member Functions

- `def _assertArgs`
Verifies the existence of the required arguments.
- `def _convertType`
Performs audio conversion.
- `def _validateSourceType`
Validates that the provided audio type match the file extension.

7.28.1 Detailed Description

Provides audio type tranformation functionalities.

Allows the transformation of an audio file to a different format. Supports the alteration of the type (i.e. headset, nao_wav_1_ch etc.), the sample rate, the audio channel number, the audio format and the audio name. Handles transform audio service callback (rapp_audio_processing.rapp_audio_processing.AudioProcessing::transform_audio)

Definition at line 32 of file rapp_transform_audio.py.

7.28.2 Member Function Documentation

7.28.2.1 `def rapp_audio_processing.rapp_transform_audio.TransformAudio._assertArgs (self, source_type, source_name, target_type, target_name, target_channels, target_rate) [private]`

Verifies the existence of the required arguments.

Parameters

<i>source_type</i>	[string] The source audio file's type
<i>source_name</i>	[string] The source audio file's name
<i>target_type</i>	[string] The target audio file's type
<i>target_name</i>	[string] The target audio file's name
<i>target_channels</i>	[string] The target audio's channel number
<i>target_rate</i>	[string] The target audio's sample rate

Exceptions

<i>Exception</i>	Arguments are invalid
------------------	-----------------------

Definition at line 76 of file rapp_transform_audio.py.

7.28.2.2 `def rapp_audio_processing.rapp_transform_audio.TransformAudio._convertType (self, source_type, source_name, target_type, target_name, target_channels, target_rate) [private]`

Performs audio conversion.

Parameters

<i>source_type</i>	[string] The source audio file's type
<i>source_name</i>	[string] The source audio file's name
<i>target_type</i>	[string] The target audio file's type
<i>target_name</i>	[string] The target audio file's name
<i>target_channels</i>	[string] The target audio's channel number
<i>target_rate</i>	[string] The target audio's sample rate

Exceptions

<i>Exception</i>	Conversion malfunction
------------------	------------------------

Definition at line 101 of file rapp_transform_audio.py.

7.28.2.3 `def rapp_audio_processing.rapp_transform_audio.TransformAudio._validateSourceType (self, source_type, name) [private]`

Validates that the provided audio type match the file extension.

Parameters

<i>source_type</i>	[string] The source audio file's type
<i>name</i>	[string] The source audio file's name

Exceptions

<i>Exception</i>	Audio type/file type mismatch
------------------	-------------------------------

Definition at line 139 of file rapp_transform_audio.py.

7.28.2.4 `def rapp_audio_processing.rapp_transform_audio.TransformAudio.transform_audio (self, source_type, source_name, target_type, target_name, target_channels, target_rate)`

Performs the audio transformation.

Parameters

<i>source_type</i>	[string] The source audio file's type
<i>source_name</i>	[string] The source audio file's name
<i>target_type</i>	[string] The target audio file's type
<i>target_name</i>	[string] The target audio file's name
<i>target_channels</i>	[string] The target audio's channel number
<i>target_rate</i>	[string] The target audio's sample rate

Returns

status [string] The status of the transformation procedure
filename [string] The name of the produced file

Definition at line 45 of file rapp_transform_audio.py.

The documentation for this class was generated from the following file:

- [/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_transform_audio.py](#)

7.29 rapp_audio_processing.rapp_utilities.Utilities Class Reference

Provides audio processing utilities.

Public Member Functions

- `def cleanup`
Removes a number of files.

7.29.1 Detailed Description

Provides audio processing utilities.

Definition at line 27 of file rapp_utilities.py.

7.29.2 Member Function Documentation

7.29.2.1 `def rapp_audio_processing.rapp_utilities.Utilities.cleanup (self, files)`

Removes a number of files.

Parameters

<i>files</i>	[list::string] The to be deleted files' paths
--------------	---

Definition at line 32 of file rapp_utilities.py.

The documentation for this class was generated from the following file:

- /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/[rapp_utilities.py](#)

Chapter 8

File Documentation

8.1 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/__init__.py File Reference

Namespaces

- [rapp_audio_processing](#)

8.2 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/__init__.py File Reference

Namespaces

- [rapp_speech_detection_sphinx4](#)

8.3 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_audio_processing.py File Reference

Classes

- class [rapp_audio_processing.rapp_audio_processing.AudioProcessing](#)
Provides audio processing utilities.

Namespaces

- [rapp_audio_processing.rapp_audio_processing](#)

Variables

- tuple [rapp_audio_processing.rapp_audio_processing.AudioProcessingNode](#) = `AudioProcessing()`

8.4 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_detect_silence.py File Reference

Classes

- class [rapp_audio_processing.rapp_detect_silence.DetectSilence](#)
Performs silence detection on an audio file.

Namespaces

- [rapp_audio_processing.rapp_detect_silence](#)

8.5 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_energy_denoise.py File Reference

Classes

- class [rapp_audio_processing.rapp_energy_denoise.EnergyDenoise](#)
Performs energy denoising on an audio file.

Namespaces

- [rapp_audio_processing.rapp_energy_denoise](#)

8.6 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_set_noise_profile.py File Reference

Classes

- class [rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile](#)
Evaluates the noise profile for an audio file.

Namespaces

- [rapp_audio_processing.rapp_set_noise_profile](#)

8.7 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_sox_denoise.py File Reference

Classes

- class [rapp_audio_processing.rapp_sox_denoise.SoxDenoise](#)
Performs denoising on an audio file employing Sox application.

Namespaces

- [rapp_audio_processing.rapp_sox_denoise](#)

8.8 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_transform_audio.py File Reference

Classes

- class [rapp_audio_processing.rapp_transform_audio.TransformAudio](#)
Provides audio type tranformation functionalities.

Namespaces

- [rapp_audio_processing.rapp_transform_audio](#)

8.9 /home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_utilities.py File Reference

Classes

- class [rapp_audio_processing.rapp_utilities.Utilities](#)
Provides audio processing utilities.

Namespaces

- [rapp_audio_processing.rapp_utilities](#)

8.10 /home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise.py File Reference

Classes

- class [cognitive_exercise.CognitiveExercise](#)
The Cognitive exercise ros node.

Namespaces

- [cognitive_exercise](#)

8.11 /home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise_main.py File Reference

Namespaces

- [cognitive_exercise_main](#)


Variables

- tuple [cognitive_exercise_main.CognitiveExerciseNode](#) = [CognitiveExercise\(\)](#)
The main function that initiates the CognitiveExercise ROS Node.


8.12 /home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detection.h File Reference

```
#include "ros/ros.h"
#include <rapp_platform_ros_communications/FaceDetectionRosSrv.h>
#include <face_detection/face_detector.h>
```

Include dependency graph for face_detection.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [FaceDetection](#)

Class [FaceDetection](#) uptakes the task of handling the ROS service callbacks.


8.13 /home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detector.h File Reference

```
#include <iostream>
#include <opencv2/core/core.hpp>
#include <opencv2/highgui/highgui.hpp>
#include <opencv2/objdetect/objdetect.hpp>
#include <opencv2/imgproc/imgproc.hpp>
```

Include dependency graph for face_detector.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [FaceDetector](#)

Class that implements a face detection algorithm based on a Haar cascade classifier.

8.14 /home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection.cpp File Reference

```
#include <face_detection/face_detection.h>
```


Include dependency graph for `face_detection.cpp`:



8.15 /home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection_node.cpp File Reference

```
#include <face_detection/face_detection.h>
```

Include dependency graph for `face_detection_node.cpp`:



Functions

- `int main (int argc, char **argv)`

The executable's main function. Creates a ROS multispinner to enable concurrent requests and declares a [Face-Detection](#) object.

8.15.1 Function Documentation

8.15.1.1 `int main (int argc, char ** argv)`


The executable's main function. Creates a ROS multispinner to enable concurrent requests and declares a [Face-Detection](#) object.

Definition at line 24 of file `face_detection_node.cpp`.

8.16 /home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detector.cpp File Reference

```
#include <face_detection/face_detector.h>
```

Include dependency graph for face_detector.cpp:




8.17 /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_wrapper.h File Reference

```
#include <string>
#include <iostream>
#include <json_prolog/prolog.h>
#include <rapp_platform_ros_communications/fetchDataSrv.h>
#include <rapp_platform_ros_communications/writeDataSrv.h>
#include <rapp_platform_ros_communications/updateDataSrv.h>
#include <rapp_platform_ros_communications/StringArrayMsg.h>
#include <rapp_platform_ros_communications/createInstanceSrv.h>
#include <rapp_platform_ros_communications/ontologyInstancesOfSrv.h>
#include <rapp_platform_ros_communications/ontologyLoadDumpSrv.h>
#include <rapp_platform_ros_communications/ontologySubSuperClassesOfSrv.h>
#include <rapp_platform_ros_communications/assertRetractAttributeSrv.h>
#include <rapp_platform_ros_communications/ontologyIsSubSuperClassOfSrv.h>
#include <rapp_platform_ros_communications/returnUserInstancesOfClassSrv.h>
#include <rapp_platform_ros_communications/createOntologyAliasSrv.h>
#include <rapp_platform_ros_communications/userPerformanceCognitiveTests-
Srv.h>
#include <rapp_platform_ros_communications/createCognitiveExerciseTestSrv.-
h>
#include <rapp_platform_ros_communications/cognitiveTestsOfTypeSrv.h>
#include <rapp_platform_ros_communications/recordUserPerformanceCognitive-
TestsSrv.h>
#include <rapp_platform_ros_communications/clearUserPerformanceCognitive-
TestsSrv.h>
```

Include dependency graph for knowrob_wrapper.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [KnowrobWrapper](#)

Class [KnowrobWrapperCommunications](#) contains all the necessary knowrob wrapper functions.


8.18 /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_wrapper_communications.h File Reference

```
#include <knowrob_wrapper/knowrob_wrapper.h>
#include <ros/ros.h>
```

Include dependency graph for knowrob_wrapper_communications.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [KnowrobWrapperCommunications](#)

Class [KnowrobWrapperCommunications](#) uptakes the task of handling the ROS service callbacks.

8.19 /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper.cpp File Reference

```
#include <knowrob_wrapper/knowrob_wrapper.h>
#include <sys/stat.h>
#include <unistd.h>
#include <sstream>
#include <ros/package.h>
#include <fstream>
```

Include dependency graph for knowrob_wrapper.cpp:



Functions

- bool [checkIfFileExists](#) (const char *fileName)
Checks if path exists.
- std::string [intToString](#) (int a)
Converts integer to string.
- std::vector< std::string > [split](#) (std::string str, std::string sep)
Splits string by delimiter.
- std::string [SplitFilename](#) (const std::string &str)
Keeps only the final folder or file from a path.

8.19.1 Function Documentation

8.19.1.1 `bool checkIfFileExists (const char * fileName)`

Checks if path exists.

Parameters

<i>fileName</i>	[char*] The input path
-----------------	------------------------

Returns

out [bool] True if file exists

Definition at line 66 of file knowrob_wrapper.cpp.

8.19.1.2 `std::string intToString (int a)`

Converts integer to string.

Parameters

<i>a</i>	[int] The input integer
----------	-------------------------

Returns

out [string] The output string

Definition at line 42 of file knowrob_wrapper.cpp.

8.19.1.3 `std::vector<std::string> split (std::string str, std::string sep)`

Splits string by delimiter.

Parameters

<i>str</i>	[string] The input string
<i>sep</i>	[string] The delimiter

Returns

arr [std::vector<std::string>] A vector with the string parts as splitted by the delimiter

Definition at line 78 of file knowrob_wrapper.cpp.

8.19.1.4 `std::string SplitFilename (const std::string & str)`

Keeps only the final folder or file from a path.

Parameters

<i>str</i>	[string&] The input path
------------	--------------------------

Returns

out [string] The output filename

Definition at line 54 of file knowrob_wrapper.cpp.

8.20 /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_communications.cpp File Reference

```
#include <knowrob_wrapper/knowrob_wrapper_communications.h>
#include <ros/package.h>
```

Include dependency graph for knowrob_wrapper_communications.cpp:



8.21 /home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_node.cpp File Reference

```
#include <knowrob_wrapper/knowrob_wrapper_communications.h>
```

Include dependency graph for knowrob_wrapper_node.cpp:



Functions

- int [main](#) (int argc, char **argv)

The executable's main function. Creates a ROS multispinner to enable concurrent requests and declares a [KnowrobWrapperCommunications](#) object.

8.21.1 Function Documentation

8.21.1.1 int main (int argc, char ** argv)

The executable's main function. Creates a ROS multispinner to enable concurrent requests and declares a [KnowrobWrapperCommunications](#) object.

Definition at line 28 of file knowrob_wrapper_node.cpp.

8.22 /home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper.py File Reference

Classes

- class [mysql_wrapper.MySQLdbWrapper](#)

The mysql wrapper ros node.

Namespaces

- [mysql_wrapper](#)

8.23 /home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper_main.py File Reference

Namespaces

- [mysql_wrapper_main](#)

Variables


- tuple [mysql_wrapper_main.MySQLWrapperNode](#) = MySQLdbWrapper()

The main function that initiates the rapp mysql wrapper ROS Node.


8.24 /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detection.h File Reference

```
#include "ros/ros.h"
#include <rapp_platform_ros_communications/QrDetectionRosSrv.h>
#include <qr_detection/qr_detector.h>
```

Include dependency graph for qr_detection.h:



This graph shows which files directly or indirectly include this file:



Classes


- class [QrDetection](#)

Uptakes the task of setting up the ROS service callbacks towards qr detection.


8.25 /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detector.h File Reference

```
#include <iostream>
#include <opencv2/core/core.hpp>
#include <opencv2/highgui/highgui.hpp>
#include <opencv2/objdetect/objdetect.hpp>
#include <opencv2/imgproc/imgproc.hpp>
#include <zbar.h>
```

Include dependency graph for qr_detector.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [QrCode](#)

Structure holding the essential info for a QR code.


- class [QrDetector](#)

Provides the QR detection functionality.

8.26 /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection.cpp File Reference

```
#include <qr_detection/qr_detection.h>
```


Include dependency graph for qr_detection.cpp:



8.27 /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection_node.cpp File Reference

```
#include <qr_detection/qr_detection.h>
```

Include dependency graph for qr_detection_node.cpp:



Functions

- `int main (int argc, char **argv)`

The main function. Retrieves the threads parameter in order to enable concurrent service invocation.

8.27.1 Function Documentation

8.27.1.1 `int main (int argc, char ** argv)`


The main function. Retrieves the threads parameter in order to enable concurrent service invocation.

Definition at line 25 of file qr_detection_node.cpp.

8.28 /home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detector.cpp File Reference

```
#include <qr_detection/qr_detector.h>
```

Include dependency graph for qr_detector.cpp:



8.29 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/rapp_exceptions.py File Reference

Classes

- class [rapp_exceptions.RappError](#)
Inherits Exception and is used to catch only RAPP-specific exceptions.

Namespaces

- [rapp_exceptions](#)

8.30 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_exceptions.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.rapp_exceptions.RappError](#)
Provides a RAPP specific exception.

Namespaces

- [rapp_speech_detection_sphinx4.rapp_exceptions](#)

8.31 /home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/rapp_exceptions.py File Reference

Classes

- class [rapp_exceptions.RappError](#)
Inherits Exception and is used to catch only RAPP-specific exceptions.

Namespaces

- [rapp_exceptions](#)

8.32 [/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/speech_recognition_google.py](#) File Reference

Classes

- class [speech_recognition_google.SpeechToTextGoogle](#)

Implements calls the Google ASR API.

Namespaces

- [speech_recognition_google](#)

Variables

- tuple [speech_recognition_google.speech_to_text_node](#) = [SpeechToTextGoogle\(\)](#)

The main function.

8.33 [/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/english_support.py](#) File Reference

Classes

- class [rapp_speech_detection_sphinx4.english_support.EnglishSupport](#)

Allows the creation of configuration files for English Sphinx speech recognition.

Namespaces

- [rapp_speech_detection_sphinx4.english_support](#)

8.34 [/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/global_parameters.py](#) File Reference

Classes

- class [rapp_speech_detection_sphinx4.global_parameters.GlobalParams](#)

Contains global Sphinx parameters.

Namespaces

- [rapp_speech_detection_sphinx4.global_parameters](#)

8.35 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/greek_support.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.greek_support.GreekSupport](#)
Allows the creation of configuration files for Greek Sphinx speech recognition.

Namespaces

- [rapp_speech_detection_sphinx4.greek_support](#)

8.36 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/limited_vocabulary_creator.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.limited_vocabulary_creator.LimitedVocabularyCreator](#)
Creates temporary configuration files for the input limited vocabulary.

Namespaces

- [rapp_speech_detection_sphinx4.limited_vocabulary_creator](#)

8.37 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_tools.py File Reference

Namespaces

- [rapp_speech_detection_sphinx4.rapp_tools](#)

Functions

- def [rapp_speech_detection_sphinx4.rapp_tools.rapp_print](#)

8.38 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/speech_recognition_sphinx4.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4](#)
Provides a complete Rapp Sphinx Entity.

Namespaces

- [rapp_speech_detection_sphinx4.speech_recognition_sphinx4](#)

Variables

- tuple [rapp_speech_detection_sphinx4.speech_recognition_sphinx4.SpeechRecognitionSphinx4Node](#) = [SpeechRecognitionSphinx4\(\)](#)

8.39 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/speech_recognition_sphinx4_handler_node.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode](#)
Maintains Sphinx instances to perform speech recognition.

Namespaces

- [rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node](#)

Variables

- tuple [rapp_speech_detection_sphinx4.speech_recognition_sphinx4_handler_node.SpeechRecognitionSphinx4HandlerNode](#) = [SpeechRecognitionSphinx4HandlerNode\(\)](#)

8.40 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/sphinx4_configuration_params.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.sphinx4_configuration_params.SphinxConfigurationParams](#)
Contains the parameters required for the Sphinx configuration.

Namespaces

- [rapp_speech_detection_sphinx4.sphinx4_configuration_params](#)

8.41 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/sphinx4_wrapper.py File Reference

Classes

- class [rapp_speech_detection_sphinx4.sphinx4_wrapper.Sphinx4Wrapper](#)
Contains the Sphinx subprocess and is responsible for configuring Sphinx and performing the recognition request.

Namespaces

- [rapp_speech_detection_sphinx4.sphinx4_wrapper](#)

8.42 /home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/Sphinx4.java File Reference

Classes

- class [Sphinx4](#)
Performs speech recognition employing Sphinx.

8.43 /home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/text_to_speech_espeak.py File Reference

Classes

- class [text_to_speech_espeak.TextToSpeechEspeak](#)

Namespaces

- [text_to_speech_espeak](#)

Variables

- tuple [text_to_speech_espeak.text_to_speech_espeak_ros_node](#) = [TextToSpeechEspeak](#)()

Index

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_audio_processing.py, 103

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_detect_silence.py, 103

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_energy_denoise.py, 104

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_set_noise_profile.py, 104

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_sox_denoise.py, 104

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_transform_audio.py, 105

/home/travis/rapp_temp/rapp-platform/rapp_audio_processing/src/rapp_audio_processing/rapp_utilities.py, 105

/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise.py, 105

/home/travis/rapp_temp/rapp-platform/rapp_cognitive_exercise/src/cognitive_exercise_main.py, 105

/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detection.h, 106

/home/travis/rapp_temp/rapp-platform/rapp_face_detection/include/face_detection/face_detector.h, 106

/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection.cpp, 107

/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detection_node.cpp, 108

/home/travis/rapp_temp/rapp-platform/rapp_face_detection/src/face_detector.cpp, 109

/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_wrapper.h, 109

/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/include/knowrob_wrapper/knowrob_wrapper_communications.h, 110

/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper.cpp, 111

/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_communications.cpp, 114

/home/travis/rapp_temp/rapp-platform/rapp_knowrob_wrapper/src/knowrob_wrapper_node.cpp, 114

/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper.py, 114

/home/travis/rapp_temp/rapp-platform/rapp_mysql_wrapper/src/mysql_wrapper_main.py, 115

/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detection.h, 115

/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/include/qr_detection/qr_detector.h, 116

/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection.cpp, 117

/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detection_node.cpp, 117

/home/travis/rapp_temp/rapp-platform/rapp_qr_detection/src/qr_detector.cpp, 118

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/rapp_exceptions.py, 118

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_google/src/speech_recognition_google.py, 119

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/Sphinx4.java, 122

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/english_support.py, 119

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/global_parameters.py, 119

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/greek_support.py, 120

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_exceptions.py, 118

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/rapp_tools.py, 120

/home/travis/rapp_temp/rapp-platform/rapp_speech_detection_sphinx4/src/rapp_speech_detection_sphinx4/sphinx4_wrapper.py, 121

/home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/rapp_exceptions.py, 118

/home/travis/rapp_temp/rapp-platform/rapp_text_to_speech_espeak/src/text_to_speech_espeak.py, 122

__init__

cognitive_exercise::CognitiveExercise, 21

mysql_wrapper::MySQLdbWrapper, 59

rapp_audio_processing::rapp_audio_processing::

- AudioProcessing, 18
- rapp_audio_processing::rapp_set_noise_profile::SetNoiseProfile, 78
- rapp_exceptions::RappError, 75
- rapp_speech_detection_sphinx4::english_support::EnglishSupport, 24
- rapp_speech_detection_sphinx4::global_parameters::GlobalParams, 31
- rapp_speech_detection_sphinx4::greek_support::GreekSupport, 34
- rapp_speech_detection_sphinx4::limited_vocabulary_creator::LimitedVocabularyCreator, 56
- rapp_speech_detection_sphinx4::rapp_exceptions::RappError, 77
- rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4, 81
- rapp_speech_detection_sphinx4::sphinx4_configuration_params::SphinxConfigurationParams, 96
- rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 92
- speech_recognition_google::SpeechToTextGoogle, 86
- text_to_speech_espeak::TextToSpeechEspeak, 99
- __str__
 - rapp_exceptions::RappError, 75
 - rapp_speech_detection_sphinx4::rapp_exceptions::RappError, 77
- _acoustic_models_url
 - rapp_speech_detection_sphinx4::global_parameters::GlobalParams, 31
- _all_special_two_digit_letters
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 36
- _allow_sphinx_output
 - rapp_speech_detection_sphinx4::global_parameters::GlobalParams, 31
 - rapp_speech_detection_sphinx4::limited_vocabulary_creator::LimitedVocabularyCreator, 56
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 94
- _assertArgs
 - rapp_audio_processing::rapp_transform_audio::TransformAudio, 100
- _audio_transform_srv
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 94
- _authentication_service
 - rapp_speech_detection_sphinx4::speech_recognition_english_dict_file_sphinx4::SpeechRecognitionSphinx4, 82
- _availableProcesses
 - rapp_speech_detection_sphinx4::speech_recognition_english_dict_mapping_sphinx4_handler_node::SpeechRecognitionSphinx4HandlerNode, 85
- _calculateRequestHash
 - rapp_speech_detection_sphinx4::speech_recognition_sphinx4_handler_node::SpeechRecognitionSphinx4HandlerNode, 84
- _callSphinxJava
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 92
- _capital_letters
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 36
- rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 94
- _configuration_params
 - rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4, 82
- _configureLetters
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 34
- _configureSpeechRecognition
 - rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4, 81
- _convertType
 - rapp_audio_processing::rapp_transform_audio::TransformAudio, 100
- _createProcessingProfile
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 92
- _createSocket
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 92
- _denoise_service
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 94
- _detect_silence_module
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 19
- _detect_silence_service
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 94
- _energy_denoise_module
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 19
- _energy_denoise_service
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 94
- _energy_denoising_debug
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 19
- _englify_words
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 34
- rapp_speech_detection_sphinx4::english_support::EnglishSupport, 25
- rapp_speech_detection_sphinx4::english_support::EnglishSupport, 25
- _english_support
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 36
- rapp_speech_detection_sphinx4::speech_recognition-

- [_sphinx4::SpeechRecognitionSphinx4](#), [82](#)
- [_generic_sphinx_configuration](#)
 - [rapp_speech_detection_sphinx4::english_support::EnglishSupport](#), [25](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [36](#)
- [_grammar](#)
 - [rapp_speech_detection_sphinx4::sphinx4_configuration_params::SphinxConfigurationParams](#), [98](#)
- [_greek_support](#)
 - [rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4](#), [82](#)
- [_language](#)
 - [rapp_speech_detection_sphinx4::sphinx4_configuration_params::SphinxConfigurationParams](#), [98](#)
- [_language_models_url](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [31](#)
- [_letters](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [36](#)
- [_literal_letters](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [36](#)
- [_lock](#)
 - [rapp_speech_detection_sphinx4::speech_recognition_sphinx4_handler_node::SpeechRecognitionSphinx4HandlerNode](#), [85](#)
- [_noise_profiles_url](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [31](#)
- [_performEnergyDenoising](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [92](#)
- [_phonemes](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [36](#)
- [_readLine](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [93](#)
- [_respawnSphinx](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [93](#)
- [_s_specific_rules](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [36](#)
- [_sentences](#)
 - [rapp_speech_detection_sphinx4::sphinx4_configuration_params::SphinxConfigurationParams](#), [98](#)
- [_separateEngGrWords](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [34](#)
- [_set_noise_profile_module](#)
 - [rapp_audio_processing::rapp_audio_processing::AudioProcessing](#), [20](#)
- [_socket_host](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [31](#)
- [_sox_denoise_module](#)
 - [rapp_audio_processing::rapp_audio_processing::AudioProcessing](#), [20](#)
- [_special_two_digit_letters](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [36](#)
- [_speechRecognition](#)
 - [rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4](#), [81](#)
- [_sphinx4](#)
 - [rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4](#), [82](#)
- [_sphinxDied](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [95](#)
- [_sphinxSubprocess](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [95](#)
- [_sphinx_jar_file](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [31](#)
- [_sphinx_jar_files_url](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [31](#)
- [_sphinx_package_url](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [31](#)
- [_sphinx_socket](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [94](#)
- [_sphinx_socket_PORT](#)
 - [rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper](#), [94](#)
- [_threadCounter](#)
 - [rapp_speech_detection_sphinx4::speech_recognition_sphinx4_handler_node::SpeechRecognitionSphinx4HandlerNode](#), [85](#)
- [_threads](#)
 - [rapp_speech_detection_sphinx4::speech_recognition_sphinx4_handler_node::SpeechRecognitionSphinx4HandlerNode](#), [85](#)
- [_tmp_language_models_url](#)
 - [rapp_speech_detection_sphinx4::global_parameters::GlobalParams](#), [32](#)
- [_transformWords](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [35](#)
- [_transform_audio_module](#)
 - [rapp_audio_processing::rapp_audio_processing::AudioProcessing](#), [20](#)
- [_two_digit_letters](#)
 - [rapp_speech_detection_sphinx4::greek_support::GreekSupport](#), [37](#)
- [_use_db_authentication](#)
 - [rapp_speech_detection_sphinx4::speech_recognition-](#)

- _sphinx4::SpeechRecognitionSphinx4, 82
- _utilities_module
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 20
- _validateSourceType
 - rapp_audio_processing::rapp_transform_audio::TransformAudio, 100
- _vocabulary
 - rapp_speech_detection_sphinx4::english_support::EnglishSupport, 26
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 37
- _word_mapping
 - rapp_speech_detection_sphinx4::speech_recognition_sphinx4::SpeechRecognitionSphinx4, 83
- _words
 - rapp_speech_detection_sphinx4::sphinx4_configuration_params::SphinxConfigurationParams, 98
- acoustic_model_path
 - Sphinx4, 88
- acoustic_model_path_prev
 - Sphinx4, 88
- assertAttributeValue
 - KnowrobWrapper, 39
- AudioProcessingNode
 - rapp_audio_processing::rapp_audio_processing, 12
- bufferRead
 - Sphinx4, 88
- bufferWrite
 - Sphinx4, 88
- center
 - QrCode, 70
- checkConnection
 - mysql_wrapper::MySQLdbWrapper, 59
- checkIfFileExists
 - knowrob_wrapper.cpp, 112
- chooserDataHandler
 - cognitive_exercise::CognitiveExercise, 21
- cleanup
 - rapp_audio_processing::rapp_utilities::Utilities, 101
- clear_user_cognitive_tests_performance_records
 - KnowrobWrapper, 40
- clear_user_cognitive_tests_performance_records_callback
 - KnowrobWrapperCommunications, 47
- clear_user_cognitive_tests_performance_records_service
 - KnowrobWrapperCommunications, 51
- clear_user_cognitive_tests_performance_records_topic
 - KnowrobWrapperCommunications, 51
- cm
 - Sphinx4, 88
- cognitive_exercise, 11
 - cognitive_exercise.CognitiveExercise, 20
 - cognitive_exercise::CognitiveExercise
 - __init__, 21
 - chooserDataHandler, 21
 - cognitiveTestCreatorDataHandler, 21
 - recordUserCognitiveTestPerformanceDataHandler, 21
 - serv, 21
 - serv_topic, 22
 - cognitive_exercise_main, 11
 - CognitiveExerciseNode, 11
 - cognitive_tests_of_type
 - KnowrobWrapper, 40
 - cognitive_tests_of_type_callback
 - KnowrobWrapperCommunications, 47
 - cognitive_tests_of_type_service
 - KnowrobWrapperCommunications, 51
 - cognitive_tests_of_type_topic
 - KnowrobWrapperCommunications, 52
 - CognitiveExerciseNode
 - cognitive_exercise_main, 11
 - cognitiveTestCreatorDataHandler
 - cognitive_exercise::CognitiveExercise, 21
 - configuration
 - Sphinx4, 88
 - configuration_model_path
 - Sphinx4, 88
 - configuration_model_path_prev
 - Sphinx4, 89
 - configureSphinx
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 93
 - constructAndQuery
 - mysql_wrapper::MySQLdbWrapper, 59
 - constructCommaColumns
 - mysql_wrapper::MySQLdbWrapper, 59
 - create_cognitive_tests
 - KnowrobWrapper, 40
 - create_cognitive_tests_callback
 - KnowrobWrapperCommunications, 48
 - create_cognitive_tests_service
 - KnowrobWrapperCommunications, 52
 - create_cognitive_tests_topic
 - KnowrobWrapperCommunications, 52
 - create_ontology_alias
 - KnowrobWrapper, 40
 - create_ontology_alias_callback
 - KnowrobWrapperCommunications, 48
 - create_ontology_alias_for_new_user
 - KnowrobWrapper, 41
 - create_ontology_alias_service
 - KnowrobWrapperCommunications, 52
 - create_ontology_alias_topic
 - KnowrobWrapperCommunications, 52
 - createConfigurationFiles
 - rapp_speech_detection_sphinx4::limited_vocabulary_creator::LimitedVocabularyCreator, 56
 - createInstanceCallback

- KnowrobWrapperCommunications, 48
- createInstanceQuery
 - KnowrobWrapper, 41
- createInstanceService_
 - KnowrobWrapperCommunications, 52
- createInstanceServiceTopic_
 - KnowrobWrapperCommunications, 52
- deleteData
 - mysql_wrapper::MySQLdbWrapper, 59
- denoiseCallback
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 18
- detectFaces
 - FaceDetector, 29
- detectQrs
 - QrDetector, 73
- detectSilence
 - rapp_audio_processing::rapp_detect_silence::DetectSilence, 22
- detectSilenceCallback
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 18
- dictionary_path
 - Sphinx4, 89
- dictionary_path_prev
 - Sphinx4, 89
- dumpOntologyCallback
 - KnowrobWrapperCommunications, 49
- dumpOntologyQuery
 - KnowrobWrapper, 41
- dumpOntologyService_
 - KnowrobWrapperCommunications, 52
- dumpOntologyServiceTopic_
 - KnowrobWrapperCommunications, 52
- energyDenoise
 - rapp_audio_processing::rapp_energy_denoise::EnergyDenoise, 23
- energyDenoiseCallback
 - rapp_audio_processing::rapp_audio_processing::AudioProcessing, 18
- equals
 - rapp_speech_detection_sphinx4::sphinx4_configuration_params::SphinxConfigurationParams, 97
- face_detection_node.cpp
 - main, 108
- face_detector_
 - FaceDetection, 27
- FaceDetection, 26
 - face_detector_, 27
 - FaceDetection, 27
 - faceDetectionCallback, 27
 - faceDetectionService_, 27
 - faceDetectionTopic_, 27
 - FaceDetection, 27
 - nh_, 28
- faceDetectionCallback
 - FaceDetection, 27
- faceDetectionService_
 - FaceDetection, 27
- faceDetectionTopic_
 - FaceDetection, 27
- FaceDetector, 28
 - detectFaces, 29
 - FaceDetector, 28
 - FaceDetector, 28
 - findFaces, 29
 - identifyUniqueFaces, 29
 - loadImage, 29
- fetchData
 - mysql_wrapper::MySQLdbWrapper, 60
- findFaces
 - FaceDetector, 29
- findQrs
 - QrDetector, 73
- get_ontology_alias
 - KnowrobWrapper, 41
- getGenericConfiguration
 - rapp_speech_detection_sphinx4::english_support::EnglishSupport, 25
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 35
- getLimitedVocebularyConfiguration
 - rapp_speech_detection_sphinx4::english_support::EnglishSupport, 25
 - rapp_speech_detection_sphinx4::greek_support::GreekSupport, 35
- getLogin
 - mysql_wrapper::MySQLdbWrapper, 60
- getTableColumnNames
 - mysql_wrapper::MySQLdbWrapper, 60
- getWordPhonemes
 - rapp_speech_detection_sphinx4::english_support::EnglishSupport, 25
- grammar_enabled
 - Sphinx4, 89
- grammar_enabled_prev
 - Sphinx4, 89
- grammar_model_file_path
 - Sphinx4, 89
- grammar_model_file_path_prev
 - Sphinx4, 89
- grammar_model_folder_path
 - Sphinx4, 89
- grammar_model_folder_path_prev
 - Sphinx4, 89
- handleSpeechRecognitionCallback
 - rapp_speech_detection_sphinx4::speech_recognition_sphinx4_handler_node::SpeechRecognitionSphinx4HandlerNode, 84
- identifyUniqueFaces
 - FaceDetector, 29

- initializeSphinx
 - rapp_speech_detection_sphinx4::sphinx4_ - wrapper::Sphinx4Wrapper, 93
- intToString
 - knowrob_wrapper.cpp, 113
- is_subsuperclass_of_service_
 - KnowrobWrapperCommunications, 53
- is_subsuperclass_of_service_topic_
 - KnowrobWrapperCommunications, 53
- isSubSuperclassOfCallback
 - KnowrobWrapperCommunications, 49
- isSubSuperclassOfQuery
 - KnowrobWrapper, 42
- knowrob_wrapper
 - KnowrobWrapperCommunications, 53
- knowrob_wrapper.cpp
 - checkIfFileExists, 112
 - intToString, 113
 - split, 113
 - SplitFilename, 113
- knowrob_wrapper_node.cpp
 - main, 114
- KnowrobWrapper, 37
 - assertAttributeValue, 39
 - clear_user_cognitive_tests_performance_records, 40
 - cognitive_tests_of_type, 40
 - create_cognitive_tests, 40
 - create_ontology_alias, 40
 - create_ontology_alias_for_new_user, 41
 - createInstanceQuery, 41
 - dumpOntologyQuery, 41
 - get_ontology_alias, 41
 - isSubSuperclassOfQuery, 42
 - KnowrobWrapper, 38
 - KnowrobWrapper, 38
 - loadOntologyQuery, 42
 - mysql_fetch_client, 44
 - mysql_update_client, 44
 - mysql_write_client, 44
 - nh_, 44
 - pl, 44
 - record_user_cognitive_tests_performance, 42
 - subclassesOfQuery, 43
 - superclassesOfQuery, 43
 - user_instances_of_class, 43
 - user_performance_cognitive_tests, 44
- KnowrobWrapperCommunications, 45
 - clear_user_cognitive_tests_performance_records_ - callback, 47
 - clear_user_cognitive_tests_performance_records_ - service_, 51
 - clear_user_cognitive_tests_performance_records_ - topic_, 51
 - cognitive_tests_of_type_callback, 47
 - cognitive_tests_of_type_service_, 51
 - cognitive_tests_of_type_topic_, 52
 - create_cognitive_tests_callback, 48
 - create_cognitive_tests_service_, 52
 - create_cognitive_tests_topic_, 52
 - create_ontology_alias_callback, 48
 - create_ontology_alias_service_, 52
 - create_ontology_alias_topic_, 52
 - createInstanceCallback, 48
 - createInstanceService_, 52
 - createInstanceServiceTopic_, 52
 - dumpOntologyCallback, 49
 - dumpOntologyService_, 52
 - dumpOntologyServiceTopic_, 52
 - is_subsuperclass_of_service_, 53
 - is_subsuperclass_of_service_topic_, 53
 - isSubSuperclassOfCallback, 49
 - knowrob_wrapper, 53
 - KnowrobWrapperCommunications, 47
 - KnowrobWrapperCommunications, 47
 - loadOntologyCallback, 49
 - loadOntologyService_, 53
 - loadOntologyServiceTopic_, 53
 - nh_, 53
 - record_user_cognitive_tests_performance_ - callback, 50
 - record_user_cognitive_tests_performance_ - service_, 53
 - record_user_cognitive_tests_performance_topic_, 53
 - subclasses_of_service_, 53
 - subclasses_of_service_topic_, 54
 - subclassesOfCallback, 50
 - superclasses_of_service_, 54
 - superclasses_of_service_topic_, 54
 - superclassesOfCallback, 50
 - user_instances_of_class_callback, 51
 - user_instances_of_class_service_, 54
 - user_instances_of_class_topic_, 54
 - user_performance_cognitive_tests_callback, 51
 - user_performance_cognitive_tests_service_, 54
 - user_performance_cognitive_tests_topic_, 54
- language_path
 - Sphinx4, 89
- language_path_prev
 - Sphinx4, 89
- languages_package
 - rapp_speech_detection_sphinx4::limited_vocabulary_ - creator::LimitedVocabularyCreator, 56
- loadImage
 - FaceDetector, 29
 - QrDetector, 73
- loadOntologyCallback
 - KnowrobWrapperCommunications, 49
- loadOntologyQuery
 - KnowrobWrapper, 42
- loadOntologyService_
 - KnowrobWrapperCommunications, 53
- loadOntologyServiceTopic_
 - KnowrobWrapperCommunications, 53

- main
 - face_detection_node.cpp, 108
 - knowrob_wrapper_node.cpp, 114
 - qr_detection_node.cpp, 117
 - Sphinx4, 88
- message
 - QrCode, 70
- MySQLWrapperNode
 - mysql_wrapper_main, 12
- mysql_fetch_client
 - KnowrobWrapper, 44
- mysql_update_client
 - KnowrobWrapper, 44
- mysql_wrapper, 11
- mysql_wrapper.MySQLdbWrapper, 57
- mysql_wrapper::MySQLdbWrapper
 - __init__, 59
 - checkConnection, 59
 - constructAndQuery, 59
 - constructCommaColumns, 59
 - deleteData, 59
 - fetchData, 60
 - getLogin, 60
 - getTableColumnNames, 60
 - serv, 69
 - serv_topic, 69
 - tblAppsRobotsDeleteDataHandler, 60
 - tblAppsRobotsFetchDataHandler, 60
 - tblAppsRobotsUpdateDataHandler, 62
 - tblAppsRobotsWriteDataHandler, 62
 - tblModelDeleteDataHandler, 62
 - tblModelFetchDataHandler, 62
 - tblModelUpdateDataHandler, 62
 - tblModelWriteDataHandler, 64
 - tblRappDeleteDataHandler, 64
 - tblRappFetchDataHandler, 64
 - tblRappUpdateDataHandler, 64
 - tblRappWriteDataHandler, 64
 - tblRobotDeleteDataHandler, 65
 - tblRobotFetchDataHandler, 65
 - tblRobotUpdateDataHandler, 65
 - tblRobotWriteDataHandler, 65
 - tblUserDeleteDataHandler, 66
 - tblUserFetchDataHandler, 66
 - tblUserUpdateDataHandler, 68
 - tblUserWriteDataHandler, 68
 - tblUsersOntologyInstancesDeleteDataHandler, 66
 - tblUsersOntologyInstancesFetchDataHandler, 66
 - tblUsersOntologyInstancesUpdateDataHandler, 66
 - tblUsersOntologyInstancesWriteDataHandler, 68
 - updateData, 68
 - viewUsersRobotsAppsFetchDataHandler, 68
 - whatRappsCanRun, 69
 - whatRappsCanRunDataHandler, 69
 - writeData, 69
- mysql_wrapper_main, 11
 - MySQLWrapperNode, 12
- mysql_write_client
 - KnowrobWrapper, 44
- nh_
 - FaceDetection, 28
 - KnowrobWrapper, 44
 - KnowrobWrapperCommunications, 53
 - QrDetection, 72
- performSpeechRecognition
 - rapp_speech_detection_sphinx4::sphinx4_wrapper::Sphinx4Wrapper, 93
- pl
 - KnowrobWrapper, 44
- qr_detection_node.cpp
 - main, 117
- qr_detector_
 - QrDetection, 72
- QrCode, 70
 - center, 70
 - message, 70
- QrDetection, 70
 - nh_, 72
 - qr_detector_, 72
 - QrDetection, 71
 - qrDetectionCallback, 71
 - qrDetectionService_, 72
 - qrDetectionTopic_, 72
 - QrDetection, 71
- qrDetectionCallback
 - QrDetection, 71
- qrDetectionService_
 - QrDetection, 72
- qrDetectionTopic_
 - QrDetection, 72
- QrDetector, 72
 - detectQrs, 73
 - findQrs, 73
 - loadImage, 73
 - QrDetector, 73
 - QrDetector, 73
- rapp_audio_processing, 12
- rapp_audio_processing.rapp_audio_processing, 12
- rapp_audio_processing.rapp_audio_processing.AudioProcessing, 17
- rapp_audio_processing.rapp_detect_silence, 12
- rapp_audio_processing.rapp_detect_silence.DetectSilence, 22
- rapp_audio_processing.rapp_energy_denoise, 12
- rapp_audio_processing.rapp_energy_denoise.EnergyDenoise, 22
- rapp_audio_processing.rapp_set_noise_profile, 13
- rapp_audio_processing.rapp_set_noise_profile.SetNoiseProfile, 77
- rapp_audio_processing.rapp_sox_denoise, 13
- rapp_audio_processing.rapp_sox_denoise.SoxDenoise, 78
- rapp_audio_processing.rapp_transform_audio, 13

rapp_audio_processing.rapp_transform_audio.Transform-
 Audio, 99
 rapp_audio_processing.rapp_utilities, 13
 rapp_audio_processing.rapp_utilities.Utilities, 101
 rapp_audio_processing::rapp_audio_processing
 AudioProcessingNode, 12
 rapp_audio_processing::rapp_audio_processing:-
 AudioProcessing
 _detect_silence_module, 19
 _energy_denoise_module, 19
 _energy_denoising_debug, 19
 _sox_denoise_module, 20
 _transform_audio_module, 20
 _utilities_module, 20
 denoiseCallback, 18
 detectSilenceCallback, 18
 energyDenoiseCallback, 18
 setNoiseProfileCallback, 19
 transformAudioCallback, 19
 rapp_audio_processing::rapp_detect_silence::Detect-
 Silence
 detectSilence, 22
 rapp_audio_processing::rapp_energy_denoise::Energy-
 Denoise
 energyDenoise, 23
 rapp_audio_processing::rapp_set_noise_profile::Set-
 NoiseProfile
 setNoise_profile, 78
 utilities, 78
 rapp_audio_processing::rapp_sox_denoise::Sox-
 Denoise
 soxDenoise, 78
 rapp_audio_processing::rapp_transform_audio:-
 TransformAudio
 _assertArgs, 100
 _convertType, 100
 _validateSourceType, 100
 transform_audio, 101
 rapp_audio_processing::rapp_utilities::Utilities
 cleanup, 101
 rapp_exceptions, 13
 rapp_exceptions.RappError, 74
 rapp_exceptions::RappError
 __init__, 75
 __str__, 75
 value, 75
 rapp_print
 rapp_speech_detection_sphinx4::rapp_tools, 14
 rapp_speech_detection_sphinx4, 13
 rapp_speech_detection_sphinx4.english_support, 14
 rapp_speech_detection_sphinx4.english_support.-
 EnglishSupport, 23
 rapp_speech_detection_sphinx4.global_parameters, 14
 rapp_speech_detection_sphinx4.global_parameters.-
 GlobalParams, 30
 rapp_speech_detection_sphinx4.greek_support, 14
 rapp_speech_detection_sphinx4.greek_support.Greek-
 Support, 32
 rapp_speech_detection_sphinx4.limited_vocabulary_-
 creator, 14
 rapp_speech_detection_sphinx4.limited_vocabulary_-
 creator.LimitedVocabularyCreator, 55
 rapp_speech_detection_sphinx4.rapp_exceptions, 14
 rapp_speech_detection_sphinx4.rapp_exceptions.-
 RappError, 76
 rapp_speech_detection_sphinx4.rapp_tools, 14
 rapp_speech_detection_sphinx4.speech_recognition_-
 sphinx4, 15
 rapp_speech_detection_sphinx4.speech_recognition_-
 sphinx4.SpeechRecognitionSphinx4, 79
 rapp_speech_detection_sphinx4.speech_recognition_-
 sphinx4_handler_node, 15
 rapp_speech_detection_sphinx4.sphinx4_configuration_-
 params, 15
 rapp_speech_detection_sphinx4.sphinx4_configuration_-
 params.SphinxConfigurationParams, 95
 rapp_speech_detection_sphinx4.sphinx4_wrapper, 16
 rapp_speech_detection_sphinx4.sphinx4_wrapper.-
 Sphinx4Wrapper, 90
 rapp_speech_detection_sphinx4::english_support:-
 EnglishSupport
 _english_dict_file, 25
 _english_dict_mapping, 25
 _generic_sphinx_configuration, 25
 _vocabulary, 26
 getGenericConfiguration, 25
 getLimitedVocebularyConfiguration, 25
 getWordPhonemes, 25
 rapp_speech_detection_sphinx4::global_parameters:-
 GlobalParams
 _acoustic_models_url, 31
 _allow_sphinx_output, 31
 _language_models_url, 31
 _noise_profiles_url, 31
 _socket_host, 31
 _sphinx_jar_file, 31
 _sphinx_package_url, 31
 rospack, 32
 rapp_speech_detection_sphinx4::greek_support:-
 GreekSupport
 _capital_letters, 36
 _configureLetters, 34
 _englify_words, 34
 _english_support, 36
 _generic_sphinx_configuration, 36
 _letters, 36
 _literal_letters, 36
 _phonemes, 36
 _s_specific_rules, 36
 _separateEngGrWords, 34
 _transformWords, 35
 _two_digit_letters, 37
 _vocabulary, 37
 getGenericConfiguration, 35
 getLimitedVocebularyConfiguration, 35

- rapp_speech_detection_sphinx4::limited_vocabulary_ - creator::LimitedVocabularyCreator
 - createConfigurationFiles, [56](#)
 - languages_package, [56](#)
 - sphinx_configuration, [56](#)
- rapp_speech_detection_sphinx4::rapp_exceptions:: - RappError
 - value, [77](#)
- rapp_speech_detection_sphinx4::rapp_tools
 - rapp_print, [14](#)
- rapp_speech_detection_sphinx4::speech_recognition_ - sphinx4
 - SpeechRecognitionSphinx4Node, [15](#)
- rapp_speech_detection_sphinx4::speech_recognition_ - sphinx4::SpeechRecognitionSphinx4
 - _speechRecognition, [81](#)
 - _sphinx4, [82](#)
 - speechRecognitionBatch, [81](#)
- rapp_speech_detection_sphinx4::sphinx4_configuration_ - _params::SphinxConfigurationParams
 - _grammar, [98](#)
 - _language, [98](#)
 - _sentences, [98](#)
 - _words, [98](#)
 - equals, [97](#)
- rapp_speech_detection_sphinx4::sphinx4_wrapper:: - Sphinx4Wrapper
 - _allow_sphinx_output, [94](#)
 - _audio_transform_srv, [94](#)
 - _callSphinxJava, [92](#)
 - _conf, [94](#)
 - _createProcessingProfile, [92](#)
 - _createSocket, [92](#)
 - _denoise_service, [94](#)
 - _detect_silence_service, [94](#)
 - _energy_denoise_service, [94](#)
 - _performEnergyDenoising, [92](#)
 - _readLine, [93](#)
 - _respawnSphinx, [93](#)
 - _sphinxDied, [95](#)
 - _sphinxSubprocess, [95](#)
 - _sphinx_socket, [94](#)
 - configureSphinx, [93](#)
 - initializeSphinx, [93](#)
 - performSpeechRecognition, [93](#)
- recognizer
 - Sphinx4, [89](#)
- record_user_cognitive_tests_performance
 - KnowrobWrapper, [42](#)
- record_user_cognitive_tests_performance_callback
 - KnowrobWrapperCommunications, [50](#)
- record_user_cognitive_tests_performance_service_
 - KnowrobWrapperCommunications, [53](#)
- record_user_cognitive_tests_performance_topic_
 - KnowrobWrapperCommunications, [53](#)
- recordUserCognitiveTestPerformanceDataHandler
 - cognitive_exercise::CognitiveExercise, [21](#)
- rospack
 - rapp_speech_detection_sphinx4::global_parameters_ - ::GlobalParams, [32](#)
- serv
 - cognitive_exercise::CognitiveExercise, [21](#)
 - mysql_wrapper::MySQLdbWrapper, [69](#)
 - speech_recognition_google::SpeechToText- Google, [86](#)
 - text_to_speech_espeak::TextToSpeechEspeak, [99](#)
- serv_topic
 - cognitive_exercise::CognitiveExercise, [22](#)
 - mysql_wrapper::MySQLdbWrapper, [69](#)
 - speech_recognition_google::SpeechToText- Google, [86](#)
 - text_to_speech_espeak::TextToSpeechEspeak, [99](#)
- setNoise_profile
 - rapp_audio_processing::rapp_set_noise_profile:: - SetNoiseProfile, [78](#)
- setNoiseProfileCallback
 - rapp_audio_processing::rapp_audio_processing:: - AudioProcessing, [19](#)
- soxDenoise
 - rapp_audio_processing::rapp_sox_denoise::Sox- Denoise, [78](#)
- speech_recognition_google, [16](#)
 - speech_to_text_node, [16](#)
- speech_recognition_google.SpeechToTextGoogle, [85](#)
- speech_recognition_google::SpeechToTextGoogle
 - _init_, [86](#)
 - serv, [86](#)
 - serv_topic, [86](#)
 - speech_to_text, [86](#)
 - speech_to_text_callback, [86](#)
- speech_to_text
 - speech_recognition_google::SpeechToText- Google, [86](#)
- speech_to_text_callback
 - speech_recognition_google::SpeechToText- Google, [86](#)
- speech_to_text_node
 - speech_recognition_google, [16](#)
- speechRecognitionBatch
 - rapp_speech_detection_sphinx4::speech_recognition_ - _sphinx4::SpeechRecognitionSphinx4, [81](#)
- SpeechRecognitionSphinx4HandlerNode
 - rapp_speech_detection_sphinx4::speech_recognition_ - _sphinx4_handler_node, [15](#)
- SpeechRecognitionSphinx4Node
 - rapp_speech_detection_sphinx4::speech_recognition_ - _sphinx4, [15](#)
- Sphinx4, [87](#)
 - acoustic_model_path, [88](#)
 - acoustic_model_path_prev, [88](#)
 - bufferRead, [88](#)
 - bufferWrite, [88](#)
 - cm, [88](#)
 - configuration, [88](#)
 - configuration_model_path, [88](#)
 - configuration_model_path_prev, [89](#)

- dictionary_path, 89
- dictionary_path_prev, 89
- grammar_enabled, 89
- grammar_enabled_prev, 89
- grammar_model_file_path, 89
- grammar_model_file_path_prev, 89
- grammar_model_folder_path, 89
- grammar_model_folder_path_prev, 89
- language_path, 89
- language_path_prev, 89
- main, 88
- recognizer, 89
- updateConfiguration, 88
- sphinx_configuration
 - rapp_speech_detection_sphinx4::limited_vocabulary-
_creator::LimitedVocabularyCreator, 56
- split
 - knowrob_wrapper.cpp, 113
- SplitFilename
 - knowrob_wrapper.cpp, 113
- subclasses_of_service_
 - KnowrobWrapperCommunications, 53
- subclasses_of_service_topic_
 - KnowrobWrapperCommunications, 54
- subclassesOfCallback
 - KnowrobWrapperCommunications, 50
- subclassesOfQuery
 - KnowrobWrapper, 43
- superclasses_of_service_
 - KnowrobWrapperCommunications, 54
- superclasses_of_service_topic_
 - KnowrobWrapperCommunications, 54
- superclassesOfCallback
 - KnowrobWrapperCommunications, 50
- superclassesOfQuery
 - KnowrobWrapper, 43
- tblAppsRobotsDeleteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 60
- tblAppsRobotsFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, 60
- tblAppsRobotsUpdateDataHandler
 - mysql_wrapper::MySQLdbWrapper, 62
- tblAppsRobotsWriteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 62
- tblModelDeleteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 62
- tblModelFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, 62
- tblModelUpdateDataHandler
 - mysql_wrapper::MySQLdbWrapper, 62
- tblModelWriteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 64
- tblRappDeleteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 64
- tblRappFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, 64
- tblRappUpdateDataHandler
 - mysql_wrapper::MySQLdbWrapper, 64
- tblRappWriteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 64
- tblRobotDeleteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 65
- tblRobotFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, 65
- tblRobotUpdateDataHandler
 - mysql_wrapper::MySQLdbWrapper, 65
- tblRobotWriteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 65
- tblUserDeleteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 66
- tblUserFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, 66
- tblUserUpdateDataHandler
 - mysql_wrapper::MySQLdbWrapper, 68
- tblUserWriteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 68
- tblUsersOntologyInstancesDeleteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 66
- tblUsersOntologyInstancesFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, 66
- tblUsersOntologyInstancesUpdateDataHandler
 - mysql_wrapper::MySQLdbWrapper, 66
- tblUsersOntologyInstancesWriteDataHandler
 - mysql_wrapper::MySQLdbWrapper, 68
- text_to_speech_callback
 - text_to_speech_espeak::TextToSpeechEspeak, 99
- text_to_speech_espeak, 16
 - text_to_speech_espeak_ros_node, 16
- text_to_speech_espeak.TextToSpeechEspeak, 98
- text_to_speech_espeak::TextToSpeechEspeak
 - __init__, 99
- serv, 99
 - serv_topic, 99
- text_to_speech_callback, 99
- text_to_speech_espeak_ros_node
 - text_to_speech_espeak, 16
- transform_audio
 - rapp_audio_processing::rapp_transform_audio::-
TransformAudio, 101
- transformAudioCallback
 - rapp_audio_processing::rapp_audio_processing::-
AudioProcessing, 19
- updateConfiguration
 - Sphinx4, 88
- updateData
 - mysql_wrapper::MySQLdbWrapper, 68
- user_instances_of_class
 - KnowrobWrapper, 43
- user_instances_of_class_callback
 - KnowrobWrapperCommunications, 51
- user_instances_of_class_service_
 - KnowrobWrapperCommunications, 54
- user_instances_of_class_topic_
 - KnowrobWrapperCommunications, 54
- user_performance_cognitive_tests
 - KnowrobWrapper, 44

- user_performance_cognitive_tests_callback
 - KnowrobWrapperCommunications, [51](#)
- user_performance_cognitive_tests_service_
 - KnowrobWrapperCommunications, [54](#)
- user_performance_cognitive_tests_topic_
 - KnowrobWrapperCommunications, [54](#)
- utilities
 - rapp_audio_processing::rapp_set_noise_profile::-
SetNoiseProfile, [78](#)
- value
 - rapp_exceptions::RappError, [75](#)
 - rapp_speech_detection_sphinx4::rapp_exceptions-
::RappError, [77](#)
- viewUsersRobotsAppsFetchDataHandler
 - mysql_wrapper::MySQLdbWrapper, [68](#)
- whatRappsCanRun
 - mysql_wrapper::MySQLdbWrapper, [69](#)
- whatRappsCanRunDataHandler
 - mysql_wrapper::MySQLdbWrapper, [69](#)
- writeData
 - mysql_wrapper::MySQLdbWrapper, [69](#)