

DataStream Report

The Report is created by **LAUNCH** X-431

Vehicle Information



Year:2011

Make:TOYOTA

Model:Tacoma

VIN:5TFUU4EN2BX005907

Engine Size:1GR-FE 4.0L 6 Dual Overhead Cam (DOHC)

Vehicle Software Version:V51.50

Diagnostic Application Version:V8.00.031

Diagnostic path:Automatic Search > North America > Tacoma > 2011 > 1GR-FE > Vacuum Type VSC > ECMECT (Engine and ECT)

Repair Shop

Shop Name:

Address:

Zip Code:

Telephone:

Email:

SN:989347712041

Test Time:2025-12-24 00:03:11



Data Stream 【Pre-Repair】

Name	Value	Unit
# Codes(Include History)	0	
+BM Voltage	14.043	V
2nd Air Monitor	Not Avl	
2nd Air Monitor	Compl	
2nd Air Monitor CMPL	Compl	
2nd Air Monitor ENA	Unable	
4WD Switch	OFF	
A/C Monitor	Not Avl	
A/C Monitor	Compl	
A/C Monitor CMPL	Compl	
A/C Monitor ENA	Unable	

A/C Signal	OFF	
A/F Heater Duty B1S1	53.906	%
A/F Heater Duty B2S1	58.594	%
A/T Oil Temperature 1	87.125	degree F
A/T Oil Temperature 2	96.125	degree F
Accel Fully Close Learn #1	19.531	deg
Accel Fully Close Learn #2	39.551	deg
Accel Sens. No.1 Volt %	15.686	%
Accel Sens. No.2 Volt %	31.765	%
Accel Sensor Out No.1	0.781	V
Accel Sensor Out No.2	1.582	V
Accelerator Idle Position	ON	
Accelerator Position	0	%
ACIS VSV	OFF	
ACT VSV	ON	
Actuator Power Supply	ON	
AF Lambda B1S1	0.998	
AF Lambda B2S1	0.998	
AFS Current B1S1	-0.031	mA
AFS Current B2S1	-0.043	mA
AFS Voltage B1S1	3.21	V
AFS Voltage B2S1	3.215	V
All Cylinders Misfire Count	0	
Atmosphere Pressure	14.55	psi
Av Engine Speed of All Cyl	51199.219	rpm
Battery Voltage	13.75	V
Calculate Load	26.275	%
Cat OT MF F/C Cylinder#1	OFF	
Cat OT MF F/C Cylinder#2	OFF	
Cat OT MF F/C Cylinder#3	OFF	
Cat OT MF F/C Cylinder#4	OFF	
Cat OT MF F/C Cylinder#5	OFF	
Cat OT MF F/C Cylinder#6	OFF	

Cat OT MF F/C History	OFF	
Catalyst Monitor	Avail	
Catalyst Monitor	Incmlpl	
Catalyst Monitor CMPL	Incmlpl	
Catalyst Monitor ENA	Enable	
Catalyst OT MF F/C	Avail	
Catalyst Temp B1S1	890.24	degree F
Catalyst Temp B1S2	271.76	degree F
Catalyst Temp B2S1	890.96	degree F
Catalyst Temp B2S2	273.02	degree F
Closed Throttle Position Switch	ON	
Complete Parts Monitor	Avail	
Component Monitor CMPL	Compl	
Component Monitor ENA	Enable	
Coolant Temp	154.4	degree F
Cylinder #1 Misfire Count	0	
Cylinder #2 Misfire Count	0	
Cylinder #3 Misfire Count	0	
Cylinder #4 Misfire Count	0	
Cylinder #5 Misfire Count	0	
Cylinder #6 Misfire Count	0	
Cylinder Number	6	
Destination	A	
Dist Batt Cable Disconnect	0	mile
Distance from DTC Cleared	0	mile
EGR/VVT Monitor	Avail	
EGR/VVT Monitor	Incmlpl	
EGR/VVT Monitor CMPL	Incmlpl	
EGR/VVT Monitor ENA	Enable	
Electrical Load Signal 1	OFF	
Electrical Load Signal 2	OFF	
Engine Run Time	419	s
Engine Speed	861.5	rpm

Engine Speed of Cyl #1	51199.219	rpm
Engine Speed of Cyl #2		rpm
Engine Speed of Cyl #3		rpm
Engine Speed of Cyl #4		rpm
Engine Speed of Cyl #5		rpm
Engine Speed of Cyl #6		rpm
Engine Type		
EVAP (Purge) VSV		%
EVAP Monitor		
EVAP Monitor		
EVAP Monitor CMPL		
EVAP Monitor ENA		
Evap Purge Flow		%
EVAP Purge VSV		
EVAP System Vent Valve		
FC TAU		
Fuel Cut Condition		
Fuel Pump Speed Control		
Fuel Pump/Speed Status		
Fuel System Monitor		
Fuel System Monitor CMPL		
Fuel System Monitor ENA		
Fuel System Monitor Result		
Fuel System Status #1		
Fuel System Status #2		
Heated Cat Monitor CMPL		
Heated Cat Monitor ENA		
Heated Catalyst Monitor		
Heated Catalyst Monitor		
Heater Monitor CMPL		
Heater Monitor ENA		
Idle Fuel Cut		
IG OFF Elapsed Time		min

IGN Advance	deg
Ignition Trig. Count	
Immobiliser Communication	
Initial Engine Coolant Temp	degree C
Initial Intake Air Temp	degree C
Injection Volum (Cylinder1)	ml
Injector(Port)	us
Intake Air	degree C
Knock Correct Learn Value	degree CA
Knock Feedback Value	degree CA
Lock Up	
Long FT B1S1	%
Long FT B2S1	%
MAF	gm/s
MIL	
MIL on Run Distance	km
MISFIRE LOAD	g/rev
Misfire Margin	%
Misfire Monitor	
Misfire Monitor CMPL	
Misfire Monitor ENA	
MISFIRE RPM	rpm
Model Code	
Neutral Position Switch Signal	
Number Of Emission DTC	
O2 Heater B1S2	
O2 Heater B2S2	
O2 Heater Curr Val B1S2	A
O2 Heater Curr Val B2S2	A
O2S B1S2	V
O2S B2S2	V
O2S Impedance B1S2	ohm
O2S Impedance B2S2	ohm

O2S(A/FS) Heater Monitor	
O2S(A/FS) Heater Monitor	
O2S(A/FS) Monitor	
O2S(A/FS) Monitor	
O2S(A/FS) Monitor CMPL	
O2S(A/FS) Monitor ENA	
OBD Requirements	
Open Side Malfunction	
Power Steering Signal	
Purge Cut VSV Duty	%
Purge Density Learn Value	
Running Time from MIL ON	min
Shift Status	
Shift Switch Status (2 Range)	
Shift Switch Status (3 Range)	
Shift Switch Status (D Range)	
Shift Switch Status (L Range)	
Shift Switch Status (R Range)	
Shift Switch Status(4 Range)	
Short FT B1S1	%
Short FT B2S1	%
SLT Solenoid Status	
SLU Solenoid Status	
SPD (NT)	rpm
SPD (SP2)	km/h
ST1	
Starter Signal	
Stop Light Switch	
System Guard	
System Identification	
Target Air-Fuel Ratio	
TC and TE1	
TC Terminal	

Throttle Fully Close Learn	V
Throttle Idle Position	
Throttle Motor Current	A
Throttle Motor DUTY	%
Throttle Motor Duty (Close)	%
Throttle Motor Duty (Open)	%
Throttle Position Command	V
Throttle Position No.1	V
Throttle Position No.2	V
Throttle Require Position	V
Throttle Sens Open Pos #1	V
Throttle Sens Open Pos #2	V
Throttle Sensor #2 Volt %	%
Throttle Sensor Position	%
Throttle Sensor Volt %	%
Time after DTC Cleared	min
TOTAL FT #1	
TOTAL FT #2	
Transfer L4	
Transmission Type	
Transmission Type2	
Vacuum Pump	
Vapor Pressure (Calculated)	kPa
Vapor Pressure Pump	kPa
Vehicle Load	%
Vehicle Speed	km/h
VN Turbo Type	
WVT Aim Angle #1	%
WVT Aim Angle #2	%
WVT Change Angle #1	degree FR
WVT Change Angle #2	degree FR
WVT Control Status #1	
WVT Control Status #2	

WVT OCV Duty #1	%
WVT OCV Duty #2	%
Warmup Cycle Cleared DTC	

.....

Disclaimer

This test report is for reference only for vehicle test and maintenance. The vehicle operating data provided in this report are all static data. The detailed dynamic diagnostic data can be read by professional maintenance device, and LAUNCH will not be liable for any accidents and failures arising therefrom!