

# AI-driven analysis of molecular pathways

Ionuț Cicio

05/11/2025

<https://github.com/CuriousCI/bsys-eval>

# Contents

<b>1 Introduction</b>	<b>3</b>
<b>2 Problem definition</b>	<b>4</b>
<b>3 Data types specification</b>	<b>6</b>
3.1 Interval .....	6
3.2 ReactomeDbId .....	6
3.3 StableIdVersion .....	7
<b>4 (<i>Reactome</i>) UML class diagram</b>	<b>8</b>
<b>5 Classes specification pt. 1</b>	<b>9</b>
5.1 CatalystActivity .....	9
5.2 Compartment .....	9
5.3 Pathway .....	10
5.4 PhysicalEntity .....	11
<b>6 Classes specification pt. 2</b>	<b>13</b>
6.1 BiologicalScenarioDefinition .....	13
6.2 ModelInstance .....	14
6.3 SimulatedModelInstance .....	14
6.4 Measurement .....	14
6.5 UnitDefinition .....	15
<b>7 Use-case diagram</b>	<b>15</b>
7.1 “Helper” use-case .....	16
<b>8 OpenBox on the Slurm Workload Manager</b>	<b>17</b>
8.1 Analysis .....	17
8.1.1 Data types specification .....	17
8.1.2 Classes specification .....	18
8.1.2.1 Job .....	18
8.2 Implementation .....	19
8.2.1 Data types definitions .....	19
8.2.2 Additional constraints .....	19
8.2.2.1 Job .....	19
<b>Bibliography</b>	<b>20</b>

# 1 Introduction

Given a set of *target species*, a set of constraints on the *target species* (constraints which model a scenario that could present, for example, in a disease) and by taking into account all the reactions within a set *target pathways* that lead to the production, both directly and indirectly, of the *target species*, the goal is to find a subset of virtual patients for the described scenario.

## 2 Problem definition

### Definition 1 (*biological network*)

A biological network  $G$  is a triple  $(S, R, E, \sigma)$  s.t.

- $S = U \sqcup X \sqcup Y$  is the set of species of the biological network
  - $U$  is the set of input species
  - $X$  is the set of other species in the network
  - $Y$  is the set of output species
- $R$  is the set of reactions in the biological network
- $E \subseteq S \times R = E_{\text{reactant}} \sqcup E_{\text{product}} \sqcup E_{\text{modifier}}$  is a relationship between species and reactions
- $\sigma : E_{\text{reactant}} \cup E_{\text{product}} \rightarrow \mathbb{N}^1$

### Definition 2 (*constraint problem*)

Given a biological network  $G = (S, R, E, \sigma)$  let  $C$  be the constraint problem s.t.

**Definition 3 ("produces" relation)**

Given a *biological graph*  $G = (S, R, E, F)$  let  $\rightsquigarrow$  be a relation s.t.

- $\forall s, r \quad (s, r) \in \text{dom}(E_{\text{reactant}} \cup E_{\text{modifier}}) \Rightarrow s \rightsquigarrow r$
- $\forall s, r \quad (s, r) \in \text{dom}(E_{\text{product}}) \Rightarrow r \rightsquigarrow s$
- $\forall c, c', c'' \quad (c \rightsquigarrow c' \wedge c' \rightsquigarrow c'') \Rightarrow c \rightsquigarrow c''$

$\rightsquigarrow$  is the "produces" relation


**Definition 4 (constraint problem on a biological model)**

Given a model  $G$  with target species  $S_T$  and target pathways  $P_T$  let the following be a constraint problem

- $k : R \rightarrow \mathbb{R}^{|R|}$

**find  $k$  subject to**

- partial order on  $k$  from the structure of the graph
- partial order on the quantities
- constraint on enzymes such that



$$k_1, k_{-1} \gg k_2$$

- for all dynamics of the environment
  - average concentration of species consistent to knowledge

$$\exists t_0 \quad \forall t \quad \forall s$$

$$(t > t_0 \wedge s \in S_{\text{avg}}) \rightarrow s(t) \in [\text{known range}]$$

Environment: all possible cuts

we can have excluded species!

$$\dot{x} = k_+ \prod_{i=1}^s S_i^{k_i} - k_- \prod_{j=1}^p P_j^{k_j}$$

$$\dot{x} = \sum_{i=1}^p \text{KP}_i - \sum_{j=1}^n \text{KN}_j$$

$$\left\{ \sum_{j=1}^n \text{KN}_j > \text{KP}_i \mid i \in \{1, \dots, p\} \right\} \cup$$

$$\left\{ \sum_{i=1}^p \text{KP}_i > \text{KN}_j \mid j \in \{1, \dots, n\} \right\}$$

### 3 Data types specification

- `\d` = `/[0-9]/`
- `\w` = `/[A-Za-z0-9_]/`

#### Math

```
Natural = Integer ≥ 0
Interval = (lower_bound: Real [0..1], upper_bound: Real [0..1])
MathML = String matching https://www.w3.org/1998/Math/MathML/
MathMLBoolean = String matching MathML returning a Boolean
MathMLNumeric = String matching MathML returning a Number
Stoichiometry = Natural > 0
```

#### Reactome

```
ReactomeDbId = Natural [1]
StableIdVersion =
  String matching regex /^R-[A-Z]{3}-\d{1,8}\.\d{1,3}$/ [2]
```

#### SBML

```
String1 = String matching regex //
SId = String matching regex /^[a-zA-Z_]\w*$/ [3, Section 3.1.7]
UnitSId = String matching regex /^[a-zA-Z_]\w*$/
```

#### 3.1 Interval

The `Interval` type represents an open interval in  $\mathbb{R}$  of the type `(lower_bound, upper_bound)` s.t.

- when `lower_bound` is not defined, it is interpreted as  $-\infty$
- when `upper_bound` is not defined, it is interpreted as  $+\infty$

```
C.Interval.lower_bound_leq_upper_bound
  ∀ interval, interval_lower_bound, interval_upper_bound
  (
    Interval(interval) ∧
    lower_bound(interval, interval_lower_bound) ∧
    upper_bound(interval, interval_upper_bound)
  ) →
    interval_lower_bound ≤ interval_upper_bound
```

#### 3.2 ReactomeDbId

This is required because not all instances of `DatabaseObject` in Reactome have a `StableIdVersion`, which is the one usually displayed in the Reactome Pathway Browser [4]. Instances of `DatabaseObject` in Reactome can be identified with a `ReactomeDbId`, but its pattern does not match the definition of `SId` used to identify objects in SBML.


In order to generate a correct `SBMLDocument` the `ReactomeDbId` must be converted into a `SIId`.

### 3.3 StableIdVersion

The `StableIdVersion` type is useful because is the one usually displayed in the Reactome Pathway Browser [4]. It is useful to accept it in the description of the models.

```
from_stable_id_version(stable_id_version:  
StableIdVersion):ReactomeDbId  
    postconditions  
        . . .
```

4 (Reactome) UML class diagram





## 5 Classes specification pt. 1

### 5.1 CatalystActivity

The role of `PhysicalEntity` in `catalyst_activity_entity` has multiplicity 0..\* because “If a *PhysicalEntity* can enable multiple molecular functions, a separate *CatalystActivity* instance is created for each” [5, Page 5].

An additional constraint is required for active units, because “If the *PhysicalEntity* is a *Complex* and a component of the complex mediates the molecular function, that component should be identified as the active unit of the *CatalystActivity*.” [5, Page 5]

```
C.CatalystActivity.active_unit_is_component_of_complex
  ∀ catalyst_activity, complex, complex_component
    (
      CatalystActivity(catalyst_activity) ∧
      Complex(complex) ∧
      PhysicalEntity(complex_component) ∧
      catalyst_activity_entity(catalyst_activity, complex)
    ∧
      catalyst_activity_active_unit(
        catalyst_activity,
        complex_component
      )
    ) →
      complex_has_component_entity(complex,
        complex_component)
```

### 5.2 Compartment

The `Compartment` class has some quirks. In Reactome, the `Compartment`’s role in the `compartment_entity` association has multiplicity 0..\*. The problem is that the SBML model requires 1..1 multiplicity for this association to be simulated.

In Reactome there are currently (TODO: version??) 19 physical entities which don’t have a compartment (see queries/helper.cypher), so this can be easily solved by just adding a **default compartment** to the SBML model to which these entities map to.

On the other hand there are 14046 entities which have multiple compartments (TODO: how many compartments has each exactly?), so the easiest choice right now is to just pick any of them. For this reason the

### 5.3 Pathway

The instances of `Pathway` are organized hierarchically, i.e. all the signaling pathways are collected under the Signal Transduction top level `Pathway` (`StableIdVersion` R-HSA-162582.13). This allows to easily extract a subset of reactions by specifying the *target pathways* in a model and taking into consideration only the reactions which are included, both directly or indirectly, in that pathway (see the `included_reactions()` operation).

There are about 34 top level pathways.

```
included_reactions():ReactionLikeEvent [0..*]  
  postconditions  
    result =  
      { reaction |  
        ReactionLikeEvent(reaction) ∧  
        pathway_has_event(this, reaction) }  
    ∪  
    { reaction | ∃ pathway  
      Pathway(pathway) ∧  
      pathway_has_event(this, pathway) ∧  
      included_reactions(pathway, reaction) }
```


## 5.4 PhysicalEntity

The set of reactions which produce `this` is needed to determine the transitive closure of the *target entities*.

```
directly_produced_by() : ReactionLikeEvent [0..*]
  postconditions
    result = { reaction |
      ReactionLikeEvent(reaction) ∧ output(this,
      reaction)
    }
```

The set of instances of `DatabaseObject` which are directly or indirectly involved in the production of `this`.

```
produced_by() : DatabaseObject [0..*]
  postconditions
    result =
      { this } ∪
      { reaction | directly_produced_by(this, reaction) }
    ∪
      { object | ∃ reaction, reaction_input
        directly_produced_by(this, reaction) ∧
        (
          *input*(reaction, reaction_input) ∨
          (∃ catalyst_activity
            CatalystActivity(catalyst_activity) ∧
            *catalyzed_event*(
              catalyst_activity,
              reaction
            ) ∧
            *catalyst_activity_entity*(
              catalyst_activity,
              reaction_input
            )
          )
        )
      }
    }
```



## 6 Classes specification pt. 2

### 6.1 BiologicalScenarioDefinition

The following operation finds the transitive closure of the *target entities* specified in the scenario, by including only reactions within the *target pathways* if necessary.

```
model_objects():DatabaseObject [1..*]
  postconditions
    result = { object | ∃ entity
      PhysicalEntity(entity) ∧
      DatabaseObject(object) ∧
      target_physical_entity(this, entity) ∧
      produced_by(entity, object) ∧
      (
        ¬RestrictedDefinition(this) ∨
        ∃ pathway, reaction
          Pathway(pathway) ∧
          ReactionLikeEvent(reaction) ∧
          included_reactions(pathway, reaction) ∧
          (
            object = reaction ∨
            entity_reaction(object, reaction) ∨
            catalyzed_reaction(object, reaction)
          )
        )
      }
  }
```

## 6.2 ModelInstance

```
C.ModelInstance.no_local_parameters_without_value
  ∀ model_instance, model, reaction, kinetic_law,
    local_parameter
    (
      ModelInstance(model_instance) ∧
      Model(model) ∧
      ReactionDefinition(reaction) ∧
      KineticLaw(kinetic_law) ∧
      LocalParameter(local_parameter) ∧
      *instance_model*(model_instance, model) ∧
      *model_definition*(model, reaction) ∧
      *kinetic_law_reaction*(kinetic_law, reaction) ∧
      *kinetic_law_local_parameter*(kinetic_law,
local_parameter) ∧
      ¬ ∃ value
        value(local_parameter, value)
    ) →
      ∃ local_parameter_assignment

      LocalParameterAssignment(local_parameter_assignment) ∧
      *model_instance_parameter*(
        model_instance,
        local_parameter_assignment
      ) ∧
      *assignment_local_parameter*(
        local_parameter_assignment,
        local_parameter
      )
    )
```

## 6.3 SimulatedModelInstance

```
is_valid()
  postconditions
    . . .
```

## 6.4 Measurement

```
C.Measurement.species_in_model
  ∀ measurement, model_instance, model, species
    (
      Model(model) ∧
      SimulatedModelInstance(model_instance) ∧
      Measurement(measurement) ∧
      Species(species) ∧
```

```

        *measurement_species*(measurement, species) ∧
        *measurement_simulation*(measurement,
model_instance) ∧
        *instance_model*(model_instance, model)
    ) →
        *model_definition*(model, species)


```

## 6.5 UnitDefinition

[3, page 45]

TODO: better description

## 7 Use-case diagram



## 7.1 “Helper” use-case

```
yield_sbml_model(description: BiologicalScenarioDefinition):  
(SBMLDocument, )
```

```
    postconditions
```

```
        TODO:
```

- create necessary units (TODO: which? how?)
- create default `CompartmentDefinition`
- create `CompartmentDefinition` from `Compartment`
  - convert id to `SIId`
- create `SpeciesDefinition` from `PhysicalEntity`
  - convert id to `SIId`
  - add one of the compartments if the entity has any
  - otherwise assign to default
- create `ReactionDefinition`
  - convert id to `SIId`
  - connect products (inputs)
  - connect reactants (outputs)
  - connect modifiers (catalysts)
  - add kinetic law (either manually specified ∨ automatic, like `LawOfMassAction`)
  - add local parameters
- create constraints
  - i.e. from `known_range` attribute
- 

```
instantiate_model(model: SBMLDocument):ModelInstance
```

```
    postconditions
```

```
        TODO:
```

- add `LocalParameterAssignment` for undefined `LocalParameters`
- add environment parameters to model (`Parameter`)

```
simulate_model(instance: ModelInstance):SimulatedModelInstance
```

```
    postconditions
```

```
        TODO:
```

- generate measurements



## 8 OpenBox on the Slurm Workload Manager


The HPC cluster at the Computer Science Department has some restrictions in place, as it's used by many different teams / students and no single user can request the indefinite usage of the whole cluster for a single job (jobs have a time limit of 6, 24 or 72 hours based on permissions and resources required).

The goals of this section are to

- be able to run an OpenBox through **multiple sessions**
- run **multiple smaller jobs** to increase **fairness** among users, instead of running a single big job for the whole simulation
- provide a simple framework that can be used **locally to simulate** executions on the cluster

### 8.1 Analysis

In order to use OpenBox on the cluster in different sessions, it's a good idea to store the results of the simulations in a database (i.e. PostgreSQL) to retrieve the data of different session for an overall analysis.



#### 8.1.1 Data types specification

`SlurmJobId` = Integer  $\geq 1$

`String1` = String matching regex `/^\$|^\$.*\$ /`

## 8.1.2 Classes specification

### 8.1.2.1 Job

**C.Job.all\_parameters\_are\_instantiated**

```

 $\forall$  job, blackbox, parameter
(
  Job(job)  $\wedge$ 
  Blackbox(blackbox)  $\wedge$ 
  Parameter(parameter)  $\wedge$ 
  blackbox_job(blackbox, job)  $\wedge$ 
  blackbox_parameter(blackbox, parameter)
)  $\rightarrow$ 
  job_parameter(job, parameter)
```

**C.Job.continuity\_1**

```

 $\forall$  job, submit_time, start_time
(
  Job(job)  $\wedge$ 
  submit_time(job, submit_time)  $\wedge$ 
  start_time(job, start_time)
)  $\rightarrow$ 
  submit_time  $\leq$  start_time
```


**C.Job.continuity\_2**

```

 $\forall$  job, start_time, end_time
(
  Job(job)  $\wedge$ 
  start_time(job, start_time)  $\wedge$ 
  end_time(job, end_time)
)  $\rightarrow$ 
  start_time  $\leq$  end_time
```

## 8.2 Implementation

Diagram restructuring for PostgreSQL. The SQL code is available in the `migration.sql` file.



### 8.2.1 Data types definitions

```

CREATE DOMAIN String1 AS varchar CHECK(value ~ '^\S$|^\S.*\S$');
CREATE DOMAIN SlurmJobId AS integer CHECK(value >= 1);
  
```

### 8.2.2 Additional constraints

#### 8.2.2.1 Job

**C.Job.end\_implies\_job\_was\_scheduled**

$$\forall \text{ job, end\_time} \\ (\text{Job}(\text{job}) \wedge \text{end\_time}(\text{job, end\_time})) \rightarrow \\ \exists \text{ start\_time } \text{start\_time}(\text{job, start\_time})$$

A result is present if and only if the job ended

**C.Job.result\_only\_on\_end\_time**

$$\forall \text{ job, job\_result} \\ (\text{Job}(\text{job}) \wedge \text{result}(\text{job, job\_result})) \rightarrow \\ \exists \text{ end\_time } \text{end\_time}(\text{job, end\_time})$$

**C.Job.end\_time\_only\_on\_result**

$$\forall \text{ job, end\_time} \\ (\text{Job}(\text{job}) \wedge \text{end\_time}(\text{job, end\_time})) \rightarrow \\ \exists \text{ job\_result } \text{result}(\text{job, job\_result})$$

## Bibliography

- [1] [Online]. Available: <https://reactome.org/content/schema/DatabaseObject>
- [2] “Reactome.” [Online]. Available: <https://reactome.org/documentation/faq/37-general-website/201-identifiers>
- [3] [Online]. Available: <https://raw.githubusercontent.com/combine-org/combine-specifications/main/specifications/files/sbml.level-3.version-2.core.release-2.pdf>
- [4] [Online]. Available: <https://reactome.org/PathwayBrowser/>
- [5] [Online]. Available: [https://download.reactome.org/documentation/DataModelGlossary\\_V90.pdf](https://download.reactome.org/documentation/DataModelGlossary_V90.pdf)