



Praktikum WS0304

Formale Entwicklung objektorientierter Software

Introduction to OCL

Andreas Roth

Object Constraint Language

- Part of the UML standard.

Object Constraint Language

- Part of the UML standard.
- Formal Specification Language. Precise semantics.


Object Constraint Language

- **Part of the UML standard.**
- **Formal Specification Language. Precise semantics.**
- **(Quite) easy to read syntax.**

Object Constraint Language


- Part of the UML standard.
- Formal Specification Language. Precise semantics.
- (Quite) easy to read syntax.
- **Why?** Because UML is not enough!

UML is not enough...




- How many persons can own a car?
- How old must a car owner be?
- How can we require that a person must at most own one black car?

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: **self. owner. age \geq 18**


Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context **Vehicle**
inv: **self. owner. age** \geq 18

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: self. **owner**. age \geq 18

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: self. owner. **age** \geq 18

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: **self. owner. age \geq 18**

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context **Vehicle**


inv: **self. owner. age \geq 18**

What does this mean, instead?

context **Person**

inv: **self.age \geq 18**

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context **Vehicle**


inv: **self. owner. age \geq 18**

“A **car** owner must be at least 18 years old”:

context **Car**

inv: **self.owner.age \geq 18**

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context **Vehicle**


inv: **self. owner. age \geq 18**

“A **car** owner must be at least 18 years old”:

context **Car**


inv: **self.owner.age \geq 18**

Some OCL examples II



“Nobody has more than 3 vehicles”:

Some OCL examples II




“Nobody has more than 3 vehicles”:

context Person

inv: self.fleet->size <= 3


or change multiplicity

Some OCL examples II



“All cars of a person are black”:

Some OCL examples II




“All cars of a person are black”:

context **Person**

inv: **self.fleet→forAll(v | v.colour = #black)**

Some OCL examples II




“All cars of a person are black”:

context **Person**

inv: **self.fleet—>forAll(v | v.colour = #black)**

“Nobody has more than 3 black vehicles”:

Some OCL examples II



“All cars of a person are black”:

context **Person**


inv: **self.fleet—>forAll(v | v.colour = #black)**

“Nobody has more than 3 black vehicles”:

context **Person**

inv: **self.fleet—>select(v | v.colour = #black)—>size <= 3**

Some OCL examples III — iterate




What does it mean?

context **Person**


inv: **self.fleet—>iterate(v; acc:Integer=0**
 | if (v.colour=#black)
 then acc + 1 else acc endif) <=3

Some OCL examples IV — oclIsKindOf



context **Person**
inv: **age < 18 implies self.fleet->forAll(v | not v.oclIsKindOf(Car))**

Some OCL examples IV — oclIsKindOf




context **Person**

inv: **age < 18 implies self.fleet->forAll(v | not v.ocIsKindOf(Car))**

“A person younger than 18 owns no cars.”

Some OCL examples IV — oclIsKindOf




context **Person**

inv: **age < 18 implies self.fleet->forAll(v | not v.oclIsKindOf(Car))**

“A person younger than 18 owns no cars.”

“self” can be omitted.

Some OCL examples IV — oclIsKindOf



context Person


inv: age < 18 implies self.fleet->forAll(v | not v.oclIsKindOf(Car))

“A person younger than 18 owns no cars.”

“self” can be omitted.

Logical Junctors: and, or, not, implies, if...then...else...endif, =


Some OCL examples V — allInstances



context Car

inv: Car.allInstances()->exists(c | c.colour=#red)

Some OCL examples V — allInstances




context Car

inv: Car.allInstances()->exists(c | c.colour=#red)


“There is a red car.”

OCL pre-/post conditions — Examples



So far only considered class invariants.


OCL pre-/post conditions — Examples



So far only considered class invariants.

OCL can also specify operations:

OCL pre-/post conditions — Examples



So far only considered class invariants.

OCL can also specify operations:


“If `setAge(...)` is called with a not negative argument then the argument becomes the new value of the attribute `age`.”

context **Person::setAge(newAge:int)**

pre: **newAge >= 0**

post: **self.age = newAge**

OCL pre-/post conditions — Examples




So far only considered class invariants.

OCL can also specify operations:

“Calling `birthday()` increments the age of a person by 1.”

context **Person::birthday()**
post: **self.age = self.age@pre + 1**

OCL pre-/post conditions — Examples




So far only considered class invariants.

OCL can also specify operations:


“Calling `getName()` delivers the value of the attribute name.”

context **Person::getName()**
post: **result = name**



Special to OCL are operations with a `<<query>>` stereotype:

Only these operations can be used within an OCL expression.



Special to OCL are operations with a `<<query>>` stereotype:

Only these operations can be used within an OCL expression.

“Calling `getName()` delivers the value of the attribute name.”

context **Person**

inv: **`self.getName() = name`**

- OCL is used to specify **invariants** of objects and **pre- and post conditions** of operations. Makes UML (class) diagrams more precise.

- OCL is used to specify **invariants** of objects and **pre- and post conditions** of operations. Makes UML (class) diagrams more precise.
- OCL expressions use vocabulary of UML class diagram.

- OCL is used to specify **invariants** of objects and **pre- and post conditions** of operations. Makes UML (class) diagrams more precise.
- OCL expressions use vocabulary of UML class diagram.
- OCL attribute accesses “navigate” through UML class diagram.

- OCL is used to specify **invariants** of objects and **pre- and post conditions** of operations. Makes UML (class) diagrams more precise.
- OCL expressions use vocabulary of UML class diagram.
- OCL attribute accesses “navigate” through UML class diagram.
- “context” specifies about which elements we are talking.

- OCL is used to specify **invariants** of objects and **pre- and post conditions** of operations. Makes UML (class) diagrams more precise.
- OCL expressions use vocabulary of UML class diagram.
- OCL attribute accesses “navigate” through UML class diagram.
- “context” specifies about which elements we are talking.
- “self” indicates the current object. “result” the return value.

- OCL can talk about collections (here: sets).

Operations on collections: →

Example operations: select, forAll, iterate

- OCL can talk about collections (here: sets).

Operations on collections: →

Example operations: select, forAll, iterate

- “iterate” can simulate all other operations on collections.

- **OCL can talk about collections (here: sets).**

Operations on collections: →

Example operations: select, forAll, iterate

- **“iterate” can simulate all other operations on collections.**
- **Queries (= side effect free operations) can be used in OCL expressions.**

TogetherCC itself cannot process OCL constraints. It is however possible to specify textual invariants and pre- and post conditions.

With the KeY-extensions to TogetherCC syntax (type) checks of OCL constraints are possible.


System state



System state




(depicted by a UML object diagram)



System state



(depicted by a UML object diagram)




context **Vehicle**

inv: **self.owner.age \geq 18**

System state



(depicted by a UML object diagram)




context **Vehicle**

inv: **self.owner.age \geq 18** ✓

System state



(depicted by a UML object diagram)



context **Vehicle**

inv: **self.owner.age \geq 18** ✓


context **Person**

inv: **self.fleet \rightarrow forAll(v | v.colour = #black)**

System state



(depicted by a UML object diagram)



context **Vehicle**

inv: **self.owner.age \geq 18** ✓


context **Person**

inv: **self.fleet \rightarrow forAll(v | v.colour = #black)** ✗

System state



(depicted by a UML object diagram)



context Vehicle

inv: self.owner.age \geq 18 ✓

context Person

inv: self.fleet \rightarrow forAll(v | v.colour = #black) ✗


context Person

inv: self.fleet \rightarrow select(v | v.colour = #black) \rightarrow size \leq 3

System state



(depicted by a UML object diagram)



context Vehicle

inv: self.owner.age \geq 18 ✓

context Person

inv: self.fleet \rightarrow forAll(v | v.colour = #black) ✗


context Person

inv: self.fleet \rightarrow select(v | v.colour = #black) \rightarrow size \leq 3 ✓

System state



(depicted by a UML object diagram)



context Vehicle
inv: self.owner.age \geq 18 ✓


context Person
inv: self.fleet \rightarrow forAll(v | v.colour = #black) ✗

context Person
inv: self.fleet \rightarrow select(v | v.colour = #black) \rightarrow size \leq 3 ✓
inv: Car.allInstances() \rightarrow exists(c | c.colour = #red)

System state



(depicted by a UML object diagram)



context Vehicle

inv: self.owner.age ≥ 18 ✓

context Person

inv: self.fleet \rightarrow forAll(v | v.colour = #black) ✗

context Person


inv: self.fleet \rightarrow select(v | v.colour = #black) \rightarrow size ≤ 3 ✓

inv: Car.allInstances() \rightarrow exists(c | c.colour = #red) ✗

System State



(depicted by a UML object diagram)




context **Person::getName()**

post: **result = name**

System State



(depicted by a UML object diagram)



context **Person::getName()** **?**
post: **result = name**

Given a UML class diagram, a system state (snapshot) is defined by

- **a UML object diagram (for the class diagram), giving**

Given a UML class diagram, a system state (snapshot) is defined by

- a UML object diagram (for the class diagram), giving
 - the set of existing instances,

Given a UML class diagram, a system state (snapshot) is defined by

- **a UML object diagram (for the class diagram), giving**
 - **the set of existing instances,**
 - **attribute-value-assignments**

Given a UML class diagram, a system state (snapshot) is defined by

- **a UML object diagram (for the class diagram), giving**
 - **the set of existing instances,**
 - **attribute-value-assignments**
 - **instances of associations (“links”)**

Given a UML class diagram, a system state (snapshot) is defined by

- **a UML object diagram (for the class diagram), giving**
 - **the set of existing instances,**
 - **attribute-value-assignments**
 - **instances of associations (“links”)**
- **an interpretation for operations,**

Given a UML class diagram, a system state (snapshot) is defined by

- **a UML object diagram (for the class diagram), giving**
 - **the set of existing instances,**
 - **attribute-value-assignments**
 - **instances of associations (“links”)**
- **an interpretation for operations,**
- **(standard) interpretation for predefined primitive data types**
(e.g. Integer, String, . . .)

- **OCCL Constraints are satisfied by certain system states.**

- **OCL Constraints are satisfied by certain system states.**
- **Given an implementation of a class diagram, a sequence of system states is reached.**

- OCL Constraints are satisfied by certain system states.
- Given an implementation of a class diagram, a sequence of system states is reached.
- The interesting question is: How can we check that constraints are satisfied in **all** system states that are reached by an implementation?

- OCL Constraints are satisfied by certain system states.
- Given an implementation of a class diagram, a sequence of system states is reached.
- The interesting question is: How can we check that constraints are satisfied in **all** system states that are reached by an implementation?

Answer in three weeks.

P. Schmitt:

Skript "Formale Spezifikationssprachen"

Jos Warmer and Anneke Kleppe:

The Object Constraint Language: Precise Modelling with UML.

UML 1.5 OCL Specification.

<http://www.omg.org/cgi-bin/apps/doc?ad/03-01-07.pdf>

UML 2.0 OCL Revised submission to OMG.

<http://www.omg.org/cgi-bin/apps/doc?ad/03-01-07.pdf>