

Denotational Semantics

A4M36TPJ, 2013/2014

Operational Semantics

- Usually well suited for reasoning about whole programs, less than ideal for reasoning about program fragments.
- Sometimes tends to overspecify the implementation of certain language features (e.g. evaluation order).
- Tends to put emphasis on syntax (rather than semantics) of the language.

Denotational Semantics

- Meaning of a program can be determined from the meaning of its parts.
- Unlike an operational semantics, a denotational semantics emphasizes ***what*** the meaning of a phrase is, not ***how*** the phrase is evaluated.

Denotational Semantics

- Consists of three parts:
 - **Syntactic Algebra**
 - **Semantic Algebra**
 - **Meaning Function**

Syntactic Algebra

- Describes abstract syntax of the language.
- Can be specified by a grammar.

Semantic Algebra

- Models the meaning of program phrases.
- Consists of a collection of semantic domains along with functions that manipulate these domains.
- The meaning of a program may be as simple as an element of a primitive semantic domain like `Int`, the domain of integers.
- More typically, the meaning of a program is an element of a function domain that maps **context domains** to an **answer domain**.

Context Domains

- Denotational analogue of state components.
- Model such entities as name/value associations, contents of memory, and control information.

Answer Domains

- Represent the possible meanings of programs.
- Include components that model context information that was transformed.

Meaning Function

- Maps elements of the ***syntactic algebra*** (i.e., nodes in the abstract syntax trees) to their meanings in the ***semantic algebra***.
- Usually a collection of so-called ***valuation*** functions, one for each ***syntactic domain*** defined by the ***abstract syntax*** for the language.
- The function must be a **homomorphism** between the syntactic algebra and the semantic algebra.

Meaning Function


Suppose M is a meaning function and t is a node in an *abstract syntax tree*, with children t_1, \dots, t_k . Then

$$(M\ t) = (f_t\ (M\ t_1)\ \dots\ (M\ t_k))$$

where f_t is a function that is determined by the syntactic class of t .

The reason to restrict meaning functions to homomorphisms is that their structure-preserving behavior greatly simplifies reasoning.

Denotational Semantics Game



Expression Language

Syntax

$$\begin{aligned} Expr ::= & Num \mid \\ & \Delta Expr \mid \\ & Expr \odot Expr \end{aligned}$$

Semantics

Semantic domain: N .

$$\llbracket n \rrbracket = n$$

$$\llbracket \Delta e \rrbracket = \llbracket \Delta \rrbracket(\llbracket e \rrbracket)$$

$$\llbracket \Delta \rrbracket = \lambda x. -x \text{ (i.e. unary minus)}$$

$$\llbracket e_1 \odot e_2 \rrbracket = \llbracket \odot \rrbracket(\llbracket e_1 \rrbracket, \llbracket e_2 \rrbracket)$$

$$\llbracket \odot \rrbracket = \lambda x, y. x + y \text{ (i.e. plus)}$$

Logic Formulae Language

Syntax

$$\begin{aligned} \textit{Formula} ::= & \textit{true} \mid \\ & \textit{false} \mid \\ & \neg \textit{Formula} \mid \\ & \textit{Formula} \textit{ BinaryConnective } \textit{Formula} \end{aligned}$$
$$\textit{BinaryConnective} ::= \wedge \mid \vee$$

Semantics

Semantic domain: $\{0, 1\}$.

$$\llbracket true \rrbracket = 1$$

$$\llbracket false \rrbracket = 0$$

$$\llbracket \neg f \rrbracket = \llbracket \neg \rrbracket(\llbracket f \rrbracket)$$

$$\llbracket \neg \rrbracket = \lambda x. 1 - x$$

Semantics

$$\llbracket f_1 \ c \ f_2 \rrbracket = \llbracket c \rrbracket(\llbracket f_1 \rrbracket, \llbracket f_2 \rrbracket) \quad (c \in \textit{BinaryConnective})$$

$$\llbracket \wedge \rrbracket = \lambda x, y. x \cdot y$$

$$\llbracket \vee \rrbracket = \lambda x, y. (x + y) - (x \cdot y)$$

Regular Expressions

Syntax

$$\begin{aligned} \textit{RegExp} ::= & \emptyset \mid \\ & \epsilon \mid \\ & A \mid \\ & \textit{RegExp}^* \mid \\ & \textit{RegExp} \textit{BinOp} \textit{RegExp} \\ \textit{BinOp} ::= & + \mid \cdot \end{aligned}$$

where A is a predefined set of characters (alphabet).

Semantics

Semantic domain: A^* .

$$\llbracket \emptyset \rrbracket = \{ \}$$

$$\llbracket \epsilon \rrbracket = \{ \epsilon \}$$

$$\llbracket a \rrbracket = \{ a \}$$

$$\llbracket e^* \rrbracket = \llbracket * \rrbracket (\llbracket e \rrbracket)$$

Semantics

$$\llbracket^* \rrbracket = \lambda L. \{l_1 \cdot \dots \cdot l_n \mid n \in N \wedge l_i \in L\} \quad (\text{note: including } \epsilon)$$

$$\llbracket e_1 \ o \ e_2 \rrbracket = \llbracket o \rrbracket(\llbracket e_1 \rrbracket, \llbracket e_2 \rrbracket) \quad (o \in \textit{BinOp})$$

$$\llbracket + \rrbracket = \cup$$

$$\llbracket \cdot \rrbracket = \lambda A, B. \{a \cdot b \mid a \in A \wedge b \in B\}$$

Lambda Calculus

Syntax

$$\begin{aligned} Expr ::= & X \mid \\ & \lambda X. Expr \mid \\ & Expr Expr \end{aligned}$$

Semantics

Semantic domains: $env = string \rightarrow function$, $fcn = fcn \rightarrow fcn$; notational conventions $e \in env$, $f, f' \in fcn$, $E, E' \in Expr$

$$\llbracket x \rrbracket = \lambda e. e(x) \tag{26}$$

$$\llbracket \lambda x. E \rrbracket = \lambda e. \lambda p. \llbracket E \rrbracket (e[x \mapsto p]) \tag{27}$$

$$\llbracket E_1 \ E_2 \rrbracket = \lambda e. (\llbracket E_1 \rrbracket (e)) (\llbracket E_2 \rrbracket (e)) \tag{28}$$