

# AVALON

## OUTLINE OF NEW FEATURES

### 1. 1MZ-FE Engine

The TOYOTA genuine Super Long Life Coolant (SLLC) has been adopted. As result, the maintenance interval has been extended.

#### ► Specifications ◀

Model			New	Previous
Engine Coolant	Capacity liters (US qts, Imp.qts)		9.0 (9.5, 7.9)	←
	Type		TOYOTA Genuine SLLC	TOYOTA Genuine LLC
	Color		Pink	Red
	Maintenance Intervals	First time	160,000 km (100,000 mile)	Every 40,000 km (25,000 mile) or 24 months whichever comes first
		Subsequent	Every 80,000 km (50,000 mail)	
Thermostat	Operating Temperature °C (°F)		80 – 84 (176 – 183)	←

- SLLC is pre-mixed (50 % coolant and 50 % distilled water), so no dilution is needed when adding or replacing SLLC in the vehicle.
- If LLC is mixed with SLLC, the interval for LLC (every 40,000 km/25,000 mile or 24 months) should be used.
- You can also apply the new maintenance interval (every 80,000 km/50,000 mile) to vehicles initially filled with LLC (red-colored), if you use SLLC (pink-colored) for the coolant change.

### 2. Headlight Level Control System

A headlight beam level control system is used as standard equipment on all models.