DI3PE-01

DTC P1128/89\* Throttle Control Motor Lock Malfunction

# **CIRCUIT** DESCRIPTION

Throttle motor sperated by the engine ECU and it opens and closes the throttle valve.

The pening angle of the throttle valve is detected by the throttle position sensor which is mounted on the throttle pody and to provide the throttle pody and to provide the throttle pody and the thr

If this DTC is stored, the regine ECU shuts down the power for the throttle motor and the magnetic clutch, and the throttle valve is fully closed by the return spring.

 $However, \center{like pening angle for the controlled by the accelerator \center{like throttle for the controlled by the accelerator \center{like throttle for the controlled by the like throttle for throttle for the like throttle for the like$ 

	DTC[No.	DTC[Detecting[Condition	Trouble[ <u>A</u> rea
	P11 <u>2</u> 8/89	Lock[hrottlecontrol]motor@uringcontrol[hrottlecontrol]motor	■ Throttle tontrol motor  ■ Throttle tody assembly ■ Engine ECU

## **WIRING DIAGRAM**

Refer[]o[DTC[P11[25/89[]Throttle[Control[Motor[Circuit[Malfunction)]pn[page[DI-85[]or[]he WIRING[DIAGRAM.

# **INSPECTION PROCEDURE**

HINT:

Read [freeze frame data using hand-held tester. Because freeze frame freeze frame from the malfunction is detected, when frouble shooting it is useful for determining whether the vehicle was funning or stopped, the engine warmed up or not, the air-fuel ratio lean or rich, etc. at the time of the malfunction.

1 Check[throttle[control[motor[See[page[DI-85,[step[2]).


NG

Replace throttle control motor (See page FI-45).

OK

<sup>\*:[</sup>ETCS[trouble[code[No.[is[31.

2 Visualy check throttle valve.



### **PREPARATION:**

Remove the intake air connector.

### **CHECK:**

Check whether or not a foreign body is caught between the throttle valve and the housing.

NG

Remove a foreign body and clean throttle body.

OK

Replace throttle body.