

‘org-trello’ Manual

Sync Emacs org-mode with Trello.com.

Manual by Daniel Birket
Package by Antoine R. Dumont

This is the ‘org-trello’ Manual, edition 0.8.1.a, released 2019-01-30, written and copyright ©2019 by Daniel Birket.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled GNU Free Documentation License.

This manual describes how to install and use the Emacs package ‘org-trello’, version 0.8.1, released 2018-03-18, written and copyright ©2013-2017 by Antoine Dumont, to synchronize org-mode TO-DO lists with Trello.com (<https://trello.com>).

This manual was written with reference to the ‘org-trello’ source-code, which begins with this license and non-warranty statement:

```
;;; org-trello.el
;;; Minor mode to synchronize org-mode buffer and trello board

;;; Copyright (C) 2013-2017 by Antoine R. Dumont (@ardumont)
;;; Author: Antoine R. Dumont <antoine.romain.dumont@gmail.com>
;;; Maintainer: Antoine R. Dumont

;;; Version: 0.8.1
;;; URL: https://github.com/org-trello/org-trello

;;; This file is NOT part of GNU Emacs.

;;; This program is free software; you can redistribute it and/or modify
;;; it under the terms of the GNU General Public License as published by
;;; the Free Software Foundation; either version 3, or (at your option)
;;; any later version.
;;;
;;; This program is distributed in the hope that it will be useful,
;;; but WITHOUT ANY WARRANTY; without even the implied warranty of
;;; MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
;;; GNU General Public License for more details.
```

Table of Contents

| | | |
|----------|---|-----------|
| 1 | CHEK About ‘org-trello’ | 1 |
| 2 | TODO Demo Videos | 2 |
| 3 | Installing ‘org-trello’ | 3 |
| 3.1 | Installing ‘org-trello’ using Package (recommended) | 3 |
| 3.1.1 | Using MELPA with Package | 3 |
| 3.1.2 | Installing from MELPA with Package | 3 |
| 3.2 | Alternate Ways to Install | 4 |
| 3.2.1 | Download and Install the Tarball | 4 |
| 3.2.2 | Get and Install with el-get | 4 |
| 3.2.3 | Clone from GitHub and Install with Cask | 4 |
| 3.3 | Loading ‘org-trello’ in Emacs | 4 |
| 3.4 | Using the ‘org-trello’ manual | 5 |
| 3.4.1 | Building the Manual | 7 |
| 3.4.2 | Installing the .info Manual | 7 |
| 3.5 | Migrating to New Releases | 7 |
| 3.5.1 | Migrate to 0.8.1 | 7 |
| 3.5.2 | Migrate to 0.7.0 | 8 |
| 3.5.3 | Migrate to 0.6.7 | 8 |
| 3.5.4 | Migrate to 0.6.6 | 8 |
| 3.5.5 | Migrate to 0.5.5 | 8 |
| 3.5.6 | Migrate to 0.5.3 | 8 |
| 3.5.7 | Migrate to 0.5.2 | 8 |
| 3.5.8 | Migrate to 0.3.8 | 9 |
| 3.5.9 | Migrate to 0.3.1 | 9 |
| 3.5.10 | Migrate to 0.2.9 | 9 |
| 3.5.11 | Migrate to 0.2.8 | 9 |
| 3.5.12 | Migrate 0.2.1 to 0.2.2 | 9 |
| 3.5.13 | Migrate 0.1.5 to 0.1.6 | 9 |
| 3.5.14 | Migrate 0.1.1 to 0.1.2 | 10 |
| 4 | CHEK Connecting to Trello.com | 11 |
| 4.1 | Installing Your Trello.com Credentials | 11 |
| 4.2 | Connect an org-mode buffer with an existing Trello board. | 13 |
| 4.3 | Create a Trello board from your org-mode buffer. | 13 |
| 5 | WORK Using ‘org-trello’ | 14 |
| 5.1 | CHEK Quick Start | 14 |
| 5.2 | Command Descriptions | 14 |
| 5.2.1 | CHEK Summary of Commands | 14 |

| | | |
|-------------------|--|-----------|
| 5.2.2 | TODO Help Commands | 15 |
| 5.2.3 | TODO Connection Commands | 15 |
| 5.2.4 | WORK Synchronization Commands | 15 |
| 5.2.5 | TODO Editing Commands | 15 |
| 5.2.6 | TODO Misc. Commands | 15 |
| 5.3 | TODO How to | 15 |
| 5.4 | CHEK Format of org-trello | 15 |
| 6 | CHEK Troubleshooting ‘org-trello’ | 17 |
| 6.1 | Common Issues | 17 |
| 6.2 | Error Messages | 17 |
| 7 | Customizing ‘org-trello’ | 19 |
| 7.1 | Customizing the Prefix Keybinding | 19 |
| 7.2 | Customizing Individual Keybindings | 19 |
| 7.3 | Customizing ‘org-trello’ Variables | 20 |
| 7.4 | Example Emacs-Lisp Customization | 21 |
| 7.5 | Automatic ‘org-trello’ Files | 22 |
| 8 | Development of ‘org-trello’ | 23 |
| 8.1 | Credits | 23 |
| 8.2 | Issue List | 23 |
| 8.2.1 | Using ‘M-x org-trello-bug-report’ | 24 |
| 8.2.2 | Using ‘orgtrello-log-trace’ | 25 |
| 8.3 | Mailing List | 25 |
| 8.4 | Release List and Notes | 25 |
| 8.5 | Compatibility with Emacs | 25 |
| 8.6 | Continuous Integration Tests | 25 |
| 8.7 | Developer’s Conventions | 26 |
| 8.7.1 | Sources | 26 |
| 8.7.2 | Makefile | 27 |
| Appendix A | GNU General Public License | 29 |
| Appendix B | GNU Free Documentation License .. | 40 |
| Appendix C | TODO Indices | 48 |
| C.1 | Concepts Index | 48 |
| C.2 | Commands Index | 48 |
| C.3 | Functions Index | 48 |
| C.4 | Variables Index | 48 |

1 CHEK About ‘org-trello’



- Why use ‘org-trello’?
 - You use Emacs org-mode (<https://orgmode.org>).
 - Your team uses Trello.com (<https://trello.com/>).
 - ‘org-trello’ is the bridge between org-mode and Trello.com.
 - Everyone wins!
- Links:
 - Download Zip (<https://github.com/org-trello/org-trello/zipball/master>)
 - Download Tarball (<https://github.com/org-trello/org-trello/tarball/master>)
 - View on GitHub (<https://github.com/org-trello/org-trello>)
- What does your page title ‘org <\$> trello’ mean?

It means “map org functions to the trello world”.

At the time, I was learning Haskell and it made an everlasting awesome impression on me. See `fmap`’s documentation for more detail (<http://hackage.haskell.org/package/base-4.9.1.0/docs/Prelude.html#v:fmap>).

2 TODO Demo Videos

Please see the HTML version of this manual for links to the demonstration videos. They are not included in the info and PDF-format manuals.

3 Installing ‘org-trello’

This section describes how to obtain and install the ‘org-trello’ package and manual.

3.1 Installing ‘org-trello’ using Package (recommended)

This section describes how to use ‘package’ to install ‘org-trello’.

3.1.1 Using MELPA with Package

This section describes how to use ‘package’ to download and install any packages including ‘org-trello’. If you already use ‘package’ to access “melpa” or “melpa-stable”, you don’t need to do this again. See the next section for how to install ‘org-trello’.

MELPA.org (<https://melpa.org>) is a large repository of ready-to-install Emacs packages. There are two flavors: melpa and melpa-stable. Melpa usually contains the bleeding-edge version of each package. Melpa-stable should contain the last stable releases of the same packages, but the two may be the same. Use Melpa if you like to help test the latest features. Use Melpa-Stable if you want something that just works.

Add the code snippet below (from melpa.org (<https://melpa.org/#/getting-started>)) to your Emacs startup file (.emacs or .emacs.d/init.el). The Melpa repository is pre-selected. If you prefer Melpa-stable, comment out the line for Melpa and uncomment the line for Melpa-stable.

```
;; https://melpa.org/#/getting-started
(require 'package)
(let* ((no-ssl (and (memq system-type '(windows-nt ms-dos))
                  (not (gnutls-available-p))))
      (proto (if no-ssl "http" "https")))

  ;; Comment/uncomment these two lines to enable/disable MELPA and MELPA Stable as des
  (add-to-list 'package-archives (cons "melpa" (concat proto "://melpa.org/packages/"))
  ;;(add-to-list 'package-archives (cons "melpa-stable" (concat proto "://stable.melpa
  (when (< emacs-major-version 24)
    ;; For important compatibility libraries like cl-lib
    (add-to-list 'package-archives (cons "gnu" (concat proto "://elpa.gnu.org/packages
  (package-initialize)
```

After you add this code snippet, exit and restart Emacs or use M-x eval-buffer to re-evaluate your initialization file.

3.1.2 Installing from MELPA with Package

This section describes how to download and install ‘org-trello’ once you have installed Package and configured it to access MELPA.

To load the latest package list from MELPA, type M-x package-refresh-contents.

To install ‘org-trello’ from Melpa, type M-x package-install RET org-trello RET.

Once you have installed the package, please see Section 3.3 [Loading ‘org-trello’ in Emacs], page 4.

3.2 Alternate Ways to Install

This section describes alternate ways to install if you do not use Package and Melpa as recommended.

Note org-trello’s Marmalade package (<http://marmalade-repo.org/packages/org-trello>) is no longer maintained. Use melpa-stable package (<http://melpa-stable.milkbox.net/#/org-trello>) instead.

3.2.1 Download and Install the Tarball

To retrieve the tarball from github (<https://github.com/org-trello/org-trello/releases>), type this at the command line, substituting the /path/to your chosen folder. Replace “0.8.1” with the current version, if different.

```
VERSION="0.8.1"
```

```
wget https://github.com/org-trello/org-trello/releases/download/$VERSION/org-trello-$V
```

Alternately, navigate to ‘org-trello’ on github (<https://github.com/org-trello/org-trello>) with a browser and click on the “releases” link, then locate and download the same file.

Then, inside Emacs, type M-x package-install-file RET /path/to/org-trello-0.8.1.tar RET

3.2.2 Get and Install with el-get

If you use el-get (<https://github.com/dimitri/el-get>) to install packages, you may install the ‘org-trello’ recipe (<https://github.com/dimitri/el-get/blob/master/recipes/org-trello.rcp>) with it. Inside Emacs, type: M-x el-get-install RET org-trello RET.

3.2.3 Clone from GitHub and Install with Cask

Use this section only if you are a developer modifying and testing ‘org-trello’.

Clone ‘org-trello’ from GitHub:

```
git clone http://github.com/org-trello/org-trello.git
```

You can use Cask (<https://cask.github.io/>) to make a local tarball and then install using Emacs:

```
make install package
```

Note ‘install’ will download Cask and ‘package’ will create an ‘org-trello’ tarball archive containing ‘org-trello’.

Now install the built ‘org-trello-\$VERSION.tar’ using Emacs. Type:

```
M-x package-install-file RET /path/to/org-trello-$VERSION.tar RET
```

3.3 Loading ‘org-trello’ in Emacs

Once ‘org-trello’ is installed, it must be loaded into Emacs before it can be used, preferably during initialization of Emacs. Add this in your emacs configuration file (“~/emacs” or “~/emacs.d/init.el”) to load ‘org-trello’ when Emacs starts:

```
(require 'org-trello)
```


Note We do not recommend starting `org-trello-mode` for every org-mode buffer (see <https://github.com/org-trello/org-trello/issues/209>). ‘org-trello’ is an org minor mode that adds trello abilities that unfortunately limit org’s power. It should only be applied to buffers synced with trello.com.

There is a variable to activate ‘org-trello’ only for specific files:

For example: to activate ‘org-trello’ when opening ‘/path/to/file0’ and ‘/path/to/file1’.

```
(custom-set-variables '(org-trello-files '("/path/to/file0" "/path/to/file1")))
```

3.4 Using the ‘org-trello’ manual

This section describes how to build and install the TexInfo-format “org-trello Manual”. TexInfo is the standard documentation format of the GNU-project and is used by Emacs and org-mode. (org-trello is NOT part of GNU emacs.) This manual is presented in three formats:

- INFO hyper-linked text format, to read from within Emacs (or with “info” at the command-line).
- HTML format, to read with a web-browser.
- PDF format, to read or print nicely-formatted on paper.

This org-trello manual may be installed in a folder on your INFOPATH and listed in the INFO directory of manuals. You may access the INFO manual directory of manuals from within Emacs by typing “C-h i d” or from the command-line using the command “info”.




Figure: Building the Manual with Texinfo

3.4.1 Building the Manual

It should not be necessary to rebuild the org-trello manual. The manual is distributed with all three formats already built and ready to read. If the org-trello.info, .HTML and .PDF files already exist, you don’t need to read this section.

This manual was written with Emacs and org-mode as “org-trello.org”, then exported to Texinfo format as “org-trello.texi” using the Texinfo exporter included with org-mode. Then, the .texi file should be converted to .info, .HTML, or .PDF using the commands included with the Texinfo package.

The “Makefile” includes the commands to make all three formats when you invoke it with “make all”. You may also request “make info”, “make view” (to view the new info manual), “make html” and “make pdf”. For any of these commands, you must install Texinfo and edit the top of the Makefile to provide the location of the Texinfo commands.

If you lack Texinfo, you may instead export org-trello.org directly to .info, .HTML or .PDF using Emacs. Without Texinfo, the resulting HTML or PDF document will be slightly different and will not have an index. Texinfo creates a more attractive manual and conforms to GNU style.

3.4.2 Installing the .info Manual

To install the org-trello.info manual so that it may be used by Emacs’ internal info reader or the command-line “info” command, you must:

1. Optionally, use gzip to compress the .info file to .info.gz
2. Copy or “install” the .info.gz (or .info) file into a folder listed in INFOPATH
3. Use “install-info” to insert the new .info.gz file into info’s “dir” file in that folder.

This process is described in the Section “Creating an Info File” in `texinfo`.

If you edit the top of the “Makefile” to provide the location of the folder in your INFOPATH where the .info should be installed, the “Makefile” will execute the gzip, install and install-info commands when you type “make install”.

Once installed, you may invoke the command-line “info” reader or Emacs’ internal info reader to view the listing of info manuals. The info reader assembles the directory of info manuals from all the “dir” files in the INFOPATH and may be different in each reader. Locate “org-trello” in this list or use “m org-trello” to jump to it.

3.5 Migrating to New Releases

If you have previously installed and used a previous release of ‘org-trello’, this section describes how to migrate your existing ‘org-trello’ installation to a new release.

3.5.1 Migrate to 0.8.1

The ‘org-trello’ key properties used in the buffer were clashing with higher org-mode functionality (lookup, cf. <https://github.com/org-trello/org-trello/issues/366>).

Those properties were renamed with clash free names (‘-’ separator symbol was replaced with ‘_’).

To help the migration, a routine has been integrated. This should not be needed by the user though (the migration is integrated to the actions). Still, if the user wants it, (s)he can do it through M-x `org-trello-migrate-buffer`.

3.5.2 Migrate to 0.7.0

As of now, ‘org-trello’ respects elisp conventions regarding the setup file location. So the default `~.trello//` will be moved silently to `~.emacs.d/.trello//`

Also, now users can use multiple trello accounts. So, provided you have multiple accounts, some commands will ask you when they need you to choose an account. Also, a silent migration will occur to existing buffers. For example, if you have a buffer setup-ed with a user *tony*, your existing configuration file `~.trello/config.el/` will be moved to `~.emacs.d/.trello/tony.el/`

Again, ‘org-trello’ tries to respect elisp conventions regarding command names. So the command names have been renamed from *org-trello/* to *org-trello-*. Still, the old command names are available.

3.5.3 Migrate to 0.6.7

The comments are now displayed inline in the card. So the binding to show the comments have been removed. To see comments, simply unfold the card.

3.5.4 Migrate to 0.6.6

We can now remove a comment at point (if we are the owner of the comment). Use `M-x org-trello-delete-card-comment`.

3.5.5 Migrate to 0.5.5

Default bindings have been updated.

| Bindings | Action |
|----------|---|
| C-c o C | Add comments to the cards at point. To show the cards comments, use <code>C-u M-x org-trello-add-card-comments</code> (<code>C-u C-c o C</code>) |
| C-c o o | Removed. To show the cards comments, use <code>C-u C-c o C</code> |

Of course, as usual, if you are not happy with this, simply update your configuration file (`bindings.html#bindings-override`).

3.5.6 Migrate to 0.5.3

Lots of work has been done to make ‘org-trello’:

- more responsive (almost no more blocking actions).
- faster (trello queries have been improved to let the trello servers do the computations)

Default interactive commands (`http://org-trello.github.io/bindings.html#keybindings`) names have been renamed to be explicit and aligned between them.

3.5.7 Migrate to 0.5.2

Decision has been taken to remove the intermediary proxy used to bounce requests to trello. This was introduced to permit asynchronous requests. This was only partially applied. So too many lines of code to maintain for small benefits.

This version is synchronous as it was in the beginning (The base code is not the same though).

This is a temporary setback. We need time to craft a better implementation for asynchronous requests (deferred, async libraries seems interesting enough).

3.5.8 Migrate to 0.3.8

‘org-trello’ now tries to enforce symmetry, mainly regarding the sync actions. So by default, an action pushes to trello. Using C-u, the symmetric action pulls from trello.

| Bindings | Action |
|-------------|---|
| C-c o c | sync the entity TO trello without its structure |
| C-u C-c o c | sync the entity FROM trello without its structure |
| C-c o C | sync the entity and its structure TO trello |
| C-u C-c o C | sync the entity and its structure FROM trello |
| C-c o s | sync the buffer TO trello |
| C-u C-c o s | sync the buffer FROM trello |
| C-c o a | assign yourself to the card |
| C-u C-c o a | unassign yourself from the card |

3.5.9 Migrate to 0.3.1

The old checklist/item format has been removed - <https://github.com/org-trello/org-trello/issues/105>. Now the org checkbox way is the standard one.

3.5.10 Migrate to 0.2.9

For information, from 0.2.9 onward, the property “orgtrello-id” from the checkbox (checklists, items) will be hidden.

Note

- Upon activating ‘org-trello’ minor mode, all existing checkbox will be migrated and should disappear before your eyes.
- Symmetrically, when deactivating ‘org-trello’, all checkbox will appear.
- For this, ‘org-trello’ use overlays (https://www.gnu.org/software/emacs/manual/html_node/elisp/Overlays.html) (implementation detail which permits to hide buffer region).

If you began to use ‘org-trello’, nothing to do.

3.5.11 Migrate to 0.2.8

From 0.2.8 onward, the card description can be synchronized too. Just synchronize as usual.

3.5.12 Migrate 0.2.1 to 0.2.2

From the 0.2.2 version onward, we can assign people to card. As a pre-requisite, we need to re-install the board (C-c o I), so that new properties will be installed (users currently assigned to the board we attach to).

This way, you will be able to use the assign (C-c o a) / unassign (C-c o u) yourself to the card.

3.5.13 Migrate 0.1.5 to 0.1.6

‘org-trello’ now uses more natural ways of dealing with checklists using checkboxes!

cf. natural org format (from 0.1.6 onwards) ([migration.html#natural-org-format-from-016-onwards](#)) for more details.

3.5.14 Migrate 0.1.1 to 0.1.2

- From version 0.1.1, some http requests will be asynchronous. For this, we use elnode as a proxy server to make requests to trello. The elnode server is started on the port 9876. You can always change this port

```
(setq *ORGTRELLO-PROXY-PORT* 9876)
```

Then M-x orgtrello-proxy/reload

4 CHEK Connecting to Trello.com

4.1 Installing Your Trello.com Credentials

You must install the `org-trello-consumer-key` and the read-write `org-trello-access-token` to permit `org-trello` to access your trello boards.

Note: This procedure only needs to be done once unless you revoke the token.

First, ensure that:


- emacs is configured to use an external web browser. Text-only web browsers internal to Emacs, like `'eww'`, `'w3'` or `'w3m-mode'`, can not execute the required JavaScript.
- the web browser emacs is configured to use is started
- you are logged into Trello.
- you know your exact Trello account name. **DO NOT** use your email address as your account name. To confirm your account name, check that `https://trello.com/*your-account-name*` exists.

Then, in Emacs, type:


- C-c o i, or
- M-x `org-trello-install-key-and-token`

This command will:

- ask for an account name, which must be your trello login. **DO NOT** use your email address as your account name.
- open your browser for you to select and copy your *org-trello-consumer-key* (Developer API Keys / key entry) and paste it inside emacs' minibuffer (hit RET when done).



- open a second tab to ask you to authorize `org-trello` to work in your name on your account



- If you are not ok with this, hit *Deny*. You won't be able to use org-trello.
- Otherwise, hit *Allow*, this will then present you a form with the read/write *org-trello-access-token*, select and copy it, then paste it inside emacs' minibuffer and hit RET.

Note: This command, if accepted, results in a file stored *only* on your disk in `~/emacs.d/.trello/.el` (this path may vary depending on **user-emacs-directory**).

This file contains your credentials and will be used to identify you when requesting trello.

```
(setq org-trello-consumer-key "abc...") ;; 32 characters string
(setq org-trello-access-token "def...") ;; 64 characters string
```

4.2 Connect an org-mode buffer with an existing Trello board.

For each org-mode file that you wish to use with Trello.com, you need to connect your org-mode file with a Trello board.

Note: This procedure must be done only once for each org-mode file you want to sync with a trello board.

To connect an buffer to an existing board, type:

- C-c o I, or
- M-x org-trello-install-board-metadata

This will:

- ask you for the accounts you want to use (if you have multiple ones, otherwise, it will select the only one and pass to the next step silently)
- present you with a list of boards for the selected account. Select the one you want and hit enter.
- edit your org-mode file to add the properties needed.

4.3 Create a Trello board from your org-mode buffer.

You can create a new Trello board from your existing org-mode file.

Note: This procedure must be done only once for each org-mode file you want to sync with a trello board.

Type:

- C-c o b, or
- M-x org-trello-create-board-and-install-metadata

This will:

- ask you for the accounts you want to use (if you have multiple ones, otherwise, it will select the only one and pass to the next step silently)
- create the Trello board lists from the keywords configured in your org-mode (cf. org-todo-keywords (http://orgmode.org/manual/In_002dbuffer-settings.html))

5 WORK Using ‘org-trello’

This section describes how to use ‘org-trello’.

5.1 CHEK Quick Start

First, do the Chapter 3 [installation], page 3, and the Chapter 4 [connection], page 11.

A typical starting point is to synchronize a trello board to the current buffer. To do this, type:

- C-u C-c o s, or
- C-u M-x org-trello-sync-buffer

This will fetch the current board’s data and write it inside the current buffer. From then on, you can use your org buffer as usual.

When you want to update the trello board from the org buffer, type:

- C-c o c/C-c o C, to update the card at point, or
- C-c o s, to sync all the entities from your buffer to Trello.

When you want to update the org buffer from trello:

- C-u C-c o c, or
- C-u C-c o C, to update the card at point from Trello.

For more usage details, see below.

5.2 Command Descriptions

This section describes all commands and their key bindings.

5.2.1 CHEK Summary of Commands

All default ‘org-trello’ key-bindings use the “C-c o” prefix.

Note: You may type “C-c o C-h” to display help for most ‘org-trello’ key bindings.

| Keys | Command |
|-----------|---|
| | Help Commands |
| C-c o C-h | Display help on all key-bindings with C-c o prefix. |
| C-c o h | Display a help message from org-trello. |
| C-c o v | Display the version of ‘org-trello’. |
| | Connection Commands |
| C-c o i | Install the Trello.com login key and access token. |
| C-c o I | Choose an existing Trello board and attach this buffer. |
| C-c o b | Create a new Trello board and connect this buffer |
| C-c o u | Update this buffer’s Trello board meta-data. |
| C-c o d | Diagnose the setup. |
| C-c o D | Delete all Trello metadata from this buffer. |
| | Synchronization Commands |
| C-c o c | Create or synchronize a complete card. |
| C-c o s | Synchronize FROM the entire buffer TO Trello. |

| | |
|-------------------------|--|
| C-u C-c o s | Synchronize TO the entire buffer FROM Trello. |
| C-c o g | Abort any synchronization in progress. (like C-g) |
| Editing Commands | |
| C-c \$ | Archive the card at point. (Standard org binding) |
| C-c o A | Archive all DONE cards. |
| C-c o k | Kill the entity and its tree from buffer and Trello. |
| C-c o K | Kill ALL entities and trees from buffer and Trello. |
| C-c o a | Assign myself to this card. |
| C-u C-c o a | Un-assign myself from this card. |
| C-c o C | Add a comment to this card. |
| C-u C-c o C | Remove this comment from the card. |
| Misc. Commands | |
| C-c o l | Display the board’s labels in a pop-up buffer. |
| C-c o j | Jump to this card on Trello.com in browser. |
| C-c o J | Jump to this board on Trello.com in browser. |

5.2.2 TODO Help Commands

5.2.3 TODO Connection Commands

This section describes the functions used to connect ‘org-trello’ to Trello.com and to attach an org file to a Trello board.

5.2.4 WORK Synchronization Commands

This section describes the synchronization commands used to move data between the buffer and Trello.com.

org-trello-sync-buffer

Type “C-c o s” to sync the entire buffer TO the Trello board.

Type “C-u C-c o s” to sync the entire buffer FROM the Trello board.

5.2.5 TODO Editing Commands

This section describes the functions used to edit, archive and delete cards, comments and list items.

5.2.6 TODO Misc. Commands

This section describes other functions not listed above.

5.3 TODO How to...

This section describes how to use commands to perform tasks with ‘org-trello’.

5.4 CHEK Format of org-trello

This section describes the format of the text in an ‘org-trello’ buffer.

There are 3 levels of meta-data:

- level 1 - Card
- level 2 - Checklist

- level 3 - Item

Natural org checkboxes (<http://orgmode.org/manual/Checkboxes.html>). Thanks to @swl1nn this is awesome!

```
* IN-PROGRESS Joy of FUN(ctional) LANGUAGES
- [-] LISP
  - [X] Emacs-Lisp
  - [X] Common-Lisp
  - [ ] Scheme
  - [X] Clojure
- [X] ML
  - [X] Haskell
  - [X] Ocaml
- [X] Hybrid
  - [X] Scala
- [ ] little more detail, this is level 2, so checklist in trello board
  - [ ] item 3
    - [ ] any entities with level superior to 4 are considered level 3
```

For example, once synced to trello, this looks like:

```
* IN-PROGRESS Joy of FUN(ctional) LANGUAGES
:PROPERTIES:
:orgtrello-id: 521dc9f3edeabee47600401e
:END:
- [-] LISP :PROPERTIES: {"orgtrello-id":"521dc9f48e95d74636004107"}
  - [X] Emacs-Lisp :PROPERTIES: {"orgtrello-id":"521dc9f7487c2e9b250047a5"}
  - [X] Common-Lisp :PROPERTIES: {"orgtrello-id":"521dc9f7ae27842a36003b26"}
  - [ ] Scheme :PROPERTIES: {"orgtrello-id":"521dc9f834f52df935003b15"}
  - [X] Clojure :PROPERTIES: {"orgtrello-id":"521dc9f9c1b85c905f006b4e"}
- [X] ML :PROPERTIES: {"orgtrello-id":"521dc9f5d49a919614000266"}
  - [X] Haskell :PROPERTIES: {"orgtrello-id":"521dc9fa5699f00b25003bd0"}
  - [X] Ocaml :PROPERTIES: {"orgtrello-id":"521dc9fb7ef4310554003ab3"}
- [X] Hybrid :PROPERTIES: {"orgtrello-id":"521dc9f6238d072770007217"}
  - [X] Scala :PROPERTIES: {"orgtrello-id":"521dc9fc8e95d74636004109"}
```

Note In the org-trello buffer, the :PROPERTIES: for the checklists/items won’t be visible for the user.

6 CHEK Troubleshooting ‘org-trello’

6.1 Common Issues

This section addresses some common issues with installing and using ‘org-trello’.

- Why am I getting errors about credentials loading, like below?

```
org-trello - Request 'sync org buffer to trello board'...
org-trello - List of errors:
  - Setup problem - Problem during credentials loading (consumer-key
    and read/write access-token) - C-c o i or M-x org-trello-install-key-and-token
  - Setup problem - You need to install the consumer-key and the
    read/write access-token - C-c o i or M-x org-trello-install-key-and-token
```

If you have already Section 4.1 [set up your credentials], page 11, then please make sure the login you used in the credential installation step match your trello login exactly, that is:

- Check ‘https://trello.com/<user-login>’ exists
- ‘<User-login>’ in the buffer is the same as the org-trello login: ‘#+PROPERTY: orgtrello-user-me <user-login>’
 at the org-trello buffer top must match too.
- For issues not listed above, please see Section 8.2 [these instructions], page 23, about the issue list on GitHub.

6.2 Error Messages

‘org-trello’ can display the following possible error messages:

- Failed to set up the consumer-key and the access-token:

```
Setup problem - You need to install the consumer-key and the read/write
access-token - C-c o i or M-x org-trello-install-board-metadata
```
- Failed to setting up the org-mode buffer:

```
Setup problem. Either you did not connect your org-mode buffer with a
trello board, to correct this:
  • attach to a board through C-c o I or M-x org-trello-install-board-
    metadata
  • or create a board from scratch with C-c o b or M-x org-trello-create-
    board-and-install-metadata). Either your org-mode’s todo keyword
    list and your trello board lists are not named the same way (which
    they must). For this, connect to trello and rename your board’s list
    according to your org-mode’s todo list.
```
- The board’s list names are different from your org-mode’s keyword list:

```
Setup problem. Either you did not connect your org-mode buffer with a
trello board, to correct this:
  • attach to a board through C-c o I or M-x org-trello-install-board-
    metadata
```

- or create a board from scratch with C-c o b or M-x org-trello-create-board-and-install-metadata). Either your org-mode's todo keyword list and your trello board lists are not named the same way (which they must). For this, connect to trello and rename your board's list according to your org-mode's todo list. Also, you can specify on your org-mode buffer the todo list you want to work with, for example:


```
#+TODO: TODO DOING
      DONE FAIL (hit C-c C-c to refresh the setup)
```
- No label on the card:

Cannot synchronize the card - missing mandatory label. Skip it. . .
- No label on the checklist:

Cannot synchronize the checklist - missing mandatory label. Skip it. . .
- No label on the item:

Cannot synchronize the item - missing mandatory label. Skip it. . .
- syncing the checklist without syncing the card first:

Cannot synchronize the checklist - the card must be synchronized first. Skip it. . .
- Syncing the item without syncing the checklist first:

Cannot synchronize the item - the checklist must be synchronized first. Skip it. . .

7 Customizing ‘org-trello’

This section describes how you may customize ‘org-trello’.

7.1 Customizing the Prefix Keybinding

By default, ‘org-trello’ uses the prefix keybinding “C-c o” to begin (almost) all of its commands. You may change this by customizing the variable `org-trello-current-prefix-keybinding`.

To customize `org-trello-current-prefix-keybinding`, type `C-h v org-trello-current-prefix-keybinding RET` to display the help text for this variable. Then follow the “customize” link on the last line. You may then use the customize interface to set another prefix keybinding.

Note: If ‘org-trello’ is already running, you must restart emacs after customizing this variable (or run `M-x org-trello-mode - twice`).

You may also change this setting in your emacs initialization file. For example, to change the ‘org-trello’ prefix keybinding to `C-c x` add these lines to your Emacs initialization file (`~/.emacs` or `~/.emacs.d/.init.el`):

```
(require 'org-trello)
(custom-set-variables '(org-trello-current-prefix-keybinding "C-c x"))
```

For an example, please see my startup file (<https://github.com/ardumont/orgmode-pack/blob/master/orgmode-pack.el#L57>).

7.2 Customizing Individual Keybindings

To redefine one or more org-trello-mode command keybindings, you should create a function to define keys in the `org-trello-mode-map` and hook your function to the `org-trello-mode-hook`. This will make ‘org-trello’ run your function each time it starts.

```
(require 'org-trello)

(defun def-my-org-trello-keys () "Define my org-trello keys."
  (define-key org-trello-mode-map (kbd "C-c x v") 'org-trello-version)
  (define-key org-trello-mode-map (kbd "C-c x i") 'org-trello-install-key-and-token)
  (define-key org-trello-mode-map (kbd "C-c x I") 'org-trello-install-board-metadata)
  (define-key org-trello-mode-map (kbd "C-c x c") 'org-trello-sync-card)
  (define-key org-trello-mode-map (kbd "C-c x s") 'org-trello-sync-buffer)
  (define-key org-trello-mode-map (kbd "C-c x a") 'org-trello-assign-me)
  (define-key org-trello-mode-map (kbd "C-c x d") 'org-trello-check-setup)
  (define-key org-trello-mode-map (kbd "C-c x D") 'org-trello-delete-setup)
  (define-key org-trello-mode-map (kbd "C-c x b") 'org-trello-create-board-and-install)
  (define-key org-trello-mode-map (kbd "C-c x k") 'org-trello-kill-entity)
  (define-key org-trello-mode-map (kbd "C-c x K") 'org-trello-kill-cards)
  (define-key org-trello-mode-map (kbd "C-c x a") 'org-trello-archive-card)
  (define-key org-trello-mode-map (kbd "C-c x A") 'org-trello-archive-cards)
  (define-key org-trello-mode-map (kbd "C-c x j") 'org-trello-jump-to-trello-card)
  (define-key org-trello-mode-map (kbd "C-c x J") 'org-trello-jump-to-trello-board))
```

```
(define-key org-trello-mode-map (kbd "C-c x C") 'org-trello-add-card-comments)
(define-key org-trello-mode-map (kbd "C-c x o") 'org-trello-show-card-comments)
(define-key org-trello-mode-map (kbd "C-c x l") 'org-trello-show-card-labels)
(define-key org-trello-mode-map (kbd "C-c x u") 'org-trello-update-board-metadata)
(define-key org-trello-mode-map (kbd "C-c x h") 'org-trello-help-describing-bindings)
```

```
(add-hook 'org-trello-mode-hook 'def-my-org-trello-keys)
```

Note: This will not update the help messages to match your key-bindings nor remove the default keybindings.

You may add several lines like this one to your hook function to remove specific existing ‘org-trello’ keybindings:

```
(define-key org-trello-mode-map (kbd "C-c o v") nil)
```

7.3 Customizing ‘org-trello’ Variables

You may customize ‘org-trello’ settings by typing:

M-x customize-group RET org-trello RET.

You may customize any of the following variables from the user-interface.

Parent groups: Org

Org-trello group: Org-trello customisation group.

State : visible group members are all at standard values.

Org Trello Add Tags

Add trello colors to org tags list?

Org Trello Current Prefix Keybinding

The default prefix keybinding to execute org-trello commands.

Org Trello Files

Org-trello files that needs org-trello activated when opened. Hide

This does not support regular expression.

Org Trello Input Completion Mechanism

The completion mechanism the user can choose from. Hide

Default is the native ido mechanism.

Other possibilities is helm but it’s up to you to install the dependencies.

```
(require 'helm)
```

```
(custom-set-variables '(org-trello-input-completion-mechanism 'helm))
```

Org Trello Mode Hook

Define org-trello hook for user to extend mode with their own behavior.

Orgtrello Log Level

Set log level. Hide

Levels:


```

0 - no log    ('orgtrello-log-quiet')
1 - errors   ('orgtrello-log-error')
2 - warnings ('orgtrello-log-warn')
3 - info     ('orgtrello-log-info')
4 - debug    ('orgtrello-log-debug')
5 - trace    ('orgtrello-log-trace')
To change such level, add this to your init.el file:
(custom-set-variables '(orgtrello-log-level orgtrello-log-trace))

```

Orgtrello Setup Use Position In Checksum Computation

Let the user decide if (s)he wants to use the position in the checksum. Hide
The checksum is a hash computation of the current entity’s data to prevent
sending too many sync requests if unnecessary (no real change since last time).

If t, when sync to trello, any change for the current entity will be reflected
in trello’s board. However, a global sync to trello, will trigger many
unnecessary sync to trello queries for any entity below the current entity
changed... Indeed, the position changes anytime you insert or delete a char.
This renders almost useless the checksum computation.

Cf. <https://github.com/org-trello/org-trello/issues/271>.

Please, do not hesitate to provide a better idea or a better implementation.

If nil, the default, the sync to trello will be limited to what’s really changed
(except for the position). So the entity’s position in trello’s board can be
slightly different than the one from the buffer.

Orgtrello With Check On Sensible Actions

Some action can be dangerous removing entity for example. Hide
This custom determine if the user wants to be asked confirmation
before doing some of those sensitive actions.

7.4 Example Emacs-Lisp Customization

Here is an example of how to configure ‘org-trello’ user-customized variables using emacs-lisp:

```

(custom-set-variables
 '(orgtrello-log-level orgtrello-log-debug) ;; log level to debug
 '(org-trello-current-prefix-keybinding "C-c x") ;; C-c x as the default prefix
 '(orgtrello-setup-use-position-in-checksum-computation nil) ;; checksum without pos
 '(org-trello-files '("~/docs/some-doc.trello"
                      "~/docs/some-other-doc.org"))) ;; automatic org-trello on file

```

To set these variables for the current session, place the cursor after the entire s-exp and
evaluate it using “M-x eval-last-sexp”.

To make these settings permanent in later sessions, put this code inside your emacs setup
file (“~/emacs” or “~/emacs.d/init.el”).

7.5 Automatic ‘org-trello’ Files

To have emacs automatically start ‘org-trello’ when you open a file with a “.trello” extension, add this to your personal emacs setup file:

```
;; org-trello major mode for all .trello files

(add-to-list 'auto-mode-alist '("\\.trello$" . org-mode))

;; add a hook function to check if this is trello file,
;; then activate the org-trello minor mode.

(add-hook 'org-mode-hook
  (lambda ()
    (let ((filename (buffer-file-name (current-buffer))))
      (when (and filename (string= "trello" (file-name-extension filename)))
        (org-trello-mode))))))

source: https://github.com/org-trello/org-trello/issues/249
```

8 Development of ‘org-trello’

8.1 Credits

Many thanks to all the contributors (<https://github.com/org-trello/org-trello/graphs/contributors>) to ‘org-trello’, including:

@dtebbs (<https://github.com/dtebbs>)

PR - fix on the card description (<https://github.com/org-trello/org-trello/pull/173>)

@jasom (<https://github.com/jasom>)

PR - improvements on the trello card’s description rendering (<https://github.com/org-trello/org-trello/pull/175>).

@nicferrier (<https://github.com/nicferrier>)

marmalade (<http://marmalade-repo.org/>), elnode (<https://github.com/nicferrier/elnode>), emacs clean install (http://nic.ferrier.me.uk/blog/2012_07/emacs-packages-for-programmers)...

@nicolas_roche (https://twitter.com/nicolas_roche)

logo and the multiple suggestions regarding the web design part.

@nmassyl (<https://twitter.com/nmassyl>)

multiple exchanges on design and functionalities.

@purcell (<https://github.com/purcell>)

various discussions, suggestions regarding packaging on Melpa (<http://melpa.milkbox.net/>)

@puzan (<https://github.com/puzan>)

org-trello’s el-get recipe

and thanks to all those that opened issues (<https://github.com/org-trello/org-trello/issues>) or pull requests (<https://github.com/org-trello/org-trello/pulls>).

Also, thank you to the entire free-software community world-wide, including the creators and contributors of Emacs and org-mode.

8.2 Issue List

If you experience an issue while using ‘org-trello’, please first confirm that you have the newest version. If you have an old version, please upgrade to the newest version - your issue may already have been solved. You may display the version of your copy of ‘org-trello’ by typing `C-c o v` or `M-x org-trello-version`.

If you have the newest version, please search the issue list (<https://github.com/org-trello/org-trello/issues>) for issues similar to yours. If your issue already exists, please describe your experiences in the comments, if different, and try the advice offered there, if any.

If you don’t find an issue like yours, you should create a new issue.

You should include the following information in your issue entry:

- Your ‘org-trello’ version
- Your ‘org-mode’ version
- Your emacs version
- Your system type and OS version
- How you installed ‘org-trello’:
 - melpa
 - melpa-stable
 - el-get
 - tarball
 - git clone
 - other
- A clear, concise and complete description of the issue. Please do state the obvious.
- Supporting data:
 - A copy of any pertinent messages produced by ‘org-trello’ or Emacs
 - A copy of buffer data necessary to reproduce the issue. (Please avoid posting private data. Do not post your Trello.com or other login credentials.)
 - If the issue is with installation, include the ‘*Compile Log*’ buffer contents.

Please use GitHub’s markdown formatting to improve readability.

We may have questions about your issue or question if we don’t understand. You can help us to help you better and faster by being clear, concise and complete in your issue description.

8.2.1 Using ‘M-x org-trello-bug-report’

You may use the bug-report function of ‘org-trello’ to print some information about ‘org-trello’ to the ‘*Messages*’ buffer to copy into the issue entry. To print the bug-report data, type M-x org-trello-bug-report or C-c o B. Then open the ‘*Messages*’ buffer and copy the block of data it produced to paste into the issue on GitHub. The block of data will resemble:

```
System information:
- system-type: darwin
- locale-coding-system: utf-8-unix
- emacs-version: GNU Emacs 26.1
- org version: 9.2
- org-trello version: 0.8.0
- org-trello path: ~/.emacs.d/elpa/org-trello-20180331.631/org-trello.el
- request-backend: curl
- kill-whole-line: nil
```

If you type C-u C-c o B instead, ‘org-trello’ will open a new issue on GitHub for you to complete.

8.2.2 Using ‘orgtrello-log-trace’

To obtain a more verbose output in the **Message** buffer, you can put this snippet of code in a ‘*scratch*’ buffer.

```
(custom-set-variables '(orgtrello-log-level orgtrello-log-trace))
```

and evaluate it with M-x eval-buffer. Then, return to your ‘org-trello’ buffer and repeat the conditions that cause the issue. Copy the resulting detailed log messages into your bug-report.

8.3 Mailing List

This project has a mailing list at librelist.com (<http://librelist.com/browser/emacs.org.trello/>) for communication and community among its users and contributors. You may join the list by sending an email to:

- subscribe: emacs.org.trello [AT] librelist.com
- unsubscribe: emacs.org.trello-unsubscribe [AT] librelist.com

8.4 Release List and Notes

The release list (<https://github.com/org-trello/org-trello/releases>) of ‘org-trello’ is on GitHub.

The separate release-notes file ([release-notes.org](https://github.com/org-trello/org-trello/blob/master/release-notes.org)) records the primary changes in each release of ‘org-trello’. Please also see the commit history (<https://github.com/org-trello/org-trello/commits/master>) of the repository (<https://github.com/org-trello/org-trello>) on GitHub.

8.5 Compatibility with Emacs

‘org-trello’ has been tested with the following versions of Emacs and Operating Systems:

| Version | OS | Status |
|-----------|------------------------------|--------|
| 24.3.1 | Linux Mint 14 | OK |
| 24.3.1 | Linux Mint 15 (ubuntu based) | OK |
| 24.3.1 | Ubuntu 13.04 | OK |
| 24.3.1 | Ubuntu 13.10 | OK |
| 24.3.50.1 | Linux Mint 16 (debian based) | OK |
| 24.4.1 | NixOS | OK |

Note: We cannot test under MacOS X or MS windows so any feedback on those is welcome.

8.6 Continuous Integration Tests

‘org-trello’ uses Travis CI (<https://travis-ci.org/org-trello/org-trello>) for continuous integration testing.

The CI tests and installs:

| Version | CI | Manual Test |
|---------|------------|-------------|
| 24.1 | Not tested | Not tested |
| 24.2 | Not tested | Not tested |
| 24.3.1 | OK | OK |
| 24.3.50 | OK | OK |
| 24.4.1 | OK | OK |

Note: Any feedback regarding the untested versions is welcome.

8.7 Developer’s Conventions

This describes the current conventions for org-trello’s development.

8.7.1 Sources

The sources are split into ‘namespaces’ in the `src/` (`./src/`) folder. This is described in the Namespaces section below.

1. Conventions

As there exists no namespace in emacs-lisp, I use:

- convention in function names to determine the nature private/public
- splitted files that represents namespaces.

1. Rules

These conventions are enforced in org-trello:

- functions are prefixed with ‘orgtrello-<NAMESPACE-FILENAME>-<FUNCTION-NAME>’
- ‘<NAMESPACE-FILENAME>’ is the filename without its path nor its extension. For example, ‘src/buffer.el’ renders ‘buffer’
- ‘<FUNCTION-NAME>’ is an alphanumeric symbol with ‘-’ as separator. For example, ‘orgtrello-api-add-board’ is a public function which does create a request to add a board.
- private functions are prefixed with ‘--’. For example, ‘orgtrello-api--deal-with-optional-va’ which is a private utility function to help in creating api request.
- predicate functions are suffixed by ‘-p’. For example, ‘orgtrello-data-entity-card-p’ which checks if the parameter entity is a card or not.

Note: I adapted the code to abide by emacs-lisp’s conventions (https://www.gnu.org/software/emacs/manual/html_node/elisp/Coding-Conventions.html).

2. Exception

‘org-trello.el’ is the main namespace that declares the:

- interactive commands used throughout all of org-trello
- minor mode

Every exposed interactive command is named ‘org-trello-fn-name’.

2. Namespaces

The namespaces are in loading order:

| Namespaces file | Description of the namespace |
|--------------------------|--|
| org-trello-log.el | Provide log facilities |
| org-trello-setup.el | Main variable definition that permits internal ... org-trello functions customization |
| org-trello-date.el | org-trello’s date manipulation |
| org-trello-hash.el | Hash-map manipulation utilities |
| org-trello-action.el | Higher-order functions helper |
| org-trello-data.el | Internal org-trello data manipulation |
| org-trello-entity.el | Entity (card/checklist/item) predicates |
| org-trello-cbx.el | Checkbox manipulation utilities |
| org-trello-api.el | Trello API abstraction DSL |
| org-trello-query.el | HTTP query utilities |
| org-trello-backend.el | Deals with trello requests |
| org-trello-proxy.el | Proxy utilities - Namespace in charge of dealing ... with the orchestration of trello requests |
| org-trello-buffer.el | Buffer manipulation functions |
| org-trello-input.el | Text input functions |
| org-trello-controller.el | Controller used by org-trello.el |
| org-trello-deferred.el | Deferred computation in org-trello |
| org-trello.el | Main information about org-trello (version, ... licence, deps, etc...) + org-trello ... minor mode definition which defines ... interactive commands and the mode |
| utilities.el | test utilities functions |

3. Loading

Use the `load-org-trello.el` (`./load-org-trello.el`) file to load org-trello for development purposes and keep the emacs way of browsing source code (`‘M-.’`, `‘M-,’`).

Open the file and `‘M-x eval-buffer’`.

8.7.2 Makefile

The Makefile (`./Makefile`) is your ally for:

- package
- test
- release

1. Package

This packages all the *org-trello*.el* into a standard tar file.

```
make package
```

2. Test

```
make test
```

3. Install

To test that the package, once created, can be installed (using the repository to fetch the dependencies).

```
make install-file-with-deps-from-melpa
```

Note: This will trigger the installation from a local package ‘org-trello-<VERSION>.tar’. The installation is used with the dependencies fetched from melpa.

Note: These are the targets used by the CI (cf. .travis.yml (./travis.yml))

4. Full install testing

As we deploy in melpa, we can ensure that once delivered, the installation is ok using those targets.

```
make install-package-from-melpa
```

5. Release

The release process is done through 2 steps:

1. Self Pull Request from the feature branch inside master

```
make pr
```

Note: You need ‘hub’ installed for this target to work.

2. Then trigger release through the call to the release target from the Makefile:

```
make release
```

This will:

- fetch the latest modifications on your repository
- checkout the master branch
- fast-forward to the latest master commit
- tag the latest commit from master using the \$VERSION you submit to the script (defaulting to the version from the org-trello.el header)
- push the tag to the upstream branch repository
- trigger the package target from the Makefile (thus building a new package to the latest version)
- Then manual delivery of the tar to the github release page

Note:

- this is an orchestration of the release.sh (./release.sh) script
- the packaging for MELPA is automatically done from ‘org-trello/org-trello’ repository

Appendix A GNU General Public License

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program—to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

“This License” refers to version 3 of the GNU General Public License.

“Copyright” also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

“The Program” refers to any copyrightable work licensed under this License. Each licensee is addressed as “you”. “Licensees” and “recipients” may be individuals or organizations.

To “modify” a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a “modified version” of the earlier work or a work “based on” the earlier work.

A “covered work” means either the unmodified Program or a work based on the Program.

To “propagate” a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To “convey” a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays “Appropriate Legal Notices” to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The “source code” for a work means the preferred form of the work for making modifications to it. “Object code” means any non-source form of a work.

A “Standard Interface” means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The “System Libraries” of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A “Major Component”, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The “Corresponding Source” for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work’s System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users’ Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a. The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b. The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c. You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d. If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c. Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d. Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e. Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A “User Product” is either (1) a “consumer product”, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, “normally used” refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

“Installation Information” for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source.

The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

“Additional permissions” are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a. Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b. Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c. Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

- d. Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e. Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f. Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered “further restrictions” within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance.

However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An “entity transaction” is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party’s predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A “contributor” is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor’s “contributor version”.

A contributor’s “essential patent claims” are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, “control” includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor’s essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a “patent license” is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To “grant” such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so

available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. “Knowingly relying” means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient’s use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is “discriminatory” if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others’ Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License “or any later version” applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the “copyright” line and a pointer to where the full notice is found.

```
one line to give the program's name and a brief idea of what it does.
Copyright (C) year name of author
```

```
This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or (at
your option) any later version.
```

```
This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program. If not, see http://www.gnu.org/licenses/.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
program Copyright (C) year name of author
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands ‘show w’ and ‘show c’ should show the appropriate parts of the General Public License. Of course, your program’s commands might be different; for a GUI interface, you would use an “about box”.

You should also get your employer (if you work as a programmer) or school, if any, to sign a “copyright disclaimer” for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

Appendix B GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released

under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any,

- be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
 - C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
 - D. Preserve all the copyright notices of the Document.
 - E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
 - F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
 - G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
 - H. Include an unaltered copy of this License.
 - I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
 - J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
 - K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
 - L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
 - M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
 - N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
 - O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their

titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements."

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts. A copy of the license is included in the section entitled ‘‘GNU
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Appendix C TODO Indices

This section contains the concepts, commands, functions and variables indices.

C.1 Concepts Index

=

=org-trello=, installing 3
 =org-trello=, using 14

C

contributing 23
 contributors 23
 credits 23
 customizing 19

E

errors 17

L

license, manual 40
 license, software 29

C.2 Commands Index

C-c o C-h 14
 C-c o s 15

C.3 Functions Index

org-trello-sync-buffer 15

C.4 Variables Index

org-trello-current-prefix-keybinding 19

M

manual, installing 5

R

release notes 25

T

trello.com, connecting 11
 troubleshooting 17

V

version history 25

C-u C-c o s 15

org-trello-mode-map 19