UCR-04 Lösung prüfen lassen (Designklassen)

Frontend (Angular)

- **CodeEditorComponent**
  - code: string
  - submissionResult: SubmissionResult
  - submitSolution()
- **SubmissionApiService**
  - submit(missionNumber, code): Observable<SubmissionResult>

HTTP POST
/api/missions/:number/submissions

Backend (Express)

- **SubmissionController**
  - submit(req, res)
- **SandboxRunner**
  - runTests(code, tests: TestCase[], timeoutMs): RunResult
- **SubmissionService**
  - evaluate(playerId, missionNumber, code): SubmissionResult
- *CodeRunner* (Interface)
  - runTests(code, tests: TestCase[], timeoutMs): RunResult
- **TestCaseRepository**
  - findByMission(missionId): TestCase[]
- **ProgressRepository**
  - incrementAttempts(playerId, missionId)
- **ProgressService**
  - completeMission(playerId, missionNumber): MissionCompletedResult

bei korrekter Lösung (UC-05)

Modelle (geteilt)

- **SubmissionResult**
  - correct: boolean
  - passedCount: number
  - totalCount: number
  - errorMessage: string
- **RunResult**
  - compileError: string
  - timedOut: boolean
  - testResults: TestResult[]
- **TestCase**
  - description: string
  - expected: string
- **TestResult**
  - description: string
  - passed: boolean
  - expected: string
  - actual: string

1 — 0..* — 0..*