

ATTACK TYPE SQLi	SEVERITY HIGH	CONFIDENCE 100.0%	SUBTYPE Boolean-based SQLi
----------------------------	-------------------------	-----------------------------	--------------------------------------

[WARNING] SQLi detected with subtype: Boolean-based SQLi

Payload

```
' OR 1=1 --
```

Request Metadata

Field	Value
ip	127.0.0.1
user_agent	Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.26100.8894
path	/api/xai/report
method	POST

Attack-Specific Explanation

- The payload uses boolean logic such as OR 1=1 or AND 1=1 to alter query truth conditions.
- This pattern is commonly used for authentication bypass or blind condition testing.
- Strong matched indicators: tautology_num, tautology_str
- Weak matched indicators: or_keyword, comment_end

Top TF-IDF Terms (Why It Was Flagged)

Token	TF-IDF Score	Visual
1=1	0.3535	#####
1=1	0.3516	##### -
1=1	0.3219	##### --
1=1	0.3198	##### --
1=	0.2844	##### ---
'	0.2774	##### ----
--	0.2774	##### ----
--	0.2769	##### ----
=1	0.2362	##### -----
or	0.2321	##### -----

Potential Impact & Recommended Protections

Potential Impact	Recommended Protections
- Authentication bypass, unauthorized data access, or database fingerprinting.	- Use parameterized queries or prepared statements everywhere.
- Potential data extraction, modification, or destruction depending on permissions.	- Never concatenate untrusted input into SQL queries.
	- Apply least-privilege database accounts and suppress verbose DB errors.

Attack Preconditions

1	User-controlled input reaches an SQL context without proper parameter binding.
2	The backend query construction allows attacker input to alter query structure.

Decision Debug / AI Gating

Key	Value
raw_pred	1
proba	{ "0": 0.0, "1": 1.0, "2": 0.0, "3": 0.0 }

Key	Value
pattern_hits	{ "sqli": { "strong": ["tautology_num", "tautology_str"], "weak": ["or_keyword", "comment_end"] }, "xss": { "strong": [], "weak": [] }, "lfi": { "strong": [], "weak": [] } }
decision_reason	multi_allowed_choose_highest
thresholds	{ "sqli": { "no_pattern_min": 0.85, "weak_min": 0.8, "strong_min": 0.6 }, "xss": { "no_pattern_min": 0.85, "weak_min": 0.8, "strong_min": 0.6 }, "lfi": { "no_pattern_min": 0.85, "weak_min": 0.8, "strong_min": 0.6 } }

Report Note

- This report was automatically generated by the HWACS Explainable AI Security Platform using captured request data, model prediction output, pattern-based analysis, subtype detection, and explainability signals. The result should be reviewed by a qualified security professional before taking operational action.