

- Filename: eccouncil-ceh31250-v12-10-5-1-botnets.md
- Show Name: CEHv12 (312-50)
- Topic Name: Network and Perimeter Hacking: Denial of Service
- Episode Name: Botnets

=====

Botnets

Objectives:

- Define Botnets and their attributes
- Describe what a typical botnet setup looks like
- Explain how a botnet attack network is built

-
- What is a botnet?
 - A dispersed group of compromised and remotely controlled systems
 - Could be any device
 - A portmanteau of roBOT + NETwork
 - Live botnet threats map: <https://www.spamhaus.com/threat-map/>
 - What is their purpose?
 - Typically employed to do...
 - Crypto-mining
 - Attack platform for cybercrime
 - Spread malware
 - Influencing online games and polls
 - DDoS attacks
 - Affiliate Networks
 - Botnets joining forces
 - More effective
 - <https://www.imperiva.com/blog/bad-bot-report-2021-the-pandemic-of-the-internet/>
 - How do hackers choose targets to become bots?
 - Scan networks for vulnerabilities
 - Random hits
 - Pseudo-random permutation list of IPs
 - Local Subnets
 - Already infected devices scan their local networks for other vulnerable targets
 - Infected bots can scan for internet facing targets as well
 - Common ways compromised hosts download attack toolkits
 - Autonomously
 - Attacker copies it directly to target
 - Target scans for more targets and repeats the cycle
 - No intermediary source required
 - Back-Chaining
 - Attacker exploits target
 - Target then requests toolkit from Attacker
 - Repeat
 - Central Source
 - Intermediary server acts as toolkit repository for bots

